
SITE IMPROVEMENTS FOR PEACH HILL SUBDIVISION **ASHLAND CITY** CHEATHAM COUNTY, TENNESSEE (049J D 00101 000 / CURRENTLY ZONED R-4)



FEMA NOTE:

A PORTION OF THE PROPERTY IS LOCATED WITHIN ZONE "AE." 100-YEAR BASE FLOOD ELEVATION = 402.0 (NAVD 88 DATUM) :

MAP NUMBER: 47021C0165D

EFFECTIVE DATE: SEPTEMBER 17, 2010

TDEC CGP NOTE:

I HEREBY CERTIFY THAT THIS PRO TOTAL DISTURBED AREA IS: 0.88	DJECT DOES <u>NOT</u> REQUIRE COVERAGE UNI <u>8 ACRES</u> .	der a tennessee constructio	N GENERAL PERMIT. THE
	IIS SITE DISCHARGES INTO WATERS IDENTIFIE	ed by tdec as:	
			NONE
(and 4 Am	a	10/16/2020	
PROFESSIONALENGINEER	REGISTERED IN THE STATE OF TENNESSEE	DATE	
CIRCLE ONE:	DEVELOPER	PROJECT ENGINEER	OTHER

SITE LOCATION MAP (NOT TO SCALE)



Current Contraction		202	0
DATE:		10-16-	-2020
DRW:	AH	СНК:	DS
descr	IPTION:		
CONST	T. DOCS IS	SUED TO C	CLIENT
DATE:			-
DRW:	-	CHK:	-
DESCR	IPTION:		
-			
DATE:			-
DRW:	-	СНК:	-
DESCR	IPTION:		
-			
DATE:			-
DRW:	-	СНК:	-
DESCR	IPTION:		
_			
DATE:			-
DRW:	-	CHK:	-
DESCR	IPTION:		
-			

VISION $\mathbf{\Gamma}$ UB 5 I \triangleleft I РП 5 4

5

	Sheet List Table	
	Sheet Number	Sheet Title
(C-0.0	COVER SHEET
(C-0.1	EXISTING CONDITIONS
(C-1.0	SITE PLAN
(C-1.1	SITE PLAN DETAILS
(C-2.0	GRADING & DRAINAGE PLAN
(C-2.1	GRADING & DRAINAGE DETAILS
(C-3.0	EPSC INITIAL PLAN
(C-3.1	EPSC INTERMEDIATE & FINAL PLAN
(C-3.2	EPSC DETAILS
(C-4.0	UTILITY PLAN

DEVELOPER INFORMATION: REGAL HOMES, INC.

290 ED HARRIS RD ASHLAND CITY, TN 37015


CIVIL ENGINEER INFORMATION:


HARPETH CIVIL, INC. 179 BELLE FOREST CIRCLE, SUITE 204E NASHVILLE, TENNESSEE, 37221 615-730-3502


LAND SURVEYOR INFORMATION: CHANDLER SURVEYING

3421 COOPER NICHOLSON ROAD PLEASANT VIEW, TN. 37146 615-746-5900










VICINITY MAP N.T.S

NOTES:

- 1. BEARING SYSTEM IS DERIVED FROM TENNESSEE STATE PLANE COORDINATE SYSTEM (NAD83) ZONE 4100, UNLESS OTHERWISE NOTED DISTANCES AND COORDINATES RECITED ARE BASED ON GROUND MEASUREMENTS, NO SCALE FACTOR APPLIED.
- 2. G.P.S. EQUIPMENT USED TO ESTABLISH GRID NORTH: TRIMBLE R-8 DUAL FREQUENCY RECEIVER AND T.D.O.T. GNSS REFERENCE NETWORK.
- 3. NUMBERS SHOWN THUS (00) PERTAIN TO CHEATHAM COUNTY PROPERTY TAX MAP NUMBER XX.
- 4. PROPERTY SUBJECT TO ANY AND ALL FINDINGS OF A CURRENT AND ACCURATE TITLE SEARCH. NO TITLE REPORT WAS FURNISHED TO THE SURVEYOR PRIOR TO SURVEY.
- 5. THIS SURVEYOR HAS NOT PHYSICALLY LOCATED THE UNDERGROUND UTILITIES. THE ABOVE GRADE AND UNDERGROUND UTILITIES SHOWN WERE TAKEN FROM VISIBLE APPURTENANCES AT THE SITE, PUBLIC RECORDS AND/OR MAPS PREPARED BY OTHERS. THE SURVEYOR MAKES NO GUARANTEE THAT THE UNDERGROUND UTILITIES SHOWN COMPRISE ALL SUCH UTILITIES IN THE AREA, EITHER IN SERVICE OR ABANDONED. THE SURVEYOR FURTHER DOES NOT WARRANT THAT THE UNDERGROUND UTILITIES ARE IN THE EXACT LOCATION INDICATED. THEREFORE, RELIANCE UPON THE TYPE, SIZE AND LOCATION OF UTILITIES SHOWN SHOULD BE DONE SO WITH THIS CIRCUMSTANCE CONSIDERED DETAILED VERIFICATION OF EXISTENCE, LOCATION AND DEPTH SHOULD ALSO BE MADE PRIOR TO ANY DECISION RELATIVE THERETO IS MADE. AVAILABILITY AND COST OF SERVICE SHOULD BE CONFIRMED WITH THE APPROPRIATE UTILITY COMPANY.
- 6. IN TENNESSEE IT IS A REQUIREMENT OF THE UNDERGROUND UTILITY DAMAGE PREVENTION ACT, THAT ANYONE WHO ENGAGES IN EXCAVATION MUST NOTIFY ALL KNOWN UNDERGROUND UTILITY OWNER(S), NO LESS THAN (3) NOR MORE THAN (10) WORKING DAYS PRIOR TO THE DATE OF THE INTENT TO EXCAVATE AND ALSO TO AVOID ANY HAZARD OR CONFLICT. TENNESSEE ONE CALL 1-800-351-1111 UTILITIES NOT CHECKED.
- 7. SURVEYORS LIABILITY FOR THIS DOCUMENT SHALL BE LIMITED TO THE ORIGINAL PURCHASER AND DOES NOT EXTEND TO ANY UNNAMED PERSON OR ENTITY WITHOUT AN EXPRESSED RE-CERTIFICATION BY THE SURVEYOR WHOSE NAME APPEARS UPON THIS SURVEY.
- 8. THIS PROPERTY WAS PREPARED FROM CURRENT DEEDS AND PLATS OF RECORD AND DOES NOT REPRESENT A TITLE SEARCH OR A GUARANTEE OF TITLE AND IS SUBJECT TO ANY STATE OF FACTS A CURRENT AND ACCURATE TITLE SEARCH MAY REVEAL. THE PROPERTY SHOWN ON THIS PLAT IS SUBJECT TO ALL COVENANTS, RIGHT-OF-WAYS, EASEMENTS, AND RESTRICTIONS WHETHER IMPLIED OR OF RECORD.
- 9. THE CERTIFICATION AS PROVIDED ON THIS SURVEY, IS PURELY A STATE OF PROFESSIONAL OPINION BASED ON KNOWLEDGE, INFORMATION AND BELIEF, BASED ON EXISTING FIELD EVIDENCE AND DOCUMENTARY EVIDENCE PROVIDED BY OTHERS.
- 10. THE CERTIFICATION IS NOT AN EXPRESSED OR IMPLIED WARRANTY OR GUARANTEE.
- 11. THIS DOCUMENT MUST BE COMPARED TO THE ORIGINAL HARD COPY ISSUED AT THE SURVEY DATE WITH ITS ORIGINAL SEAL TO INSURE THE ACCURACY OF THE INFORMATION AND NO RELIANCE SHOULD BE MADE ON A DOCUMENT TRANSMITTED BY COMPUTER OR OTHER ELECTRONIC MEANS UNLESS FIRST COMPARED TO THE ORIGINAL SEALED DOCUMENT ISSUED AT THE TIME OF THE SURVEY.

SURVEY INFORMATION NOTE:

THE EXISTING CONDITIONS SHOWN ON THESE PLANS HAS BEEN PROVIDED BY CHANDLER SURVEY. HARPETH CIVIL, INC. (HCI) TAKES NO RESPONSIBILITY AS TO THE ACCURACY, PRECISION, CORRECTNESS, OR COMPLETENESS OF THE SURVEY INFORMATION.






DRVV:	АП	CHK.	DS
DESCR	IPTION:		
CONST	. DOCS I	ssued to c	LIENT
DATE:			-
DRW:	-	CHK:	-
DESCR	IPTION:		
-			
DATE:			_
DRW:	-	CHK:	-
DESCR	IPTION:		
-			
DATE:			-
DRW:	-	CHK:	-
DESCR	IPTION:		
-			
DATE:			-
DRW:	-	CHK:	-
DESCR	IPTION:		

5 Ζ **VISIO** 0 3 Z Ш R UB 5 5 HILL Ζ I 1 SH 1 Ш 4




EXISTING CONDITIONS



GENERAL SITE NOTES:

- 1. LAYOUT ALL CURVES SMOOTHLY WITH NO ABRUPT CHANGES AT TANGENT POINTS.
- 2. ALL DIMENSIONS ARE TO THE FACE OF BUILDING AND / OR CURB UNLESS OTHERWISE NOTED.
- 3. SEE ARCHITECTURAL DRAWINGS FOR BUILDING DIMENSIONS.
- 4. CONTRACTOR TO TAKE ALL PRECAUTIONS TO FIND AND AVOID SITE UTILITIES. ALL UTILITIES MAY NOT BE SHOWN ON DRAWING. VERIFY LOCATIONS AND CONSIDER SUCH WHEN ESTIMATING AND PERFORMING WORK.
- 5. ALL LANDSCAPE ISLANDS SHALL BE MOUNDED WITH TOPSOIL 4" ABOVE THE CURB LINE TO PROMOTE POSITIVE DRAINAGE.
- 6. ALL PAVEMENT MARKINGS AND SIGNAGE SHALL BE INSTALLED PER THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES, LATEST EDITION.
- 7. SAW CUT LINES SHALL BE DONE IN A STRAIGHT NEAT LINE A MINIMUM OF 18" FROM THE EXISTING EDGE OF PAVEMENT.
- 8. CONTRACTOR SHALL IMMEDIATELY NOTIFY THE ARCHITECT OR ENGINEER OF ANY DISCREPANCIES FOUND BETWEEN THESE PLANS, THE ARCHITECTURAL PLANS, AND/OR FIELD CONDITIONS PRIOR TO CONSTRUCTION.
- 9. APPARENT ERRORS, DISCREPANCIES, OR OMISSIONS ON THE DRAWING SHALL BE BROUGHT TO THE ATTENTION OF THE ENGINEER PRIOR TO BID SUBMITTAL.
- 10. THE CONTRACTOR SHALL EMPLOY A REGISTERED LICENSED SURVEYOR OF TENNESSEE TO PROVIDE CONSTRUCTION LAYOUT SURVEYING SERVICES.
- 11. THE CONTRACTOR SHALL STAKE ALL IMPROVEMENTS USING THE GEOMETRIC DATA PROVIDED IN THE DRAWINGS. IT IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR TO COMPLETELY STAKE AND CHECK ALL IMPROVEMENTS TO ENSURE ADEQUATE POSITIONING, BOTH HORIZONTAL AND VERTICAL, PRIOR TO THE INSTALLATION OF ANY IMPROVEMENTS.
- 12. AFTER COMPLETION OF CONSTRUCTION, THE CONTRACTOR SHALL PERFORM SITE CLEANUP TO REMOVE ALL TRASH, DEBRIS, EXCESS MATERIALS, EQUIPMENT, AND OTHER DELETERIOUS MATERIALS ASSOCIATED WITH CONSTRUCTION. THE CONTRACTOR IS EXPRESSLY RESPONSIBLE FOR ENSURING THE SITE IS CLEAN AND IN OPERABLE CONDITION AT THE TIME OF FINAL ACCEPTANCE.
- 13. THE CONTRACTOR IS RESPONSIBLE FOR THE PROTECTION AND REPLACEMENT OF ALL PROPERTY PINS ON THIS SITE.
- 14. THESE DRAWINGS ARE INTENDED FOR USE ON THIS SITE ONLY AND AS AN INTEGRATED SET FOR THIS SPECIFIC PROJECT. THESE DRAWINGS MAY NOT BE USED IN WHOLE OR IN PART ON ANY OTHER PROJECT UNDER THE PROFESSIONAL ENGINEER'S SEAL.
- 15. THE CONTRACTOR SHALL ASSURE TO METRO THAT ALL SERVICES PROVIDED THROUGH THIS CONTRACT SHALL BE COMPLETED IN FULL COMPLIANCE WITH THE AMERICANS WITH DISABILITIES ACT ("ADA") AND ARCHITECTURAL AND TRANSPORTATION BARRIERS COMPLIANCE BOARD, FEDERAL REGISTER 36 CFR PART 1190 AND 1191, ACCESSIBILITY GUIDELINES FOR BUILDINGS AND FACILITIES; ARCHITECTURAL BARRIERS ACT (ABA) ACCESSIBILITY GUIDELINES; PROPOSED RULE, PUBLISHED IN THE FEDERAL REGISTER ON JULY 23, 2004, AS HAS BEEN ADOPTED BY METRO.
- 16. THE CONTRACTOR SHALL BE RESPONSIBLE FOR DEMOLITION AND REMOVAL OF ANY EXISTING STRUCTURES, RELATED UTILITIES, PAVING, AND ANY OTHER EXISTING IMPROVEMENTS AS NOTED OR NEEDED TO COMPLETE THE WORK.
- 17. THE CONTRACTOR IS TO REMOVE AND DISPOSE OF ALL DEBRIS, RUBBISH, AND OTHER MATERIALS RESULTING FROM PREVIOUS AND CURRENT DEMOLITION OPERATIONS. DISPOSAL WILL BE IN ACCORDANCE WITH ALL LOCAL, STATE, AND/OR FEDERAL REGULATIONS GOVERNING SUCH OPERATIONS.
- 18. THE GENERAL CONTRACTOR WILL BE HELD SOLELY RESPONSIBLE FOR AND SHALL TAKE ALL PRECAUTIONS NECESSARY TO AVOID PROPERTY DAMAGE TO ADJACENT PROPERTIES DURING THE CONSTRUCTION PHASES OF THIS PROJECT.
- 19. SAFETY NOTICE TO CONTRACTOR: IN ACCORDANCE WITH GENERALLY ACCEPTED CONSTRUCTION PRACTICES, THE CONTRACTOR SHALL BE SOLELY AND COMPLETELY RESPONSIBLE FOR CONDITIONS OF THE JOB SITE, INCLUDING SAFETY OF ALL PERSONS AND PROPERTY DURING PERFORMANCE OF THE WORK. THIS REQUIREMENT WILL APPLY CONTINUOUSLY AND NOT BE LIMITED TO NORMAL WORKING HOURS. ANY CONSTRUCTION OBSERVATION BY THE ENGINEER OF THE CONTRACTOR'S PERFORMANCE IS NOT INTENDED TO INCLUDE REVIEW OF THE ADEQUACY OF THE CONTRACTOR'S SAFETY MEASURES, IN, ON OR NEAR THE CONSTRUCTION SITE.
- 20. ALL SITE WORK FOR THIS PROJECT SHALL MEET OR EXCEED THE SPECIFICATIONS OF THE RELEVANT UTILITY COMPANY OR REGULATORY AUTHORITY
- 21. HCI EXCLUDES THE DESIGN OF SITE RETAINING WALLS OR VERTICAL STRUCTURAL FEATURES INCLUDING, BUT NOT LIMITED TO,CAST-IN-PLACE CONCRETE, MODULAR BLOCK, OR MECHANICALLY STABILIZE EARTH FEATURES.



MINIMUM BUILDING SETBACK LINES AND <u>PUBLIC UTILITY & DRAINAGE EASEMENT (TYP.)</u>

N.T.S.


JOHNAR ASS'ELONASS' JOHNAR ASS'ELONASS' NARRAR BORGE ASO' RECORDER O.C.

FEMA FLOOD ZONE 'AE' ELEVATION 402.0 PER FIRM NO.47021C0165D, REVISED SEPTEMBER 17, 2010

R

Ð

18



GENERAL SITE NOTES:


- 1. LAYOUT ALL CURVES SMOOTHLY WITH NO ABRUPT CHANGES AT TANGENT POINTS.
- 2. CONTRACTOR TO TAKE ALL PRECAUTIONS TO FIND AND AVOID SITE UTILITIES. ALL UTILITIES MAY NOT BE SHOWN


- ON DRAWING. VERIFY LOCATIONS AND CONSIDER SUCH WHEN ESTIMATING AND PERFORMING WORK.
- 3. ALL LANDSCAPE ISLANDS SHALL BE MOUNDED WITH TOPSOIL 4" ABOVE THE CURB LINE TO PROMOTE POSITIVE
- DRAINAGE.
- 4. ALL PAVEMENT MARKINGS AND SIGNAGE SHALL BE INSTALLED PER THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES, LATEST EDITION.
- 5. SAW CUT LINES SHALL BE DONE IN A STRAIGHT NEAT LINE A MINIMUM OF 18" FROM THE EXISTING EDGE OF
- PAVEMENT.
- 6. CONTRACTOR SHALL IMMEDIATELY NOTIFY THE ARCHITECT OR ENGINEER OF ANY DISCREPANCIES FOUND
- BETWEEN THESE PLANS, THE ARCHITECTURAL PLANS, AND/OR FIELD CONDITIONS PRIOR TO CONSTRUCTION.
- 7. APPARENT ERRORS, DISCREPANCIES, OR OMISSIONS ON THE DRAWING SHALL BE BROUGHT TO THE ATTENTION
- OF THE ENGINEER PRIOR TO BID SUBMITTAL.
- 8. THE CONTRACTOR SHALL EMPLOY A REGISTERED LICENSED SURVEYOR OF TENNESSEE TO PROVIDE
- CONSTRUCTION LAYOUT SURVEYING SERVICES.
- 9. THE CONTRACTOR SHALL STAKE ALL IMPROVEMENTS USING THE GEOMETRIC DATA PROVIDED IN THE DRAWINGS. IT IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR TO COMPLETELY STAKE AND CHECK ALL IMPROVEMENTS TO ENSURE ADEQUATE POSITIONING, BOTH HORIZONTAL AND VERTICAL, PRIOR TO THE
- INSTALLATION OF ANY IMPROVEMENTS. 10. AFTER COMPLETION OF CONSTRUCTION, THE CONTRACTOR SHALL PERFORM SITE CLEANUP TO REMOVE ALL
- TRASH, DEBRIS, EXCESS MATERIALS, EQUIPMENT, AND OTHER DELETERIOUS MATERIALS ASSOCIATED WITH CONSTRUCTION. THE CONTRACTOR IS EXPRESSLY RESPONSIBLE FOR ENSURING THE SITE IS CLEAN AND IN OPERABLE CONDITION AT THE TIME OF FINAL ACCEPTANCE.
- 11. THE CONTRACTOR IS RESPONSIBLE FOR THE PROTECTION AND REPLACEMENT OF ALL PROPERTY PINS ON THIS SITE.
- 12. THESE DRAWINGS ARE INTENDED FOR USE ON THIS SITE ONLY AND AS AN INTEGRATED SET FOR THIS SPECIFIC PROJECT. THESE DRAWINGS MAY NOT BE USED IN WHOLE OR IN PART ON ANY OTHER PROJECT UNDER THE PROFESSIONAL ENGINEER'S SEAL.
- 13. THE CONTRACTOR SHALL BE RESPONSIBLE FOR DEMOLITION AND REMOVAL OF ANY EXISTING STRUCTURES, RELATED UTILITIES, PAVING, AND ANY OTHER EXISTING IMPROVEMENTS AS NOTED OR NEEDED TO COMPLETE THE WORK.
- 14. THE CONTRACTOR IS TO REMOVE AND DISPOSE OF ALL DEBRIS, RUBBISH, AND OTHER MATERIALS RESULTING FROM PREVIOUS AND CURRENT DEMOLITION OPERATIONS. DISPOSAL WILL BE IN ACCORDANCE WITH ALL LOCAL, STATE, AND/OR FEDERAL REGULATIONS GOVERNING SUCH OPERATIONS.
- 15. THE GENERAL CONTRACTOR WILL BE HELD SOLELY RESPONSIBLE FOR AND SHALL TAKE ALL PRECAUTIONS NECESSARY TO AVOID PROPERTY DAMAGE TO ADJACENT PROPERTIES DURING THE CONSTRUCTION PHASES OF THIS PROJECT.
- 16. SAFETY NOTICE TO CONTRACTOR: IN ACCORDANCE WITH GENERALLY ACCEPTED CONSTRUCTION PRACTICES, THE CONTRACTOR SHALL BE SOLELY AND COMPLETELY RESPONSIBLE FOR CONDITIONS OF THE JOB SITE, INCLUDING SAFETY OF ALL PERSONS AND PROPERTY DURING PERFORMANCE OF THE WORK. THIS REQUIREMENT WILL APPLY CONTINUOUSLY AND NOT BE LIMITED TO NORMAL WORKING HOURS. ANY CONSTRUCTION OBSERVATION BY THE ENGINEER OF THE CONTRACTOR'S PERFORMANCE IS NOT INTENDED TO INCLUDE REVIEW OF THE ADEQUACY OF THE CONTRACTOR'S SAFETY MEASURES, IN, ON OR NEAR THE CONSTRUCTION SITE.
- 17. ALL SITE WORK FOR THIS PROJECT SHALL MEET OR EXCEED THE SPECIFICATIONS OF THE RELEVANT UTILITY COMPANY OR REGULATORY AUTHORITY


PUBLIC RIGHT OF WAY CONSTRUCTION NOTES:


- 1. ALL ELEMENTS WITHIN THE RIGHT-OF-WAY SHALL BE CONSTRUCTED PER THE TOWN OF ASHLAND CITY PUBLIC WORKS STANDARDS AND SPECIFICATIONS
- 2. ALL PAVEMENT SECTION IMPROVEMENTS SHALL BE CONSTRUCTED TO THE APPROPRIATE ROAD CLASSIFICATION PER THE TOWN OF ASHLAND CITY PUBLIC WORKS STANDARDS.
- 3. THE PROPOSED GRADES SHOWN ON PUBLIC DRIVEWAY ENTRANCE ARE FOR GENERAL GUIDANCE ONLY. THE FINISHED GRADE SHALL MEET THE STANDARDS AND SPECIFICATIONS OF THE TOWN OF ASHLAND CITY PUBLIC WORKS AS INDICATED ON THE CONSTRUCTION DETAILS PROVIDED.
- STANDARDS AND SPECIFICATIONS AND REQUEST AN INSPECTION BY THE TOWN OF ASHLAND CITY PUBLIC WORKS PRIOR TO CONSTRUCTION.
- 5. THE CONTRACTOR SHALL NOTIFY THE ENGINEER OF DISCREPANCIES IDENTIFIED IN THE FIELD PRIOR TO CONSTRUCTION.

4. THE CONTRACTOR SHALL VERIFY THAT ALL CROSS SLOPES MEET THE TOWN OF ASHLAND CITY PUBLIC WORKS











ST	RUCTURE ID	ТҮРЕ	CASTING TYPE	RIM ELEV.	I.E. (IN)	I.E. (OUT)						HORIZC	
	A1	HEADWALL (TYP.)			441.0								
	A2	HEADWALL (TYP.)				439.0							
							STORM PIPE SCHE		RM PIPE SCHEDULE				
	B1	HEADWALL (TYP.)			441.0		F	PIPE ID)	SIZE (In.)	MATERIAL	LENGTH (Ft.)	SLOPE (%)
	B2	HEADWALL (TYP.)				442.0	A2	-	A 1	15"	RCP	36	5.56%
*	SEE GRADING AND SHEET C-2.1 FOR STR						B2	-	B1	15"	RCP	34	2.91%



Know what's below. Call before you dig.

GENERAL GRADING NOTES:


- 1. ALL UNSUITABLE SUBSURFACE MATERIAL IS TO BE EXCAVATED IN ACCORDANCE WITH THESE PLANS AND SPECIFICATIONS OR THE RECOMMENDATIONS OF THE CONTRACTORS TENNESSEE REGISTERED GEOTECHNICAL ENGINEER. UNSUITABLE MATERIAL IS TO BE STOCKPILED, REMOVED, AND PROPERLY DISPOSED OF OFF-SITE. EXCAVATED AREAS ARE TO BE BACK FILLED WITH APPROVED MATERIALS AND COMPACTED AS INDICATED ON THESE PLANS AND SPECIFICATIONS OR THE RECOMMENDATIONS OF THE CONTRACTORS GEOTECHNICAL ENGINEER.
- 2. THE CONTRACTOR SHALL NOT STOCK PILE DEBRIS AND/OR SOIL NEAR ENVIRONMENTALLY SENSITIVE AREAS (I.E. STREAM BUFFERS, WETLANDS, AREAS OF EXCESSIVE SLOPE, PROTECTED TREES OR THEIR RESPECTIVE CANOPY DRIP LINES, ETC ...).
- 3. THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROTECTING TRENCH EXCAVATIONS AGAINST COLLAPSE AND SHALL PROVIDE BRACING, SHEETING, OR SHORING WHERE NECESSARY. DEWATERING METHODS SHALL BE USED AS REQUIRED TO KEEP TRENCHES DRY WHILE PIPE AND APPURTENANCES ARE BEING INSTALLED.
- 4. ALL NECESSARY FILL AND EMBANKMENT THAT IS PLACED DURING CONSTRUCTION SHALL CONSIST OF MATERIAL SPECIFIED BY THE CONTRACTORS TENNESSEE REGISTERED GEOTECHNICAL ENGINEER. THE CONTRACTOR IS RESPONSIBLE FOR ENSURING THAT ALL CONSTRUCTION ACTIVITIES, WHICH INCLUDE BUT ARE NOT LIMITED TO EARTHWORK ACTIVITIES, SUB GRADE PREPARATION, ETC. CONFORM TO THE STRICTER OF THE GEOTECHNICAL RECOMMENDATIONS OR TDOT (TENNESSEE DEPARTMENT OF TRANSPORTATION) STANDARDS AND SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION (LATEST EDITION).
- 5. THE CONTRACTOR SHALL NOTIFY THE OWNER AND ENGINEER OF RECORD IMMEDIATELY IF UNSUITABLE SOIL IS ENCOUNTERED DURING EXCAVATION. UNSUITABLE SOIL SHALL NOT BE USED ON-SITE WITHOUT A WRITTEN RECOMMENDATION BY THE CONTRACTORS TENNESSEE REGISTERED GEOTECHNICAL ENGINEER AND CONSENT GRANTED IN WRITING BY THE OWNER AND THE ENGINEER OF RECORD.
- 6. REFER TO THE PROJECT EPSC (EROSION PREVENTION AND SEDIMENT CONTROL PLANS) PLANS FOR ADDITIONAL INFORMATION.
- 7. ALL MATERIALS SHALL CONFORM TO TDOT STANDARDS.
- 8. PROPOSED SPOT ELEVATIONS REPRESENT FINISHED PAVEMENT OR GROUND SURFACE GRADE UNLESS OTHERWISE NOTED ON THE DRAWINGS.
- 9. THE CONTRACTOR SHALL STABILIZE ALL DISTURBED GROUND BY SEEDING / MULCHING, SODDING, OR OTHER APPROVED MATERIAL IN ACCORDANCE WITH TDEC (TENNESSEE DEPARTMENT OF ENVIRONMENT AND CONSERVATION) VOLUME 4 HANDBOOK. DISTURBED AREAS SHALL BE STABILIZED WITHIN ONE WEEK (OR SOONER) FOLLOWING CONSTRUCTION OF THE UNDERLYING ACTIVITY. THE CONTRACTOR SHALL MAINTAIN SUCH AREAS BY REPAIRING AND WATER SOD OR SEEDED AREAS UNTIL THE AREA IS STABLE AND EROSION FREE.
- 10. THE CONTRACTOR SHALL TAKE ALL NECESSARY MEASURES TO PREVENT EROSION. ANY DAMAGE FROM FAILURE TO ADEQUATELY STABILIZE, PROTECT, AND MAINTAIN THESE AREAS SHALL BE THE SOLE RESPONSIBILITY OF THE CONTRACTOR. NEITHER THE ENGINEER OF RECORD OR THE OWNER ARE RESPONSIBLE FOR THE MEANS AND METHODS OF ADEQUATELY STABILIZING THE PROJECT.
- 11. THE CONTRACTOR SHALL NOT ALTER THE EXISTING HISTORICAL DRAINAGE PATTERNS IN REGARDS TO THE EXISTING PAVING CROSS SECTIONS, SIDEWALKS AND GRASS SWALES ON OR ADJACENT TO THE PROJECT UNLESS OTHERWISE DEPICTED ON THE CONSTRUCTIONS PLANS OR AS REQUIRED BY LOCAL AGENCIES.
- 12. ALL UNDERGROUND UTILITIES INCLUDING BUT NOT LIMITED TO WATER MAINS AND SERVICES, SEWER MAINS AND SERVICES, GAS, POWER, CONDUIT, DATA / COMMUNICATIONS, ETC... SHALL BE INSTALLED PRIOR TO PAVEMENT CONSTRUCTION. CONTRACTOR TO COORDINATE INSTALLATION OF ANY ADDITIONAL CONDUIT LOCATIONS WITH THE OWNER.
- 13. ALL MATERIALS AND CONSTRUCTION PROCEDURES SHALL BE IN ACCORDANCE WITH THE MORE STRICT LOCAL AGENCY OR TDOT STANDARD AND SPECIFICATIONS.
- 14. JOINTS OF THE STORM SEWER SHALL BE STAGGERED FOR CROSSINGS OF THE SANITARY SEWER WITH LESS THAN 18" VERTICAL CLEARANCE SO THAT PIPE BELL IS NOT LOCATED AT THE CROSSING.




TYPICAL SECTION - SWALE

TYPICAL SECTION - SWALE

(NOT TO SCALE)





EROSION PREVENTION AND SEDIMENT CONTROL NOTES:

EROSION PREVENTION AND SEDIMENT CONTROL MEASURES TO BE SELECTED, INSTALLED, AND MAINTAINED IN ACCORDANCE WITH THE TENNESSEE DEPARTMENT OF ENVIRONMENT AND CONSERVATION (TDEC) EROSION AND SEDIMENT CONTROL HANDBOOK, LATEST EDITION.

2

18-

 $\langle \leftarrow$

E'AE'

102.0

ISED

2010


- 2. SITE EROSION CONTROLS SHALL BE CHECKED DAILY AND WITHIN 24 HOURS AFTER EACH RAINFALL EVENT GREATER THAN OR EQUAL TO 0.5 INCHES OF CONTINUOUS RAINFALL. EROSION CONTROLS SHALL BE REPAIRED IMMEDIATELY.
- 3. ANY OFF-SITE SEDIMENT ACCUMULATIONS SHALL BE REMOVED DAILY. IF OFF-SITE ACCUMULATIONS OCCUR ON ADJACENT PRIVATE PROPERTY, IT SHALL BE IMMEDIATELY REMOVED BY METHODS AGREED UPON BY THE CONTRACTOR AND ADJACENT PROPERTY OWNER.
- 4. STABILIZED ALL DISTURBED AREAS WITHIN 14 DAYS AND STEEP SLOPES EQUAL TO OR GREATER THAN 3:1 WITHIN 7 DAYS.
- 5. CONTRACTOR SHALL PROVIDE AN AREA FOR CONCRETE WASHOUT AND EQUIPMENT FUELING IN ACCORDANCE WITH METRO CP-10 AND CP-13 RESPECTIVELY. CONTRACTOR TO COORDINATE EXACT LOCATION WITH NPDES DEPARTMENT DURING PRE-CONSTRUCTION MEETING. CONTROL OF OTHER SITE WASTES SUCH AS DICARDED MATERIALS, CHEMICALS, LITTER, AND SANITARY WASTES THAT MAY CAUSE ADVERSE IMPACT TO WATER QUALITY IS ALSO REQUIRED BY THE GRADING PERMITTEE.
- 6. CONTROL OF OTHER SITE WASTE SUCH AS DISCARDED BUILDING MATERIALS, CHEMICALS, LITTER, AND SANITARY WASTES THAT MAY CAUSE ADVERSE IMPACTS TO WATER QUALITY IS ALSO REQUIRED.
- 7. INLET PROTECTION TO BE REMOVED AFTER FINAL SITE STABILIZATION.
- 8. AN ON-SITE COPY OF THE EPSC PLANS SHALL BE KEPT CURRENT AND AVAILABLE TO THOSE RESPONSIBLE FOR EROSION PREVENTION AND SEDIMENT CONTROL MEASURES AND INSPECTION.
- 9. FOR PROJECTS REQUIRING COVERAGE UNDER THE TENNESSEE CONSTRUCTION GENERAL PERMIT (CGP), A COPY OF THE NOI, SWPPP, AND NOC SHALL BE AVAILABLE TO THOSE RESPONSIBLE FOR EROSION PREVENTION AND SEDIMENT CONTROL MEASURES AND INSPECTIONS. THE NOC AND TRACKING NUMBER SHALL BE POSTED AT THE ENTRANCE OF THE SITE.
- 10. THE INITIAL CONDITIONS EPSC MEASURES AND/OR SWPPP MUST BE IMPLEMENTED, INSTALLED, AND INSPECTED BY THE LOCAL AUTHORITY PRIOR TO THE COMMENCEMENT OF ANY CONSTRUCTION ACTIVITIES.
- 11. DISCHARGES FROM DEWATERING ACTIVITIES, IF NECESSARY, SHALL BE MANAGED WITH APPROPRIATE CONTROLS AS REQUIRED BY THE LOCAL AUTHORITY. THE CONTRACTOR SHALL WORK WITH THE INSPECTOR FROM THE LOCAL AUTHORITY FOR PROPER MANAGEMENT PRIOR TO THE COMMENCEMENT OF DEWATERING ACTIVITIES.
- 12. ALL EXISTING AND NEWLY CONSTRUCTED DRAINAGE STRUCTURES, PIPES, SWALES, AND RIP RAP SHALL HAVE ALL SEDIMENT REMOVED AND PROPERLY DISPOSED OF OFF-SITE UPON PROJECT STABILIZATION. THIS WILL BE REQUIRED PRIOR TO THE ACCEPTANCE OF FINAL CONSTRUCTION.
- 13. EROSION CONTROL MEASURES SHALL BE CLEANED WITH AT APPROXIMATELY 50% CAPACITY OR AS DIRECTED BY THE LOCAL AUTHORITY OR TDEC EROSION PREVENTION AND SEDIMENT CONTROL HANDBOOK, LATEST EDITION. THE MOST STRINGENT REQUIREMENT SHALL APPLY.
- 14. THE DESIGNATED PLACEMENT OF EPSC MEASURES SHALL BE SUBJECT TO ADJUSTMENT BY THE SITE EPSC INSPECTOR. ADJUSTMENTS SHALL BE RECORDED IN THE ON-SITE SET OF EPSC PLANS.
- 15. ALL PERIMETER MEASURES MUST BE IN PLACE, APPROVED BY FINAL INSPECTION, AND GRADING PERMIT OBTAINED PRIOR TO THE ONSET OF GRADING ACTIVITIES.


TOTAL HYDROLOGICALLY DISTURBED AREA = 0.88 Ac.

	TDEC	CGP	NOTE:
--	------	-----	-------

I HEREBY CERTIFY THAT THIS PROJECT DOES **NOT** REQUIRE COVERAGE UNDER A TENNESSEE CONSTRUCTION GENERAL PERMIT. THE TOTAL DISTURBED AREA IS: **0.88 ACRES**.

THIS SITE DISCHARGES INTO WATERS IDENTIFIED BY TDEC AS: CHECK ALL THAT APPLY: EXCEPTIONAL NOT SUPPORTING NONE FULLY SUP 10/16/2020 PROFESSIONAL ENGINEER REGISTERED IN THE STATE OF TENNESSEE DATE PROJECT ENGINEER OTHER CIRCLE ONE: DEVELOPER





EROSION PREVENTION AND SEDIMENT CONTROL NOTES:

- EROSION PREVENTION AND SEDIMENT CONTROL MEASURES TO BE SELECTED, INSTALLED, AND MAINTAINED IN ACCORDANCE WITH THE TENNESSEE DEPARTMENT OF ENVIRONMENT AND CONSERVATION (TDEC) EROSION AND SEDIMENT CONTROL HANDBOOK, LATEST EDITION.
- 2. SITE EROSION CONTROLS SHALL BE CHECKED DAILY AND WITHIN 24 HOURS AFTER EACH RAINFALL EVENT GREATER THAN OR EQUAL TO 0.5 INCHES OF CONTINUOUS RAINFALL. EROSION CONTROLS SHALL BE REPAIRED IMMEDIATELY.
- 3. ANY OFF-SITE SEDIMENT ACCUMULATIONS SHALL BE REMOVED DAILY. IF OFF-SITE ACCUMULATIONS OCCUR ON ADJACENT PRIVATE PROPERTY, IT SHALL BE IMMEDIATELY REMOVED BY METHODS AGREED UPON BY THE CONTRACTOR AND ADJACENT PROPERTY OWNER.
- 4. STABILIZED ALL DISTURBED AREAS WITHIN 14 DAYS AND STEEP SLOPES EQUAL TO OR GREATER THAN 3:1 WITHIN 7 DAYS.
- 5. CONTRACTOR SHALL PROVIDE AN AREA FOR CONCRETE WASHOUT AND EQUIPMENT FUELING IN ACCORDANCE WITH METRO CP-10 AND CP-13 RESPECTIVELY. CONTRACTOR TO COORDINATE EXACT LOCATION WITH NPDES DEPARTMENT DURING PRE-CONSTRUCTION MEETING. CONTROL OF OTHER SITE WASTES SUCH AS DICARDED MATERIALS, CHEMICALS, LITTER, AND SANITARY WASTES THAT MAY CAUSE ADVERSE IMPACT TO WATER QUALITY IS ALSO REQUIRED BY THE GRADING PERMITTEE.
- 6. CONTROL OF OTHER SITE WASTE SUCH AS DISCARDED BUILDING MATERIALS, CHEMICALS, LITTER, AND SANITARY WASTES THAT MAY CAUSE ADVERSE IMPACTS TO WATER QUALITY IS ALSO REQUIRED.
- 7. INLET PROTECTION TO BE REMOVED AFTER FINAL SITE STABILIZATION.
- 8. AN ON-SITE COPY OF THE EPSC PLANS SHALL BE KEPT CURRENT AND AVAILABLE TO THOSE RESPONSIBLE FOR EROSION PREVENTION AND SEDIMENT CONTROL MEASURES AND INSPECTION.
- 9. FOR PROJECTS REQUIRING COVERAGE UNDER THE TENNESSEE CONSTRUCTION GENERAL PERMIT (CGP), A COPY OF THE NOI, SWPPP, AND NOC SHALL BE AVAILABLE TO THOSE RESPONSIBLE FOR EROSION PREVENTION AND SEDIMENT CONTROL MEASURES AND INSPECTIONS. THE NOC AND TRACKING NUMBER SHALL BE POSTED AT THE ENTRANCE OF THE SITE.
- 10. THE INITIAL CONDITIONS EPSC MEASURES AND/OR SWPPP MUST BE IMPLEMENTED, INSTALLED, AND INSPECTED BY THE LOCAL AUTHORITY PRIOR TO THE COMMENCEMENT OF ANY CONSTRUCTION ACTIVITIES.
- 11. DISCHARGES FROM DEWATERING ACTIVITIES, IF NECESSARY, SHALL BE MANAGED WITH APPROPRIATE CONTROLS AS REQUIRED BY THE LOCAL AUTHORITY. THE CONTRACTOR SHALL WORK WITH THE INSPECTOR FROM THE LOCAL AUTHORITY FOR PROPER MANAGEMENT PRIOR TO THE COMMENCEMENT OF DEWATERING ACTIVITIES.
- 12. ALL EXISTING AND NEWLY CONSTRUCTED DRAINAGE STRUCTURES, PIPES, SWALES, AND RIP RAP SHALL HAVE ALL SEDIMENT REMOVED AND PROPERLY DISPOSED OF OFF-SITE UPON PROJECT STABILIZATION. THIS WILL BE REQUIRED PRIOR TO THE ACCEPTANCE OF FINAL CONSTRUCTION.
- 13. EROSION CONTROL MEASURES SHALL BE CLEANED WITH AT APPROXIMATELY 50% CAPACITY OR AS DIRECTED BY THE LOCAL AUTHORITY OR TDEC EROSION PREVENTION AND SEDIMENT CONTROL HANDBOOK, LATEST EDITION. THE MOST STRINGENT REQUIREMENT SHALL APPLY.
- 14. THE DESIGNATED PLACEMENT OF EPSC MEASURES SHALL BE SUBJECT TO ADJUSTMENT BY THE SITE EPSC INSPECTOR. ADJUSTMENTS SHALL BE RECORDED IN THE ON-SITE SET OF EPSC PLANS.
- 15. ALL PERIMETER MEASURES MUST BE IN PLACE, APPROVED BY FINAL INSPECTION, AND GRADING PERMIT OBTAINED PRIOR TO THE ONSET OF GRADING ACTIVITIES.

TOTAL HYDROLOGICALLY DISTURBED AREA = 0.88 Ac.

'AE' 02.0 SED 010	A 35°53'49"

2

18


 $\langle \langle \langle \cdot \rangle$


TDEC CGP NOTE:

I HEREBY CERTIFY THAT THIS PROJECT DOES **NOT** REQUIRE COVERAGE UNDER A TENNESSEE CONSTRUCTION GENERAL PERMIT. THE TOTAL DISTURBED AREA IS: **0.88 ACRES**.

CHECK ALL THAT APPLY: THIS SITE DISCHARGES INTO WATERS IDENTIFIED BY TDEC AS: FULLY SUPPORTIN NOT SUPPORTING EXCEPTIONAL NONE 10/16/2020 PROFESSIONAL ENGINEER REGISTERED IN THE STATE OF TENNESSEE DATE PROJECT ENGINEER OTHER_ DEVELOPER


CIRCLE ONE:







- EROSION AND SEDIMENT CONTROL HANDBOOK, LATEST EDITION.
- REPAIRED IMMEDIATELY.
- THE CONTRACTOR AND ADJACENT PROPERTY OWNER.
- TO WATER QUALITY IS ALSO REQUIRED BY THE GRADING PERMITTEE.

- THE LOCAL AUTHORITY FOR PROPER MANAGEMENT PRIOR TO THE COMMENCEMENT OF DEWATERING ACTIVITIES.
- BE REQUIRED PRIOR TO THE ACCEPTANCE OF FINAL CONSTRUCTION.
- LATEST EDITION. THE MOST STRINGENT REQUIREMENT SHALL APPLY.





NORTH MAIN STREET (ASHLAND CITY HIGHWAY)



OH-E OH-E OH-E OH-E OH-E OH-E OH-E OH-E	0-	DATE: 10-16-2020 DRW: AH CHK: DS DESCRIPTION: . CONST. DOCCS ISSUED TO CLIENT DATE: . DRW: - CHK: . DATE: . DRW: - CHK: . DATE: . . DRW: . CHK: . DRW: . CHK: . DRW: . CHK: . DRW: .<
UPS MAIN 'A' STA: 0+27 UPS MAIN 'B' STA: 2+16 2" X 2.5" X 1-1/2" TEE Image: Construction of the second		PEACH HILL SUBDIVISION PEACH STREET ASHLAND CITY, TN, 37015
D 00 EXISTING CONTOUR 00 EXISTING CONTOUR 5" FM PROPOSED 1.25" SDR-21 PVC LPS FORCE MAIN "FM PROPOSED 1.5" SDR-21 PVC LPS FORCE MAIN "FM PROPOSED 1.5" SDR-21 PVC LPS FORCE MAIN "FM PROPOSED 2.5" SDR-21 PVC LPS FORCE MAIN	SCALE: 1" = 30	ICINICATION CONTRACTOR OF CONT

	PLAN. VIEW
	THRUST BLOCK
env	TYPICAL FLUSHI
	EXISTING PAVEMENT
	3'4" COMPACTED CRUSHED STONE TO BOTTOM OF PAVEMENT 3" CONTINUOUS WARNING TAPE
	NOTE: EDGE OF PAVEMENT TO BE TR TRENCH WIDTH TO OBTAIN NE TEMPORARY SURFACE WITHIN
	ASPHALT PAVEN STANDARD WATER AND SEWER SYSTEM DE THE TOWN OF ASHLAND CITY, TENNES


Prepared E Aston Hute	-			
Zone	Connects	Number	Accum	Gal
Number	to Zone	of Pumps	Pumps	per
		in Zone	in Zone	
This spread	sheet was o	alculated	using pip	e di
1.00	2.00	3	3	
2.00	3.00	6	9	
3.00	4.00	11	20	
4.00	4.00	14	34	

ASHLAND CITY UTILITY NOTES:

- 1. ALL APPLICABLE FEDERAL AND STATE LAWS, MUNICIPAL ORDINANCES, AND THE RULES AND REGULATIONS OF ALL AUTHORITIES HAVING JURISDICTION OVER CONSTRUCTION OF THE PROJECT SHALL APPLY TO THE CONSTRUCTION THROUGHOUT.
- 2. SIZES AND LOCATIONS OF ALL WATER AND SEWER LINES AND APPURTENANCES, AND ALL CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE PLANS APPROVED BY THE TOWN.
- PERMITS FOR PAVEMENTS CUTS OR CROSSINGS OF PUBLIC ROADS, INCLUDING ANY SPECIAL BACKFILL AND PAVEMENT REPAIR REQUIRED BY THE AGENCY HAVING JURISDICTION, ARE THE RESPONSIBILITY OF THE DEVELOPER. A BOND MAY BE REQUIRED FROM THE DEVELOPER TO COVER ALL COSTS OF REPAIR AND MAINTENANCE FOR A PERIOD OF ONE (1) YEAR FROM THE DATE OF ACCEPTANCE OF THE PROJECT FOR ALL WORK PERFORMED IN EXISTING RIGHT-OF-WAYS OF ALL ROAD.
- 4. IF CONSTRUCTION HAS NOT STARTED WITHIN ONE (1) YEAR FROM THE DATE OF APPROVAL, UTILITY PLANS SHALL BE RESUBMITTED TO RENEW APPROVAL. RENEWAL IS NOT GUARANTEED.
- 5. THE CONTRACTORS NAME, PROJECT COST, AND ESTIMATING WORKING TIME FOR EACH PROJECT SHALL BE SUBMITTED TO THE TOWN. THE TOWN WILL BE REIMBURSED FOR EACH DAY THAT AN INSPECTOR IS REQUIRED ON THE JOB SITE UNTIL COMPLETION OF THE PROJECT.
- 6. LABORATORY TEST REPORTS SHALL BE PROVIDED ON ALL PIPE TO ASSURE THAT IT MEETS THE REQUIREMENTS OF THE TOWN'S SPECIFICATIONS.
- 7. SHOP DRAWINGS FOR UTILITY MATERIALS SHALL BE SUBMITTED TO THE TOWN OF ASHLAND CITY FOR REVIEW AFTER BEING THOROUGHLY CHECKED BY THE CONTRACTOR AND STAMPED WITH HIS APPROVAL.
- THE TOWN RESERVES THE RIGHT TO RELOCATE WATER AND SEWER LINES ON THE CONSTRUCTION PLANS TO FACILITATE MAINTENANCE.
- 9. THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATING AND VERIFYING THE ELEVATIONS OF EXISTING UTILITIES PRIOR TO CONSTRUCTION.
- 10. THE CONTRACTOR SHALL PROVIDE A SET OF CONSTRUCTION CUT SHEETS TO THE PRECONSTRUCTION MEETING AND THE CUT SHEETS SHALL INCLUDE THE STATIONS OF ALL PROPOSED SERVICE CONNECTIONS.

GENERAL UTILITY NOTES:

- 1. THE CONTRACTOR WILL PROVIDE ALL NECESSARY PROTECTIVE MEASURES TO SAFEGUARD EXISTING UTILITIES FROM DAMAGE DURING THE CONSTRUCTION OF THIS PROJECT. IN THE EVENT THAT SPECIAL EQUIPMENT IS REQUIRED TO WORK OVER OR AROUND THE EXISTING UTILITIES, THE CONTRACTOR SHALL BE REQUIRED TO PROVIDE SUCH EQUIPMENT. THE COST OF PROTECTING UTILITIES FROM DAMAGE AND FURNISHING OF ANY REQUIRED SPECIAL EQUIPMENT WILL BE INCLUDED IN THE PRICE BID FOR OTHER ITEMS OF CONSTRUCTION. 3. THE CONTRACTOR SHALL NOTIFY EACH INDIVIDUAL UTILITY OWNER OF HIS PLAN OF OPERATION IN THE AREA OF THEIR RESPECTIVE UTILITIES. PRIOR TO COMMENCEMENT OF WORK THE CONTRACTOR SHALL CONTACT EACH UTILITY OWNERS AND REQUEST THEM TO PROPERLY LOCATE THEIR RESPECTIVE UTILITIES ON THE GROUND. THIS NOTIFICATION SHALL BE GIVEN AT LEAST THREE (3) BUSINESS DAYS PRIOR TO COMMENCEMENT OF OPERATIONS AROUND THE UTILITY.
- EXISTING UTILITY LINES SHOWN ARE APPROXIMATE LOCATIONS ONLY AND SHALL BE FIELD VERIFIED PRIOR TO ANY CONSTRUCTION. IF UPON FIELD LOCATION, ANY DEVIATIONS FROM THE SHOWN DESIGN LOCATIONS SHALL BE REPORTED TO THE OWNER OR ENGINEER PRIOR TO CONSTRUCTION.
- 3. THE CONTRACTOR SHALL NOTIFY EACH INDIVIDUAL UTILITY OWNER OF HIS PLAN OF OPERATION IN THE AREA OF THEIR RESPECTIVE UTILITIES. PRIOR TO COMMENCEMENT OF WORK THE CONTRACTOR SHALL CONTACT EACH UTILITY OWNERS AND REQUEST THEM TO PROPERLY LOCATE THEIR RESPECTIVE UTILITIES ON THE GROUND. THIS NOTIFICATION SHALL BE GIVEN AT LEAST THREE (3) BUSINESS DAYS PRIOR TO COMMENCEMENT OF OPERATIONS AROUND THE UTILITY.
- ALL UNDERGROUND UTILITIES (WATER, SANITARY SEWER, STORM SEWER, ELECTRICAL CONDUITS, IRRIGATION SLEEVES, ETC..) SHALL BE IN PLACE PRIOR TO THE PLACEMENT OF ALL BASE COURSE MATERIAL.
- 5. THE UTILITY CONTRACTOR SHALL BE HELD RESPONSIBLE FOR ALL TAP AND TIE-IN FEES REQUIRED, AS WELL AS COST OF THE UNDERGROUND SERVICE CONNECTIONS TO THEIR FACILITIES.
- 6. THOSE UTILITY OWNERS WHO PARTICIPATE IN THE "TENNESSEE ONE CALL" SYSTEM CAN BE NOTIFIED TOLL FREE AT 1-800-351-1111.
- 7. ALL SEWER AND WATER CONNECTIONS SHALL BE IN ACCORDANCE WITH THE SPECIFICATIONS OUTLINED BY THE TOWN OF ASHLAND CITY STANDARD SPECIFICATIONS AND INSTALLATION GUIDELINES FOR THE CONSTRUCTION OF PUBLIC INFRASTRUCTURE (LATEST EDITION).
- 8. THE CONTRACTOR SHALL BE RESPONSIBLE FOR REIMBURSING THE TOWN OF ASHLAND CITY DEPARTMENT OF PUBLIC WORKS FOR THE COST OF INSPECTION.
- 9. THE CONTRACTOR SHALL NOTIFY THE TOWN OF ASHLAND CITY PUBLIC WORKS DEPARTMENT AND ARRANGE INSPECTION PRIOR TO BEGINNING.
- 10. COORDINATES AND DIMENSIONS SHOWN ARE TO CENTERLINE OF PIPE, OR FITTING, OR TO CENTERLINE OF MANHOLE.
- 11. THE MINIMUM HORIZONTAL SEPARATION BETWEEN THE CLOSEST TWO POINTS OF THE WATER AND SEWER LINES SHALL BE 10'. THE MINIMUM VERTICAL SEPARATION BETWEEN THE CLOSEST TWO POINTS OF THE WATER AND SEWER LINES SHALL BE 18".



	PRELIMINARY PRESSURE SEWER - PIPE SIZING AND BRANCH ANALYSIS Peach Hill Subdivision October 7, 2020												
	Max Flow Per Pump (gpm)	Max Sim Ops		Pipe Size (inches)	Max Velocity (FPS)		Factor	Friction Loss This Zone	Accum Fric Loss (feet)	Max Main Elevation	Minimum Pump Elevation	Static Head (feet)	
diameters for: SDR21PVC Friction loss calculations were based on a Constant for inside roughness"C" of: 150													
350	11.00	2	22.00	1.25	4.00	83.00	4.22	3.50	23.91	487.00	400.00	87.00	110.91
350	11.00	3	33.00	1.50	4.56	162.00	4.56	7.39	20.41	487.00	438.50	48.50	68.91
350	11.00	5	55.00	2.00	4.86	208.00	3.97	8.27	13.02	487.00	432.00	55.00	68.02
350	11.00	6	66.00	2.50	3.98	216.00	2.20	4.75	4.75	487.00	455.00	32.00	36.75

PRELIMINARY PRESSURE	SEW	ER	- 1	
	-		-	

C-4.1

Zone Number	Connects to Zone	Accumulated Total of Pumps this Zone	Pipe Size (inches)	Gallons per 100 lineal feet	Length of Zone	Сар
This sprea	dsheet was ca	alculated using pi	pe diameters for: SD	R21PVC		
1.00	2.00	3	1.25	9.15	83.00	
1.00	2.00	2	1.4.2	2.12	00.00	
2.00	3.00	9	1.50	12.07	162.00	
144.66		9 20				