## Section 5.15.8.R. Carports

**General:** Residential Detached Accessory Structure

Size Range: Maximum 600 SF, however, cannot exceed maximum lot coverage based

on principal building type

**Maximum Footprint:** 600 SF

**Height:** No taller than the principal structure or 18' whichever is less.

## **Characteristics:**

No solid walls

- No more than 2 sides made be enclosed with louvered or horizontal panels or siding
- Limited power is allowed
- No internal plumbing
- Placement in rear of lot or at a minimum of 20' behind the front plane of the principal structure
- Columns, Posts and Roof material to be consistent with residential character
- Not allowed on commercial or mixed-use lots
- Only one allowed per lot
- Must have a principal structure to meet requirement

**Section 5.15.5.A Neighborhood Core Historic District** 

Neighborhood Core Building Type Requirements:	Front Build-to Zone	Lot Width Lot Width	Frontage Requirement	Setback (from rear property line)	Side Setback (from side property lines)	Height (in stories)	Maximum Lot Coverage
Main Street Building	10'-20'	50'- 100'	70% - 90%	25'	5'	2-3	<u>80%</u>
Commercial Cottage	10'-15'	50'-75'	40% - 70%	25'	8'	1-1.5	<u>80%</u>
Live-Work Sideyard	10'-15'	50'-65'	50% - 75%	25'	5'	2-2.5	<u>80%</u>
Duplex	10'-15'	55'-70'	N/A	25'	5'	2-3	<u>75%</u>
Triplex	10'-15'	70'- 100'					<u>75%</u>
Mansion Apartment House	10'-25'	60'-80'	N/A	25'	5'	2-2.5	<u>70%</u>
Civic Building	10'-25'	N/A	N/A	N/A	5'	2.5	<u>80%</u>
Carriage House			for placement uirements	5'	5'	1-2	
Additional Building Types	10'-25'	50'- 100'	TBD by UDO Admin.	25'	5'	2-3	<u>80%</u>

Neighborhood Center Building Type Requirements:		Lot Width	Frontage Requirement	Setback (from rear property line)	Side Setback (from side property lines)	Height (in stories)	Maximum Lot Coverage
Main Street Building	10'- 25'	50'- 80'	75% - 90%	25'	8'	2-2.5	<u>80%</u>
Commercial Cottage	10'- 20'	50'- 60'	50% - 70%	25'	8'	1-1.5	<u>80%</u>
Live-Work Sideyard	5'-10'	50'- 60'	40% - 75%	25'	8'	1.5-2.5	<u>80%</u>
Duplex	10'- 15'	55'- 70'	N/A	25'	8'	1.5-2.5	<u>75%</u>
Triplex	10'- 15'	70'- 100'					<u>75%</u>
Mansion Apartment House	10'- 25'	60'- 80'	N/A	25'	10'	2-2.5	<u>70%</u>
Main Street Building	10'- 25'	50'- 80'	75% - 90%	25'	8'	2-2.5	<u>65%</u>
Carriage House			.15.8.F. for and other ments	5'	5'	1-2	<u>65%</u>
Cottage	10'- 15'	50'- 60'	N/A	25'	8'	1-1.5	<u>65%</u>
Medium House	5'-15'	50'- 60'	N/A	25'	8'	1-2	<u>65%</u>
Village House	10'- 15'	50'- 60'	N/A	25'	8'	2-2.5	<u>65%</u>
Sideyard House	10'- 15'	50'- 65'	N/A	25'	8'	2-2.5	<u>65%</u>
Vernacular House	10'- 20'	60'- 80'	N/A	25'	10'	1.5	<u>65%</u>
Civic Building	10'- 25'	N/A	N/A	N/A	8'	2	<u>80%</u>
Additional Building Types	10'- 25'	50'- 100'	TBD by the UDO Admin	25'	8'	1-2.5	<u>80%</u>

Neighborhoo d General Building Type Requirements :	Front Build-to Zone	Lot Width	Frontage Require ment	Setback (from rear property line)	Side Setback (fro m side property lines)	Height (in stories )	Maximu m Lot Coverag e
Carraige House	See Sec. 5.15.8.F. for Placement and other requirements.			5'	5'	1-2	
Live-Work Sideyard	10'-20'	50'-100'	N/A	25'	10'	1-2.5	<u>60%</u>
Commercial Cottage	10'-20	50'-100'	N/A	25'	10'	1-1.5	<u>60%</u>
Bungalow Court	10'-20'	60'-100'	N/A	25'	15'	1-1.5	<u>65%</u>
Cottage	10'-20'	50'-60'	N/A	25'	10'	1-1.5	<u>60%</u>
Medium House	10'-20'	50'-60'	N/A	25'	10'	1-2	<u>60%</u>
Village House	10'-20'	50'-65'	N/A	30'	15'	2-2.5	<u>60%</u>
Sideyard House	10'-15'	50'-65'	N/A	30'	5'	2	<u>60%</u>
Vernacular House	10'-20'	60'-100'	N/A	30'	15'	1.5	<u>60%</u>
Center Hall House	15'-25'	70'-100'	N/A	30'	15'	2-2.5	<u>60%</u>
Civic Building	10'-35'	N/A	N/A	N/A	10'	2	<u>80%</u>
Additional Building Types	10'-20'	50'-100'	N/A	25'	10'	1-2.5	<u>70%</u>

Neighborhoo d Conservation Building Type Requirements :	Front Build- to Zone	Lot Width	Frontage Require ment	Setback (from rear property line)	Side Setback (from side property lines)	Height (in stories )	Maximum Lot Coverage
Carriage House		Sec. 5.15.		5'	5'	1-2	
nouse	•	ement and requiremer		5	5	1-2	
Cottage	10'-20'	50'-60'	N/A	30'	10'	1-1.5	<u>60%</u>
Medium House	10'-20'	50'-70'	N/A	30'	10'	1-2	<u>60%</u>
Village House	10'-20'	50'-70'	N/A	30'	10'	2-2.5	<u>60%</u>
Vernacular House	15'-25'	60'-100'	N/A	30'	10'	1.5	<u>60%</u>
Center Hall House	20'-35'	80'-100'	N/A	30'	15'	2-2.5	<u>60%</u>
Civic Building	15'-40'	N/A	N/A	N/A	10'	1.5	<u>80%</u>
Additional Building Types	10'-35'	50'-100'	N/A	30'	10'	1 - 2.5	<u>70%</u>

Riverfront Edge Building Type Requirements :	Riverfront Build-to Zone	Lot Width	Frontage Requiremen t	Setbac k (from rear propert y line)	Side Setback (from side propert y lines)	Height (in stories )	Maximum Lot Coverage
Carriage House	See Sec. 5.15.8.F. for placement and other requirements	N/A	N/A	5'	10	1-2	
Cottage	≥150' Perpendicular to, and in a horizontal plane from, the OCRM line	≥60'	N/A	20'	10'	1-1.5	<u>50%</u>
Vernacular House	≥150' Perpendicular to, and in a horizontal plane from, the OCRM line	≥75'	N/A	20'	20'	1.5	<u>50%</u>
Center Hall House	≥150' Perpendicular to, and in a horizontal plane from, the OCRM line	≥75'	N/A	20'	20'	2-2.5	<u>50%</u>
River House	≥150' Perpendicular to, and in a horizontal plane from, the OCRM line	≥75'	N/A	20'	20'	1.5-2	<u>50%</u>
Civic Building	15'-50'	≥60'	N/A	N/A	15'	1.5	<u>80%</u>
Additional Building Types	≥150' Perpendicular to, and in a horizontal plane from, the OCRM line	≥60'	N/A	20'	20'	1-2.5	<u>50%</u>