

Schedule										
Symbol	Label	Image	Quantity	Manufacturer	Catalog Number	Description	Number Lamps	Lumens Per Lamp	Light Loss Factor	Wattage
	A		14	Holophane	PTUE3 P60 30K GL3_RFD330000	Taft Utility Gen 3, P60 Performance Package, 3000K, 70 CRI, Type 3 Glass refractor_RFD330000	1	8915	0.9	75
										

Statistics

Description	Symbol	Avg	Max	Min	Max/Min	Avg/Min
OVERALL		0.5 fc	3.9 fc	0.0 fc	N/A	N/A
WALKING TRAIL		0.8 fc	3.8 fc	0.0 fc	N/A	N/A

CLASSIFICATION, TYPE, SPECIFICATION, AND ADDITIONAL ATTRIBUTES MEET UTILITY GRADE REQUIREMENTS FOR ALL LIGHT FIXTURES. ASSOCIATED POLE MOUNTING HEIGHTS, AND POLES. PHOTOMETRIC PLANS ARE SUBJECT TO CHANGE BASED ON PREDICTED AND ACTUAL FIELD INSTALLATION LOCATIONS AND ARE POTENTIALLY AFFECTED VIA OTHER GOVERNING AUTHORITIES IN THE INSTALLATION LOCATIONS. USE OF THIS PHOTOMETRIC PLAN IS SOLELY PERMITTED TO DOMINION ENERGY. LIGHTING SERVICES APPROVED PERSONNEL. USE OF THIS PHOTOMETRIC PLAN MUST BE CONSTRUCTED VIA DOMINION ENERGY - LIGHTING SERVICES APPROVED PERSONNEL. USE OF THIS PHOTOMETRIC PLAN FOR FIELD INSTALLATIONS ARE LIMITED TO DOMINION ENERGY COMPANY CREWS AND COMMON ENERGY CONTRACTORS. ALL DOMINION ENERGY APPROVED LIGHTING PLANS ADHERE TO THE MOST CURRENT NESC RULES AND REGULATIONS AT THE TIME OF THE PROJECT APPROVAL.

