

For NCSA Contract Purchases:

Please send P.O. to Amick & NCSA including: Contract #, Spec #, Contact Info, & Fed. Tax ID # NCSA: kmitman@ncsheriffs.net LINK: NCSA Terms & Conditions

> 26-10-0422 ITEM # 2214

END USER: BLUFFTON
LARRY BECKLER

EQUIPMENT INSTALL TYMCO - WACO, TX

LOCATION:

Description Contract Price

MODEL: TYMCO 435
SIZE: 4 YD
PAINT: WHITE

WARRANTY: TYMCO: 1 YR SWEEPER, 2 YR SKIDS. AUX. ENGINE: SEE MFG. WARRANTY FOR DETAILS.

STANDARD EQUIPMENT INCLUDED

AUXILIARY ENGINE: KUBOTA V2403-CR-TE48 FINAL TIER-4 TURBO CHARGED DIESEL 4 CYL;

148.5 CID; 56 HP @ 2100 RPM; TORQUE 140 FT LB. @ 2100 RPM.

FUEL WATER SEPARATOR

DONALDSON POWERCORE AIR FILTER WITH PRECLEANER.

AUXILIARY ENGINE PROTECTION SYSTEM. DERATE OR SHUTDOWN WHEN ENGINE PROBLEM IS

DETECTED SUCH AS HIGH COOLANT TEMPERATURE OR LOW OIL PRESSURE.

ABRASION PROTECTION PACKAGE. BOLT-IN REPLACEABLE RUBBER OR POLY LINERS TO PROTECT AREAS PRONE TO ABRASION IN SANDY APPLICATIONS. INCLUDES SUCTION INLET LINER, DUST SEPARATOR LINER, BLOWER HOUSING LINER; PICK-UP HEAD SUCTION NOZZLE LINER AND PRESSURE WEAR PADS; HEAVY DUTY PRESSURE AND SUCTION HOSES.

BLUE LOGIC CONTROL SYSTEM. SEE BLUELOGIC BROCHURE FOR COMPLETE DETAILS.
MULTIPLEXED ELECTRICAL SYSTEM INCLUDES HARDWARE AND TYMCO DESIGNED SOFTWARE
THAT INTEGRATES THE IN-CAB CONTROLS TO THE AUXILIARY ENGINE AND ALL SWEEPER
FUNCTIONS, INCLUDING ADDITIONAL SAFETY FEATURES. THE BLUELOGIC CONTROL SYSTEM
PROVIDES SWEEPER AND AUXILIARY ENGINE DATA TO THE OPERATOR THROUGH THE
TOUCHSCREEN DISPLAY AND INTERACTIVE MULTICOLOR SWITCHES.

FEEDBACK INCLUDES HOUR METERS (TRIP AND TOTAL) FOR THE AUXILIARY ENGINE, PICKUP

HEAD, BLOWER, GUTTER BROOMS AND WATER PUMP IF APPLICABLE.

SWEEPER ODOMETER RECORDS CURB MILES SWEPT & SWEEPING HOURS.

SERVICE REMINDERS, CUSTOM REMINDERS, OVERSPEED WARNING, LOW WATER AUDIBLE

ALARM, DUST CONTROL SYSTEM WINTERIZATION GUIDE.

ON-BOARD DIAGNOSTICS (OBD) FOR THE AUXILIARY ENGINE & SWEEPER.

DUST SEPARATOR CLEANOUT PLUG EXTENSION HANDLE.

HOPPER SAFETY PROP.

HOPPER INSPECTION DOOR.

HOPPER DRIP EDGE EXTENSION.

HYDRAULIC SYSTEM FILTER RESTRICTION INDICATOR

HYDRAULIC TANK SIGHT/TEMPERATURE GAUGE

LEFT GUTTER BROOM, FLOODLIGHT, PARABOLIC MIRROR

435 GULLWING LOCKABLE STORAGE COMPARTMENT. A MODULAR DESIGN MULTI-CHAMBER

COMPARTMENT WITH A COMBINED 55 CU.FT. OF PROTECTED STORAGE CAPACITY,

ACCESSIBLE FROM LEFT OR RIGHT HAND SIDE THROUGH LARGE GULL WING DOORS;

AUXILIARY ENGINE AND BLOWER AREA ACCESSED THROUGH SWING AWAY SIDE ACCESS

PANELS.

REAR LOCKABLE STORAGE COMPARTMENTS (2) - $26\,\mathrm{CU}$. FT. TOTAL CAPACITY.

PRESSURE BLEEDER. DEFLECTS HIGH-PRESSURE AIRFLOW OUT, INCREASING SUCTION ACROSS

FRONT OF PICK-UP HEAD.

BACK-UP ALARM

DUO SKIDS. CARBIDE INSERT PICKUP HEAD SKIDS ARE WARRANTED FOR 2 YRS. / 2000 HRS.

REAR BUMPER PADS.

REAR MOUNTED OVAL DESIGN ALTERNATING/FLASHING WARNING LIGHTS (2) LED.

REAR MOUNTED WORKLIGHT (1).

REVERSE PICK-UP HEAD PROTECTION SYSTEM.

RUBBER COATED BLOWER WHEEL.

HOPPER DOOR OPENING DIMENSION 77-1/4"X 70" SCREEN LIFTS WITH DOOR.

OPTIONAL UPGRADES AND ACCESSORIES INCLUDED

AUXILIARY ENGINE IN-CAB AIR FILTER RESTRICTION INDICATOR W/ GAUGE

AUXILIARY HYDRAULIC SYSTEM

GUTTER BROOM; TWIN; LED FLOODLIGHTS & PARABOLIC MIRRORS

GUTTER BROOM TILT ADJUSTER, RIGHT

GUTTER BROOM TILT ADJUSTER, LEFT

ADDITIONAL GUTTER BROOM WATER NOZZLE, RIGHT

ADDITIONAL GUTTER BROOM WATER NOZZLE, LEFT

ADDITIONAL HOPPER WATER NOZZLE

HI/LOW PRESSURE WASH DOWN SYSTEM

HYDRANT WRENCH

SHOP AIR PURGE

DUMP SWITCH IN CAB

HOPPER "UP " ALARM

AUTO SWEEP ASSIST (ASA)

LINEAR ACTUATOR W/GAUGE - PRESSURE BLEEDER

PICK UP HEAD CURTAIN LIFTER

PICK UP HEAD PRESSURE INLET WATER INJECTION SYSTEM

REMOVEABLE FRONT CURTAIN SET

SHKID BUMPER EXTENSION SET (3")

STAINLESS STEEL HOPPER

STAINLESS STEEL AUXILIARY HAND HOSE

STAINLESS STEEL DUST SEPERATOR

CURBVIEW CAMERA SYSTEM: RIGHT SIDE GUTTER BROOM VIEW

PICK UP HEAD CAMERA

AUTOMATED WATER SYSTEM

REMOTE GREASE ZERK - SEPERATOR INNER BEARING

HOPPER VIBRATOR

DEALER SERVICES INCLUDED

FREIGHT TO AMICK EQUIPMENT

BODY PRE-DELIVERY INSPECTION

AECI MOBILE ON-SITE WARRANTY PKG., 12 MO.

ON-SITE TRAINING - PROVIDED BY REQUEST

DELIVERY OPTION INCLUDED:

AECI DELIVERS TO END USER.

COMMENTS:

Pricing Disclaimer: Due to recent tariff announcements, steel prices and foreign components are expected to increase noticably. This may result in retroactive price increases and surcharges on ordered equipment. Amick Equipment will absorb these increases when possible but may pass them along as announced by each of the manufacturer. We appreciate your understanding during this volatile period.

Subtotal:	\$ 235,968.00
Contract Discount - Options / Accessories:	\$ (2,463.00)
Additional Discount:	\$ (6,000.00)
Subtotal:	\$ 227,505.00

Chassis Description

2024 ISUZU NQR

MODEL:

GVWR:	17950 LBS			
ENG & TRAN:	ISUZU DIESEL, 4HK1-TC / AISIN 6-SP A/T - A465			
PAINT:	WHITE			
VIN:	902109			
COMMENTS:	SEE CHASSIS SPECIFICATIONS FOR COMPLETE DETAILS.			
	FIRE EXTINGUISHER			
	HAZARD REFLECTORS			
	LED AMBER STROBES FRONT BUMPER			
	LED AMBER TRAFFIC DIRECTING LIGHT REAR MOUNT	ED		
	PARABOLIC MIRROR 12" (2)			
	BATTERY DISCONNECT			
		Unit Subtotal:	\$	227,505.00
		Tax - Motor Vehicle (SC IMF / NC HUT):	\$	522.50
		Unit Purchase Price:	\$	228,027.50
		Payment Terms	MALINII P. CLIACCI	S DEALERS: NET 15
		Payment Terms:	* C.O.D Discour	
			* Late Fee: 1%	ic / ivaliable
		Completion ETA:	8/15/25 Sched	duled Completion Date
		Note:		on schedule at time of
			quote and are su	ubject to change.
		Chassis Dealers:	Please include fl	oorplan in chassis pricing,
QUOTED BY:	Dave Hull			
DATE:	6/27/2025			
VALID UNTIL:	*Demo Unit, Subject to Sale.*			
ORDER A	CCEPTANCE			
ONDERV	CCE1 1741CE			
SIGNATUR	E		DATE	
	ONS: Prices shown in "additional options available" section are not in nized above, prices do not include local, state or federal taxes.	cluded in the "Total" price and do not include taxes.		

MOTOR VEHICLE TAXES: AECI no longer collects SC "IMF" or NC "Highway Use Tax". Either the chassis dealer or the DMV will collect motor vehicle tax/fees when registering vehicle.

PAYMENT TERMS: Payment is due PRIOR to delivery. When ample credit has been extended to customer, payment is due within 30 Days of invoice.

TITLEWORK / MCO: Allow 5-10 business days after receipt of payment to process Title or Manufacturer's Certificate of Origin (MCO).

QUOTE EXPIRATION: Pricing is honored for 30 days from date quoted, barring extenuating circumstances such as, but not limited to, volatile markets, factory price increases, etc. AECI makes every effort to give as much notice as possible in such instances.

DELIVERY ESTIMATES: ETA's are based on production schedules at the time of quote and are subject to changes in truck or body production schedules as well other factors such as transportation delays, etc.

WEIGHT RESTRICTIONS: Operating overweight equipment can result in fines, damage to equipment or injury to operators. AECI makes every effort to quote equipment meeting local, state & federal weight regulations. Nevertheless, it is up to the end user to familiarize themselves with all applicable weight laws and avoid exceeding legal weight limits, regardless of truck's GVWR.

CHASSIS DEALERS: Please ensure chassis specs meet body manufacturer's minimum requirements, which are supplied upon request. Deviations may result in additional charges, for which the truck

dealer will be responsible.

CHASSIS DEALER PAYMENT TERMS: Payment term begins when truck is delivered to customer or truck dealer for PDI, whichever is first. Payments received later than 15 DAYS are subject to penalty of Prime % APR, calculated on a daily basis. ANY EXCEPTIONS must be agreed to writing prior to order.

COOPERATIVE PURCHASING CONTRACTS: Cooperative purchasing contract such as NCSA, Sourcewell, etc. are a tool which satisfies the competitive bidding requirements for some

municipalities. Amick Equipment (or its Body Manufacturer) are approved vendors on several contracts, authorized to offer awarded equipment according to each contract's terms and conditions. If a contract award included both body and chassis, then that contract clearly satisfies the bidding requirements for both body and chassis. Some of Amick's contracts were awarded for the body portion only. Upon request, Amick may offer a compatible chassis from another qualified contract holder or may offer a non-contract option.. Unless explicitly stated, customers shall not assume that any of the equipment quoted are being offered under a purchasing contract. It is up the purchaser to determine whether purchasing any items - both explicitly listed on the contract or not, are permitted by









GENERAL SPECIFICATIONS

MODEL 435® MID-SIZE REGENERATIVE® AIR SWEEPER DIESEL AUXILIARY ENGINE / DIESEL CABOVER CHASSIS

DriveConstant speed

SWEEPER AUXILIARY ENGINE
Engine Kubota V2403-CR-TE4B FT4, 4 cyl.
Displacement
Power 56 hp (41.7 kW) @ 2100 RPM
Net torque140 lb-ft (190 Nm) @ 2100 RPM
Air cleanerHeavy duty, w/pre-cleaner
Oil filter
CoolingLiquid
Diesel fuel supplied from chassis fuel tank
Fuel tank capacity30 gal (113 L)
Auxiliary engine protection system
Fuel/water separator with separate fuel filter
Fuel filters 10 µm primary, 5 µm secondary

BLOWER, RUBBER COATED

Aluminum alloy, hig	h volume, open face
turbine	
Bearings	(2) Anti-friction
	. Steel w/abrasion resistant,
replaceable liner	
Drive	Heavy duty power band

DUST SEPARATOR, RUBBER LINED

Type	Cyclonic, multipass,
centrifugal separation	
Cylindrical area	20 x 22.5 in
(51 x 57 cm)	
Location	Adjacent to hopper
Particulate removal achiev	ed through 22.5 in
(57 cm) skimmer slot into	o skimmer hood
Inspection/cleanout port	

HOPPER

IIOI I EIX
Capacity (volumetric)4.0 yd3 (3.06 m3)
Capacity (useable)3.1 yd3 (2.37 m3)
ConstructionWelded steel plate
Dump door opening77.25 x 70 in
(196 x 178 cm)
Insection door(1) Right side of hopper
8.5 x 8.5 in (21.5 x 21.5 cm)
Dump methodHydraulic tilt
Dump directionRear
Dump floor angle37°
Dump height 72 in (183 cm)
Dump clearance height154 in (391 cm)
Dump door hydraulically opened/closed
Hopper screen lifts with door for easy cleaning
Abrasion protection package

STORAGE COMPARTMENTS

Rear (2)	.13.3 ft ³	(0.38 r)	n³) (ea.) ca	pacity	/

DICK HD HEAD

PICK-UP READ	
Type	Dual chamber
Width (inside dimension)	78 in (198 cm)
Pick-up head area2	
Suspension 4 spr	
Skids DUO-SKID®	, long life carbide
Suction hose diameter	12 in (30.5 cm)
Pressure hose diameter	12 in (30.5 cm)
Pressure bleeder	Cable operated
Reverse pick-up head system	

GUTTER BROOM, LEFT, Patented

non-reversible hydraulic motor
AdjustmentAdjustable for
down pressure, pattern and wear
Down pressureAutomatic
FlexibilityIntegral
anti-damage "swing away" relief valve
BroomSteel wire vertical
digger 36 in (91 cm)
FloodlightLED
Parabolic mirror

HYDR	RAULIC SYSTEM
	es gutter broom(s), dump door and
pick-ι	up head
Drive	Gear driven from auxiliary engine
Flow ra	ate5 GPM (18.925 LPM)
Reserv	oir13.5 gal (51.1 L) w/80 mesh
suction	on strainer, sight/temperature gauge, oil
coole	r
Filter	10 micron in-line
Hydrau	lic oil Extended life 10W ISO 46
Cooler	Air to oil

DUST CONTROL SYSTEM

١	Vater spray nozzles for dust suppression
ŀ	Pump Electric diaphragm
F	ReservoirPolyethylene, 150 gal (567.7 L)
	ilter80 mesh in-liné
I	ow water shut-offSafety shut-off
	with audible and visual indicator in cab
(Spray nozzlesAt gutter broom(s)
	and inside hopper
_	

Fire hydrant and garden hose connections Hydrant fill hose......20 ft (6 m)

CONTROL SYSTEM

BlueLogic® Control System

Multiplexed electrical system includes hardware and TYMCO designed software that integrates the in-cab controls to the auxiliary engine and all sweeper functions; as well as provides intelligent safety features and on-board diagnostics (OBD) for the auxiliary engine and sweeper through the BlueLogic display.

BlueLogic Display

Pedestal mounted touchscreen display provides sweeper and auxiliary engine data and includes hour meters (trip and total) for the auxiliary engine, gutter broom(s), pick-up head, blower, and water pump; sweeper odometer (records curb miles swept and sweeping hours), service reminders, custom reminders, overspeed warning, low water audible alarm, dust control system winterization guide, and OBD.

Interior Components

Pressure bleeder control, BlueLogic display, auxiliary fuse panel, illuminated control switches: pick-up head, gutter broom(s),

auxiliary engine RPM, dust control water system nozzles, safety lights

Exterior Controls

Dump switch, BlueLogic Control Module (BCM)

SAFETY/WARNING DEVICES

Alternating LED rear flashers (2) Rear view camera system Back-up alarm Hopper safety prop

OPTIONAL EQUIPMENT

Auto Sweep Interrupt (ASI) Auxiliary hand hose 6 in (15 cm) dia. Auxiliary hydraulic system Camera/monitor systems: Additional camera view - pick-up head CurbView camera system COMDEX package Up to 145 gal (549 L) Requires Isuzu 132.5 in wheelbase Gutter broom(s)(right or twin) Gutter broom tilt adjuster(s) (left, right, or twin) Gutter broom variable speed Gutter broom drop-down Requires Isuzu 150 in wheelbase High output water system

Hi/Low washdown system Hopper drain system Hopper deluge system Light bar, cab mounted, LED

Linear actuator - pressure bleeder with gauge Low emissions package (required for South

Coast AQMD Rule 1186) Magnet, front bumper mounted, light duty Pick-up head curtain lifter

Shop air purge, dust control system Sound Reduction Engineering (SRE®) Stainless steel (non-magnetic) options:

Hopper:

Hopper weldment Hopper door Hopper screen

Inspection door Skimmer hood

Suction inlet tube Blower housing

Dust separator

Hopper drain

Hopper inspection door Hopper screen

Auxiliary hand hose hardware

Paint color (other than TYMCO standard white)

Special options are available. Contact your local dealer or TYMCO.

CABOVER CHASSIS AVAILABLE

Isuzu NQR Diesel - 150 in wheelbase (WB) Isuzu NQR Diesel- 132.5 in WB (COMDEX) Isuzu NPR-XD Diesel - 132.5 in WB (COMDEX)

Superior Training from TYMCO

We want you to understand the Regenerative Air System and your TYMCO sweeper completely, so you can get optimal performance from your equipment investment. That's why, for more than twenty-five years, we've offered two-day scheduled training schools at our facility in Waco, Texas. Owners, managers, operators and mechanics get hands-on training and answers to specific questions. Enrollment levels are kept low, so you and your team will get personal attention as well as the opportunity to learn from the experiences of other attendees through the interaction of the class.



When your operators and mechanics are thoroughly trained and knowledgeable about the TYMCO sweeper, you get better performance and a lower cost per operating hour.

- TYMCO offers full two-day schools
- Choose from over 30 schools scheduled per year
- Yearly class schedules and class agendas are available
- Learn through demonstrations on an operational sweeper
- Special schools arranged for large groups
- Register to attend on our web site

Specifically designed for training, our 3500 square foot, temperature controlled facility provides ample space for demonstrations on an operational sweeper and systems components. We also provide daily ground transportation from the hotel to our training facility, and lunch is on us.



Convenient Dealer Service Centers

In over 50 U.S. locations and dozens of others worldwide, you receive on-the-spot parts and service from TYMCO's exclusive network of dealers.

This product is protected by numerous U.S. and Foreign Patents.

Specifications subject to change without notice.











TYMCO REGENERATIVE AIR SWEEPERS are AQMD Rule 1186 Certified PM₁₀-Efficient 1208 - 20M - 01SM © TYMCO, Inc. 2008









THE STATE OF THE ART - FROM THE PEOPLE WHO INVENTED REGENERATIVE AIR SWEEPING!

DESIGNED with both the CONTRACTOR and MUNICIPALITY in MIND, the TYMCO Model 435 gives you . . .

STANDARD FEATURES:

- Large 4.0 cubic yard, heavy duty, steel hopper increases sweeping time.
- 72 inch dump height enables dumping into various size containers.
- Patented centrifugal dust separator keeps the fines and dust inside the hopper without exhausting air back into the atmosphere. There are no filters or baffles to clean or replace.
- Streamlined side panels help reduce noise and swing open for easy access to auxiliary engine.
- Heavy duty Isuzu 17,950 lb. GVW chassis. (Can be equipped with optional dual steering for right curb-side view)
- Front and rear locking storage areas give you a combined 80 cubic foot of protected space.
- Large hydraulically operated dump door allows for easy discharge and cleaning.
- Patented TYMCO gutter broom with floodlight and parabolic mirror.
- Time tested, heavy duty 78 inch inside width / 82 inch outside width, pick-up head.
- Inside the cab, illuminated sweeper controls.
- 150 gallon water capacity.



- Superior Performance
- Maneuverability
- Operability
- Ease of Maintenance
- TYMCO Reliability

All with our proven...

TYMCO REGENERATIVE AIR DESIGN



Extra large door allows for easy dumping



Locking side panels swing away for easy access to auxiliary engine.



Sweeper Control Panel illuminates for easy night vision.

TYMCO Regenerative Air Cleans Deeper