



CUSTOM WOOD SLIDING DOOR

SCALE: 1/2"=1'-0"

#### CUSTOM WOOD SLIDING DOOR GENERAL NOTES:

**QUALITY ASSURANCE:** ALL WOODWORK TO CONFORM TO THE "QUALITY STANDARDS" OF THE ARCHITECTURAL WOODWORK INSTITUTE (AWI) FOR "PREMIUM GRADE" CONSTRUCTION.

**DIMENSIONS:** GENERAL CONTRACTOR TO VERIFY ALL DIMENSIONS IN FIELD PRIOR TO SHOP DRAWINGS TO COORDINATE WITH EXISTING FIELD CONDITIONS.

**SHOP DRAWINGS:** SUBMIT SHOP DRAWINGS FOR ARCHITECT'S REVIEW PRIOR TO STARTING FABRICATION. PROVIDE EITHER AUTOCAD FILES OR 2 PRINTED SETS OF DRAWINGS FOR REVIEW.

**FRAME AND DOOR MATERIAL:** DOORS AND FRAMES TO BE PAINT GRADE ROT AND INSECT RESISTANT WOOD (FINAL SPECIES TO BE DETERMINED DURING SHOP DRAWINGS).

**FRAME THICKNESS:** FRAMES TO BE DOUBLE RABBETED PAINT GRADE ROT AND INSECT RESISTANT WOOD (FINAL SPECIES TO BE DETERMINED DURING SHOP DRAWINGS) SET UP FOR SCREEN/STORM DOORS.

**DOOR THICKNESS:** DOOR TO BE 2 1/4" THICK.

**STILE AND RAIL CONSTRUCTION:** ALL DOOR STILES AND RAILS TO BE FABRICATED WITH STAYED LUMBER CORE AND THICK FACE VENEERS. GRAIN DIRECTION TO FLOW WITH THE LONGEST DIMENSION OF THE STILE AND RAIL. EXPOSED EDGES TO BE CLEAR PAINT GRADE ROT AND INSECT RESISTANT WOOD (FINAL SPECIES TO BE DETERMINED DURING SHOP DRAWINGS).

**STILE DETAILS:** MANUFACTURER TO SUBMIT STOCK STILE PROFILE DETAILS FOR ARCHITECT'S SELECTION.

**PANEL DETAILS:** MANUFACTURER TO SUBMIT STOCK PANEL PROFILE DETAILS FOR ARCHITECT'S SELECTION.

**THRESHOLD:** 1 3/4" THICK CLEAR SAPELE WITH EXTENDED HORNS

**GLAZING:** PROVIDE INSULATED DUAL PANE LOW-E ARGON-FILLED.

**WEATHER STRIPPING:** MANUFACTURER TO PROVIDE STANDARD WEATHER STRIPPING OPTIONS FOR REVIEW.

**HARDWARE:** HARDWARE TO BE SELECTED BY OWNER.

**SCREENS:** CONCEALED ROLL SCREEN

ANDREOZZI ARCHITECTURE

