

STORMWATER MANAGEMENT REPORT

LONGFIELD ESTATES

AP 103 LOT 2 & 14
1200 & 1202 HOPE STREET
BRISTOL, RI

JUNE, 2022

Revised: December 9, 2022

Prepared for:

MI 1200 HOPE ST., LLC.
133 OLD TOWER HILL ROAD, SUITE 1
WAKEFIELD, RI 02879

Prepared by:

Land Development Engineering & Consulting, LLC
207 High Point Ave., Unit 6
Portsmouth, RI 02871



A handwritten signature in cursive script, appearing to read "Michael E. Russell", written over the bottom of the professional seal.



207 High Point Avenue, Unit #6
Portsmouth, RI 02871
T: 401-354-2050 | F: 401-369-9775
EMAIL: mrussell@sde-ldec.com

TABLE OF CONTENTS

	<u>Pages</u>
INTRODUCTION	3
EXISTING CONDITIONS	3
PROPOSED CONDITIONS	3
SITE SOIL & GROUNDWATER CONDITIONS	4
METHODOLOGY	4
DRAINAGE SYSTEM MODEL	4-5
STORMWATER TREATMENT	5
ANALYSIS DATA	5

APPENDICES

- Appendix 1 - Pre-Development Analysis Output
- Post-Development Analysis Output
- Appendix 2 - Stormwater Quality Calculations
- Soil Logs
- Appendix 3 - Stormwater Management Checklist
- Mounding Analysis

FIGURES

Pre-Development Watershed Plan &
Post-Development Watershed Plan

- Figure 2 - Site Locus Plan
- Figure 3 - Soil Survey Map



207 High Point Avenue, Unit #6
Portsmouth, RI 02871
T: 401-354-2050 | F: 401-369-9775
EMAIL: mrussell@sde-ldec.com

INTRODUCTION

This report was prepared to address the Stormwater Management System (SMS) for the Residential Development on AP 103 Lot 2 & 14, 1200 & 1202 Hope Street in Bristol. The project proposes construct four new residential buildings that will have a total of 8 residential units between them. The existing residential dwelling (Longfield) shall be renovated and will provide an additional 2 residential units. The Development will create 10 parking spaces with associated landscaping, utilities & stormwater management system. This report will outline and summarize the current SMS as well the improvements of the proposed development. Said improvements are intended to control peak runoff & volume rates for the added impervious area(s). Additionally, the proposed SMS will provide, at minimum, the water quality & stormwater recharge volumes as required. The SMS as proposed will comply with the Town of Bristol's & State of Rhode Island's Stormwater Management Policy (2018).

EXISTING CONDITIONS (SUMMARY)

The subject property is approximately 1.76 acres in area and fronts along Hope Street (Route 114). The existing ground cover consists mainly of a lawn with brush/woods along the edges of the property. There is also an existing dwelling and a gravel driveway for the dwelling. The site slopes generally towards the South/Southeast towards an existing wetland. The elevation change across the site is approximately 8 feet. Currently, most of the Runoff from the site sheet flows across the site to an isolated wetland in the southeastern corner of the lot. Some runoff in the Northwestern edge of the lot flows Southwest towards Hope Street (Route 114). The summary of the Pre-Development Analysis is located in Appendix 1 of this report.

PROPOSED CONDITIONS (SUMMARY)

The project proposes construct four new residential buildings that will have a total of 8 residential units between them. The existing residential dwelling (Longfield) shall be renovated and will provide an additional 2 residential units. The Development will create 10 parking spaces with associated landscaping, utilities & stormwater management system. Site grading will create the cuts & fills throughout the project limits to create the desired site layout and function and will maintain pre-development runoff patterns towards the Southeastern portion of the site. A stormwater collection system will be incorporated into the newly designed parking area to collect runoff from impervious surfaces and landscaped areas within the limit of disturbance. This system consists of dry swales, sediment forebays, lined bio-retention basins, and a dry extended detention basin. The forebays will provide pre-treatment for the bio-retention basins. The system will accommodate a 100-year storm event, handle the water quality volume (WQv) and provide for total suspended solids (TSS) removal. This overall system is designed to accommodate, at minimum, the water quality volume (WQv) required for new development projects. Low impact development practices (LID) will be employed to the maximum extent practicable. Summary of the Post-Development Conditions Analysis is located in Appendix 1 of this report.

SITE SOIL & GROUNDWATER CONDITIONS

The underlying watershed soils within the developed area consist of the Pittstown silt loam Hydrologic Group C). A soil evaluation and groundwater determination was performed in



207 High Point Avenue, Unit #6
Portsmouth, RI 02871
T: 401-354-2050 | F: 401-369-9775
EMAIL: mrussell@sde-ldec.com

December 2018. Soil textures below the fill consisted primarily of a silt loam mixture with groundwater elevation approximately 12” to 32” feet below original grade.

METHODOLOGY

HydroCad® Stormwater Modeling System was used to quantify stormwater runoff generated by WQv, 1-year, 2-year, 10-year and 25-year design storms in pre and post development conditions. The calculations were performed using “Dynamic Storage-Indication” to also analyze the impact of the pipe size, material and slope selection in upstream structures. The HydroCad® program utilizes Natural Resource Conservation Service (NRCS) techniques (TR-20) to predict stormwater runoff for given design storms. The calculations performed by HydroCad® are based on the NRCS model return frequency Type III distribution and a user specified design storms. The calculation is also performed using the simple dynamic method which utilizes *Rawls Rate* for infiltration based on soil texture.

The analysis is performed by modeling the drainage area as subcatchments and ponds. A subcatchment is an area that produces runoff and drains into a pond. A pond can be a natural depression, wetland, or manmade structure that detains or retains stormwater runoff. The drainage network pipe design adequacy is evaluated by integrating it in the HydroCad® pond model for drainage structures. The pipes are modeled as the pond outlet-culvert type. Manning’s Equation and/or Hazen-Williams hydraulic equations were also utilized to determine the required pipe sizes as well as minimum and maximum pipe slopes.

DRAINAGE SYSTEM MODEL

The proposed development is analyzed by creating an existing condition or pre-development model and a full build-out or post-development model. The models were created to compare the existing and post-development runoff to the abutting properties and existing SMS. The post-development analysis results are also utilized to adequately size the proposed practices. Analysis within the site was performed using WQv, 1, 2, 10 and 25-year design storm projections. All excess stormwater runoff captured on site will be treated and retained/recharged on site. On site post-development runoff rates flowing overland toward abutting properties will not exceed pre-development runoff rates up to the 25-year event.

The pre-development HydroCad® model within the site consists of two subcatchments, One subcatchment corresponds to the Northwestern portion of the lot that flows southwest towards Hope Street (Route 114). The other subcatchment encompasses the rest of the lot that flows Southeasterly towards the isolated wetland in the corner of the lot. This was created to determine the existing stormwater runoff originating from the site flowing to Hope Street and the to the existing wetland.

Post-development subcatchment models were created for the site. Subcatchment models represent the drainage areas to each of the proposed reaches, drainage structures, or storage & treatment areas. Each of these areas provides elements of treatment, storage, and infiltration in order to effectively mitigate flows to the Point of Analysis in each analyzed storm event. See Post-Development output in Appendix B and summary at the end of this narrative.



207 High Point Avenue, Unit #6
Portsmouth, RI 02871
T: 401-354-2050 | F: 401-369-9775
EMAIL: mrussell@sde-ldec.com

The majority of the paved & landscaped areas for the developed area discharge into a dry swale or sediment forebay before flowing into a bio-retention basin and a detention basin.

STORMWATER TREATMENT

Stormwater runoff will be treated through the use of Best Management Practices (BMP's). The BMP's used within the proposed development include dry-swales, forebays, bio-retention basins, underground storage systems, underground infiltration systems and a dry extended detention basin. These BMP's will aid in the removal of pollutants within the stormwater runoff as well as provide recharge to the groundwater aquifer.

This system will provide pollutant removal and treatment as required for this development.

ANALYSIS DATA

The following information was used in performing the calculations for the drainage system.



RUNOFF SUMMARY AT ANALYSIS POINTS		
Cover Description		
Cover Type	Hydrologic condition	Curve Number (Class: C)
Landscaping, Lawns	Good	74
Woods	Good	70
Gravel	Good	89
Brush	Good	65
Buildings	-	98
Pavement	-	98
Brick Walkways	-	98

Rainfall Data (Type III - 24 Hour Storm Duration*)

Storm Event	Rainfall
WQv	1.2 inches
1 - Year	2.8 inches
2 - Year	3.3 inches
10 - Year	4.9 inches
25 - Year	6.1 inches
100 - Year	8.6 inches



207 High Point Avenue, Unit #6
Portsmouth, RI 02871
T: 401-354-2050 | F: 401-369-9775
EMAIL: mrussell@sde-ldec.com



22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Area Listing (selected nodes)

Area (sq-ft)	CN	Description (subcatchment-numbers)
64,639	74	>75% Grass cover, Good, HSG C (e1S, e2S)
7,182	65	Brush, Good, HSG C (e1S, e2S)
2,708	96	Gravel surface, HSG C (e1S, e2S)
1,919	98	Paved parking, HSG C (e2S)
2,892	98	Roofs, HSG C (e2S)
79,340	75	TOTAL AREA

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 1-yr Rainfall=2.80"

Printed 6/20/2022

Page 3

Time span=0.00-72.00 hrs, dt=0.04 hrs, 1801 points

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv.

Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

Subcatchment e1S: Pre-Development - Western Portion of Lot

Runoff Area=9,269 sf 0.00% Impervious Runoff Depth=0.88"
Flow Length=163' Tc=6.8 min CN=76/0 Runoff=0.20 cfs 682 cf

Subcatchment e2S: Pre-Development - Eastern Portion of Lot

Runoff Area=70,071 sf 6.87% Impervious Runoff Depth=0.91"
Flow Length=366' Tc=18.3 min CN=74/98 Runoff=1.08 cfs 5,293 cf

Pond eA1: Analysis Point - Pre Dev Catch Basin in Hope St.

Inflow=0.20 cfs 682 cf
Primary=0.20 cfs 682 cf

Pond eA2: Analysis Point - Pre Dev Flow Towards Wetland

Inflow=1.08 cfs 5,293 cf
Primary=1.08 cfs 5,293 cf

Total Runoff Area = 79,340 sf Runoff Volume = 5,975 cf Average Runoff Depth = 0.90"
93.94% Pervious = 74,529 sf 6.06% Impervious = 4,811 sf

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 1-yr Rainfall=2.80"

Printed 6/20/2022

Page 4

Summary for Subcatchment e1S: Pre-Development - Western Portion of Lot

Runoff = 0.20 cfs @ 12.11 hrs, Volume= 682 cf, Depth= 0.88"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 1-yr Rainfall=2.80"

Area (sf)		CN	Description		
825	65	Brush, Good, HSG C			
1,021	96	Gravel surface, HSG C			
7,423	74	>75% Grass cover, Good, HSG C			
9,269	76	Weighted Average			
9,269	76	100.00% Pervious Area			
Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.8	20	0.0600	0.09		Sheet Flow, AB Grass: Bermuda n= 0.410 P2= 3.30"
0.2	14	0.0050	1.14		Shallow Concentrated Flow, BC Unpaved Kv= 16.1 fps
0.3	33	0.0180	2.16		Shallow Concentrated Flow, CD Unpaved Kv= 16.1 fps
2.5	96	0.0160	0.63		Shallow Concentrated Flow, DE Woodland Kv= 5.0 fps

Summary for Subcatchment e2S: Pre-Development - Eastern Portion of Lot

Runoff = 1.08 cfs @ 12.27 hrs, Volume= 5,293 cf, Depth= 0.91"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 1-yr Rainfall=2.80"

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 1-yr Rainfall=2.80"

Printed 6/20/2022

Page 5

Area (sf)		CN	Description
6,357	65	Brush, Good, HSG C	
1,687	96	Gravel surface, HSG C	
2,892	98	Roofs, HSG C	
57,216	74	>75% Grass cover, Good, HSG C	
1,919	98	Paved parking, HSG C	
70,071	75	Weighted Average	
65,260	74	93.13% Pervious Area	
4,811	98	6.87% Impervious Area	

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.2	50	0.0260	0.07		Sheet Flow, AB Grass: Bermuda n= 0.410 P2= 3.30"
3.2	100	0.0110	0.52		Shallow Concentrated Flow, BC Woodland Kv= 5.0 fps
3.9	216	0.0340	0.92		Shallow Concentrated Flow, CD Woodland Kv= 5.0 fps

Summary for Pond eA1: Analysis Point - Pre Dev Catch Basin in Hope St.

Inflow Area = 9,269 sf, 0.00% Impervious, Inflow Depth = 0.88" for 1-yr event
Inflow = 0.20 cfs @ 12.11 hrs, Volume= 682 cf
Primary = 0.20 cfs @ 12.11 hrs, Volume= 682 cf, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

Summary for Pond eA2: Analysis Point - Pre Dev Flow Towards Wetland

Inflow Area = 70,071 sf, 6.87% Impervious, Inflow Depth = 0.91" for 1-yr event
Inflow = 1.08 cfs @ 12.27 hrs, Volume= 5,293 cf
Primary = 1.08 cfs @ 12.27 hrs, Volume= 5,293 cf, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.30"

Printed 6/20/2022

Page 6

Time span=0.00-72.00 hrs, dt=0.04 hrs, 1801 points

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv.

Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

Subcatchment e1S: Pre-Development - Western Portion of Lot

Runoff Area=9,269 sf 0.00% Impervious Runoff Depth=1.22"
Flow Length=163' Tc=6.8 min CN=76/0 Runoff=0.28 cfs 944 cf

Subcatchment e2S: Pre-Development - Eastern Portion of Lot

Runoff Area=70,071 sf 6.87% Impervious Runoff Depth=1.24"
Flow Length=366' Tc=18.3 min CN=74/98 Runoff=1.53 cfs 7,233 cf

Pond eA1: Analysis Point - Pre Dev Catch Basin in Hope St.

Inflow=0.28 cfs 944 cf
Primary=0.28 cfs 944 cf

Pond eA2: Analysis Point - Pre Dev Flow Towards Wetland

Inflow=1.53 cfs 7,233 cf
Primary=1.53 cfs 7,233 cf

Total Runoff Area = 79,340 sf Runoff Volume = 8,177 cf Average Runoff Depth = 1.24"
93.94% Pervious = 74,529 sf 6.06% Impervious = 4,811 sf

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.30"

Printed 6/20/2022

Page 7

Summary for Subcatchment e1S: Pre-Development - Western Portion of Lot

Runoff = 0.28 cfs @ 12.11 hrs, Volume= 944 cf, Depth= 1.22"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 2-yr Rainfall=3.30"

Area (sf)		CN	Description		
825	65	Brush, Good, HSG C			
1,021	96	Gravel surface, HSG C			
7,423	74	>75% Grass cover, Good, HSG C			
9,269	76	Weighted Average			
9,269	76	100.00% Pervious Area			
Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.8	20	0.0600	0.09		Sheet Flow, AB Grass: Bermuda n= 0.410 P2= 3.30"
0.2	14	0.0050	1.14		Shallow Concentrated Flow, BC Unpaved Kv= 16.1 fps
0.3	33	0.0180	2.16		Shallow Concentrated Flow, CD Unpaved Kv= 16.1 fps
2.5	96	0.0160	0.63		Shallow Concentrated Flow, DE Woodland Kv= 5.0 fps

Summary for Subcatchment e2S: Pre-Development - Eastern Portion of Lot

Runoff = 1.53 cfs @ 12.27 hrs, Volume= 7,233 cf, Depth= 1.24"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 2-yr Rainfall=3.30"

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.30"

Printed 6/20/2022

Page 8

Area (sf)		CN	Description
6,357	65	Brush, Good, HSG C	
1,687	96	Gravel surface, HSG C	
2,892	98	Roofs, HSG C	
57,216	74	>75% Grass cover, Good, HSG C	
1,919	98	Paved parking, HSG C	
70,071	75	Weighted Average	
65,260	74	93.13% Pervious Area	
4,811	98	6.87% Impervious Area	

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.2	50	0.0260	0.07		Sheet Flow, AB Grass: Bermuda n= 0.410 P2= 3.30"
3.2	100	0.0110	0.52		Shallow Concentrated Flow, BC Woodland Kv= 5.0 fps
3.9	216	0.0340	0.92		Shallow Concentrated Flow, CD Woodland Kv= 5.0 fps

Summary for Pond eA1: Analysis Point - Pre Dev Catch Basin in Hope St.

Inflow Area = 9,269 sf, 0.00% Impervious, Inflow Depth = 1.22" for 2-yr event
Inflow = 0.28 cfs @ 12.11 hrs, Volume= 944 cf
Primary = 0.28 cfs @ 12.11 hrs, Volume= 944 cf, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

Summary for Pond eA2: Analysis Point - Pre Dev Flow Towards Wetland

Inflow Area = 70,071 sf, 6.87% Impervious, Inflow Depth = 1.24" for 2-yr event
Inflow = 1.53 cfs @ 12.27 hrs, Volume= 7,233 cf
Primary = 1.53 cfs @ 12.27 hrs, Volume= 7,233 cf, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=4.90"

Printed 6/20/2022

Page 9

Time span=0.00-72.00 hrs, dt=0.04 hrs, 1801 points

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv.

Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

Subcatchment e1S: Pre-Development - Western Portion of Lot

Runoff Area=9,269 sf 0.00% Impervious Runoff Depth=2.45"
Flow Length=163' Tc=6.8 min CN=76/0 Runoff=0.58 cfs 1,895 cf

Subcatchment e2S: Pre-Development - Eastern Portion of Lot

Runoff Area=70,071 sf 6.87% Impervious Runoff Depth=2.45"
Flow Length=366' Tc=18.3 min CN=74/98 Runoff=3.15 cfs 14,295 cf

Pond eA1: Analysis Point - Pre Dev Catch Basin in Hope St.

Inflow=0.58 cfs 1,895 cf
Primary=0.58 cfs 1,895 cf

Pond eA2: Analysis Point - Pre Dev Flow Towards Wetland

Inflow=3.15 cfs 14,295 cf
Primary=3.15 cfs 14,295 cf

Total Runoff Area = 79,340 sf Runoff Volume = 16,190 cf Average Runoff Depth = 2.45"
93.94% Pervious = 74,529 sf 6.06% Impervious = 4,811 sf

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=4.90"

Printed 6/20/2022

Page 10

Summary for Subcatchment e1S: Pre-Development - Western Portion of Lot

Runoff = 0.58 cfs @ 12.10 hrs, Volume= 1,895 cf, Depth= 2.45"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 10-yr Rainfall=4.90"

Area (sf)		CN	Description		
825	65	Brush, Good, HSG C			
1,021	96	Gravel surface, HSG C			
7,423	74	>75% Grass cover, Good, HSG C			
9,269	76	Weighted Average			
9,269	76	100.00% Pervious Area			
Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.8	20	0.0600	0.09		Sheet Flow, AB Grass: Bermuda n= 0.410 P2= 3.30"
0.2	14	0.0050	1.14		Shallow Concentrated Flow, BC Unpaved Kv= 16.1 fps
0.3	33	0.0180	2.16		Shallow Concentrated Flow, CD Unpaved Kv= 16.1 fps
2.5	96	0.0160	0.63		Shallow Concentrated Flow, DE Woodland Kv= 5.0 fps

Summary for Subcatchment e2S: Pre-Development - Eastern Portion of Lot

Runoff = 3.15 cfs @ 12.26 hrs, Volume= 14,295 cf, Depth= 2.45"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 10-yr Rainfall=4.90"

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=4.90"

Printed 6/20/2022

Page 11

Area (sf)		CN	Description
6,357	65	Brush, Good, HSG C	
1,687	96	Gravel surface, HSG C	
2,892	98	Roofs, HSG C	
57,216	74	>75% Grass cover, Good, HSG C	
1,919	98	Paved parking, HSG C	
70,071	75	Weighted Average	
65,260	74	93.13% Pervious Area	
4,811	98	6.87% Impervious Area	

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.2	50	0.0260	0.07		Sheet Flow, AB Grass: Bermuda n= 0.410 P2= 3.30"
3.2	100	0.0110	0.52		Shallow Concentrated Flow, BC Woodland Kv= 5.0 fps
3.9	216	0.0340	0.92		Shallow Concentrated Flow, CD Woodland Kv= 5.0 fps

Summary for Pond eA1: Analysis Point - Pre Dev Catch Basin in Hope St.

Inflow Area = 9,269 sf, 0.00% Impervious, Inflow Depth = 2.45" for 10-yr event
Inflow = 0.58 cfs @ 12.10 hrs, Volume= 1,895 cf
Primary = 0.58 cfs @ 12.10 hrs, Volume= 1,895 cf, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

Summary for Pond eA2: Analysis Point - Pre Dev Flow Towards Wetland

Inflow Area = 70,071 sf, 6.87% Impervious, Inflow Depth = 2.45" for 10-yr event
Inflow = 3.15 cfs @ 12.26 hrs, Volume= 14,295 cf
Primary = 3.15 cfs @ 12.26 hrs, Volume= 14,295 cf, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.10"

Printed 6/20/2022

Page 12

Time span=0.00-72.00 hrs, dt=0.04 hrs, 1801 points

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv.

Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

Subcatchment e1S: Pre-Development - Western Portion of Lot

Runoff Area=9,269 sf 0.00% Impervious Runoff Depth=3.47"
Flow Length=163' Tc=6.8 min CN=76/0 Runoff=0.83 cfs 2,678 cf

Subcatchment e2S: Pre-Development - Eastern Portion of Lot

Runoff Area=70,071 sf 6.87% Impervious Runoff Depth=3.45"
Flow Length=366' Tc=18.3 min CN=74/98 Runoff=4.47 cfs 20,129 cf

Pond eA1: Analysis Point - Pre Dev Catch Basin in Hope St.

Inflow=0.83 cfs 2,678 cf
Primary=0.83 cfs 2,678 cf

Pond eA2: Analysis Point - Pre Dev Flow Towards Wetland

Inflow=4.47 cfs 20,129 cf
Primary=4.47 cfs 20,129 cf

Total Runoff Area = 79,340 sf Runoff Volume = 22,806 cf Average Runoff Depth = 3.45"
93.94% Pervious = 74,529 sf 6.06% Impervious = 4,811 sf

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.10"

Printed 6/20/2022

Page 13

Summary for Subcatchment e1S: Pre-Development - Western Portion of Lot

Runoff = 0.83 cfs @ 12.10 hrs, Volume= 2,678 cf, Depth= 3.47"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 25-yr Rainfall=6.10"

Area (sf)		CN	Description		
825	65	Brush, Good, HSG C			
1,021	96	Gravel surface, HSG C			
7,423	74	>75% Grass cover, Good, HSG C			
9,269	76	Weighted Average			
9,269	76	100.00% Pervious Area			
Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.8	20	0.0600	0.09		Sheet Flow, AB Grass: Bermuda n= 0.410 P2= 3.30"
0.2	14	0.0050	1.14		Shallow Concentrated Flow, BC Unpaved Kv= 16.1 fps
0.3	33	0.0180	2.16		Shallow Concentrated Flow, CD Unpaved Kv= 16.1 fps
2.5	96	0.0160	0.63		Shallow Concentrated Flow, DE Woodland Kv= 5.0 fps

Summary for Subcatchment e2S: Pre-Development - Eastern Portion of Lot

Runoff = 4.47 cfs @ 12.25 hrs, Volume= 20,129 cf, Depth= 3.45"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 25-yr Rainfall=6.10"

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.10"

Printed 6/20/2022

Page 14

Area (sf)		CN	Description		
6,357	65	Brush, Good, HSG C			
1,687	96	Gravel surface, HSG C			
2,892	98	Roofs, HSG C			
57,216	74	>75% Grass cover, Good, HSG C			
1,919	98	Paved parking, HSG C			
70,071	75	Weighted Average			
65,260	74	93.13% Pervious Area			
4,811	98	6.87% Impervious Area			
Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.2	50	0.0260	0.07		Sheet Flow, AB Grass: Bermuda n= 0.410 P2= 3.30"
3.2	100	0.0110	0.52		Shallow Concentrated Flow, BC Woodland Kv= 5.0 fps
3.9	216	0.0340	0.92		Shallow Concentrated Flow, CD Woodland Kv= 5.0 fps

Summary for Pond eA1: Analysis Point - Pre Dev Catch Basin in Hope St.

Inflow Area = 9,269 sf, 0.00% Impervious, Inflow Depth = 3.47" for 25-yr event
Inflow = 0.83 cfs @ 12.10 hrs, Volume= 2,678 cf
Primary = 0.83 cfs @ 12.10 hrs, Volume= 2,678 cf, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

Summary for Pond eA2: Analysis Point - Pre Dev Flow Towards Wetland

Inflow Area = 70,071 sf, 6.87% Impervious, Inflow Depth = 3.45" for 25-yr event
Inflow = 4.47 cfs @ 12.25 hrs, Volume= 20,129 cf
Primary = 4.47 cfs @ 12.25 hrs, Volume= 20,129 cf, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=8.60"

Printed 6/20/2022

Page 15

Time span=0.00-72.00 hrs, dt=0.04 hrs, 1801 points

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv.

Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

Subcatchment e1S: Pre-Development - Western Portion of Lot

Runoff Area=9,269 sf 0.00% Impervious Runoff Depth=5.71"
Flow Length=163' Tc=6.8 min CN=76/0 Runoff=1.36 cfs 4,408 cf

Subcatchment e2S: Pre-Development - Eastern Portion of Lot

Runoff Area=70,071 sf 6.87% Impervious Runoff Depth=5.66"
Flow Length=366' Tc=18.3 min CN=74/98 Runoff=7.34 cfs 33,076 cf

Pond eA1: Analysis Point - Pre Dev Catch Basin in Hope St.

Inflow=1.36 cfs 4,408 cf
Primary=1.36 cfs 4,408 cf

Pond eA2: Analysis Point - Pre Dev Flow Towards Wetland

Inflow=7.34 cfs 33,076 cf
Primary=7.34 cfs 33,076 cf

Total Runoff Area = 79,340 sf Runoff Volume = 37,484 cf Average Runoff Depth = 5.67"
93.94% Pervious = 74,529 sf 6.06% Impervious = 4,811 sf

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=8.60"

Printed 6/20/2022

Page 16

Summary for Subcatchment e1S: Pre-Development - Western Portion of Lot

Runoff = 1.36 cfs @ 12.10 hrs, Volume= 4,408 cf, Depth= 5.71"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 100-yr Rainfall=8.60"

Area (sf)		CN	Description		
825	65	Brush, Good, HSG C			
1,021	96	Gravel surface, HSG C			
7,423	74	>75% Grass cover, Good, HSG C			
9,269	76	Weighted Average			
9,269	76	100.00% Pervious Area			
Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.8	20	0.0600	0.09		Sheet Flow, AB Grass: Bermuda n= 0.410 P2= 3.30"
0.2	14	0.0050	1.14		Shallow Concentrated Flow, BC Unpaved Kv= 16.1 fps
0.3	33	0.0180	2.16		Shallow Concentrated Flow, CD Unpaved Kv= 16.1 fps
2.5	96	0.0160	0.63		Shallow Concentrated Flow, DE Woodland Kv= 5.0 fps

Summary for Subcatchment e2S: Pre-Development - Eastern Portion of Lot

Runoff = 7.34 cfs @ 12.25 hrs, Volume= 33,076 cf, Depth= 5.66"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 100-yr Rainfall=8.60"

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=8.60"

Printed 6/20/2022

Page 17

Area (sf)		CN	Description		
6,357	65	Brush, Good, HSG C			
1,687	96	Gravel surface, HSG C			
2,892	98	Roofs, HSG C			
57,216	74	>75% Grass cover, Good, HSG C			
1,919	98	Paved parking, HSG C			
70,071	75	Weighted Average			
65,260	74	93.13% Pervious Area			
4,811	98	6.87% Impervious Area			
Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.2	50	0.0260	0.07		Sheet Flow, AB Grass: Bermuda n= 0.410 P2= 3.30"
3.2	100	0.0110	0.52		Shallow Concentrated Flow, BC Woodland Kv= 5.0 fps
3.9	216	0.0340	0.92		Shallow Concentrated Flow, CD Woodland Kv= 5.0 fps

Summary for Pond eA1: Analysis Point - Pre Dev Catch Basin in Hope St.

Inflow Area = 9,269 sf, 0.00% Impervious, Inflow Depth = 5.71" for 100-yr event
Inflow = 1.36 cfs @ 12.10 hrs, Volume= 4,408 cf
Primary = 1.36 cfs @ 12.10 hrs, Volume= 4,408 cf, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

Summary for Pond eA2: Analysis Point - Pre Dev Flow Towards Wetland

Inflow Area = 70,071 sf, 6.87% Impervious, Inflow Depth = 5.66" for 100-yr event
Inflow = 7.34 cfs @ 12.25 hrs, Volume= 33,076 cf
Primary = 7.34 cfs @ 12.25 hrs, Volume= 33,076 cf, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr WQv Rainfall=1.20"

Printed 6/20/2022

Page 18

Time span=0.00-72.00 hrs, dt=0.04 hrs, 1801 points

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv.

Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

Subcatchment e1S: Pre-Development - Western Portion of Lot

Runoff Area=9,269 sf 0.00% Impervious Runoff Depth=0.09"
Flow Length=163' Tc=6.8 min CN=76/0 Runoff=0.01 cfs 67 cf

Subcatchment e2S: Pre-Development - Eastern Portion of Lot

Runoff Area=70,071 sf 6.87% Impervious Runoff Depth=0.13"
Flow Length=366' Tc=18.3 min CN=74/98 Runoff=0.09 cfs 730 cf

Pond eA1: Analysis Point - Pre Dev Catch Basin in Hope St.

Inflow=0.01 cfs 67 cf
Primary=0.01 cfs 67 cf

Pond eA2: Analysis Point - Pre Dev Flow Towards Wetland

Inflow=0.09 cfs 730 cf
Primary=0.09 cfs 730 cf

Total Runoff Area = 79,340 sf Runoff Volume = 797 cf Average Runoff Depth = 0.12"
93.94% Pervious = 74,529 sf 6.06% Impervious = 4,811 sf

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr WQv Rainfall=1.20"

Printed 6/20/2022

Page 19

Summary for Subcatchment e1S: Pre-Development - Western Portion of Lot

Runoff = 0.01 cfs @ 12.36 hrs, Volume= 67 cf, Depth= 0.09"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr WQv Rainfall=1.20"

Area (sf)	CN	Description		
825	65	Brush, Good, HSG C		
1,021	96	Gravel surface, HSG C		
7,423	74	>75% Grass cover, Good, HSG C		
9,269	76	Weighted Average		
9,269	76	100.00% Pervious Area		
Tc (min)	Length (feet)	Slope (ft/ft) Velocity (ft/sec) Capacity (cfs) Description		
3.8	20	0.0600	0.09	Sheet Flow, AB Grass: Bermuda n= 0.410 P2= 3.30"
0.2	14	0.0050	1.14	Shallow Concentrated Flow, BC Unpaved Kv= 16.1 fps
0.3	33	0.0180	2.16	Shallow Concentrated Flow, CD Unpaved Kv= 16.1 fps
2.5	96	0.0160	0.63	Shallow Concentrated Flow, DE Woodland Kv= 5.0 fps

Summary for Subcatchment e2S: Pre-Development - Eastern Portion of Lot

Runoff = 0.09 cfs @ 12.25 hrs, Volume= 730 cf, Depth= 0.13"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr WQv Rainfall=1.20"

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr WQv Rainfall=1.20"

Printed 6/20/2022

Page 20

Area (sf)					CN	Description
6,357	65	Brush, Good, HSG C				
1,687	96	Gravel surface, HSG C				
2,892	98	Roofs, HSG C				
57,216	74	>75% Grass cover, Good, HSG C				
1,919	98	Paved parking, HSG C				
70,071	75	Weighted Average				
65,260	74	93.13% Pervious Area				
4,811	98	6.87% Impervious Area				
Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description	
11.2	50	0.0260	0.07		Sheet Flow, AB	
					Grass: Bermuda n= 0.410 P2= 3.30"	
3.2	100	0.0110	0.52		Shallow Concentrated Flow, BC	
					Woodland Kv= 5.0 fps	
3.9	216	0.0340	0.92		Shallow Concentrated Flow, CD	
					Woodland Kv= 5.0 fps	
18.3	366	Total				

Summary for Pond eA1: Analysis Point - Pre Dev Catch Basin in Hope St.


Inflow Area = 9,269 sf, 0.00% Impervious, Inflow Depth = 0.09" for WQv event
Inflow = 0.01 cfs @ 12.36 hrs, Volume= 67 cf
Primary = 0.01 cfs @ 12.36 hrs, Volume= 67 cf, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

Summary for Pond eA2: Analysis Point - Pre Dev Flow Towards Wetland

Inflow Area = 70,071 sf, 6.87% Impervious, Inflow Depth = 0.13" for WQv event
Inflow = 0.09 cfs @ 12.25 hrs, Volume= 730 cf
Primary = 0.09 cfs @ 12.25 hrs, Volume= 730 cf, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs



22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Printed 12/9/2022

Page 2

Area Listing (selected nodes)

Area (sq-ft)	CN	Description (subcatchment-numbers)
53,735	74	>75% Grass cover, Good, HSG C (pB1, pF1, pF2, pS1, pS2, pS3, pS4, pS5, pS6, pS7)
956	98	Patio/Deck/Stairs (pF1, pS2, pS5, pS7)
11,048	98	Paved parking, HSG C (pF1, pF2, pS6)
12,326	98	Roofs, HSG C (RF1, RF2, RF3, RF4, RF5)
1,622	98	Walkway (pF1, pF2, pS6)
79,687	82	TOTAL AREA

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 1-yr Rainfall=2.80"

Printed 12/9/2022

Page 3

Time span=0.00-72.00 hrs, dt=0.04 hrs, 1801 points

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv.

Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

Pond B1: Post - Dry Extended Detention Basin

Peak Elev=80.64' Storage=900 cf Inflow=0.73 cfs 4,501 cf
Primary=0.33 cfs 4,171 cf Secondary=0.00 cfs 0 cf Outflow=0.33 cfs 4,171 cf

Pond BR1: Post - Bio-retention Basin-1

Peak Elev=85.42' Storage=1,018 cf Inflow=0.44 cfs 1,624 cf
Primary=0.00 cfs 0 cf Secondary=0.02 cfs 1,363 cf Outflow=0.02 cfs 1,363 cf

Pond BR2: Post - Bio-retention Basin-2

Peak Elev=82.25' Storage=927 cf Inflow=0.77 cfs 3,997 cf
Primary=0.53 cfs 1,926 cf Secondary=0.02 cfs 1,997 cf Outflow=0.55 cfs 3,923 cf

Pond BR3: Post - Bio-retention Basin-3

Peak Elev=84.96' Storage=510 cf Inflow=0.18 cfs 1,113 cf
Primary=0.02 cfs 126 cf Secondary=0.02 cfs 930 cf Outflow=0.04 cfs 1,056 cf

Pond BR4: Post - Bio-retention Basin-4

Peak Elev=83.83' Storage=277 cf Inflow=0.23 cfs 770 cf
Outflow=0.18 cfs 516 cf

Pond DMH: post - DMH

Peak Elev=83.00' Inflow=0.12 cfs 1,693 cf
8.0" Round Culvert n=0.013 L=92.0' S=0.0087 '/' Outflow=0.12 cfs 1,693 cf

Pond FB1: Post - Forebay-1

Peak Elev=86.14' Storage=210 cf Inflow=0.41 cfs 1,610 cf
Outflow=0.40 cfs 1,438 cf

Pond FB2: Post - Forebay-2

Peak Elev=83.87' Storage=86 cf Inflow=0.20 cfs 760 cf
Outflow=0.20 cfs 684 cf

Pond FB3: Post - Forebay-3

Peak Elev=82.18' Storage=243 cf Inflow=0.58 cfs 3,486 cf
Outflow=0.57 cfs 3,294 cf

Pond pA1: Analysis Point - Post Dev Catch Basin in Hope St.

Inflow=0.02 cfs 126 cf
Primary=0.02 cfs 126 cf

Pond pA2: Analysis Point - Post Dev Flow to Wetland

Inflow=0.39 cfs 6,541 cf
Primary=0.39 cfs 6,541 cf

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 1-yr Rainfall=2.80"

Printed 12/9/2022

Page 4

Subcatchment pB1: Post - Runoff to Detention Basin-1

Runoff Area=2,690 sf 0.00% Impervious Runoff Depth=0.78"
Tc=5.0 min CN=74/0 Runoff=0.05 cfs 176 cf

Subcatchment pF1: Post - Runoff to Forebay-1

Runoff Area=12,569 sf 42.19% Impervious Runoff Depth=1.54"
Flow Length=126' Tc=10.0 min CN=74/98 Runoff=0.41 cfs 1,610 cf

Subcatchment pF2: Post - Runoff to Forebay-2

Runoff Area=4,810 sf 62.31% Impervious Runoff Depth=1.90"
Flow Length=64' Tc=8.0 min CN=74/98 Runoff=0.20 cfs 760 cf

Subcatchment pS1: Post - Runoff to Bio-retention Basin

Runoff Area=2,851 sf 0.00% Impervious Runoff Depth=0.78"
Tc=5.0 min CN=74/0 Runoff=0.06 cfs 186 cf

Subcatchment pS2: Post - Runoff to Swale-1

Runoff Area=5,173 sf 9.22% Impervious Runoff Depth=0.95"
Tc=5.0 min CN=74/98 Runoff=0.12 cfs 409 cf

Subcatchment pS3: Post - Flow to wetlands

Runoff Area=5,708 sf 0.00% Impervious Runoff Depth=0.78"
Flow Length=453' Tc=22.1 min CN=74/0 Runoff=0.07 cfs 373 cf

Subcatchment pS4: Post - Runoff to Bio-retention Basin-4

Runoff Area=1,321 sf 0.00% Impervious Runoff Depth=0.78"
Flow Length=64' Tc=8.0 min CN=74/0 Runoff=0.02 cfs 86 cf

Subcatchment pS5: Post - Runoff to Bio-retention Basin-2

Runoff Area=1,840 sf 12.93% Impervious Runoff Depth=1.01"
Tc=5.0 min CN=74/98 Runoff=0.05 cfs 156 cf

Subcatchment pS6: Post - Runoff to Forebay-3

Runoff Area=13,640 sf 32.91% Impervious Runoff Depth=1.37"
Tc=5.0 min CN=74/98 Runoff=0.46 cfs 1,559 cf

Subcatchment pS7: Post - Flow to Hope Street

Runoff Area=16,759 sf 0.73% Impervious Runoff Depth=0.80"
Flow Length=104' Tc=30.8 min CN=74/98 Runoff=0.18 cfs 1,113 cf

Subcatchment RF1: Post - Roof Area (Units 3&4)

Runoff Area=2,556 sf 100.00% Impervious Runoff Depth=2.57"
Tc=5.0 min CN=0/98 Runoff=0.16 cfs 547 cf

Subcatchment RF2: Post - Roof Area (Units 5&6)

Runoff Area=2,556 sf 100.00% Impervious Runoff Depth=2.57"
Tc=5.0 min CN=0/98 Runoff=0.16 cfs 547 cf

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 1-yr Rainfall=2.80"

Printed 12/9/2022

Page 5

Subcatchment RF3: Post - Roof Area (Units 7&8)

Runoff Area=2,556 sf 100.00% Impervious Runoff Depth=2.57"
Tc=5.0 min CN=0/98 Runoff=0.16 cfs 547 cf

Subcatchment RF4: Post- Roof Area (Units 9&10)

Runoff Area=2,102 sf 100.00% Impervious Runoff Depth=2.57"
Tc=5.0 min CN=0/98 Runoff=0.13 cfs 450 cf

Subcatchment RF5: Post - Roof Area (Units 1&2)

Runoff Area=2,556 sf 100.00% Impervious Runoff Depth=2.57"
Tc=5.0 min CN=0/98 Runoff=0.16 cfs 547 cf

Reach S1: Post - Dry Swale 1

Avg. Flow Depth=0.06' Max Vel=0.89 fps Inflow=0.12 cfs 409 cf
n=0.035 L=150.0' S=0.0200 '/' Capacity=17.43 cfs Outflow=0.11 cfs 409 cf

Pond SB: Post - Settling Basin

Peak Elev=82.06' Storage=241 cf Inflow=0.20 cfs 2,102 cf
Outflow=0.17 cfs 1,883 cf

Pond US1: Post - Recharge System-1

Peak Elev=85.04' Storage=423 cf Inflow=0.32 cfs 1,094 cf
Discarded=0.01 cfs 764 cf Primary=0.10 cfs 330 cf Outflow=0.11 cfs 1,094 cf

Pond US2: Post - Underground Storage System

Peak Elev=83.44' Storage=203 cf Inflow=0.30 cfs 997 cf
4.0" Round Culvert n=0.013 L=100.0' S=0.0105 '/' Outflow=0.15 cfs 997 cf

Total Runoff Area = 79,687 sf Runoff Volume = 9,067 cf Average Runoff Depth = 1.37"
67.43% Pervious = 53,735 sf 32.57% Impervious = 25,952 sf

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 1-yr Rainfall=2.80"

Printed 12/9/2022

Page 6

Summary for Pond B1: Post - Dry Extended Detention Basin

Inflow Area = 57,220 sf, 45.14% Impervious, Inflow Depth = 0.94" for 1-yr event
Inflow = 0.73 cfs @ 12.21 hrs, Volume= 4,501 cf
Outflow = 0.33 cfs @ 12.71 hrs, Volume= 4,171 cf, Atten= 55%, Lag= 30.0 min
Primary = 0.33 cfs @ 12.71 hrs, Volume= 4,171 cf
Secondary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs / 2
Peak Elev= 80.64' @ 12.71 hrs Surf.Area= 1,522 sf Storage= 900 cf
Flood Elev= 82.50' Surf.Area= 2,300 sf Storage= 4,432 cf

Plug-Flow detention time= 152.3 min calculated for 4,169 cf (93% of inflow)
Center-of-Mass det. time= 87.1 min (1,087.5 - 1,000.5)

Volume	Invert	Avail.Storage	Storage Description
#1	80.00'	4,432 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
80.00	1,273	0	0
81.00	1,660	1,467	1,467
82.00	2,080	1,870	3,337
82.50	2,300	1,095	4,432

Device	Routing	Invert	Outlet Devices
#1	Secondary	82.00'	4.0' long x 2.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32
#2	Primary	80.45'	8.0" Round Culvert L= 12.0' RCP, sq.cut end projecting, Ke= 0.500 Inlet / Outlet Invert= 80.45' / 79.50' S= 0.0792 '/' Cc= 0.900
#3	Primary	80.25'	n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.35 sf 4.0" Round Culvert L= 12.0' RCP, sq.cut end projecting, Ke= 0.500 Inlet / Outlet Invert= 80.25' / 79.50' S= 0.0625 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.09 sf

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 1-yr Rainfall=2.80"

Printed 12/9/2022

Page 7

Primary OutFlow Max=0.33 cfs @ 12.71 hrs HW=80.64' (Free Discharge)

└─2=Culvert (Inlet Controls 0.13 cfs @ 1.50 fps)

└─3=Culvert (Inlet Controls 0.20 cfs @ 2.29 fps)

Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=80.00' (Free Discharge)

└─1=Broad-Crested Rectangular Weir (Controls 0.00 cfs)

Summary for Pond BR1: Post - Bio-retention Basin-1

Inflow Area = 15,420 sf, 34.39% Impervious, Inflow Depth = 1.26" for 1-yr event
Inflow = 0.44 cfs @ 12.15 hrs, Volume= 1,624 cf
Outflow = 0.02 cfs @ 15.75 hrs, Volume= 1,363 cf, Atten= 95%, Lag= 215.8 min
Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf
Secondary = 0.02 cfs @ 15.75 hrs, Volume= 1,363 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs / 2
Peak Elev= 85.42' @ 15.75 hrs Surf.Area= 1,891 sf Storage= 1,018 cf
Flood Elev= 86.00' Surf.Area= 2,110 sf Storage= 1,567 cf

Plug-Flow detention time= 532.5 min calculated for 1,362 cf (84% of inflow)
Center-of-Mass det. time= 464.4 min (1,304.4 - 840.0)

Volume	Invert	Avail.Storage	Storage Description
#1	85.00'	867 cf	Custom Stage Data (Prismatic) Listed below (Recalc)
#2	83.00'	694 cf	Filter Material (Prismatic) Listed below (Recalc)
#3	83.75'	7 cf	2,110 cf Overall - 7 cf Embedded = 2,103 cf x 33.0% Voids
		L= 35.0'	6.0" Round Pipe Storage Inside #2
		1,567 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
85.00	678	0	0
86.00	1,055	867	867

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 1-yr Rainfall=2.80"

Printed 12/9/2022

Page 8

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
83.00	1,055	0	0
85.00	1,055	2,110	2,110

Device Routing Invert Outlet Devices

#1	Primary	85.75'	4.0' long x 2.5' breadth Broad-Crested Rectangular Weir																
			Head (feet)	0.20	0.40	0.60	0.80	1.00	1.20	1.40	1.60	1.80	2.00	2.50	3.00	3.50	4.00		
			Coef. (English)	2.48	2.60	2.60	2.60	2.60	2.64	2.65	2.68	2.75	2.74	2.76	2.89	3.05	3.19	3.32	
#2	Device 3	83.00'	0.500 in/hr Exfiltration over Surface area Phase-In= 0.01'																
#3	Secondary	83.75'	6.0" Round Culvert L= 100.0' RCP, sq.cut end projecting, Ke= 0.500																
			Inlet / Outlet Invert= 83.75' / 82.85' S= 0.0090 '/' Cc= 0.900																
			n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf																

Primary OutFlow Max=0.00 cfs @ 0.00 hrs HW=83.00' (Free Discharge)

1=Broad-Crested Rectangular Weir (Controls 0.00 cfs)

Secondary OutFlow Max=0.02 cfs @ 15.75 hrs HW=85.42' (Free Discharge)

3=Culvert (Passes 0.02 cfs of 0.74 cfs potential flow)

2=Exfiltration (Exfiltration Controls 0.02 cfs)

Summary for Pond BR2: Post - Bio-retention Basin-2

Inflow Area =	22,694 sf,	52.62% Impervious,	Inflow Depth =	2.11"	for 1-yr event
Inflow =	0.77 cfs @	12.09 hrs,	Volume=	3,997 cf	
Outflow =	0.55 cfs @	12.21 hrs,	Volume=	3,923 cf,	Atten= 29%, Lag= 6.7 min
Primary =	0.53 cfs @	12.21 hrs,	Volume=	1,926 cf	
Secondary =	0.02 cfs @	12.21 hrs,	Volume=	1,997 cf	

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs / 2

Peak Elev= 82.25' @ 12.21 hrs Surf.Area= 1,720 sf Storage= 927 cf

Flood Elev= 82.50' Surf.Area= 1,796 sf Storage= 1,140 cf

Plug-Flow detention time= 283.1 min calculated for 3,921 cf (98% of inflow)

Center-of-Mass det. time= 265.0 min (1,192.0 - 927.1)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 1-yr Rainfall=2.80"

Printed 12/9/2022

Page 9

Volume	Invert	Avail. Storage	Storage Description
#1	81.35'	836 cf	Custom Stage Data (Prismatic) Listed below (Recalc)
#2	80.35'	292 cf	Filter Material (Prismatic) Listed below (Recalc)
			898 cf Overall - 12 cf Embedded = 886 cf x 33.0% Voids
#3	80.60'	12 cf	6.0" Round Pipe Storage Inside #2
			L= 61.0'
		1,140 cf	Total Available Storage

Elevation (feet)	Surf. Area (sq-ft)	Inc. Store (cubic-feet)	Cum. Store (cubic-feet)
81.35	563	0	0
82.00	745	425	425
82.50	898	411	836

Elevation (feet)	Surf. Area (sq-ft)	Inc. Store (cubic-feet)	Cum. Store (cubic-feet)
80.35	898	0	0
81.35	898	898	898

Device	Routing	Invert	Outlet Devices
#1	Primary	82.10'	3.5' long x 2.0' breadth Broad-Crested Rectangular Weir
			Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50
			Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32
#2	Device 3	80.35'	0.500 in/hr Exfiltration over Surface area Phase-In= 0.01'
#3	Secondary	80.60'	6.0" Round Culvert L= 62.0' RCP, sq. cut end projecting, Ke= 0.500
			Inlet / Outlet Invert= 80.60' / 79.00' S= 0.0258 '/' Cc= 0.900
			n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf

Primary OutFlow Max=0.52 cfs @ 12.21 hrs HW=82.25' (Free Discharge)

↑ **1=Broad-Crested Rectangular Weir** (Weir Controls 0.52 cfs @ 0.99 fps)

Secondary OutFlow Max=0.02 cfs @ 12.21 hrs HW=82.25' (Free Discharge)

↑ **3=Culvert** (Passes 0.02 cfs of 1.03 cfs potential flow)

↑ **2=Exfiltration** (Exfiltration Controls 0.02 cfs)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 1-yr Rainfall=2.80"

Printed 12/9/2022

Page 10

Summary for Pond BR3: Post - Bio-retention Basin-3

Inflow Area = 16,759 sf, 0.73% Impervious, Inflow Depth = 0.80" for 1-yr event
Inflow = 0.18 cfs @ 12.48 hrs, Volume= 1,113 cf
Outflow = 0.04 cfs @ 13.64 hrs, Volume= 1,056 cf, Atten= 78%, Lag= 69.8 min
Primary = 0.02 cfs @ 13.64 hrs, Volume= 126 cf
Secondary = 0.02 cfs @ 13.64 hrs, Volume= 930 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Peak Elev= 84.96' @ 13.64 hrs Surf.Area= 1,310 sf Storage= 510 cf

Plug-Flow detention time= 371.6 min calculated for 1,056 cf (95% of inflow)
Center-of-Mass det. time= 345.5 min (1,236.9 - 891.4)

Volume	Invert	Avail.Storage	Storage Description
#1	84.40'	371 cf	Custom Stage Data (Prismatic) Listed below (Recalc)
#2	83.40'	224 cf	Filter Material (Prismatic) Listed below (Recalc)
#3	83.65'	6 cf	686 cf Overall - 6 cf Embedded = 680 cf x 33.0% Voids
		6.0" Round Pipe Storage Inside #2	
		L= 30.0'	
		601 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
84.40	374	0	0
85.10	686	371	371

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
83.40	686	0	0
84.40	686	686	686

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 1-yr Rainfall=2.80"

Printed 12/9/2022

Page 11

Device Routing Invert Outlet Devices

#1	Primary	84.95'	8.0' long x 2.0' breadth Broad-Crested Rectangular Weir													
			Head (feet)	0.20	0.40	0.60	0.80	1.00	1.20	1.40	1.60	1.80	2.00	2.50	3.00	3.50
			Coef. (English)	2.54	2.61	2.61	2.60	2.66	2.70	2.77	2.89	2.88	2.85	3.07	3.20	3.32
#2	Device 3	85.00'	6.0" Horiz. Orifice/Grate C= 0.600 Limited to weir flow at low heads													
#3	Secondary	83.65'	6.0" Round Culvert L= 68.0' RCP, sq.cut end projecting, Ke= 0.500													
			Inlet / Outlet Invert= 83.65' / 83.00' S= 0.0096 '/' Cc= 0.900													
			n= 0.013 Concrete pipe, bends & connections, Flow Area= 0.20 sf													
#4	Device 3	83.40'	0.500 in/hr Exfiltration over Surface area Phase-In= 0.01'													

Primary OutFlow Max=0.02 cfs @ 13.64 hrs HW=84.96' (Free Discharge)

└─**1=Broad-Crested Rectangular Weir** (Weir Controls 0.02 cfs @ 0.26 fps)

Secondary OutFlow Max=0.02 cfs @ 13.64 hrs HW=84.96' (Free Discharge)

└─**3=Culvert** (Passes 0.02 cfs of 0.73 cfs potential flow)

└─**2=Orifice/Grate** (Controls 0.00 cfs)

└─**4=Exfiltration** (Exfiltration Controls 0.02 cfs)

Summary for Pond BR4: Post - Bio-retention Basin-4

Inflow Area =	6,131 sf, 48.88% Impervious, Inflow Depth = 1.51" for 1-yr event
Inflow =	0.23 cfs @ 12.12 hrs, Volume= 770 cf
Outflow =	0.18 cfs @ 12.22 hrs, Volume= 516 cf, Atten= 21%, Lag= 5.6 min
Primary =	0.18 cfs @ 12.22 hrs, Volume= 516 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs / 2

Peak Elev= 83.83' @ 12.22 hrs Surf.Area= 570 sf Storage= 277 cf

Flood Elev= 84.00' Surf.Area= 594 sf Storage= 325 cf

Plug-Flow detention time= 164.1 min calculated for 516 cf (67% of inflow)

Center-of-Mass det. time= 65.7 min (888.7 - 823.0)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 1-yr Rainfall=2.80"

Printed 12/9/2022

Page 12

Volume	Invert	Avail.Storage	Storage Description
#1	83.00'	227 cf	Custom Stage Data (Prismatic) Listed below (Recalc)
#2	82.00'	98 cf	Filter Material (Prismatic) Listed below (Recalc)
		297 cf Overall x 33.0% Voids	
		325 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
83.00	157	0	0
84.00	297	227	227

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
82.00	297	0	0
83.00	297	297	297

Device	Routing	Invert	Outlet Devices
#1	Primary	83.75'	3.0' long x 2.0' breadth Broad-Crested Rectangular Weir
Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50			
Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32			

Primary OutFlow Max=0.17 cfs @ 12.22 hrs HW=83.83' (Free Discharge)

1-Broad-Crested Rectangular Weir (Weir Controls 0.17 cfs @ 0.71 fps)

Summary for Pond DMH: post - DMH

Inflow Area = 5,112 sf, 100.00% Impervious, Inflow Depth = 3.98" for 1-yr event
Inflow = 0.12 cfs @ 12.40 hrs, Volume= 1,693 cf
Outflow = 0.12 cfs @ 12.40 hrs, Volume= 1,693 cf, Atten= 0%, Lag= 0.0 min
Primary = 0.12 cfs @ 12.40 hrs, Volume= 1,693 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

Peak Elev= 83.00' @ 12.40 hrs

Flood Elev= 85.00'

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 1-yr Rainfall=2.80"

Printed 12/9/2022

Page 13

Device	Routing	Invert	Outlet Devices
#1	Primary	82.80'	8.0" Round Culvert L= 92.0' RCP, sq.cut end projecting, Ke= 0.500 Inlet / Outlet Invert= 82.80' / 82.00' S= 0.0087 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.35 sf

Primary OutFlow Max=0.12 cfs @ 12.40 hrs HW=83.00' (Free Discharge)

1=Culvert (Barrel Controls 0.12 cfs @ 2.05 fps)

Summary for Pond FB1: Post - Forebay-1

Inflow Area = 12,569 sf, 42.19% Impervious, Inflow Depth = 1.54" for 1-yr event
Inflow = 0.41 cfs @ 12.14 hrs, Volume= 1,610 cf
Outflow = 0.40 cfs @ 12.16 hrs, Volume= 1,438 cf, Atten= 1%, Lag= 1.3 min
Primary = 0.40 cfs @ 12.16 hrs, Volume= 1,438 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

Peak Elev= 86.14' @ 12.16 hrs Surf.Area= 278 sf Storage= 210 cf

Flood Elev= 86.50' Surf.Area= 350 sf Storage= 323 cf

Plug-Flow detention time= 93.2 min calculated for 1,437 cf (89% of inflow)

Center-of-Mass det. time= 40.2 min (836.1 - 795.9)

Volume	Invert	Avail.Storage	Storage Description
#1	85.00'	323 cf	Custom Stage Data (Prismatic) Listed below (Recalc)
Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
85.00	95	0	0
86.00	250	173	173
86.50	350	150	323

Device	Routing	Invert	Outlet Devices
#1	Primary	86.00'	3.0' long x 2.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 1-yr Rainfall=2.80"

Printed 12/9/2022

Page 14

Primary OutFlow Max=0.40 cfs @ 12.16 hrs HW=86.14' (Free Discharge)

1-Broad-Crested Rectangular Weir (Weir Controls 0.40 cfs @ 0.95 fps)

Summary for Pond FB2: Post - Forebay-2

Inflow Area = 4,810 sf, 62.31% Impervious, Inflow Depth = 1.90" for 1-yr event
Inflow = 0.20 cfs @ 12.11 hrs, Volume= 760 cf
Outflow = 0.20 cfs @ 12.12 hrs, Volume= 684 cf, Atten= 1%, Lag= 0.5 min
Primary = 0.20 cfs @ 12.12 hrs, Volume= 684 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs / 2

Peak Elev= 83.87' @ 12.12 hrs Surf.Area= 133 sf Storage= 86 cf

Flood Elev= 84.00' Surf.Area= 143 sf Storage= 103 cf

Plug-Flow detention time= 88.3 min calculated for 684 cf (90% of inflow)

Center-of-Mass det. time= 38.1 min (816.7 - 778.6)

Volume	Invert	Avail.Storage	Storage Description
#1	83.00'	103 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
83.00	63	0	0
84.00	143	103	103

Device	Routing	Invert	Outlet Devices
--------	---------	--------	----------------

#1	Primary	83.80'	4.0' long x 2.0' breadth Broad-Crested Rectangular Weir
			Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50
			Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32

Primary OutFlow Max=0.20 cfs @ 12.12 hrs HW=83.87' (Free Discharge)

1-Broad-Crested Rectangular Weir (Weir Controls 0.20 cfs @ 0.69 fps)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 1-yr Rainfall=2.80"

Printed 12/9/2022

Page 15

Summary for Pond FB3: Post - Forebay-3

Inflow Area = 18,298 sf, 49.99% Impervious, Inflow Depth = 2.29" for 1-yr event
Inflow = 0.58 cfs @ 12.08 hrs, Volume= 3,486 cf
Outflow = 0.57 cfs @ 12.11 hrs, Volume= 3,294 cf, Atten= 3%, Lag= 1.2 min
Primary = 0.57 cfs @ 12.11 hrs, Volume= 3,294 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Peak Elev= 82.18' @ 12.11 hrs Surf.Area= 312 sf Storage= 243 cf
Flood Elev= 82.50' Surf.Area= 400 sf Storage= 358 cf

Plug-Flow detention time= 81.6 min calculated for 3,294 cf (94% of inflow)
Center-of-Mass det. time= 31.3 min (959.5 - 928.2)

Volume	Invert	Avail.Storage	Storage Description
#1	81.00'	358 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
81.00	121	0	0
82.00	263	192	192
82.50	400	166	358

Device	Routing	Invert	Outlet Devices
#1	Primary	82.00'	3.0' long x 2.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32

Primary OutFlow Max=0.56 cfs @ 12.11 hrs HW=82.18' (Free Discharge)
1-Broad-Crested Rectangular Weir (Weir Controls 0.56 cfs @ 1.06 fps)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 1-yr Rainfall=2.80"

Printed 12/9/2022

Page 16

Summary for Pond pA1: Analysis Point - Post Dev Catch Basin in Hope St.

Inflow Area = 16,759 sf, 0.73% Impervious, Inflow Depth = 0.09" for 1-yr event
Inflow = 0.02 cfs @ 13.64 hrs, Volume= 126 cf
Primary = 0.02 cfs @ 13.64 hrs, Volume= 126 cf, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

Summary for Pond pA2: Analysis Point - Post Dev Flow to Wetland

Inflow Area = 62,928 sf, 41.05% Impervious, Inflow Depth = 1.25" for 1-yr event
Inflow = 0.39 cfs @ 12.67 hrs, Volume= 6,541 cf
Primary = 0.39 cfs @ 12.67 hrs, Volume= 6,541 cf, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

Summary for Subcatchment pB1: Post - Runoff to Detention Basin-1

Runoff = 0.05 cfs @ 12.09 hrs, Volume= 176 cf, Depth= 0.78"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 1-yr Rainfall=2.80"

Area (sf)	CN	Description
2,690	74	>75% Grass cover, Good, HSG C
0	98	Paved parking, HSG C
0	98	Walkway
0	98	Roofs, HSG C
2,690	74	Weighted Average
2,690	74	100.00% Pervious Area

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 1-yr Rainfall=2.80"

Printed 12/9/2022

Page 17

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry, AB

Summary for Subcatchment pF1: Post - Runoff to Forebay-1

Runoff = 0.41 cfs @ 12.14 hrs, Volume= 1,610 cf, Depth= 1.54"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 1-yr Rainfall=2.80"

Area (sf)	CN	Description
4,205	98	Paved parking, HSG C
7,266	74	>75% Grass cover, Good, HSG C
*	979	98 Walkway
*	119	98 Patio/Deck/Stairs
12,569	84	Weighted Average
7,266	74	57.81% Pervious Area
5,303	98	42.19% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.5	44	0.0300	0.08		Sheet Flow, AB
					Grass: Bermuda n= 0.410 P2= 3.30"
0.5	82	0.0180	2.72		Shallow Concentrated Flow, BC
					Paved Kv= 20.3 fps
10.0	126	Total			

Summary for Subcatchment pF2: Post - Runoff to Forebay-2

Runoff = 0.20 cfs @ 12.11 hrs, Volume= 760 cf, Depth= 1.90"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 1-yr Rainfall=2.80"

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 1-yr Rainfall=2.80"

Printed 12/9/2022

Page 18

Area (sf)		CN	Description		
*	1,813	74	>75% Grass cover, Good, HSG C		
	2,847	98	Paved parking, HSG C		
	150	98	Walkway		
	0	98	Roofs, HSG C		
4,810		89	Weighted Average		
1,813		74	37.69% Pervious Area		
2,997		98	62.31% Impervious Area		
Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.9	40	0.0400	0.08		Sheet Flow, AB
					Grass: Bermuda n= 0.410 P2= 3.30"
0.1	24	0.0200	2.87		Shallow Concentrated Flow, BC
					Paved Kv= 20.3 fps

Summary for Subcatchment pS1: Post - Runoff to Bio-retention Basin

Runoff = 0.06 cfs @ 12.09 hrs, Volume= 186 cf, Depth= 0.78"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 1-yr Rainfall=2.80"

Area (sf)		CN	Description		
*	2,851	74	>75% Grass cover, Good, HSG C		
	0	98	Patio/Deck/Stairs		
	2,851	74	Weighted Average		
	2,851	74	100.00% Pervious Area		
Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0	Direct Entry, Runoff to swale				

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 1-yr Rainfall=2.80"

Printed 12/9/2022

Page 19

Summary for Subcatchment pS2: Post - Runoff to Swale-1

Runoff = 0.12 cfs @ 12.08 hrs, Volume= 409 cf, Depth= 0.95"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 1-yr Rainfall=2.80"

Area (sf)	CN	Description
0	98	Paved parking, HSG C
4,696	74	>75% Grass cover, Good, HSG C
0	98	Walkway
477	98	Patio/Deck/Stairs
5,173	76	Weighted Average
4,696	74	90.78% Pervious Area
477	98	9.22% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					

Direct Entry, Parking Runoff

Summary for Subcatchment pS3: Post - Flow to wetlands

Runoff = 0.07 cfs @ 12.34 hrs, Volume= 373 cf, Depth= 0.78"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 1-yr Rainfall=2.80"

Area (sf)	CN	Description
5,708	74	>75% Grass cover, Good, HSG C
0	98	Paved parking, HSG C
0	70	Woods, Good, HSG C
5,708	74	Weighted Average
5,708	74	100.00% Pervious Area

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 1-yr Rainfall=2.80"

Printed 12/9/2022

Page 20

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.2	50	0.0260	0.07		Sheet Flow, AB Grass: Bermuda n= 0.410 P2= 3.30"
8.6	183	0.0050	0.35		Shallow Concentrated Flow, BC Woodland Kv= 5.0 fps
1.9	117	0.0400	1.00		Shallow Concentrated Flow, CD Woodland Kv= 5.0 fps
0.3	103	0.0300	5.33	26.67	Channel Flow, DE Area= 5.0 sf Perim= 10.2' r= 0.49' n= 0.030 Earth, grassed & winding
22.1	453	Total			

Summary for Subcatchment pS4: Post - Runoff to Bio-retention Basin-4

Runoff = 0.02 cfs @ 12.13 hrs, Volume= 86 cf, Depth= 0.78"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 1-yr Rainfall=2.80"

Area (sf)	CN	Description
1,321	74	>75% Grass cover, Good, HSG C
0	98	Paved parking, HSG C
0	98	Walkway
0	98	Roofs, HSG C
1,321	74	Weighted Average
1,321	74	100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.9	40	0.0400	0.08		Sheet Flow, AB Grass: Bermuda n= 0.410 P2= 3.30"
0.1	24	0.0200	2.87		Shallow Concentrated Flow, BC Paved Kv= 20.3 fps
8.0	64	Total			

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 1-yr Rainfall=2.80"

Printed 12/9/2022

Page 21

Summary for Subcatchment pS5: Post - Runoff to Bio-retention Basin-2

Runoff = 0.05 cfs @ 12.08 hrs, Volume= 156 cf, Depth= 1.01"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 1-yr Rainfall=2.80"

Area (sf)	CN	Description
0	98	Paved parking, HSG C
1,602	74	>75% Grass cover, Good, HSG C
0	98	Walkway
238	98	Patio/Deck/Stairs
0	98	Roofs, HSG C

1,840	77	Weighted Average
1,602	74	87.07% Pervious Area
238	98	12.93% Impervious Area

Tc Length Slope Velocity Capacity Description
(min) (feet) (ft/ft) (ft/sec) (cfs)

5.0

Direct Entry, AB

Summary for Subcatchment pS6: Post - Runoff to Forebay-3

Runoff = 0.46 cfs @ 12.08 hrs, Volume= 1,559 cf, Depth= 1.37"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 1-yr Rainfall=2.80"

Area (sf)	CN	Description
3,996	98	Paved parking, HSG C
9,151	74	>75% Grass cover, Good, HSG C
493	98	Walkway

13,640	82	Weighted Average
9,151	74	67.09% Pervious Area
4,489	98	32.91% Impervious Area

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 1-yr Rainfall=2.80"

Printed 12/9/2022

Page 22

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry, AB

Summary for Subcatchment pS7: Post - Flow to Hope Street

Runoff = 0.18 cfs @ 12.48 hrs, Volume= 1,113 cf, Depth= 0.80"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 1-yr Rainfall=2.80"

Area (sf)	CN	Description
16,637	74	>75% Grass cover, Good, HSG C
0	98	Paved parking, HSG C
0	98	Walkways
122	98	Patio/Deck/Stairs
16,759	74	Weighted Average
16,637	74	99.27% Pervious Area
122	98	0.73% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
30.6	60	0.0030	0.03		Sheet Flow, AB
					Grass: Bermuda n= 0.410 P2= 3.30"
0.2	44	0.0450	3.42		Shallow Concentrated Flow, BC
					Unpaved Kv= 16.1 fps
30.8	104	Total			

Summary for Subcatchment RF1: Post - Roof Area (Units 3&4)

Runoff = 0.16 cfs @ 12.07 hrs, Volume= 547 cf, Depth= 2.57"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 1-yr Rainfall=2.80"

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 1-yr Rainfall=2.80"

Printed 12/9/2022

Page 23

Area (sf)	CN	Description
2,556	98	Roofs, HSG C
2,556	98	100.00% Impervious Area
Tc (min)	Length (feet)	Slope (ft/ft)
	Velocity (ft/sec)	Capacity (cfs)
	Description	

5.0

Direct Entry, Roof Runoff

Summary for Subcatchment RF2: Post - Roof Area (Units 5&6)

Runoff = 0.16 cfs @ 12.07 hrs, Volume= 547 cf, Depth= 2.57"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 1-yr Rainfall=2.80"

Area (sf)	CN	Description
2,556	98	Roofs, HSG C
2,556	98	100.00% Impervious Area
Tc (min)	Length (feet)	Slope (ft/ft)
	Velocity (ft/sec)	Capacity (cfs)
	Description	

5.0

Direct Entry, Roof Runoff

Summary for Subcatchment RF3: Post - Roof Area (Units 7&8)

Runoff = 0.16 cfs @ 12.07 hrs, Volume= 547 cf, Depth= 2.57"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 1-yr Rainfall=2.80"

Area (sf)	CN	Description
2,556	98	Roofs, HSG C
2,556	98	100.00% Impervious Area

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 1-yr Rainfall=2.80"

Printed 12/9/2022

Page 24

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry, Roof Runoff

Summary for Subcatchment RF4: Post- Roof Area (Units 9&10)

Runoff = 0.13 cfs @ 12.07 hrs, Volume= 450 cf, Depth= 2.57"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 1-yr Rainfall=2.80"

Area (sf)	CN	Description
2,102	98	Roofs, HSG C
2,102	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry, Roof Runoff

Summary for Subcatchment RF5: Post - Roof Area (Units 1&2)

Runoff = 0.16 cfs @ 12.07 hrs, Volume= 547 cf, Depth= 2.57"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 1-yr Rainfall=2.80"

Area (sf)	CN	Description
2,556	98	Roofs, HSG C
2,556	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry, Roof Runoff


Summary for Reach S1: Post - Dry Swale 1

Inflow Area = 20,593 sf, 28.07% Impervious, Inflow Depth = 0.24" for 1-yr event
Inflow = 0.12 cfs @ 12.08 hrs, Volume= 409 cf
Outflow = 0.11 cfs @ 12.16 hrs, Volume= 409 cf, Atten= 8%, Lag= 4.8 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Max. Velocity= 0.89 fps, Min. Travel Time= 2.8 min
Avg. Velocity = 0.30 fps, Avg. Travel Time= 8.3 min

Peak Storage= 19 cf @ 12.12 hrs
Average Depth at Peak Storage= 0.06'
Bank-Full Depth= 1.00' Flow Area= 4.0 sf, Capacity= 17.43 cfs

Custom cross-section, Length= 150.0' Slope= 0.0200 '/
Constant n= 0.035 Earth, dense weeds
Inlet Invert= 85.00', Outlet Invert= 82.00'



Offset (feet)	Elevation (feet)	Chan.Depth (feet)
-3.00	1.00	0.00
-1.00	0.00	1.00
1.00	0.00	1.00
3.00	1.00	0.00

Depth (feet)	End Area (sq-ft)	Perim. (feet)	Storage (cubic-feet)	Discharge (cfs)
0.00	0.0	2.0	0	0.00
1.00	4.0	6.5	600	17.43

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 1-yr Rainfall=2.80"

Printed 12/9/2022

Page 26

Summary for Pond SB: Post - Settling Basin

Inflow Area = 25,705 sf, 42.37% Impervious, Inflow Depth = 0.98" for 1-yr event
Inflow = 0.20 cfs @ 12.21 hrs, Volume= 2,102 cf
Outflow = 0.17 cfs @ 12.44 hrs, Volume= 1,883 cf, Atten= 15%, Lag= 13.8 min
Primary = 0.17 cfs @ 12.44 hrs, Volume= 1,883 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Peak Elev= 82.06' @ 12.44 hrs Surf.Area= 347 sf Storage= 241 cf

Plug-Flow detention time= 143.1 min calculated for 1,882 cf (90% of inflow)
Center-of-Mass det. time= 53.2 min (1,188.1 - 1,134.9)

Volume	Invert	Avail.Storage	Storage Description
#1	81.00'	416 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
81.00	108	0	0
82.00	331	220	220
82.50	456	197	416

Device	Routing	Invert	Outlet Devices
#1	Primary	82.00'	4.0' long x 2.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32

Primary OutFlow Max=0.17 cfs @ 12.44 hrs HW=82.06' (Free Discharge)
1-Broad-Crested Rectangular Weir (Weir Controls 0.17 cfs @ 0.65 fps)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 1-yr Rainfall=2.80"

Printed 12/9/2022

Page 27

Summary for Pond US1: Post - Recharge System-1

Inflow Area = 5,112 sf,100.00% Impervious, Inflow Depth = 2.57" for 1-yr event
Inflow = 0.32 cfs @ 12.07 hrs, Volume= 1,094 cf
Outflow = 0.11 cfs @ 12.33 hrs, Volume= 1,094 cf, Atten= 66%, Lag= 15.4 min
Discarded = 0.01 cfs @ 8.60 hrs, Volume= 764 cf
Primary = 0.10 cfs @ 12.33 hrs, Volume= 330 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Peak Elev= 85.04' @ 12.33 hrs Surf.Area= 715 sf Storage= 423 cf
Flood Elev= 86.30' Surf.Area= 715 sf Storage= 837 cf

Plug-Flow detention time= 263.3 min calculated for 1,094 cf (100% of inflow)
Center-of-Mass det. time= 263.4 min (1,021.8 - 758.4)

Volume	Invert	Avail.Storage	Storage Description
#1A	84.00'	405 cf	21.50"W x 33.25'L x 2.33'H Field A 1,668 cf Overall - 439 cf Embedded = 1,229 cf x 33.0% Voids
#2A	84.50'	439 cf	Infiltrator H-20 Chamber x 30 Inside #1 Effective Size= 27.5"W x 14.0"H => 2.34 sf x 6.25'L = 14.6 cf Overall Size= 34.0"W x 16.0"H x 6.25'L
		845 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	84.00'	0.500 in/hr Exfiltration over Surface area
#2	Primary	84.85'	6.0" Round Culvert L= 12.0' RCP, sq.cut end projecting, Ke= 0.500 Inlet / Outlet Invert= 84.85' / 84.60' S= 0.0208 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf

Discarded OutFlow Max=0.01 cfs @ 8.60 hrs HW=84.02' (Free Discharge)
↑**1=Exfiltration** (Exfiltration Controls 0.01 cfs)

Primary OutFlow Max=0.10 cfs @ 12.33 hrs HW=85.04' (Free Discharge)
↑**2=Culvert** (Inlet Controls 0.10 cfs @ 1.49 fps)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 1-yr Rainfall=2.80"

Printed 12/9/2022

Page 28

Summary for Pond US2: Post - Underground Storage System

Inflow Area = 4,658 sf, 100.00% Impervious, Inflow Depth = 2.57" for 1-yr event
Inflow = 0.30 cfs @ 12.07 hrs, Volume= 997 cf
Outflow = 0.15 cfs @ 12.21 hrs, Volume= 997 cf, Atten= 51%, Lag= 8.3 min
Primary = 0.15 cfs @ 12.21 hrs, Volume= 997 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Peak Elev= 83.44' @ 12.21 hrs Surf.Area= 998 sf Storage= 203 cf

Plug-Flow detention time= 33.7 min calculated for 997 cf (100% of inflow)
Center-of-Mass det. time= 33.9 min (792.3 - 758.4)

Volume	Invert	Avail.Storage	Storage Description
#1	83.15'	1,484 cf	18.0" Round Pipe Storage x 14 L= 60.0'

Device	Routing	Invert	Outlet Devices
#1	Primary	83.15'	4.0" Round Culvert L= 100.0' RCP, sq.cut end projecting, Ke= 0.500 Inlet / Outlet Invert= 83.15' / 82.10' S= 0.0105 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.09 sf

Primary OutFlow Max=0.14 cfs @ 12.21 hrs HW=83.44' (Free Discharge)
1=Culvert (Barrel Controls 0.14 cfs @ 2.39 fps)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.30"

Printed 12/9/2022

Page 29

Time span=0.00-72.00 hrs, dt=0.04 hrs, 1801 points

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv.

Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

Pond B1: Post - Dry Extended Detention Basin

Peak Elev=80.81' Storage=1,161 cf Inflow=1.21 cfs 6,343 cf
Primary=0.66 cfs 6,012 cf Secondary=0.00 cfs 0 cf Outflow=0.66 cfs 6,012 cf

Pond BR1: Post - Bio-retention Basin-1

Peak Elev=85.76' Storage=1,328 cf Inflow=0.57 cfs 2,114 cf
Primary=0.02 cfs 81 cf Secondary=0.02 cfs 1,771 cf Outflow=0.04 cfs 1,852 cf

Pond BR2: Post - Bio-retention Basin-2

Peak Elev=82.31' Storage=973 cf Inflow=0.98 cfs 4,854 cf
Primary=0.84 cfs 2,685 cf Secondary=0.02 cfs 2,093 cf Outflow=0.86 cfs 4,778 cf

Pond BR3: Post - Bio-retention Basin-3

Peak Elev=84.99' Storage=528 cf Inflow=0.27 cfs 1,562 cf
Primary=0.16 cfs 501 cf Secondary=0.02 cfs 1,004 cf Outflow=0.17 cfs 1,505 cf

Pond BR4: Post - Bio-retention Basin-4

Peak Elev=83.86' Storage=284 cf Inflow=0.28 cfs 978 cf
Outflow=0.27 cfs 723 cf

Pond DMH: post - DMH

Peak Elev=83.06' Inflow=0.20 cfs 2,272 cf
8.0" Round Culvert n=0.013 L=92.0' S=0.0087 '/' Outflow=0.20 cfs 2,272 cf

Pond FB1: Post - Forebay-1

Peak Elev=86.16' Storage=216 cf Inflow=0.52 cfs 2,024 cf
Outflow=0.51 cfs 1,851 cf

Pond FB2: Post - Forebay-2

Peak Elev=83.88' Storage=87 cf Inflow=0.25 cfs 933 cf
Outflow=0.25 cfs 857 cf

Pond FB3: Post - Forebay-3

Peak Elev=82.21' Storage=253 cf Inflow=0.75 cfs 4,184 cf
Outflow=0.73 cfs 3,992 cf

Pond pA1: Analysis Point - Post Dev Catch Basin in Hope St.

Inflow=0.16 cfs 501 cf
Primary=0.16 cfs 501 cf

Pond pA2: Analysis Point - Post Dev Flow to Wetland

Inflow=0.76 cfs 8,631 cf
Primary=0.76 cfs 8,631 cf

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.30"

Printed 12/9/2022

Page 30

Subcatchment pB1: Post - Runoff to Detention Basin-1

Runoff Area=2,690 sf 0.00% Impervious Runoff Depth=1.10"
Tc=5.0 min CN=74/0 Runoff=0.08 cfs 247 cf

Subcatchment pF1: Post - Runoff to Forebay-1

Runoff Area=12,569 sf 42.19% Impervious Runoff Depth=1.93"
Flow Length=126' Tc=10.0 min CN=74/98 Runoff=0.52 cfs 2,024 cf

Subcatchment pF2: Post - Runoff to Forebay-2

Runoff Area=4,810 sf 62.31% Impervious Runoff Depth=2.33"
Flow Length=64' Tc=8.0 min CN=74/98 Runoff=0.25 cfs 933 cf

Subcatchment pS1: Post - Runoff to Bio-retention Basin

Runoff Area=2,851 sf 0.00% Impervious Runoff Depth=1.10"
Tc=5.0 min CN=74/0 Runoff=0.08 cfs 262 cf

Subcatchment pS2: Post - Runoff to Swale-1

Runoff Area=5,173 sf 9.22% Impervious Runoff Depth=1.28"
Tc=5.0 min CN=74/98 Runoff=0.17 cfs 554 cf

Subcatchment pS3: Post - Flow to wetlands

Runoff Area=5,708 sf 0.00% Impervious Runoff Depth=1.10"
Flow Length=453' Tc=22.1 min CN=74/0 Runoff=0.10 cfs 525 cf

Subcatchment pS4: Post - Runoff to Bio-retention Basin-4

Runoff Area=1,321 sf 0.00% Impervious Runoff Depth=1.10"
Flow Length=64' Tc=8.0 min CN=74/0 Runoff=0.03 cfs 122 cf

Subcatchment pS5: Post - Runoff to Bio-retention Basin-2

Runoff Area=1,840 sf 12.93% Impervious Runoff Depth=1.36"
Tc=5.0 min CN=74/98 Runoff=0.06 cfs 208 cf

Subcatchment pS6: Post - Runoff to Forebay-3

Runoff Area=13,640 sf 32.91% Impervious Runoff Depth=1.75"
Tc=5.0 min CN=74/98 Runoff=0.60 cfs 1,989 cf

Subcatchment pS7: Post - Flow to Hope Street

Runoff Area=16,759 sf 0.73% Impervious Runoff Depth=1.12"
Flow Length=104' Tc=30.8 min CN=74/98 Runoff=0.27 cfs 1,562 cf

Subcatchment RF1: Post - Roof Area (Units 3&4)

Runoff Area=2,556 sf 100.00% Impervious Runoff Depth=3.07"
Tc=5.0 min CN=0/98 Runoff=0.19 cfs 653 cf

Subcatchment RF2: Post - Roof Area (Units 5&6)

Runoff Area=2,556 sf 100.00% Impervious Runoff Depth=3.07"
Tc=5.0 min CN=0/98 Runoff=0.19 cfs 653 cf

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.30"

Printed 12/9/2022

Page 31

Subcatchment RF3: Post - Roof Area (Units 7&8)

Runoff Area=2,556 sf 100.00% Impervious Runoff Depth=3.07"
Tc=5.0 min CN=0/98 Runoff=0.19 cfs 653 cf

Subcatchment RF4: Post- Roof Area (Units 9&10)

Runoff Area=2,102 sf 100.00% Impervious Runoff Depth=3.07"
Tc=5.0 min CN=0/98 Runoff=0.16 cfs 537 cf

Subcatchment RF5: Post - Roof Area (Units 1&2)

Runoff Area=2,556 sf 100.00% Impervious Runoff Depth=3.07"
Tc=5.0 min CN=0/98 Runoff=0.19 cfs 653 cf

Reach S1: Post - Dry Swale 1

Avg. Flow Depth=0.07' Max Vel=1.01 fps Inflow=0.17 cfs 635 cf
n=0.035 L=150.0' S=0.0200 '/' Capacity=17.43 cfs Outflow=0.16 cfs 635 cf

Pond SB: Post - Settling Basin

Peak Elev=82.10' Storage=253 cf Inflow=0.35 cfs 2,907 cf
Outflow=0.33 cfs 2,687 cf

Pond US1: Post - Recharge System-1

Peak Elev=85.11' Storage=461 cf Inflow=0.38 cfs 1,307 cf
Discarded=0.01 cfs 806 cf Primary=0.18 cfs 501 cf Outflow=0.19 cfs 1,307 cf

Pond US2: Post - Underground Storage System

Peak Elev=83.48' Storage=239 cf Inflow=0.35 cfs 1,191 cf
4.0" Round Culvert n=0.013 L=100.0' S=0.0105 '/' Outflow=0.17 cfs 1,191 cf

Total Runoff Area = 79,687 sf Runoff Volume = 11,577 cf Average Runoff Depth = 1.74"
67.43% Pervious = 53,735 sf 32.57% Impervious = 25,952 sf

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.30"

Printed 12/9/2022

Page 32

Summary for Pond B1: Post - Dry Extended Detention Basin

Inflow Area = 57,220 sf, 45.14% Impervious, Inflow Depth = 1.33" for 2-yr event
Inflow = 1.21 cfs @ 12.24 hrs, Volume= 6,343 cf
Outflow = 0.66 cfs @ 12.51 hrs, Volume= 6,012 cf, Atten= 45%, Lag= 16.7 min
Primary = 0.66 cfs @ 12.51 hrs, Volume= 6,012 cf
Secondary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs / 2
Peak Elev= 80.81' @ 12.51 hrs Surf.Area= 1,587 sf Storage= 1,161 cf
Flood Elev= 82.50' Surf.Area= 2,300 sf Storage= 4,432 cf

Plug-Flow detention time= 131.1 min calculated for 6,009 cf (95% of inflow)
Center-of-Mass det. time= 72.4 min (1,082.4 - 1,010.0)

Volume	Invert	Avail.Storage	Storage Description
#1	80.00'	4,432 cf	Custom Stage Data (Prismatic) Listed below (Recalc)
Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
80.00	1,273	0	0
81.00	1,660	1,467	1,467
82.00	2,080	1,870	3,337
82.50	2,300	1,095	4,432

Device	Routing	Invert	Outlet Devices
#1	Secondary	82.00'	4.0' long x 2.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32
#2	Primary	80.45'	8.0" Round Culvert L= 12.0' RCP, sq.cut end projecting, Ke= 0.500 Inlet / Outlet Invert= 80.45' / 79.50' S= 0.0792 '/' Cc= 0.900
#3	Primary	80.25'	n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.35 sf 4.0" Round Culvert L= 12.0' RCP, sq.cut end projecting, Ke= 0.500 Inlet / Outlet Invert= 80.25' / 79.50' S= 0.0625 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.09 sf

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.30"

Printed 12/9/2022

Page 33

Primary OutFlow Max=0.66 cfs @ 12.51 hrs HW=80.81' (Free Discharge)

└─2=Culvert (Inlet Controls 0.40 cfs @ 2.05 fps)

└─3=Culvert (Inlet Controls 0.26 cfs @ 3.03 fps)

Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=80.00' (Free Discharge)

└─1=Broad-Crested Rectangular Weir (Controls 0.00 cfs)

Summary for Pond BR1: Post - Bio-retention Basin-1

Inflow Area = 15,420 sf, 34.39% Impervious, Inflow Depth = 1.64" for 2-yr event
Inflow = 0.57 cfs @ 12.15 hrs, Volume= 2,114 cf
Outflow = 0.04 cfs @ 14.41 hrs, Volume= 1,852 cf, Atten= 93%, Lag= 135.7 min
Primary = 0.02 cfs @ 14.41 hrs, Volume= 81 cf
Secondary = 0.02 cfs @ 14.41 hrs, Volume= 1,771 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs / 2
Peak Elev= 85.76' @ 14.41 hrs Surf.Area= 2,021 sf Storage= 1,328 cf
Flood Elev= 86.00' Surf.Area= 2,110 sf Storage= 1,567 cf

Plug-Flow detention time= 609.7 min calculated for 1,851 cf (88% of inflow)
Center-of-Mass det. time= 553.1 min (1,385.9 - 832.8)

Volume	Invert	Avail.Storage	Storage Description
#1	85.00'	867 cf	Custom Stage Data (Prismatic) Listed below (Recalc)
#2	83.00'	694 cf	Filter Material (Prismatic) Listed below (Recalc)
#3	83.75'	7 cf	2,110 cf Overall - 7 cf Embedded = 2,103 cf x 33.0% Voids
		L= 35.0'	6.0" Round Pipe Storage Inside #2
		1,567 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
85.00	678	0	0
86.00	1,055	867	867

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.30"

Printed 12/9/2022

Page 34

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
83.00	1,055	0	0
85.00	1,055	2,110	2,110

Device Routing Invert Outlet Devices

#1	Primary	85.75'	4.0' long x 2.5' breadth Broad-Crested Rectangular Weir														
			Head (feet)	0.20	0.40	0.60	0.80	1.00	1.20	1.40	1.60	1.80	2.00	2.50	3.00	3.50	4.00
			Coef. (English)	2.48	2.60	2.60	2.60	2.64	2.65	2.68	2.75	2.74	2.76	2.89	3.05	3.19	3.32
#2	Device 3	83.00'	0.500 in/hr Exfiltration over Surface area Phase-In= 0.01'														
#3	Secondary	83.75'	6.0" Round Culvert L= 100.0' RCP, sq.cut end projecting, Ke= 0.500														
			Inlet / Outlet Invert= 83.75' / 82.85' S= 0.0090 '/' Cc= 0.900														
			n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf														

Primary OutFlow Max=0.01 cfs @ 14.41 hrs HW=85.76' (Free Discharge)

↑ **1=Broad-Crested Rectangular Weir** (Weir Controls 0.01 cfs @ 0.28 fps)

Secondary OutFlow Max=0.02 cfs @ 14.41 hrs HW=85.76' (Free Discharge)

↑ **3=Culvert** (Passes 0.02 cfs of 0.80 cfs potential flow)

↑ **2=Exfiltration** (Exfiltration Controls 0.02 cfs)

Summary for Pond BR2: Post - Bio-retention Basin-2

Inflow Area =	22,694 sf, 52.62% Impervious, Inflow Depth = 2.57" for 2-yr event
Inflow =	0.98 cfs @ 12.09 hrs, Volume= 4,854 cf
Outflow =	0.86 cfs @ 12.14 hrs, Volume= 4,778 cf, Atten= 12%, Lag= 2.9 min
Primary =	0.84 cfs @ 12.14 hrs, Volume= 2,685 cf
Secondary =	0.02 cfs @ 12.14 hrs, Volume= 2,093 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs / 2

Peak Elev= 82.31' @ 12.14 hrs Surf.Area= 1,737 sf Storage= 973 cf

Flood Elev= 82.50' Surf.Area= 1,796 sf Storage= 1,140 cf

Plug-Flow detention time= 244.9 min calculated for 4,775 cf (98% of inflow)

Center-of-Mass det. time= 228.6 min (1,144.5 - 916.0)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.30"

Printed 12/9/2022

Page 35

Volume	Invert	Avail. Storage	Storage Description
#1	81.35'	836 cf	Custom Stage Data (Prismatic) Listed below (Recalc)
#2	80.35'	292 cf	Filter Material (Prismatic) Listed below (Recalc)
			898 cf Overall - 12 cf Embedded = 886 cf x 33.0% Voids
#3	80.60'	12 cf	6.0" Round Pipe Storage Inside #2
			L= 61.0'
		1,140 cf	Total Available Storage

Elevation (feet)	Surf. Area (sq-ft)	Inc. Store (cubic-feet)	Cum. Store (cubic-feet)
81.35	563	0	0
82.00	745	425	425
82.50	898	411	836

Elevation (feet)	Surf. Area (sq-ft)	Inc. Store (cubic-feet)	Cum. Store (cubic-feet)
80.35	898	0	0
81.35	898	898	898

Device	Routing	Invert	Outlet Devices
#1	Primary	82.10'	3.5' long x 2.0' breadth Broad-Crested Rectangular Weir
			Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50
			Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32
#2	Device 3	80.35'	0.500 in/hr Exfiltration over Surface area Phase-In= 0.01'
#3	Secondary	80.60'	6.0" Round Culvert L= 62.0' RCP, sq. cut end projecting, Ke= 0.500
			Inlet / Outlet Invert= 80.60' / 79.00' S= 0.0258 '/' Cc= 0.900
			n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf

Primary OutFlow Max=0.83 cfs @ 12.14 hrs HW=82.31' (Free Discharge)

↑ **1=Broad-Crested Rectangular Weir** (Weir Controls 0.83 cfs @ 1.15 fps)

Secondary OutFlow Max=0.02 cfs @ 12.14 hrs HW=82.31' (Free Discharge)

↑ **3=Culvert** (Passes 0.02 cfs of 1.04 cfs potential flow)

↑ **2=Exfiltration** (Exfiltration Controls 0.02 cfs)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.30"

Printed 12/9/2022

Page 36

Summary for Pond BR3: Post - Bio-retention Basin-3

Inflow Area = 16,759 sf, 0.73% Impervious, Inflow Depth = 1.12" for 2-yr event
Inflow = 0.27 cfs @ 12.46 hrs, Volume= 1,562 cf
Outflow = 0.17 cfs @ 12.79 hrs, Volume= 1,505 cf, Atten= 35%, Lag= 19.9 min
Primary = 0.16 cfs @ 12.79 hrs, Volume= 501 cf
Secondary = 0.02 cfs @ 12.79 hrs, Volume= 1,004 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Peak Elev= 84.99' @ 12.79 hrs Surf.Area= 1,323 sf Storage= 528 cf

Plug-Flow detention time= 291.9 min calculated for 1,505 cf (96% of inflow)
Center-of-Mass det. time= 271.8 min (1,152.9 - 881.1)

Volume	Invert	Avail.Storage	Storage Description
#1	84.40'	371 cf	Custom Stage Data (Prismatic) Listed below (Recalc)
#2	83.40'	224 cf	Filter Material (Prismatic) Listed below (Recalc)
#3	83.65'	6 cf	686 cf Overall - 6 cf Embedded = 680 cf x 33.0% Voids
		6.0" Round Pipe Storage Inside #2	
		L= 30.0'	
		601 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
84.40	374	0	0
85.10	686	371	371

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
83.40	686	0	0
84.40	686	686	686

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.30"

Printed 12/9/2022

Page 37

Device Routing Invert Outlet Devices

#1	Primary	84.95'	8.0' long x 2.0' breadth Broad-Crested Rectangular Weir													
			Head (feet)	0.20	0.40	0.60	0.80	1.00	1.20	1.40	1.60	1.80	2.00	2.50	3.00	3.50
			Coef. (English)	2.54	2.61	2.61	2.60	2.66	2.70	2.77	2.89	2.88	2.85	3.07	3.20	3.32
#2	Device 3	85.00'	6.0" Horiz. Orifice/Grate C= 0.600 Limited to weir flow at low heads													
#3	Secondary	83.65'	6.0" Round Culvert L= 68.0' RCP, sq.cut end projecting, Ke= 0.500													
			Inlet / Outlet Invert= 83.65' / 83.00' S= 0.0096 '/' Cc= 0.900													
			n= 0.013 Concrete pipe, bends & connections, Flow Area= 0.20 sf													
#4	Device 3	83.40'	0.500 in/hr Exfiltration over Surface area Phase-In= 0.01'													

Primary OutFlow Max=0.16 cfs @ 12.79 hrs HW=84.99' (Free Discharge)

└─**1=Broad-Crested Rectangular Weir** (Weir Controls 0.16 cfs @ 0.50 fps)

Secondary OutFlow Max=0.02 cfs @ 12.79 hrs HW=84.99' (Free Discharge)

└─**3=Culvert** (Passes 0.02 cfs of 0.73 cfs potential flow)

└─**2=Orifice/Grate** (Controls 0.00 cfs)

└─**4=Exfiltration** (Exfiltration Controls 0.02 cfs)

Summary for Pond BR4: Post - Bio-retention Basin-4

Inflow Area =	6,131 sf, 48.88% Impervious, Inflow Depth = 1.91" for 2-yr event
Inflow =	0.28 cfs @ 12.12 hrs, Volume= 978 cf
Outflow =	0.27 cfs @ 12.15 hrs, Volume= 723 cf, Atten= 5%, Lag= 1.8 min
Primary =	0.27 cfs @ 12.15 hrs, Volume= 723 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs / 2

Peak Elev= 83.86' @ 12.15 hrs Surf.Area= 574 sf Storage= 284 cf

Flood Elev= 84.00' Surf.Area= 594 sf Storage= 325 cf

Plug-Flow detention time= 140.3 min calculated for 723 cf (74% of inflow)

Center-of-Mass det. time= 52.2 min (868.9 - 816.7)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.30"

Printed 12/9/2022

Page 38

Volume	Invert	Avail.Storage	Storage Description
#1	83.00'	227 cf	Custom Stage Data (Prismatic) Listed below (Recalc)
#2	82.00'	98 cf	Filter Material (Prismatic) Listed below (Recalc)
		297 cf Overall x 33.0% Voids	
		325 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
83.00	157	0	0
84.00	297	227	227

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
82.00	297	0	0
83.00	297	297	297

Device	Routing	Invert	Outlet Devices
#1	Primary	83.75'	3.0' long x 2.0' breadth Broad-Crested Rectangular Weir
Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50			
Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32			

Primary OutFlow Max=0.26 cfs @ 12.15 hrs HW=83.86' (Free Discharge)

1-Broad-Crested Rectangular Weir (Weir Controls 0.26 cfs @ 0.83 fps)

Summary for Pond DMH: post - DMH

Inflow Area = 5,112 sf, 100.00% Impervious, Inflow Depth = 5.33" for 2-yr event
Inflow = 0.20 cfs @ 12.23 hrs, Volume= 2,272 cf
Outflow = 0.20 cfs @ 12.23 hrs, Volume= 2,272 cf, Atten= 0%, Lag= 0.0 min
Primary = 0.20 cfs @ 12.23 hrs, Volume= 2,272 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

Peak Elev= 83.06' @ 12.23 hrs

Flood Elev= 85.00'

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.30"

Printed 12/9/2022

Page 39

Device	Routing	Invert	Outlet Devices
#1	Primary	82.80'	8.0" Round Culvert L= 92.0' RCP, sq.cut end projecting, Ke= 0.500 Inlet / Outlet Invert= 82.80' / 82.00' S= 0.0087 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.35 sf

Primary OutFlow Max=0.20 cfs @ 12.23 hrs HW=83.06' (Free Discharge)

1=Culvert (Barrel Controls 0.20 cfs @ 2.36 fps)

Summary for Pond FB1: Post - Forebay-1

Inflow Area = 12,569 sf, 42.19% Impervious, Inflow Depth = 1.93" for 2-yr event
Inflow = 0.52 cfs @ 12.14 hrs, Volume= 2,024 cf
Outflow = 0.51 cfs @ 12.16 hrs, Volume= 1,851 cf, Atten= 1%, Lag= 1.2 min
Primary = 0.51 cfs @ 12.16 hrs, Volume= 1,851 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

Peak Elev= 86.16' @ 12.16 hrs Surf.Area= 283 sf Storage= 216 cf

Flood Elev= 86.50' Surf.Area= 350 sf Storage= 323 cf

Plug-Flow detention time= 80.4 min calculated for 1,851 cf (91% of inflow)

Center-of-Mass det. time= 35.1 min (829.1 - 793.9)

Volume	Invert	Avail.Storage	Storage Description
#1	85.00'	323 cf	Custom Stage Data (Prismatic) Listed below (Recalc)
Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
85.00	95	0	0
86.00	250	173	173
86.50	350	150	323

Device	Routing	Invert	Outlet Devices
#1	Primary	86.00'	3.0' long x 2.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.30"

Printed 12/9/2022

Page 40

Primary OutFlow Max=0.51 cfs @ 12.16 hrs HW=86.16' (Free Discharge)

1-Broad-Crested Rectangular Weir (Weir Controls 0.51 cfs @ 1.03 fps)

Summary for Pond FB2: Post - Forebay-2

Inflow Area = 4,810 sf, 62.31% Impervious, Inflow Depth = 2.33" for 2-yr event
Inflow = 0.25 cfs @ 12.11 hrs, Volume= 933 cf
Outflow = 0.25 cfs @ 12.12 hrs, Volume= 857 cf, Atten= 1%, Lag= 0.5 min
Primary = 0.25 cfs @ 12.12 hrs, Volume= 857 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs / 2

Peak Elev= 83.88' @ 12.12 hrs Surf.Area= 134 sf Storage= 87 cf

Flood Elev= 84.00' Surf.Area= 143 sf Storage= 103 cf

Plug-Flow detention time= 77.0 min calculated for 857 cf (92% of inflow)

Center-of-Mass det. time= 34.0 min (810.3 - 776.3)

Volume	Invert	Avail.Storage	Storage Description
#1	83.00'	103 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
83.00	63	0	0
84.00	143	103	103

Device	Routing	Invert	Outlet Devices
--------	---------	--------	----------------

#1	Primary	83.80'	4.0' long x 2.0' breadth Broad-Crested Rectangular Weir
			Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50
			Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32

Primary OutFlow Max=0.25 cfs @ 12.12 hrs HW=83.88' (Free Discharge)

1-Broad-Crested Rectangular Weir (Weir Controls 0.25 cfs @ 0.74 fps)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.30"

Printed 12/9/2022

Page 41

Summary for Pond FB3: Post - Forebay-3

Inflow Area = 18,298 sf, 49.99% Impervious, Inflow Depth = 2.74" for 2-yr event
Inflow = 0.75 cfs @ 12.08 hrs, Volume= 4,184 cf
Outflow = 0.73 cfs @ 12.10 hrs, Volume= 3,992 cf, Atten= 3%, Lag= 1.1 min
Primary = 0.73 cfs @ 12.10 hrs, Volume= 3,992 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Peak Elev= 82.21' @ 12.10 hrs Surf.Area= 320 sf Storage= 253 cf
Flood Elev= 82.50' Surf.Area= 400 sf Storage= 358 cf

Plug-Flow detention time= 72.1 min calculated for 3,990 cf (95% of inflow)
Center-of-Mass det. time= 27.7 min (946.9 - 919.2)

Volume	Invert	Avail.Storage	Storage Description
#1	81.00'	358 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
81.00	121	0	0
82.00	263	192	192
82.50	400	166	358

Device	Routing	Invert	Outlet Devices
#1	Primary	82.00'	3.0' long x 2.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32

Primary OutFlow Max=0.72 cfs @ 12.10 hrs HW=82.21' (Free Discharge)
1-Broad-Crested Rectangular Weir (Weir Controls 0.72 cfs @ 1.16 fps)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.30"

Printed 12/9/2022

Page 42

Summary for Pond pA1: Analysis Point - Post Dev Catch Basin in Hope St.

Inflow Area = 16,759 sf, 0.73% Impervious, Inflow Depth = 0.36" for 2-yr event
Inflow = 0.16 cfs @ 12.79 hrs, Volume= 501 cf
Primary = 0.16 cfs @ 12.79 hrs, Volume= 501 cf, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

Summary for Pond pA2: Analysis Point - Post Dev Flow to Wetland

Inflow Area = 62,928 sf, 41.05% Impervious, Inflow Depth = 1.65" for 2-yr event
Inflow = 0.76 cfs @ 12.50 hrs, Volume= 8,631 cf
Primary = 0.76 cfs @ 12.50 hrs, Volume= 8,631 cf, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

Summary for Subcatchment pB1: Post - Runoff to Detention Basin-1

Runoff = 0.08 cfs @ 12.08 hrs, Volume= 247 cf, Depth= 1.10"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 2-yr Rainfall=3.30"

Area (sf)	CN	Description
2,690	74	>75% Grass cover, Good, HSG C
0	98	Paved parking, HSG C
0	98	Walkway
0	98	Roofs, HSG C
2,690	74	Weighted Average
2,690	74	100.00% Pervious Area

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.30"

Printed 12/9/2022

Page 43

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry, AB

Summary for Subcatchment pF1: Post - Runoff to Forebay-1

Runoff = 0.52 cfs @ 12.14 hrs, Volume= 2,024 cf, Depth= 1.93"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 2-yr Rainfall=3.30"

Area (sf)	CN	Description
4,205	98	Paved parking, HSG C
7,266	74	>75% Grass cover, Good, HSG C
*	979	98 Walkway
*	119	98 Patio/Deck/Stairs
12,569	84	Weighted Average
7,266	74	57.81% Pervious Area
5,303	98	42.19% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.5	44	0.0300	0.08		Sheet Flow, AB
					Grass: Bermuda n= 0.410 P2= 3.30"
0.5	82	0.0180	2.72		Shallow Concentrated Flow, BC
					Paved Kv= 20.3 fps
10.0	126	Total			

Summary for Subcatchment pF2: Post - Runoff to Forebay-2

Runoff = 0.25 cfs @ 12.11 hrs, Volume= 933 cf, Depth= 2.33"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 2-yr Rainfall=3.30"

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.30"

Printed 12/9/2022

Page 44

Area (sf)		CN	Description		
*	1,813	74	>75% Grass cover, Good, HSG C		
	2,847	98	Paved parking, HSG C		
	150	98	Walkway		
	0	98	Roofs, HSG C		
4,810		89	Weighted Average		
1,813		74	37.69% Pervious Area		
2,997		98	62.31% Impervious Area		
Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.9	40	0.0400	0.08		Sheet Flow, AB
					Grass: Bermuda n= 0.410 P2= 3.30"
0.1	24	0.0200	2.87		Shallow Concentrated Flow, BC
					Paved Kv= 20.3 fps

Summary for Subcatchment pS1: Post - Runoff to Bio-retention Basin

Runoff = 0.08 cfs @ 12.08 hrs, Volume= 262 cf, Depth= 1.10"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 2-yr Rainfall=3.30"

Area (sf)		CN	Description		
*	2,851	74	>75% Grass cover, Good, HSG C		
	0	98	Patio/Deck/Stairs		
	2,851	74	Weighted Average		
	2,851	74	100.00% Pervious Area		
Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0	Direct Entry, Runoff to swale				

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.30"

Printed 12/9/2022

Page 45

Summary for Subcatchment pS2: Post - Runoff to Swale-1

Runoff = 0.17 cfs @ 12.08 hrs, Volume= 554 cf, Depth= 1.28"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 2-yr Rainfall=3.30"

Area (sf)	CN	Description
0	98	Paved parking, HSG C
4,696	74	>75% Grass cover, Good, HSG C
0	98	Walkway
477	98	Patio/Deck/Stairs
5,173	76	Weighted Average
4,696	74	90.78% Pervious Area
477	98	9.22% Impervious Area

Tc Length Slope Velocity Capacity Description
(min) (feet) (ft/ft) (ft/sec) (cfs)

5.0

Direct Entry, Parking Runoff

Summary for Subcatchment pS3: Post - Flow to wetlands

Runoff = 0.10 cfs @ 12.33 hrs, Volume= 525 cf, Depth= 1.10"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 2-yr Rainfall=3.30"

Area (sf)	CN	Description
5,708	74	>75% Grass cover, Good, HSG C
0	98	Paved parking, HSG C
0	70	Woods, Good, HSG C
5,708	74	Weighted Average
5,708	74	100.00% Pervious Area

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.30"

Printed 12/9/2022

Page 46

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.2	50	0.0260	0.07		Sheet Flow, AB Grass: Bermuda n= 0.410 P2= 3.30"
8.6	183	0.0050	0.35		Shallow Concentrated Flow, BC Woodland Kv= 5.0 fps
1.9	117	0.0400	1.00		Shallow Concentrated Flow, CD Woodland Kv= 5.0 fps
0.3	103	0.0300	5.33	26.67	Channel Flow, DE Area= 5.0 sf Perim= 10.2' r= 0.49' n= 0.030 Earth, grassed & winding
22.1	453	Total			

Summary for Subcatchment pS4: Post - Runoff to Bio-retention Basin-4

Runoff = 0.03 cfs @ 12.12 hrs, Volume= 122 cf, Depth= 1.10"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 2-yr Rainfall=3.30"

Area (sf)	CN	Description
1,321	74	>75% Grass cover, Good, HSG C
0	98	Paved parking, HSG C
0	98	Walkway
0	98	Roofs, HSG C
1,321	74	Weighted Average
1,321	74	100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.9	40	0.0400	0.08		Sheet Flow, AB Grass: Bermuda n= 0.410 P2= 3.30"
0.1	24	0.0200	2.87		Shallow Concentrated Flow, BC Paved Kv= 20.3 fps
8.0	64	Total			

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.30"

Printed 12/9/2022

Page 47

Summary for Subcatchment pS5: Post - Runoff to Bio-retention Basin-2

Runoff = 0.06 cfs @ 12.08 hrs, Volume= 208 cf, Depth= 1.36"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 2-yr Rainfall=3.30"

Area (sf)	CN	Description
0	98	Paved parking, HSG C
1,602	74	>75% Grass cover, Good, HSG C
0	98	Walkway
238	98	Patio/Deck/Stairs
0	98	Roofs, HSG C

1,840	77	Weighted Average
1,602	74	87.07% Pervious Area
238	98	12.93% Impervious Area

Tc Length Slope Velocity Capacity Description
(min) (feet) (ft/ft) (ft/sec) (cfs)

5.0

Direct Entry, AB

Summary for Subcatchment pS6: Post - Runoff to Forebay-3

Runoff = 0.60 cfs @ 12.08 hrs, Volume= 1,989 cf, Depth= 1.75"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 2-yr Rainfall=3.30"

Area (sf)	CN	Description
3,996	98	Paved parking, HSG C
9,151	74	>75% Grass cover, Good, HSG C
493	98	Walkway

13,640	82	Weighted Average
9,151	74	67.09% Pervious Area
4,489	98	32.91% Impervious Area

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.30"

Printed 12/9/2022

Page 48

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry, AB

Summary for Subcatchment pS7: Post - Flow to Hope Street

Runoff = 0.27 cfs @ 12.46 hrs, Volume= 1,562 cf, Depth= 1.12"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 2-yr Rainfall=3.30"

Area (sf)	CN	Description
16,637	74	>75% Grass cover, Good, HSG C
0	98	Paved parking, HSG C
0	98	Walkways
122	98	Patio/Deck/Stairs
16,759	74	Weighted Average
16,637	74	99.27% Pervious Area
122	98	0.73% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
30.6	60	0.0030	0.03		Sheet Flow, AB
					Grass: Bermuda n= 0.410 P2= 3.30"
0.2	44	0.0450	3.42		Shallow Concentrated Flow, BC
					Unpaved Kv= 16.1 fps
30.8	104	Total			

Summary for Subcatchment RF1: Post - Roof Area (Units 3&4)

Runoff = 0.19 cfs @ 12.07 hrs, Volume= 653 cf, Depth= 3.07"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 2-yr Rainfall=3.30"

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.30"

Printed 12/9/2022

Page 49

Area (sf)	CN	Description
2,556	98	Roofs, HSG C
2,556	98	100.00% Impervious Area
Tc (min)	Length (feet)	Slope (ft/ft)
	Velocity (ft/sec)	Capacity (cfs)
	Description	

5.0

Direct Entry, Roof Runoff

Summary for Subcatchment RF2: Post - Roof Area (Units 5&6)

Runoff = 0.19 cfs @ 12.07 hrs, Volume= 653 cf, Depth= 3.07"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 2-yr Rainfall=3.30"

Area (sf)	CN	Description
2,556	98	Roofs, HSG C
2,556	98	100.00% Impervious Area
Tc (min)	Length (feet)	Slope (ft/ft)
	Velocity (ft/sec)	Capacity (cfs)
	Description	

5.0

Direct Entry, Roof Runoff

Summary for Subcatchment RF3: Post - Roof Area (Units 7&8)

Runoff = 0.19 cfs @ 12.07 hrs, Volume= 653 cf, Depth= 3.07"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 2-yr Rainfall=3.30"

Area (sf)	CN	Description
2,556	98	Roofs, HSG C
2,556	98	100.00% Impervious Area

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.30"

Printed 12/9/2022

Page 50

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry, Roof Runoff

Summary for Subcatchment RF4: Post- Roof Area (Units 9&10)

Runoff = 0.16 cfs @ 12.07 hrs, Volume= 537 cf, Depth= 3.07"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 2-yr Rainfall=3.30"

Area (sf)	CN	Description
2,102	98	Roofs, HSG C
2,102	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry, Roof Runoff

Summary for Subcatchment RF5: Post - Roof Area (Units 1&2)

Runoff = 0.19 cfs @ 12.07 hrs, Volume= 653 cf, Depth= 3.07"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 2-yr Rainfall=3.30"

Area (sf)	CN	Description
2,556	98	Roofs, HSG C
2,556	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry, Roof Runoff


Summary for Reach S1: Post - Dry Swale 1

Inflow Area = 20,593 sf, 28.07% Impervious, Inflow Depth = 0.37" for 2-yr event
Inflow = 0.17 cfs @ 12.08 hrs, Volume= 635 cf
Outflow = 0.16 cfs @ 12.15 hrs, Volume= 635 cf, Atten= 6%, Lag= 4.2 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Max. Velocity= 1.01 fps, Min. Travel Time= 2.5 min
Avg. Velocity = 0.32 fps, Avg. Travel Time= 7.7 min

Peak Storage= 24 cf @ 12.11 hrs
Average Depth at Peak Storage= 0.07"
Bank-Full Depth= 1.00' Flow Area= 4.0 sf, Capacity= 17.43 cfs

Custom cross-section, Length= 150.0' Slope= 0.0200 '/
Constant n= 0.035 Earth, dense weeds
Inlet Invert= 85.00', Outlet Invert= 82.00'



Offset (feet)	Elevation (feet)	Chan.Depth (feet)	Depth (feet)	End Area (sq-ft)	Perim. (feet)	Storage (cubic-feet)	Discharge (cfs)
-3.00	1.00	0.00	0.00	0.0	2.0	0	0.00
-1.00	0.00	1.00	1.00	4.0	6.5	600	17.43
1.00	0.00	1.00	1.00				
3.00	1.00	0.00					

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.30"

Printed 12/9/2022

Page 52

Summary for Pond SB: Post - Settling Basin

Inflow Area = 25,705 sf, 42.37% Impervious, Inflow Depth = 1.36" for 2-yr event
Inflow = 0.35 cfs @ 12.17 hrs, Volume= 2,907 cf
Outflow = 0.33 cfs @ 12.26 hrs, Volume= 2,687 cf, Atten= 6%, Lag= 5.2 min
Primary = 0.33 cfs @ 12.26 hrs, Volume= 2,687 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Peak Elev= 82.10' @ 12.24 hrs Surf.Area= 355 sf Storage= 253 cf

Plug-Flow detention time= 123.1 min calculated for 2,686 cf (92% of inflow)
Center-of-Mass det. time= 42.7 min (1,221.5 - 1,178.8)

Volume	Invert	Avail.Storage	Storage Description
#1	81.00'	416 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
81.00	108	0	0
82.00	331	220	220
82.50	456	197	416

Device	Routing	Invert	Outlet Devices
#1	Primary	82.00'	4.0' long x 2.0' breadth Broad-Crested Rectangular Weir
			Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50
			Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32

Primary OutFlow Max=0.30 cfs @ 12.26 hrs HW=82.10' (Free Discharge)
1-Broad-Crested Rectangular Weir (Weir Controls 0.30 cfs @ 0.79 fps)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.30"

Printed 12/9/2022

Page 53

Summary for Pond US1: Post - Recharge System-1

Inflow Area = 5,112 sf, 100.00% Impervious, Inflow Depth = 3.07" for 2-yr event
Inflow = 0.38 cfs @ 12.07 hrs, Volume= 1,307 cf
Outflow = 0.19 cfs @ 12.21 hrs, Volume= 1,307 cf, Atten= 50%, Lag= 8.2 min
Discarded = 0.01 cfs @ 8.08 hrs, Volume= 806 cf
Primary = 0.18 cfs @ 12.21 hrs, Volume= 501 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Peak Elev= 85.11' @ 12.21 hrs Surf.Area= 715 sf Storage= 461 cf
Flood Elev= 86.30' Surf.Area= 715 sf Storage= 837 cf

Plug-Flow detention time= 237.9 min calculated for 1,306 cf (100% of inflow)
Center-of-Mass det. time= 238.1 min (992.9 - 754.8)

Volume	Invert	Avail. Storage	Storage Description
#1A	84.00'	405 cf	21.50"W x 33.25'L x 2.33'H Field A 1,668 cf Overall - 439 cf Embedded = 1,229 cf x 33.0% Voids
#2A	84.50'	439 cf	Infiltrator H-20 Chamber x 30 Inside #1 Effective Size= 27.5"W x 14.0"H => 2.34 sf x 6.25'L = 14.6 cf Overall Size= 34.0"W x 16.0"H x 6.25'L
		845 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	84.00'	0.500 in/hr Exfiltration over Surface area
#2	Primary	84.85'	6.0" Round Culvert L= 12.0' RCP, sq. cut end projecting, Ke= 0.500 Inlet / Outlet Invert= 84.85' / 84.60' S= 0.0208 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf

Discarded OutFlow Max=0.01 cfs @ 8.08 hrs HW=84.02' (Free Discharge)
↑ **1=Exfiltration** (Exfiltration Controls 0.01 cfs)

Primary OutFlow Max=0.18 cfs @ 12.21 hrs HW=85.11' (Free Discharge)
↑ **2=Culvert** (Inlet Controls 0.18 cfs @ 1.74 fps)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.30"

Printed 12/9/2022

Page 54

Summary for Pond US2: Post - Underground Storage System

Inflow Area = 4,658 sf, 100.00% Impervious, Inflow Depth = 3.07" for 2-yr event
Inflow = 0.35 cfs @ 12.07 hrs, Volume= 1,191 cf
Outflow = 0.17 cfs @ 12.21 hrs, Volume= 1,191 cf, Atten= 52%, Lag= 8.5 min
Primary = 0.17 cfs @ 12.21 hrs, Volume= 1,191 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Peak Elev= 83.48' @ 12.21 hrs Surf.Area= 1,041 sf Storage= 239 cf

Plug-Flow detention time= 33.5 min calculated for 1,191 cf (100% of inflow)
Center-of-Mass det. time= 32.8 min (787.7 - 754.8)

Volume	Invert	Avail.Storage	Storage Description
#1	83.15'	1,484 cf	18.0" Round Pipe Storage x 14 L= 60.0'

Device	Routing	Invert	Outlet Devices
#1	Primary	83.15'	4.0" Round Culvert L= 100.0' RCP, sq.cut end projecting, Ke= 0.500 Inlet / Outlet Invert= 83.15' / 82.10' S= 0.0105 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.09 sf

Primary OutFlow Max=0.17 cfs @ 12.21 hrs HW=83.48' (Free Discharge)
1=Culvert (Barrel Controls 0.17 cfs @ 2.45 fps)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=4.90"

Printed 12/9/2022

Page 55

Time span=0.00-72.00 hrs, dt=0.04 hrs, 1801 points

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv.

Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

Pond B1: Post - Dry Extended Detention Basin

Peak Elev=81.45' Storage=2,259 cf Inflow=2.88 cfs 12,754 cf
Primary=1.80 cfs 12,424 cf Secondary=0.00 cfs 0 cf Outflow=1.80 cfs 12,424 cf

Pond BR1: Post - Bio-retention Basin-1

Peak Elev=85.91' Storage=1,474 cf Inflow=1.01 cfs 3,815 cf
Primary=0.63 cfs 1,542 cf Secondary=0.02 cfs 2,013 cf Outflow=0.66 cfs 3,555 cf

Pond BR2: Post - Bio-retention Basin-2

Peak Elev=82.41' Storage=1,058 cf Inflow=1.66 cfs 7,690 cf
Primary=1.53 cfs 5,316 cf Secondary=0.02 cfs 2,300 cf Outflow=1.55 cfs 7,616 cf

Pond BR3: Post - Bio-retention Basin-3

Peak Elev=85.04' Storage=559 cf Inflow=0.57 cfs 3,215 cf
Primary=0.52 cfs 1,964 cf Secondary=0.05 cfs 1,194 cf Outflow=0.57 cfs 3,158 cf

Pond BR4: Post - Bio-retention Basin-4

Peak Elev=83.90' Storage=297 cf Inflow=0.48 cfs 1,685 cf
Outflow=0.46 cfs 1,430 cf

Pond DMH: post - DMH

Peak Elev=83.20' Inflow=0.45 cfs 3,094 cf
8.0" Round Culvert n=0.013 L=92.0' S=0.0087 '/' Outflow=0.45 cfs 3,094 cf

Pond FB1: Post - Forebay-1

Peak Elev=86.24' Storage=237 cf Inflow=0.89 cfs 3,444 cf
Outflow=0.88 cfs 3,272 cf

Pond FB2: Post - Forebay-2

Peak Elev=83.92' Storage=91 cf Inflow=0.41 cfs 1,510 cf
Outflow=0.40 cfs 1,434 cf

Pond FB3: Post - Forebay-3

Peak Elev=82.30' Storage=283 cf Inflow=1.28 cfs 6,491 cf
Outflow=1.26 cfs 6,299 cf

Pond pA1: Analysis Point - Post Dev Catch Basin in Hope St.

Inflow=0.52 cfs 1,964 cf
Primary=0.52 cfs 1,964 cf

Pond pA2: Analysis Point - Post Dev Flow to Wetland

Inflow=2.02 cfs 15,811 cf
Primary=2.02 cfs 15,811 cf

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=4.90"

Printed 12/9/2022

Page 56

Subcatchment pB1: Post - Runoff to Detention Basin-1

Runoff Area=2,690 sf 0.00% Impervious Runoff Depth=2.28"
Tc=5.0 min CN=74/0 Runoff=0.17 cfs 512 cf

Subcatchment pF1: Post - Runoff to Forebay-1

Runoff Area=12,569 sf 42.19% Impervious Runoff Depth=3.29"
Flow Length=126' Tc=10.0 min CN=74/98 Runoff=0.89 cfs 3,444 cf

Subcatchment pF2: Post - Runoff to Forebay-2

Runoff Area=4,810 sf 62.31% Impervious Runoff Depth=3.77"
Flow Length=64' Tc=8.0 min CN=74/98 Runoff=0.41 cfs 1,510 cf

Subcatchment pS1: Post - Runoff to Bio-retention Basin

Runoff Area=2,851 sf 0.00% Impervious Runoff Depth=2.28"
Tc=5.0 min CN=74/0 Runoff=0.18 cfs 543 cf

Subcatchment pS2: Post - Runoff to Swale-1

Runoff Area=5,173 sf 9.22% Impervious Runoff Depth=2.50"
Tc=5.0 min CN=74/98 Runoff=0.35 cfs 1,079 cf

Subcatchment pS3: Post - Flow to wetlands

Runoff Area=5,708 sf 0.00% Impervious Runoff Depth=2.28"
Flow Length=453' Tc=22.1 min CN=74/0 Runoff=0.22 cfs 1,087 cf

Subcatchment pS4: Post - Runoff to Bio-retention Basin-4

Runoff Area=1,321 sf 0.00% Impervious Runoff Depth=2.28"
Flow Length=64' Tc=8.0 min CN=74/0 Runoff=0.07 cfs 252 cf

Subcatchment pS5: Post - Runoff to Bio-retention Basin-2

Runoff Area=1,840 sf 12.93% Impervious Runoff Depth=2.59"
Tc=5.0 min CN=74/98 Runoff=0.13 cfs 398 cf

Subcatchment pS6: Post - Runoff to Forebay-3

Runoff Area=13,640 sf 32.91% Impervious Runoff Depth=3.07"
Tc=5.0 min CN=74/98 Runoff=1.08 cfs 3,487 cf

Subcatchment pS7: Post - Flow to Hope Street

Runoff Area=16,759 sf 0.73% Impervious Runoff Depth=2.30"
Flow Length=104' Tc=30.8 min CN=74/98 Runoff=0.57 cfs 3,215 cf

Subcatchment RF1: Post - Roof Area (Units 3&4)

Runoff Area=2,556 sf 100.00% Impervious Runoff Depth=4.66"
Tc=5.0 min CN=0/98 Runoff=0.29 cfs 993 cf

Subcatchment RF2: Post - Roof Area (Units 5&6)

Runoff Area=2,556 sf 100.00% Impervious Runoff Depth=4.66"
Tc=5.0 min CN=0/98 Runoff=0.29 cfs 993 cf

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=4.90"

Printed 12/9/2022

Page 57

Subcatchment RF3: Post - Roof Area (Units 7&8)

Runoff Area=2,556 sf 100.00% Impervious Runoff Depth=4.66"
Tc=5.0 min CN=0/98 Runoff=0.29 cfs 993 cf

Subcatchment RF4: Post- Roof Area (Units 9&10)

Runoff Area=2,102 sf 100.00% Impervious Runoff Depth=4.66"
Tc=5.0 min CN=0/98 Runoff=0.24 cfs 817 cf

Subcatchment RF5: Post - Roof Area (Units 1&2)

Runoff Area=2,556 sf 100.00% Impervious Runoff Depth=4.66"
Tc=5.0 min CN=0/98 Runoff=0.29 cfs 993 cf

Reach S1: Post - Dry Swale 1

Avg. Flow Depth=0.19' Max Vel=1.74 fps Inflow=0.78 cfs 2,622 cf
n=0.035 L=150.0' S=0.0200 '/' Capacity=17.43 cfs Outflow=0.77 cfs 2,622 cf

Pond SB: Post - Settling Basin

Peak Elev=82.22' Storage=298 cf Inflow=1.05 cfs 5,715 cf
Outflow=1.04 cfs 5,496 cf

Pond US1: Post - Recharge System-1

Peak Elev=85.30' Storage=552 cf Inflow=0.57 cfs 1,987 cf
Discarded=0.01 cfs 906 cf Primary=0.42 cfs 1,080 cf Outflow=0.43 cfs 1,987 cf

Pond US2: Post - Underground Storage System

Peak Elev=83.60' Storage=378 cf Inflow=0.52 cfs 1,810 cf
4.0" Round Culvert n=0.013 L=100.0' S=0.0105 '/' Outflow=0.21 cfs 1,810 cf

Total Runoff Area = 79,687 sf Runoff Volume = 20,316 cf Average Runoff Depth = 3.06"
67.43% Pervious = 53,735 sf 32.57% Impervious = 25,952 sf

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=4.90"

Printed 12/9/2022

Page 58

Summary for Pond B1: Post - Dry Extended Detention Basin

Inflow Area = 57,220 sf, 45.14% Impervious, Inflow Depth = 2.67" for 10-yr event
Inflow = 2.88 cfs @ 12.13 hrs, Volume= 12,754 cf
Outflow = 1.80 cfs @ 12.44 hrs, Volume= 12,424 cf, Atten= 37%, Lag= 18.8 min
Primary = 1.80 cfs @ 12.44 hrs, Volume= 12,424 cf
Secondary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs / 2
Peak Elev= 81.45' @ 12.44 hrs Surf.Area= 1,850 sf Storage= 2,259 cf
Flood Elev= 82.50' Surf.Area= 2,300 sf Storage= 4,432 cf

Plug-Flow detention time= 77.6 min calculated for 12,417 cf (97% of inflow)
Center-of-Mass det. time= 43.9 min (969.7 - 925.8)

Volume	Invert	Avail.Storage	Storage Description
#1	80.00'	4,432 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
80.00	1,273	0	0
81.00	1,660	1,467	1,467
82.00	2,080	1,870	3,337
82.50	2,300	1,095	4,432

Device	Routing	Invert	Outlet Devices
#1	Secondary	82.00'	4.0' long x 2.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32
#2	Primary	80.45'	8.0" Round Culvert L= 12.0' RCP, sq.cut end projecting, Ke= 0.500 Inlet / Outlet Invert= 80.45' / 79.50' S= 0.0792 '/' Cc= 0.900
#3	Primary	80.25'	n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.35 sf 4.0" Round Culvert L= 12.0' RCP, sq.cut end projecting, Ke= 0.500 Inlet / Outlet Invert= 80.25' / 79.50' S= 0.0625 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.09 sf

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=4.90"

Printed 12/9/2022

Page 59

Primary OutFlow Max=1.80 cfs @ 12.44 hrs HW=81.45' (Free Discharge)

└─2=Culvert (Inlet Controls 1.37 cfs @ 3.94 fps)

└─3=Culvert (Inlet Controls 0.43 cfs @ 4.90 fps)

Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=80.00' (Free Discharge)

└─1=Broad-Crested Rectangular Weir (Controls 0.00 cfs)

Summary for Pond BR1: Post - Bio-retention Basin-1

Inflow Area = 15,420 sf, 34.39% Impervious, Inflow Depth = 2.97" for 10-yr event
Inflow = 1.01 cfs @ 12.14 hrs, Volume= 3,815 cf
Outflow = 0.66 cfs @ 12.30 hrs, Volume= 3,555 cf, Atten= 35%, Lag= 9.3 min
Primary = 0.63 cfs @ 12.30 hrs, Volume= 1,542 cf
Secondary = 0.02 cfs @ 12.30 hrs, Volume= 2,013 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs / 2
Peak Elev= 85.91' @ 12.30 hrs Surf.Area= 2,076 sf Storage= 1,474 cf
Flood Elev= 86.00' Surf.Area= 2,110 sf Storage= 1,567 cf

Plug-Flow detention time= 383.7 min calculated for 3,555 cf (93% of inflow)
Center-of-Mass det. time= 347.2 min (1,164.2 - 817.0)

Volume	Invert	Avail.Storage	Storage Description
#1	85.00'	867 cf	Custom Stage Data (Prismatic) Listed below (Recalc)
#2	83.00'	694 cf	Filter Material (Prismatic) Listed below (Recalc)
#3	83.75'	7 cf	2,110 cf Overall - 7 cf Embedded = 2,103 cf x 33.0% Voids
		L= 35.0'	6.0" Round Pipe Storage Inside #2
		1,567 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
85.00	678	0	0
86.00	1,055	867	867

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=4.90"

Printed 12/9/2022

Page 60

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
83.00	1,055	0	0
85.00	1,055	2,110	2,110

Device Routing Invert Outlet Devices

#1	Primary	85.75'	4.0' long x 2.5' breadth Broad-Crested Rectangular Weir															
			Head (feet)	0.20	0.40	0.60	0.80	1.00	1.20	1.40	1.60	1.80	2.00	2.50	3.00	3.50	4.00	
			Coef. (English)	2.48	2.60	2.60	2.60	2.64	2.65	2.68	2.75	2.74	2.76	2.89	3.05	3.19	3.32	
#2	Device 3	83.00'	0.500 in/hr Exfiltration over Surface area Phase-In= 0.01'															
#3	Secondary	83.75'	6.0" Round Culvert L= 100.0' RCP, sq.cut end projecting, Ke= 0.500															
			Inlet / Outlet Invert= 83.75' / 82.85' S= 0.0090 '/' Cc= 0.900															
			n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf															

Primary OutFlow Max=0.62 cfs @ 12.30 hrs HW=85.91' (Free Discharge)

↑ **1=Broad-Crested Rectangular Weir** (Weir Controls 0.62 cfs @ 0.98 fps)

Secondary OutFlow Max=0.02 cfs @ 12.30 hrs HW=85.91' (Free Discharge)

↑ **3=Culvert** (Passes 0.02 cfs of 0.82 cfs potential flow)

↑ **2=Exfiltration** (Exfiltration Controls 0.02 cfs)

Summary for Pond BR2: Post - Bio-retention Basin-2

Inflow Area =	22,694 sf, 52.62% Impervious, Inflow Depth = 4.07" for 10-yr event
Inflow =	1.66 cfs @ 12.09 hrs, Volume= 7,690 cf
Outflow =	1.55 cfs @ 12.12 hrs, Volume= 7,616 cf, Atten= 7%, Lag= 1.9 min
Primary =	1.53 cfs @ 12.12 hrs, Volume= 5,316 cf
Secondary =	0.02 cfs @ 12.12 hrs, Volume= 2,300 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs / 2

Peak Elev= 82.41' @ 12.12 hrs Surf.Area= 1,767 sf Storage= 1,058 cf

Flood Elev= 82.50' Surf.Area= 1,796 sf Storage= 1,140 cf

Plug-Flow detention time= 171.3 min calculated for 7,616 cf (99% of inflow)

Center-of-Mass det. time= 159.2 min (1,039.9 - 880.7)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=4.90"

Printed 12/9/2022

Page 61

Volume	Invert	Avail. Storage	Storage Description
#1	81.35'	836 cf	Custom Stage Data (Prismatic) Listed below (Recalc)
#2	80.35'	292 cf	Filter Material (Prismatic) Listed below (Recalc)
			898 cf Overall - 12 cf Embedded = 886 cf x 33.0% Voids
#3	80.60'	12 cf	6.0" Round Pipe Storage Inside #2
			L= 61.0'
		1,140 cf	Total Available Storage

Elevation (feet)	Surf. Area (sq-ft)	Inc. Store (cubic-feet)	Cum. Store (cubic-feet)
81.35	563	0	0
82.00	745	425	425
82.50	898	411	836

Elevation (feet)	Surf. Area (sq-ft)	Inc. Store (cubic-feet)	Cum. Store (cubic-feet)
80.35	898	0	0
81.35	898	898	898

Device	Routing	Invert	Outlet Devices
#1	Primary	82.10'	3.5' long x 2.0' breadth Broad-Crested Rectangular Weir
			Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50
			Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32
#2	Device 3	80.35'	0.500 in/hr Exfiltration over Surface area Phase-In= 0.01'
#3	Secondary	80.60'	6.0" Round Culvert L= 62.0' RCP, sq. cut end projecting, Ke= 0.500
			Inlet / Outlet Invert= 80.60' / 79.00' S= 0.0258 '/' Cc= 0.900
			n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf

Primary OutFlow Max=1.53 cfs @ 12.12 hrs HW=82.41' (Free Discharge)

↑ **1=Broad-Crested Rectangular Weir** (Weir Controls 1.53 cfs @ 1.43 fps)

Secondary OutFlow Max=0.02 cfs @ 12.12 hrs HW=82.41' (Free Discharge)

↑ **3=Culvert** (Passes 0.02 cfs of 1.06 cfs potential flow)

↑ **2=Exfiltration** (Exfiltration Controls 0.02 cfs)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=4.90"

Printed 12/9/2022

Page 62

Summary for Pond BR3: Post - Bio-retention Basin-3

Inflow Area = 16,759 sf, 0.73% Impervious, Inflow Depth = 2.30" for 10-yr event
Inflow = 0.57 cfs @ 12.44 hrs, Volume= 3,215 cf
Outflow = 0.57 cfs @ 12.46 hrs, Volume= 3,158 cf, Atten= 0%, Lag= 1.0 min
Primary = 0.52 cfs @ 12.46 hrs, Volume= 1,964 cf
Secondary = 0.05 cfs @ 12.46 hrs, Volume= 1,194 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Peak Elev= 85.04' @ 12.46 hrs Surf.Area= 1,344 sf Storage= 559 cf

Plug-Flow detention time= 164.1 min calculated for 3,158 cf (98% of inflow)
Center-of-Mass det. time= 153.5 min (1,013.6 - 860.1)

Volume	Invert	Avail.Storage	Storage Description
#1	84.40'	371 cf	Custom Stage Data (Prismatic) Listed below (Recalc)
#2	83.40'	224 cf	Filter Material (Prismatic) Listed below (Recalc)
#3	83.65'	6 cf	686 cf Overall - 6 cf Embedded = 680 cf x 33.0% Voids
		6.0" Round Pipe Storage	Inside #2
		L= 30.0'	
		601 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
84.40	374	0	0
85.10	686	371	371

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
83.40	686	0	0
84.40	686	686	686

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=4.90"

Printed 12/9/2022

Page 63

Device Routing Invert Outlet Devices

#1	Primary	84.95'	8.0' long x 2.0' breadth Broad-Crested Rectangular Weir													
			Head (feet)	0.20	0.40	0.60	0.80	1.00	1.20	1.40	1.60	1.80	2.00	2.50	3.00	3.50
			Coef. (English)	2.54	2.61	2.61	2.60	2.66	2.70	2.77	2.89	2.88	2.85	3.07	3.20	3.32
#2	Device 3	85.00'	6.0" Horiz. Orifice/Grate C= 0.600 Limited to weir flow at low heads													
#3	Secondary	83.65'	6.0" Round Culvert L= 68.0' RCP, sq.cut end projecting, Ke= 0.500													
			Inlet / Outlet Invert= 83.65' / 83.00' S= 0.0096 '/' Cc= 0.900													
			n= 0.013 Concrete pipe, bends & connections, Flow Area= 0.20 sf													
#4	Device 3	83.40'	0.500 in/hr Exfiltration over Surface area Phase-In= 0.01'													

Primary OutFlow Max=0.52 cfs @ 12.46 hrs HW=85.04' (Free Discharge)

└─1=Broad-Crested Rectangular Weir (Weir Controls 0.52 cfs @ 0.75 fps)

Secondary OutFlow Max=0.05 cfs @ 12.46 hrs HW=85.04' (Free Discharge)

└─3=Culvert (Passes 0.05 cfs of 0.74 cfs potential flow)

└─2=Orifice/Grate (Weir Controls 0.04 cfs @ 0.63 fps)

└─4=Exfiltration (Exfiltration Controls 0.02 cfs)

Summary for Pond BR4: Post - Bio-retention Basin-4

Inflow Area =	6,131 sf, 48.88% Impervious, Inflow Depth = 3.30" for 10-yr event
Inflow =	0.48 cfs @ 12.12 hrs, Volume= 1,685 cf
Outflow =	0.46 cfs @ 12.14 hrs, Volume= 1,430 cf, Atten= 3%, Lag= 1.0 min
Primary =	0.46 cfs @ 12.14 hrs, Volume= 1,430 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs / 2

Peak Elev= 83.90' @ 12.14 hrs Surf.Area= 581 sf Storage= 297 cf

Flood Elev= 84.00' Surf.Area= 594 sf Storage= 325 cf

Plug-Flow detention time= 102.0 min calculated for 1,430 cf (85% of inflow)

Center-of-Mass det. time= 37.2 min (840.0 - 802.8)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=4.90"

Printed 12/9/2022

Page 64

Volume	Invert	Avail.Storage	Storage Description
#1	83.00'	227 cf	Custom Stage Data (Prismatic) Listed below (Recalc)
#2	82.00'	98 cf	Filter Material (Prismatic) Listed below (Recalc)
		297 cf Overall x 33.0% Voids	
		325 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
83.00	157	0	0
84.00	297	227	227

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
82.00	297	0	0
83.00	297	297	297

Device	Routing	Invert	Outlet Devices
#1	Primary	83.75'	3.0' long x 2.0' breadth Broad-Crested Rectangular Weir
Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50			
Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32			

Primary OutFlow Max=0.46 cfs @ 12.14 hrs HW=83.90' (Free Discharge)

1-Broad-Crested Rectangular Weir (Weir Controls 0.46 cfs @ 0.99 fps)

Summary for Pond DMH: post - DMH

Inflow Area = 5,112 sf, 100.00% Impervious, Inflow Depth = 7.26" for 10-yr event
Inflow = 0.45 cfs @ 12.14 hrs, Volume= 3,094 cf
Outflow = 0.45 cfs @ 12.14 hrs, Volume= 3,094 cf, Atten= 0%, Lag= 0.0 min
Primary = 0.45 cfs @ 12.14 hrs, Volume= 3,094 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

Peak Elev= 83.20' @ 12.14 hrs

Flood Elev= 85.00'

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=4.90"

Printed 12/9/2022

Page 65

Device	Routing	Invert	Outlet Devices
#1	Primary	82.80'	8.0" Round Culvert L= 92.0' RCP, sq.cut end projecting, Ke= 0.500 Inlet / Outlet Invert= 82.80' / 82.00' S= 0.0087 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.35 sf

Primary OutFlow Max=0.44 cfs @ 12.14 hrs HW=83.20' (Free Discharge)
1=Culvert (Barrel Controls 0.44 cfs @ 2.89 fps)

Summary for Pond FB1: Post - Forebay-1

Inflow Area = 12,569 sf, 42.19% Impervious, Inflow Depth = 3.29" for 10-yr event
Inflow = 0.89 cfs @ 12.14 hrs, Volume= 3,444 cf
Outflow = 0.88 cfs @ 12.16 hrs, Volume= 3,272 cf, Atten= 1%, Lag= 1.1 min
Primary = 0.88 cfs @ 12.16 hrs, Volume= 3,272 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Peak Elev= 86.24' @ 12.16 hrs Surf.Area= 297 sf Storage= 237 cf
Flood Elev= 86.50' Surf.Area= 350 sf Storage= 323 cf

Plug-Flow detention time= 53.9 min calculated for 3,270 cf (95% of inflow)
Center-of-Mass det. time= 25.3 min (813.6 - 788.2)

Volume	Invert	Avail.Storage	Storage Description
#1	85.00'	323 cf	Custom Stage Data (Prismatic) Listed below (Recalc)
Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
85.00	95	0	0
86.00	250	173	173
86.50	350	150	323

Device	Routing	Invert	Outlet Devices
#1	Primary	86.00'	3.0' long x 2.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=4.90"

Printed 12/9/2022

Page 66

Primary OutFlow Max=0.88 cfs @ 12.16 hrs HW=86.24' (Free Discharge)
1-Broad-Crested Rectangular Weir (Weir Controls 0.88 cfs @ 1.24 fps)

Summary for Pond FB2: Post - Forebay-2

Inflow Area = 4,810 sf, 62.31% Impervious, Inflow Depth = 3.77" for 10-yr event
Inflow = 0.41 cfs @ 12.11 hrs, Volume= 1,510 cf
Outflow = 0.40 cfs @ 12.12 hrs, Volume= 1,434 cf, Atten= 1%, Lag= 0.4 min
Primary = 0.40 cfs @ 12.12 hrs, Volume= 1,434 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs / 2
Peak Elev= 83.92' @ 12.12 hrs Surf.Area= 136 sf Storage= 91 cf
Flood Elev= 84.00' Surf.Area= 143 sf Storage= 103 cf

Plug-Flow detention time= 54.3 min calculated for 1,433 cf (95% of inflow)
Center-of-Mass det. time= 25.4 min (796.2 - 770.8)

Volume	Invert	Avail.Storage	Storage Description
#1	83.00'	103 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
83.00	63	0	0
84.00	143	103	103

Device	Routing	Invert	Outlet Devices
#1	Primary	83.80'	4.0' long x 2.0' breadth Broad-Crested Rectangular Weir
			Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50
			Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32

Primary OutFlow Max=0.40 cfs @ 12.12 hrs HW=83.92' (Free Discharge)
1-Broad-Crested Rectangular Weir (Weir Controls 0.40 cfs @ 0.87 fps)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=4.90"

Printed 12/9/2022

Page 67

Summary for Pond FB3: Post - Forebay-3

Inflow Area = 18,298 sf, 49.99% Impervious, Inflow Depth = 4.26" for 10-yr event
Inflow = 1.28 cfs @ 12.08 hrs, Volume= 6,491 cf
Outflow = 1.26 cfs @ 12.09 hrs, Volume= 6,299 cf, Atten= 2%, Lag= 0.9 min
Primary = 1.26 cfs @ 12.09 hrs, Volume= 6,299 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Peak Elev= 82.30' @ 12.09 hrs Surf.Area= 345 sf Storage= 283 cf
Flood Elev= 82.50' Surf.Area= 400 sf Storage= 358 cf

Plug-Flow detention time= 52.4 min calculated for 6,295 cf (97% of inflow)
Center-of-Mass det. time= 20.0 min (905.8 - 885.8)

Volume	Invert	Avail.Storage	Storage Description
#1	81.00'	358 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
81.00	121	0	0
82.00	263	192	192
82.50	400	166	358

Device	Routing	Invert	Outlet Devices
#1	Primary	82.00'	3.0' long x 2.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32

Primary OutFlow Max=1.23 cfs @ 12.09 hrs HW=82.29' (Free Discharge)
1-Broad-Crested Rectangular Weir (Weir Controls 1.23 cfs @ 1.40 fps)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=4.90"

Printed 12/9/2022

Page 68

Summary for Pond pA1: Analysis Point - Post Dev Catch Basin in Hope St.

Inflow Area = 16,759 sf, 0.73% Impervious, Inflow Depth = 1.41" for 10-yr event
Inflow = 0.52 cfs @ 12.46 hrs, Volume= 1,964 cf
Primary = 0.52 cfs @ 12.46 hrs, Volume= 1,964 cf, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

Summary for Pond pA2: Analysis Point - Post Dev Flow to Wetland

Inflow Area = 62,928 sf, 41.05% Impervious, Inflow Depth = 3.01" for 10-yr event
Inflow = 2.02 cfs @ 12.41 hrs, Volume= 15,811 cf
Primary = 2.02 cfs @ 12.41 hrs, Volume= 15,811 cf, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

Summary for Subcatchment pB1: Post - Runoff to Detention Basin-1

Runoff = 0.17 cfs @ 12.08 hrs, Volume= 512 cf, Depth= 2.28"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 10-yr Rainfall=4.90"

Area (sf)	CN	Description
2,690	74	>75% Grass cover, Good, HSG C
0	98	Paved parking, HSG C
0	98	Walkway
0	98	Roofs, HSG C
2,690	74	Weighted Average
2,690	74	100.00% Pervious Area

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=4.90"

Printed 12/9/2022

Page 69

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry, AB

Summary for Subcatchment pF1: Post - Runoff to Forebay-1

Runoff = 0.89 cfs @ 12.14 hrs, Volume= 3,444 cf, Depth= 3.29"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 10-yr Rainfall=4.90"

Area (sf)	CN	Description
4,205	98	Paved parking, HSG C
7,266	74	>75% Grass cover, Good, HSG C
* 979	98	Walkway
* 119	98	Patio/Deck/Stairs
12,569	84	Weighted Average
7,266	74	57.81% Pervious Area
5,303	98	42.19% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.5	44	0.0300	0.08		Sheet Flow, AB
					Grass: Bermuda n= 0.410 P2= 3.30"
0.5	82	0.0180	2.72		Shallow Concentrated Flow, BC
					Paved Kv= 20.3 fps
10.0	126	Total			

Summary for Subcatchment pF2: Post - Runoff to Forebay-2

Runoff = 0.41 cfs @ 12.11 hrs, Volume= 1,510 cf, Depth= 3.77"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 10-yr Rainfall=4.90"

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=4.90"

Printed 12/9/2022

Page 70

Area (sf)		CN	Description		
*	1,813	74	>75% Grass cover, Good, HSG C		
	2,847	98	Paved parking, HSG C		
	150	98	Walkway		
	0	98	Roofs, HSG C		
4,810		89	Weighted Average		
1,813		74	37.69% Pervious Area		
2,997		98	62.31% Impervious Area		
Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.9	40	0.0400	0.08		Sheet Flow, AB
					Grass: Bermuda n= 0.410 P2= 3.30"
0.1	24	0.0200	2.87		Shallow Concentrated Flow, BC
					Paved Kv= 20.3 fps

Summary for Subcatchment pS1: Post - Runoff to Bio-retention Basin

Runoff = 0.18 cfs @ 12.08 hrs, Volume= 543 cf, Depth= 2.28"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 10-yr Rainfall=4.90"

Area (sf)		CN	Description		
*	2,851	74	>75% Grass cover, Good, HSG C		
	0	98	Patio/Deck/Stairs		
	2,851	74	Weighted Average		
	2,851	74	100.00% Pervious Area		
Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0	Direct Entry, Runoff to swale				

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=4.90"

Printed 12/9/2022

Page 71

Summary for Subcatchment pS2: Post - Runoff to Swale-1

Runoff = 0.35 cfs @ 12.08 hrs, Volume= 1,079 cf, Depth= 2.50"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 10-yr Rainfall=4.90"

		Area (sf)	CN	Description	
*		0	98	Paved parking, HSG C	
		4,696	74	>75% Grass cover, Good, HSG C	
		0	98	Walkway	
		477	98	Patio/Deck/Stairs	
		5,173	76	Weighted Average	
		4,696	74	90.78% Pervious Area	
		477	98	9.22% Impervious Area	
Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
5.0	Direct Entry, Parking Runoff				

Summary for Subcatchment pS3: Post - Flow to wetlands

Runoff = 0.22 cfs @ 12.32 hrs, Volume= 1,087 cf, Depth= 2.28"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 10-yr Rainfall=4.90"

		Area (sf)	CN	Description
		5,708	74	>75% Grass cover, Good, HSG C
		0	98	Paved parking, HSG C
		0	70	Woods, Good, HSG C
		5,708	74	Weighted Average
		5,708	74	100.00% Pervious Area

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=4.90"

Printed 12/9/2022

Page 72

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.2	50	0.0260	0.07		Sheet Flow, AB Grass: Bermuda n= 0.410 P2= 3.30"
8.6	183	0.0050	0.35		Shallow Concentrated Flow, BC Woodland Kv= 5.0 fps
1.9	117	0.0400	1.00		Shallow Concentrated Flow, CD Woodland Kv= 5.0 fps
0.3	103	0.0300	5.33	26.67	Channel Flow, DE Area= 5.0 sf Perim= 10.2' r= 0.49' n= 0.030 Earth, grassed & winding
22.1	453	Total			

Summary for Subcatchment pS4: Post - Runoff to Bio-retention Basin-4

Runoff = 0.07 cfs @ 12.12 hrs, Volume= 252 cf, Depth= 2.28"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 10-yr Rainfall=4.90"

Area (sf)		CN	Description		
1,321		74	>75% Grass cover, Good, HSG C		
0		98	Paved parking, HSG C		
0		98	Walkway		
0		98	Roofs, HSG C		
1,321		74	Weighted Average		
1,321		74	100.00% Pervious Area		
Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.9	40	0.0400	0.08		Sheet Flow, AB Grass: Bermuda n= 0.410 P2= 3.30"
0.1	24	0.0200	2.87		Shallow Concentrated Flow, BC Paved Kv= 20.3 fps
8.0	64	Total			

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=4.90"

Printed 12/9/2022

Page 73

Summary for Subcatchment pS5: Post - Runoff to Bio-retention Basin-2

Runoff = 0.13 cfs @ 12.08 hrs, Volume= 398 cf, Depth= 2.59"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 10-yr Rainfall=4.90"

Area (sf)	CN	Description
0	98	Paved parking, HSG C
1,602	74	>75% Grass cover, Good, HSG C
0	98	Walkway
238	98	Patio/Deck/Stairs
0	98	Roofs, HSG C

1,840	77	Weighted Average
1,602	74	87.07% Pervious Area
238	98	12.93% Impervious Area

Tc Length Slope Velocity Capacity Description
(min) (feet) (ft/ft) (ft/sec) (cfs)

5.0

Direct Entry, AB

Summary for Subcatchment pS6: Post - Runoff to Forebay-3

Runoff = 1.08 cfs @ 12.08 hrs, Volume= 3,487 cf, Depth= 3.07"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 10-yr Rainfall=4.90"

Area (sf)	CN	Description
3,996	98	Paved parking, HSG C
9,151	74	>75% Grass cover, Good, HSG C
493	98	Walkway

13,640	82	Weighted Average
9,151	74	67.09% Pervious Area
4,489	98	32.91% Impervious Area

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=4.90"

Printed 12/9/2022

Page 74

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry, AB

Summary for Subcatchment pS7: Post - Flow to Hope Street

Runoff = 0.57 cfs @ 12.44 hrs, Volume= 3,215 cf, Depth= 2.30"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 10-yr Rainfall=4.90"

Area (sf)	CN	Description
16,637	74	>75% Grass cover, Good, HSG C
0	98	Paved parking, HSG C
0	98	Walkways
122	98	Patio/Deck/Stairs
16,759	74	Weighted Average
16,637	74	99.27% Pervious Area
122	98	0.73% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
30.6	60	0.0030	0.03		Sheet Flow, AB Grass: Bermuda n= 0.410 P2= 3.30"
0.2	44	0.0450	3.42		Shallow Concentrated Flow, BC Unpaved Kv= 16.1 fps
30.8	104	Total			

Summary for Subcatchment RF1: Post - Roof Area (Units 3&4)

Runoff = 0.29 cfs @ 12.07 hrs, Volume= 993 cf, Depth= 4.66"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 10-yr Rainfall=4.90"

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=4.90"

Printed 12/9/2022

Page 75

Area (sf)	CN	Description
2,556	98	Roofs, HSG C
2,556	98	100.00% Impervious Area
Tc (min)	Length (feet)	Slope (ft/ft) Velocity (ft/sec) Capacity (cfs) Description

5.0

Direct Entry, Roof Runoff

Summary for Subcatchment RF2: Post - Roof Area (Units 5&6)

Runoff = 0.29 cfs @ 12.07 hrs, Volume= 993 cf, Depth= 4.66"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 10-yr Rainfall=4.90"

Area (sf)	CN	Description
2,556	98	Roofs, HSG C
2,556	98	100.00% Impervious Area
Tc (min)	Length (feet)	Slope (ft/ft) Velocity (ft/sec) Capacity (cfs) Description

5.0

Direct Entry, Roof Runoff

Summary for Subcatchment RF3: Post - Roof Area (Units 7&8)

Runoff = 0.29 cfs @ 12.07 hrs, Volume= 993 cf, Depth= 4.66"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 10-yr Rainfall=4.90"

Area (sf)	CN	Description
2,556	98	Roofs, HSG C
2,556	98	100.00% Impervious Area

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=4.90"

Printed 12/9/2022

Page 76

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
-------------	------------------	------------------	----------------------	-------------------	-------------

5.0

Direct Entry, Roof Runoff

Summary for Subcatchment RF4: Post- Roof Area (Units 9&10)

Runoff = 0.24 cfs @ 12.07 hrs, Volume= 817 cf, Depth= 4.66"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 10-yr Rainfall=4.90"

Area (sf)	CN	Description
-----------	----	-------------

2,102	98	Roofs, HSG C
-------	----	--------------

2,102	98	100.00% Impervious Area
-------	----	-------------------------

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
-------------	------------------	------------------	----------------------	-------------------	-------------

5.0

Direct Entry, Roof Runoff

Summary for Subcatchment RF5: Post - Roof Area (Units 1&2)

Runoff = 0.29 cfs @ 12.07 hrs, Volume= 993 cf, Depth= 4.66"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 10-yr Rainfall=4.90"

Area (sf)	CN	Description
-----------	----	-------------

2,556	98	Roofs, HSG C
-------	----	--------------

2,556	98	100.00% Impervious Area
-------	----	-------------------------

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
-------------	------------------	------------------	----------------------	-------------------	-------------

5.0

Direct Entry, Roof Runoff

Summary for Reach S1: Post - Dry Swale 1


Inflow Area = 20,593 sf, 28.07% Impervious, Inflow Depth = 1.53" for 10-yr event
Inflow = 0.78 cfs @ 12.29 hrs, Volume= 2,622 cf
Outflow = 0.77 cfs @ 12.34 hrs, Volume= 2,622 cf, Atten= 1%, Lag= 2.7 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

Max. Velocity= 1.74 fps, Min. Travel Time= 1.4 min
Avg. Velocity = 0.41 fps, Avg. Travel Time= 6.1 min

Peak Storage= 66 cf @ 12.32 hrs
Average Depth at Peak Storage= 0.19'
Bank-Full Depth= 1.00' Flow Area= 4.0 sf, Capacity= 17.43 cfs

Custom cross-section, Length= 150.0' Slope= 0.0200 '/
Constant n= 0.035 Earth, dense weeds
Inlet Invert= 85.00', Outlet Invert= 82.00'



Offset (feet)	Elevation (feet)	Chan.Depth (feet)	Depth (feet)	End Area (sq-ft)	Perim. (feet)	Storage (cubic-feet)	Discharge (cfs)
-3.00	1.00	0.00	0.00	0.0	2.0	0	0.00
-1.00	0.00	1.00	1.00	4.0	6.5	600	17.43
1.00	0.00	1.00					
3.00	1.00	0.00					

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=4.90"

Printed 12/9/2022

Page 78

Summary for Pond SB: Post - Settling Basin

Inflow Area = 25,705 sf, 42.37% Impervious, Inflow Depth = 2.67" for 10-yr event
Inflow = 1.05 cfs @ 12.33 hrs, Volume= 5,715 cf
Outflow = 1.04 cfs @ 12.35 hrs, Volume= 5,496 cf, Atten= 1%, Lag= 1.2 min
Primary = 1.04 cfs @ 12.35 hrs, Volume= 5,496 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Peak Elev= 82.22' @ 12.35 hrs Surf.Area= 385 sf Storage= 298 cf

Plug-Flow detention time= 68.4 min calculated for 5,496 cf (96% of inflow)
Center-of-Mass det. time= 17.5 min (1,046.1 - 1,028.6)

Volume	Invert	Avail.Storage	Storage Description
#1	81.00'	416 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
81.00	108	0	0
82.00	331	220	220
82.50	456	197	416

Device	Routing	Invert	Outlet Devices
#1	Primary	82.00'	4.0' long x 2.0' breadth Broad-Crested Rectangular Weir
			Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50
			Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32

Primary OutFlow Max=1.03 cfs @ 12.35 hrs HW=82.22' (Free Discharge)
1-Broad-Crested Rectangular Weir (Weir Controls 1.03 cfs @ 1.19 fps)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=4.90"

Printed 12/9/2022

Page 79

Summary for Pond US1: Post - Recharge System-1

Inflow Area = 5,112 sf, 100.00% Impervious, Inflow Depth = 4.66" for 10-yr event
Inflow = 0.57 cfs @ 12.07 hrs, Volume= 1,987 cf
Outflow = 0.43 cfs @ 12.14 hrs, Volume= 1,987 cf, Atten= 25%, Lag= 4.0 min
Discarded = 0.01 cfs @ 6.40 hrs, Volume= 906 cf
Primary = 0.42 cfs @ 12.14 hrs, Volume= 1,080 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Peak Elev= 85.30' @ 12.14 hrs Surf.Area= 715 sf Storage= 552 cf
Flood Elev= 86.30' Surf.Area= 715 sf Storage= 837 cf

Plug-Flow detention time= 188.1 min calculated for 1,985 cf (100% of inflow)
Center-of-Mass det. time= 188.3 min (935.7 - 747.4)

Volume	Invert	Avail.Storage	Storage Description
#1A	84.00'	405 cf	21.50"W x 33.25'L x 2.33'H Field A 1,668 cf Overall - 439 cf Embedded = 1,229 cf x 33.0% Voids
#2A	84.50'	439 cf	Infiltrator H-20 Chamber x 30 Inside #1 Effective Size= 27.5"W x 14.0"H => 2.34 sf x 6.25'L = 14.6 cf Overall Size= 34.0"W x 16.0"H x 6.25'L
		845 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	84.00'	0.500 in/hr Exfiltration over Surface area
#2	Primary	84.85'	6.0" Round Culvert L= 12.0' RCP, sq.cut end projecting, Ke= 0.500 Inlet / Outlet Invert= 84.85' / 84.60' S= 0.0208 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf

Discarded OutFlow Max=0.01 cfs @ 6.40 hrs HW=84.02' (Free Discharge)
↑ **1=Exfiltration** (Exfiltration Controls 0.01 cfs)

Primary OutFlow Max=0.42 cfs @ 12.14 hrs HW=85.29' (Free Discharge)
↑ **2=Culvert** (Inlet Controls 0.42 cfs @ 2.27 fps)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=4.90"

Printed 12/9/2022

Page 80

Summary for Pond US2: Post - Underground Storage System

Inflow Area = 4,658 sf, 100.00% Impervious, Inflow Depth = 4.66" for 10-yr event
Inflow = 0.52 cfs @ 12.07 hrs, Volume= 1,810 cf
Outflow = 0.21 cfs @ 12.50 hrs, Volume= 1,810 cf, Atten= 61%, Lag= 25.5 min
Primary = 0.21 cfs @ 12.50 hrs, Volume= 1,810 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Peak Elev= 83.60' @ 12.29 hrs Surf.Area= 1,157 sf Storage= 378 cf

Plug-Flow detention time= 31.6 min calculated for 1,809 cf (100% of inflow)
Center-of-Mass det. time= 31.7 min (779.2 - 747.4)

Volume	Invert	Avail.Storage	Storage Description
#1	83.15'	1,484 cf	18.0" Round Pipe Storage x 14 L= 60.0'

Device	Routing	Invert	Outlet Devices
#1	Primary	83.15'	4.0" Round Culvert L= 100.0' RCP, sq.cut end projecting, Ke= 0.500 Inlet / Outlet Invert= 83.15' / 82.10' S= 0.0105 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.09 sf

Primary OutFlow Max=0.21 cfs @ 12.50 hrs HW=83.57' (Free Discharge)
1=Culvert (Barrel Controls 0.21 cfs @ 2.42 fps)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.10"

Printed 12/9/2022

Page 81

Time span=0.00-72.00 hrs, dt=0.04 hrs, 1801 points

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv.

Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

Pond B1: Post - Dry Extended Detention Basin

Peak Elev=82.07' Storage=3,485 cf Inflow=4.24 cfs 17,915 cf
Primary=2.45 cfs 17,488 cf Secondary=0.19 cfs 97 cf Outflow=2.64 cfs 17,584 cf

Pond BR1: Post - Bio-retention Basin-1

Peak Elev=85.99' Storage=1,562 cf Inflow=1.37 cfs 5,174 cf
Primary=1.21 cfs 2,777 cf Secondary=0.02 cfs 2,138 cf Outflow=1.24 cfs 4,915 cf

Pond BR2: Post - Bio-retention Basin-2

Peak Elev=82.47' Storage=1,110 cf Inflow=2.17 cfs 9,891 cf
Primary=2.02 cfs 7,444 cf Secondary=0.02 cfs 2,374 cf Outflow=2.04 cfs 9,818 cf

Pond BR3: Post - Bio-retention Basin-3

Peak Elev=85.06' Storage=574 cf Inflow=0.83 cfs 4,592 cf
Primary=0.73 cfs 3,214 cf Secondary=0.09 cfs 1,321 cf Outflow=0.82 cfs 4,535 cf

Pond BR4: Post - Bio-retention Basin-4

Peak Elev=83.94' Storage=306 cf Inflow=0.63 cfs 2,242 cf
Outflow=0.61 cfs 1,987 cf

Pond DMH: post - DMH

Peak Elev=83.26' Inflow=0.55 cfs 3,681 cf
8.0" Round Culvert n=0.013 L=92.0' S=0.0087 '/' Outflow=0.55 cfs 3,681 cf

Pond FB1: Post - Forebay-1

Peak Elev=86.29' Storage=252 cf Inflow=1.19 cfs 4,570 cf
Outflow=1.18 cfs 4,397 cf

Pond FB2: Post - Forebay-2

Peak Elev=83.94' Storage=94 cf Inflow=0.53 cfs 1,958 cf
Outflow=0.52 cfs 1,882 cf

Pond FB3: Post - Forebay-3

Peak Elev=82.35' Storage=303 cf Inflow=1.67 cfs 8,282 cf
Outflow=1.64 cfs 8,090 cf

Pond pA1: Analysis Point - Post Dev Catch Basin in Hope St.

Inflow=0.73 cfs 3,214 cf
Primary=0.73 cfs 3,214 cf

Pond pA2: Analysis Point - Post Dev Flow to Wetland

Inflow=2.96 cfs 21,513 cf
Primary=2.96 cfs 21,513 cf

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.10"

Printed 12/9/2022

Page 82

Subcatchment pB1: Post - Runoff to Detention Basin-1

Runoff Area=2,690 sf 0.00% Impervious Runoff Depth=3.27"
Tc=5.0 min CN=74/0 Runoff=0.24 cfs 733 cf

Subcatchment pF1: Post - Runoff to Forebay-1

Runoff Area=12,569 sf 42.19% Impervious Runoff Depth=4.36"
Flow Length=126' Tc=10.0 min CN=74/98 Runoff=1.19 cfs 4,570 cf

Subcatchment pF2: Post - Runoff to Forebay-2

Runoff Area=4,810 sf 62.31% Impervious Runoff Depth=4.88"
Flow Length=64' Tc=8.0 min CN=74/98 Runoff=0.53 cfs 1,958 cf

Subcatchment pS1: Post - Runoff to Bio-retention Basin

Runoff Area=2,851 sf 0.00% Impervious Runoff Depth=3.27"
Tc=5.0 min CN=74/0 Runoff=0.26 cfs 777 cf

Subcatchment pS2: Post - Runoff to Swale-1

Runoff Area=5,173 sf 9.22% Impervious Runoff Depth=3.51"
Tc=5.0 min CN=74/98 Runoff=0.49 cfs 1,512 cf

Subcatchment pS3: Post - Flow to wetlands

Runoff Area=5,708 sf 0.00% Impervious Runoff Depth=3.27"
Flow Length=453' Tc=22.1 min CN=74/0 Runoff=0.32 cfs 1,555 cf

Subcatchment pS4: Post - Runoff to Bio-retention Basin-4

Runoff Area=1,321 sf 0.00% Impervious Runoff Depth=3.27"
Flow Length=64' Tc=8.0 min CN=74/0 Runoff=0.11 cfs 360 cf

Subcatchment pS5: Post - Runoff to Bio-retention Basin-2

Runoff Area=1,840 sf 12.93% Impervious Runoff Depth=3.60"
Tc=5.0 min CN=74/98 Runoff=0.18 cfs 553 cf

Subcatchment pS6: Post - Runoff to Forebay-3

Runoff Area=13,640 sf 32.91% Impervious Runoff Depth=4.12"
Tc=5.0 min CN=74/98 Runoff=1.45 cfs 4,686 cf

Subcatchment pS7: Post - Flow to Hope Street

Runoff Area=16,759 sf 0.73% Impervious Runoff Depth=3.29"
Flow Length=104' Tc=30.8 min CN=74/98 Runoff=0.83 cfs 4,592 cf

Subcatchment RF1: Post - Roof Area (Units 3&4)

Runoff Area=2,556 sf 100.00% Impervious Runoff Depth=5.86"
Tc=5.0 min CN=0/98 Runoff=0.36 cfs 1,249 cf

Subcatchment RF2: Post - Roof Area (Units 5&6)

Runoff Area=2,556 sf 100.00% Impervious Runoff Depth=5.86"
Tc=5.0 min CN=0/98 Runoff=0.36 cfs 1,249 cf

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.10"

Printed 12/9/2022

Page 83

Subcatchment RF3: Post - Roof Area (Units 7&8)

Runoff Area=2,556 sf 100.00% Impervious Runoff Depth=5.86"
Tc=5.0 min CN=0/98 Runoff=0.36 cfs 1,249 cf

Subcatchment RF4: Post- Roof Area (Units 9&10)

Runoff Area=2,102 sf 100.00% Impervious Runoff Depth=5.86"
Tc=5.0 min CN=0/98 Runoff=0.29 cfs 1,027 cf

Subcatchment RF5: Post - Roof Area (Units 1&2)

Runoff Area=2,556 sf 100.00% Impervious Runoff Depth=5.86"
Tc=5.0 min CN=0/98 Runoff=0.36 cfs 1,249 cf

Reach S1: Post - Dry Swale 1

Avg. Flow Depth=0.27' Max Vel=2.15 fps Inflow=1.49 cfs 4,289 cf
n=0.035 L=150.0' S=0.0200 '/' Capacity=17.43 cfs Outflow=1.48 cfs 4,289 cf

Pond SB: Post - Settling Basin

Peak Elev=82.33' Storage=342 cf Inflow=1.97 cfs 7,971 cf
Outflow=1.95 cfs 7,751 cf

Pond US1: Post - Recharge System-1

Peak Elev=85.41' Storage=600 cf Inflow=0.72 cfs 2,497 cf
Discarded=0.01 cfs 953 cf Primary=0.52 cfs 1,544 cf Outflow=0.53 cfs 2,497 cf

Pond US2: Post - Underground Storage System

Peak Elev=83.72' Storage=515 cf Inflow=0.65 cfs 2,275 cf
4.0" Round Culvert n=0.013 L=100.0' S=0.0105 '/' Outflow=0.21 cfs 2,275 cf

Total Runoff Area = 79,687 sf Runoff Volume = 27,316 cf Average Runoff Depth = 4.11"
67.43% Pervious = 53,735 sf 32.57% Impervious = 25,952 sf

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.10"

Printed 12/9/2022

Page 84

Summary for Pond B1: Post - Dry Extended Detention Basin

Inflow Area = 57,220 sf, 45.14% Impervious, Inflow Depth = 3.76" for 25-yr event
Inflow = 4.24 cfs @ 12.16 hrs, Volume= 17,915 cf
Outflow = 2.64 cfs @ 12.39 hrs, Volume= 17,584 cf, Atten= 38%, Lag= 13.9 min
Primary = 2.45 cfs @ 12.39 hrs, Volume= 17,488 cf
Secondary = 0.19 cfs @ 12.39 hrs, Volume= 97 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs / 2
Peak Elev= 82.07' @ 12.39 hrs Surf.Area= 2,111 sf Storage= 3,485 cf
Flood Elev= 82.50' Surf.Area= 2,300 sf Storage= 4,432 cf

Plug-Flow detention time= 63.8 min calculated for 17,584 cf (98% of inflow)
Center-of-Mass det. time= 37.7 min (932.8 - 895.0)

Volume	Invert	Avail.Storage	Storage Description
#1	80.00'	4,432 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
80.00	1,273	0	0
81.00	1,660	1,467	1,467
82.00	2,080	1,870	3,337
82.50	2,300	1,095	4,432

Device	Routing	Invert	Outlet Devices
#1	Secondary	82.00'	4.0' long x 2.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32
#2	Primary	80.45'	8.0" Round Culvert L= 12.0' RCP, sq.cut end projecting, Ke= 0.500 Inlet / Outlet Invert= 80.45' / 79.50' S= 0.0792 '/' Cc= 0.900
#3	Primary	80.25'	n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.35 sf 4.0" Round Culvert L= 12.0' RCP, sq.cut end projecting, Ke= 0.500 Inlet / Outlet Invert= 80.25' / 79.50' S= 0.0625 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.09 sf

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.10"

Printed 12/9/2022

Page 85

Primary OutFlow Max=2.45 cfs @ 12.39 hrs HW=82.07' (Free Discharge)

└─2=Culvert (Inlet Controls 1.91 cfs @ 5.46 fps)

└─3=Culvert (Inlet Controls 0.54 cfs @ 6.19 fps)

Secondary OutFlow Max=0.19 cfs @ 12.39 hrs HW=82.07' (Free Discharge)

└─1=Broad-Crested Rectangular Weir (Weir Controls 0.19 cfs @ 0.67 fps)

Summary for Pond BR1: Post - Bio-retention Basin-1

Inflow Area = 15,420 sf, 34.39% Impervious, Inflow Depth = 4.03" for 25-yr event
Inflow = 1.37 cfs @ 12.14 hrs, Volume= 5,174 cf
Outflow = 1.24 cfs @ 12.20 hrs, Volume= 4,915 cf, Atten= 9%, Lag= 3.6 min
Primary = 1.21 cfs @ 12.20 hrs, Volume= 2,777 cf
Secondary = 0.02 cfs @ 12.20 hrs, Volume= 2,138 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs / 2
Peak Elev= 85.99' @ 12.20 hrs Surf.Area= 2,108 sf Storage= 1,562 cf
Flood Elev= 86.00' Surf.Area= 2,110 sf Storage= 1,567 cf

Plug-Flow detention time= 299.3 min calculated for 4,912 cf (95% of inflow)
Center-of-Mass det. time= 272.0 min (1,081.0 - 808.9)

Volume	Invert	Avail.Storage	Storage Description
#1	85.00'	867 cf	Custom Stage Data (Prismatic) Listed below (Recalc)
#2	83.00'	694 cf	Filter Material (Prismatic) Listed below (Recalc)
#3	83.75'	7 cf	2,110 cf Overall - 7 cf Embedded = 2,103 cf x 33.0% Voids
		L= 35.0'	6.0" Round Pipe Storage Inside #2
		1,567 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
85.00	678	0	0
86.00	1,055	867	867

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.10"

Printed 12/9/2022

Page 86

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
83.00	1,055	0	0
85.00	1,055	2,110	2,110

Device Routing Invert Outlet Devices

#1	Primary	85.75'	4.0' long x 2.5' breadth Broad-Crested Rectangular Weir															
			Head (feet)	0.20	0.40	0.60	0.80	1.00	1.20	1.40	1.60	1.80	2.00	2.50	3.00	3.50	4.00	
			Coef. (English)	2.48	2.60	2.60	2.60	2.60	2.64	2.65	2.68	2.75	2.74	2.76	2.89	3.05	3.19	3.32
#2	Device 3	83.00'	0.500 in/hr Exfiltration over Surface area Phase-In= 0.01'															
#3	Secondary	83.75'	6.0" Round Culvert L= 100.0' RCP, sq.cut end projecting, Ke= 0.500															
			Inlet / Outlet Invert= 83.75' / 82.85' S= 0.0090 '/' Cc= 0.900															
			n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf															

Primary OutFlow Max=1.21 cfs @ 12.20 hrs HW=85.99' (Free Discharge)

↑ **1=Broad-Crested Rectangular Weir** (Weir Controls 1.21 cfs @ 1.24 fps)

Secondary OutFlow Max=0.02 cfs @ 12.20 hrs HW=85.99' (Free Discharge)

↑ **3=Culvert** (Passes 0.02 cfs of 0.84 cfs potential flow)

↑ **2=Exfiltration** (Exfiltration Controls 0.02 cfs)

Summary for Pond BR2: Post - Bio-retention Basin-2

Inflow Area =	22,694 sf, 52.62% Impervious, Inflow Depth = 5.23" for 25-yr event
Inflow =	2.17 cfs @ 12.09 hrs, Volume= 9,891 cf
Outflow =	2.04 cfs @ 12.12 hrs, Volume= 9,818 cf, Atten= 6%, Lag= 1.8 min
Primary =	2.02 cfs @ 12.12 hrs, Volume= 7,444 cf
Secondary =	0.02 cfs @ 12.12 hrs, Volume= 2,374 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs / 2

Peak Elev= 82.47' @ 12.12 hrs Surf.Area= 1,786 sf Storage= 1,110 cf

Flood Elev= 82.50' Surf.Area= 1,796 sf Storage= 1,140 cf

Plug-Flow detention time= 138.4 min calculated for 9,818 cf (99% of inflow)

Center-of-Mass det. time= 128.7 min (986.4 - 857.7)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.10"

Printed 12/9/2022

Page 87

Volume	Invert	Avail. Storage	Storage Description
#1	81.35'	836 cf	Custom Stage Data (Prismatic) Listed below (Recalc)
#2	80.35'	292 cf	Filter Material (Prismatic) Listed below (Recalc)
898 cf Overall - 12 cf Embedded = 886 cf x 33.0% Voids			
#3	80.60'	12 cf	6.0" Round Pipe Storage Inside #2
L= 61.0'			
		1,140 cf	Total Available Storage

Elevation (feet)	Surf. Area (sq-ft)	Inc. Store (cubic-feet)	Cum. Store (cubic-feet)
81.35	563	0	0
82.00	745	425	425
82.50	898	411	836

Elevation (feet)	Surf. Area (sq-ft)	Inc. Store (cubic-feet)	Cum. Store (cubic-feet)
80.35	898	0	0
81.35	898	898	898

Device	Routing	Invert	Outlet Devices
#1	Primary	82.10'	3.5' long x 2.0' breadth Broad-Crested Rectangular Weir
Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50			
Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32			
#2	Device 3	80.35'	0.500 in/hr Exfiltration over Surface area Phase-In= 0.01'
#3	Secondary	80.60'	6.0" Round Culvert L= 62.0' RCP, sq. cut end projecting, Ke= 0.500
Inlet / Outlet Invert= 80.60' / 79.00' S= 0.0258 '/' Cc= 0.900			
n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf			

Primary OutFlow Max=2.00 cfs @ 12.12 hrs HW=82.46' (Free Discharge)

↑ **1=Broad-Crested Rectangular Weir** (Weir Controls 2.00 cfs @ 1.57 fps)

Secondary OutFlow Max=0.02 cfs @ 12.12 hrs HW=82.46' (Free Discharge)

↑ **3=Culvert** (Passes 0.02 cfs of 1.07 cfs potential flow)

↑ **2=Exfiltration** (Exfiltration Controls 0.02 cfs)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.10"

Printed 12/9/2022

Page 88

Summary for Pond BR3: Post - Bio-retention Basin-3

Inflow Area = 16,759 sf, 0.73% Impervious, Inflow Depth = 3.29" for 25-yr event
Inflow = 0.83 cfs @ 12.43 hrs, Volume= 4,592 cf
Outflow = 0.82 cfs @ 12.45 hrs, Volume= 4,535 cf, Atten= 0%, Lag= 0.9 min
Primary = 0.73 cfs @ 12.45 hrs, Volume= 3,214 cf
Secondary = 0.09 cfs @ 12.45 hrs, Volume= 1,321 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Peak Elev= 85.06' @ 12.45 hrs Surf.Area= 1,354 sf Storage= 574 cf

Plug-Flow detention time= 119.0 min calculated for 4,535 cf (99% of inflow)
Center-of-Mass det. time= 111.3 min (961.3 - 850.0)

Volume	Invert	Avail.Storage	Storage Description
#1	84.40'	371 cf	Custom Stage Data (Prismatic) Listed below (Recalc)
#2	83.40'	224 cf	Filter Material (Prismatic) Listed below (Recalc)
#3	83.65'	6 cf	686 cf Overall - 6 cf Embedded = 680 cf x 33.0% Voids
		L= 30.0'	6.0" Round Pipe Storage Inside #2
		601 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
84.40	374	0	0
85.10	686	371	371

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
83.40	686	0	0
84.40	686	686	686

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.10"

Printed 12/9/2022

Page 89

Device Routing Invert Outlet Devices

#1	Primary	84.95'	8.0' long x 2.0' breadth Broad-Crested Rectangular Weir														
			Head (feet)	0.20	0.40	0.60	0.80	1.00	1.20	1.40	1.60	1.80	2.00	2.50	3.00	3.50	
			Coef. (English)	2.54	2.61	2.61	2.60	2.66	2.70	2.77	2.89	2.88	2.85	3.07	3.20	3.32	
#2	Device 3	85.00'	6.0" Horiz. Orifice/Grate C= 0.600 Limited to weir flow at low heads														
#3	Secondary	83.65'	6.0" Round Culvert L= 68.0' RCP, sq.cut end projecting, Ke= 0.500														
			Inlet / Outlet Invert= 83.65' / 83.00' S= 0.0096 '/' Cc= 0.900														
			n= 0.013 Concrete pipe, bends & connections, Flow Area= 0.20 sf														
#4	Device 3	83.40'	0.500 in/hr Exfiltration over Surface area Phase-In= 0.01'														

Primary OutFlow Max=0.73 cfs @ 12.45 hrs HW=85.06' (Free Discharge)

└─**1=Broad-Crested Rectangular Weir** (Weir Controls 0.73 cfs @ 0.84 fps)

Secondary OutFlow Max=0.09 cfs @ 12.45 hrs HW=85.06' (Free Discharge)

└─**3=Culvert** (Passes 0.09 cfs of 0.75 cfs potential flow)

└─**2=Orifice/Grate** (Weir Controls 0.07 cfs @ 0.79 fps)

└─**4=Exfiltration** (Exfiltration Controls 0.02 cfs)

Summary for Pond BR4: Post - Bio-retention Basin-4

Inflow Area =	6,131 sf,	48.88% Impervious,	Inflow Depth =	4.39"	for 25-yr event
Inflow =	0.63 cfs @	12.12 hrs,	Volume=	2,242 cf	
Outflow =	0.61 cfs @	12.13 hrs,	Volume=	1,987 cf,	Atten= 2%, Lag= 0.9 min
Primary =	0.61 cfs @	12.13 hrs,	Volume=	1,987 cf	

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs / 2

Peak Elev= 83.94' @ 12.13 hrs Surf.Area= 585 sf Storage= 306 cf

Flood Elev= 84.00' Surf.Area= 594 sf Storage= 325 cf

Plug-Flow detention time= 86.5 min calculated for 1,987 cf (89% of inflow)

Center-of-Mass det. time= 32.9 min (828.5 - 795.7)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.10"

Printed 12/9/2022

Page 90

Volume	Invert	Avail.Storage	Storage Description
#1	83.00'	227 cf	Custom Stage Data (Prismatic) Listed below (Recalc)
#2	82.00'	98 cf	Filter Material (Prismatic) Listed below (Recalc)
		297 cf Overall x 33.0% Voids	
		325 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
83.00	157	0	0
84.00	297	227	227

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
82.00	297	0	0
83.00	297	297	297

Device	Routing	Invert	Outlet Devices
#1	Primary	83.75'	3.0' long x 2.0' breadth Broad-Crested Rectangular Weir
Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50			
Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32			

Primary OutFlow Max=0.60 cfs @ 12.13 hrs HW=83.93' (Free Discharge)

1-Broad-Crested Rectangular Weir (Weir Controls 0.60 cfs @ 1.09 fps)

Summary for Pond DMH: post - DMH

Inflow Area = 5,112 sf, 100.00% Impervious, Inflow Depth = 8.64" for 25-yr event
Inflow = 0.55 cfs @ 12.14 hrs, Volume = 3,681 cf
Outflow = 0.55 cfs @ 12.14 hrs, Volume = 3,681 cf, Atten = 0%, Lag = 0.0 min
Primary = 0.55 cfs @ 12.14 hrs, Volume = 3,681 cf

Routing by Stor-Ind method, Time Span = 0.00-72.00 hrs, dt = 0.04 hrs

Peak Elev = 83.26' @ 12.14 hrs

Flood Elev = 85.00'

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.10"

Printed 12/9/2022

Page 91

Device	Routing	Invert	Outlet Devices
#1	Primary	82.80'	8.0" Round Culvert L= 92.0' RCP, sq.cut end projecting, Ke= 0.500 Inlet / Outlet Invert= 82.80' / 82.00' S= 0.0087 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.35 sf

Primary OutFlow Max=0.54 cfs @ 12.14 hrs HW=83.25' (Free Discharge)

1=Culvert (Barrel Controls 0.54 cfs @ 3.04 fps)

Summary for Pond FB1: Post - Forebay-1

Inflow Area = 12,569 sf, 42.19% Impervious, Inflow Depth = 4.36" for 25-yr event
Inflow = 1.19 cfs @ 12.14 hrs, Volume= 4,570 cf
Outflow = 1.18 cfs @ 12.15 hrs, Volume= 4,397 cf, Atten= 1%, Lag= 1.0 min
Primary = 1.18 cfs @ 12.15 hrs, Volume= 4,397 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

Peak Elev= 86.29' @ 12.15 hrs Surf.Area= 307 sf Storage= 252 cf

Flood Elev= 86.50' Surf.Area= 350 sf Storage= 323 cf

Plug-Flow detention time= 43.4 min calculated for 4,395 cf (96% of inflow)

Center-of-Mass det. time= 21.1 min (805.7 - 784.6)

Volume	Invert	Avail.Storage	Storage Description
#1	85.00'	323 cf	Custom Stage Data (Prismatic) Listed below (Recalc)
Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
85.00	95	0	0
86.00	250	173	173
86.50	350	150	323

Device	Routing	Invert	Outlet Devices
#1	Primary	86.00'	3.0' long x 2.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.10"

Printed 12/9/2022

Page 92

Primary OutFlow Max=1.17 cfs @ 12.15 hrs HW=86.28' (Free Discharge)

1-Broad-Crested Rectangular Weir (Weir Controls 1.17 cfs @ 1.37 fps)

Summary for Pond FB2: Post - Forebay-2

Inflow Area = 4,810 sf, 62.31% Impervious, Inflow Depth = 4.88" for 25-yr event
Inflow = 0.53 cfs @ 12.11 hrs, Volume= 1,958 cf
Outflow = 0.52 cfs @ 12.12 hrs, Volume= 1,882 cf, Atten= 1%, Lag= 0.4 min
Primary = 0.52 cfs @ 12.12 hrs, Volume= 1,882 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs / 2

Peak Elev= 83.94' @ 12.12 hrs Surf.Area= 138 sf Storage= 94 cf

Flood Elev= 84.00' Surf.Area= 143 sf Storage= 103 cf

Plug-Flow detention time= 44.6 min calculated for 1,882 cf (96% of inflow)

Center-of-Mass det. time= 21.4 min (789.1 - 767.7)

Volume	Invert	Avail.Storage	Storage Description
#1	83.00'	103 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
83.00	63	0	0
84.00	143	103	103

Device	Routing	Invert	Outlet Devices
#1	Primary	83.80'	4.0' long x 2.0' breadth Broad-Crested Rectangular Weir
			Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50
			Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32

Primary OutFlow Max=0.52 cfs @ 12.12 hrs HW=83.94' (Free Discharge)

1-Broad-Crested Rectangular Weir (Weir Controls 0.52 cfs @ 0.94 fps)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.10"

Printed 12/9/2022

Page 93

Summary for Pond FB3: Post - Forebay-3

Inflow Area = 18,298 sf, 49.99% Impervious, Inflow Depth = 5.43" for 25-yr event
Inflow = 1.67 cfs @ 12.08 hrs, Volume= 8,282 cf
Outflow = 1.64 cfs @ 12.09 hrs, Volume= 8,090 cf, Atten= 1%, Lag= 0.8 min
Primary = 1.64 cfs @ 12.09 hrs, Volume= 8,090 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Peak Elev= 82.35' @ 12.09 hrs Surf.Area= 360 sf Storage= 303 cf
Flood Elev= 82.50' Surf.Area= 400 sf Storage= 358 cf

Plug-Flow detention time= 42.4 min calculated for 8,086 cf (98% of inflow)
Center-of-Mass det. time= 16.4 min (878.5 - 862.1)

Volume	Invert	Avail.Storage	Storage Description
#1	81.00'	358 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
81.00	121	0	0
82.00	263	192	192
82.50	400	166	358

Device	Routing	Invert	Outlet Devices
#1	Primary	82.00'	3.0' long x 2.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32

Primary OutFlow Max=1.61 cfs @ 12.09 hrs HW=82.35' (Free Discharge)
1-Broad-Crested Rectangular Weir (Weir Controls 1.61 cfs @ 1.53 fps)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.10"

Printed 12/9/2022

Page 94

Summary for Pond pA1: Analysis Point - Post Dev Catch Basin in Hope St.

Inflow Area = 16,759 sf, 0.73% Impervious, Inflow Depth = 2.30" for 25-yr event
Inflow = 0.73 cfs @ 12.45 hrs, Volume= 3,214 cf
Primary = 0.73 cfs @ 12.45 hrs, Volume= 3,214 cf, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

Summary for Pond pA2: Analysis Point - Post Dev Flow to Wetland

Inflow Area = 62,928 sf, 41.05% Impervious, Inflow Depth = 4.10" for 25-yr event
Inflow = 2.96 cfs @ 12.38 hrs, Volume= 21,513 cf
Primary = 2.96 cfs @ 12.38 hrs, Volume= 21,513 cf, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

Summary for Subcatchment pB1: Post - Runoff to Detention Basin-1

Runoff = 0.24 cfs @ 12.08 hrs, Volume= 733 cf, Depth= 3.27"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 25-yr Rainfall=6.10"

Area (sf)	CN	Description
2,690	74	>75% Grass cover, Good, HSG C
0	98	Paved parking, HSG C
0	98	Walkway
0	98	Roofs, HSG C
2,690	74	Weighted Average
2,690	74	100.00% Pervious Area

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.10"

Printed 12/9/2022

Page 95

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry, AB

Summary for Subcatchment pF1: Post - Runoff to Forebay-1

Runoff = 1.19 cfs @ 12.14 hrs, Volume= 4,570 cf, Depth= 4.36"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 25-yr Rainfall=6.10"

Area (sf)	CN	Description
4,205	98	Paved parking, HSG C
7,266	74	>75% Grass cover, Good, HSG C
* 979	98	Walkway
* 119	98	Patio/Deck/Stairs
12,569	84	Weighted Average
7,266	74	57.81% Pervious Area
5,303	98	42.19% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.5	44	0.0300	0.08		Sheet Flow, AB
					Grass: Bermuda n= 0.410 P2= 3.30"
0.5	82	0.0180	2.72		Shallow Concentrated Flow, BC
					Paved Kv= 20.3 fps
10.0	126	Total			

Summary for Subcatchment pF2: Post - Runoff to Forebay-2

Runoff = 0.53 cfs @ 12.11 hrs, Volume= 1,958 cf, Depth= 4.88"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 25-yr Rainfall=6.10"

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.10"

Printed 12/9/2022

Page 96

Area (sf)		CN	Description		
*	1,813	74	>75% Grass cover, Good, HSG C		
	2,847	98	Paved parking, HSG C		
	150	98	Walkway		
	0	98	Roofs, HSG C		
4,810		89	Weighted Average		
1,813		74	37.69% Pervious Area		
2,997		98	62.31% Impervious Area		
Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.9	40	0.0400	0.08		Sheet Flow, AB
					Grass: Bermuda n= 0.410 P2= 3.30"
0.1	24	0.0200	2.87		Shallow Concentrated Flow, BC
					Paved Kv= 20.3 fps

Summary for Subcatchment pS1: Post - Runoff to Bio-retention Basin

Runoff = 0.26 cfs @ 12.08 hrs, Volume= 777 cf, Depth= 3.27"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 25-yr Rainfall=6.10"

Area (sf)		CN	Description		
*	2,851	74	>75% Grass cover, Good, HSG C		
	0	98	Patio/Deck/Stairs		
	2,851	74	Weighted Average		
	2,851	74	100.00% Pervious Area		
Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0	Direct Entry, Runoff to swale				

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.10"

Printed 12/9/2022

Page 97

Summary for Subcatchment pS2: Post - Runoff to Swale-1

Runoff = 0.49 cfs @ 12.08 hrs, Volume= 1,512 cf, Depth= 3.51"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 25-yr Rainfall=6.10"

Area (sf)	CN	Description
0	98	Paved parking, HSG C
4,696	74	>75% Grass cover, Good, HSG C
0	98	Walkway
477	98	Patio/Deck/Stairs
5,173	76	Weighted Average
4,696	74	90.78% Pervious Area
477	98	9.22% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry, Parking Runoff

Summary for Subcatchment pS3: Post - Flow to wetlands

Runoff = 0.32 cfs @ 12.31 hrs, Volume= 1,555 cf, Depth= 3.27"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 25-yr Rainfall=6.10"

Area (sf)	CN	Description
5,708	74	>75% Grass cover, Good, HSG C
0	98	Paved parking, HSG C
0	70	Woods, Good, HSG C
5,708	74	Weighted Average
5,708	74	100.00% Pervious Area

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.10"

Printed 12/9/2022

Page 98

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.2	50	0.0260	0.07		Sheet Flow, AB Grass: Bermuda n= 0.410 P2= 3.30"
8.6	183	0.0050	0.35		Shallow Concentrated Flow, BC Woodland Kv= 5.0 fps
1.9	117	0.0400	1.00		Shallow Concentrated Flow, CD Woodland Kv= 5.0 fps
0.3	103	0.0300	5.33	26.67	Channel Flow, DE Area= 5.0 sf Perim= 10.2' r= 0.49' n= 0.030 Earth, grassed & winding
22.1	453	Total			

Summary for Subcatchment pS4: Post - Runoff to Bio-retention Basin-4

Runoff = 0.11 cfs @ 12.12 hrs, Volume= 360 cf, Depth= 3.27"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 25-yr Rainfall=6.10"

Area (sf)	CN	Description
1,321	74	>75% Grass cover, Good, HSG C
0	98	Paved parking, HSG C
0	98	Walkway
0	98	Roofs, HSG C
1,321	74	Weighted Average
1,321	74	100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.9	40	0.0400	0.08		Sheet Flow, AB Grass: Bermuda n= 0.410 P2= 3.30"
0.1	24	0.0200	2.87		Shallow Concentrated Flow, BC Paved Kv= 20.3 fps
8.0	64	Total			

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.10"

Printed 12/9/2022

Page 99

Summary for Subcatchment pS5: Post - Runoff to Bio-retention Basin-2

Runoff = 0.18 cfs @ 12.08 hrs, Volume= 553 cf, Depth= 3.60"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 25-yr Rainfall=6.10"

Area (sf)	CN	Description
0	98	Paved parking, HSG C
1,602	74	>75% Grass cover, Good, HSG C
0	98	Walkway
238	98	Patio/Deck/Stairs
0	98	Roofs, HSG C

1,840	77	Weighted Average
1,602	74	87.07% Pervious Area
238	98	12.93% Impervious Area

Tc Length Slope Velocity Capacity Description
(min) (feet) (ft/ft) (ft/sec) (cfs)

5.0

Direct Entry, AB

Summary for Subcatchment pS6: Post - Runoff to Forebay-3

Runoff = 1.45 cfs @ 12.08 hrs, Volume= 4,686 cf, Depth= 4.12"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 25-yr Rainfall=6.10"

Area (sf)	CN	Description
3,996	98	Paved parking, HSG C
9,151	74	>75% Grass cover, Good, HSG C
493	98	Walkway

13,640	82	Weighted Average
9,151	74	67.09% Pervious Area
4,489	98	32.91% Impervious Area

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.10"

Printed 12/9/2022

Page 100

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry, AB

Summary for Subcatchment pS7: Post - Flow to Hope Street

Runoff = 0.83 cfs @ 12.43 hrs, Volume= 4,592 cf, Depth= 3.29"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 25-yr Rainfall=6.10"

Area (sf)	CN	Description
16,637	74	>75% Grass cover, Good, HSG C
0	98	Paved parking, HSG C
0	98	Walkways
122	98	Patio/Deck/Stairs
16,759	74	Weighted Average
16,637	74	99.27% Pervious Area
122	98	0.73% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
30.6	60	0.0030	0.03		Sheet Flow, AB Grass: Bermuda n= 0.410 P2= 3.30"
0.2	44	0.0450	3.42		Shallow Concentrated Flow, BC Unpaved Kv= 16.1 fps
30.8	104	Total			

Summary for Subcatchment RF1: Post - Roof Area (Units 3&4)

Runoff = 0.36 cfs @ 12.07 hrs, Volume= 1,249 cf, Depth= 5.86"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 25-yr Rainfall=6.10"

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.10"

Printed 12/9/2022

Page 101

Area (sf)	CN	Description
2,556	98	Roofs, HSG C
2,556	98	100.00% Impervious Area
Tc (min)	Length (feet)	Slope (ft/ft) Velocity (ft/sec) Capacity (cfs) Description

5.0

Direct Entry, Roof Runoff

Summary for Subcatchment RF2: Post - Roof Area (Units 5&6)

Runoff = 0.36 cfs @ 12.07 hrs, Volume= 1,249 cf, Depth= 5.86"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 25-yr Rainfall=6.10"

Area (sf)	CN	Description
2,556	98	Roofs, HSG C
2,556	98	100.00% Impervious Area
Tc (min)	Length (feet)	Slope (ft/ft) Velocity (ft/sec) Capacity (cfs) Description

5.0

Direct Entry, Roof Runoff

Summary for Subcatchment RF3: Post - Roof Area (Units 7&8)

Runoff = 0.36 cfs @ 12.07 hrs, Volume= 1,249 cf, Depth= 5.86"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 25-yr Rainfall=6.10"

Area (sf)	CN	Description
2,556	98	Roofs, HSG C
2,556	98	100.00% Impervious Area

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.10"

Printed 12/9/2022

Page 102

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry, Roof Runoff

Summary for Subcatchment RF4: Post- Roof Area (Units 9&10)

Runoff = 0.29 cfs @ 12.07 hrs, Volume= 1,027 cf, Depth= 5.86"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 25-yr Rainfall=6.10"

Area (sf)	CN	Description
2,102	98	Roofs, HSG C
2,102	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry, Roof Runoff

Summary for Subcatchment RF5: Post - Roof Area (Units 1&2)

Runoff = 0.36 cfs @ 12.07 hrs, Volume= 1,249 cf, Depth= 5.86"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 25-yr Rainfall=6.10"

Area (sf)	CN	Description
2,556	98	Roofs, HSG C
2,556	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry, Roof Runoff

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.10"

Printed 12/9/2022

Page 103

Summary for Reach S1: Post - Dry Swale 1

Inflow Area = 20,593 sf, 28.07% Impervious, Inflow Depth = 2.50" for 25-yr event
Inflow = 1.49 cfs @ 12.18 hrs, Volume= 4,289 cf
Outflow = 1.48 cfs @ 12.22 hrs, Volume= 4,289 cf, Atten= 1%, Lag= 2.2 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

Max. Velocity= 2.15 fps, Min. Travel Time= 1.2 min

Avg. Velocity = 0.47 fps, Avg. Travel Time= 5.4 min

Peak Storage= 103 cf @ 12.20 hrs


Average Depth at Peak Storage= 0.27'

Bank-Full Depth= 1.00' Flow Area= 4.0 sf, Capacity= 17.43 cfs

Custom cross-section, Length= 150.0' Slope= 0.0200 '/'

Constant n= 0.035 Earth, dense weeds

Inlet Invert= 85.00', Outlet Invert= 82.00'



Offset (feet)	Elevation (feet)	Chan.Depth (feet)	Depth (feet)	End Area (sq-ft)	Perim. (feet)	Storage (cubic-feet)	Discharge (cfs)
-3.00	1.00	0.00	0.00	0.0	2.0	0	0.00
-1.00	0.00	1.00	1.00	4.0	6.5	600	17.43
1.00	0.00	1.00	1.00				
3.00	1.00	0.00					

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.10"

Printed 12/9/2022

Page 104

Summary for Pond SB: Post - Settling Basin

Inflow Area = 25,705 sf, 42.37% Impervious, Inflow Depth = 3.72" for 25-yr event
Inflow = 1.97 cfs @ 12.21 hrs, Volume= 7,971 cf
Outflow = 1.95 cfs @ 12.23 hrs, Volume= 7,751 cf, Atten= 1%, Lag= 0.8 min
Primary = 1.95 cfs @ 12.23 hrs, Volume= 7,751 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Peak Elev= 82.33' @ 12.23 hrs Surf.Area= 413 sf Storage= 342 cf

Plug-Flow detention time= 51.7 min calculated for 7,751 cf (97% of inflow)
Center-of-Mass det. time= 12.4 min (986.3 - 973.9)

Volume	Invert	Avail.Storage	Storage Description
#1	81.00'	416 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
81.00	108	0	0
82.00	331	220	220
82.50	456	197	416

Device	Routing	Invert	Outlet Devices
#1	Primary	82.00'	4.0' long x 2.0' breadth Broad-Crested Rectangular Weir

Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50
Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32

Primary OutFlow Max=1.94 cfs @ 12.23 hrs HW=82.33' (Free Discharge)
1-Broad-Crested Rectangular Weir (Weir Controls 1.94 cfs @ 1.48 fps)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.10"

Printed 12/9/2022

Page 105

Summary for Pond US1: Post - Recharge System-1

Inflow Area = 5,112 sf,100.00% Impervious, Inflow Depth = 5.86" for 25-yr event
Inflow = 0.72 cfs @ 12.07 hrs, Volume= 2,497 cf
Outflow = 0.53 cfs @ 12.14 hrs, Volume= 2,497 cf, Atten= 26%, Lag= 4.0 min
Discarded = 0.01 cfs @ 4.96 hrs, Volume= 953 cf
Primary = 0.52 cfs @ 12.14 hrs, Volume= 1,544 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Peak Elev= 85.41' @ 12.14 hrs Surf.Area= 715 sf Storage= 600 cf
Flood Elev= 86.30' Surf.Area= 715 sf Storage= 837 cf

Plug-Flow detention time= 164.1 min calculated for 2,496 cf (100% of inflow)
Center-of-Mass det. time= 164.4 min (908.4 - 744.0)

Volume	Invert	Avail.Storage	Storage Description
#1A	84.00'	405 cf	21.50"W x 33.25'L x 2.33'H Field A 1,668 cf Overall - 439 cf Embedded = 1,229 cf x 33.0% Voids
#2A	84.50'	439 cf	Infiltrator H-20 Chamber x 30 Inside #1 Effective Size= 27.5"W x 14.0"H => 2.34 sf x 6.25'L = 14.6 cf Overall Size= 34.0"W x 16.0"H x 6.25'L
		845 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	84.00'	0.500 in/hr Exfiltration over Surface area
#2	Primary	84.85'	6.0" Round Culvert L= 12.0' RCP, sq.cut end projecting, Ke= 0.500 Inlet / Outlet Invert= 84.85' / 84.60' S= 0.0208 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf

Discarded OutFlow Max=0.01 cfs @ 4.96 hrs HW=84.02' (Free Discharge)
↑**1=Exfiltration** (Exfiltration Controls 0.01 cfs)

Primary OutFlow Max=0.52 cfs @ 12.14 hrs HW=85.40' (Free Discharge)
↑**2=Culvert** (Inlet Controls 0.52 cfs @ 2.64 fps)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.10"

Printed 12/9/2022

Page 106

Summary for Pond US2: Post - Underground Storage System

Inflow Area = 4,658 sf, 100.00% Impervious, Inflow Depth = 5.86" for 25-yr event
Inflow = 0.65 cfs @ 12.07 hrs, Volume= 2,275 cf
Outflow = 0.21 cfs @ 12.86 hrs, Volume= 2,275 cf, Atten= 68%, Lag= 47.0 min
Primary = 0.21 cfs @ 12.86 hrs, Volume= 2,275 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Peak Elev= 83.72' @ 12.36 hrs Surf.Area= 1,222 sf Storage= 515 cf

Plug-Flow detention time= 32.9 min calculated for 2,274 cf (100% of inflow)
Center-of-Mass det. time= 33.0 min (777.0 - 744.0)

Volume	Invert	Avail.Storage	Storage Description
#1	83.15'	1,484 cf	18.0" Round Pipe Storage x 14 L= 60.0'

Device	Routing	Invert	Outlet Devices
#1	Primary	83.15'	4.0" Round Culvert L= 100.0' RCP, sq.cut end projecting, Ke= 0.500 Inlet / Outlet Invert= 83.15' / 82.10' S= 0.0105 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.09 sf

Primary OutFlow Max=0.21 cfs @ 12.86 hrs HW=83.57' (Free Discharge)
1=Culvert (Barrel Controls 0.21 cfs @ 2.42 fps)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=8.60"

Printed 12/9/2022

Page 107

Time span=0.00-72.00 hrs, dt=0.04 hrs, 1801 points

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv.

Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

Pond B1: Post - Dry Extended Detention Basin

Peak Elev=82.46' Storage=4,335 cf Inflow=7.03 cfs 28,949 cf
Primary=2.78 cfs 25,267 cf Secondary=3.23 cfs 3,348 cf Outflow=6.01 cfs 28,615 cf

Pond BR1: Post - Bio-retention Basin-1

Peak Elev=86.09' Storage=1,567 cf Inflow=2.13 cfs 8,130 cf
Primary=2.04 cfs 5,529 cf Secondary=0.02 cfs 2,275 cf Outflow=2.06 cfs 7,804 cf

Pond BR2: Post - Bio-retention Basin-2

Peak Elev=82.56' Storage=1,140 cf Inflow=3.25 cfs 14,644 cf
Primary=2.82 cfs 11,922 cf Secondary=0.02 cfs 2,486 cf Outflow=2.84 cfs 14,408 cf

Pond BR3: Post - Bio-retention Basin-3

Peak Elev=85.10' Storage=601 cf Inflow=1.38 cfs 7,663 cf
Primary=1.20 cfs 5,986 cf Secondary=0.18 cfs 1,620 cf Outflow=1.38 cfs 7,606 cf

Pond BR4: Post - Bio-retention Basin-4

Peak Elev=84.00' Storage=324 cf Inflow=0.95 cfs 3,439 cf
Outflow=0.93 cfs 3,184 cf

Pond DMH: post - DMH

Peak Elev=83.36' Inflow=0.76 cfs 4,838 cf
8.0" Round Culvert n=0.013 L=92.0' S=0.0087 '/' Outflow=0.76 cfs 4,838 cf

Pond FB1: Post - Forebay-1

Peak Elev=86.38' Storage=281 cf Inflow=1.82 cfs 7,004 cf
Outflow=1.81 cfs 6,831 cf

Pond FB2: Post - Forebay-2

Peak Elev=83.98' Storage=100 cf Inflow=0.78 cfs 2,914 cf
Outflow=0.77 cfs 2,838 cf

Pond FB3: Post - Forebay-3

Peak Elev=82.46' Storage=343 cf Inflow=2.51 cfs 12,160 cf
Outflow=2.47 cfs 11,968 cf

Pond pA1: Analysis Point - Post Dev Catch Basin in Hope St.

Inflow=1.20 cfs 5,986 cf
Primary=1.20 cfs 5,986 cf

Pond pA2: Analysis Point - Post Dev Flow to Wetland

Inflow=6.49 cfs 33,700 cf
Primary=6.49 cfs 33,700 cf

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=8.60"

Printed 12/9/2022

Page 108

Subcatchment pB1: Post - Runoff to Detention Basin-1

Runoff Area=2,690 sf 0.00% Impervious Runoff Depth=5.47"
Tc=5.0 min CN=74/0 Runoff=0.40 cfs 1,225 cf

Subcatchment pF1: Post - Runoff to Forebay-1

Runoff Area=12,569 sf 42.19% Impervious Runoff Depth=6.69"
Flow Length=126' Tc=10.0 min CN=74/98 Runoff=1.82 cfs 7,004 cf

Subcatchment pF2: Post - Runoff to Forebay-2

Runoff Area=4,810 sf 62.31% Impervious Runoff Depth=7.27"
Flow Length=64' Tc=8.0 min CN=74/98 Runoff=0.78 cfs 2,914 cf

Subcatchment pS1: Post - Runoff to Bio-retention Basin

Runoff Area=2,851 sf 0.00% Impervious Runoff Depth=5.47"
Tc=5.0 min CN=74/0 Runoff=0.43 cfs 1,299 cf

Subcatchment pS2: Post - Runoff to Swale-1

Runoff Area=5,173 sf 9.22% Impervious Runoff Depth=5.73"
Tc=5.0 min CN=74/98 Runoff=0.80 cfs 2,471 cf

Subcatchment pS3: Post - Flow to wetlands

Runoff Area=5,708 sf 0.00% Impervious Runoff Depth=5.47"
Flow Length=453' Tc=22.1 min CN=74/0 Runoff=0.54 cfs 2,600 cf

Subcatchment pS4: Post - Runoff to Bio-retention Basin-4

Runoff Area=1,321 sf 0.00% Impervious Runoff Depth=5.47"
Flow Length=64' Tc=8.0 min CN=74/0 Runoff=0.18 cfs 602 cf

Subcatchment pS5: Post - Runoff to Bio-retention Basin-2

Runoff Area=1,840 sf 12.93% Impervious Runoff Depth=5.84"
Tc=5.0 min CN=74/98 Runoff=0.29 cfs 895 cf

Subcatchment pS6: Post - Runoff to Forebay-3

Runoff Area=13,640 sf 32.91% Impervious Runoff Depth=6.42"
Tc=5.0 min CN=74/98 Runoff=2.26 cfs 7,295 cf

Subcatchment pS7: Post - Flow to Hope Street

Runoff Area=16,759 sf 0.73% Impervious Runoff Depth=5.49"
Flow Length=104' Tc=30.8 min CN=74/98 Runoff=1.38 cfs 7,663 cf

Subcatchment RF1: Post - Roof Area (Units 3&4)

Runoff Area=2,556 sf 100.00% Impervious Runoff Depth=8.36"
Tc=5.0 min CN=0/98 Runoff=0.51 cfs 1,781 cf

Subcatchment RF2: Post - Roof Area (Units 5&6)

Runoff Area=2,556 sf 100.00% Impervious Runoff Depth=8.36"
Tc=5.0 min CN=0/98 Runoff=0.51 cfs 1,781 cf

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=8.60"

Printed 12/9/2022

Page 109

Subcatchment RF3: Post - Roof Area (Units 7&8)

Runoff Area=2,556 sf 100.00% Impervious Runoff Depth=8.36"
Tc=5.0 min CN=0/98 Runoff=0.51 cfs 1,781 cf

Subcatchment RF4: Post- Roof Area (Units 9&10)

Runoff Area=2,102 sf 100.00% Impervious Runoff Depth=8.36"
Tc=5.0 min CN=0/98 Runoff=0.42 cfs 1,464 cf

Subcatchment RF5: Post - Roof Area (Units 1&2)

Runoff Area=2,556 sf 100.00% Impervious Runoff Depth=8.36"
Tc=5.0 min CN=0/98 Runoff=0.51 cfs 1,781 cf

Reach S1: Post - Dry Swale 1

Avg. Flow Depth=0.38' Max Vel=2.59 fps Inflow=2.71 cfs 8,000 cf
n=0.035 L=150.0' S=0.0200 '/' Capacity=17.43 cfs Outflow=2.65 cfs 8,000 cf

Pond SB: Post - Settling Basin

Peak Elev=82.47' Storage=404 cf Inflow=3.41 cfs 12,837 cf
Outflow=3.41 cfs 12,618 cf

Pond US1: Post - Recharge System-1

Peak Elev=85.70' Storage=696 cf Inflow=1.01 cfs 3,561 cf
Discarded=0.01 cfs 999 cf Primary=0.73 cfs 2,562 cf Outflow=0.74 cfs 3,561 cf

Pond US2: Post - Underground Storage System

Peak Elev=83.97' Storage=828 cf Inflow=0.92 cfs 3,245 cf
4.0" Round Culvert n=0.013 L=100.0' S=0.0105 '/' Outflow=0.22 cfs 3,245 cf

Total Runoff Area = 79,687 sf Runoff Volume = 42,554 cf Average Runoff Depth = 6.41"
67.43% Pervious = 53,735 sf 32.57% Impervious = 25,952 sf

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=8.60"

Printed 12/9/2022

Page 110

Summary for Pond B1: Post - Dry Extended Detention Basin

Inflow Area = 57,220 sf, 45.14% Impervious, Inflow Depth = 6.07" for 100-yr event
Inflow = 7.03 cfs @ 12.12 hrs, Volume= 28,949 cf
Outflow = 6.01 cfs @ 12.22 hrs, Volume= 28,615 cf, Atten= 15%, Lag= 5.7 min
Primary = 2.78 cfs @ 12.22 hrs, Volume= 25,267 cf
Secondary = 3.23 cfs @ 12.22 hrs, Volume= 3,348 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs / 2
Peak Elev= 82.46' @ 12.22 hrs Surf.Area= 2,281 sf Storage= 4,335 cf
Flood Elev= 82.50' Surf.Area= 2,300 sf Storage= 4,432 cf

Plug-Flow detention time= 46.7 min calculated for 28,615 cf (99% of inflow)
Center-of-Mass det. time= 29.7 min (888.7 - 859.0)

Volume	Invert	Avail.Storage	Storage Description
#1	80.00'	4,432 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
80.00	1,273	0	0
81.00	1,660	1,467	1,467
82.00	2,080	1,870	3,337
82.50	2,300	1,095	4,432

Device Routing Invert Outlet Devices

#1	Secondary	82.00'	4.0' long x 2.0' breadth Broad-Crested Rectangular Weir
			Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50
			Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32
#2	Primary	80.45'	8.0" Round Culvert L= 12.0' RCP, sq.cut end projecting, Ke= 0.500
			Inlet / Outlet Invert= 80.45' / 79.50' S= 0.0792 '/' Cc= 0.900
#3	Primary	80.25'	4.0" Round Culvert L= 12.0' RCP, sq.cut end projecting, Ke= 0.500
			Inlet / Outlet Invert= 80.25' / 79.50' S= 0.0625 '/' Cc= 0.900
			n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.09 sf

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=8.60"

Printed 12/9/2022

Page 111

Primary OutFlow Max=2.77 cfs @ 12.22 hrs HW=82.45' (Free Discharge)

└─2=Culvert (Inlet Controls 2.17 cfs @ 6.22 fps)

└─3=Culvert (Inlet Controls 0.60 cfs @ 6.87 fps)

Secondary OutFlow Max=3.16 cfs @ 12.22 hrs HW=82.45' (Free Discharge)

└─1=Broad-Crested Rectangular Weir (Weir Controls 3.16 cfs @ 1.75 fps)

Summary for Pond BR1: Post - Bio-retention Basin-1

Inflow Area = 15,420 sf, 34.39% Impervious, Inflow Depth = 6.33" for 100-yr event
Inflow = 2.13 cfs @ 12.14 hrs, Volume= 8,130 cf
Outflow = 2.06 cfs @ 12.14 hrs, Volume= 7,804 cf, Atten= 3%, Lag= 0.0 min
Primary = 2.04 cfs @ 12.14 hrs, Volume= 5,529 cf
Secondary = 0.02 cfs @ 12.08 hrs, Volume= 2,275 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs / 2

Peak Elev= 86.09' @ 12.14 hrs Surf.Area= 2,110 sf Storage= 1,567 cf

Flood Elev= 86.00' Surf.Area= 2,110 sf Storage= 1,567 cf

Plug-Flow detention time= 210.5 min calculated for 7,804 cf (96% of inflow)

Center-of-Mass det. time= 186.9 min (984.1 - 797.2)

Volume	Invert	Avail.Storage	Storage Description
#1	85.00'	867 cf	Custom Stage Data (Prismatic) Listed below (Recalc)
#2	83.00'	694 cf	Filter Material (Prismatic) Listed below (Recalc)
#3	83.75'	7 cf	2,110 cf Overall - 7 cf Embedded = 2,103 cf x 33.0% Voids
			6.0" Round Pipe Storage Inside #2
			L= 35.0'
		1,567 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
85.00	678	0	0
86.00	1,055	867	867

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=8.60"

Printed 12/9/2022

Page 112

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
83.00	1,055	0	0
85.00	1,055	2,110	2,110

Device Routing Invert Outlet Devices

#1	Primary	85.75'	4.0' long x 2.5' breadth Broad-Crested Rectangular Weir															
			Head (feet)	0.20	0.40	0.60	0.80	1.00	1.20	1.40	1.60	1.80	2.00	2.50	3.00	3.50	4.00	
			Coef. (English)	2.48	2.60	2.60	2.60	2.60	2.64	2.65	2.68	2.75	2.74	2.76	2.89	3.05	3.19	3.32
#2	Device 3	83.00'	0.500 in/hr Exfiltration over Surface area Phase-In= 0.01'															
#3	Secondary	83.75'	6.0" Round Culvert L= 100.0' RCP, sq.cut end projecting, Ke= 0.500															
			Inlet / Outlet Invert= 83.75' / 82.85' S= 0.0090 '/' Cc= 0.900															
			n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf															

Primary OutFlow Max=2.01 cfs @ 12.14 hrs HW=86.09' (Free Discharge)

↑ **1=Broad-Crested Rectangular Weir** (Weir Controls 2.01 cfs @ 1.49 fps)

Secondary OutFlow Max=0.02 cfs @ 12.08 hrs HW=86.06' (Free Discharge)

↑ **3=Culvert** (Passes 0.02 cfs of 0.85 cfs potential flow)

↑ **2=Exfiltration** (Exfiltration Controls 0.02 cfs)

Summary for Pond BR2: Post - Bio-retention Basin-2

Inflow Area =	22,694 sf, 52.62% Impervious, Inflow Depth = 7.74" for 100-yr event
Inflow =	3.25 cfs @ 12.09 hrs, Volume= 14,644 cf
Outflow =	2.84 cfs @ 12.09 hrs, Volume= 14,408 cf, Atten= 13%, Lag= 0.0 min
Primary =	2.82 cfs @ 12.09 hrs, Volume= 11,922 cf
Secondary =	0.02 cfs @ 12.04 hrs, Volume= 2,486 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs / 2

Peak Elev= 82.56' @ 12.09 hrs Surf.Area= 1,796 sf Storage= 1,140 cf

Flood Elev= 82.50' Surf.Area= 1,796 sf Storage= 1,140 cf

Plug-Flow detention time= 113.3 min calculated for 14,408 cf (98% of inflow)

Center-of-Mass det. time= 94.7 min (923.6 - 828.8)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=8.60"

Printed 12/9/2022

Page 113

Volume	Invert	Avail. Storage	Storage Description
#1	81.35'	836 cf	Custom Stage Data (Prismatic) Listed below (Recalc)
#2	80.35'	292 cf	Filter Material (Prismatic) Listed below (Recalc)
			898 cf Overall - 12 cf Embedded = 886 cf x 33.0% Voids
#3	80.60'	12 cf	6.0" Round Pipe Storage Inside #2
			L= 61.0'
		1,140 cf	Total Available Storage

Elevation (feet)	Surf. Area (sq-ft)	Inc. Store (cubic-feet)	Cum. Store (cubic-feet)
81.35	563	0	0
82.00	745	425	425
82.50	898	411	836

Elevation (feet)	Surf. Area (sq-ft)	Inc. Store (cubic-feet)	Cum. Store (cubic-feet)
80.35	898	0	0
81.35	898	898	898

Device	Routing	Invert	Outlet Devices
#1	Primary	82.10'	3.5' long x 2.0' breadth Broad-Crested Rectangular Weir
			Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50
			Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32
#2	Device 3	80.35'	0.500 in/hr Exfiltration over Surface area Phase-In= 0.01'
#3	Secondary	80.60'	6.0" Round Culvert L= 62.0' RCP, sq. cut end projecting, Ke= 0.500
			Inlet / Outlet Invert= 80.60' / 79.00' S= 0.0258 '/' Cc= 0.900
			n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf

Primary OutFlow Max=2.78 cfs @ 12.09 hrs HW=82.55' (Free Discharge)

↑ **1=Broad-Crested Rectangular Weir** (Weir Controls 2.78 cfs @ 1.76 fps)

Secondary OutFlow Max=0.02 cfs @ 12.04 hrs HW=82.51' (Free Discharge)

↑ **3=Culvert** (Passes 0.02 cfs of 1.08 cfs potential flow)

↑ **2=Exfiltration** (Exfiltration Controls 0.02 cfs)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=8.60"

Printed 12/9/2022

Page 114

Summary for Pond BR3: Post - Bio-retention Basin-3

Inflow Area = 16,759 sf, 0.73% Impervious, Inflow Depth = 5.49" for 100-yr event
Inflow = 1.38 cfs @ 12.42 hrs, Volume= 7,663 cf
Outflow = 1.38 cfs @ 12.43 hrs, Volume= 7,606 cf, Atten= 0%, Lag= 0.6 min
Primary = 1.20 cfs @ 12.43 hrs, Volume= 5,986 cf
Secondary = 0.18 cfs @ 12.43 hrs, Volume= 1,620 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Peak Elev= 85.10' @ 12.43 hrs Surf.Area= 1,372 sf Storage= 601 cf

Plug-Flow detention time= 76.7 min calculated for 7,606 cf (99% of inflow)
Center-of-Mass det. time= 71.7 min (907.2 - 835.5)

Volume	Invert	Avail.Storage	Storage Description
#1	84.40'	371 cf	Custom Stage Data (Prismatic) Listed below (Recalc)
#2	83.40'	224 cf	Filter Material (Prismatic) Listed below (Recalc)
#3	83.65'	6 cf	686 cf Overall - 6 cf Embedded = 680 cf x 33.0% Voids
		6.0" Round Pipe Storage Inside #2	
		L= 30.0'	
		601 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
84.40	374	0	0
85.10	686	371	371

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
83.40	686	0	0
84.40	686	686	686

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=8.60"

Printed 12/9/2022

Page 115

Device Routing Invert Outlet Devices

#1	Primary	84.95'	8.0' long x 2.0' breadth Broad-Crested Rectangular Weir														
			Head (feet)	0.20	0.40	0.60	0.80	1.00	1.20	1.40	1.60	1.80	2.00	2.50	3.00	3.50	
			Coef. (English)	2.54	2.61	2.61	2.60	2.66	2.70	2.77	2.89	2.88	2.85	3.07	3.20	3.32	
#2	Device 3	85.00'	6.0" Horiz. Orifice/Grate C= 0.600 Limited to weir flow at low heads														
#3	Secondary	83.65'	6.0" Round Culvert L= 68.0' RCP, sq.cut end projecting, Ke= 0.500														
			Inlet / Outlet Invert= 83.65' / 83.00' S= 0.0096 '/' Cc= 0.900														
			n= 0.013 Concrete pipe, bends & connections, Flow Area= 0.20 sf														
#4	Device 3	83.40'	0.500 in/hr Exfiltration over Surface area Phase-In= 0.01'														

Primary OutFlow Max=1.20 cfs @ 12.43 hrs HW=85.10' (Free Discharge)

└─1=Broad-Crested Rectangular Weir (Weir Controls 1.20 cfs @ 0.99 fps)

Secondary OutFlow Max=0.18 cfs @ 12.43 hrs HW=85.10' (Free Discharge)

└─3=Culvert (Passes 0.18 cfs of 0.76 cfs potential flow)

└─2=Orifice/Grate (Weir Controls 0.17 cfs @ 1.04 fps)

└─4=Exfiltration (Exfiltration Controls 0.02 cfs)

Summary for Pond BR4: Post - Bio-retention Basin-4

Inflow Area =	6,131 sf, 48.88% Impervious, Inflow Depth = 6.73" for 100-yr event
Inflow =	0.95 cfs @ 12.12 hrs, Volume= 3,439 cf
Outflow =	0.93 cfs @ 12.13 hrs, Volume= 3,184 cf, Atten= 2%, Lag= 0.8 min
Primary =	0.93 cfs @ 12.13 hrs, Volume= 3,184 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs / 2

Peak Elev= 84.00' @ 12.13 hrs Surf.Area= 593 sf Storage= 324 cf

Flood Elev= 84.00' Surf.Area= 594 sf Storage= 325 cf

Plug-Flow detention time= 66.3 min calculated for 3,184 cf (93% of inflow)

Center-of-Mass det. time= 27.1 min (812.3 - 785.3)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=8.60"

Printed 12/9/2022

Page 116

Volume	Invert	Avail.Storage	Storage Description
#1	83.00'	227 cf	Custom Stage Data (Prismatic) Listed below (Recalc)
#2	82.00'	98 cf	Filter Material (Prismatic) Listed below (Recalc)
		297 cf Overall x 33.0% Voids	
		325 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
83.00	157	0	0
84.00	297	227	227

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
82.00	297	0	0
83.00	297	297	297

Device	Routing	Invert	Outlet Devices
#1	Primary	83.75'	3.0' long x 2.0' breadth Broad-Crested Rectangular Weir
Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50			
Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32			

Primary OutFlow Max=0.92 cfs @ 12.13 hrs HW=83.99' (Free Discharge)

1-Broad-Crested Rectangular Weir (Weir Controls 0.92 cfs @ 1.26 fps)

Summary for Pond DMH: post - DMH

Inflow Area = 5,112 sf, 100.00% Impervious, Inflow Depth = 11.36" for 100-yr event
Inflow = 0.76 cfs @ 12.14 hrs, Volume= 4,838 cf
Outflow = 0.76 cfs @ 12.14 hrs, Volume= 4,838 cf, Atten= 0%, Lag= 0.0 min
Primary = 0.76 cfs @ 12.14 hrs, Volume= 4,838 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

Peak Elev= 83.36' @ 12.14 hrs

Flood Elev= 85.00'

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=8.60"

Printed 12/9/2022

Page 117

Device Routing Invert Outlet Devices

#1	Primary	82.80'	8.0" Round Culvert L= 92.0' RCP, sq.cut end projecting, Ke= 0.500 Inlet / Outlet Invert= 82.80' / 82.00' S= 0.0087 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.35 sf
----	---------	--------	---

Primary OutFlow Max=0.75 cfs @ 12.14 hrs HW=83.36' (Free Discharge)

1=1=Culvert (Barrel Controls 0.75 cfs @ 3.26 fps)

Summary for Pond FB1: Post - Forebay-1

Inflow Area =	12,569 sf,	42.19% Impervious,	Inflow Depth = 6.69"	for 100-yr event
Inflow =	1.82 cfs @	12.14 hrs, Volume=	7,004 cf	
Outflow =	1.81 cfs @	12.15 hrs, Volume=	6,831 cf,	Atten= 1%, Lag= 0.9 min
Primary =	1.81 cfs @	12.15 hrs, Volume=	6,831 cf	

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

Peak Elev= 86.38' @ 12.15 hrs Surf.Area= 325 sf Storage= 281 cf

Flood Elev= 86.50' Surf.Area= 350 sf Storage= 323 cf

Plug-Flow detention time= 30.9 min calculated for 6,828 cf (97% of inflow)

Center-of-Mass det. time= 15.7 min (794.3 - 778.5)

Volume Invert Avail.Storage Storage Description

#1	85.00'	323 cf	Custom Stage Data (Prismatic) Listed below (Recalc)
----	--------	--------	--

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
85.00	95	0	0
86.00	250	173	173
86.50	350	150	323

Device Routing Invert Outlet Devices

#1	Primary	86.00'	3.0' long x 2.0' breadth Broad-Crested Rectangular Weir
			Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50
			Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=8.60"

Printed 12/9/2022

Page 118

Primary OutFlow Max=1.79 cfs @ 12.15 hrs HW=86.37' (Free Discharge)

1-Broad-Crested Rectangular Weir (Weir Controls 1.79 cfs @ 1.59 fps)

Summary for Pond FB2: Post - Forebay-2

Inflow Area = 4,810 sf, 62.31% Impervious, Inflow Depth = 7.27" for 100-yr event
Inflow = 0.78 cfs @ 12.11 hrs, Volume= 2,914 cf
Outflow = 0.77 cfs @ 12.12 hrs, Volume= 2,838 cf, Atten= 1%, Lag= 0.3 min
Primary = 0.77 cfs @ 12.12 hrs, Volume= 2,838 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs / 2

Peak Elev= 83.98' @ 12.12 hrs Surf.Area= 141 sf Storage= 100 cf

Flood Elev= 84.00' Surf.Area= 143 sf Storage= 103 cf

Plug-Flow detention time= 32.3 min calculated for 2,836 cf (97% of inflow)

Center-of-Mass det. time= 16.0 min (778.9 - 762.9)

Volume	Invert	Avail.Storage	Storage Description
#1	83.00'	103 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
83.00	63	0	0
84.00	143	103	103

Device	Routing	Invert	Outlet Devices
--------	---------	--------	----------------

#1	Primary	83.80'	4.0' long x 2.0' breadth Broad-Crested Rectangular Weir
			Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50
			Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32

Primary OutFlow Max=0.77 cfs @ 12.12 hrs HW=83.98' (Free Discharge)

1-Broad-Crested Rectangular Weir (Weir Controls 0.77 cfs @ 1.08 fps)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=8.60"

Printed 12/9/2022

Page 119

Summary for Pond FB3: Post - Forebay-3

Inflow Area = 18,298 sf, 49.99% Impervious, Inflow Depth = 7.97" for 100-yr event
Inflow = 2.51 cfs @ 12.08 hrs, Volume= 12,160 cf
Outflow = 2.47 cfs @ 12.09 hrs, Volume= 11,968 cf, Atten= 1%, Lag= 0.8 min
Primary = 2.47 cfs @ 12.09 hrs, Volume= 11,968 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Peak Elev= 82.46' @ 12.09 hrs Surf.Area= 390 sf Storage= 343 cf
Flood Elev= 82.50' Surf.Area= 400 sf Storage= 358 cf

Plug-Flow detention time= 30.9 min calculated for 11,968 cf (98% of inflow)
Center-of-Mass det. time= 12.1 min (844.4 - 832.3)

Volume	Invert	Avail.Storage	Storage Description
#1	81.00'	358 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
81.00	121	0	0
82.00	263	192	192
82.50	400	166	358

Device	Routing	Invert	Outlet Devices
#1	Primary	82.00'	3.0' long x 2.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32

Primary OutFlow Max=2.43 cfs @ 12.09 hrs HW=82.46' (Free Discharge)
1-Broad-Crested Rectangular Weir (Weir Controls 2.43 cfs @ 1.77 fps)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=8.60"

Printed 12/9/2022

Page 120

Summary for Pond pA1: Analysis Point - Post Dev Catch Basin in Hope St.

Inflow Area = 16,759 sf, 0.73% Impervious, Inflow Depth = 4.29" for 100-yr event
Inflow = 1.20 cfs @ 12.43 hrs, Volume= 5,986 cf
Primary = 1.20 cfs @ 12.43 hrs, Volume= 5,986 cf, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

Summary for Pond pA2: Analysis Point - Post Dev Flow to Wetland

Inflow Area = 62,928 sf, 41.05% Impervious, Inflow Depth = 6.43" for 100-yr event
Inflow = 6.49 cfs @ 12.22 hrs, Volume= 33,700 cf
Primary = 6.49 cfs @ 12.22 hrs, Volume= 33,700 cf, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

Summary for Subcatchment pB1: Post - Runoff to Detention Basin-1

Runoff = 0.40 cfs @ 12.08 hrs, Volume= 1,225 cf, Depth= 5.47"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 100-yr Rainfall=8.60"

Area (sf)	CN	Description
2,690	74	>75% Grass cover, Good, HSG C
0	98	Paved parking, HSG C
0	98	Walkway
0	98	Roofs, HSG C
2,690	74	Weighted Average
2,690	74	100.00% Pervious Area

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=8.60"

Printed 12/9/2022

Page 121

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry, AB

Summary for Subcatchment pF1: Post - Runoff to Forebay-1

Runoff = 1.82 cfs @ 12.14 hrs, Volume= 7,004 cf, Depth= 6.69"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 100-yr Rainfall=8.60"

Area (sf)	CN	Description
4,205	98	Paved parking, HSG C
7,266	74	>75% Grass cover, Good, HSG C
* 979	98	Walkway
* 119	98	Patio/Deck/Stairs
12,569	84	Weighted Average
7,266	74	57.81% Pervious Area
5,303	98	42.19% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.5	44	0.0300	0.08		Sheet Flow, AB
					Grass: Bermuda n= 0.410 P2= 3.30"
0.5	82	0.0180	2.72		Shallow Concentrated Flow, BC
					Paved Kv= 20.3 fps
10.0	126	Total			

Summary for Subcatchment pF2: Post - Runoff to Forebay-2

Runoff = 0.78 cfs @ 12.11 hrs, Volume= 2,914 cf, Depth= 7.27"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 100-yr Rainfall=8.60"

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=8.60"

Printed 12/9/2022

Page 122

Area (sf)	CN	Description
1,813	74	>75% Grass cover, Good, HSG C
2,847	98	Paved parking, HSG C
150	98	Walkway
0	98	Roofs, HSG C

4,810	89	Weighted Average
1,813	74	37.69% Pervious Area
2,997	98	62.31% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.9	40	0.0400	0.08		Sheet Flow, AB
					Grass: Bermuda n= 0.410 P2= 3.30"
0.1	24	0.0200	2.87		Shallow Concentrated Flow, BC
					Paved Kv= 20.3 fps

8.0	64	Total
-----	----	-------

Summary for Subcatchment pS1: Post - Runoff to Bio-retention Basin

Runoff = 0.43 cfs @ 12.08 hrs, Volume= 1,299 cf, Depth= 5.47"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 100-yr Rainfall=8.60"

Area (sf)	CN	Description
2,851	74	>75% Grass cover, Good, HSG C
0	98	Patio/Deck/Stairs

2,851	74	Weighted Average
2,851	74	100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry, Runoff to swale

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=8.60"

Printed 12/9/2022

Page 123

Summary for Subcatchment pS2: Post - Runoff to Swale-1

Runoff = 0.80 cfs @ 12.08 hrs, Volume= 2,471 cf, Depth= 5.73"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 100-yr Rainfall=8.60"

		Area (sf)	CN	Description
*		0	98	Paved parking, HSG C
		4,696	74	>75% Grass cover, Good, HSG C
		0	98	Walkway
		477	98	Patio/Deck/Stairs
		5,173	76	Weighted Average
		4,696	74	90.78% Pervious Area
		477	98	9.22% Impervious Area
Tc	Length	Slope	Velocity	Capacity
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)
5.0				

Direct Entry, Parking Runoff

Summary for Subcatchment pS3: Post - Flow to wetlands

Runoff = 0.54 cfs @ 12.30 hrs, Volume= 2,600 cf, Depth= 5.47"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 100-yr Rainfall=8.60"

		Area (sf)	CN	Description
		5,708	74	>75% Grass cover, Good, HSG C
		0	98	Paved parking, HSG C
		0	70	Woods, Good, HSG C
		5,708	74	Weighted Average
		5,708	74	100.00% Pervious Area

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=8.60"

Printed 12/9/2022

Page 124

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.2	50	0.0260	0.07		Sheet Flow, AB Grass: Bermuda n= 0.410 P2= 3.30"
8.6	183	0.0050	0.35		Shallow Concentrated Flow, BC Woodland Kv= 5.0 fps
1.9	117	0.0400	1.00		Shallow Concentrated Flow, CD Woodland Kv= 5.0 fps
0.3	103	0.0300	5.33	26.67	Channel Flow, DE Area= 5.0 sf Perim= 10.2' r= 0.49' n= 0.030 Earth, grassed & winding
22.1	453	Total			

Summary for Subcatchment pS4: Post - Runoff to Bio-retention Basin-4

Runoff = 0.18 cfs @ 12.12 hrs, Volume= 602 cf, Depth= 5.47"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 100-yr Rainfall=8.60"

Area (sf)	CN	Description
1,321	74	>75% Grass cover, Good, HSG C
0	98	Paved parking, HSG C
0	98	Walkway
0	98	Roofs, HSG C
1,321	74	Weighted Average
1,321	74	100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.9	40	0.0400	0.08		Sheet Flow, AB Grass: Bermuda n= 0.410 P2= 3.30"
0.1	24	0.0200	2.87		Shallow Concentrated Flow, BC Paved Kv= 20.3 fps
8.0	64	Total			

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=8.60"

Printed 12/9/2022

Page 125

Summary for Subcatchment pS5: Post - Runoff to Bio-retention Basin-2

Runoff = 0.29 cfs @ 12.08 hrs, Volume= 895 cf, Depth= 5.84"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 100-yr Rainfall=8.60"

Area (sf)	CN	Description
0	98	Paved parking, HSG C
1,602	74	>75% Grass cover, Good, HSG C
0	98	Walkway
238	98	Patio/Deck/Stairs
0	98	Roofs, HSG C

1,840	77	Weighted Average
1,602	74	87.07% Pervious Area
238	98	12.93% Impervious Area

Tc Length Slope Velocity Capacity Description
(min) (feet) (ft/ft) (ft/sec) (cfs)

5.0

Direct Entry, AB

Summary for Subcatchment pS6: Post - Runoff to Forebay-3

Runoff = 2.26 cfs @ 12.07 hrs, Volume= 7,295 cf, Depth= 6.42"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 100-yr Rainfall=8.60"

Area (sf)	CN	Description
3,996	98	Paved parking, HSG C
9,151	74	>75% Grass cover, Good, HSG C
493	98	Walkway

13,640	82	Weighted Average
9,151	74	67.09% Pervious Area
4,489	98	32.91% Impervious Area

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=8.60"

Printed 12/9/2022

Page 126

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
-------------	------------------	------------------	----------------------	-------------------	-------------

5.0

Direct Entry, AB

Summary for Subcatchment pS7: Post - Flow to Hope Street

Runoff = 1.38 cfs @ 12.42 hrs, Volume= 7,663 cf, Depth= 5.49"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 100-yr Rainfall=8.60"

Area (sf)	CN	Description
16,637	74	>75% Grass cover, Good, HSG C
0	98	Paved parking, HSG C
0	98	Walkways
122	98	Patio/Deck/Stairs
16,759	74	Weighted Average
16,637	74	99.27% Pervious Area
122	98	0.73% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
-------------	------------------	------------------	----------------------	-------------------	-------------

30.6 60 0.0030 0.03

Sheet Flow, AB

Grass: Bermuda n= 0.410 P2= 3.30"

Shallow Concentrated Flow, BC

Unpaved Kv= 16.1 fps

30.8 104 Total

Summary for Subcatchment RF1: Post - Roof Area (Units 3&4)

Runoff = 0.51 cfs @ 12.07 hrs, Volume= 1,781 cf, Depth= 8.36"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 100-yr Rainfall=8.60"

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=8.60"

Printed 12/9/2022

Page 127

Area (sf)	CN	Description
2,556	98	Roofs, HSG C
2,556	98	100.00% Impervious Area
Tc (min)	Length (feet)	Slope (ft/ft) Velocity (ft/sec) Capacity (cfs) Description

5.0

Direct Entry, Roof Runoff

Summary for Subcatchment RF2: Post - Roof Area (Units 5&6)

Runoff = 0.51 cfs @ 12.07 hrs, Volume= 1,781 cf, Depth= 8.36"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 100-yr Rainfall=8.60"

Area (sf)	CN	Description
2,556	98	Roofs, HSG C
2,556	98	100.00% Impervious Area
Tc (min)	Length (feet)	Slope (ft/ft) Velocity (ft/sec) Capacity (cfs) Description

5.0

Direct Entry, Roof Runoff

Summary for Subcatchment RF3: Post - Roof Area (Units 7&8)

Runoff = 0.51 cfs @ 12.07 hrs, Volume= 1,781 cf, Depth= 8.36"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 100-yr Rainfall=8.60"

Area (sf)	CN	Description
2,556	98	Roofs, HSG C
2,556	98	100.00% Impervious Area

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=8.60"

Printed 12/9/2022

Page 128

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry, Roof Runoff

Summary for Subcatchment RF4: Post- Roof Area (Units 9&10)

Runoff = 0.42 cfs @ 12.07 hrs, Volume= 1,464 cf, Depth= 8.36"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 100-yr Rainfall=8.60"

Area (sf)	CN	Description
2,102	98	Roofs, HSG C
2,102	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry, Roof Runoff

Summary for Subcatchment RF5: Post - Roof Area (Units 1&2)

Runoff = 0.51 cfs @ 12.07 hrs, Volume= 1,781 cf, Depth= 8.36"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr 100-yr Rainfall=8.60"

Area (sf)	CN	Description
2,556	98	Roofs, HSG C
2,556	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry, Roof Runoff

Summary for Reach S1: Post - Dry Swale 1


Inflow Area = 20,593 sf, 28.07% Impervious, Inflow Depth = 4.66" for 100-yr event
Inflow = 2.71 cfs @ 12.11 hrs, Volume= 8,000 cf
Outflow = 2.65 cfs @ 12.15 hrs, Volume= 8,000 cf, Atten= 2%, Lag= 2.0 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

Max. Velocity= 2.59 fps, Min. Travel Time= 1.0 min
Avg. Velocity = 0.56 fps, Avg. Travel Time= 4.4 min

Peak Storage= 158 cf @ 12.13 hrs
Average Depth at Peak Storage= 0.38'
Bank-Full Depth= 1.00' Flow Area= 4.0 sf, Capacity= 17.43 cfs

Custom cross-section, Length= 150.0' Slope= 0.0200 '/
Constant n= 0.035 Earth, dense weeds
Inlet Invert= 85.00', Outlet Invert= 82.00'



Offset (feet)	Elevation (feet)	Chan.Depth (feet)	Depth (feet)	End Area (sq-ft)	Perim. (feet)	Storage (cubic-feet)	Discharge (cfs)
-3.00	1.00	0.00	0.00	0.0	2.0	0	0.00
-1.00	0.00	1.00	1.00	4.0	6.5	600	17.43
1.00	0.00	1.00					
3.00	1.00	0.00					

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=8.60"

Printed 12/9/2022

Page 130

Summary for Pond SB: Post - Settling Basin

Inflow Area = 25,705 sf, 42.37% Impervious, Inflow Depth = 5.99" for 100-yr event
Inflow = 3.41 cfs @ 12.15 hrs, Volume= 12,837 cf
Outflow = 3.41 cfs @ 12.16 hrs, Volume= 12,618 cf, Atten= 0%, Lag= 0.9 min
Primary = 3.41 cfs @ 12.16 hrs, Volume= 12,618 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Peak Elev= 82.47' @ 12.16 hrs Surf.Area= 449 sf Storage= 404 cf

Plug-Flow detention time= 34.2 min calculated for 12,618 cf (98% of inflow)
Center-of-Mass det. time= 8.4 min (918.7 - 910.3)

Volume	Invert	Avail.Storage	Storage Description
#1	81.00'	416 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
81.00	108	0	0
82.00	331	220	220
82.50	456	197	416

Device	Routing	Invert	Outlet Devices
#1	Primary	82.00'	4.0' long x 2.0' breadth Broad-Crested Rectangular Weir

Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50
Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32

Primary OutFlow Max=3.40 cfs @ 12.16 hrs HW=82.47' (Free Discharge)
1-Broad-Crested Rectangular Weir (Weir Controls 3.40 cfs @ 1.80 fps)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=8.60"

Printed 12/9/2022

Page 131

Summary for Pond US1: Post - Recharge System-1

Inflow Area = 5,112 sf, 100.00% Impervious, Inflow Depth = 8.36" for 100-yr event
Inflow = 1.01 cfs @ 12.07 hrs, Volume= 3,561 cf
Outflow = 0.74 cfs @ 12.14 hrs, Volume= 3,561 cf, Atten= 27%, Lag= 4.2 min
Discarded = 0.01 cfs @ 2.96 hrs, Volume= 999 cf
Primary = 0.73 cfs @ 12.14 hrs, Volume= 2,562 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Peak Elev= 85.70' @ 12.14 hrs Surf.Area= 715 sf Storage= 696 cf
Flood Elev= 86.30' Surf.Area= 715 sf Storage= 837 cf

Plug-Flow detention time= 130.6 min calculated for 3,559 cf (100% of inflow)
Center-of-Mass det. time= 130.9 min (870.3 - 739.4)

Volume	Invert	Avail.Storage	Storage Description
#1A	84.00'	405 cf	21.50"W x 33.25'L x 2.33'H Field A 1,668 cf Overall - 439 cf Embedded = 1,229 cf x 33.0% Voids
#2A	84.50'	439 cf	Infiltrator H-20 Chamber x 30 Inside #1 Effective Size= 27.5"W x 14.0"H => 2.34 sf x 6.25'L = 14.6 cf Overall Size= 34.0"W x 16.0"H x 6.25'L
		845 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	84.00'	0.500 in/hr Exfiltration over Surface area
#2	Primary	84.85'	6.0" Round Culvert L= 12.0' RCP, sq.cut end projecting, Ke= 0.500 Inlet / Outlet Invert= 84.85' / 84.60' S= 0.0208 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf

Discarded OutFlow Max=0.01 cfs @ 2.96 hrs HW=84.02' (Free Discharge)
↑ **1=Exfiltration** (Exfiltration Controls 0.01 cfs)

Primary OutFlow Max=0.73 cfs @ 12.14 hrs HW=85.69' (Free Discharge)
↑ **2=Culvert** (Inlet Controls 0.73 cfs @ 3.70 fps)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=8.60"

Printed 12/9/2022

Page 132

Summary for Pond US2: Post - Underground Storage System

Inflow Area = 4,658 sf, 100.00% Impervious, Inflow Depth = 8.36" for 100-yr event
Inflow = 0.92 cfs @ 12.07 hrs, Volume= 3,245 cf
Outflow = 0.22 cfs @ 12.44 hrs, Volume= 3,245 cf, Atten= 76%, Lag= 22.0 min
Primary = 0.22 cfs @ 12.44 hrs, Volume= 3,245 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Peak Elev= 83.97' @ 12.44 hrs Surf.Area= 1,255 sf Storage= 828 cf

Plug-Flow detention time= 37.3 min calculated for 3,243 cf (100% of inflow)
Center-of-Mass det. time= 37.5 min (776.9 - 739.4)

Volume	Invert	Avail.Storage	Storage Description
#1	83.15'	1,484 cf	18.0" Round Pipe Storage x 14 L= 60.0'

Device	Routing	Invert	Outlet Devices
#1	Primary	83.15'	4.0" Round Culvert L= 100.0' RCP, sq.cut end projecting, Ke= 0.500 Inlet / Outlet Invert= 83.15' / 82.10' S= 0.0105 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.09 sf

Primary OutFlow Max=0.22 cfs @ 12.44 hrs HW=83.97' (Free Discharge)
1=Culvert (Barrel Controls 0.22 cfs @ 2.56 fps)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr WQv Rainfall=1.20"

Printed 12/9/2022

Page 133

Time span=0.00-72.00 hrs, dt=0.04 hrs, 1801 points

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv.

Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

Pond B1: Post - Dry Extended Detention Basin

Peak Elev=80.01' Storage=14 cf Inflow=0.00 cfs 14 cf
Primary=0.00 cfs 0 cf Secondary=0.00 cfs 0 cf Outflow=0.00 cfs 0 cf

Pond BR1: Post - Bio-retention Basin-1

Peak Elev=83.78' Storage=272 cf Inflow=0.10 cfs 315 cf
Primary=0.00 cfs 0 cf Secondary=0.00 cfs 54 cf Outflow=0.00 cfs 54 cf

Pond BR2: Post - Bio-retention Basin-2

Peak Elev=81.58' Storage=444 cf Inflow=0.22 cfs 883 cf
Primary=0.00 cfs 0 cf Secondary=0.02 cfs 809 cf Outflow=0.02 cfs 809 cf

Pond BR3: Post - Bio-retention Basin-3

Peak Elev=83.68' Storage=62 cf Inflow=0.01 cfs 96 cf
Primary=0.00 cfs 0 cf Secondary=0.00 cfs 39 cf Outflow=0.00 cfs 39 cf

Pond BR4: Post - Bio-retention Basin-4

Peak Elev=83.46' Storage=186 cf Inflow=0.07 cfs 186 cf
Outflow=0.00 cfs 0 cf

Pond DMH: post - DMH

Peak Elev=82.83' Inflow=0.00 cfs 54 cf
8.0" Round Culvert n=0.013 L=92.0' S=0.0087 '/' Outflow=0.00 cfs 54 cf

Pond FB1: Post - Forebay-1

Peak Elev=86.06' Storage=187 cf Inflow=0.12 cfs 473 cf
Outflow=0.10 cfs 300 cf

Pond FB2: Post - Forebay-2

Peak Elev=83.84' Storage=81 cf Inflow=0.07 cfs 255 cf
Outflow=0.07 cfs 179 cf

Pond FB3: Post - Forebay-3

Peak Elev=82.07' Storage=212 cf Inflow=0.16 cfs 837 cf
Outflow=0.15 cfs 645 cf

Pond pA1: Analysis Point - Post Dev Catch Basin in Hope St.

Inflow=0.00 cfs 0 cf
Primary=0.00 cfs 0 cf

Pond pA2: Analysis Point - Post Dev Flow to Wetland

Inflow=0.02 cfs 838 cf
Primary=0.02 cfs 838 cf

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr WQv Rainfall=1.20"

Printed 12/9/2022

Page 134

Subcatchment pB1: Post - Runoff to Detention Basin-1

Runoff Area=2,690 sf 0.00% Impervious Runoff Depth=0.06"
Tc=5.0 min CN=74/0 Runoff=0.00 cfs 14 cf

Subcatchment pF1: Post - Runoff to Forebay-1

Runoff Area=12,569 sf 42.19% Impervious Runoff Depth=0.45"
Flow Length=126' Tc=10.0 min CN=74/98 Runoff=0.12 cfs 473 cf

Subcatchment pF2: Post - Runoff to Forebay-2

Runoff Area=4,810 sf 62.31% Impervious Runoff Depth=0.64"
Flow Length=64' Tc=8.0 min CN=74/98 Runoff=0.07 cfs 255 cf

Subcatchment pS1: Post - Runoff to Bio-retention Basin

Runoff Area=2,851 sf 0.00% Impervious Runoff Depth=0.06"
Tc=5.0 min CN=74/0 Runoff=0.00 cfs 15 cf

Subcatchment pS2: Post - Runoff to Swale-1

Runoff Area=5,173 sf 9.22% Impervious Runoff Depth=0.15"
Tc=5.0 min CN=74/98 Runoff=0.01 cfs 63 cf

Subcatchment pS3: Post - Flow to wetlands

Runoff Area=5,708 sf 0.00% Impervious Runoff Depth=0.06"
Flow Length=453' Tc=22.1 min CN=74/0 Runoff=0.00 cfs 29 cf

Subcatchment pS4: Post - Runoff to Bio-retention Basin-4

Runoff Area=1,321 sf 0.00% Impervious Runoff Depth=0.06"
Flow Length=64' Tc=8.0 min CN=74/0 Runoff=0.00 cfs 7 cf

Subcatchment pS5: Post - Runoff to Bio-retention Basin-2

Runoff Area=1,840 sf 12.93% Impervious Runoff Depth=0.18"
Tc=5.0 min CN=74/98 Runoff=0.01 cfs 28 cf

Subcatchment pS6: Post - Runoff to Forebay-3

Runoff Area=13,640 sf 32.91% Impervious Runoff Depth=0.37"
Tc=5.0 min CN=74/98 Runoff=0.12 cfs 416 cf

Subcatchment pS7: Post - Flow to Hope Street

Runoff Area=16,759 sf 0.73% Impervious Runoff Depth=0.07"
Flow Length=104' Tc=30.8 min CN=74/98 Runoff=0.01 cfs 96 cf

Subcatchment RF1: Post - Roof Area (Units 3&4)

Runoff Area=2,556 sf 100.00% Impervious Runoff Depth=0.99"
Tc=5.0 min CN=0/98 Runoff=0.07 cfs 210 cf

Subcatchment RF2: Post - Roof Area (Units 5&6)

Runoff Area=2,556 sf 100.00% Impervious Runoff Depth=0.99"
Tc=5.0 min CN=0/98 Runoff=0.07 cfs 210 cf

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr WQv Rainfall=1.20"

Printed 12/9/2022

Page 135

Subcatchment RF3: Post - Roof Area (Units 7&8)

Runoff Area=2,556 sf 100.00% Impervious Runoff Depth=0.99"
Tc=5.0 min CN=0/98 Runoff=0.07 cfs 210 cf

Subcatchment RF4: Post- Roof Area (Units 9&10)

Runoff Area=2,102 sf 100.00% Impervious Runoff Depth=0.99"
Tc=5.0 min CN=0/98 Runoff=0.05 cfs 173 cf

Subcatchment RF5: Post - Roof Area (Units 1&2)

Runoff Area=2,556 sf 100.00% Impervious Runoff Depth=0.99"
Tc=5.0 min CN=0/98 Runoff=0.07 cfs 210 cf

Reach S1: Post - Dry Swale 1

Avg. Flow Depth=0.01' Max Vel=0.36 fps Inflow=0.01 cfs 63 cf
n=0.035 L=150.0' S=0.0200 '/' Capacity=17.43 cfs Outflow=0.01 cfs 63 cf

Pond SB: Post - Settling Basin

Peak Elev=81.65' Storage=117 cf Inflow=0.01 cfs 117 cf
Outflow=0.00 cfs 0 cf

Pond US1: Post - Recharge System-1

Peak Elev=84.61' Storage=181 cf Inflow=0.13 cfs 420 cf
Discarded=0.01 cfs 420 cf Primary=0.00 cfs 0 cf Outflow=0.01 cfs 420 cf

Pond US2: Post - Underground Storage System

Peak Elev=83.32' Storage=90 cf Inflow=0.12 cfs 383 cf
4.0" Round Culvert n=0.013 L=100.0' S=0.0105 '/' Outflow=0.06 cfs 383 cf

Total Runoff Area = 79,687 sf Runoff Volume = 2,408 cf Average Runoff Depth = 0.36"
67.43% Pervious = 53,735 sf 32.57% Impervious = 25,952 sf

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr WQv Rainfall=1.20"

Printed 12/9/2022

Page 136

Summary for Pond B1: Post - Dry Extended Detention Basin

Inflow Area = 57,220 sf, 45.14% Impervious, Inflow Depth = 0.00" for WQv event
Inflow = 0.00 cfs @ 12.40 hrs, Volume= 14 cf
Outflow = 0.00 cfs @ 0.00 hrs, Volume= 0 cf, Atten= 100%, Lag= 0.0 min
Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf
Secondary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs / 2
Peak Elev= 80.01' @ 24.32 hrs Surf.Area= 1,277 sf Storage= 14 cf
Flood Elev= 82.50' Surf.Area= 2,300 sf Storage= 4,432 cf

Plug-Flow detention time= (not calculated: initial storage exceeds outflow)
Center-of-Mass det. time= (not calculated: no outflow)

Volume	Invert	Avail.Storage	Storage Description
#1	80.00'	4,432 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
80.00	1,273	0	0
81.00	1,660	1,467	1,467
82.00	2,080	1,870	3,337
82.50	2,300	1,095	4,432

Device	Routing	Invert	Outlet Devices
#1	Secondary	82.00'	4.0' long x 2.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32
#2	Primary	80.45'	8.0" Round Culvert L= 12.0' RCP, sq.cut end projecting, Ke= 0.500 Inlet / Outlet Invert= 80.45' / 79.50' S= 0.0792 '/' Cc= 0.900
#3	Primary	80.25'	n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.35 sf 4.0" Round Culvert L= 12.0' RCP, sq.cut end projecting, Ke= 0.500 Inlet / Outlet Invert= 80.25' / 79.50' S= 0.0625 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.09 sf

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr WQv Rainfall=1.20"

Printed 12/9/2022

Page 137

Primary OutFlow Max=0.00 cfs @ 0.00 hrs HW=80.00' (Free Discharge)

└─2=Culvert (Controls 0.00 cfs)

└─3=Culvert (Controls 0.00 cfs)

Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=80.00' (Free Discharge)

└─1=Broad-Crested Rectangular Weir (Controls 0.00 cfs)

Summary for Pond BR1: Post - Bio-retention Basin-1

Inflow Area = 15,420 sf, 34.39% Impervious, Inflow Depth = 0.25" for WQv event
Inflow = 0.10 cfs @ 12.22 hrs, Volume= 315 cf
Outflow = 0.00 cfs @ 20.81 hrs, Volume= 54 cf, Atten= 97%, Lag= 515.6 min
Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf
Secondary = 0.00 cfs @ 20.81 hrs, Volume= 54 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs / 2

Peak Elev= 83.78' @ 20.81 hrs Surf.Area= 1,055 sf Storage= 272 cf

Flood Elev= 86.00' Surf.Area= 2,110 sf Storage= 1,567 cf

Plug-Flow detention time= 603.4 min calculated for 54 cf (17% of inflow)

Center-of-Mass det. time= 442.2 min (1,338.2 - 895.9)

Volume	Invert	Avail.Storage	Storage Description
#1	85.00'	867 cf	Custom Stage Data (Prismatic) Listed below (Recalc)
#2	83.00'	694 cf	Filter Material (Prismatic) Listed below (Recalc)
#3	83.75'	7 cf	2,110 cf Overall - 7 cf Embedded = 2,103 cf x 33.0% Voids
		L= 35.0'	6.0" Round Pipe Storage Inside #2
		1,567 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
85.00	678	0	0
86.00	1,055	867	867

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr WQv Rainfall=1.20"

Printed 12/9/2022

Page 138

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
83.00	1,055	0	0
85.00	1,055	2,110	2,110

Device	Routing	Invert	Outlet Devices
#1	Primary	85.75'	4.0' long x 2.5' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 Coef. (English) 2.48 2.60 2.60 2.60 2.64 2.65 2.68 2.75 2.74 2.76 2.89 3.05 3.19 3.32
#2	Device 3	83.00'	0.500 in/hr Exfiltration over Surface area Phase-In= 0.01'
#3	Secondary	83.75'	6.0" Round Culvert L= 100.0' RCP, sq.cut end projecting, Ke= 0.500 Inlet / Outlet Invert= 83.75' / 82.85' S= 0.0090 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf

Primary OutFlow Max=0.00 cfs @ 0.00 hrs HW=83.00' (Free Discharge)

↑ **1=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)

Secondary OutFlow Max=0.00 cfs @ 20.81 hrs HW=83.78' (Free Discharge)

↑ **3=Culvert** (Barrel Controls 0.00 cfs @ 0.68 fps)

↑ **2=Exfiltration** (Passes 0.00 cfs of 0.01 cfs potential flow)

Summary for Pond BR2: Post - Bio-retention Basin-2

Inflow Area =	22,694 sf, 52.62% Impervious, Inflow Depth = 0.47" for WQv event
Inflow =	0.22 cfs @ 12.10 hrs, Volume= 883 cf
Outflow =	0.02 cfs @ 14.55 hrs, Volume= 809 cf, Atten= 92%, Lag= 147.1 min
Primary =	0.00 cfs @ 0.00 hrs, Volume= 0 cf
Secondary =	0.02 cfs @ 14.55 hrs, Volume= 809 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs / 2

Peak Elev= 81.58' @ 14.55 hrs Surf.Area= 1,526 sf Storage= 444 cf

Flood Elev= 82.50' Surf.Area= 1,796 sf Storage= 1,140 cf

Plug-Flow detention time= 339.0 min calculated for 809 cf (92% of inflow)

Center-of-Mass det. time= 291.8 min (1,161.9 - 870.1)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr WQv Rainfall=1.20"

Printed 12/9/2022

Page 139

Volume	Invert	Avail. Storage	Storage Description
#1	81.35'	836 cf	Custom Stage Data (Prismatic) Listed below (Recalc)
#2	80.35'	292 cf	Filter Material (Prismatic) Listed below (Recalc)
			898 cf Overall - 12 cf Embedded = 886 cf x 33.0% Voids
#3	80.60'	12 cf	6.0" Round Pipe Storage Inside #2
			L= 61.0'
		1,140 cf	Total Available Storage

Elevation (feet)	Surf. Area (sq-ft)	Inc. Store (cubic-feet)	Cum. Store (cubic-feet)
81.35	563	0	0
82.00	745	425	425
82.50	898	411	836

Elevation (feet)	Surf. Area (sq-ft)	Inc. Store (cubic-feet)	Cum. Store (cubic-feet)
80.35	898	0	0
81.35	898	898	898

Device	Routing	Invert	Outlet Devices
#1	Primary	82.10'	3.5' long x 2.0' breadth Broad-Crested Rectangular Weir
			Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50
			Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32
#2	Device 3	80.35'	0.500 in/hr Exfiltration over Surface area Phase-In= 0.01'
#3	Secondary	80.60'	6.0" Round Culvert L= 62.0' RCP, sq. cut end projecting, Ke= 0.500
			Inlet / Outlet Invert= 80.60' / 79.00' S= 0.0258 '/' Cc= 0.900
			n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf

Primary OutFlow Max=0.00 cfs @ 0.00 hrs HW=80.35' (Free Discharge)

↑ **1=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)

Secondary OutFlow Max=0.02 cfs @ 14.55 hrs HW=81.58' (Free Discharge)

↑ **3=Culvert** (Passes 0.02 cfs of 0.81 cfs potential flow)

↑ **2=Exfiltration** (Exfiltration Controls 0.02 cfs)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr WQv Rainfall=1.20"

Printed 12/9/2022

Page 140

Summary for Pond BR3: Post - Bio-retention Basin-3

Inflow Area = 16,759 sf, 0.73% Impervious, Inflow Depth = 0.07" for WQv event
Inflow = 0.01 cfs @ 12.77 hrs, Volume= 96 cf
Outflow = 0.00 cfs @ 18.37 hrs, Volume= 39 cf, Atten= 71%, Lag= 335.9 min
Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf
Secondary = 0.00 cfs @ 18.37 hrs, Volume= 39 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Peak Elev= 83.68' @ 18.37 hrs Surf.Area= 686 sf Storage= 62 cf

Plug-Flow detention time= 491.2 min calculated for 39 cf (41% of inflow)
Center-of-Mass det. time= 298.9 min (1,289.2 - 990.3)

Volume	Invert	Avail.Storage	Storage Description
#1	84.40'	371 cf	Custom Stage Data (Prismatic) Listed below (Recalc)
#2	83.40'	224 cf	Filter Material (Prismatic) Listed below (Recalc)
#3	83.65'	6 cf	686 cf Overall - 6 cf Embedded = 680 cf x 33.0% Voids
		6.0" Round Pipe Storage	Inside #2
		L= 30.0'	
		601 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
84.40	374	0	0
85.10	686	371	371

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
83.40	686	0	0
84.40	686	686	686

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr WQv Rainfall=1.20"

Printed 12/9/2022

Page 141

Device	Routing	Invert	Outlet Devices
#1	Primary	84.95'	8.0' long x 2.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32
#2	Device 3	85.00'	6.0" Horiz. Orifice/Grate C= 0.600 Limited to weir flow at low heads
#3	Secondary	83.65'	6.0" Round Culvert L= 68.0' RCP, sq.cut end projecting, Ke= 0.500 Inlet / Outlet Invert= 83.65' / 83.00' S= 0.0096 '/' Cc= 0.900 n= 0.013 Concrete pipe, bends & connections, Flow Area= 0.20 sf
#4	Device 3	83.40'	0.500 in/hr Exfiltration over Surface area Phase-In= 0.01'

Primary OutFlow Max=0.00 cfs @ 0.00 hrs HW=83.40' (Free Discharge)

└─**1=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)

Secondary OutFlow Max=0.00 cfs @ 18.37 hrs HW=83.68' (Free Discharge)

└─**3=Culvert** (Barrel Controls 0.00 cfs @ 0.60 fps)

└─**2=Orifice/Grate** (Controls 0.00 cfs)

└─**4=Exfiltration** (Passes 0.00 cfs of 0.01 cfs potential flow)

Summary for Pond BR4: Post - Bio-retention Basin-4

Inflow Area = 6,131 sf, 48.88% Impervious, Inflow Depth = 0.36" for WQv event
Inflow = 0.07 cfs @ 12.12 hrs, Volume= 186 cf
Outflow = 0.00 cfs @ 0.00 hrs, Volume= 0 cf, Atten= 100%, Lag= 0.0 min
Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs / 2

Peak Elev= 83.46' @ 25.16 hrs Surf.Area= 519 sf Storage= 186 cf

Flood Elev= 84.00' Surf.Area= 594 sf Storage= 325 cf

Plug-Flow detention time= (not calculated: initial storage exceeds outflow)

Center-of-Mass det. time= (not calculated: no outflow)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr WQv Rainfall=1.20"

Printed 12/9/2022

Page 142

Volume	Invert	Avail.Storage	Storage Description
#1	83.00'	227 cf	Custom Stage Data (Prismatic) Listed below (Recalc)
#2	82.00'	98 cf	Filter Material (Prismatic) Listed below (Recalc)
		297 cf Overall x 33.0% Voids	
		325 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
83.00	157	0	0
84.00	297	227	227

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
82.00	297	0	0
83.00	297	297	297

Device	Routing	Invert	Outlet Devices
#1	Primary	83.75'	3.0' long x 2.0' breadth Broad-Crested Rectangular Weir
Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50			
Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32			

Primary OutFlow Max=0.00 cfs @ 0.00 hrs HW=82.00' (Free Discharge)

1-Broad-Crested Rectangular Weir (Controls 0.00 cfs)

Summary for Pond DMH: post - DMH

Inflow Area = 5,112 sf, 100.00% Impervious, Inflow Depth = 0.13" for WQv event
Inflow = 0.00 cfs @ 20.81 hrs, Volume= 54 cf
Outflow = 0.00 cfs @ 20.81 hrs, Volume= 54 cf, Atten= 0%, Lag= 0.0 min
Primary = 0.00 cfs @ 20.81 hrs, Volume= 54 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

Peak Elev= 82.83' @ 20.81 hrs

Flood Elev= 85.00'

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr WQv Rainfall=1.20"

Printed 12/9/2022

Page 143

Device Routing Invert Outlet Devices

#1	Primary	82.80'	8.0" Round Culvert L= 92.0' RCP, sq.cut end projecting, Ke= 0.500 Inlet / Outlet Invert= 82.80' / 82.00' S= 0.0087 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.35 sf
----	---------	--------	---

Primary OutFlow Max=0.00 cfs @ 20.81 hrs HW=82.83' (Free Discharge)

1=1=Culvert (Barrel Controls 0.00 cfs @ 0.63 fps)

Summary for Pond FB1: Post - Forebay-1

Inflow Area =	12,569 sf, 42.19% Impervious, Inflow Depth = 0.45" for WQv event
Inflow =	0.12 cfs @ 12.14 hrs, Volume= 473 cf
Outflow =	0.10 cfs @ 12.22 hrs, Volume= 300 cf, Atten= 14%, Lag= 4.9 min
Primary =	0.10 cfs @ 12.22 hrs, Volume= 300 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

Peak Elev= 86.06' @ 12.22 hrs Surf.Area= 261 sf Storage= 187 cf

Flood Elev= 86.50' Surf.Area= 350 sf Storage= 323 cf

Plug-Flow detention time= 199.3 min calculated for 300 cf (64% of inflow)

Center-of-Mass det. time= 89.4 min (891.5 - 802.1)

Volume Invert Avail.Storage Storage Description

#1	85.00'	323 cf	Custom Stage Data (Prismatic) Listed below (Recalc)
----	--------	--------	--

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
85.00	95	0	0
86.00	250	173	173
86.50	350	150	323

Device Routing Invert Outlet Devices

#1	Primary	86.00'	3.0' long x 2.0' breadth Broad-Crested Rectangular Weir
			Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50
			Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr WQv Rainfall=1.20"

Printed 12/9/2022

Page 144

Primary OutFlow Max=0.09 cfs @ 12.22 hrs HW=86.05' (Free Discharge)
1-Broad-Crested Rectangular Weir (Weir Controls 0.09 cfs @ 0.59 fps)

Summary for Pond FB2: Post - Forebay-2

Inflow Area = 4,810 sf, 62.31% Impervious, Inflow Depth = 0.64" for WQv event
Inflow = 0.07 cfs @ 12.11 hrs, Volume= 255 cf
Outflow = 0.07 cfs @ 12.12 hrs, Volume= 179 cf, Atten= 2%, Lag= 0.7 min
Primary = 0.07 cfs @ 12.12 hrs, Volume= 179 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs / 2
Peak Elev= 83.84' @ 12.12 hrs Surf.Area= 130 sf Storage= 81 cf
Flood Elev= 84.00' Surf.Area= 143 sf Storage= 103 cf

Plug-Flow detention time= 164.5 min calculated for 179 cf (70% of inflow)
Center-of-Mass det. time= 69.0 min (860.4 - 791.4)

Volume	Invert	Avail.Storage	Storage Description
#1	83.00'	103 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
83.00	63	0	0
84.00	143	103	103

Device	Routing	Invert	Outlet Devices
#1	Primary	83.80'	4.0' long x 2.0' breadth Broad-Crested Rectangular Weir
			Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50
			Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32

Primary OutFlow Max=0.07 cfs @ 12.12 hrs HW=83.84' (Free Discharge)
1-Broad-Crested Rectangular Weir (Weir Controls 0.07 cfs @ 0.48 fps)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr WQv Rainfall=1.20"

Printed 12/9/2022

Page 145

Summary for Pond FB3: Post - Forebay-3

Inflow Area = 18,298 sf, 49.99% Impervious, Inflow Depth = 0.55" for WQv event
Inflow = 0.16 cfs @ 12.08 hrs, Volume= 837 cf
Outflow = 0.15 cfs @ 12.12 hrs, Volume= 645 cf, Atten= 4%, Lag= 1.9 min
Primary = 0.15 cfs @ 12.12 hrs, Volume= 645 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Peak Elev= 82.07' @ 12.12 hrs Surf.Area= 283 sf Storage= 212 cf
Flood Elev= 82.50' Surf.Area= 400 sf Storage= 358 cf

Plug-Flow detention time= 167.3 min calculated for 645 cf (77% of inflow)
Center-of-Mass det. time= 64.7 min (900.2 - 835.5)

Volume	Invert	Avail.Storage	Storage Description
#1	81.00'	358 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
81.00	121	0	0
82.00	263	192	192
82.50	400	166	358

Device	Routing	Invert	Outlet Devices
#1	Primary	82.00'	3.0' long x 2.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32

Primary OutFlow Max=0.15 cfs @ 12.12 hrs HW=82.07' (Free Discharge)
1-Broad-Crested Rectangular Weir (Weir Controls 0.15 cfs @ 0.69 fps)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr WQv Rainfall=1.20"

Printed 12/9/2022

Page 146

Summary for Pond pA1: Analysis Point - Post Dev Catch Basin in Hope St.

Inflow Area = 16,759 sf, 0.73% Impervious, Inflow Depth = 0.00" for WQv event
Inflow = 0.00 cfs @ 0.00 hrs, Volume= 0 cf
Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

Summary for Pond pA2: Analysis Point - Post Dev Flow to Wetland

Inflow Area = 62,928 sf, 41.05% Impervious, Inflow Depth = 0.16" for WQv event
Inflow = 0.02 cfs @ 12.72 hrs, Volume= 838 cf
Primary = 0.02 cfs @ 12.72 hrs, Volume= 838 cf, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs

Summary for Subcatchment pB1: Post - Runoff to Detention Basin-1

Runoff = 0.00 cfs @ 12.40 hrs, Volume= 14 cf, Depth= 0.06"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr WQv Rainfall=1.20"

Area (sf)	CN	Description
2,690	74	>75% Grass cover, Good, HSG C
0	98	Paved parking, HSG C
0	98	Walkway
0	98	Roofs, HSG C
2,690	74	Weighted Average
2,690	74	100.00% Pervious Area

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr WQv Rainfall=1.20"

Printed 12/9/2022

Page 147

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
-------------	------------------	------------------	----------------------	-------------------	-------------

5.0

Direct Entry, AB

Summary for Subcatchment pF1: Post - Runoff to Forebay-1

Runoff = 0.12 cfs @ 12.14 hrs, Volume= 473 cf, Depth= 0.45"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr WQv Rainfall=1.20"

Area (sf)	CN	Description
4,205	98	Paved parking, HSG C
7,266	74	>75% Grass cover, Good, HSG C
* 979	98	Walkway
* 119	98	Patio/Deck/Stairs
12,569	84	Weighted Average
7,266	74	57.81% Pervious Area
5,303	98	42.19% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
-------------	------------------	------------------	----------------------	-------------------	-------------

9.5 44 0.0300 0.08

Sheet Flow, AB

Grass: Bermuda n= 0.410 P2= 3.30"

Shallow Concentrated Flow, BC

Paved Kv= 20.3 fps

10.0 126 Total

Summary for Subcatchment pF2: Post - Runoff to Forebay-2

Runoff = 0.07 cfs @ 12.11 hrs, Volume= 255 cf, Depth= 0.64"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr WQv Rainfall=1.20"

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr WQv Rainfall=1.20"

Printed 12/9/2022

Page 148

Area (sf)	CN	Description
1,813	74	>75% Grass cover, Good, HSG C
2,847	98	Paved parking, HSG C
150	98	Walkway
0	98	Roofs, HSG C

4,810	89	Weighted Average
1,813	74	37.69% Pervious Area
2,997	98	62.31% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.9	40	0.0400	0.08		Sheet Flow, AB
					Grass: Bermuda n= 0.410 P2= 3.30"
0.1	24	0.0200	2.87		Shallow Concentrated Flow, BC
					Paved Kv= 20.3 fps

8.0	64	Total
-----	----	-------

Summary for Subcatchment pS1: Post - Runoff to Bio-retention Basin

Runoff = 0.00 cfs @ 12.40 hrs, Volume= 15 cf, Depth= 0.06"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr WQv Rainfall=1.20"

Area (sf)	CN	Description
2,851	74	>75% Grass cover, Good, HSG C
0	98	Patio/Deck/Stairs

2,851	74	Weighted Average
2,851	74	100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry, Runoff to swale

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr WQv Rainfall=1.20"

Printed 12/9/2022

Page 149

Summary for Subcatchment pS2: Post - Runoff to Swale-1

Runoff = 0.01 cfs @ 12.07 hrs, Volume= 63 cf, Depth= 0.15"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr WQv Rainfall=1.20"

		Area (sf)	CN	Description
*		0	98	Paved parking, HSG C
		4,696	74	>75% Grass cover, Good, HSG C
		0	98	Walkway
		477	98	Patio/Deck/Stairs
		5,173	76	Weighted Average
		4,696	74	90.78% Pervious Area
		477	98	9.22% Impervious Area
Tc	Length	Slope	Velocity	Capacity
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)
5.0				

Direct Entry, Parking Runoff

Summary for Subcatchment pS3: Post - Flow to wetlands

Runoff = 0.00 cfs @ 12.67 hrs, Volume= 29 cf, Depth= 0.06"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr WQv Rainfall=1.20"

		Area (sf)	CN	Description
		5,708	74	>75% Grass cover, Good, HSG C
		0	98	Paved parking, HSG C
		0	70	Woods, Good, HSG C
		5,708	74	Weighted Average
		5,708	74	100.00% Pervious Area

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr WQv Rainfall=1.20"

Printed 12/9/2022

Page 150

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.2	50	0.0260	0.07		Sheet Flow, AB Grass: Bermuda n= 0.410 P2= 3.30"
8.6	183	0.0050	0.35		Shallow Concentrated Flow, BC Woodland Kv= 5.0 fps
1.9	117	0.0400	1.00		Shallow Concentrated Flow, CD Woodland Kv= 5.0 fps
0.3	103	0.0300	5.33	26.67	Channel Flow, DE Area= 5.0 sf Perim= 10.2' r= 0.49' n= 0.030 Earth, grassed & winding
22.1	453	Total			

Summary for Subcatchment pS4: Post - Runoff to Bio-retention Basin-4

Runoff = 0.00 cfs @ 12.45 hrs, Volume= 7 cf, Depth= 0.06"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr WQv Rainfall=1.20"

Area (sf)		CN	Description		
1,321		74	>75% Grass cover, Good, HSG C		
0		98	Paved parking, HSG C		
0		98	Walkway		
0		98	Roofs, HSG C		
1,321		74	Weighted Average		
1,321		74	100.00% Pervious Area		
Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.9	40	0.0400	0.08		Sheet Flow, AB Grass: Bermuda n= 0.410 P2= 3.30"
0.1	24	0.0200	2.87		Shallow Concentrated Flow, BC Paved Kv= 20.3 fps
8.0	64	Total			

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr WQv Rainfall=1.20"

Printed 12/9/2022

Page 151

Summary for Subcatchment pS5: Post - Runoff to Bio-retention Basin-2

Runoff = 0.01 cfs @ 12.07 hrs, Volume= 28 cf, Depth= 0.18"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr WQv Rainfall=1.20"

Area (sf)	CN	Description
0	98	Paved parking, HSG C
1,602	74	>75% Grass cover, Good, HSG C
0	98	Walkway
238	98	Patio/Deck/Stairs
0	98	Roofs, HSG C
1,840	77	Weighted Average
1,602	74	87.07% Pervious Area
238	98	12.93% Impervious Area

Tc Length Slope Velocity Capacity Description
(min) (feet) (ft/ft) (ft/sec) (cfs)

5.0

Direct Entry, AB

Summary for Subcatchment pS6: Post - Runoff to Forebay-3

Runoff = 0.12 cfs @ 12.07 hrs, Volume= 416 cf, Depth= 0.37"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr WQv Rainfall=1.20"

Area (sf)	CN	Description
3,996	98	Paved parking, HSG C
9,151	74	>75% Grass cover, Good, HSG C
493	98	Walkway
13,640	82	Weighted Average
9,151	74	67.09% Pervious Area
4,489	98	32.91% Impervious Area

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr WQv Rainfall=1.20"

Printed 12/9/2022

Page 152

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry, AB

Summary for Subcatchment pS7: Post - Flow to Hope Street

Runoff = 0.01 cfs @ 12.77 hrs, Volume= 96 cf, Depth= 0.07"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr WQv Rainfall=1.20"

Area (sf)	CN	Description
16,637	74	>75% Grass cover, Good, HSG C
0	98	Paved parking, HSG C
0	98	Walkways
122	98	Patio/Deck/Stairs
16,759	74	Weighted Average
16,637	74	99.27% Pervious Area
122	98	0.73% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
30.6	60	0.0030	0.03		Sheet Flow, AB
					Grass: Bermuda n= 0.410 P2= 3.30"
0.2	44	0.0450	3.42		Shallow Concentrated Flow, BC
					Unpaved Kv= 16.1 fps
30.8	104	Total			

Summary for Subcatchment RF1: Post - Roof Area (Units 3&4)

Runoff = 0.07 cfs @ 12.07 hrs, Volume= 210 cf, Depth= 0.99"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr WQv Rainfall=1.20"

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr WQv Rainfall=1.20"

Printed 12/9/2022

Page 153

Area (sf)	CN	Description
2,556	98	Roofs, HSG C
2,556	98	100.00% Impervious Area
Tc (min)	Length (feet)	Slope (ft/ft) Velocity (ft/sec) Capacity (cfs) Description

5.0

Direct Entry, Roof Runoff

Summary for Subcatchment RF2: Post - Roof Area (Units 5&6)

Runoff = 0.07 cfs @ 12.07 hrs, Volume= 210 cf, Depth= 0.99"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr WQv Rainfall=1.20"

Area (sf)	CN	Description
2,556	98	Roofs, HSG C
2,556	98	100.00% Impervious Area
Tc (min)	Length (feet)	Slope (ft/ft) Velocity (ft/sec) Capacity (cfs) Description

5.0

Direct Entry, Roof Runoff

Summary for Subcatchment RF3: Post - Roof Area (Units 7&8)

Runoff = 0.07 cfs @ 12.07 hrs, Volume= 210 cf, Depth= 0.99"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr WQv Rainfall=1.20"

Area (sf)	CN	Description
2,556	98	Roofs, HSG C
2,556	98	100.00% Impervious Area

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr WQv Rainfall=1.20"

Printed 12/9/2022

Page 154

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry, Roof Runoff

Summary for Subcatchment RF4: Post- Roof Area (Units 9&10)

Runoff = 0.05 cfs @ 12.07 hrs, Volume= 173 cf, Depth= 0.99"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr WQv Rainfall=1.20"

Area (sf)	CN	Description
2,102	98	Roofs, HSG C
2,102	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry, Roof Runoff

Summary for Subcatchment RF5: Post - Roof Area (Units 1&2)

Runoff = 0.07 cfs @ 12.07 hrs, Volume= 210 cf, Depth= 0.99"

Runoff by SCS TR-20 method, UH=SCS, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Type III 24-hr WQv Rainfall=1.20"

Area (sf)	CN	Description
2,556	98	Roofs, HSG C
2,556	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry, Roof Runoff

Summary for Reach S1: Post - Dry Swale 1

Inflow Area = 20,593 sf, 28.07% Impervious, Inflow Depth = 0.04" for WQv event
Inflow = 0.01 cfs @ 12.07 hrs, Volume= 63 cf
Outflow = 0.01 cfs @ 12.25 hrs, Volume= 63 cf, Atten= 20%, Lag= 10.6 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Max. Velocity= 0.36 fps, Min. Travel Time= 7.0 min
Avg. Velocity = 0.28 fps, Avg. Travel Time= 9.0 min

Peak Storage= 4 cf @ 12.13 hrs
Average Depth at Peak Storage= 0.01'
Bank-Full Depth= 1.00' Flow Area= 4.0 sf, Capacity= 17.43 cfs

Custom cross-section, Length= 150.0' Slope= 0.0200 '/
Constant n= 0.035 Earth, dense weeds
Inlet Invert= 85.00', Outlet Invert= 82.00'



Offset (feet)	Elevation (feet)	Chan.Depth (feet)
-3.00	1.00	0.00
-1.00	0.00	1.00
1.00	0.00	1.00
3.00	1.00	0.00

Depth (feet)	End Area (sq-ft)	Perim. (feet)	Storage (cubic-feet)	Discharge (cfs)
0.00	0.0	2.0	0	0.00
1.00	4.0	6.5	600	17.43

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr WQv Rainfall=1.20"

Printed 12/9/2022

Page 156

Summary for Pond SB: Post - Settling Basin

Inflow Area = 25,705 sf, 42.37% Impervious, Inflow Depth = 0.05" for WQv event
Inflow = 0.01 cfs @ 12.25 hrs, Volume= 117 cf
Outflow = 0.00 cfs @ 0.00 hrs, Volume= 0 cf, Atten= 100%, Lag= 0.0 min
Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Peak Elev= 81.65' @ 71.00 hrs Surf.Area= 253 sf Storage= 117 cf

Plug-Flow detention time= (not calculated: initial storage exceeds outflow)
Center-of-Mass det. time= (not calculated: no outflow)

Volume	Invert	Avail.Storage	Storage Description
#1	81.00'	416 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
81.00	108	0	0
82.00	331	220	220
82.50	456	197	416

Device	Routing	Invert	Outlet Devices
#1	Primary	82.00'	4.0' long x 2.0' breadth Broad-Crested Rectangular Weir

Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50
Coef. (English) 2.54 2.61 2.61 2.60 2.66 2.70 2.77 2.89 2.88 2.85 3.07 3.20 3.32

Primary OutFlow Max=0.00 cfs @ 0.00 hrs HW=81.00' (Free Discharge)
1-Broad-Crested Rectangular Weir (Controls 0.00 cfs)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr WQv Rainfall=1.20"

Printed 12/9/2022

Page 157

Summary for Pond US1: Post - Recharge System-1

Inflow Area = 5,112 sf,100.00% Impervious, Inflow Depth = 0.99" for WQv event
Inflow = 0.13 cfs @ 12.07 hrs, Volume= 420 cf
Outflow = 0.01 cfs @ 11.20 hrs, Volume= 420 cf, Atten= 94%, Lag= 0.0 min
Discarded = 0.01 cfs @ 11.20 hrs, Volume= 420 cf
Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Peak Elev= 84.61' @ 13.61 hrs Surf.Area= 715 sf Storage= 181 cf
Flood Elev= 86.30' Surf.Area= 715 sf Storage= 837 cf

Plug-Flow detention time= 185.9 min calculated for 420 cf (100% of inflow)
Center-of-Mass det. time= 185.8 min (966.9 - 781.1)

Volume	Invert	Avail.Storage	Storage Description
#1A	84.00'	405 cf	21.50"W x 33.25'L x 2.33'H Field A 1,668 cf Overall - 439 cf Embedded = 1,229 cf x 33.0% Voids
#2A	84.50'	439 cf	Infiltrator H-20 Chamber x 30 Inside #1 Effective Size= 27.5"W x 14.0"H => 2.34 sf x 6.25'L = 14.6 cf Overall Size= 34.0"W x 16.0"H x 6.25'L
		845 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Discarded	84.00'	0.500 in/hr Exfiltration over Surface area
#2	Primary	84.85'	6.0" Round Culvert L= 12.0' RCP, sq.cut end projecting, Ke= 0.500 Inlet / Outlet Invert= 84.85' / 84.60' S= 0.0208 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf

Discarded OutFlow Max=0.01 cfs @ 11.20 hrs HW=84.02' (Free Discharge)
↑**1=Exfiltration** (Exfiltration Controls 0.01 cfs)

Primary OutFlow Max=0.00 cfs @ 0.00 hrs HW=84.00' (Free Discharge)
↑**2=Culvert** (Controls 0.00 cfs)

22024 Hope Street HydroCAD 6-13-22

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 05085 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr WQv Rainfall=1.20"

Printed 12/9/2022

Page 158

Summary for Pond US2: Post - Underground Storage System

Inflow Area = 4,658 sf, 100.00% Impervious, Inflow Depth = 0.99" for WQv event
Inflow = 0.12 cfs @ 12.07 hrs, Volume= 383 cf
Outflow = 0.06 cfs @ 12.22 hrs, Volume= 383 cf, Atten= 53%, Lag= 8.8 min
Primary = 0.06 cfs @ 12.22 hrs, Volume= 383 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.04 hrs
Peak Elev= 83.32' @ 12.22 hrs Surf.Area= 790 sf Storage= 90 cf

Plug-Flow detention time= 41.7 min calculated for 382 cf (100% of inflow)
Center-of-Mass det. time= 41.9 min (823.0 - 781.1)

Volume	Invert	Avail.Storage	Storage Description
#1	83.15'	1,484 cf	18.0" Round Pipe Storage x 14 L= 60.0'

Device	Routing	Invert	Outlet Devices
#1	Primary	83.15'	4.0" Round Culvert L= 100.0' RCP, sq.cut end projecting, Ke= 0.500 Inlet / Outlet Invert= 83.15' / 82.10' S= 0.0105 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.09 sf

Primary OutFlow Max=0.06 cfs @ 12.22 hrs HW=83.32' (Free Discharge)
1-1=Culvert (Barrel Controls 0.06 cfs @ 1.90 fps)

LONGFIELD ESTATES
1200 & 1202 Hope Street - Bristol, RI
STORMWATER MANAGEMENT
STORMWATER RUNOFF VOLUME & FLOW RATES SUMMARY

SDE Job No.: 22024
Prepared by: SJE

Date: 6/20/2022 , Revised: 12/9/2022
Checked by: MER

PRE-DEVELOPMENT

Analysis Points (Subcatchment/Pond)	Storm Event									
	1-yr		2-yr		10-yr		25-yr		100-yr	
	Rate (cfs)	Vol. (cf)	Rate (cfs)	Vol. (cf)	Rate (cfs)	Vol. (cf)	Rate (cfs)	Vol. (cf)	Rate (cfs)	Vol. (cf)
eA1	0.20	682	0.25	944	0.58	1,895	0.83	2,678	1.36	4,408
eA2	1.08	5,293	1.53	7,233	3.15	14,295	4.47	20,129	7.34	33,076
Totals	1.28	5,975	1.78	8,177	3.73	16,190	5.30	22,807	8.70	37,484

POST-DEVELOPMENT

Analysis Points (Subcatchment/Pond)	Storm Event									
	1-yr		2-yr		10-yr		25-yr		100-yr	
	Rate (cfs)	Vol. (cf)	Rate (cfs)	Vol. (cf)	Rate (cfs)	Vol. (cf)	Rate (cfs)	Vol. (cf)	Rate (cfs)	Vol. (cf)
pA1	0.02	126	0.16	501	0.52	1,964	0.73	3,214	1.20	5,986
pA2	0.39	6,541	0.76	8,631	2.02	15,811	2.96	21,513	6.49	33,700
Totals	0.41	6,667	0.92	9,132	2.54	17,775	3.69	24,727	7.69	39,686

Notes:

Totals are the summations of the Analysis points values (Overall combine values leaving the site).
Analysis points **eA1** & **pA1** are pre-development and post-development comparisons. (Site's runoff flow toward Hope Street)
Analysis points **eP1** & **pP1** are pre-development and post-development comparisons. (Site's runoff flow to the existing wetland)

Refer to Hydrocad® calculations for additional information.

LONGFIELD ESTATES
1200 & 1202 Hope Stree - Bristol, RI
STORMWATER MANAGEMENT
STORMWATER RECHARGE CALCULATION WORKSHEET

SDE Job No.: 22024
Prepared by: SJE

Date: 6/20/2022 , Revised: 12/9/2022
Checked by: MER

Hydrologic Group	A	B	C	D	ReV
Target Runoff Depth Factor (Inches of Runoff)	0.60	0.35	0.25	0.10	(cf)
Total Increase of Impervious Areas, (sf):					
Proposed Driveway & Parking			13,626		
Proposed Buildings			10,224		
X inches of runoff, (cf)	0	0	497	0	497
Total Recharge Volume Required = $1" \times F \times Ai / 12$, (ac-ft.)			Total ReV (cf) =		497

Structure	Infiltration Rate (inches / hour)	Recharged Volume (cu.ft.)	ReV Volume Below Outlet Structure (cu.ft.)
Underground System-1	0.50	764	319
Total Recharge Volume Provided, (cf) =		765	319

Note:

1. System Infiltration rates are derived from the 1982 Rawls rates based on field observed soil texture (HSG C).
2. Recharged volume are calculated utilizing Simple Dynamic Method : Automated
3. Calculations are based on 1-Yr , 24-Hr storm event.

LONGFIELD ESTATES
1200 & 1202 Hope Street - Bristol, RI
STORMWATER MANAGEMENT
WATER QUALITY TREATMENT VOLUME CALCULATION WORKSHEET

SDE Job No.: 22024
Prepared by: SJE

Date: 6/20/2022 , Revised: 12/9/2022
Checked by: MER

Impervious Area	Area sf		X in. of runoff 1.0 cf		1.2 inch rainfall cf
Total Impervious Area Excluding Roof	13,626		1,136		
Building Roof Area	12,326		1,027		
1.2 inch rainfall total runoff					2,575
Total Water Quality Volume , (cf) =			2,163		2,575
<u>System Water Quality Volume</u> <u>(volumes below lowest outlet device)</u>	Impervious Area to BMP	WQv	Treatment Required (cf)	Pretreatment Provided (cf)	Extended Treatment (cf)
(FB1) Forebay-1 =	5,303 sf	442.0	25% = 111	173	1,315
(BR1) Bio-Retention Basin-1 =			75% = 331		
(FB3) Forebay-3 =	9,147 sf	762.0	25% = 191	192	Required = 805 Provided = 805
(BR2) Bio-Retention Basin-2 =			75% = 572		
	4' 2,794 sf	233.0	100% = 233		
(BR3) Bio-Retention Basin-3 =	4' 122 sf	10.0	100% = 10		503
(US1) Underground System-1 =	5' 5,112 sf	426.0	100% = 426		WQv storm contained & infiltrated (426 cf)
(FB2) Forebay-2 =	2,997 sf	250.0	25% = 63	76	255
(BR4) Bio-Retention Basin-4 =			75% = 187		
Total =	25,475 sf			441	3,304
Total Water Quality Volume Available , (cf) =			3,745		

Note:

1. Total water quality volume (WQV) in the 1.2 inch rainfall event is the inflow volume flowing toward the drainage system.
2. Recharged volume are calculated utilizing Simple Dynamic Method : Automated
3. Refer to HydroCAD report for additional information.
4. Inflow is roof runoff and/or deck/patio runoff that directly flows into bio-retention basins 2&3
5. Inflow is roof runoff only '5'
6. 477 sf of deck/patio area discharges into the dry swale before entering the extended detention basin.

LONGFIELD ESTATES
1200 & 1202 Hope Street - Bristol, RI
STORMWATER MANAGEMENT
TSS REMOVAL CALCULATION WORKSHEET

SDE Job No.: 22024
Prepared by: SJE

Date: 6/20/2022 , Revised: 12/9/2022
Checked by: MER

Design Point PA1 - Hope Street

A BMP	B TSS Removal Rate	C Starting TSS Load*	D Amount Removed (BxC)	E Remaining Load (C-D)
Bio-retention Basin	90.0%	1.000	0.900	0.100
	0.0%	0.100	0.000	0.100
		0.100	0.000	0.100
Total TSS Removal =			90.0%	

Design Point PA2 - Existing Wetland

A BMP	B TSS Removal Rate	C Starting TSS Load*	D Amount Removed (BxC)	E Remaining Load (C-D)
Forebay	25.0%	1.000	0.250	0.750
Bio-retention Basin	90.0%	0.750	0.675	0.075
		0.075	0.000	0.075
Total TSS Removal =			92.5%	



STATE OF RHODE ISLAND AND PROVIDENCE PLANTATIONS

Department of Environmental Management
Office of Water Resources
Onsite Wastewater Treatment System Program



Site Evaluation Form

Part A - Soil Profile Description

Application Number _____

Property Owner: 1200 HOPE STREET, L.L.C.Property Location: BRISTOL 1200 HOPE STREETDate of Test Hole: 10 DECEMBER, 2018Soil Evaluator: N. LETENDRELicense Number: D4019Weather: SUNNY 36°F 0-5mphShaded: Yes ☐ No ☐ Time: 10:30

TH 1 Horizon	Depth	Horizon Boundaries		Soil Colors		Re-Dox		Texture	Structure	Consistence	Soil Category
		Dist	Topo	Matrix	Re-Dox Features	Ab.	S. Contr.				
A	6	g	s	10YR 3/3				FSL	1fgr	fr	4
Bw ₁	12	g	s	10YR 3/6				SL	1fsbk	fr	3
Bw ₂	20	c	w	10YR 4/4				SL	1fsbk	fr	3
C	30	c	w	2.5Y 9/2	@ 24 2.5Y 5/6	f	1 f	SL	omm	fr	6
Cd	52			2.5Y 4/1	10YR 5/6	c	1 d	FSL	omm	Vfi	9
TH 2 Horizon	Depth	Horizon Boundaries		Soil Colors		Re-Dox		Texture	Structure	Consistence	Soil Category
		Dist	Topo	Matrix	Re-Dox Features	Ab.	S. Contr.				
A	10	c	w	10YR 3/3				ch FSL	1fgr	fr	4
Bw	16	c	w	10YR 4/6	@ 12 10YR 5/8	f	1 f	SL	1fsbk.	fr	3
C	50			2.5Y 4/1	10YR 5/6	c	1 d	FSL	omm	fr	7

TH 1 Soil Class A Total Depth 52" Impervious/Limiting Layer Depth N/A (og) GW Seepage Depth N/A SHWT 24" (og)TH 2 Soil Class A Total Depth 50" Impervious/Limiting Layer Depth N/A (og) GW Seepage Depth 38" SHWT 12" (og)

Comments: _____

Part B

Site Evaluation – to be completed by Soil Evaluator or Class II or III Designer


Please use the area below to locate:

1. Test holes and bedrock test holes,
2. Approximate direction of due north,
3. Offsets from all test holes to fixed points such as street, utility pole, or other permanent, marked object.*

*OFFSETS MUST BE SHOWN

Key:

- Approximate location of test holes
- Approximate location of bedrock test holes
- Estimated gradient and direction of slope
- Approximate direction of due north



1. Relief and Slope: _____
2. Presence of any watercourse, wetlands or surface water bodies, within 200 feet of test holes? If yes, locate on above sketch. NO ☒ YES ☐
3. Restrictive Layer or Bedrock within 4' below original ground within 25 feet of test hole? Provide all test hole locations & depths above. NO ☒ YES ☐
4. Presence of existing or proposed private drinking water wells within 200 feet of test holes? If yes, locate on above sketch. NO ☒ YES ☐
5. Public drinking water wells within 500 feet of test holes? If yes, locate on above sketch. NO ☒ YES ☐
6. Is site within the watershed of a public drinking water reservoir or other critical area defined in Rule 38? NO ☒ YES ☐
7. Has soil been excavated from or fill deposited on site? If yes, locate on above sketch. SITE IS PREVIOUSLY DEVELOPED NO ☐ YES ☒
8. Site's potential for flooding or ponding: NONE ☐ SLIGHT ☒ MODERATE ☐ SEVERE ☐
9. Landscape position: SHOULDER SLOPE
10. Vegetation: DISTURBANCE VARIETY
11. Indicate approximate location of property lines and roadways.
12. Additional comments, site constraints or additional information regarding site: _____

Certification

The undersigned hereby certifies that all information on this application and accompanying forms, submittals and sketches are true and accurate and that I have been authorized by the owner(s) to conduct these necessary field investigations and submit this request.

Part A prepared by: [Signature] D4C19 License # _____ Part B prepared by: [Signature] D4C19 License # _____

DO NOT WRITE IN THIS SPACE

Witnessed Soil Evaluation Decision: Concur ☐ Inconclusive ☐ Disclaim ☐

Unwitnessed Soil Evaluations Decision: Accept ☐ Inconclusive ☐ Disclaim ☐

Wet Season Determination required ☐ Additional Field Review Required ☐

Explanation: _____

Signature Authorized Agent

Date



STATE OF RHODE ISLAND AND PROVIDENCE PLANTATIONS

Department of Environmental Management
Office of Water Resources
Onsite Wastewater Treatment System Program



Site Evaluation Form

Part A - Soil Profile Description

Application Number _____

Property Owner: 1200 HOPE STREET, L.L.C.Property Location: BRISTOL 1200 HOPE STREETDate of Test Hole: 10 DECEMBER, 2018Soil Evaluator: N. LETENDRELicense Number: D4019Weather: SUNNY 36°F 0-5 mphShaded: Yes ☐ No ☐ Time: 10:30

TH <u>3</u> Horizon	Depth	Horizon Boundaries		Soil Colors		Re-Dox		Texture	Structure	Consistence	Soil Category
		Dist	Topo	Matrix	Re-Dox Features	Ab.	S. Contr.				
FILL	-8 to 0										
A	10	C	S	10YR 3/4				FSL	1fsbk	fr	4
Bw ₁	17	g	w	10YR 4/2				SL	1fsbk	fr	3
Bw ₂	22	C	S	10YR 4/4				SL	1fsbk	fr	3
C	26	e	w	2.5Y 4/2	@24 2.5Y 4/4	f	1 f.	gLS	omm	fr	6
2C	42			2.5Y 4/1	10YR 5/6	C	1 d	FSL	omm	fr	7
TH <u>4</u> Horizon	Depth	Horizon Boundaries		Soil Colors		Re-Dox		Texture	Structure	Consistence	Soil Category
		Dist	Topo	Matrix	Re-Dox Features	Ab.	S. Contr.				
Ap	10	e	w	10YR 3/3				FSL	1fgr	1fr	4
Bw ₁	16	g	w	10YR 4/6				SL	1fsbk	fr	3
Bw ₂	21	g	w	10YR 5/4				SL	1fsbk	fr	3
C	36	C	i	2.5Y 6/4	@24 10YR 5/6	e	1 d	FSL	omm	fr	7
2C	57			5Y 4/2	10YR 5/6	C	1 d	vgSL	omm	fip fih	8

TH 3 Soil Class A Total Depth 50" Impervious/Limiting Layer Depth N/A (og) GW Seepage Depth N/A SHWT 24" (og)TH 4 Soil Class A Total Depth 57" Impervious/Limiting Layer Depth N/A (og) GW Seepage Depth N/A SHWT 24" (og)

Comments: _____

Part B


Site Evaluation -- to be completed by Soil Evaluator or Class II or III Designer

Please use the area below to locate:

1. Test holes and bedrock test holes,
2. Approximate direction of due north,
3. Offsets from all test holes to fixed points such as street, utility pole, or other permanent, marked object.*

*OFFSETS MUST BE SHOWN

Key:	
	Approximate location of test holes
	Approximate location of bedrock test holes
	Estimated gradient and direction of slope
	Approximate direction of due north



1. Relief and Slope: _____
2. Presence of any watercourse, wetlands or surface water bodies, within 200 feet of test holes? If yes, locate on above sketch. NO ☒ YES ☐
3. Restrictive Layer or Bedrock within 4' below original ground within 25 feet of test hole? Provide all test hole locations & depths above. NO ☒ YES ☐
4. Presence of existing or proposed private drinking water wells within 200 feet of test holes? If yes, locate on above sketch. NO ☒ YES ☐
5. Public drinking water wells within 500 feet of test holes? If yes, locate on above sketch. NO ☒ YES ☐
6. Is site within the watershed of a public drinking water reservoir or other critical area defined in Rule 38? NO ☒ YES ☐
7. Has soil been excavated from or fill deposited on site? If yes, locate on above sketch. SITE IS PREVIOUSLY DEVELOPED NO ☐ YES ☒
8. Site's potential for flooding or ponding: NONE ☐ SLIGHT ☒ MODERATE ☐ SEVERE ☐
9. Landscape position: SHOULDER SLOPE
10. Vegetation: DISTURBANCE VARIETY
11. Indicate approximate location of property lines and roadways.
12. Additional comments, site constraints or additional information regarding site: _____

Certification

The undersigned hereby certifies that all information on this application and accompanying forms, submittals and sketches are true and accurate and that I have been authorized by the owner(s) to conduct these necessary field investigations and submit this request.

Part A prepared by: [Signature] D4619
Signature License #

Part B prepared by: [Signature] D4619
Signature License #

DO NOT WRITE IN THIS SPACE

Witnessed Soil Evaluation Decision: Concur ☐ Inconclusive ☐ Disclaim ☐

Unwitnessed Soil Evaluations Decision: Accept ☐ Inconclusive ☐ Disclaim ☐

Wet Season Determination required ☐ Additional Field Review Required ☐

Explanation: _____

Signature Authorized Agent

Date



STATE OF RHODE ISLAND AND PROVIDENCE PLANTATIONS

Department of Environmental Management
Office of Water Resources
Onsite Wastewater Treatment System Program



Site Evaluation Form

Part A - Soil Profile Description

Application Number _____

Property Owner: 1200 HOPE STREET, L.L.C.Property Location: BRISTOL 1200 HOPE STREETDate of Test Hole: 10 DECEMBER, 2018Soil Evaluator: N. LETENDRELicense Number: D4019Weather: SUNNY 32°F 0-5mphShaded: Yes ☐ No ☐ Time: 10:30

TH <u>5</u> Horizon	Depth	Horizon Boundaries		Soil Colors		Re-Dox		Texture	Structure	Consistence	Soil Category
		Dist	Topo	Matrix	Re-Dox Features	Ab.	S. Contr.				
<u>FILL</u>	<u>-30 to 0</u>										
<u>C</u>	<u>12</u>	<u>C</u>	<u>b</u>	<u>2.5Y 6/4</u>	<u>@ 0 10YR 5/8</u>	<u>C</u>	<u>1 d</u>	<u>FSL</u>	<u>omm</u>	<u>fr</u>	<u>7</u>
<u>C</u>	<u>18</u>			<u>5Y 4/2</u>	<u>10YR 5/6</u>	<u>C</u>	<u>1 d</u>	<u>vgSL</u>	<u>omm</u>	<u>fr</u>	<u>6</u>
TH <u>6</u> Horizon	Depth	Horizon Boundaries		Soil Colors		Re-Dox		Texture	Structure	Consistence	Soil Category
		Dist	Topo	Matrix	Re-Dox Features	Ab.	S. Contr.				
<u>Ap</u>	<u>12</u>	<u>C</u>	<u>S</u>	<u>10YR 3/3</u>				<u>FSL</u>	<u>1 fgr</u>	<u>Vsr</u>	<u>4</u>
<u>Bw₁</u>	<u>20</u>	<u>g</u>	<u>i</u>	<u>10YR 4/6</u>				<u>vc bSL</u>	<u>1 f b k</u>	<u>fr</u>	<u>3</u>
<u>Bw₂</u>	<u>29</u>	<u>g</u>	<u>S</u>	<u>10YR 5/4</u>				<u>cb SL</u>	<u>1 f b k</u>	<u>fr</u>	<u>3</u>
<u>C</u>	<u>38</u>	<u>C</u>	<u>S</u>	<u>2.5Y 6/3</u>	<u>@ 32 10YR 5/6</u>	<u>f</u>	<u>1 d</u>	<u>SL</u>	<u>omm</u>	<u>fr</u>	<u>6</u>
<u>Cd</u>	<u>56</u>			<u>2.5Y 4/1</u>	<u>10YR 5/6</u>	<u>C</u>	<u>1 d</u>	<u>gSL</u>	<u>omm</u>	<u>fi</u>	<u>8</u>

TH 5 Soil Class A Total Depth 48" Impervious/Limiting Layer Depth N/A (og) GW Seepage Depth N/A SHWT 0 (og)TH 6 Soil Class A Total Depth 56" Impervious/Limiting Layer Depth N/A (og) GW Seepage Depth N/A SHWT 32" (og)

Comments: _____

Part B

Site Evaluation - to be completed by Soil Evaluator or Class II or III Designer


Please use the area below to locate:

1. Test holes and bedrock test holes,
2. Approximate direction of due north,
3. Offsets from all test holes to fixed points such as street, utility pole, or other permanent, marked object.*

*OFFSETS MUST BE SHOWN

Key:

- Approximate location of test holes
- Approximate location of bedrock test holes
- Estimated gradient and direction of slope
- Approximate direction of due north



1. Relief and Slope: _____
2. Presence of any watercourse, wetlands or surface water bodies, within 200 feet of test holes? If yes, locate on above sketch. NO ☒ YES ☐
3. Restrictive Layer or Bedrock within 4' below original ground within 25 feet of test hole? Provide all test hole locations & depths above. NO ☒ YES ☐
4. Presence of existing or proposed private drinking water wells within 200 feet of test holes? If yes, locate on above sketch. NO ☒ YES ☐
5. Public drinking water wells within 500 feet of test holes? If yes, locate on above sketch. NO ☒ YES ☐
6. Is site within the watershed of a public drinking water reservoir or other critical area defined in Rule 38? NO ☒ YES ☐
7. Has soil been excavated from or fill deposited on site? If yes, locate on above sketch. SITE IS PREVIOUSLY DEVELOPED NO ☐ YES ☒
8. Site's potential for flooding or ponding: NONE ☐ SLIGHT ☒ MODERATE ☐ SEVERE ☐
9. Landscape position: SHOULDER SLOPE
10. Vegetation: DISTURBANCE VARIETY
11. Indicate approximate location of property lines and roadways.
12. Additional comments, site constraints or additional information regarding site: _____

Certification

The undersigned hereby certifies that all information on this application and accompanying forms, submittals and sketches are true and accurate and that I have been authorized by the owner(s) to conduct these necessary field investigations and submit this request.

Part A prepared by: [Signature] D4619
Signature License #

Part B prepared by: [Signature] D4619
Signature License #

DO NOT WRITE IN THIS SPACE

Witnessed Soil Evaluation Decision: Concur ☐ Inconclusive ☐ Disclaim ☐

Unwitnessed Soil Evaluations Decision: Accept ☐ Inconclusive ☐ Disclaim ☐

Wet Season Determination required ☐ Additional Field Review Required ☐

Explanation: _____

Signature Authorized Agent _____ Date _____

APPENDIX A: STORMWATER MANAGEMENT PLAN CHECKLIST AND LID PLANNING REPORT – STORMWATER DESIGN SUMMARY

PROJECT NAME Longfield Estates	(RIDEM USE ONLY) STW/WQC File #: Date Received:
TOWN Bristol	
BRIEF PROJECT DESCRIPTION: Construction of 4 residential structures with associated improvements and renovations of an existing dwelling.	

Stormwater Management Plan (SMP) Elements – Minimum Standards

When submitting a SMP,¹ submit **four separately bound** documents: Appendix A Checklist; Stormwater Site Planning, Analysis and Design Report with Plan Set/Drawings; Soil Erosion and Sediment Control (SESC) Plan, and Post Construction Operations and Maintenance (O&M) Plan. Please refer to [Suggestions to Promote Brevity](#).

Note: All stormwater construction projects **must create** a Stormwater Management Plan (SMP). However, not every element listed below is required per the [RIDEM Stormwater Rules](#) and the [RIPDES Construction General Permit \(CGP\)](#). This checklist will help identify the required elements to be submitted with an Application for Stormwater Construction Permit & Water Quality Certification.

PART 1. PROJECT AND SITE INFORMATION

PROJECT TYPE (Check all that apply)				
☒ Residential	☐ Commercial	☐ Federal	☐ Retrofit	☐ Restoration
☒ Road	☒ Utility	☒ Fill	☐ Dredge	☐ Mine
☐ Other (specify):				

SITE INFORMATION

☒ Vicinity Map
--

INITIAL DISCHARGE LOCATION(S): The WQv discharges to: (You may choose more than one answer if several discharge points are associated with the project.)

☒ Groundwater	☒ Surface Water	☐ MS4
☐ GAA	☒ Isolated Wetland	☐ RIDOT
☐ GA	☐ Named Waterbody	☐ RIDOT Alteration Permit is Approved
☒ GB	☐ Unnamed Waterbody Connected to Named Waterbody	☐ Town
		☐ Other (specify):

ULTIMATE RECEIVING WATERBODY LOCATION(S): Include pertinent information that applies to both WQv and flow from larger storm events including overflows. Choose all that apply, and repeat table for each waterbody.

☒ Groundwater or Disconnected Wetland	☐ SRWP
☐ Waterbody Name:	☐ Coldwater ☐ Warmwater ☐ Unassessed
☐ Waterbody ID:	☐ 4 th order stream of pond 50 acres or more
☐ TMDL for:	☐ Watershed of flood prone river (e.g., Pocasset River)
☐ Contributes to a priority outfall listed in the TMDL	☐ Contributes stormwater to a public beach
☐ 303(d) list – Impairment(s) for:	☐ Contributes to shellfishing grounds

¹ Applications for a Construction General Permit that do not require any other permits from RIDEM and will disturb less than 5 acres over the entire course of the project do not need to submit a SMP. The Appendix A checklist must still be submitted.

PROJECT HISTORY		
☐ RIDEM Pre- Application Meeting	Meeting Date:	☐ Minutes Attached
☐ Municipal Master Plan Approval	Approval Date:	☐ Minutes Attached
☐ Subdivision Suitability Required	Approval #:	
☐ Previous Enforcement Action has been taken on the property	Enforcement #:	
FLOODPLAIN & FLOODWAY See Guidance Pertaining to Floodplain and Floodways		
☐ Riverine 100-year floodplain: FEMA FLOODPLAIN FIRMETTE has been reviewed and the 100-year floodplain is on site		
☐ Delineated from FEMA Maps		
NOTE: Per Rule 250-RICR-150-10-8-1.1(B)(5)(d)(3), provide volumetric floodplain compensation calculations for cut and fill/displacement calculated by qualified professional		
☐ Calculated by Professional Engineer		
☐ Calculations are provided for cut vs. fill/displacement volumes proposed within the 100-year floodplain	Amount of Fill (CY):	
	Amount of Cut (CY):	
☐ Restrictions or modifications are proposed to the flow path or velocities in a floodway		
☐ Floodplain storage capacity is impacted		
☐ Project area is not within 100-year floodplain as defined by RIDEM		

CRMC JURISDICTION
☐ CRMC Assent required
☐ Property subject to a Special Area Management Plan (SAMP). If so, specify which SAMP:
☐ Sea level rise mitigation has been designed into this project

LUHPPL IDENTIFICATION - MINIMUM STANDARD 8:		
1. OFFICE OF Land Revitalization and Sustainable Materials Management (OLRSMM)		
☐ Known or suspected releases of HAZARDOUS MATERIAL are present at the site (Hazardous Material is defined in Rule 1.4(A)(33) of 250-140-30-1 of the RIDEM Rules and Regulations for Investigation and Remediation of Hazardous Materials (the Remediation Regulations))		RIDEM CONTACT:
☐ Known or suspected releases of PETROLEUM PRODUCT are present at the site (Petroleum Product as defined in Rule 1.5(A)(84) of 250-140-25-1 of the RIDEM Rules and Regulations for Underground Storage Facilities Used for Regulated Substances and Hazardous Materials)		
☐ This site is identified on the RIDEM Environmental Resources Map as one of the following regulated facilities		SITE ID#:
☐ CERCLIS/Superfund (NPL)		
☐ State Hazardous Waste Site (SHWS)		
☐ Environmental Land Usage Restriction (ELUR)		
☐ Leaking Underground Storage Tank (LUST)		
☐ Closed Landfill		
Note: If any boxes in 1 above are checked, the applicant must contact the RIDEM OLRSM Project Manager associated with the Site to determine if subsurface infiltration of stormwater is allowable for the project. Indicate if the infiltration corresponds to "Red," "Yellow" or "Green" as described in Section 3.2.8 of the RISDISM Guidance (Subsurface Contamination Guidance). Also, note and reference approval in PART 3, Minimum Standard 2: Groundwater Recharge/Infiltration.		
2. PER MINIMUM STANDARD 8 of RICR 8.14.C.1-6 "LUHPPLS," THE SITE IS/HAS:		
☐ Industrial Site with RIPDES MSGP, except where No Exposure Certification exists. http://www.dem.ri.gov/programs/water/permits/ripdes/stormwater/status.php		
☐ Auto Fueling Facility (e.g., gas station)		
☐ Exterior Vehicles Service, Maintenance, or Equipment Cleaning Area		

Stormwater Management, Design, and Installation Rules (250-RICR-150-10-8)

☐	Road Salt Storage and Loading Areas (exposed to rainwater)	
☐	Outdoor Storage and Loading/Unloading of Hazardous Substances	
3. STORMWATER INDUSTRIAL PERMITTING		
☐	The site is associated with existing or proposed activities that are considered Land Uses with Higher Potential Pollutant Loads (LUHPPLS) (see RICR 8.14.C)	Activities: Sector:
☐	Construction is proposed on a site that is subject to THE MULTI-SECTOR GENERAL PERMIT (MSGP) UNDER RULE 31(B)15 OF THE RIPDES REGULATIONS.	MSGP permit #
☐	Additional stormwater treatment is required by the MSGP Explain:	

REDEVELOPMENT STANDARD – MINIMUM STANDARD 6		
☒ Pre Construction Impervious Area		
☒	Total Pre-Construction Impervious Area (TIA): 5,106 sf	
☒	Total Site Area (TSA): 76,705 sf	
☒	Jurisdictional Wetlands (JW): 48 sf	
☒	Conservation Land (CL)	
☐ Calculate the Site Size (defined as contiguous properties under same ownership)		
☒	Site Size (SS) = (TSA) – (JW) – (CL)	
☒	(TIA) / (SS) = 0.067	☐ (TIA) / (SS) >0.4?
☐ YES, Redevelopment		

PART 2. LOW IMPACT DEVELOPMENT ASSESSMENT – MINIMUM STANDARD 1
(NOT REQUIRED FOR REDEVELOPMENT OR RETROFITS)
This section may be deleted if not required.

Note: A written description must be provided specifying why each method is not being used or is not applicable at the Site. Appropriate answers may include:

- Town requires ... (state the specific local requirement)
- Meets Town's dimensional requirement of ...
- Not practical for site because ...
- Applying for waiver/variance to achieve this (pending/approved/denied)
- Applying for wavier/variance to seek relief from this (pending/approved/denied)

A) PRESERVATION OF UNDISTURBED AREAS, BUFFERS, AND FLOODPLAINS

- ☒ Sensitive resource areas and site constraints are identified (required)
- ☒ Local development regulations have been reviewed (required)
- ☒ All vegetated buffers and coastal and freshwater wetlands will be protected during and after construction
- ☐ Conservation Development or another site design technique has been incorporated to protect open space and pre-development hydrology. **Note:** If Conservation Development has been used, check box and skip to Subpart C
- ☒ As much natural vegetation and pre-development hydrology as possible has been maintained

IF NOT IMPLEMENTED, EXPLAIN HERE

B) LOCATE DEVELOPMENT IN LESS SENSITIVE AREAS AND WORK WITH THE NATURAL LANDSCAPE CONDITIONS, HYDROLOGY, AND SOILS ☐ Development sites and building envelopes have been appropriately distanced from wetlands and waterbodies ☐ Development and stormwater systems have been located in areas with greatest infiltration capacity (e.g., soil groups A and B) ☐ Plans show measures to prevent soil compaction in areas designated as Qualified Pervious Areas (QPA's) ☐ Development sites and building envelopes have been positioned outside of floodplains ☒ Site design positions buildings, roadways and parking areas in a manner that avoids impacts to surface water features ☒ Development sites and building envelopes have been located to minimize impacts to steep slopes ($\geq 15\%$) ☐ Other (describe):	
C) MINIMIZE CLEARING AND GRADING ☒ Site clearing has been restricted to <u>minimum area needed</u> for building footprints, development activities, construction access, and safety. ☒ Site has been designed to position buildings, roadways, and parking areas in a manner that minimizes grading (cut and fill quantities) ☐ Protection for stands of trees and individual trees and their root zones to be preserved has been specified, and such protection extends at least to the tree canopy drip line(s) ☐ Plan notes specify that public trees removed or damaged during construction shall be replaced with equivalent	
D) REDUCE IMPERVIOUS COVER ☐ Reduced roadway widths (≤ 22 feet for ADT ≤ 400; ≤ 26 feet for ADT 400 - 2,000) ☐ Reduced driveway areas (length minimized via reduced ROW width (≤ 45 ft.) and/or reduced (or absolute minimum) front yard setback; width minimized to ≤ 9 ft. wide one lane; ≤ 18 ft. wide two lanes; shared driveways; pervious surface) ☐ Reduced building footprint: Explain approach: ☐ Reduced sidewalk area (≤ 4 ft. wide; one side of the street; unpaved path; pervious surface) ☐ Reduced cul-de-sacs (radius < 45 ft; vegetated island; alternative turn-around) ☐ Reduced parking lot area: Explain approach ☐ Use of pervious surfaces for driveways, sidewalks, parking areas/overflow parking areas, etc. ☐ Minimized impervious surfaces (project meets or is less than maximum specified by Zoning Ordinance) ☐ Other (describe):	
E) DISCONNECT IMPERVIOUS AREA ☐ Impervious surfaces have been disconnected, and runoff has been diverted to QPAs to the maximum extent possible ☐ Residential street edges allow side-of-the-road drainage into vegetated open swales ☐ Parking lot landscaping breaks up impervious expanse AND accepts runoff ☐ Other (describe):	
F) MITIGATE RUNOFF AT THE POINT OF GENERATION ☒ Small-scale BMPs have been designated to treat runoff as close as possible to the source	

Stormwater Management, Design, and Installation Rules (250-RICR-150-10-8)

G) PROVIDE LOW-MAINTENANCE NATIVE VEGETATION ☐ Low-maintenance landscaping has been proposed using native species and cultivars ☐ Plantings of native trees and shrubs in areas previously cleared of native vegetation are shown on site plan ☐ Lawn areas have been limited/minimized, and yards have been kept undisturbed to the maximum extent practicable on residential lots	
H) RESTORE STREAMS/WETLANDS ☐ Historic drainage patterns have been restored by removing closed drainage systems, daylighting buried streams, and/or restoring degraded stream channels and/or wetlands ☐ Removal of invasive species ☐ Other	

PART 3. SUMMARY OF REMAINING STANDARDS

GROUNDWATER RECHARGE – MINIMUM STANDARD 2		
YES	NO	
☒	☐	The project has been designed to meet the groundwater recharge standard.
☐	☐	If “No,” the justification for groundwater recharge criterion waiver has been explained in the Narrative (e.g., threat of groundwater contamination or physical limitation), if applicable (see RICR 8.8.D);
☐	☐	Your waiver request has been explained in the Narrative, if applicable.
☐	☒	Is this site identified as a Regulated Facility in Part 1, Minimum Standard 8: LUHPPL Identification?
☐	☐	If “Yes,” has approval for infiltration by the OLRSM Site Project Manager, per Part 1, Minimum Standard 8, been requested?

TABLE 2-1: Summary of Recharge (see RISDISM Section 3.3.2)
(Add or Subtract Rows as Necessary)

Design Point	Impervious Area Treated (sq ft)	Total Re _v Required (cu ft)	LID Stormwater Credits (see RISDISM Section 4.6.1)	Recharge Required by Remaining BMPs (cu ft)	Recharge Provided by BMPs (cu ft)
			Portion of Re _v directed to a QPA (cu ft)		
DP-1:	23,850	497		497	764
DP-2:					
DP-3:					
DP-4:					
TOTALS:					

Notes:

- Only BMPs listed in RISDISM Table 3-5 “List of BMPs Acceptable for Recharge” may be used to meet the recharge requirement.
- Recharge requirement must be satisfied for each waterbody ID.

☒ Indicate where the pertinent calculations and/or information for the above items are provided (i.e., name of report/document, page numbers, appendices, etc.):

See Appendix 2 of the Stormwater Management Report

Stormwater Management, Design, and Installation Rules (250-RICR-150-10-8)

WATER QUALITY – MINIMUM STANDARD 3		
YES	NO	
☒	☐	Does this project meet or exceed the required water quality volume WQv (see RICR 8.9.E-I)?
☒	☐	Is the proposed final impervious cover greater than 20% of the disturbed area (see RICR 8.9.E-I)?
☒	☐	If “Yes,” either the Modified Curve Number Method or the Split Pervious/Impervious method in Hydro-CAD was used to calculate WQv; or,
☐	☐	If “Yes,” either TR-55 or TR-20 was used to calculate WQv; and,
☐	☐	If “No,” the project meets the minimum WQv of 0.2 watershed inches over the entire disturbed area.
☐	☐	Not Applicable
☒	☐	Does this project meet or exceed the ability to treat required water quality flow WQf (see RICR 8.9.I.1-3)?
☐	☒	Does this project propose an increase of impervious cover to a receiving water body with impairments? If “Yes,” please indicate below the method that was used to address the water quality requirements of no further degradation to a low-quality water.
☐	☒	RICR 8.36. A Pollutant Loading Analysis is needed and has been completed.
☐	☐	The Water Quality Guidance Document (Water Quality Goals and Pollutant Loading Analysis Guidance for Discharges to Impaired Waters) has been followed as applicable.
☐	☒	BMPs are proposed that are on the approved technology list . If “Yes,” please provide all required worksheets from the manufacturer.
☐	☐	Additional pollutant-specific requirements and/or pollutant removal efficiencies are applicable to the site as the result of a TMDL, SAMP, or other watershed-specific requirements. If “Yes,” please describe:

TABLE 3-1: Summary of Water Quality (see RICR 8.9)					
Design Point and WB ID	Impervious area treated (sq ft)	Total WQ _v Required (cu ft)	LID Stormwater Credits (see RICR 8.18)	Water Quality Treatment Remaining (cu ft)	Water Quality Provided by BMPs (cu ft)
			WQ _v directed to a QPA (cu ft)		
DP-1:	25,952	2,163		2,163	3,745
DP-2:					
DP-3:					
DP-4:					
TOTALS:					
Notes: 1. Only BMPs listed in RICR 8.20 and 8.25 or the Approved Technologies List of BMPs is Acceptable for Water Quality treatment. 2. For each Design Point, the Water Quality Volume Standard must be met for each Waterbody ID.					
☒ YES ☐ NO		This project has met the setback requirements for each BMP. If “No,” please explain:			
☒ Indicate where the pertinent calculations and/or information for the above items are provided (i.e., name of report/document, page numbers, appendices, etc.): See Appendix 2 of the Stormwater Management Report					

Stormwater Management, Design, and Installation Rules (250-RICR-150-10-8)

CONVEYANCE AND NATURAL CHANNEL PROTECTION (RICR 8.10) – MINIMUM STANDARD 4		
YES	NO	
☒	☐	Is this standard waived? If “Yes,” please indicate one or more of the reasons below:
		☐ The project directs discharge to a large river (i.e., 4th-order stream or larger. See RISDISM Appendix I for State-wide list and map of stream orders), bodies of water >50.0 acres in surface area (i.e., lakes, ponds, reservoirs), or tidal waters. ☒ The project is a small facility with impervious cover of less than or equal to 1 acre. ☐ The project has a post-development peak discharge rate from the facility that is less than 2 cfs for the 1-year, 24-hour Type III design storm event (prior to any attenuation). (<u>Note</u> : LID design strategies can greatly reduce the peak discharge rate).
☐	☐	Conveyance and natural channel protection for the site have been met. If “No,” explain why:

TABLE 4-1: Summary of Channel Protection Volumes (see RICR 8.10)					
Design Point	Receiving Water Body Name	Coldwater Fishery? (Y/N)	Total CPv Required (cu ft)	Total CPv Provided (cu ft)	Average Release Rate Modeled in the 1-yr storm (cfs)
DP-1:					
DP-2:					
DP-3:					
DP-4:					
TOTALS:					
<u>Note</u> : The Channel Protection Volume Standard must be met in each waterbody ID.					
☐ YES ☐ NO	The CPv is released at roughly a uniform rate over a 24-hour duration (see examples of sizing calculations in Appendix D of the RISDISM).				
☐ YES ☐ NO	Do additional design restrictions apply resulting from any discharge to cold-water fisheries; If “Yes,” please indicate restrictions and solutions below.				
☐ Indicate below where the pertinent calculations and/or information for the above items are provided (i.e., name of report/document, page numbers, appendices, etc.).					

Stormwater Management, Design, and Installation Rules (250-RICR-150-10-8)

OVERBANK FLOOD PROTECTION (RICR 8.11) AND OTHER POTENTIAL HIGH FLOWS – MINIMUM STANDARD 5			
YES	NO		
☐	☒	Is this standard waived? If yes, please indicate one or more of the reasons below:	
		☐	The project directs discharge to a large river (i.e., 4th-order stream or larger. See Appendix I for state-wide list and map of stream orders), bodies of water >50.0 acres in surface area (i.e., lakes, ponds, reservoirs), or tidal waters.
		☐	A Downstream Analysis (see RICR 8.11.D and E) indicates that peak discharge control would not be beneficial or would exacerbate peak flows in a downstream tributary of a particular site (e.g., through coincident peaks).
☐	☒	Does the project flow to an MS4 system or subject to other stormwater requirements? If “Yes,” indicate as follows:	
		☐	RIDOT
		☐	Other (specify):
Note: The project could be approved by RIDEM but not meet RIDOT or Town standards. RIDOT’s regulations indicate that post-volumes must be less than pre-volumes for the 10-yr storm at the design point entering the RIDOT system. If you have not already received approval for the discharge to an MS4, please explain below your strategy to comply with RIDEM and the MS4.			
		Indicate below which model was used for your analysis. ☐ TR-55 ☐ TR-20 ☐ HydroCAD ☐ Bentley/Haestad ☐ Intellisolve ☐ Other (Specify):	
YES	NO		
☒	☐	Does the drainage design demonstrate that flows from the 100-year storm event through a BMP will safely manage and convey the 100-year storm? If “No,” please explain briefly below and reference where in the application further documentation can be found (i.e., name of report/document, page numbers, appendices, etc.):	
☒	☐	Do off-site areas contribute to the sub-watersheds and design points? If “Yes,”	
☒	☐	Are the areas modeled as “present condition” for both pre- and post-development analysis?	
☒	☐	Are the off-site areas shown on the subwatershed maps?	
☒	☐	Does the drainage design confirm safe passage of the 100-year flow through the site for off-site runoff?	
☐	☒	Is a Downstream Analysis required (see RICR 8.11.E.1)?	
☒	☐	Calculate the following:	
		☒	Area of disturbance within the sub-watershed (areas): 1.76+/- acres
		☒	Impervious cover (%): 32.6%
☐	☒	Is a dam breach analysis required (earthen embankments over six (6) feet in height, or a capacity of 15 acre-feet or more, and contributes to a significant or high hazard dam)?	
☒	☐	Does this project meet the overbank flood protection standard?	

Stormwater Management, Design, and Installation Rules (250-RICR-150-10-8)

Table 5-1 Hydraulic Analysis Summary

Subwatershed (Design Point)	1.2" Peak Flow (cfs) **		1-yr Peak Flow (cfs)		10-yr Peak Flow (cfs)		100-yr Peak Flow (cfs)	
	Pre (cfs)	Post (cfs)	Pre (cfs)	Post (cfs)	Pre (cfs)	Post (cfs)	Pre (cfs)	Post (cfs)
A1:	0.01	0.00	0.20	0.02	0.58	0.52	1.36	1.20
A2:	0.09	0.02	1.08	0.39	3.15	2.02	7.34	6.49
TOTALS:								

** Utilize modified curve number method or split pervious /impervious method in HydroCAD.

Note: The hydraulic analysis must demonstrate no impact to each individual subwatershed DP unless each DP discharges to the same wetland or water resource.

Indicate as follows where the pertinent calculations and/or information for the items above are provided	Name of report/document, page numbers, appendices, etc.
Existing conditions analysis for each subwatershed, including curve numbers, times of concentration, runoff rates, volumes, and water surface elevations showing methodologies used and supporting calculations.	See Appendix 2 of the Stormwater Management Report
Proposed conditions analysis for each subwatershed, including curve numbers, times of concentration, runoff rates, volumes, water surface elevations, and routing showing the methodologies used and supporting calculations.	See Appendix 2 of the Stormwater Management Report
Final sizing calculations for structural stormwater BMPs, including contributing drainage area, storage, and outlet configuration.	See Appendix 2 of the Stormwater Management Report
Stage-storage, inflow and outflow hydrographs for storage facilities (e.g., detention, retention, or infiltration facilities).	See Appendix 2 of the Stormwater Management Report

Table 5-2 Summary of Best Management Practices

DP #	BMP ID	BMP Type (e.g., bioretention, tree filter)	BMP Functions					Bypass Type	Horizontal Setback Criteria are met per RICR 8.21.B.10, 8.22.D.11, and 8.35.B.4		
			Pre-Treatment (Y/N/NA)	Re _v	WQ _v	CP _v (Y/N/NA)	Overbank Flood Reduction (Y/N/NA)		Yes/No	Technical Justification (Design Report page number)	Distance Provided
pA2	US1	Underground Infiltration System		764	426			N/a	Y		
pA2	FB1	Sediment Forebay-1	173					N/a	Y		
pA2	FB2	Sediment Forebay-2	76					N/a	Y		
pA2	FB3	Sediment Forebay-3	192					N/a	Y		

Stormwater Management, Design, and Installation Rules (250-RICR-150-10-8)

Table 5-2 Summary of Best Management Practices											
DP #	BMP ID	BMP Type (e.g., bioretention, tree filter)	BMP Functions					Bypass Type	Horizontal Setback Criteria are met per RICR 8.21.B.10, 8.22.D.11, and 8.35.B.4		
			Pre-Treatment (Y/N/NA)	Re _v	WQ _v	CP _v (Y/N/NA)	Overbank Flood Reduction (Y/N/NA)		External (E) Internal (I) or NA	Yes/ No	Technical Justification (Design Report page number) Distance Provided
pA2	BR1	Bio-retention Basin-1			1315				N/a	Y	
pA2	BR2	Bio-retention Basin-2			805				N/a	Y	
pA1	BR3	Bio-retention Basin-3			503				N/a	Y	
pA1	BR4	Bio-retention Basin-4			255				N/a	Y	
		TOTALS:									

Stormwater Management, Design, and Installation Rules (250-RICR-150-10-8)

Table 5.3 Summary of Soils to Evaluate Each BMP									
DP #	BMP ID	BMP Type (e.g., bioretention, tree filter)	Soils Analysis for Each BMP						Exfiltration Rate Applied (in/hr)
			Test Pit ID# and Ground Elevation		SHWT Elevation (ft)	Bottom of Practice Elevation* (ft)	Separation Distance Provided (ft)	Hydrologic Soil Group (A, B, C, D)	
			Primary	Secondary					
pA2	US1	Underground Infiltration System	TH-3	TH-4	84.0	82.0	2'	C	.27
pA2	FB1	Sediment Forebay-1	TH-3	TH-4	85.5	85.0	Lined	C	N/a
pA2	FB2	Sediment Forebay-2	TH-2	TH-3	81.0	83.0	Lined	C	N/a
pA2	FB3	Sediment Forebay-3	TH-1	TH-6	80.5	80.3	Lined	c	N/a
pA2	BR1	Bio-retention Basin-1	TH-3	TH-4	85.5	85.0	Lined	C	N/a
pA2	BR2	Bio-retention Basin-2	TH-2	TH-1	81.0	80.0	Lined	C	N/a
pA1	BR3	Bio-retention Basin-3	TH-1	TH-6	84.4	82.7	Lined	C	N/a
pA1	BR4	Bio-retention Basin-4	TH-2	TH-3	81.0	83.0	2'	C	N/a
pA2	B1	Dry Extended Detention Basin	TH-2	TH-3	80.0	80.0	0'	C	N/a
		TOTALS:							
* For underground infiltration systems (UICs) bottom equals bottom of stone, for surface infiltration basins bottom equals bottom of basin, for filters bottom equals interface of storage and top of filter layer									

LAND USES WITH HIGHER POTENTIAL POLLUTANTS LOADS (LUHPPLs) – MINIMUM STANDARD 8			
YES	NO	N/A	
☐	☐	☒	Describe any LUHPPLs identified in Part 1, Minimum Standard 8, Section 2. If not applicable, continue to Minimum Standard 9.
☐	☐	☐	Are these activities already covered under an MSGP? If “No,” please explain if you have applied for an MSGP or intend to do so?
☐	☐	☐	List the specific BMPs that are proposed for this project that receive stormwater from LUHPPL drainage areas. These BMP types must be listed in RISDISM Table 3-3, “Acceptable BMPs for Use at LUHPPLs.” Please list BMPs:
☐	☐	☐	Additional BMPs, or additional pretreatment BMP’s if any, that meet RIPDES MSGP requirements; Please list BMPs:

Stormwater Management, Design, and Installation Rules (250-RICR-150-10-8)

			Indicate below where the pertinent calculations and/or information for the above items are provided (i.e., name of report/document, page numbers, appendices, etc.).

ILLICIT DISCHARGES – MINIMUM STANDARD 9

Illicit discharges are defined as unpermitted discharges to Waters of the State that do not consist entirely of stormwater or uncontaminated groundwater, except for certain discharges identified in the RIPDES Phase II Stormwater General Permit.

YES	NO	N/A	
☒	☐	☐	Have you checked for illicit discharges?
☐	☒	☐	Have any been found and/or corrected? If “Yes,” please identify.
☐	☐	☐	Does your report explain preventative measures that keep non-stormwater discharges out of the Waters of the State (during and after construction)?

SOIL EROSION AND SEDIMENT CONTROL (SESC) – MINIMUM STANDARD 10

YES	NO	N/A	
☒	☐	☐	Have you included a Soil Erosion and Sediment Control Plan Set and/or Complete Construction Plan Set?
☒	☐	☐	Have you provided a separately-bound document based upon the SESC Template ? If yes, proceed to Minimum Standard 11 (the following items can be assumed to be addressed).
			If “No,” include a document with your submittal that addresses the following elements of an SESC Plan:
		☐	Soil Erosion and Sediment Control Plan Project Narrative, including a description of how the fifteen (15) Performance Criteria have been met:
		☐	Provide Natural Buffers and Maintain Existing Vegetation
		☐	Minimize Area of Disturbance
		☐	Minimize the Disturbance of Steep Slopes
		☐	Preserve Topsoil
		☐	Stabilize Soils
		☐	Protect Storm Drain Inlets
		☐	Protect Storm Drain Outlets
		☐	Establish Temporary Controls for the Protection of Post-Construction Stormwater Control Measures
		☐	Establish Perimeter Controls and Sediment Barriers
		☐	Divert or Manage Run-On from Up-Gradient Areas
		☐	Properly Design Constructed Stormwater Conveyance Channels
		☐	Retain Sediment On-Site
		☐	Control Temporary Increases in Stormwater Velocity, Volume, and Peak Flows
		☐	Apply Construction Activity Pollution Prevention Control Measures
		☐	Install, Inspect, and Maintain Control Measures and Take Corrective Actions
		☐	Qualified SESC Plan Preparer’s Information and Certification
		☐	Operator’s Information and Certification; if not known at the time of application, the Operator must certify the SESC Plan upon selection and prior to initiating site activities
		☐	Description of Control Measures, such as Temporary Sediment Trapping and Conveyance Practices, including design calculations and supporting documentation, as required

STORMWATER MANAGEMENT SYSTEM OPERATION, MAINTENANCE, AND POLLUTION PREVENTION PLAN – MINIMUM STANDARDS 7 AND 9

Operation and Maintenance Section

YES	NO	
☒	☐	Have you minimized all sources of pollutant contact with stormwater runoff, to the maximum extent practicable?

Stormwater Management, Design, and Installation Rules (250-RICR-150-10-8)

☒	☐	Have you provided a separately-bound Operation and Maintenance Plan for the site and for all of the BMPs, and does it address each element of RICR 8.17 and RISDISM Appendix C and E?
☒	☐	Lawn, Garden, and Landscape Management meet the requirements of RISDISM Section G.7? If "No," why not?
☒	☐	Is the property owner or homeowner's association responsible for the stormwater maintenance of all BMP's? If "No," you must provide a legally binding and enforceable maintenance agreement (see RISDISM Appendix E, page 26) that identifies the entity that will be responsible for maintenance of the stormwater. Indicate where this agreement can be found in your report (i.e., name of report/document, page numbers, appendices, etc.).
☐	☒	Do you anticipate that you will need legal agreements related to the stormwater structures? (e.g. off-site easements, deed restrictions, covenants, or ELUR per the Remediation Regulations). If "Yes," have you obtained them? Or please explain your plan to obtain them:
☐	☒	Is stormwater being directed from public areas to private property? If "Yes," note the following: <u>Note:</u> This is not allowed unless a funding mechanism is in place to provide the finances for the long-term maintenance of the BMP and drainage, or a funding mechanism is demonstrated that can guarantee the long-term maintenance of a stormwater BMP by an individual homeowner.
Pollution Prevention Section		
☐	☒	Designated snow stockpile locations?
☐	☒	Trash racks to prevent floatables, trash, and debris from discharging to Waters of the State?
☐	☒	Asphalt-only based sealants?
☐	☒	Pet waste stations? (<u>Note:</u> If a receiving water has a bacterial impairment, and the project involves housing units, then this could be an important part of your pollution prevention plan).
☐	☒	Regular sweeping? Please describe:
☐	☒	De-icing specifications, in accordance with RISDISM Appendix G. (NOTE: If the groundwater is GAA, or this area contributes to a drinking water supply, then this could be an important part of your pollution prevention plan).
☐	☒	A prohibition of phosphate-based fertilizers? (<u>Note:</u> If the site discharges to a phosphorus impaired waterbody, then this could be an important part of your pollution prevention plan).

PART 4. SUBWATERSHED MAPPING AND SITE-PLAN DETAILS

Existing and Proposed Subwatershed Mapping (REQUIRED)		
YES	NO	
☒	☐	Existing and proposed drainage area delineations
☒	☐	Locations of all streams and drainage swales
☒	☐	Drainage flow paths, mapped according to the DEM <i>Guidance for Preparation of Drainage Area Maps</i> (included in RISDISM Appendix K)
☒	☐	Complete drainage area boundaries; include off-site areas in both mapping and analyses, as applicable
☒	☐	Logs of borings and/or test pit investigations along with supporting soils/geotechnical report
☒	☐	Mapped seasonal high-water-table test pit locations
☒	☐	Mapped locations of the site-specific borings and/or test pits and soils information from the test pits at the locations of the BMPs
☒	☐	Mapped locations of the BMPs, with the BMPs consistently identified on the Site Construction Plans
☒	☐	Mapped bedrock outcrops adjacent to any infiltration BMP
☒	☐	Soils were logged by a:
	☒	DEM-licensed Class IV soil evaluator

Stormwater Management, Design, and Installation Rules (250-RICR-150-10-8)

		Name: N. Letendre
	☐	RI-registered P.E. Name:

Subwatershed and Impervious Area Summary				
Subwatershed (area to each design point)	First Receiving Water ID or MS4	Area Disturbed (units)	Existing Impervious (units)	Proposed Impervious (units)
DP-1:				
DP-2:				
DP-3:				
DP-4:				
TOTALS:				

Stormwater Management, Design, and Installation Rules (250-RICR-150-10-8)

Site Construction Plans (Indicate that the following applicable specifications are provided)		
YES	NO	
☒	☐	Existing and proposed plans (scale not greater than 1" = 40') with North arrow
☒	☐	Existing and proposed site topography (with 1 or 2-foot contours); 10-foot contours accepted for off-site areas
☒	☐	Boundaries of existing predominant vegetation and proposed limits of clearing
☒	☐	Site Location clarification
☒	☐	Location and field-verified boundaries of resource protection areas such as: ▶ freshwater and coastal wetlands, including lakes and ponds ▶ coastal shoreline features Perennial and intermittent streams, in addition to Areas Subject to Storm Flowage (ASSFs)
☒	☐	All required setbacks (e.g., buffers, water-supply wells, septic systems)
☒	☐	Representative cross-section and profile drawings, and notes and details of structural stormwater management practices and conveyances (i.e., storm drains, open channels, swales, etc.), which include: ▶ Location and size of the stormwater treatment practices (type of practice, depth, area). Stormwater treatment practices (BMPs) must have labels that correspond to RISDISM Table 5-2; ▶ Design water surface elevations (applicable storms); ▶ Structural details of outlet structures, embankments, spillways, stilling basins, grade-control structures, conveyance channels, etc.; ▶ Existing and proposed structural elevations (e.g., inverts of pipes, manholes, etc.); ▶ Location of floodplain and, if applicable, floodway limits and relationship of site to upstream and downstream properties or drainage that could be affected by work in the floodplain; ▶ Planting plans for structural stormwater BMPs, including species, size, planting methods, and maintenance requirements of proposed planting
☒	☐	Logs of borings and/or test pit investigations along with supporting soils/geotechnical report and corresponding water tables
☒	☐	Mapping of any OLRSM approved remedial actions/systems (including ELURs)
☒	☐	Location of existing and proposed roads, buildings, and other structures including limits of disturbance; ▶ Existing and proposed utilities (e.g., water, sewer, gas, electric) and easements; ▶ Location of existing and proposed conveyance systems, such as grass channels, swales, and storm drains, and location(s) of final discharge point(s) (wetland, waterbody, etc.); ▶ Cross sections of roadways, with edge details such as curbs and sidewalks; ▶ Location and dimensions of channel modifications, such as bridge or culvert crossings
☒	☐	Locations, cross sections, and profiles of all stream or wetland crossings and their method of stabilization

MOUNDSOLV

GROUNDWATER MOUNDING ANALYSIS FOR A SLOPING WATER-TABLE AQUIFER ZLOTNIK ET AL. (2017) SOLUTION

Solution Method

**Zlotnik et al. (2017) transient solution for a rectangular source
(linearization method 1)**

Site Description

Aquifer Data

Property	Value
Horizontal hydraulic conductivity, K (ft/d)	2.5
Specific yield, S_y	0.2
Initial saturated thickness, h_0 (ft)	10
Maximum allowable water-table rise, σ (ft)	2
Dip, i (ft/ft)	0.05
Slope rotation from x axis, γ (°)	0

Recharge Sources

Property	Source 1
X coordinate at center, X (ft)	0
Y coordinate at center, Y (ft)	0
Dimension along x* axis, L (ft)	21.5
Dimension along y* axis, W (ft)	33.25
Rotation from slope direction, ϕ (°)	0
Recharge rate, Q (ft ³ /d)	357.4375
Infiltration rate, q (ft/d)	0.5

Monitoring Points

Elapsed Time, $t = 1$ d

Name	x (ft)	y (ft)	s (ft)	h (ft)	z (ft)

Source 1	0	0	1.561	11.56	0
----------	---	---	-------	-------	---

Time Series Data

Time (d)	Source 1	
	s (ft)	h (ft)
0	0	10
0.002916	0.00729	10.01
0.006561	0.0164	10.02
0.01112	0.02779	10.03
0.01681	0.04203	10.04
0.02393	0.05983	10.06
0.03283	0.08207	10.08
0.04395	0.1099	10.11
0.05786	0.1445	10.14
0.07524	0.1876	10.19
0.09696	0.2408	10.24
0.1241	0.3058	10.31
0.1581	0.3843	10.38
0.2005	0.4776	10.48
0.2535	0.5868	10.59
0.3198	0.7122	10.71
0.4027	0.8537	10.85
0.5063	1.011	11.01
0.6358	1.182	11.18
0.7977	1.366	11.37
1	1.561	11.56

Profile Data

***Profile Along X* Axis for
Source 1 at Elapsed Time, t =
1 d***

x* (ft) s (ft) h (ft) z (ft)

-34	0.05054	8.351	-1.7
-32.64	0.06272	8.431	-1.632
-31.28	0.07742	8.513	-1.564
-29.92	0.09508	8.599	-1.496
-28.56	0.1162	8.688	-1.428
-27.2	0.1413	8.781	-1.36
-25.84	0.1709	8.879	-1.292
-24.48	0.2058	8.982	-1.224
-23.12	0.2466	9.091	-1.156
-21.76	0.294	9.206	-1.088
-20.4	0.349	9.329	-1.02
-19.04	0.4124	9.46	-0.952
-17.68	0.4851	9.601	-0.884
-16.32	0.5681	9.752	-0.816
-14.96	0.6624	9.914	-0.748
-13.6	0.7688	10.09	-0.68
-12.24	0.8886	10.28	-0.612
-10.88	1.023	10.48	-0.544
-9.52	1.156	10.68	-0.476
-8.16	1.27	10.86	-0.408
-6.8	1.363	11.02	-0.34
-5.44	1.438	11.17	-0.272
-4.08	1.495	11.29	-0.204
-2.72	1.534	11.4	-0.136
-1.36	1.556	11.49	-0.068
0	1.561	11.56	0
1.36	1.55	11.62	0.068
2.72	1.522	11.66	0.136
4.08	1.478	11.68	0.204
5.44	1.416	11.69	0.272
6.8	1.337	11.68	0.34
8.16	1.24	11.65	0.408

9.52	1.123	11.6	0.476
10.88	0.9873	11.53	0.544
12.24	0.8526	11.46	0.612
13.6	0.733	11.41	0.68
14.96	0.6275	11.38	0.748
16.32	0.5349	11.35	0.816
17.68	0.4539	11.34	0.884
19.04	0.3834	11.34	0.952
20.4	0.3224	11.34	1.02
21.76	0.2699	11.36	1.088
23.12	0.2249	11.38	1.156
24.48	0.1865	11.41	1.224
25.84	0.1539	11.45	1.292
27.2	0.1264	11.49	1.36
28.56	0.1033	11.53	1.428
29.92	0.08403	11.58	1.496
31.28	0.06799	11.63	1.564
32.64	0.05472	11.69	1.632
34	0.04382	11.74	1.7

The axes of Source 1 (x^ , y^*) are rotated 0° from the axes of mapping coordinate system (x , y)*

**Profile Along Y^* Axis for
Source 1 at Elapsed Time, t
 $= 1 d$**

y^* (ft)	s (ft)	h (ft)	z (ft)
-34	0.08893	10.09	0
-32.64	0.1089	10.11	0
-31.28	0.1327	10.13	0
-29.92	0.161	10.16	0
-28.56	0.1946	10.19	0
-27.2	0.2343	10.23	0
-25.84	0.2809	10.28	0

-24.48	0.3355	10.34	0
-23.12	0.3994	10.4	0
-21.76	0.4736	10.47	0
-20.4	0.5598	10.56	0
-19.04	0.6594	10.66	0
-17.68	0.7741	10.77	0
-16.32	0.9045	10.9	0
-14.96	1.028	11.03	0
-13.6	1.134	11.13	0
-12.24	1.225	11.23	0
-10.88	1.303	11.3	0
-9.52	1.368	11.37	0
-8.16	1.422	11.42	0
-6.8	1.467	11.47	0
-5.44	1.502	11.5	0
-4.08	1.528	11.53	0
-2.72	1.547	11.55	0
-1.36	1.558	11.56	0
0	1.561	11.56	0
1.36	1.558	11.56	0
2.72	1.547	11.55	0
4.08	1.528	11.53	0
5.44	1.502	11.5	0
6.8	1.467	11.47	0
8.16	1.422	11.42	0
9.52	1.368	11.37	0
10.88	1.303	11.3	0
12.24	1.225	11.23	0
13.6	1.134	11.13	0
14.96	1.028	11.03	0
16.32	0.9045	10.9	0
17.68	0.7741	10.77	0

19.04	0.6594	10.66	0
20.4	0.5598	10.56	0
21.76	0.4736	10.47	0
23.12	0.3994	10.4	0
24.48	0.3355	10.34	0
25.84	0.2809	10.28	0
27.2	0.2343	10.23	0
28.56	0.1946	10.19	0
29.92	0.161	10.16	0
31.28	0.1327	10.13	0
32.64	0.1089	10.11	0
34	0.08893	10.09	0

The axes of Source 1 (x^ , y^*) are rotated 0° from the axes of mapping coordinate system (x , y)*

Sensitivity Data

Source 1, $x=0$ ft, $y=0$ ft

Parameter	Water-Table Rise (ft)			
Multiplier	K	Sy	h_o	i
0.8	1.71	1.765	1.71	1.561
0.82	1.694	1.742	1.694	1.561
0.84	1.678	1.719	1.678	1.561
0.86	1.662	1.698	1.662	1.561
0.88	1.647	1.677	1.647	1.561
0.9	1.632	1.656	1.632	1.561
0.92	1.617	1.636	1.617	1.561
0.94	1.603	1.617	1.603	1.561
0.96	1.589	1.598	1.589	1.561
0.98	1.575	1.579	1.575	1.561
1	1.561	1.561	1.561	1.561
1.02	1.548	1.544	1.548	1.561
1.04	1.535	1.527	1.535	1.561

1.06	1.522	1.51	1.522	1.561
1.08	1.51	1.494	1.51	1.561
1.1	1.497	1.478	1.497	1.561
1.12	1.485	1.462	1.485	1.561
1.14	1.473	1.447	1.473	1.561
1.16	1.462	1.432	1.462	1.561
1.18	1.45	1.417	1.45	1.561
1.2	1.439	1.403	1.439	1.561

Notation

h is water-table elevation above datum¹

h_0 is aquifer saturated thickness prior to mounding

i is dip of aquifer

K is horizontal hydraulic conductivity

L is dimension of recharge source parallel to x^* axis

q is infiltration rate ($= Q / L \cdot W$)

Q is recharge rate

s is water-table rise above static water table

S_y is specific yield

t is time since start of recharge

t_0 is time when recharge stops

W is dimension of recharge source parallel to y^* axis

x, y are mapping Cartesian coordinate axes

x^*, y^* are recharge source Cartesian coordinate axes

z is elevation above datum¹


γ is angle between x axis and dip direction

ϕ is angle between dip direction and x^* axis of recharge source


σ is maximum acceptable water-table rise

¹*Elevation datum is the base of aquifer beneath the center of primary recharge source*


Report generated by MOUNDSOLV v4.0 on 12 Dec 2022 at 10:30:38
MOUNDSOLV (www.aqtesolv.com)
Copyright © 2019-2021 HydroSOLVE, Inc. All rights reserved.




Water-Table Rise (t=1 d)
K = 2.5 ft/d
Sy = 0.2
h₀ = 10 ft
i = 0.05 ft/ft
γ = 0°
L = 21.5 ft
W = 33.25 ft
φ = 0°
Q = 357.438 ft³/d




Water-Table Rise Along X* Axis of Source 1 (t=1 d)




Water-Table Rise Along Y* Axis of Source 1 (t=1 d)





- WATERSHED LEGEND**
- SUBCATCHMENT AREA
 - POND / STRUCTURE
 - REACH / CHANNEL
 - PRE-DEVELOPMENT SUBCATCHMENT BOUNDARY




**PRE DEVELOPMENT
WATERSHED PLAN**

1200 & 1202 HOPE STREET
ASSESSOR'S MAP 103 , LOT 2 & 14
BRISTOL, RHODE ISLAND

DATE: JUNE 15, 2022			REV. DATE:
PROJ.#: 22024	SCALE : 1" = 40'	DRAWN BY: SJE	CHECK BY: MER
ISSUED FOR : PERMITTING			
PREPARED FOR: EXPRESS REALTY TRUST, LLC			



207 HIGH POINT AVE.
UNIT 6
Portsmouth, RI 02871
T: 401-354-2050
F: 401-369-9775
WWW.SDE-LDEC.COM




HOPE STREET
(PUBLIC - RTE. 114 - VARIABLE WIDTH)

KNOWLTON COURT
(PUBLIC - 50' WIDE - UNDER CONSTRUCTION)

Analysis Pt. PA1

Analysis Pt. PA2

- WATERSHED LEGEND**
- 1 SUBCATCHMENT AREA
 - 1 POND / STRUCTURE
 - 1 REACH / CHANNEL
 - A → B Tc-FLOWPATH
START → END POST-DEVELOPMENT
 - POSTE-DEVELOPMENT SUBCATCHMENT BOUNDARY



SCALE: 1 INCH = 40 FEET


POST DEVELOPMENT WATERSHED PLAN

1200 & 1202 HOPE STREET
ASSESSOR'S MAP 103 , LOT 2 & 14
BRISTOL, RHODE ISLAND

207 HIGH POINT AVE.
UNIT 6
Portsmouth, RI 02871
T: 401-354-2050
F: 401-369-9775
WWW.SDE-LDEC.COM



DATE: JUNE 15, 2022			REV. DATE:
PROJ.#: 22024			CHECK BY: MER
SCALE : 1" = 40'			DRAWN BY: SJE
ISSUED FOR : PERMITTING			
PREPARED FOR: EXPRESS REALTY TRUST, LLC			




1200 Hope Street - Bristol, Rhode Island
Map 103 Parcel 2
LDEC Project No. 18050

Figure 2 - Site Locus
February 19, 2019

UNEDC, RIGIS

LDEC
Land Development Engineering & Consulting, LLC



1200 Hope Street - Bristol, Rhode Island
Map 103 Parcel 2
LDEC Project No. 18050

Figure 3 - SSURGO Soils
February 19, 2019