#### TOWN OF BRISTOL, RI APPLICATION FOR SEWER PERMIT

Date: 5/23/23	Permit: 2	786 ]	-0
The undersigned licensed Drainlayer requests permission to	install a sewer line at:		
	70 PLAT	5 (	_
NO. STREET	PLAT	LOT	
ASSESSABLEYESNO ACCO	OUNT NO:		
GENERAL RULES FOR I	NSTALLING SEWER	LINES:	
<ol> <li>Pipes from public sewer to property line shall be 6" in degree of the property line to building shall be 4" in diamals. Junctions with public sewers shall be made at an angle of the Clean outs are required outside the foundation plus at 7 direction; and at all 45 degree or greater angles.</li> <li>Pipes shall be imbedded in 6" of sand, processed gravely is not acceptable.</li> <li>Pipes shall be laid at a minimum of 3" below grade.</li> <li>Inspection manholes shall be installed outside of common sampling.</li> <li>Plumbing Permit from building Inspector is required for 9. Roadcut Permit from Department of Public Works is red.</li> <li>All Permits must be on job site.</li> <li>Sewer Permit is good for 4 weeks.</li> <li>Dig Safe must be notified by Drainlayer.</li> <li>NO INSPECTIONS WILL BE MADE AFTER 3:001 OR HOLIDAYS.</li> <li>It is the responsibility of the property owner and/or drait Local permits have been obtained.</li> <li>Easements, Deeds, and all legal documents are the responser.</li> <li>Backflow Preventer/Check Valves are required on all be NOTE: Roof downspouts, foundation drains, area drain.</li> </ol>	eter. by installing a wye or a to 5' increments; at all sign or stone no greater than ercial buildings for purpor all interior connections quired for all roadcuts.  PM WEEKDAYS OR A nlayer to ensure that all 1 onsibility of the applican uildings with basement p	a 3/4". Existing a 3/4". Existing a 3/4". Existing a sees of Pretreat	g gravel ment EEKENDS and
water to the public sewers are prohibited.			
FEE: \$ 10 CK# 425 C 445	Property Owner		
Water Pollution Control Facility	Licensed Drainlayer		<b>FOWN COUNCIL</b>
Superintendent	Diceised Diamayer		COUNCIL
			AUG 23 2023
			MEETING

Pink: Drainlayer Gold: Homeowner

White: WPCF

Green: Tax Assessor Yellow: Town Council

Repain

Date: $\frac{4/3}{23}$	Perm	it: 2800 **D	
The undersigned licensed Drainlayer requests perm	ission to install a sewer l	ine at:	
335 High St	13	4/	
NO. STREET	PLAT	LOT	
ASSESSABLEYESNO	ACCOUNT NO:		
GENERAL RULES	FOR INSTALLING S	EWER LINES:	
<ol> <li>Pipes from public sewer to property line shall be</li> <li>Pipes from property line to building shall be 4"</li> <li>Junctions with public sewers shall be made at at</li> <li>Clean outs are required outside the foundation p</li> </ol>	in diameter. n angle by installing a w		
<ul> <li>direction; and at all 45 degree or greater angles</li> <li>5. Pipes shall be imbedded in 6" of sand, processed is not acceptable.</li> <li>6. Pipes shall be laid at a minimum of 3' below greater angles</li> </ul>	d gravel, or stone no grea		
<ol> <li>Inspection manholes shall be installed outside o sampling.</li> <li>Plumbing Permit from building Inspector is req</li> </ol>	f commercial buildings f		
<ol> <li>Roadcut Permit from Department of Public Wor</li> <li>All Permits must be on job site.</li> <li>Sewer Permit is good for 4 weeks.</li> </ol>			
<ul><li>12. Dig Safe must be notified by Drainlayer.</li><li>13. NO INSPECTIONS WILL BE MADE AFTE OR HOLIDAYS.</li></ul>	CR 3:00PM WEEKDAY	'S OR ANYTIME WEEKENDS	
14. It is the responsibility of the property owner and Local permits have been obtained.			
<ol><li>Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.</li></ol>			
16. Backflow Preventer/Check Valves are required	on all buildings with bas	sement plumbing.	
NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.			
FEE: \$ 10 CK# 44)	Property Own		
4.6	Jehan	- cen nan	
Water Pollution Control Facility Superintendent	Licensed Dra	inlayer	

New

/		
Date: $4/3/23$	Permit: 2801 \$10	
The undersigned licensed Drainlayer requests permission to		
429 Chestnot ST	108 15	
NO. STREET	PLAT LOT	
ASSESSABLEYESNO ACCO	OUNT NO:	
GENERAL RULES FOR I	NSTALLING SEWER LINES:	
1. Pipes from public sewer to property line shall be 6" in di		
<ul><li>2. Pipes from property line to building shall be 4" in diame</li><li>3. Junctions with public sewers shall be made at an angle b</li></ul>		
4. Clean outs are required outside the foundation plus at 75		
direction; and at all 45 degree or greater angles.		
5. Pipes shall be imbedded in 6" of sand, processed gravel,	or stone no greater than 3/4". Existing gravel	
is not acceptable.		
<ul><li>6. Pipes shall be laid at a minimum of 3' below grade.</li><li>7. Inspection manholes shall be installed outside of comme</li></ul>	ercial buildings for purposes of Pretreatment	
sampling.	brotal bullatings for purposes of Fretreatment	
8. Plumbing Permit from building Inspector is required for	r all interior connections.	
9. Roadcut Permit from Department of Public Works is req	quired for all roadcuts.	
10. All Permits must be on job site.		
<ul><li>11. Sewer Permit is good for <u>4 weeks</u>.</li><li>12. Dig Safe must be notified by Drainlayer.</li></ul>		
13. NO INSPECTIONS WILL BE MADE AFTER 3:00P	PM WEEKDAYS OR ANYTIME WEEKEND	S
OR HOLIDAYS.		~
14. It is the responsibility of the property owner and/or drain	nlayer to ensure that all Federal, State, and	
Local permits have been obtained.		
<ol> <li>Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.</li> </ol>		
16. Backflow Preventer/Check Valves are required on all be	uildings with basement plumbing.	
NOTE: Roof downspouts, foundation drains, area drains	s, and/or other sources of surface runoff or gr	ound
water to the public sewers are prohibited.		
FEE: \$ 25 - CK# 4421	Fairpoint Real	
TEL. T	Property Owner	
6/_	0	
Jui Co	John Connan	
Water Pollution Control Facility	Licensed Drainlayer	
Superintendent		

Date: 5/23/23	Permit: 2787 *V	
The undersigned licensed Drainlayer requests permission	to install a sewer line at:	
1 Jana Lane	51 12	
NO. STREET	PLAT LOT	
ACCECCADIE VEC NO ACC	OUNT NO.	
ASSESSABLEYESNO ACC	COUNT NO:	
GENERAL RULES FOR	INSTALLING SEWER LINES:	
1. Pipes from public sewer to property line shall be 6" in	diameter.	
2. Pipes from property line to building shall be 4" in diar		
3. Junctions with public sewers shall be made at an angle		
4. Clean outs are required outside the foundation plus at direction; and at all 45 degree or greater angles.	75 increments; at all significant changes in	
5. Pipes shall be imbedded in 6" of sand, processed grave	el, or stone no greater than 3/4". Existing gravel	
is not acceptable.		
6. Pipes shall be laid at a minimum of 3' below grade.		
<ol><li>Inspection manholes shall be installed outside of commanding.</li></ol>	nercial buildings for purposes of Pretreatment	
Plumbing Permit from building Inspector is required f	or all interior connections.	
9. Roadcut Permit from Department of Public Works is r		
10. All Permits must be on job site.		
11. Sewer Permit is good for <u>4 weeks</u> .		
<ul><li>12. Dig Safe must be notified by Drainlayer.</li><li>13. NO INSPECTIONS WILL BE MADE AFTER 3:00</li></ul>	ODM WEEKDAVE OD ANVTIME WEEKENDE	
OR HOLIDAYS.	JAM WEEKDATS OR ANTITUTE WEEKENDS	
14. It is the responsibility of the property owner and/or dra	ainlayer to ensure that all Federal, State, and	
Local permits have been obtained.		
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property		
owner.  16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.		
NOTE: Roof downspouts, foundation drains, area drains	ins, and/or other sources of surface runoff or ground	
water to the public sewers are prohibited.		
FEE: \$ 10.00 CK#		
	Property Owner	
5	L. Ramos	
Water Pollution Control Facility	Licensed Drainlayer	
Superintendent		

Date: 7/5/23	Permit: 2791KD
The undersigned licensed Drainlayer requests permission to	install a sewer line at:
500 Hope St. Chinden Place,	13 56
NO. STREET	PLAT LOT
ASSESSABLEYESNO ACCOU	JNT NO:
GENERAL RULES FOR IN	STALLING SEWER LINES:
1. Pipes from public sewer to property line shall be 6" in dia	ameter.
2. Pipes from property line to building shall be 4" in diamet	
3. Junctions with public sewers shall be made at an angle by	
4. Clean outs are required outside the foundation plus at 75 direction; and at all 45 degree or greater angles.	increments; at all significant changes in
5. Pipes shall be imbedded in 6" of sand, processed gravel,	or stone no greater than 3/4". Existing gravel
is not acceptable.	
6. Pipes shall be laid at a minimum of 3' below grade.	
7. Inspection manholes shall be installed outside of commer	rcial buildings for purposes of Pretreatment
sampling.  8. Plumbing Permit from building Inspector is required for	all interior connections
9. Roadcut Permit from Department of Public Works is requ	
10. All Permits must be on job site.	
11. Sewer Permit is good for 4 weeks.	
12. Dig Safe must be notified by Drainlayer.	
13. NO INSPECTIONS WILL BE MADE AFTER 3:00PLOR HOLIDAYS.	M WEEKDAYS OR ANYTIME WEEKENDS
14. It is the responsibility of the property owner and/or drain	layer to ensure that all Federal State, and
Local permits have been obtained.	anyor to ondure that are reductar, state, and
15. Easements, Deeds, and all legal documents are the response	nsibility of the applicant and/or property
owner.	
16. Backflow Preventer/Check Valves are required on all bu	ildings with basement plumbing.
NOTE: Roof downspouts, foundation drains, area drains water to the public sewers are prohibited.	, and/or other sources of surface runoff or ground
	1
FEE: \$	Friends of Lindon Place Property Owner
10/1	JMC
Water Pollution Control Facility	Licensed Drainlayer
Superintendent	

2785

Date $5 - 3 - 23$	Permit: 2775KD	
The undersigned licensed Drainlayer requests permission to in	stall a sewer line at:	
23 Wilk St.	14 82	
NO. STREET	PLAT LOT	
ASSESSABLEYESNO ACCOUNT	NT NO:	
GENERAL RULES FOR INS	TALLING SEWER LINES:	
1. Pipes from public sewer to property line shall be 6" in diar		
2. Pipes from property line to building shall be 4" in diamete		
3. Junctions with public sewers shall be made at an angle by		
4. Clean outs are required outside the foundation plus at 75's direction; and at all 45 degree or greater angles.	increments, at all significant changes in	
<ul><li>5. Pipes shall be imbedded in 6" of sand, processed gravel, or is not acceptable.</li></ul>	r stone no greater than 3/4". Existing gravel	
6. Pipes shall be laid at a minimum of 3' below grade.		
<ol> <li>Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.</li> </ol>		
8. Plumbing Permit from building Inspector is required for al		
9. Roadcut Permit from Department of Public Works is requi	red for all roadcuts.	
<ul><li>10. All Permits must be on job site.</li><li>11. Sewer Permit is good for 4 weeks.</li></ul>		
12. Dig Safe must be notified by Drainlayer.		
13. NO INSPECTIONS WILL BE MADE AFTER 3:00PM OR HOLIDAYS.	WEEKDAYS OR ANYTIME WEEKENDS	
14. It is the responsibility of the property owner and/or drainla Local permits have been obtained.	yer to ensure that all Federal, State, and	
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.		
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.		
NOTE: Roof downspouts, foundation drains, area drains, water to the public sewers are prohibited.	and/or other sources of surface runoff or ground	
11)		
FEE: \$ () \ CK# a (NSO. 4256		
Name of the Control o	Property Owner	
1 Allin	CFC	
	Licensed Drainlayer	
Superintendent		

Date: 7/19/23	Permit: 2793 KD
The undersigned licensed Drainlayer requests permission to	o install a sewer line at:
149 High St	15 30
NO. STREET	PLAT LOT
ASSESSABLEYESNO ACC	OUNT NO:
GENERAL RULES FOR	INSTALLING SEWER LINES:
1. Pipes from public sewer to property line shall be 6" in	
2. Pipes from property line to building shall be 4" in diar	
3. Junctions with public sewers shall be made at an angle	
4. Clean outs are required outside the foundation plus at direction; and at all 45 degree or greater angles.	75 Increments; at all significant changes in
5. Pipes shall be imbedded in 6" of sand, processed grave	el, or stone no greater than 3/4". Existing gravel
is not acceptable.	
6. Pipes shall be laid at a minimum of 3' below grade.	. 11 '11' C
<ol><li>Inspection manholes shall be installed outside of common sampling.</li></ol>	nercial buildings for purposes of Prefreatment
8. Plumbing Permit from building Inspector is required for	or all interior connections.
9. Roadcut Permit from Department of Public Works is re	
10. All Permits must be on job site.	
11. Sewer Permit is good for 4 weeks.	
<ul><li>12. Dig Safe must be notified by Drainlayer.</li><li>13. NO INSPECTIONS WILL BE MADE AFTER 3:00</li></ul>	DM WEEKDAYS OD ANYTIME WEEKENDS
OR HOLIDAYS.	III WEEKDAIS OR ANTILUE WEEKENDS
14. It is the responsibility of the property owner and/or dra	ninlayer to ensure that all Federal, State, and
Local permits have been obtained.	
15. Easements, Deeds, and all legal documents are the res	ponsibility of the applicant and/or property
owner.  16. Backflow Preventer/Check Valves are required on all	buildings with basement plumbing.
NOTE: Roof downspouts, foundation drains, area drain	ns, and/or other sources of surface runoff or ground
water to the public sewers are prohibited.	
6	()
FEE: \$ /(/, CK# 260%	lansa
1 X1	Property Owner
	No ve to
Water Pollution Control Facility	Licensed Drainlayer
Superintendent Secretary	Diceised Diamayer