1 /		
Date: 1/4/23	Permit: 2776 KP	
The undersigned licensed Drainlayer requests pe	ermission to install a sewer line at:	
100	121 15%	
NO. STREET	PLAT LOT	
ASSESSABLE YES NO	ACCOUNT NO:	
GENERAL RUL	LES FOR INSTALLING SEWER LINES:	
1. Pipes from public sewer to property line shall		
<ol> <li>Pipes from property line to building shall be</li> <li>Junctions with public sewers shall be made a</li> </ol>		
	on plus at 75' increments; at all significant changes in	
direction; and at all 45 degree or greater ang		
	ssed gravel, or stone no greater than 3/4". Existing gravel	
<ul><li>is not acceptable.</li><li>6. Pipes shall be laid at a minimum of 3' below</li></ul>	grade.	
	le of commercial buildings for purposes of Pretreatment	
sampling.	16 11:	
8. Plumbing Permit from building Inspector is		
<ol> <li>Roadcut Permit from Department of Public Works is required for all roadcuts.</li> <li>All Permits must be on job site.</li> </ol>		
11. Sewer Permit is good for 4 weeks.		
12. Dig Safe must be notified by Drainlayer.		
13. NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS		
OR HOLIDAYS.  14 It is the responsibility of the property owner:	and/or drainlayer to ensure that all Federal. State, and	
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.		
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property		
owner.  16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.		
10. Dacknow Treventer/Check varies are require	tod off an oundings with ousement prantomy.	
	area drains, and/or other sources of surface runoff or gr	ound
water to the public sewers are prohibited.		
2011 1212		
FEE: \$ CK#	Mendshi	
1/1/	Property Owner	
The AVIZ	h h construction	
Water Pollution Control Facility	Licensed Drainlayer	
Superintendent		
White: WPCF Green: Tax Assessor Yellow: Town C	Council Pink: Drainlayer Gold: Homeowner	

Date: $3-24-23$	Pern	nit: 3784KD
The undersigned licensed Drainlayer requests permis	ssion to install a sewer	line at:
NO. STREET	PLAT	LOT
ASSESSABLEYESNO	ACCOUNT NO:	
GENERAL RULES	FOR INSTALLING S	SEWER LINES:
GENERAL RULES FOR INSTALLING SEWER LINES:  1. Pipes from public sewer to property line shall be 6" in diameter. 2. Pipes from property line to building shall be 4" in diameter. 3. Junctions with public sewers shall be made at an angle by installing a wye or a tee. 4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles. 5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable. 6. Pipes shall be laid at a minimum of 3' below grade. 7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling. 8. Plumbing Permit from building Inspector is required for all interior connections. 9. Roadcut Permit from Department of Public Works is required for all roadcuts. 10. All Permits must be on job site. 11. Sewer Permit is good for 4 weeks. 12. Dig Safe must be notified by Drainlayer. 13. NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS. 14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained. 15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner. 16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.  NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.		
White: WPCF Green: Tay Assessor Vellow: Town Council	l Pink: Drainlayer	Gold: Homeowner

2805 KA

Date: 12/14/23	Permit:_	28050
The undersigned licensed Drainlayer requests permission	to install a sewer line	at:
151 terry Rd		
NO. STREET	PLAT	LOT
ASSESSABLEYESNO AC	COUNT NO:	
GENERAL RULES FOR INSTALLING SEWER LINES:		
<ol> <li>Pipes from public sewer to property line shall be 6" in</li> <li>Pipes from property line to building shall be 4" in dia</li> </ol>		
3. Junctions with public sewers shall be made at an ang	e by installing a wye o	
<ol> <li>Clean outs are required outside the foundation plus a direction; and at all 45 degree or greater angles.</li> </ol>	75' increments; at all	significant changes in
5. Pipes shall be imbedded in 6" of sand, processed grav	el, or stone no greater	than 3/4". Existing gravel
is not acceptable.		
6. Pipes shall be laid at a minimum of 3' below grade.		
7. Inspection manholes shall be installed outside of com	mercial buildings for p	ourposes of Pretreatment
sampling.  8. Plumbing Permit from building Inspector is required	for all interior connect	ions
<ol> <li>Roadcut Permit from Department of Public Works is required for all roadcuts.</li> <li>All Permits must be on job site.</li> </ol>		
11. Sewer Permit is good for 4 weeks.		
12. Dig Safe must be notified by Drainlayer.		
13. NO INSPECTIONS WILL BE MADE AFTER 3:	OPM WEEKDAYS (	OR ANYTIME WEEKENDS
OR HOLIDAYS.		
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and		
Local permits have been obtained.		
<ol> <li>Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.</li> </ol>		
16. Backflow Preventer/Check Valves are required on al	l buildings with basem	ent plumbing.
NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.		
115		
FEE: \$ 10 \ CK# 965 \		and the second s
	Property Owner	
11/10	11000	
Water Pollution Control Facility	Licensed Drainla	yer
Superintendent		

Date: 1/31/24	Permit: 2806 KD	
The second secon		
The undersigned licensed Drainlayer requests permission	to install a sewer line at:	
43 High St.	16 38	
NO. STREET	PLAT LOT	
ASSESSABLEYESNO ACC	COUNT NO:	
GENERAL RULES FOR	INSTALLING SEWER LINES:	
<ol> <li>Pipes from public sewer to property line shall be 6" in</li> <li>Pipes from property line to building shall be 4" in diar</li> </ol>	neter.	
3. Junctions with public sewers shall be made at an angle		
4. Clean outs are required outside the foundation plus at	75' increments; at all significant changes in	
direction; and at all 45 degree or greater angles.  5. Pipes shall be imbedded in 6" of sand, processed grave	of or stone no greater than 3/4" Existing gravel	
is not acceptable.	s, of stolle no greater than 5/4. Existing graver	
6. Pipes shall be laid at a minimum of 3' below grade.		
7. Inspection manholes shall be installed outside of comm	nercial buildings for purposes of Pretreatment	
sampling.		
8. Plumbing Permit from building Inspector is required f		
9. Roadcut Permit from Department of Public Works is required for all roadcuts.		
10. All Permits must be on job site.		
<ul><li>11. Sewer Permit is good for <u>4 weeks</u>.</li><li>12. Dig Safe must be notified by Drainlayer.</li></ul>		
	DPM WEEKDAYS OR ANYTIME WEEKENDS	
13. NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.		
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and		
Local permits have been obtained.		
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.		
16. Backflow Preventer/Check Valves are required on all	buildings with basement plumbing.	
NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.		
water to the public sewers are prombited.		
FEE: \$ 10 CK# C/S h		
1. Del Li	Property Owner	
Water Pollution Control Facility	Licensed Drainlayer	
Superintendent		

Date: 7 1 2	Permit:	2813KD
The undersigned licensed Drainlayer requests permissi	on to install a sewer line a	at:
103 Fales Rd	80	84
NO. STREET	PLAT	LOT
ASSESSABLEYESNO A	CCOUNT NO:	
GENERAL RULES FO	OR INSTALLING SEW	ER LINES:
1. Pipes from public sewer to property line shall be 6" in diameter. 2. Pipes from property line to building shall be 4" in diameter. 3. Junctions with public sewers shall be made at an angle by installing a wye or a tee. 4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles. 5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable. 6. Pipes shall be laid at a minimum of 3' below grade. 7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling. 8. Plumbing Permit from building Inspector is required for all interior connections. 9. Roadcut Permit from Department of Public Works is required for all roadcuts. 10. All Permits must be on job site. 11. Sewer Permit is good for 4 weeks. 12. Dig Safe must be notified by Drainlayer. 13. NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS. 14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.		
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.		
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.		
NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.		
Water Pollution Control Facility Superintendent	Property Owner  Licensed Drainlay	rer

Date: 6/25/24	Permit: <u>580 K</u> D	
The undersigned licensed Drainlayer requests permission to install	a sewer line at:	
45 Harreworth	. 4	
NO. STREET PLAT	T LOT	
ASSESSABLE YES NO ACCOUNT N	10.	
ASSESSABLEYESNO ACCOUNT N	0	
GENERAL RULES FOR INSTAL	LING SEWER LINES:	
1. Pipes from public sewer to property line shall be 6" in diameter		
2. Pipes from property line to building shall be 4" in diameter.		
3. Junctions with public sewers shall be made at an angle by instal		
4. Clean outs are required outside the foundation plus at 75' incre	ments; at all significant changes in	
direction; and at all 45 degree or greater angles.  5. Pipes shall be imbedded in 6" of sand, processed gravel, or ston	e no greater than 3/4" Existing gravel	
is not acceptable.	e no greater than 3/4 . Existing graver	
6. Pipes shall be laid at a minimum of 3' below grade.		
7. Inspection manholes shall be installed outside of commercial but	aildings for purposes of Pretreatment	
sampling.		
8. Plumbing Permit from building Inspector is required for all inte	erior connections.	
9. Roadcut Permit from Department of Public Works is required for	or all roadcuts.	
10. All Permits must be on job site.		
11. Sewer Permit is good for 4 weeks.		
<ul><li>12. Dig Safe must be notified by Drainlayer.</li><li>13. NO INSPECTIONS WILL BE MADE AFTER 3:00PM WE</li></ul>	FEDAVE OD ANVTIME WEEKENDS	
OR HOLIDAYS.	ENDATS OR ANTITUTE WEEKENDS	
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and		
Local permits have been obtained.	onours that are a survey, state, and	
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property		
owner.		
16. Backflow Preventer/Check Valves are required on all buildings	with basement plumbing.	
NOTE: Roof downspouts, foundation drains, area drains, and/o water to the public sewers are prohibited.	or other sources of surface runoff or ground	
ANU _	erty Owner nsed Drainlayer	

White: WPCF

Green: Tax Assessor Yellow: Town Council

Pink: Drainlayer Gold: Homeowner

14/1/32

## TOWN OF BRISTOL, RI APPLICATION FOR SEWER PERMIT

Date: 6/10/24	Permit: 2810 KD	
The undersigned licensed Drainlayer requests permission	on to install a sewer line at:	
The undersigned incensed Dramayor requests permission	to histail a sewer fine at.	
17 Inchael DI	PLAT LOT	
NO. STREET	PLAT LOT	
ASSESSABLEYESNO AC	CCOUNT NO:	
GENERAL RULES FO	R INSTALLING SEWER LINES:	
1. Pipes from public sewer to property line shall be 6"	in diameter.	
2. Pipes from property line to building shall be 4" in di	iameter.	
3. Junctions with public sewers shall be made at an ang		
4. Clean outs are required outside the foundation plus	at 75' increments; at all significant changes in	
direction; and at all 45 degree or greater angles.  5. Pipes shall be imbedded in 6" of sand, processed gra	avel or stone no greater than 3/4" Existing gravel	
is not acceptable.	ivol, of stollo no greater than 571. Existing graves	
6. Pipes shall be laid at a minimum of 3' below grade.		
7. Inspection manholes shall be installed outside of con	mmercial buildings for purposes of Pretreatment	
sampling.	and the second s	
8. Plumbing Permit from building Inspector is required		
9. Roadcut Permit from Department of Public Works is	s required for all roadcuts.	
10. All Permits must be on job site.  11. Sewer Permit is good for 4 weeks.		
12. Dig Safe must be notified by Drainlayer.		
13. NO INSPECTIONS WILL BE MADE AFTER 3:	:00PM WEEKDAYS OR ANYTIME WEEKENDS	
OR HOLIDAYS.		
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and		
Local permits have been obtained.		
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property		
owner.  16. Backflow Preventer/Check Valves are required on a	all buildings with basement plumbing	
10. Backilow Heventer Check varios are required on a	in oundings with ousement pramoning.	
NOTE: Roof downspouts, foundation drains, area di	rains, and/or other sources of surface runoff or ground	
water to the public sewers are prohibited.		
h -	1 -	
FEE: \$ CK#	Mavid Sa	
CK#	Property Owner	
ton Illa	(homeowner)	
Water Pollution Control Facility	Licensed Drainlayer	
Superintendent Secretory		

White: WPCF

Green: Tax Assessor Yellow: Town Council

Pink: Drainlayer

Gold: Homeowner

Date: 6/21/24	Permit:	281180
The undersigned licensed Drainlayer requests permission	to install a sewer line a	t:
NO. STREET	PLAT	LOT
ASSESSABLEYESNO ACC	COUNT NO:	
GENERAL RULES FOR	R INSTALLING SEWE	ER LINES:
<ol> <li>Pipes from public sewer to property line shall be 6" in</li> <li>Pipes from property line to building shall be 4" in dia</li> </ol>		
3. Junctions with public sewers shall be made at an angle		
4. Clean outs are required outside the foundation plus at	75' increments; at all s	ignificant changes in
direction; and at all 45 degree or greater angles.  5. Pipes shall be imbedded in 6" of sand, processed grav	rel or stone no greater th	nan 3/4" Existing gravel
is not acceptable.	ci, or stone no greater to	inan 5/4 . Daisting graver
6. Pipes shall be laid at a minimum of 3' below grade.		
7. Inspection manholes shall be installed outside of com	mercial buildings for pu	rposes of Pretreatment
sampling.		
8. Plumbing Permit from building Inspector is required		
9. Roadcut Permit from Department of Public Works is required for all roadcuts.		
10. All Permits must be on job site. 11. Sewer Permit is good for 4 weeks.		
12. Dig Safe must be notified by Drainlayer.		
13. NO INSPECTIONS WILL BE MADE AFTER 3:0	OPM WEEKDAYS OF	R ANYTIME WEEKENDS
OR HOLIDAYS.		
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and		
Local permits have been obtained.		
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.		
16. Backflow Preventer/Check Valves are required on all	l buildings with basemen	nt plumbing.
NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.		
Water Pollution Control Facility Superintendent	Property Owner  Licensed Drainlaye	er .

White: WPCF

Green: Tax Assessor Yellow: Town Council

Pink: Drainlayer Gold: Homeowner

2807

### TOWN OF BRISTOL, RI APPLICATION FOR SEWER PERMIT

Date: 3-13-24	Permit:_	2807KD
The undersigned licensed Drainlayer requests permission to	install a sewer line	at:
21 Verna		
NO. STREET	PLAT	LOT
ASSESSABLEYESNO ACCC	UNT NO:	
GENERAL RULES FOR INSTALLING SEWER LINES:		
1. Pipes from public sewer to property line shall be 6" in d		
<ol> <li>Pipes from property line to building shall be 4" in diame</li> <li>Junctions with public sewers shall be made at an angle be</li> </ol>		ar a tee
4. Clean outs are required outside the foundation plus at 7:		
direction; and at all 45 degree or greater angles.		1 0/4" F : :
<ol><li>Pipes shall be imbedded in 6" of sand, processed gravel, is not acceptable.</li></ol>	or stone no greater	than 3/4". Existing gravel
6. Pipes shall be laid at a minimum of 3' below grade.		
7. Inspection manholes shall be installed outside of commo	ercial buildings for p	ourposes of Pretreatment
sampling.  8. Plumbing Permit from building Inspector is required for all interior connections.		
9. Roadcut Permit from Department of Public Works is required for all roadcuts.		
<ul><li>10. All Permits must be on job site.</li><li>11. Sewer Permit is good for 4 weeks.</li></ul>		
12. Dig Safe must be notified by Drainlayer.		
13. NO INSPECTIONS WILL BE MADE AFTER 3:001	M WEEKDAYS C	OR ANYTIME WEEKENDS
OR HOLIDAYS.  14 It is the responsibility of the property owner and/or drain	nlaver to ensure that	all Federal State and
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.		
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property		
owner.  16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.		
NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.		
21	111.00	meStructures
FEE: \$ CK#	-	nostracia res
1. / 1. / 1	Property Owner	
The Secretary)	JMC	
Water Pollution Control Facility Superintendent	Licensed Drainla	yer

White: WPCF

Green: Tax Assessor Yellow: Town Council

Pink: Drainlayer

Gold: Homeowner

Date: 7/31/24	Permit: 2416KD	
Date.	remit.	
The undersigned licensed Drainlayer requests perm	ission to install a sewer line at:	
65 Savrens		
NO. STREET	PLAT LOT	
ASSESSABLEYESNO	ACCOUNT NO:	
GENERAL RULES	FOR INSTALLING SEWER LINES:	
<ol> <li>Pipes from public sewer to property line shall be</li> <li>Pipes from property line to building shall be 4"</li> </ol>		
3. Junctions with public sewers shall be made at an		
4. Clean outs are required outside the foundation p		
direction; and at all 45 degree or greater angles.		
is not acceptable.	d gravel, or stone no greater than 3/4". Existing gravel	
6. Pipes shall be laid at a minimum of 3' below gr	ade.	
	f commercial buildings for purposes of Pretreatment	
sampling.		
8. Plumbing Permit from building Inspector is required for all interior connections.		
<ol> <li>Roadcut Permit from Department of Public Works is required for all roadcuts.</li> <li>All Permits must be on job site.</li> </ol>		
11. Sewer Permit is good for 4 weeks.		
12. Dig Safe must be notified by Drainlayer.		
13. NO INSPECTIONS WILL BE MADE AFTE	R 3:00PM WEEKDAYS OR ANYTIME WEEKENDS	
OR HOLIDAYS.		
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and		
Local permits have been obtained.  15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property		
owner.		
16. Backflow Preventer/Check Valves are required	on all buildings with basement plumbing.	
NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.		
hater to the passes series are promoted.		
FEE: \$ 10 CK# CAST		
1 /	Property Owner	
1011.	cotte	
Water Pollution Control Facility	Licensed Drainlayer	
Superintendent	Zioniou z iumu, ii	

White: WPCF

Green: Tax Assessor Yellow: Town Council

Pink: Drainlayer Gold: Homeowner