

LUXURY HIGH-PERFORMANCE DECKING

Trex Signature® decking is made of nature-inspired wood thermoplastic lumber (WTCL) for a look as much like wood as wood itself. The proprietary shell formulation creates an elegant grain pattern finish and a high-end matte feel. An alternative to naturally durable hardwood lumber, Signature Decking is ICC-ES ESR-2089-certified to be a minimum of 92.6% recycled content by weight.



FEATURES	DECKING BOARDS	
	1" x 6" Grooved Edge	1" x 6" Square Edge
Actual Dimensions - Standard	.94" x 5.5"	.94" x 5.5"
Actual Dimensions - Metric	24 mm x 140 mm	24 mm x 140 mm
Available Lengths - Standard	12', 16', 20'	20'
Available Lengths - Metric	365 cm, 487 cm, 609 cm	609 cm
Weight per Lineal Foot	2.4 lbs	2.5 lbs

PHYSICAL & MECHANICAL PROPERTIES

TEST	TEST METHOD	VALUE
Flame Spread	ASTM E 84	Class C Flame Spread Index
Thermal Expansion	ASTM D 1037	1.9 × 10 ⁻⁵ in/in/°F
Moisture Absorption	ASTM D 1037	< 1%
Screw Head Pull-Through	ASTM D1761	161 lbf/screw*
Fungus Resistance	ASTM D1413	Rating – no decay
Termite Resistance	AWPAE1-72	Rating = 9.6

*Fastener used in testing: #8 x 2.5" HEADCOTE Stainless Steel Screw

COLORS



With the reassurance of our **50-Year Limited Residential and Fade & Stain Warranty**.

For warranty and installation information, please visit signature.trex.com

FASTENERS

Trex Hideaway® Hidden Fastening System

Self-gapping, glass-filled nylon fastener with 304 grade stainless steel sharp point screw for wood framing. Increase installation speed and accuracy with the Trex® Universal Fastener Installation Tool. Other approved fasteners include color-matched composite deck screw, matching composite plug with composite screw, color-coordinated fascia screw and uncoated stainless steel fascia screw.

For a full list of approved fasteners, download our Installation Guide at trex.com/literature

