

Repair

2832 KD

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date:

7/11/25

Permit:

2832 KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

13 Baker St.

NO. STREET

PLAT

LOT

ASSESSABLE ☐ YES ☐ NO

ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$

105

CK#

cash

Water Pollution Control Facility
Superintendent

Jim DePina
Secretary

Property Owner

[Signature]

L. Ramos
Licensed Drainlayer

White: WPCF

Green: Tax Assessor Yellow: Town Council

Pink: Drainlayer

Gold: Homeowner

2833 JD

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date: 7/15/25Permit: 2833 JD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

28 Center ST 33 71
NO. STREET PLAT LOT

ASSESSABLE ☐ YES ☐ NO

ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$ 10.00CK# 4759

Ron L.
Property Owner

JML
Licensed Drainlayer

Water Pollution Control Facility
Superintendent

ck # 4759

White: WPCF

Green: Tax Assessor Yellow: Town Council

Pink: Drainlayer

Gold: Homeowner

Repair

2827KD

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date: 4/28/25

Permit: 2827KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

Philip King
enter

NO. STREET PLAT LOT

ASSESSABLE ☐ YES ☐ NO ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$ 10 CK# _____

Philip King

Water Pollution Control Facility
Superintendent

Property Owner

JML
Licensed Drainlayer

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date:

4/23/05

Permit:

2826KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

106 King Philip

NO. STREET

PLAT

LOT

ASSESSABLE ☒ YES ☐ NO

ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$

105

CK#

1

Property Owner

ELJ

Water Pollution Control Facility
Superintendent

Licensed Drainlayer

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date: 4/30/05

Permit: 2829KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

103 Aaron Ave
NO. STREET PLAT LOT

ASSESSABLE ☐ YES ☐ NO ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$ 10

CK# 1144

Water Pollution Control Facility
Superintendent

Property Owner

David Kames, landscaping
Licensed Drainlayer

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date: 6/13/25

Permit: _____

The undersigned licensed Drainlayer requests permission to install a sewer line at:

<u>3</u>	<u>Hawthorne</u>	<u>121</u>	<u>130</u>
NO.	STREET	PLAT	LOT


ASSESSABLE ☐ YES ☒ NO

ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$ 10.00CK# 4754R. Marcaccio
Property OwnerJML
Licensed Drainlayer

Water Pollution Control Facility
Superintendent