TOWN OF BRISTOL, RI

2 /10	2798 KD
TOWN OF BRISTOL, RI APPLICATION FOR SEWER PERMIT	
Date: $10/24/23$ Permit: $2798K$	D
The undersigned licensed Drainlayer requests permission to install a sewer line at:	
1-7 Correshall 147 50	
NO. STREET PLAT LOT	energia de la companio del companio de la companio del companio de la companio della companio de la companio della companio de
ASSESSABLEYESNO ACCOUNT NO:	
GENERAL RULES FOR INSTALLING SEWER LINES:	
1. Pipes from public sewer to property line shall be 6" in diameter.	
2. Pipes from property line to building shall be 4" in diameter.	
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in the control of the cont	in
direction; and at all 45 degree or greater angles.	III
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing a	gravel
is not acceptable.	
6. Pipes shall be laid at a minimum of 3' below grade.	
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment	ent
sampling.	
8. Plumbing Permit from building Inspector is required for all interior connections.9. Roadcut Permit from Department of Public Works is required for all roadcuts.	
10. All Permits must be on job site.	
11. Sewer Permit is good for 4 weeks.	
12. Dig Safe must be notified by Drainlayer.	
13. NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEE	EKENDS
OR HOLIDAYS.	
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.	nd
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property	ı
owner.	(
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.	
NOTE: Decidence of femaletic decidence of the second of th	00
NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runof water to the public sewers are prohibited.	ff or ground
water to the public severs are promotion.	
FEE: \$ 20. CK# 4558 Fair Wind Propertie	0 5
AlD each con rection Property Owner	2
(10 each Greeting)	
Am Della (secretary) JMC	
Water Pollution Control Facility Licensed Drainlayer	TOIAIR
Superintendent	TOWN COUNCIL
	DEC 0 6 2023
WAY WOOD	A free proofer to
White: WPCF Green: Tax Assessor Yellow: Town Council Pink: Drainlayer Gold: Homeowner	MEETING

2795

Date: 4/20/23 Permit: 9795KD		
contractive Labilities (
The undersigned licensed Drainlayer requests permission to install a sewer line at:		
27/ Hase 14 116		
NO. STREET PLAT LOT		
ASSESSABLEYESNO ACCOUNT NO:		
GENERAL RULES FOR INSTALLING SEWER LINES:		
1. Pipes from public sewer to property line shall be 6" in diameter.		
2. Pipes from property line to building shall be 4" in diameter.		
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.		
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.		
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel		
is not acceptable.		
6. Pipes shall be laid at a minimum of 3' below grade.		
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment		
sampling.		
 Plumbing Permit from building Inspector is required for all interior connections. Roadcut Permit from Department of Public Works is required for all roadcuts. 		
10. All Permits must be on job site.		
11. Sewer Permit is good for 4 weeks.		
12. Dig Safe must be notified by Drainlayer.		
13. NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS		
OR HOLIDAYS.		
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and		
Local permits have been obtained. 15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property		
owner.		
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.		
NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground		
water to the public sewers are prohibited.		
FEE: \$ CK# 2577		
Property Owner		
Water Pollution Control Facility Licensed Drainlayer		
Superintendent Edition Control Lasmy Electrical Brandayer		

2796 K

TOWN OF BRISTOL, RI APPLICATION FOR SEWER PERMIT

Date: 01-11-23	Permit:	5796
The undersigned licensed Drainlayer requests perm	ission to install a sewer line	at:
12 Loa Dr		
NO. STREET	PLAT	LOT
ASSESSABLEYESNO	ACCOUNT NO:	·
GENERAL RULES	S FOR INSTALLING SEV	VER LINES:
		or a tee. I significant changes in than 3/4". Existing gravel purposes of Pretreatment tions. Its. OR ANYTIME WEEKENDS It all Federal, State, and licant and/or property ment plumbing. Inces of surface runoff or ground
Water Pollution Control Facility Superintendent	Licensed Drainla	iyei
30010		

Pink: Drainlayer

Gold: Homeowner

White: WPCF

Green: Tax Assessor Yellow: Town Council

2802

Date: $\frac{4^{i}/3}{2}$	Permit: 2802 JD	
The undersigned licensed Drainlayer requests perm	ission to install a sewer line at:	
180 M+ H & A.	41	
NO. STREET	PLAT LOT	
ASSESSABLEYESNO	ACCOUNT NO:	
GENERAL RULES	FOR INSTALLING SEWER LINES:	
1. Pipes from public sewer to property line shall be	e 6" in diameter.	
2. Pipes from property line to building shall be 4"		
3. Junctions with public sewers shall be made at an		
4. Clean outs are required outside the foundation p		
direction; and at all 45 degree or greater angles. 5. Pines shall be imbedded in 6" of sand, processes.	d gravel, or stone no greater than 3/4". Existing gravel	
is not acceptable.	a graver, or stone no greater than 5/4. Existing graver	
6. Pipes shall be laid at a minimum of 3' below gra	ade	
	f commercial buildings for purposes of Pretreatment	
sampling.	2 volumerous outlands for purposes of Frenchisters	
8. Plumbing Permit from building Inspector is req	uired for all interior connections.	
9. Roadcut Permit from Department of Public Wor		
10. All Permits must be on job site.		
11. Sewer Permit is good for <u>4 weeks</u> .		
12. Dig Safe must be notified by Drainlayer.		
13. NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS		
OR HOLIDAYS.		
14. It is the responsibility of the property owner and	l/or drainlayer to ensure that all Federal, State, and	
Local permits have been obtained.		
15. Easements, Deeds, and all legal documents are	the responsibility of the applicant and/or property	
owner.	an all buildings with becoment absorbing	
16. Backflow Preventer/Check Valves are required	on all buildings with basement plumbing.	
NOTE: Roof downspouts, foundation drains, are water to the public sewers are prohibited.	ea drains, and/or other sources of surface runoff or ground	
FEE: \$ / / CK# _ CK#	DXD Bristol Stonege	
	Property Owner	
2. Comment	E / 1	
Water Pollution Control Essility	Licensed Designation	
Water Pollution Control Facility	Licensed Drainlayer	
Superintendent		

TOWN OF BRISTOL, RI APPLICATION FOR SEWER PERMIT

Date: 3/14/23	Permit:	782KD	
The undersigned licensed Drainlayer requests permission	to install a sewer line at:		
3 Anguan Ave	122	6	
NO. STREET	PLAT	LOT	
ASSESSABLEYESNO ACC	OUNT NO:		
GENERAL RULES FOR	INSTALLING SEWER I	LINES:	
1. Pipes from public sewer to property line shall be 6" in	diameter		
2. Pipes from property line to building shall be 4" in dian			
3. Junctions with public sewers shall be made at an angle		e.	
4. Clean outs are required outside the foundation plus at			
direction; and at all 45 degree or greater angles.	, s merements, at an signi	modific changes in	
5. Pipes shall be imbedded in 6" of sand, processed grave	el, or stone no greater than	3/4" Existing gravel	
is not acceptable.	on, or brone no greater than	ST. LANGUING BILLYON	
6. Pipes shall be laid at a minimum of 3' below grade.			
7. Inspection manholes shall be installed outside of communities of the community of the co	nercial buildings for purpos	ses of Pretreatment	
sampling.	nereiai bundings for purpos	ses of Frencament	
Plumbing Permit from building Inspector is required from building Inspector.	or all interior connections		
9. Roadcut Permit from Department of Public Works is r			
10. All Permits must be on job site.	equired for an roadcuts.		
11. Sewer Permit is good for 4 weeks.			
12. Dig Safe must be notified by Drainlayer.			
13. NO INSPECTIONS WILL BE MADE AFTER 3:00	DM WEEKDAYS OD A	NVTIME WEEVENDS	
OR HOLIDAYS.	FINI WEEKDATS OR A	NI THE WEEKENDS	
	simlayer to answer that all E	adoral State and	
14. It is the responsibility of the property owner and/or dra	imayer to ensure that all F	ederal, State, and	
Local permits have been obtained.			
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.			
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.			
NOTE: Roof downspouts, foundation drains, area dra	ins, and/or other sources of	of surface runoff or ground	
water to the public sewers are prohibited.			
	1.7		
FEE: \$ CK# CASh	Almord	a	
	Property Owner		
	Troporty Owner		
And della	L. Kania	2	
Water Pollution Control Facility	Licensed Drainlayer		
Superintendent	Division Dining of		

White: WPCF Green: Tax Assessor Yellow: Town Council

Pink: Drainlayer Gold: Homeowner

Date: 3/4/2/	Permit: 2723 KD		
The undersigned licensed Drainlayer requests perm	hission to install a sewer line at:		
16 San Francisco	St. 90 #12		
NO. STREET	PLAT LOT		
ASSESSABLEYESNO	ACCOUNT NO:		
GENERAL RULES	S FOR INSTALLING SEWER LINES:		
 Pipes from public sewer to property line shall b Pipes from property line to building shall be 4" 	in diameter.		
Junctions with public sewers shall be made at aClean outs are required outside the foundation direction; and at all 45 degree or greater angles	Junctions with public sewers shall be made at an angle by installing a wye or a tee.Clean outs are required outside the foundation plus at 75' increments; at all significant changes in		
5. Pipes shall be imbedded in 6" of sand, processe is not acceptable.	d gravel, or stone no greater than 3/4". Existing gravel		
6. Pipes shall be laid at a minimum of 3' below gr			
sampling.	of commercial buildings for purposes of Pretreatment		
8. Plumbing Permit from building Inspector is req	jured for all interior connections.		
 Roadcut Permit from Department of Public Wo All Permits must be on job site. 	rks is required for all roadcuts.		
11. Sewer Permit is good for 4 weeks.			
12. Dig Safe must be notified by Drainlayer.			
	CR 3:00PM WEEKDAYS OR ANYTIME WEEKENDS		
OR HOLIDAYS.	3. 3. 3. 3. 3. 3. 3. 3. 3. 3. 3. 3. 3. 3		
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.			
 Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner. 			
16. Backflow Preventer/Check Valves are required	on all buildings with basement plumbing.		
NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.			
FEE: \$ 250 CK# 4100	Name and control of the control of t		
1 Alla	Property Owner		
Water Pollution Control Facility Superintendent	Licensed Drainlayer		

2722 KI

Date: $3/4/2/$	Permit: <u>2722 K</u> b	
The undersigned licensed Drainlayer requests permission to	install a sewer line at:	
Jan Francisco St.	70 118	
NO. STREET	PLAT LOT	
ASSESSABLE YES NO ACCO	UNT NO:	
GENERAL RULES FOR II	NSTALLING SEWER LINES:	
1. Pipes from public sewer to property line shall be 6" in di	ameter.	
2. Pipes from property line to building shall be 4" in diame	eter.	
3. Junctions with public sewers shall be made at an angle b	y installing a wye or a tee.	
4. Clean outs are required outside the foundation plus at 75	'increments; at all significant changes in	
direction; and at all 45 degree or greater angles.		
5. Pipes shall be imbedded in 6" of sand, processed gravel, is not acceptable.	or stone no greater than 3/4". Existing gravel	
6. Pipes shall be laid at a minimum of 3' below grade.		
7. Inspection manholes shall be installed outside of comme	rcial buildings for purposes of Protreatment	
sampling.	icial buildings for purposes of Fretteatment	
8. Plumbing Permit from building Inspector is required for	all interior connections	
9. Roadcut Permit from Department of Public Works is req	uired for all roadcuts.	
10. All Permits must be on job site.		
11. Sewer Permit is good for 4 weeks.		
12. Dig Safe must be notified by Drainlayer.		
13. NO INSPECTIONS WILL BE MADE AFTER 3:00P	M WEEKDAYS OR ANYTIME WEEKENDS	
OR HOLIDAYS.		
14. It is the responsibility of the property owner and/or drain	layer to ensure that all Federal, State, and	
Local permits have been obtained.		
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property		
owner. 16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.		
NOTE: Past downsparts foundation during area during	and/anathanana C	
NOTE: Roof downspouts, foundation drains, area drains water to the public sewers are prohibited.	s, and/or other sources of surface runoff or ground	
water to the public sewers are promotted.		
100		
FEE: \$ CK#		
	Property Owner	
1 1/	1/0.4 /	
- Note of the second se	-J///	
Water Pollution Control Facility	Licensed Drainlayer	
Superintendent		

2799/0

Date: 10 37 23		Permit: <u>9799(C)</u>
The undersigned licensed Drainlayer requests permis	ssion to install a se	ewer line at:
3) Keck St	-	
NO. STREET	PLAT	LOT
ASSESSABLEYESNO	ACCOUNT NO:_	
GENERAL RULES	FOR INSTALLI	NG SEWER LINES:
 Pipes from public sewer to property line shall be Pipes from property line to building shall be 4" in 		
3. Junctions with public sewers shall be made at an	angle by installing	
4. Clean outs are required outside the foundation pl	us at 75' incremen	nts; at all significant changes in
direction; and at all 45 degree or greater angles. 5. Pipes shall be imbedded in 6" of sand, processed	gravel or stone no	o greater than 3/4" Existing gravel
is not acceptable.	graver, or stone in	o greater than 5/4. Existing graver
6. Pipes shall be laid at a minimum of 3' below gra		
Inspection manholes shall be installed outside of sampling.	commercial buildi	ings for purposes of Pretreatment
8. Plumbing Permit from building Inspector is requ	ired for all interior	r connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.		
10. All Permits must be on job site.		
11. Sewer Permit is good for 4 weeks.12. Dig Safe must be notified by Drainlayer.		
13. NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS		
OR HOLIDAYS. 14. It is the responsibility of the property owner and/	or drainlayer to en	sure that all Federal, State, and
Local permits have been obtained.	19.1914	
 Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner. 		
16. Backflow Preventer/Check Valves are required of	on all buildings wi	th basement plumbing.
NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.		
FEE: \$		
1 1 1 1	Property	Owner
Water Pollution Control Facility	Licensed	l Drainlayer
Superintendent		

TOWN OF BRISTOL, RI

APPLICATION FOR	SEWER PERMIT	
Date: 11 8/33	Permit: 2803 KD	
The undersigned licensed Drainlayer requests permission to	install a sewer line at:	
2 Peter Rd	108 13	
NO. STREET	PLAT LÔT	
ASSESSABLEYESNO ACCO	OUNT NO:	
GENERAL RULES FOR I	NSTALLING SEWER LINES:	
 Pipes from public sewer to property line shall be 6" in d Pipes from property line to building shall be 4" in diame 	eter.	
 Junctions with public sewers shall be made at an angle to Clean outs are required outside the foundation plus at 75 direction; and at all 45 degree or greater angles. 		
5. Pipes shall be imbedded in 6" of sand, processed gravel, is not acceptable.	, or stone no greater than 3/4". Existing gravel	
6. Pipes shall be laid at a minimum of 3' below grade.		
 Inspection manholes shall be installed outside of common sampling. 		
8. Plumbing Permit from building Inspector is required for9. Roadcut Permit from Department of Public Works is rec		
10. All Permits must be on job site.		
11. Sewer Permit is good for 4 weeks.		
12. Dig Safe must be notified by Drainlayer. 13. NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS		
OR HOLIDAYS.		
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and		
Local permits have been obtained.		
Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.		
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.		
NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.		
FEE: \$ 10 CK# paidck#		
	Property Owner	
the delta (seretin)	L. Kames	
Water Pollution Control Facility	Licensed Drainlayer	
Superintendent		

TOWN OF BRISTOL, RI APPLICATION FOR SEWER PERMIT

12/12/2	1797 N		
Date: 10 8 80	Permit:		
The undersigned licensed Drainlayer requests permis	ssion to install a sewer line at:		
253 Franklin But	muood		
NO. STREET	PLAT LOT		
ASSESSABLEYESNO	ACCOUNT NO:		
GENERAL RULES	FOR INSTALLING SEWER LINES:		
1. Pipes from public sewer to property line shall be	6" in diameter.		
2. Pipes from property line to building shall be 4" in	n diameter.		
3. Junctions with public sewers shall be made at an			
4. Clean outs are required outside the foundation pl	us at 75' increments; at all significant changes in		
direction; and at all 45 degree or greater angles.	and a standard than 2/4" Frieting and		
is not acceptable.	gravel, or stone no greater than 3/4". Existing gravel		
6. Pipes shall be laid at a minimum of 3' below gra	de		
7. Inspection manholes shall be installed outside of			
sampling.	- Faritain		
8. Plumbing Permit from building Inspector is requ	ired for all interior connections.		
Roadcut Permit from Department of Public Work	cs is required for all roadcuts.		
	10. All Permits must be on job site.		
11. Sewer Permit is good for 4 weeks.			
12. Dig Safe must be notified by Drainlayer.	R 3:00PM WEEKDAYS OR ANYTIME WEEKENDS		
OR HOLIDAYS.	N 3:00FM WEEKDA IS ON AN I IIME WEEKENDS		
14. It is the responsibility of the property owner and/	or drainlayer to ensure that all Federal. State, and		
Local permits have been obtained.			
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.			
16. Backflow Preventer/Check Valves are required of	on all buildings with basement plumbing.		
NOTE: Roof downspouts, foundation drains, area	a drains, and/or other sources of surface runoff or ground		
water to the public sewers are prohibited.			
FEE: \$ 10 CK# 45980	Property Owner		
the remaining	perpetit CB Willy		
Water Pollution Control Facility	Licensed Drainlayer		
Superintendent	· · · · · · · · · · · · · · · · · · ·		

White: WPCF Green: Tax Assessor Yellow: Town Council

Pink: Drainlayer Gold: Homeowner