

2781KD

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date: 3/10/23

Permit: 2781KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

44 Vinum Ave 24 53
NO. STREET PLAT LOT

ASSESSABLE ☐ YES ☐ NO ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$ 25 CK# _____

[Signature]
Water Pollution Control Facility
Superintendent

[Signature]
Property Owner
[Signature]
Licensed Drainlayer

White: WPCF Green: Tax Assessor Yellow: Town Council Pink: Drainlayer Gold: Homeowner

TOWN COUNCIL
MAR 29 2023
MEETING

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date:

1/31/23

Permit:

2780KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

39 Richmond St. 25 66
NO. STREET PLAT LOT

ASSESSABLE ____ YES ____ NO

ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$

100

CK#

cash

Property Owner

Licensed Drainlayer

Water Pollution Control Facility
Superintendent

2726 KD

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

I+I

Date: 4/9/21

Permit: 2726KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

2 Elm Farm Dr 89 74
NO. STREET PLAT LOT

ASSESSABLE ☐ YES ☐ NO

ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$ 25

CK# 4110

Legacy Investments
Property Owner

[Signature]
Water Pollution Control Facility
Superintendent

JML
Licensed Drainlayer

2742KD

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date: 7/23/21

Permit: 2742KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

<u>1</u>	<u>Cortland Ln</u>	<u>133</u>	<u>134</u>
NO.	STREET	PLAT	LOT

ASSESSABLE ☐ YES ☐ NO

ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$ 257 CK# 4954

[Signature]
Water Pollution Control Facility
Superintendent

Barry
Property Owner
JmC
Licensed Drainlayer

1-11
paid

2767KD

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date: 8/12/22

Permit: 2767KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

105 Kickmunt 133 133
NO. STREET PLAT LOT

ASSESSABLE YES NO ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$ 25.00 CK# 4342

[Signature]
Water Pollution Control Facility
Superintendent Secretary

Caromite
Property Owner
JHIC
Licensed Drainlayer

141 paid

2765 KD

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date: 8/12/22

Permit: 2765 KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

133 Sunrise 151 244
NO. STREET PLAT LOT

ASSESSABLE ☐ YES ☐ NO ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$ 2500 CK# 4342

Jim Delia
Water Pollution Control Facility
Superintendent Secretary

Skilling
Property Owner
JML
Licensed Drainlayer

White: WPCF

Green: Tax Assessor Yellow: Town Council

Pink: Drainlayer

Gold: Homeowner

141 paid

2766 KD

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date: 8/12/02

Permit: 2766KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

43 Platt St. 148 1
NO. STREET PLAT LOT

ASSESSABLE ☐ YES ☐ NO ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$ 25.00 CK# 4312

[Signature]
Water Pollution Control Facility
Superintendent Secretary

Morra
Property Owner

JML
Licensed Drainlayer

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date: 5/26/22Permit: 2759 KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

13 Low h 166 5
NO. STREET PLAT LOT

ASSESSABLE ☐ YES ☐ NO

ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$ 10 CK# _____

[Signature]
Water Pollution Control Facility
Superintendent

Malcolm Trust
Property Owner

ELJ
Licensed Drainlayer

1-1
paid
7/26/22

2773 KD

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date: 11/18/22

Permit: 2773 KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

509 Metacom Ave 108 7
NO. STREET PLAT LOT

ASSESSABLE ☐ YES ☐ NO ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$ 25 CK# 385

[Signature]
Water Pollution Control Facility
Superintendent

Guerreiro
Property Owner
UU-44260
Licensed Drainlayer

Repair

2778 KD

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date:

12/15/22

Permit:

2778 KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

5 Thames St. 11 8
NO. STREET PLAT LOT

ASSESSABLE YES NO

ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$

10+

CK#

cash

Water Pollution Control Facility
Superintendent

Property Owner

Licensed Drainlayer

White: WPCF

Green: Tax Assessor Yellow: Town Council

Pink: Drainlayer

Gold: Homeowner

1st 1st
new connection

2777 KD

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date: 12-6-22

Permit: 2777 KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

25 Patricia Ave Dr 55 108
NO. STREET PLAT LOT

ASSESSABLE ☐ YES ☐ NO ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$ 2500 CK# 4378

Water Pollution Control Facility
Superintendent

Gaul
Property Owner
JML
Licensed Drainlayer

Repair

2774 KD

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date: 11/18/22 Permit: 2774KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

43 Sherry Ave 36 9
NO. STREET PLAT LOT

ASSESSABLE YES NO ACCOUNT NO:

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$ 10- CK# CASH

L. K...
Water Pollution Control Facility
Superintendent

Corey
Property Owner
FLJ
Licensed Drainlayer

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date:

3-23-23

Permit:

2783KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

10 Gladding

NO.	STREET	PLAT	LOT

ASSESSABLE ☐ YES ☐ NO

ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$

10

CK#

cash

Property Owner

Scott's

Water Pollution Control Facility
Superintendent

Licensed Drainlayer