

2725KD

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date: 3-23-21

Permit: 2725KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

117 Beck Ave. 61 18
NO. STREET PLAT LOT

ASSESSABLE ☐ YES ☐ NO ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

2022 OCT -5 AM 11:29

TOWN CLERK'S OFFICE
BRISTOL, RHODE ISLAND

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$ 107

CK# 71062

Statewide prop.
Property Owner

East Coast
Licensed Drainlayer

[Signature]
Water Pollution Control Facility
Superintendent

White: WPCF

Green: Tax Assessor Yellow: Town Council

Pink: Drainlayer

Gold: Homeowner

TOWN COUNCIL

OCT 12 2022

MEETING

2740KD

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date: 7/20/01

Permit: 2740KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

125 Tupelo St. - extension of main line

NO. STREET PLAT LOT

ASSESSABLE YES NO ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$ 50

CK# 3450

[Signature]
Water Pollution Control Facility
Superintendent

[Signature]
Property Owner

[Signature]
Licensed Drainlayer

White: WPCF

Green: Tax Assessor Yellow: Town Council

Pink: Drainlayer

Gold: Homeowner

TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT

Date: 4/13/22Permit: 2757KI

The undersigned licensed Drainlayer requests permission to install a sewer line at:

NO. 57 STREET Garfield AvePLAT 26LOT 113ASSESSABLE ☐ YES ☐ NO

ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$ 25CK# CC

[Signature]
 Water Pollution Control Facility
 Superintendent

[Signature]
 Property Owner

[Signature]
 Licensed Drainlayer

2743 K

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date: 8/31/21

Permit: 2743KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

13 Low Ln 166 5
NO. STREET PLAT LOT

ASSESSABLE ☐ YES ☐ NO

ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$ 10

CK# 1243

Malverne Trust
Property Owner

[Signature]
Water Pollution Control Facility
Superintendent

[Signature]
Licensed Drainlayer

2744 KD

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date: 9-13-21

Permit: 2744KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

24 Primrose 154 715
NO. STREET PLAT LOT

ASSESSABLE ☐ YES ☐ NO ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$ 10

CK# 6399

[Signature]
Water Pollution Control Facility
Superintendent

[Signature]
Property Owner

[Signature]
Licensed Drainlayer

2745 K1

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date:

9/23/21

Permit:

2745KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

23 Robin Dr.

159

858

NO. STREET

PLAT

LOT

ASSESSABLE ____ YES ____ NO

ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$

10

CK#

per 116 Wood
Canceled

Property Owner

Reynolds

Licensed Drainlayer

Water Pollution Control Facility
Superintendent

L. Ramo

White: WPCF

Green: Tax Assessor Yellow: Town Council

Pink: Drainlayer

Gold: Homeowner

2746 KD

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date:

10/18/21

Permit:

2746 KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

NO.

STREET

PLAT

LOT

656 Hope St.

13

18

ASSESSABLE ____ YES ____ NO

ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$

105

CK#

cash

Property Owner

Lavelle

Water Pollution Control Facility
Superintendent

L. Ramos
Licensed Drainlayer

White: WPCF

Green: Tax Assessor Yellow: Town Council

Pink: Drainlayer

Gold: Homeowner

2747 KD

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date: 10/28/21

Permit: 2747KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

27 Colonial Rd 61 52
NO. STREET PLAT LOT

ASSESSABLE ☐ YES ☐ NO

ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$ 107 CK# ✓

O'Hanley
Property Owner

L. DelZim
Water Pollution Control Facility
Superintendent

L. Ramos
Licensed Drainlayer

White: WPCF

Green: Tax Assessor Yellow: Town Council

Pink: Drainlayer

Gold: Homeowner

2748KD

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date: 12/7/21

Permit: 2748KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

1238 Hope St. 100 59
NO. STREET PLAT LOT

ASSESSABLE ☐ YES ☐ NO

ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$ 25 CK# _____

Josephus/Klein
Property Owner

[Signature]
Water Pollution Control Facility
Superintendent

JML
Licensed Drainlayer

White: WPCF

Green: Tax Assessor Yellow: Town Council

Pink: Drainlayer

Gold: Homeowner

2749 KD

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date: 12/7/21

Permit: 2749KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

92 Kickemuit 133 109
NO. STREET PLAT LOT

ASSESSABLE ☐ YES ☐ NO

ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$ 25 CK# _____

Wood Frame Structures
Property Owner

[Signature]
Water Pollution Control Facility
Superintendent

[Signature]
Licensed Drainlayer

White: WPCF

Green: Tax Assessor Yellow: Town Council

Pink: Drainlayer

Gold: Homeowner

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date:

12/9/21

Permit:

2751KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

32 Brookwood

79

501

NO. STREET

PLAT

LOT

ASSESSABLE ☐ YES ☐ NO

ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$

10

CK#

6464

Property Owner

[Signature]

Licensed Drainlayer

ELJ

Water Pollution Control Facility
Superintendent

TOWN OF BRISTOL, RI APPLICATION FOR SEWER PERMIT

Date: 1-6-20Permit: 2752KX

The undersigned licensed Drainlayer requests permission to install a sewer line at:

NO. 1051 Hope StPLAT 82LOT 6ASSESSABLE ☐ YES ☐ NO

ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$ 10CK# cash_____
Property OwnerScotts
Licensed DrainlayerLetellier
Water Pollution Control Facility
Superintendent

TOWN OF BRISTOL, RI APPLICATION FOR SEWER PERMIT

Date: 3-22-22Permit: 2753KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

<u>10 Center St.</u>	<u>33</u>	<u>138</u>
NO. STREET	PLAT	LOT

ASSESSABLE ☐ YES ☐ NO

ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$ 25CK# 4268Reliable Pest Control

Property Owner

JML

Licensed Drainlayer

[Signature]
 Water Pollution Control Facility
 Superintendent

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date: 3-28-22Permit: 2754 KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

125/27 Franklin St. 17 18
 NO. STREET PLAT LOT

ASSESSABLE ☐ YES ☐ NO

ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$ 10- CK# 2367

V+J Properties
 Property Owner

 Water Pollution Control Facility
 Superintendent

Anawan GC
 Licensed Drainlayer

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date: 3/29/22Permit: 2755KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

217 State St. 24 9
 NO. STREET PLAT LOT

ASSESSABLE ☐ YES ☐ NO

ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$ 10

CK# _____

[Signature]
 Water Pollution Control Facility
 Superintendent

217 State LLC
 Property Owner

NCD Developers
 Licensed Drainlayer

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date: 6/17/22Permit: 2760KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

8 Anthony Ave 40 17
 NO. STREET PLAT LOT

ASSESSABLE ☐ YES ☐ NO

ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$ 107CK# cash
Simpson
 Property Owner

ELJ
 Licensed Drainlayer

Jim DeLuca
 Water Pollution Control Facility
 Superintendent

Repair
clay to pvc

2761 KD

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date: 7/6/2022

Permit: 2761 KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

133 Ferry Rd 165 5
NO. STREET PLAT LOT

ASSESSABLE ☐ YES ☐ NO

ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$ 105 CK# paid

[Signature]
Water Pollution Control Facility
Superintendent

Andersen
Property Owner
ELJ
Licensed Drainlayer

Repair

2762KD

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date: 7/11/22

Permit: 2762KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

32 Ridge Rd 70 55
NO. STREET PLAT LOT

ASSESSABLE ☐ YES ☐ NO

ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$ 105

CK# pad

L. Del Zin
Water Pollution Control Facility
Superintendent

Skuba
Property Owner

Pol. Drain Serv.
Licensed Drainlayer

White: WPCF

Green: Tax Assessor Yellow: Town Council

Pink: Drainlayer

Gold: Homeowner

Repair

2763 KD

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date: 7/10/22

Permit: 2763KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

400 Franklin St. 46 12
NO. STREET PLAT LOT

ASSESSABLE ☐ YES ☐ NO

ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$ 10.00

CK# paid

[Signature]
Water Pollution Control Facility
Superintendent

Victory Realty, LLC
Property Owner

L. Ramos
Licensed Drainlayer

White: WPCF

Green: Tax Assessor Yellow: Town Council

Pink: Drainlayer

Gold: Homeowner

Repair

2764 Kd

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date: 8-9-2022

Permit: 2764 Kd

The undersigned licensed Drainlayer requests permission to install a sewer line at:

48 Union St. 15 42
NO. STREET PLAT LOT

ASSESSABLE YES NO ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$ 10- CK# cash

[Signature]
Water Pollution Control Facility
Superintendent

[Signature]
Property Owner
James Tavares - Contractor
Licensed Drainlayer

**TOWN OF BRISTOL, RI
APPLICATION FOR SEWER PERMIT**

Date: 8/18/22

Permit: 2769KD

The undersigned licensed Drainlayer requests permission to install a sewer line at:

16 Kingswood 79 364
NO. STREET PLAT LOT

ASSESSABLE ☐ YES ☐ NO

ACCOUNT NO: _____

GENERAL RULES FOR INSTALLING SEWER LINES:

1. Pipes from public sewer to property line shall be 6" in diameter.
2. Pipes from property line to building shall be 4" in diameter.
3. Junctions with public sewers shall be made at an angle by installing a wye or a tee.
4. Clean outs are required outside the foundation plus at 75' increments; at all significant changes in direction; and at all 45 degree or greater angles.
5. Pipes shall be imbedded in 6" of sand, processed gravel, or stone no greater than 3/4". Existing gravel is not acceptable.
6. Pipes shall be laid at a minimum of 3' below grade.
7. Inspection manholes shall be installed outside of commercial buildings for purposes of Pretreatment sampling.
8. Plumbing Permit from building Inspector is required for all interior connections.
9. Roadcut Permit from Department of Public Works is required for all roadcuts.
10. All Permits must be on job site.
11. Sewer Permit is good for 4 weeks.
12. Dig Safe must be notified by Drainlayer.
13. **NO INSPECTIONS WILL BE MADE AFTER 3:00PM WEEKDAYS OR ANYTIME WEEKENDS OR HOLIDAYS.**
14. It is the responsibility of the property owner and/or drainlayer to ensure that all Federal, State, and Local permits have been obtained.
15. Easements, Deeds, and all legal documents are the responsibility of the applicant and/or property owner.
16. Backflow Preventer/Check Valves are required on all buildings with basement plumbing.

NOTE: Roof downspouts, foundation drains, area drains, and/or other sources of surface runoff or ground water to the public sewers are prohibited.

FEE: \$ 25 CK# _____

Tom Dulin
Water Pollution Control Facility
Superintendent Secretary

Fairpoint Realty
Property Owner

JML
Licensed Drainlayer