DESIGN REVIEW CHECKLIST

DR23-03 Camas Meadows Hole 9 Mixed Use Development

The purpose of this sheet is to provide a simplified and expedited review of the design review principles and guidelines using objective review standards. The standards are intended as a tool for the decision-maker in making findings that the proposal either achieves compliance with the intent of the principles or reasonably mitigates any conflict. When reviewing the check sheet, the proposal should as a whole "comply" with the standards and thus be generally consistent with the overriding principles. [Yes = In Compliance; No = Not In Compliance; NA = Not Applicable]

Standard Principles and Guidelines

ARCH	ARCHITECTURE				
Yes	No	NA	Principles and Guidelines	Comments	
			Corrugated materials, standing seam, T-1 11, or similar siding		
			materials are avoided unless it produces a high visual (or		
			aesthetic) quality.		
			Buildings walls or fences visible from roadways are articulated		
			in order to avoid a blank look.		
			The use of bold colors has been avoided unless used as minor		
			accents.		
			Higher density/larger structures abutting lower density		
			residential structures have been designed to mitigate size and		
			scale differences.		
LAND	SCAPI	NG AI	ND SCREENING		
Yes	No	NA	Principles and Guidelines	Comments	
			Vegetation for landscaping includes native, low maintenance		
			plantings. Significant trees are retained if feasible.		
			Trees planted along streetscapes with overhead power lines		
			include only those trees identified on the City's Tree list.		
			Landscaping, including trees, shrubs, and vegetative		
			groundcover, is provided to visually screen and buffer the use		
			from adjoining less intense uses including parking.		
			Proposed fencing is incorporated into the landscaping so as to		
			have little or no visual impact.		
			Signs located on buildings or incorporated into the landscaping		

			are unobtrusive and vandal resistant. If illuminated they are		
			front lit.		
			Landscape lighting - low voltage, non-glare, indirect lighting is		
			directed, hooded or shielded away from neighboring		
			properties.		
			Street lighting (poles, lamps) is substantially similar or		
			architecturally more significant than other street lighting		
			existing on the same street and do not conflict with any City		
			approved street lighting plans for the street.		
			Parking and building lighting is directed away from		
			surrounding properties through the use of hooding, shielding,		
			siting and/or landscaping.		
			Outdoor furniture samples are consistent with the overall		
			project design.		
			Existing trees over 6" dbh that are not required to be removed		
			to accommodate the proposed development are retained and		
			incorporated into the landscape plan.		
			Rock outcropping's, forested areas and water bodies are		
			retained.		
HISTO	HISTORIC AND HERITAGE PRESERVATION				
Yes	No	NA	Principles and Guidelines	Comments	
			The use of Historic Markers, information kiosks, project		
			names, architectural features, or other elements of the project		
			promote the historic heritage of the site or surrounding area.		

Specific Principles and Guidelines

			GATEWAYS AND CORRIDORS		
SIGN	SIGNAGE				
Yes	No	NA	Principles and Guidelines	Comments	
			Gateways are devoid of free-standing signs. Preexisting freestanding signs are proposed for removal at the time of development, redevelopment, or major rehabilitation on the site.		
			Permanent signage within a gateway are standardized to create a consistent look in terms of size, color, and materials.		

STREE	STREETSCAPE					
Yes	No	NA	Principles and Guidelines	Comments		
			The main public entrance is oriented toward the public right-of-			
			way.			
			Pedestrian walkways connect each building's front entry with			
			the sidewalk.			
			Bike lanes are provided and link public areas with			
			neighborhoods and other local and regional bicycle corridors.			
			Alternative transportation, such as attractive bus stop shelters,			
			bicycle parking, etc. are provided.			
			Trees, planting strips or bioswales are used for separating			
			vehicles and pedestrian movements.			
			Street trees no less than two inches in diameter are planted			
			within planter strips or tree wells at a spacing that creates the			
			appearance of a continuous canopy at tree maturation.			
			The surface of pedestrian walkways within intersections are			
			accentuated with a unique character (i.e. pattern stone,			
			exposed aggregate, stamped concrete, etc.)			
			Buildings are placed as close to streets and roads as the zoning			
			code allows.			
			On-site parking is located to the rear or the side of the building.			
			A consistent iconic streetscape lighting scheme is used that			
			portrays the primary development period, architecture			
			characteristics, or predetermined theme as identified in a			
			concept plan, sub-area plan, or master plan recognized by the			
			City.			
LAND						
Yes	No	NA	Principles and Guidelines	Comments		
			Landscaping adjacent to the public right of way provides			
			multiple layers of plantings, including canopy trees, understory			
			trees, shrubs and groundcover.			
			Hanging baskets provided along building frontages add visual			
			interest and the bottom of the basket is a minimum of 80 inches			
			above the finished grade of the sidewalk.			
			Median planting design/plant selection create a unique and			
			cohesive streetscape design.			

	COMMERCIAL				
ARCHITE	ARCHITECTURE				
Yes N	lo	NA	Principles and Guidelines	Comments	
			Office and retail buildings provide a minimum solid to void ratio of 60%/40%		
			The development is built with a residential feel (i.e. size, scale,		
			and materials compatible with neighboring buildings) if		
			surrounded by residential areas or adjacent to residentially		
			zone properties.		
			Buildings over two stories have the third story and above offset		
			from the first two stories, if surrounding developments are less		
			than three stories or land use designations on adjacent sites do		
			not allow more than three story development.		
1		NG & S	SCREENING		
Yes N	No	NA	Principles and Guidelines	Comments	
			Intersections are illuminated, but not dominated by lighting.		
			Lighting is incorporated into the landscape and illuminates the		
			quality of the natural environment. Street light poles and lamps		
			are compatible with other nearby lighting on the same street.		
			Parking spaces are clustered in small groupings and separated		
			by landscaping to create a pedestrian friendly, park like		
CEREETO			environment.		
STREETS			Provide and California	Community	
Yes N	No.	NA	Principles and Guidelines	Comments	
			On-site parking areas are located to the interior of the		
			development unless site development proved prohibitive.		
			Otherwise, parking areas are screened with landscaping.		
			Buildings are placed close to streets and roads unless site constraints made it impossible or characteristics of the		
			surrounding properties already developed made it		
			incompatible. Otherwise, retail frontage setbacks do not		
			exceed 25 feet from back of curb.		
	+		Window and door placement provides a high degree of		
			transparency at the lower levels of the building and maximize		
			visibility of pedestrian active uses.		
			Each use/activity in a development containing multiple		
			uses/activities is integrated in a manner that achieves a		

	1	1	<u> </u>	
			seamless appearance or creates a cohesive development.	
			New streets intersecting commercial properties are designed to	
			create a safe environment. "Coving" techniques and "round-a-	
			bouts" were considered for traffic calming when appropriate.	
			MULTI-FAMI	LY
Yes	No	NA	Principles and Guidelines	Comments
2	. TO	WNHC	DMES AND ROWHOUSES	
			All on-site parking areas (excluding driveways & garages) are	
			screened with landscaping.	
			Buildings are brought up to the road to help define	
			traffic/pedestrian movements.	
			Structures abutting or located in single family residentially	
			zoned areas are designed to mitigate size and scale differences	
			when appropriate.	
			Walls are articulated in order to avoid a blank look and provide	
			a sense of scale including a minimum solid to void ratio of	
			70%/30%.	
			Detachable garages are located to the rear of the townhouse or	
			rowhouse unit(s) so as not to be directly viewable from a public	
			street.	
			Attached garages account for less than 50% of the front face of	
			the structure. Garages visible from the street are articulated by	
			architectural features, such as windows, to avoid a blanklook.	
			Green belts are used to separate different uses whenever	
			possible.	
			Vertical intensity of landscaping increases as the height of the	
			structure increases.	
	•			