

Exhibit D: Price Schedule

Price quote for: **SINGLE AXLE CAB & CHASSIS**

Vendor Name: **Boyer Trucks**
 Contact Person: **Bill Fischer / Brian Sutlief**
 Street Address: **4631 Odessa Ave NE**
 P.O. Box:
 City, State, Zip: **St. Michael, MN 55376**
 Phone #: **Bill (612) 676-3806 / Brian (612) 676-3804**
 Toll Free #:
 Fax #:
 Email Address: **bfischer@boyertrucks.com / bsutlief@boyertrucks.com**

Version of Excel used:

2010

Spec #	Information Requested	Answer
1.0	Make & Model	WESTERN STAR 47X
	C.A. & W.B. dimension	80" CA & 161" WB
	Front Axle Location (Set Forward, Set Back)	Set Forward
	Frame, Steel PSI	120,000 PSI
	Frame, Section Modulus	14.94 SM
	Frame, Resistance to Bending Moment	1,792,426 RBM
	Frame overhang length	34"
	Type of fasteners used on frame members	Huck-Spin, Round Collar
	Front bumper description	Painted Steel
	Front Axle Type & Size	Single Front Axle
	Front Spring length	56"
	Front brake size	15 x 4
	Front Brake chamber size	20 sq/in
	U Joint Make, Model & Type (1/2 round, etc.)	Meritor MXL 176T, Half Round
	Rear Axle Type & Size	Single Rear Axle
	Rear brake size	16.5 x 7
	Rear brake chamber size	30/30 sq/in
	Parking Brake Type & Model #	Spring, WABCO TRISTOP Longstroke

Front Tire Make & Size	Hankook 11R22.5 14-ply
Front Rim Size & Rating	22.5 x 8.25 7,400#
Rear tire make & size	Hankook 11R22.5 14-ply
Rear rim size & rating	22.5 x 8.25 7,400#
Air compressor type & size	Cummins 18.7 CFM
Air dryer info	Wabco System Saver HP
Engine type, HP & torque	Cummins L9, 260 HP & 860 LB/FT Torque
Type of engine fan drive	Air Powered On/Off
Exhaust description	Horizontal Aftertreatment System
Starter motor Make & Model	Delco 12V 39MT HD/OCP
Right side steering assist (Auxiliary gear,	None
Transmission Make & Model, # of Speeds	Eaton Fuller FRO-14210C, 10-speed
Clutch size and # of plates	14", 2 Plate
Battery CCA, # of batteries, CCA of each battery	2000 CCA, 2 Batteries, 1000 CCA each
Fuel tank size, shape and material	60 Gallon, Round, Aluminum
Alternator Type & Size	LN 12V, 170-Amp Pad Mount
Radiator Sq in & Material	1400 Square Inch, Aluminum
Type and number of horns	Electric, 1
Cab ride (type of mounting)	Air
Cab size door to door, floor to ceiling	76", 57"
Distance of cab floor to ground	52"
Description of seats supplied with base cab &	Seat, No Passenger Seat
Windshield washer nozzle location	Wiper Arm
Interior package (Low, Med or Premium)	Medium
Does unit include cruise control	Yes

How is dome light activated	LH, RH, and Dash Switch
Steering wheel adjustment (tilt, telescoping, etc.)	Adjustable Tilt and Telescoping
Cab grab handle locations	Interior LH/RH & Lower LH/RH A Pillar
Storage pocket description	Console
Cab Gauges, List	Voltage, Fuel Level, DEF Level, Coolant
Dimmer switch location	Turn Signal Lever
Paint description	Base Coat/Clear Coat, White
Cab & chassis warranty (time & mileage)	1 YEAR / UNLIMITED
Engine warranty (time & mileage)	2 YEAR / 250,000 MILES
Transmission warranty (time & mileage)	3 YEAR / UNLIMITED
Rear end warranty (time & mileage)	2 YEAR / 100,000 MILES
Delivery of chassis starting point	Michael, MN - Sioux Falls, SD - Superior,
Estimated weight on front axle of base unit	7,137 lbs.
Estimated weight on rear axle of base unit	4,386 lbs.