

Proposal for **Columbia Heights Fire Department**

Prepared by **MacQueen Emergency Group**

11/10/2020



PERFORM. LIKE NO OTHER.™

CONTENTS

GENERAL DESIGN AND CONSTRUCTION 15

QUALITY AND WORKMANSHIP 15

DELIVERY 16

MANUAL AND SERVICE INFORMATION 16

SAFETY VIDEO 16

PERFORMANCE TESTS..... 16

SERVICE AND WARRANTY SUPPORT 16

LIABILITY 17

INSURANCE PROVIDED BY BIDDER 17

COMMERCIAL GENERAL LIABILITY INSURANCE 17

COMMERCIAL AUTOMOBILE LIABILITY INSURANCE..... 18

UMBRELLA/EXCESS LIABILITY INSURANCE 18

INSURANCE PROVIDED BY MANUFACTURER 18

PRODUCT LIABILITY INSURANCE 18

UMBRELLA/EXCESS LIABILITY INSURANCE 19

SINGLE SOURCE MANUFACTURER..... 19

NFPA 2016 STANDARDS 19

NFPA COMPLIANCY 20

VEHICLE INSPECTION PROGRAM CERTIFICATION..... 20

PUMP TEST 20

GENERATOR TEST 20

BREATHING AIR TEST 20

BID BOND NOT REQUESTED..... 20

PERFORMANCE BOND NOT REQUESTED 21

APPROVAL DRAWING 21

ELECTRICAL WIRING DIAGRAMS 22

IMPEL CHASSIS..... 22

WHEELBASE 22

GVW RATING 22

FRAME 22

FRONT NON DRIVE AXLE 22

FRONT SUSPENSION 23

Columbia Heights Bid 941 Full Specification

FRONT SHOCK ABSORBERS 23

FRONT OIL SEALS 23

FRONT TIRES 23

REAR AXLE 23

TOP SPEED OF VEHICLE 23

REAR SUSPENSION..... 24

REAR OIL SEALS..... 24

REAR TIRES..... 24

TIRE BALANCE 24

TIRE PRESSURE MANAGEMENT 24

FRONT HUB COVERS..... 24

CHROME LUG NUT COVERS..... 24

MUD FLAPS..... 24

WHEEL CHOCKS 25

 Wheel Chock Brackets 25

ANTI-LOCK BRAKE SYSTEM..... 25

BRAKES 25

BRAKE SYSTEM AIR COMPRESSOR..... 25

BRAKE SYSTEM 25

BRAKE SYSTEM AIR DRYER 26

BRAKE LINES..... 26

AIR INLET 26

ENGINE..... 26

HIGH IDLE..... 27

ENGINE BRAKE 27

CLUTCH FAN..... 27

ENGINE AIR INTAKE 27

EXHAUST SYSTEM 27

RADIATOR..... 28

COOLANT LINES..... 28

FUEL TANK..... 28

DIESEL EXHAUST FLUID TANK..... 29

FUEL SHUTOFF 29

Columbia Heights Bid 941 Full Specification

TRANSMISSION..... 29

TRANSMISSION SHIFTER 29

TRANSMISSION COOLER 30

TRANSMISSION DIPSTICK CAP 30

DOWNSHIFT MODE (w/engine brake) 30

TRANSMISSION FLUID 30

DRIVELINE..... 30

STEERING 30

STEERING WHEEL 30

LOGO AND CUSTOMER DESIGNATION ON DASH 31

BUMPER 31

 Gravel Pan..... 31

CENTER HOSE TRAY..... 31

 Center Hose Tray Cover 32

LIFT AND TOW MOUNTS 32

TOW HOOKS 32

HINGED CENTER SECTION 32

CAB 32

INTERIOR CAB INSULATION..... 33

FENDER LINERS..... 33

PANORAMIC WINDSHIELD..... 33

WINDSHIELD WIPERS 34

FAST SERVICE ACCESS FRONT TILT HOOD 34

ENGINE TUNNEL 34

CAB REAR WALL EXTERIOR COVERING..... 34

CAB LIFT 34

 Cab Lift Interlock..... 35

GRILLE 35

DOOR JAMB SCUFFPLATES..... 35

FRONT CAB TRIM..... 35

SIDE OF CAB MOLDING..... 35

MIRRORS..... 35

CAB DOORS..... 36

Columbia Heights Bid 941 Full Specification

Door Panels..... 36

RECESSED POCKET WITH ELASTIC COVER..... 36

ELECTRIC WINDOW CONTROLS 36

DUAL STEPS..... 37

CAB EXTERIOR HANDRAILS..... 37

STEP LIGHTS..... 37

FENDER CROWNS 37

CREW CAB WINDOWS..... 37

STORAGE COMPARTMENTS..... 37

 Compartment Light..... 38

CAB INTERIOR..... 38

CAB INTERIOR UPHOLSTERY 38

CAB INTERIOR PAINT 39

CAB FLOOR..... 39

DEFROST/AIR CONDITIONING SYSTEM 39

 Cab Defroster 39

 Cab/Crew Auxiliary Heater 39

 Air Conditioning 39

 Climate Control..... 40

 Gravity Drain Tubes..... 40

SUN VISORS 41

GRAB HANDLE..... 41

ENGINE COMPARTMENT LIGHTS..... 41

ACCESS TO ENGINE DIPSTICKS 41

CAB SAFETY SYSTEM..... 41

FRONTAL IMPACT PROTECTION..... 42

SIDE ROLL PROTECTION..... 42

SEATING CAPACITY 42

DRIVER SEAT 42

OFFICER SEAT 43

RADIO COMPARTMENT..... 43

REAR FACING DRIVER SIDE OUTBOARD SEAT 44

REAR FACING PASSENGER SIDE OUTBOARD SEAT 44

Columbia Heights Bid 941 Full Specification

FORWARD FACING LEFT SIDE CABINET..... 44
Cabinet Light 45
FORWARD FACING CENTER SEATS 45
FORWARD FACING RIGHT SIDE CABINET 45
 Cabinet Light..... 45
SEAT UPHOLSTERY 45
SEAT BELTS..... 45
SHOULDER HARNESS HEIGHT ADJUSTMENT 46
HELMET STORAGE PROVIDED BY FIRE DEPARTMENT 46
CAB DOME LIGHTS 46
PORTABLE HAND LIGHTS, PROVIDED BY FIRE DEPARTMENT 46
CAB INSTRUMENTATION 46
 Gauges 47
 Indicator Lamps 48
 Alarms..... 48
 Indicator Lamp and Alarm Prove-Out 49
 Control Switches..... 49
 Custom Switch Panels..... 50
 Diagnostic Panel..... 50
 Cab LCD Display 51
AIR RESTRICTION INDICATOR..... 51
"DO NOT MOVE APPARATUS" INDICATOR..... 51
DO NOT MOVE TRUCK MESSAGES..... 51
SWITCH PANELS..... 52
WIPER CONTROL 52
SPARE CIRCUIT..... 52
SPARE CIRCUIT..... 52
SPARE CIRCUIT..... 53
INFORMATION CENTER 53
 ADDITIONAL INFORMATION CENTER 53
 GENERAL SCREEN DESIGN 54
 HOME/TRANSIT SCREEN 54
 ON SCENE SCREEN..... 54

Columbia Heights Bid 941 Full Specification

VIRTUAL BUTTONS 55

PAGE SCREEN..... 55

COLLISION MITIGATION..... 57

VEHICLE DATA RECORDER 57

 Seat Belt Monitoring System..... 58

TWO-WAY RADIO CABLE INSTALLATION..... 58

TWO WAY RADIO SPEAKER INSTALLATION..... 58

TWO WAY RADIO INSTALLATION 58

RADIO ANTENNA MOUNT 58

VEHICLE CAMERA SYSTEM 58

ELECTRICAL POWER CONTROL SYSTEM 59

SOLID-STATE CONTROL SYSTEM..... 59

CIRCUIT PROTECTION AND CONTROL DIAGRAM 60

ON-BOARD ADVANCED/VISUAL ELECTRICAL SYSTEM DIAGNOSTICS..... 60

TECH MODULE WITH WIFI 61

PROGNOSTICS..... 61

 ADVANCED DIAGNOSTICS..... 61

INDICATOR LIGHT AND ALARM PROVE-OUT SYSTEM..... 62

VOLTAGE MONITOR SYSTEM 62

DEDICATED RADIO EQUIPMENT CONNECTION POINTS..... 62

ENHANCED SOFTWARE 62

EMI/RFI PROTECTION 62

ELECTRICAL 63

BATTERY SYSTEM..... 64

BATTERY SYSTEM..... 64

MASTER BATTERY SWITCH 64

BATTERY COMPARTMENTS..... 64

JUMPER STUDS 64

BATTERY CHARGER/ AIR COMPRESSOR..... 64

SHORELINE..... 65

GENERATOR TO SHORELINE TRANSFER SWITCH 65

ALTERNATOR 65

ELECTRONIC LOAD MANAGER..... 65

Columbia Heights Bid 941 Full Specification

SEQUENCER..... 66

HEADLIGHTS 67

DIRECTIONAL LIGHTS 67

INTERMEDIATE LIGHT 67

CAB CLEARANCE/MARKER/ID LIGHTS 67

REAR CLEARANCE/MARKER/ID LIGHTING 67

REAR FMVSS LIGHTING..... 68

LICENSE PLATE BRACKET 68

LIGHTING BEZEL..... 69

BACK-UP ALARM..... 69

CAB PERIMETER SCENE LIGHTS..... 69

PUMP HOUSE PERIMETER LIGHTS..... 69

BODY PERIMETER SCENE LIGHTS 69

STEP LIGHTS 69

LIGHT GUARD..... 69

12 VOLT LIGHTING 70

12 VOLT LIGHTING 70

12 VOLT LIGHTING 70

12 VOLT LIGHTING 70

12 VOLT LIGHTING 70

HOSE BED LIGHTS..... 71

REAR SCENE LIGHT(S) 71

WALKING SURFACE LIGHT 71

WATER TANK..... 71

SLEEVE, PLUMBING, THROUGH TANK 72

HOSE BED 72

HOSE BED DIVIDER 73

MONITOR STORAGE IN HOSEBED..... 73

HOSE BED COVER..... 73

HOSEBED END FLAP 73

RUNNING BOARDS 74

TAILBOARD 74

REAR WALL, SMOOTH ALUMINUM/BODY MATERIAL 74

Columbia Heights Bid 941 Full Specification

TOW BAR..... 74

RUNNING BOARD HOSE RESTRAINT 74

HOSE TRAY..... 74

COMPARTMENTATION..... 75

UNDERBODY SUPPORT SYSTEM..... 75

AGGRESSIVE WALKING SURFACE 76

LOUVERS 76

TESTING OF BODY DESIGN 76

LEFT SIDE COMPARTMENTATION 76

RIGHT SIDE COMPARTMENTATION..... 77

SIDE COMPARTMENT ROLLUP DOOR(S) 77

REAR COMPARTMENTATION..... 78

ROLLUP REAR COMPARTMENT DOOR 78

DOOR GUARD..... 79

COMPARTMENT LIGHTING..... 79

MOUNTING TRACKS..... 79

ADJUSTABLE SHELVES 79

SLIDE-OUT/TILT-DOWN TRAY FOR SCBA PACKS 79

SLIDE-OUT FLOOR MOUNTED TRAY 80

SLIDE-OUT TOOLBOARD 80

DRAWER ASSEMBLY 81

RUB RAIL..... 81

BODY FENDER CROWNS..... 82

BODY FENDER LINER..... 82

HARD SUCTION HOSE..... 82

HANDRAILS..... 82

HANDRAILS..... 82

HANDRAIL 82

EXTINGUISHER/AIR BOTTLE/ STORAGE (Triangular)..... 82

AIR BOTTLE COMPARTMENT STRAP 82

AIR BOTTLE STORAGE (Triple)..... 83

AIR BOTTLE COMPARTMENT STRAP 83

AIR BOTTLE HOLDERS..... 83

Columbia Heights Bid 941 Full Specification

EXTENSION LADDER..... 83

ROOF LADDER 83

HYDRAULIC LADDER RACK..... 83

LADDER RACK INTERLOCK AND NOT STOWED INDICATOR LIGHT 84

HYDRAULIC LADDER RACK DEPLOYED LIGHTS 84

FOLDING LADDER..... 84

HYDRAULIC LADDER RACK PUMP LOCATION 84

PIKE POLE PROVIDED BY FIRE DEPARTMENT 84

6' PIKE POLE PROVIDED BY FIRE DEPARTMENT 84

PIKE POLE STORAGE..... 85

FOLDING STEPS FRONT OF BODY 85

REAR FOLDING STEPS 85

PUMP 85

PUMP TRANSMISSION 86

PUMPING MODE..... 86

AIR PUMP SHIFT..... 86

TRANSMISSION LOCK-UP..... 87

AUXILIARY COOLING SYSTEM..... 87

INTAKE RELIEF VALVE 87

PRESSURE CONTROLLER..... 87

PRIMING PUMP..... 87

PUMP MANUALS..... 88

PLUMBING, STAINLESS STEEL AND HOSE..... 88

FOAM SYSTEM PLUMBING 88

MAIN PUMP INLETS 88

INLET VALVES WITH INTAKE RELIEF VALVE 88

SHORT SUCTION TUBE(S)..... 89

VALVES..... 89

LEFT SIDE INLET 89

ANODE, INLET 89

INLET CONTROL..... 89

INLET BLEEDER VALVE 89

TANK TO PUMP 90

Columbia Heights Bid 941 Full Specification

TANK REFILL..... 90

LEFT SIDE DISCHARGE OUTLETS..... 90

RIGHT SIDE DISCHARGE OUTLETS 90

LARGE DIAMETER DISCHARGE OUTLET 90

FRONT DISCHARGE OUTLET 90

REAR DISCHARGE OUTLET 90

FRONT OF HOSE BED DISCHARGE OUTLET 90

DISCHARGE CAPS/ INLET PLUGS 91

OUTLET BLEEDER VALVE 91

LEFT SIDE OUTLET ELBOWS 91

RIGHT SIDE OUTLET ELBOWS..... 91

REAR OUTLET ELBOWS 91

LARGE DIAMETER OUTLET ELBOWS 92

DISCHARGE OUTLET CONTROLS 92

DELUGE RISER..... 92

MONITOR..... 92

NOZZLE, DELUGE 92

SPEEDLAYS WITH ALUM TRAYS 92

SPEEDLAY HOSE RESTRAINT 93

HUSKY 3 FOAM PROPORTIONER..... 93

 System Capacity..... 93

 Control System 93

 Hydraulic Drive System 94

 Foam Concentrate Pump 94

 External Foam Concentrate Connection..... 94

 Panel Mounted External Pick-Up Connection / Valve 94

 Pick-Up Hose..... 95

 Discharges..... 95

 System Electrical Load..... 95

SINGLE FOAM TANK REFILL..... 95

FOAM TANK 95

FOAM TANK DRAIN..... 95

PUMP COMPARTMENT..... 95

Columbia Heights Bid 941 Full Specification

PUMP MOUNTING 96

LEFT SIDE PUMP CONTROL PANELS 96

IDENTIFICATION TAGS..... 96

PUMP OPERATOR'S PANEL DRAWING..... 97

COLOR CODED TAGS..... 97

SPECIAL TEXT/VERBIAGE TAGS 97

PUMP PANEL CONFIGURATION 97

PUMP AND GAUGE PANEL 97

PUMP COMPARTMENT LIGHT..... 97

THROTTLE READY GREEN INDICATOR LIGHT..... 98

OK TO PUMP INDICATOR LIGHT 98

ALUMINUM HEAT ENCLOSURE..... 98

ELECTRIC GAUGE HEATER..... 98

PUMP COMPARTMENT HEATER..... 98

RUBBER BOOT 98

VACUUM AND PRESSURE GAUGES 98

PRESSURE GAUGES 99

WATER LEVEL GAUGE 99

WATER LEVEL GAUGE 100

FOAM LEVEL GAUGE..... 100

LIGHT SHIELD..... 100

AIR HORN SYSTEM..... 101

 Air Horn Location..... 101

 Air Horn Control..... 101

ELECTRONIC SIREN..... 101

SIREN CONTROL..... 101

SPEAKER..... 101

AUXILIARY MECHANICAL SIREN 101

FRONT ZONE UPPER WARNING LIGHTS 102

CAB FACE WARNING LIGHTS..... 103

HEADLIGHT FLASHER 103

SIDE ZONE LOWER LIGHTING 103

REAR ZONE LOWER LIGHTING..... 103

Columbia Heights Bid 941 Full Specification

REAR/SIDE ZONE UPPER WARNING LIGHTS 104

TRAFFIC DIRECTING LIGHT 104

ELECTRICAL SYSTEM GENERAL DESIGN for ALTERNATING CURRENT 104

 General 104

 Grounding 104

 Operation 105

 Overcurrent protection 105

 Wiring Methods 106

 Wiring Identification 106

 Wet Locations 106

 Dry Locations 106

 Listing 107

 Electrical System Testing 107

 Operational Test per Current NFPA 1901 Standard 107

GENERATOR 107

GENERATOR LOCATION 108

GENERATOR START 108

GENERATOR REMOTE START 108

CIRCUIT BREAKER PANEL 108

ELECTRIC CORD REEL 108

CORD 108

PORTABLE JUNCTION BOX 108

JUNCTION BOX HOLDER 109

POWER OUTLET STRIP 109

POWER OUTLET STRIP 109

120 VOLT RECEPTACLE 109

LOOSE EQUIPMENT 110

NFPA REQUIRED LOOSE EQUIPMENT PROVIDED BY FIRE DEPARTMENT 110

SOFT SUCTION HOSE PROVIDED BY FIRE DEPARTMENT 111

DRY CHEMICAL EXTINGUISHER PROVIDED BY FIRE DEPARTMENT 111

WATER EXTINGUISHER PROVIDED BY FIRE DEPARTMENT 111

FLATHEAD AXE PROVIDED BY FIRE DEPARTMENT 111

PICKHEAD AXE PROVIDED BY FIRE DEPARTMENT 111

Columbia Heights Bid 941 Full Specification

PAINT - BODY PAINTED TO MATCH CAB..... 111

 PAINT - ENVIRONMENTAL IMPACT..... 113

PAINT CHASSIS FRAME ASSEMBLY 113

AXLE HUB PAINT 114

PAINT HYDRAULIC LADDER RACK 2-TONE 114

COMPARTMENT INTERIOR PAINT..... 114

REFLECTIVE STRIPES..... 114

REAR CHEVRON STRIPING 114

JOG IN REFLECTIVE STRIPE..... 114

CAB DOOR REFLECTIVE STRIPE 114

LETTERING 115

LETTERING 115

LETTERING 115

MALTESE CROSS INSTALLATION..... 115

E-COATING OF STEEL COMPONENTS 115

UNDERCOATING, CAB & BODY..... 115

FIRE APPARATUS PARTS MANUAL..... 116

 Service Parts Internet Site..... 116

CHASSIS SERVICE MANUALS..... 116

CHASSIS OPERATION MANUAL..... 117

ONE (1) YEAR MATERIAL AND WORKMANSHIP 117

THREE (3) YEAR MATERIAL AND WORKMANSHIP..... 117

ENGINE WARRANTY..... 117

STEERING GEAR WARRANTY..... 117

FIFTY (50) YEAR STRUCTURAL INTEGRITY 117

FRONT AXLE THREE (3) YEAR MATERIAL AND WORKMANSHIP WARRANTY..... 117

SINGLE REAR AXLE FIVE (5) YEAR MATERIAL AND WORKMANSHIP WARRANTY 117

ABS BRAKE SYSTEM THREE (3) YEAR MATERIAL AND WORKMANSHIP WARRANTY 117

TEN (10) YEAR STRUCTURAL INTEGRITY..... 118

TEN (10) YEAR PRO-RATED PAINT AND CORROSION 118

FIVE (5) YEAR MATERIAL AND WORKMANSHIP 118

CAMERA SYSTEM WARRANTY 118

COMPARTMENT LIGHT WARRANTY 118

Columbia Heights Bid 941 Full Specification

TRANSMISSION WARRANTY 118

TRANSMISSION COOLER WARRANTY 118

WATER TANK WARRANTY 118

TEN (10) YEAR STRUCTURAL INTEGRITY 118

ROLL UP DOOR MATERIAL AND WORKMANSHIP WARRANTY 118

PUMP WARRANTY 118

TEN (10) YEAR PUMP PLUMBING WARRANTY 119

FOAM SYSTEM WARRANTY 119

SIX (6) YEAR GENERATOR MATERIAL AND WORKMANSHIP WARRANTY 119

TEN (10) YEAR PRO-RATED PAINT AND CORROSION 119

THREE (3) YEAR MATERIAL AND WORKMANSHIP 119

VEHICLE STABILITY CERTIFICATION..... 119

ENGINE INSTALLATION CERTIFICATION..... 119

POWER STEERING CERTIFICATION 119

CAB INTEGRITY CERTIFICATION..... 119

 Roof Crush..... 119

 Additional Roof Crush..... 120

 Side Impact..... 120

 Frontal Impact..... 120

 Additional Frontal Impact..... 120

CAB DOOR DURABILITY CERTIFICATION..... 120

WINDSHIELD WIPER DURABILITY CERTIFICATION 120

ELECTRIC WINDOW DURABILITY CERTIFICATION 120

SEAT BELT ANCHOR STRENGTH 120

SEAT MOUNTING STRENGTH 121

PERFORMANCE CERTIFICATIONS 121

 Cab Air Conditioning..... 121

 Cab Defroster 121

 Cab Auxiliary Heater..... 121

AMP DRAW REPORT 121

Columbia Heights Bid 941 Full Specification

MacQueen Emergency is pleased to submit a proposal to Columbia Heights Fire Dept for a **Pierce® triple combination pumper** per your request for quotation. The following paragraphs will describe in detail the apparatus, construction methods, and equipment proposed. This proposal will indicate size, type, model and make of components parts and equipment, providing proof of compliance with each and every item (except where noted) in the departments advertised specifications.

PIERCE MANUFACTURING was founded in 1913. Since then we have been building bodies with one philosophy, "BUILD THE FINEST". Our skilled craftsmen take pride in their work, which is reflected, in the final product. We have been building fire apparatus since the early "forties" giving Pierce Manufacturing over 75 years of experience in the fire apparatus market. Pierce Manufacturing has built and put into service more than 62,500 apparatus, including more than 33,900 on Pierce custom chassis designed and built specifically for fire and emergency applications. Our Appleton, Wisconsin facility has over 870,000 total square feet of floor space situated on approximately 105 acres of land. Our Bradenton, Florida facility has 300,000 square feet of floor space situated on approximately 38 acres of land.

Our beliefs in high ethical standards are carried through in all of our commitments and to everyone with whom we do business. Honesty, Integrity, Accountability and Citizenship are global tenets by which we all live and work. Consequently, we neither engage in, nor have we ever been convicted of price fixing, bid rigging, or collusion in any domestic or international fire apparatus market.

Pierce has only one brand of fire apparatus "Pierce", ensuring you are receiving top of the line product that meets your specification.

In accordance with the current edition of NFPA 1901 standards, this proposal will specify whether the fire department, manufacturer, or apparatus dealership will provide required loose equipment.

Images and illustrative material in this proposal are as accurate as known at the time of publication, but are subject to change without notice. Images and illustrative material is for reference only, and may include optional equipment and accessories and may not include all standard equipment.

GENERAL DESIGN AND CONSTRUCTION

To control quality, ensure compatibility, and provide a single source for service and warranty, the custom cab, chassis, pump module and body will be entirely designed, assembled/welded and painted in Pierce owned manufacturing facilities. This includes, but not limited to the cab weldment, the pumphouse module assembly, the chassis assembly, the body and the electrical system.

QUALITY AND WORKMANSHIP

Pierce has set the pace for quality and workmanship in the fire apparatus field. Our tradition of building the highest quality units with craftsmen second to none has been the rule right from the beginning and we demonstrate that ongoing commitment by: Ensuring all steel welding follows American Welding Society D1.1-2004 recommendations for structural steel welding. All aluminum welding follows American Welding society and ANSI D1.2-2003 requirements for structural welding of aluminum. All sheet metal welding follows American welding Society B2.1-2000 requirements for structural welding of sheet metal. Our flux core arc welding uses alloy rods, type 7000 and is performed to American Welding Society standards A5.20-E70T1. Furthermore, all employees classified as welders are tested

and certified to meet the American welding Society codes upon hire and every three (3) years thereafter. Pierce also employs an American Welding Society certified welding inspector in plant during working hours to monitor weld quality.

Pierce Manufacturing operates a Quality Management System under the requirements of ISO 9001. These standards sponsored by the International Organization for Standardization (ISO) specify the quality systems that are established by the manufacturer for design, manufacture, installation and service. A copy of the certificate of compliance is included with this proposal.

In addition to the Quality Management system, we also employ a Quality Achievement Supplier program to insure the vendors and suppliers that we utilize meet the high standards we demand. That is just part of our overall "Quality at the Source" program at Pierce.

To demonstrate the quality of our products and services, a list of at least ten (10) fire departments/municipalities that have purchased vehicles for a second time is provided.

DELIVERY

The apparatus will be delivered under its own power to insure proper break-in of all components while the apparatus is still under warranty. A qualified delivery representative shall deliver the apparatus and remain for a sufficient length of time to instruct personnel in proper operation, care and maintenance of the equipment delivered.

MANUAL AND SERVICE INFORMATION

At time of delivery, complete operation and maintenance manuals covering the apparatus will be provided. A permanent plate will be mounted in the driver's compartment specifying the quantity and type of fluids required including engine oil, engine coolant, transmission, pump transmission lubrication, pump primer and drive axle.

SAFETY VIDEO

At the time of delivery Pierce will also provide one (1) 39-minute, professionally produced apparatus safety video, in DVD format. This video will address key safety considerations for personnel to follow when they are driving, operating, and maintaining the apparatus, including the following: vehicle pre-trip inspection, chassis operation, pump operation, aerial operation, and safety during maintenance.

PERFORMANCE TESTS

A road test will be conducted with the apparatus fully loaded and a continuous run of no less than ten (10) miles. During that time the apparatus will show no loss of power nor will it overheat. The transmission drive shaft or shafts and the axles will run quietly and be free of abnormal vibration or noise. The apparatus when fully loaded will not have less than 25 percent nor more than 50 percent on the front axle, and not less than 50 percent nor more than 75 percent on the rear axle. The apparatus will meet NFPA 1901 acceleration and braking requirements.

SERVICE AND WARRANTY SUPPORT

Pierce dealership support will be provided by MacQueen Emergency by operating a Pierce authorized service center. The service center will have factory-trained mechanics on staff versed in Pierce fire apparatus. The service facility will be located within twenty five (25) miles of the fire department.

Columbia Heights Bid 941 Full Specification

In addition to the dealership, Pierce has service facilities located in both, Weyauwega, Wisconsin and Bradenton, Florida. Pierce also maintains a dedicated parts facility of over 100,000 square feet in Appleton, Wisconsin. The parts facility stocks in excess of \$5,000,000 in parts dedicated to service and replacement parts. The parts facility employs a staff dedicated solely for the distribution and shipment of service and replacement parts.

Service parts for the apparatus being proposed can be found via Pierceparts.com which, is an interactive online tool that delivers information regarding your specific apparatus as well as the opportunity to register for training classes.

As a Pierce customer you have the ability to view the complete bill of materials for your specific apparatus, including assembly drawings, piece part drawings, and beneficial parts notations. You will also have the ability to search the complete Pierce item master through a parts search function which offers all Pierce SKU's and descriptions offered on all Pierce apparatus. Published component catalogs, which include proprietary systems along with an extensive operators manual library is available for easy reference.

Pierce Manufacturing maintains a dedicated service and warranty staff of over 35 personnel, dedicated to customer support, which also maintains a 24 hour 7 day a week toll free hot line, four (4) on staff EVTs, and offers hands-on repair and maintenance training classes multiple times a year.

LIABILITY

The successful bidder will defend any and all suits and assume all liability for the use of any patented process including any device or article forming a part of the apparatus or any appliance furnished under the contract.

INSURANCE PROVIDED BY BIDDER

COMMERCIAL GENERAL LIABILITY INSURANCE

The successful bidder will, during the performance of the contract and for three (3) years following acceptance of the product, keep in force at least the following minimum limits of commercial general liability insurance:

Each Occurrence\$1,000,000

Products/Completed Operations Aggregate\$1,000,000

Personal and Advertising Injury\$1,000,000

General Aggregate\$2,000,000

Coverage will be written on a Commercial General Liability form. The policy will be written on an occurrence form and will include Contractual Liability coverage for bodily injury and property damage subject to the terms and conditions of the policy. The policy will include Owner as an additional insured when required by written contract.

COMMERCIAL AUTOMOBILE LIABILITY INSURANCE

The successful bidder will, during the performance of the contract, keep in force at least the following minimum limits of commercial automobile liability insurance and coverage will be written on a Commercial Automobile liability form:

Each Accident Combined Single Limit:\$1,000,000

UMBRELLA/EXCESS LIABILITY INSURANCE

The successful bidder will, during the performance of the contract and for three (3) years following acceptance of the product, keep in force at least the following minimum limits of umbrella liability insurance:

Aggregate:\$3,000,000

Each Occurrence:\$3,000,000

The umbrella policy will be written on an occurrence basis and at a minimum provide excess to the bidder's General Liability and Automobile Liability policies.

The required limits can be provided by one (1) or more policies provided all other insurance requirements are met.

Coverage will be provided by a carrier(s) rated A- or better by A.M. Best.

All policies will provide a 30-day notice of cancellation to the named insured. The Certificate of Insurance will provide the following cancellation clause: Should any of the above described policies be cancelled before the expiration date thereof, notice will be delivered in accordance with the policy provisions.

Bidder agrees to furnish owner with a current Certificate of Insurance with the coverages listed above along with the bid. The certificate will show the purchaser as certificate holder.

INSURANCE PROVIDED BY MANUFACTURER

PRODUCT LIABILITY INSURANCE

The manufacturer will, during the performance of the contract and for three (3) years following acceptance of the product, keep in force at least the following minimum limits of Product Liability insurance:

Each Occurrence\$1,000,000

Products/Completed Operations Aggregate\$1,000,000

Coverage will be written on a Commercial General Liability form. The policy will be written on an occurrence form. The manufacturer's policy will include the owner as additional insured when required by written contract between the Owner and a Pierce authorized dealer.

UMBRELLA/EXCESS LIABILITY INSURANCE

The manufacturer will, during the performance of the contract and for three (3) years following acceptance of the product, keep in force at least the following minimum limits of umbrella liability insurance:

Each Occurrence:\$25,000,000

Aggregate:\$25,000,000

The umbrella policy will be written on an occurrence basis and provide excess to the manufacturer's General Liability/Products policies.

The required limits can be provided by one (1) or more policies provided all other insurance requirements are met.

Coverage will be provided by a carrier(s) rated A- or better by A.M. Best.

All policies will provide a 30-day notice of cancellation to the named insured. The Certificate of Insurance will provide the following cancellation clause: Should any of the above described policies be cancelled before the expiration date thereof, notice will be delivered in accordance with the policy provisions.

Manufacturer agrees to furnish owner with a current Certificate of Insurance with the coverages listed above along with the bid. The certificate will show the purchaser as the certificate holder.

SINGLE SOURCE MANUFACTURER

Pierce Manufacturing, Inc. provides an integrated approach to the design and manufacture of our products that delivers superior apparatus and a dedicated support team. From our facilities, the chassis, cab weldment, cab, pumphouse (including the sheet metal enclosure, valve controls, piping and operators panel) and body will be entirely designed, tested, and hand assembled to the customer's exact specifications. The electrical system either hardwired or multiplexed, will be both designed and integrated by Pierce Manufacturing. The warranties relative to these major components (excluding component warranties such as engine, transmission, axles, pump, etc.) will be provided by Pierce as a single source manufacturer. Pierce's single source solution adds value by providing a fully engineered product that offers durability, reliability, maintainability, performance, and a high level of quality.

Your apparatus will be manufactured in Appleton, Wisconsin.

NFPA 2016 STANDARDS

This unit will comply with the NFPA standards effective January 1, 2016, except for fire department directed exceptions. These exceptions will be set forth in the Statement of Exceptions.

Certification of slip resistance of all stepping, standing and walking surfaces will be supplied with delivery of the apparatus.

All horizontal surfaces designated as a standing or walking surface that are greater than 48.00" above the ground must be defined by a 1.00" wide line along its outside perimeter. Perimeter markings and designated access paths to destination points will be identified on the customer approval print and are

Columbia Heights Bid 941 Full Specification

shown as approximate. Actual location(s) will be determined based on materials used and actual conditions at final build. Access paths may pass through hose storage areas and opening or removal of covers or restraints may be required. Access paths may require the operation of devices and equipment such as the aerial device or ladder rack.

A plate that is highly visible to the driver while seated will be provided. This plate will show the overall height, length, and gross vehicle weight rating.

The manufacturer will have programs in place for training, proficiency testing and performance for any staff involved with certifications.

An official of the company will designate, in writing, who is qualified to witness and certify test results.

NFPA COMPLIANCY

Apparatus proposed by the bidder will meet the applicable requirements of the National Fire Protection Association (NFPA) as stated in current edition at time of contract execution. Fire department's specifications that differ from NFPA specifications will be indicated in the proposal as "non-NFPA".

VEHICLE INSPECTION PROGRAM CERTIFICATION

To assure the vehicle is built to current NFPA standards, the apparatus, in its entirety, will be third-party, audit-certified through Underwriters Laboratory (UL) that it is built and complies to all applicable standards in the current edition of NFPA 1901. The certification will include: all design, production, operational, and performance testing of not only the apparatus, but those components that are installed on the apparatus.

A placard will be affixed in the driver's side area stating the third party agency, the date, the standard and the certificate number of the whole vehicle audit.

PUMP TEST

Underwriters Laboratory (UL) will test, approve, and certify the pump. The test results and the pump manufacturer's certification of hydrostatic test; the engine manufacturer's certified brake horsepower curve; and the pump manufacturer's record of pump construction details will be forwarded to the Fire Department.

GENERATOR TEST

If the unit has a generator, Underwriters Laboratory (UL) will test, approve, and certify the generator. The test results will be provided to the Fire Department at the time of delivery.

BREATHING AIR TEST

If the unit has breathing air, Pierce Manufacturing will draw an air sample from the air system and have the sample certified that the air quality meets the requirements of NFPA 1989, *Standard on Breathing Air Quality for Fire and Emergency Services Respiratory Protection*.

BID BOND NOT REQUESTED

A bid bond will not be included. If requested, the following will apply:

All bidders will provide a bid bond as security for the bid in the form of a 5% bid bond to accompany their bid. This bid bond will be issued by a Surety Company who is listed on the U.S. Treasury

Columbia Heights Bid 941 Full Specification

Departments list of acceptable sureties as published in Department Circular 570. The bid bond will be issued by an authorized representative of the Surety Company and will be accompanied by a certified power of attorney dated on or before the date of bid. The bid bond will include language, which assures that the bidder/principal will give a bond or bonds as may be specified in the bidding or contract documents, with good and sufficient surety for the faithful performance of the contract, including the Basic One (1) Year Limited Warranty, and for the prompt payment of labor and material furnished in the prosecution of the contract.

Notwithstanding any document or assertion to the contrary, any surety bond related to the sale of a vehicle will apply only to the Basic One (1) Year Limited Warranty for such vehicle. Any surety bond related to the sale of a vehicle will not apply to any other warranties that are included within this bid (OEM or otherwise) or to the warranties (if any) of any third party of any part, component, attachment or accessory that is incorporated into or attached to the vehicle. In the event of any contradiction or inconsistency between this provision and any other document or assertion, this provision will prevail.

PERFORMANCE BOND NOT REQUESTED

A performance bond will not be included. If requested at a later date, one will be provided to you for an additional cost and the following will apply:

The successful bidder will furnish a Performance and Payment bond (Bond) equal to 100 percent of the total contract amount within 30 days of the notice of award. Such Bond will be in a form acceptable to the Owner and issued by a surety company included within the Department of Treasury's Listing of Approved Sureties (Department Circular 570) with a minimum A.M. Best Financial Strength Rating of A and Size Category of XV. In the event of a bond issued by a surety of a lesser Size Category, a minimum Financial Strength rating of A+ is required.

Bidder and Bidder's surety agree that the Bond issued hereunder, whether expressly stated or not, also includes the surety's guarantee of the vehicle manufacturer's Bumper to Bumper warranty period included within this proposal. Owner agrees that the penal amount of this bond will be simultaneously amended to 25 percent of the total contract amount upon satisfactory acceptance and delivery of the vehicle(s) included herein. Notwithstanding anything contained within this contract to the contrary, the surety's liability for any warranties of any type will not exceed three (3) years from the date of such satisfactory acceptance and delivery, or the actual Bumper to Bumper warranty period, whichever is shorter.

APPROVAL DRAWING

A drawing of the proposed apparatus will be prepared and provided to the purchaser for approval before construction begins. The Pierce sales representative will also be provided with a copy of the same drawing. The finalized and approved drawing will become part of the contract documents. This drawing will indicate the chassis make and model, location of the lights, siren, horns, compartments, major components, etc.

A "revised" approval drawing of the apparatus will be prepared and submitted by Pierce to the purchaser showing any changes made to the approval drawing.

ELECTRICAL WIRING DIAGRAMS

Two (2) electrical wiring diagrams, prepared for the model of chassis and body, will be provided.

IMPEL CHASSIS

The Pierce Impel® is the custom chassis developed exclusively for the fire service. Chassis provided will be a new, tilt type custom fire apparatus. The chassis will be manufactured in the apparatus body builder's facility eliminating any split responsibility. The chassis will be designed and manufactured for heavy duty service, with adequate strength, capacity for the intended load to be sustained, and the type of service required. The chassis will be the manufacturer's first line tilt cab.

WHEELBASE

The wheelbase of the vehicle will be 198.

GVW RATING

The gross vehicle weight rating will be 46,500.

FRAME

The chassis frame will be built with two (2) steel channels bolted to five (5) cross members or more, depending on other options of the apparatus. The side rails will have a 13.38" tall web over the front and mid sections of the chassis, with a continuous smooth taper to 10.75" over the rear axle. Each rail will have a section modulus of 25.992 cubic inches and a resisting bending moment (rbm) of 3,119,040 in-lb over the critical regions of the frame assembly, with a section modulus of 18.96 cubic inches with an rbm of 2,275,200 in-lb over the rear axle. The frame rails will be constructed of 120,000 psi yield strength heat-treated 0.38" thick steel with 3.50" wide flanges.

FRONT NON DRIVE AXLE

The Oshkosh TAK-4® front axle will be of the independent suspension design with a ground rating of 19,500 lb.

Upper and lower control arms will be used on each side of the axle. Upper control arm castings will be made of 100,000-psi yield strength 8630 steel and the lower control arm casting will be made of 55,000-psi yield ductile iron.

The center cross members and side plates will be constructed out of 80,000-psi yield strength steel.

Each control arm will be mounted to the center section using elastomer bushings. These rubber bushings will rotate on low friction plain bearings and be lubricated for life. Each bushing will also have a flange end to absorb longitudinal impact loads, reducing noise and vibrations.

There will be nine (9) grease fittings supplied, one (1) on each control arm pivot and one (1) on the steering gear extension.

The upper control arm will be shorter than the lower arm so that wheel end geometry provides positive camber when deflected below rated load and negative camber above rated load.

Camber at load will be 0 degrees for optimum tire life.

The ball joint bearing will be of low friction design and be maintenance free.

Columbia Heights Bid 941 Full Specification

Toe links that are adjustable for alignment of the wheel to the center of the chassis will be provided.

The wheel ends must have little to no bump steer when the chassis encounters a hole or obstacle.

The steering linkage will provide proper steering angles for the inside and outside wheel, based on the vehicle wheelbase.

The axle will have a third party certified turning angle of 45 degrees. Front discharge, front suction, or aluminum wheels will not infringe on this cramp angle.

FRONT SUSPENSION

Front Oshkosh TAK-4™ independent suspension will be provided with a minimum ground rating of 19,500 lb.

The independent suspension system will be designed to provide maximum ride comfort. The design will allow the vehicle to travel at highway speeds over improved road surfaces and at moderate speeds over rough terrain with minimal transfer of road shock and vibration to the vehicle's crew compartment.

Each wheel will have torsion bar type spring. In addition, each front wheel end will also have energy absorbing jounce bumpers to prevent bottoming of the suspension.

The suspension design will be such that there is at least 10.00" of total wheel travel and a minimum of 3.75" before suspension bottoms.

The torsion bar anchor lock system allows for simple lean adjustments, without the use of shims. One can adjust for a lean within 15 minutes per side. Anchor adjustment design is such that it allows for ride height adjustment on each side.

The independent suspension was put through a durability test that simulated 140,000 miles of inner city driving.

FRONT SHOCK ABSORBERS

KONI heavy-duty telescoping shock absorbers will be provided on the front suspension.

FRONT OIL SEALS

Oil seals with viewing window will be provided on the front axle.

FRONT TIRES

Front tires will be Goodyear® 315/80R22.50 radials, 20 ply G289 WHA tread, rated for 20,400 lb maximum axle load and 68 mph maximum speed.

The tires will be mounted on Alcoa 22.50" x 9.00" polished aluminum disc wheels with a ten (10) stud, 11.25" bolt circle.

REAR AXLE

The rear axle will be a Meritor™, Model RS-24-160, with a capacity of 24,000 lb.

TOP SPEED OF VEHICLE

A rear axle ratio will be furnished to allow the vehicle to reach a top speed of 68 mph.

REAR SUSPENSION

The rear suspension will be Standens, semi-elliptical, 3.00" wide x 53.00" long, 12-leaf pack with a ground rating of 24,000 lb. The spring hangers will be castings.

The two (2) top leaves will wrap the forward spring hanger pin, and the rear of the spring will be a slipper style end that will ride in a rear slipper hanger. To reduce bending stress due to acceleration and braking, the front eye will be a berlin eye that will place the front spring pin in the horizontal plane within the main leaf.

A steel encased rubber bushing will be used in the spring eye. The steel encased rubber bushing will be maintenance free and require no lubrication.

REAR OIL SEALS

Oil seals will be provided on the rear axle(s).

REAR TIRES

Rear tires will be four (4) Goodyear® 12R22.50 radials, 16 ply all season G622 RSD tread, rated for 27,120 lb maximum axle load and 75 mph maximum speed.

The tires will be mounted on Alcoa 22.50" x 8.25" polished aluminum disc wheels with a ten (10) stud 11.25" bolt circle.

TIRE BALANCE

All tires will be balanced with Counteract balancing beads. The beads will be inserted into the tire and eliminate the need for wheel weights.

TIRE PRESSURE MANAGEMENT

There will be a RealWheels LED AirSecure™ tire alert pressure management system provided, that will monitor each tire's pressure. A sensor will be provided on the valve stem of each tire for a total of six (6) tires.

The sensor will calibrate to the tire pressure when installed on the valve stem for pressures between 10 and 200 psi. The sensor will activate an integral battery operated LED when the pressure of that tire drops 5 to 8 psi.

Removing the cap from the sensor will indicate the functionality of the sensor and battery. If the sensor and battery are in working condition, the LED will immediately start to flash.

FRONT HUB COVERS

Stainless steel hub covers will be provided on the front axle. An oil level viewing window will be provided.

CHROME LUG NUT COVERS

Chrome lug nut covers will be supplied on front and rear wheels.

MUD FLAPS

Mud flaps with a Pierce logo will be installed behind the front and rear wheels.

WHEEL CHOCKS

There will be one (1) pair of folding Ziamatic, Model SAC-44-E, aluminum alloy, Quick-Choc wheel blocks, with easy-grip handle provided.

Wheel Chock Brackets

There will be one (1) pair of Zico, Model SQCH-44-H, horizontal mounting wheel chock brackets provided for the Ziamatic, Model SAC-44-E, folding wheel chocks. The brackets will be made of aluminum and consist of a quick release spring loaded rod to hold the wheel chocks in place. The brackets will be mounted below the left side rear compartment.

ANTI-LOCK BRAKE SYSTEM

The vehicle will be equipped with a Meritor WABCO 4S4M, anti-lock braking system. The ABS will provide a 4-channel anti-lock braking control on both the front and rear wheels. A digitally controlled system that utilizes microprocessor technology will control the anti-lock braking system. Each wheel will be monitored by the system. When any particular wheel begins to lockup, a signal will be sent to the control unit. This control unit then will reduce the braking of that wheel for a fraction of a second and then reapply the brake. This anti-lock brake system will eliminate the lockup of any wheel thus helping to prevent the apparatus from skidding out of control.

BRAKES

The service brake system will be full air type.

The front brakes will be Knorr/Bendix disc type with a 17.00" ventilated rotor for improved stopping distance.

The brake system will be certified, third party inspected, for improved stopping distance.

The rear brakes will be Meritor™ 16.50" x 7.00" cam operated with automatic slack adjusters. Dust shields will be provided.

BRAKE SYSTEM AIR COMPRESSOR

The air compressor will be a Cummins/WABCO with 18.7 cubic feet per minute output.

BRAKE SYSTEM

The brake system will include:

- Bendix® dual brake treadle valve
- Heated automatic moisture ejector on air dryer
- Total air system capacity of 4,362 cubic inches
- Two (2) air pressure gauges with a red warning light and an audible alarm, that activates when air pressure falls below 60 psi
- Spring set parking brake system
- Parking brake operated by a push-pull style control valve
- A parking "brake on" indicator light on instrument panel
- Park brake relay/inversion and anti-compounding valve, in conjunction with a double check valve system, with an automatic spring brake application at 40 psi

Columbia Heights Bid 941 Full Specification

- A pressure protection valve to prevent all air operated accessories from drawing air from the air system when the system pressure drops below 80 psi (550 kPa)
- 1/4 turn drain valve on each air tank

The air tank will be primed and painted to meet a minimum 750 hour salt spray test.

To reduce the effects of corrosion, the air tank will be mounted with stainless steel brackets.

BRAKE SYSTEM AIR DRYER

The air dryer will be WABCO System Saver 1200 with spin-on coalescing filter cartridge and 100 watt heater.

BRAKE LINES

Color-coded nylon brake lines will be provided. The lines will be wrapped in a heat protective loom in the chassis areas that are subject to excessive heat.

AIR INLET

One (1) air inlet with 3D series male coupling will be provided. It will allow station air to be supplied to the apparatus brake system through a shoreline hose. The inlet will be located forward in the driver side lower step well of cab. A check valve will be provided to prevent reverse flow of air. The inlet will discharge into the "wet" tank of the brake system. A mating female fitting will also be provided with the loose equipment.

ENGINE

The chassis will be powered by an electronically controlled engine as described below:

Make:	Cummins
Model:	L9
Power:	450 hp at 2100 rpm
Torque:	1250 lb-ft at 1400 rpm
Governed Speed:	2200 rpm
Emissions Level:	EPA 2021
Fuel:	Diesel
Cylinders:	Six (6)
Displacement:	543 cubic inches (8.9L)
Starter:	Delco 39MT™
Fuel Filters:	Spin-on style primary filter with water separator and water-in-fuel sensor. Secondary spin-on style filter.

The engine will include On-board diagnostics (OBD), which provides self diagnostic and reporting. The system will give the owner or repair technician access to state of health information for various vehicle sub systems. The system will monitor vehicle systems, engine and after treatment. The system will illuminate a malfunction indicator light on the dash console if a problem is detected.

HIGH IDLE

A high idle switch will be provided, inside the cab, on the instrument panel, that will automatically maintain a preset engine rpm. A switch will be installed, at the cab instrument panel, for activation/deactivation.

The high idle will be operational only when the parking brake is on and the truck transmission is in neutral. A green indicator light will be provided, adjacent to the switch. The light will illuminate when the above conditions are met. The light will be labeled "OK to Engage High Idle."

ENGINE BRAKE

A Jacobs® engine brake is to be installed with the controls located on the instrument panel within easy reach of the driver.

The driver will be able to turn the engine brake system on/off and have a high, medium and low setting.

The engine brake will activate when the system is on and the throttle is released.

The high setting of the brake application will activate and work simultaneously with the variable geometry turbo (VGT) provided on the engine.

The engine brake will be installed in such a manner that when the engine brake is slowing the vehicle the brake lights are activated.

The ABS system will automatically disengage the auxiliary braking device, when required.

CLUTCH FAN

A Horton fan clutch will be provided. The fan clutch will be automatic when the pump transmission is in "Road" position, and fully engaged in "Pump" position.

A momentary switch will be provided in the cab instrument panel to disengage the engine fan clutch when the fire pump is engaged. The purpose is to help increase the engine coolant temperature during cold weather operations. When a rocker switch is used, it will be red in color with a red indicator light in it that is illuminated when the fan clutch is disengaged by the switch. When a membrane switch is used, it will be illuminated in red when the fan clutch is disengaged by the switch. The switch will be labeled "Fan Clutch Disengaged". The fan clutch will return to its normal mode of operation when the pump is disengaged or by using the switch. The fan clutch will cycle automatically to keep the engine coolant from exceeding the engine manufacturer's recommendations during all operating conditions regardless of the switch position.

ENGINE AIR INTAKE

An air intake with an ember separator (to prevent road dirt, burning embers, and recirculating hot air from entering the engine) will be mounted at the front of the apparatus, on the passenger side of the engine. The ember separator will be mounted in the air intake with flame retardant, roto-molded polyethylene housing. It will be easily accessible by the hinged access panel at the front of the vehicle.

EXHAUST SYSTEM

The exhaust system will be stainless steel from the turbo to the engine's aftertreatment device, and will be 4.00" in diameter. The exhaust system will include a single module aftertreatment device to meet

current EPA standards. An insulation wrap will be provided on all exhaust pipes between the turbo and aftertreatment device to minimize the heat loss to the aftertreatment device . The exhaust will terminate horizontally ahead of the right side rear wheels. A tailpipe diffuser will be provided to reduce the temperature of the exhaust as it exits. Heat deflector shields will be provided to isolate chassis and body components from the heat of the tailpipe diffuser.

RADIATOR

The radiator and the complete cooling system will meet or exceed NFPA and engine manufacturer cooling system standards.

For maximum corrosion resistance and cooling performance, the entire radiator core will be constructed using long life aluminum alloy. The core will be made of aluminum fins, having a serpentine design, brazed to aluminum tubes. The tubes will be brazed to aluminum headers. The radiator core will have a minimum frontal area of 1434 square inches. Supply tank made of glass-reinforced nylon and a return tank of cast aluminum alloy will be crimped on to the core assembly using header tabs and a compression gasket to complete the radiator core assembly. The radiator will be compatible with commercial antifreeze solutions.

There will be a full steel frame around the entire radiator core assembly. The radiator core assembly will be isolated within the steel frame by rubber inserts to enhance cooling system durability and reliability. The radiator will be mounted in such a manner as to prevent the development of leaks caused by twisting or straining when the apparatus operates over uneven ground. The radiator assembly will be isolated from the chassis frame rails with rubber isolators.

The radiator assembly will include an integral deaeration tank permanently mounted to the top of the radiator framework, with a readily accessible remote-mounted overflow tank. For visual coolant level inspection, the radiator will have a built-in sight glass. The radiator will be equipped with a 15 psi pressure relief cap.

A drain port will be located at the lowest point of the cooling system and/or the bottom of the radiator to permit complete flushing of the coolant from the system.

A heavy-duty fan will draw in fresh, cool air through the radiator. Shields or baffles will be provided to prevent recirculation of hot air to the inlet side of the radiator.

COOLANT LINES

Gates, or Goodyear, rubber hose will be used for all engine coolant lines installed by the chassis manufacturer.

Hose clamps will be stainless steel "constant torque type" to prevent coolant leakage. They will react to temperature changes in the cooling system and expand or contract accordingly while maintaining a constant clamping pressure on the hose.

FUEL TANK

A 65 gallon fuel tank will be provided and mounted at the rear of the chassis. The tank will be constructed of 12-gauge, hot rolled steel. It will be equipped with swash partitions and a vent. To eliminate the effects of corrosion, the fuel tank will be mounted with stainless steel straps.

Columbia Heights Bid 941 Full Specification

A 0.75" drain plug will be located in a low point of the tank for drainage.

A fill inlet will be located on the left hand side of the body and is covered with a hinged, spring loaded, stainless steel door that is marked "Ultra Low Sulfur - Diesel Fuel Only."

A 0.50" diameter vent will be installed from tank top to just below fuel fill inlet.

The fuel tank will meet all FHWA 393.67 requirements including a fill capacity of 95 percent of tank volume.

All fuel lines will be provided as recommended by the engine manufacturer.

DIESEL EXHAUST FLUID TANK

A 4.5 gallon diesel exhaust fluid (DEF) tank will be provided and mounted in the driver's side body rearward of the rear axle.

A 0.50" drain plug will be provided in a low point of the tank for drainage.

A fill inlet will be provided and marked "Diesel Exhaust Fluid Only". The fill inlet will be located adjacent to the engine fuel inlet behind a common hinged, spring loaded, polished stainless steel door on the driver side of the vehicle.

The tank will meet the engine manufacturers requirement for 10 percent expansion space in the event of tank freezing.

The tank will include an integrated heater unit that utilizes engine coolant to thaw the DEF in the event of freezing.

FUEL SHUTOFF

A fuel line shutoff valve will be installed on both the inlet and outlet of the primary fuel filter.

TRANSMISSION

An Allison 5th generation, Model EVS 3000P, electronic torque converting automatic transmission will be provided.

The transmission will be equipped with prognostics to monitor oil life, filter life, and transmission health. A wrench icon on the shift selector's digital display will indicate when service is due.

Two (2) PTO openings will be located on both sides of converter housing (positions 4 o'clock and 8 o'clock) as viewed from the rear.

A transmission temperature gauge with red light and audible alarm will be installed on the cab dash.

TRANSMISSION SHIFTER

A five (5)-speed push button shift module will be mounted to right of driver on console. Shift position indicator will be indirectly lit for after dark operation.

The transmission ratio will be:

1st	3.49 to 1.00
2nd	1.86 to 1.00
3rd	1.41 to 1.00
4th	1.00 to 1.00
5th	0.75 to 1.00
R	5.03 to 1.00

TRANSMISSION COOLER

A Modine plate and fin transmission oil cooler will be provided using engine coolant to control the transmission oil temperature.

TRANSMISSION DIPSTICK CAP

The transmission dipstick cap will be engraved with "ALLISON TES-295 APPROVED SYNTHETIC TRANS FLUID ONLY".

DOWNSHIFT MODE (W/ENGINE BRAKE)

The transmission will be provided with an aggressive downshift mode.

This will provided earlier transmission downshifts to 2nd gear, resulting in improved engine braking performance.

TRANSMISSION FLUID

The transmission will be provided with TranSynd, or other Allison approved TES-295 heavy duty synthetic transmission fluid.

DRIVELINE

Drivelines will be a heavy-duty metal tube and be equipped with Spicer® 1710 universal joints.

The shafts will be dynamically balanced before installation.

A splined slip joint will be provided in each driveshaft where the driveline design requires it. The slip joint will be coated with Glidecoat® or equivalent.

STEERING

Dual Sheppard, Model M110, steering gears, with integral heavy-duty power steering, will be provided. For reduced system temperatures, the power steering will incorporate an air to oil cooler and an Eaton, Model VN20, hydraulic pump with integral pressure and flow control. All power steering lines will have wire braded lines with crimped fittings.

A tilt and telescopic steering column will be provided to improve fit for a broader range of driver configurations.

STEERING WHEEL

The steering wheel will be 18.00" in diameter, have tilting and telescoping capabilities, and a four (4)-spoke design.

Columbia Heights Bid 941 Full Specification

There will be a switch pod provided on each side of the steering wheel between the spokes. The switch pods will be an integral part of the steering wheel. Each switch pod will contain four (4) switches. The following switches will be provided:

Air horn

Emergency lighting

Area lighting

Front dome light

Rear dome light

Q2B siren activate

Q2B siren brake

Wiper mist

Full floating horn pad

LOGO AND CUSTOMER DESIGNATION ON DASH

The dash panel will have an emblem containing the Pierce logo and customer name. The emblem will have three (3) rows of text for the customer's department name. There will be a maximum of eight (8) characters in the first row, 11 characters in the second row and 11 characters in the third row.

The first row of text will be: Columbia

The second row of text will be: Heights

The third row of text will be: Fire Dept

BUMPER

A one (1) piece, ten (1) gauge, 304-2B type polished stainless steel bumper, a minimum of 10.00" high, will be attached to a bolted modular extension frame constructed of 50,000 psi tensile steel "C" channel mounted directly behind it to provide adequate support strength.

The bumper will be extended 19.00" from front face of cab.

Gravel Pan

A gravel pan, constructed of bright aluminum treadplate, will be furnished between the bumper and cab face. The gravel pan will be properly supported from the underside to prevent flexing and vibration of the aluminum treadplate.

CENTER HOSE TRAY

A hose tray, constructed of aluminum, will be placed in the center of the bumper extension.

The tray will have a capacity of 150' of 1.75" double jacket cotton-polyester hose.

Black rubber grating will be provided at the bottom of the tray. Drain holes are also provided.

Center Hose Tray Cover

A bright aluminum treadplate cover will be provided over the center hose tray.

The cover will be attached with a stainless steel hinge.

One (1) D-ring latch will secure the cover in the closed position and a pneumatic stay arm will hold the cover in the open position.

LIFT AND TOW MOUNTS

Mounted to the frame extension will be lift and tow mounts. The lift and tow mounts will be designed and positioned to adapt to certain tow truck lift systems.

The lift and tow mounts with eyes will be painted the same color as the frame.

TOW HOOKS

No tow hooks are to be provided. This truck will be equipped with a lift and tow package with integral tow eyes.

HINGED CENTER SECTION

The center section of the bumper will be hinged at the bottom. Two (2) paddle latches will hold the section in the closed position.

CAB

The Impel™ cab will be designed specifically for the fire service and will be manufactured by Pierce Manufacturing.

To provide quality at the source and single source customer support, the cab will be built by the apparatus manufacturer in a facility located on the manufacturer's premises.

For reasons of structural integrity and enhanced occupant protection, the cab will be of heavy duty design, constructed to the following minimal standards.

The cab will have 12 main vertical structural members located in the A-pillar (front cab corner posts), B-pillar (side center posts), C-pillar (rear corner posts) and rear wall areas. The A-pillar will be constructed of 0.25" heavy wall extrusions joined by a solid A356-T6 aluminum joint casting. The B-pillar and C-pillar will also be constructed from 0.25" heavy wall extrusions. The rear wall will be constructed of two (2) 4.00" x 2.00" outer aluminum extrusions and two (2) 3.00" x 2.00" inner aluminum extrusions. All main vertical structural members will run from the floor to 7.50" x 3.50" x 0.125" thick roof extrusions to provide a cage-like structure with the A-pillar and roof extrusions being welded into a 0.75" thick corner casting at each of the front corners of the roof assembly.

The front of the cab will be constructed of a 0.25" thick firewall, covered with a 0.125" front skin (for a total thickness of 0.38"), and reinforced with 24.50" wide x 10.00" deep x 0.50" thick supports on each side of the engine tunnel. The cross-cab support will be welded to the A-pillar, 0.25" firewall, and engine tunnel, on the left and right sides.

Columbia Heights Bid 941 Full Specification

The cab floors will be constructed of 0.1875" thick aluminum plate and reinforced at the firewall with an additional 0.25" thick cross-floor support providing a total thickness of 0.44" of structural material at the front floor area. The front floor area will also be supported with three (3) 0.50" plates bolted together that also provides the mounting point for the cab lift. This tubing will run from the front of the cab to the 0.1875" thick engine tunnel, creating the structure to support the forces created when lifting the cab.

The cab will be a full-tilt style. A three (3)-point cab mount system with rubber isolators will improve ride quality by isolating chassis vibrations from the cab.

The crew cab will be a totally enclosed design with the interior area completely open to improve visibility and verbal communication between the occupants.

The overall height (from the cab roof to the ground) will be approximately 102.00". The crew cab section will have a 10.00" raised roof, with an overall cab height of approximately 112.00". The raised portion will start at the most forward point of the B-pillar and continue rearward to the back of the cab. The overall height listed will be calculated based on a truck configuration with the lowest suspension weight ratings, the smallest diameter tires for the suspension, no water weight, no loose equipment weight, and no personnel weight. Larger tires, wheels, and suspension will increase the overall height listed.

The cab will have an interior width of not less than 93.50". The driver and passenger seating positions will have a minimum 24.00" clear width at knee level.

To reduce injuries to occupants in the seated positions, proper head clearance will be provided. The floor-to-ceiling height inside the forward cab will be no less than 60.25". The floor-to-ceiling height inside the crew cab will be no less than 62.95" in the center position and 68.75" in the outboard positions.

The crew cab will measure a minimum of 57.50" from the rear wall to the backside of the engine tunnel (knee level) for optimal occupant legroom.

INTERIOR CAB INSULATION

The cab walls, ceiling and engine tunnel will be insulated in all strategic locations to maximize acoustic absorption and thermal insulation. The cab will be insulated with 2.00" insulation in the rear wall, 3.00" insulation in the side walls, and 1.50" insulation in the ceiling.

FENDER LINERS

Full-circular, aluminum inner fender liners in the wheel wells will be provided.

PANORAMIC WINDSHIELD

A one (1)-piece, safety glass windshield with more than 2,802 square inches of clear viewing area will be provided. The windshield will be full width and will provide the occupants with a panoramic view. The windshield will consist of three (3) layers; the outer light, the middle safety laminate, and the inner light. The 0.114" thick outer light layer will provide superior chip resistance. The middle safety laminate layer will prevent the windshield glass pieces from detaching in the event of breakage. The inner light will provide yet another chip resistant layer. The cab windshield will be bonded to the

aluminum windshield frame using a urethane adhesive. A custom frit pattern will be applied on the outside perimeter of the windshield for a finished automotive appearance.

WINDSHIELD WIPERS

Three (3) electric windshield wipers with a washer, in conformance with FMVSS and SAE requirements, will be provided. The wiper blades will be 21.65" long and together will clear a minimum of 1,783 square inches of the windshield for maximum visibility in inclement weather.

The windshield washer fluid reservoir will be located at the front of the vehicle and be accessible through the access hood for simple maintenance.

FAST SERVICE ACCESS FRONT TILT HOOD

A full-width access hood will be provided for convenient access to engine coolant, steering fluid, wiper fluid, cab lift controls, headlight power modules, and ember separator. The hood will also provide complete access to the windshield wiper motor and components. The hood will be contoured to provide a sleek, automotive appearance. The hood will be constructed of two (2) fiberglass panels bonded together and will include reinforcing ribs for structural integrity. The hood will include air cylinders to hold the hood in open and closed positions, and a heavy duty latch system that will meet FMVSS 113 (Hood Latch System). The spring-loaded hood latch will be located at the center of the hood with a double-action release lever located behind the Pierce logo. The two (2)-step release requires the lever first be pulled to the driver side until the hood releases from the first latch (primary latch) then to the passenger side to fully release the hood (secondary latch).

ENGINE TUNNEL

To provide structural strength, the engine tunnel sidewalls will be constructed of 0.50" aluminum plate that is welded to both the 0.25" firewall and 0.38" heavy wall extrusion under the crew cab floor. To maximize occupant space, the top edges will be tapered.

The back of the engine tunnel will be no higher than 16.25" off the crew cab floor.

The engine tunnel will be insulated on both sides for thermal and acoustic absorption. The underside of the tunnel will be covered with 1.00" thick polyether foam that is reinforced with an aluminized face. Thermal rating for this insulation will be -40 degrees Fahrenheit to 300 degrees Fahrenheit. The insulation will keep noise (dBA) levels at or lower than the specifications in the current edition of the NFPA 1901 standards.

CAB REAR WALL EXTERIOR COVERING

The exterior surface of the rear wall of the cab will be overlaid with bright aluminum treadplate except for areas that are not typically visible when the cab is lowered.

CAB LIFT

A hydraulic cab lift system will be provided, consisting of an electric-powered hydraulic pump, fluid reservoir, dual lift cylinders, remote cab lift controls and all necessary hoses and valves. The hydraulic pump will have a backup manual override, for use in the event of an electrical failure.

The cab lift controls will be located at the driver side front of the cab, easily accessible under the full width front access hood. The controls will include a permanently mounted raise/lower switch. For

Columbia Heights Bid 941 Full Specification

enhanced visibility during cab tilt operations, a remote control tether with on/off switch will be supplied on a coiled cord that will extend from 2.00' (coiled) to 6.00' (extended).

The cab will be capable of tilting 42 degrees and 80 degrees with crane assist to accommodate engine maintenance and removal. The cab pivots will be located 46.00" apart to provide stability while tilting the cab.

The rear of the cab will be locked down by a two (2)-point, automatic, hydraulic, double hook mechanism that fully engages after the cab has been lowered (self-locking). The dual 2.25" diameter hydraulic cylinders will be equipped with a velocity fuse that protects the cab from accidentally descending when the cab is in the tilt position.

For increased safety, a redundant mechanical stay arm will be provided that must be manually put in place on the driver side between the chassis and cab frame when cab is in the raised position. This device will be manually stowed to its original position before the cab can be lowered.

Cab Lift Interlock

The cab lift safety system will be interlocked to the parking brake. The cab tilt mechanism will be active only when the parking brake is set and the ignition switch is in the on position. If the parking brake is released, the cab tilt mechanism will be disabled.

GRILLE

A bright finished aluminum mesh grille screen, inserted behind a formed bright finished grille surround, will be provided on the front center of the cab, and will serve as an air intake to the radiator.

DOOR JAMB SCUFFPLATES

All cab door jambs will be furnished with a polished stainless steel scuffplate, mounted on the striker side of the jamb.

FRONT CAB TRIM

A band of 22 gauge polished stainless steel trim will be installed across the front of the cab, from door hinge to door hinge. The trim band will be centered on the head lights and applied with two (2)-sided tape. A 0.625" self adhesive trim strip will be applied around the perimeter of the trim band.

There will be polished stainless steel corner covers provided over the painted cab corner where the cab turn signals are located.

SIDE OF CAB MOLDING

Chrome molding will be provided on both sides of cab.

MIRRORS

A Retraco, Model 613423, dual vision, motorized, west coast style mirror, with chrome finish, will be mounted on each side of the front cab door with spring loaded retractable arms. The flat glass and convex glass will be heated and adjustable with remote control within reach of the driver.

CAB DOORS

The forward cab and crew cab doors will be the half-height style door. To enhance entry and egress to the cab, the forward cab doors will be a minimum of 43.59" wide x 64.71" high. The crew cab doors will measure a minimum of 37.87" wide x 73.75" high.

The forward cab and crew cab doors will be constructed of extruded aluminum with a nominal material thickness of 0.125". The exterior door skins will be constructed from 0.090" aluminum.

The forward cab door windows will include a 7.50" high x 10.00" wide drop area at the front to enhance visibility.

A customized, vertical, pull-down type door handle will be provided on the exterior of each cab door. The exterior handle will be designed specifically for the fire service to prevent accidental activation, and will provide 4.00" wide x 2.00" deep hand clearance for ease of use with heavy gloved hands. Each door will also be provided with an interior flush, open style paddle handle that will be readily operable from fore and aft positions, and be designed to prevent accidental activation. The interior handles will provide 4.00" wide x 1.25" deep hand clearance for ease of use with heavy gloved hands.

The cab doors will be provided with both interior (rotary knob) and exterior (keyed) locks exceeding FMVSS standards. The keys will be Model 751. The locks will be capable of activating when the doors are open or closed. The doors will remain locked if locks are activated when the doors are opened, then closed.

A full length, heavy duty, stainless steel, piano-type hinge with a 0.38" pin and 11 gauge leaf will be provided on all cab doors. There will be double automotive-type rubber seals around the perimeter of the door framing and door edges to ensure a weather-tight fit.

A chrome grab handle will be provided on the inside of each cab and crew cab door.

A red webbed grab handle will be installed on the crew cab door stop strap. The grab handles will be securely mounted.

The cab steps at each cab door location will be located below the cab doors and will be exposed to the exterior of the cab.

Door Panels

The inner cab door panels will be constructed out of brushed stainless steel. The cab door panels will be removable.

RECESSED POCKET WITH ELASTIC COVER

To provide organized storage (clutter control) in the cab for miscellaneous equipment, the cab interior will be provided with recessed storage pockets. The pockets will be 5.63" wide x 2.00" high x 4.00" deep. The pockets will be provided with a perforated elastic material cover to secure the equipment in the pocket. The pockets will be installed in all available mounting locations of the overhead console.

ELECTRIC WINDOW CONTROLS

Each cab entry door will be equipped with an electrically operated tempered glass window. A window control panel will be located on the door panel within easy reach of the respective occupant. Each

Columbia Heights Bid 941 Full Specification

switch will allow intermittent or auto down operation for ease of use. Auto down operation will be actuated by holding the window down switch for approximately 1 second. The driver control panel will contain a control switch for each cab door's window. All other door control panels will contain a single switch to operate the window within that door.

The window switches will be connected directly to the battery power. This allows the windows to be raised and lowered when the battery switch is in the off position.

DUAL STEPS

A dual step will be provided below each cab and crew cab door. The steps will be designed with a grip pattern punched into bright aluminum treadplate material providing support, slip resistance, and drainage. The steps will be a bolt-on design and provide a 24.00" wide x 9.00" deep stepping surface. The step design raises the middle step higher and closer to the cab floor, resulting in a 12.00" distance from the step to cab floor in the cab and a 13.50" distance from the step to cab floor in the crew cab. Stepping distances from the ground to first step will be 16.50" and from first step to middle step will be 12.00".

The first step will be lit by a white 12 volt DC LED light provided on the step.

CAB EXTERIOR HANDRAILS

A 1.25" diameter slip-resistant, knurled aluminum handrail will be provided adjacent to each cab and crew cab door opening to assist during cab ingress and egress.

STEP LIGHTS

For reduced overall maintenance costs compared to incandescent lighting, there will be four (4) white LED step lights provided. The lights will be installed at each cab and crew cab door, one (1) per step. The lights will be located in the driver side front doorstep, driver side crew cab doorstep, passenger side front doorstep and passenger side crew cab doorstep.

In order to ensure exceptional illumination, each light will provide a minimum of 25 foot-candles (fc) covering an entire 15.00" x 15.00" square placed 10.00" below the light and a minimum of 1.5 fc covering an entire 30.00" x 30.00" square at the same 10.00" distance below the light.

The lights will be activated when the adjacent door is opened.

FENDER CROWNS

Stainless steel fender crowns will be installed at the cab wheel openings.

CREW CAB WINDOWS

One (1) fixed window with tinted glass will be provided on each side of the cab, to the rear of the front cab door. The windows will be sized to enhance light penetration into the cab interior. The windows will measure 20.00" wide x 20.50" high.

STORAGE COMPARTMENTS

Provided on each side of the cab, to the rear of the crew cab access doors, will be a storage compartment.

The compartments will be approximately 10.71" wide x 30.00" high x 14.00" deep.

There will be two (2) double pan doors painted to match the cab exterior with a non-locking D-Ring latch, one (1) on each side of the cab. A rubber bumper for each exterior door will be used as a door stop.

The compartment interior will be painted spatter gray.

Compartment Light

There will be two (2) white LED strip lights provided, one (1) each hinged side of compartment door openings. The lights will be controlled by an automatic door switch.

CAB INTERIOR

With safety as the primary objective, the wrap-around style cab instrument panel will be designed with unobstructed visibility to instrumentation. The dash layout will provide the driver with a quick reference to gauges that allows more time to focus on the road.

The center console will be a high impact ABS polymer and will be easily removable for access to the defroster. The center console will include louvers strategically located for optimal air flow and defrost capability to the windshield.

The passenger side dashboard will be constructed of painted aluminum for durability and low maintenance. For enhanced versatility, the passenger side dash will include a flat working surface.

To provide optional (service friendly) control panels, switches and storage modules, a painted aluminum overhead console will also be provided.

To complete the cab front interior design, painted aluminum modesty panels will be provided under the dash on both sides of the cab. The driver side modesty panel will provide mounting for the battery switch and diagnostic connectors, while the passenger side modesty panel provides a glove box, and ground access to the main electrical distribution panel via quick quarter turn fasteners.

To provide a deluxe automotive interior, the engine tunnel will be covered by leather grain vinyl that is resistant to oil, grease, and mildew. For durability and ease of maintenance, the cab interior side walls will be painted aluminum. The rear wall will be painted aluminum.

The headliner will be installed in both forward and rear cab sections. The headliner panel will be a composition of an aluminum panel covered with a sound barrier and upholstery.

The cab structure will include designated raceways for electrical harness routing from the front of the cab to the rear upper portion of the cab. Raceways will be extruded in the forward door frame, floor, walls and overhead in the area where the walls meet the ceiling. The raceways located in the floor will be covered by aluminum extrusion, while the vertical and overhead raceways will be covered by painted aluminum covers. The raceways will improve harness integrity by providing a continuous harness path that eliminates wire chafing and abrasion associated with exposed wiring or routing through drilled metal holes. Harnesses will be laid in place.

CAB INTERIOR UPHOLSTERY

The cab interior upholstery will be 36 oz dark silver gray vinyl. All cab interior materials will meet FMVSS 302 (flammability of interior materials).

CAB INTERIOR PAINT

The following metal surfaces will be painted black, vinyl textured paint:

- Modesty panel in front of driver
- Vertical surface of dash in front of the officer (not applicable for recessed dash)
- Glove box in front of the officer (if applicable)
- Power distribution in front of the officer
- Rear heater vent panels

The remaining cab interior metal surfaces will be painted fire smoke gray, vinyl texture paint.

CAB FLOOR

The cab and crew cab floor areas will be covered with Polydamp™ acoustical floor mat consisting of a black pyramid rubber facing and closed cell foam decoupler.

The top surface of the material has a series of raised pyramid shapes evenly spaced, which offer a superior grip surface. Additionally, the material has a 0.25" thick closed cell foam (no water absorption) which offers a sound dampening material for reducing sound levels.

DEFROST/AIR CONDITIONING SYSTEM

A ceiling mounted combination heater, defroster and air conditioning system will be installed in the cab above the engine tunnel area.

Cab Defroster

A 54,000 BTU heater-defroster unit with 690 SCFM of air flow will be provided inside the cab. The heater-defrost will be installed in the forward portion of the cab ceiling. Air outlets will be strategically located in the cab header extrusion per the following:

- One (1) adjustable will be directed towards the left side cab window
- One (1) adjustable will be directed towards the right side cab window
- Six (6) fixed outlets will be directed at the windshield

The defroster will be capable of clearing 98 percent of the windshield and side glass when tested under conditions where the cab has been cold soaked at 0 degrees Fahrenheit for 10 hours, and a 2 ounce per square inch layer of frost/ice has been able to build up on the exterior windshield. The defroster system will meet or exceed SAE J382 requirements.

Cab/Crew Auxiliary Heater

There will be one (1) 31,000 BTU auxiliary heater with 560 SCFM of air flow provided in each outboard rear facing seat risers with a dual scroll blower. An aluminum plenum incorporated into the cab structure used to transfer heat to the forward positions.

Air Conditioning

A 19.10 cubic inch compressor will be installed on the engine.

Columbia Heights Bid 941 Full Specification

A roof-mounted condenser with a 78,000 BTU output at 2,400 SCFM that meets and exceeds the performance specification will be installed on the cab roof. The condenser cover and mounting legs to be painted white as provided by the A/C manufacturer.

The air conditioning system will be capable of cooling the average cab temperature from 100 degrees Fahrenheit to 75 degrees Fahrenheit at 50 percent relative humidity within 30 minutes. The cooling performance test will be run only after the cab has been heat soaked at 100 degrees Fahrenheit for a minimum of 4 hours.

The evaporator unit will be installed in the rear portion of the cab ceiling over the engine tunnel. The evaporator will include one (1) high performance heating core, one (1) high performance cooling core with (1) plenum directed to the front and one (1) plenum directed to the rear of the cab.

The evaporator unit will have a 52,000 BTU at 690 SCFM rating that meets and exceeds the performance specifications.

Adjustable air outlets will be strategically located on the forward plenum cover per the following:

- Four (4) will be directed towards the seating position on the left side of the cab
- Four (4) will be directed towards the seating position on the right side of the cab

Adjustable air outlets will be strategically located on the evaporator cover per the following:

- Five (5) will be directed towards crew cab area

A high efficiency particulate air (HEPA) filter will be included for the system. Access to the filter cover will be secured with four (4) screws.

The air conditioner refrigerant will be R-134A and will be installed by a certified technician.

Climate Control

An automotive style controller will be provided to control the heat and air conditioning system within the cab. The controller will have three (3) functional knobs for fan speed, temperature, and air flow distribution (front to rear) control.

The system will control the temperature of the cab and crew cab automatically by pushing the center of the fan speed control knob. Rotate the center temperature control knob to set the cab and crew cab temperature.

The AC system will be manually activated by pushing the center of the temperature control knob. Pushing the center of the air flow distribution knob will engage the AC for max defrost, setting the fan speeds to 100 percent and directing all air flow to the overhead forward position.

Gravity Drain Tubes

Two (2) condensate drain tubes will be provided for the air conditioning evaporator. The drip pan will have two (2) drain tubes plumbed separately to allow for the condensate to exit the drip pan. No pumps will be provided.

SUN VISORS

Two (2) smoked Lexan™ sun visors provided. The sun visors will be located above the windshield with one (1) mounted on each side of the cab.

There will be no retention bracket provided to help secure each sun visor in the stowed position.

GRAB HANDLE

A black rubber covered grab handle will be mounted on the door post of the driver side cab door to assist in entering the cab. The grab handle will be securely mounted to the post area between the door and windshield.

A long rubber grab handle will be mounted on the dash board in front of the officer.

ENGINE COMPARTMENT LIGHTS

There will be one (1) Whelen, Model 3SC0CDCR, 12 volt DC, 3.00" white LED light(s) with Whelen, Model 3FLANGEC, chrome flange kit(s) installed under the cab to be used as engine compartment illumination.

These light(s) will be activated automatically when the cab is raised.

ACCESS TO ENGINE DIPSTICKS

For access to the engine oil and transmission fluid dipsticks, there will be a door on the engine tunnel, inside the crew cab. The door will be on the rear wall of the engine tunnel, on the vertical surface. The door will be 20.00" wide x 8.25" high and be flush with the wall of the engine tunnel.

The engine oil dipstick will allow for checking only. The transmission dipstick will allow for both checking and filling. An additional port will be provided for filling the engine oil.

The door will have a rubber seal for thermal and acoustic insulation. One (1) flush latch will be provided on the access door.

CAB SAFETY SYSTEM

The cab will be provided with a safety system designed to protect occupants in the event of a side roll or frontal impact, and will include the following:

- A supplemental restraint system (SRS) sensor will be installed on a structural cab member behind the instrument panel. The SRS sensor will perform real time diagnostics of all critical subsystems and will record sensory inputs immediately before and during a side roll or frontal impact event.
- A slave SRS sensor will be installed in the cab to provide capacity for eight (8) crew cab seating positions.
- A fault-indicating light will be provided on the vehicle's instrument panel allowing the driver to monitor the operational status of the SRS system.
- A driver side front air bag will be mounted in the steering wheel and will be designed to protect the head and upper torso of the occupant, when used in combination with the 3-point seat belt.

Columbia Heights Bid 941 Full Specification

- A passenger side knee bolster air bag will be mounted in the modesty panel below the dash panel and will be designed to protect the legs of the occupant, when used in combination with the 3-point seat belt.
- Air curtains will be provided in the outboard bolster of outboard seat backs to provide a cushion between occupant and the cab wall.
- Suspension seats will be provided with devices to retract them to the lowest travel position during a side roll or frontal impact event.
- Seat belts will be provided with pre-tensioners to remove slack from the seat belt during a side roll or frontal impact event.

FRONTAL IMPACT PROTECTION

The SRS system will provide protection during a frontal or oblique impact event. The system will activate when the vehicle decelerates at a predetermined G force known to cause injury to the occupants. The cab and chassis will have been subjected, via third party test facility, to a crash impact during frontal and oblique impact testing. Testing included all major chassis and cab components such as mounting straps for fuel and air tanks, suspension mounts, front suspension components, rear suspensions components, frame rail cross members, engine and transmission and their mounts, pump house and mounts, frame extensions and body mounts. The testing provided configuration specific information used to optimize the timing for firing the safety restraint system. The sensor will activate the pyrotechnic devices when the correct crash algorithm, wave form, is detected.

The SRS system will deploy the following components in the event of a frontal or oblique impact event:

- Driver side front air bag
- Passenger side knee bolster air bag
- Air curtains mounted in the outboard bolster of outboard seat backs
- Suspension seats will be retracted to the lowest travel position
- Seat belts will be pre-tensioned to firmly hold the occupant in place

SIDE ROLL PROTECTION

The SRS system will provide protection during a fast or slow 90 degree roll to the side, in which the vehicle comes to rest on its side. The system will analyze the vehicle's angle and rate of roll to determine the optimal activation of the advanced occupant restraints.

The SRS system will deploy the following components in the event of a side roll:

- Air curtains mounted in the outboard bolster of outboard seat backs
- Suspension seats will be retracted to the lowest travel position
- Seat belts will be pre-tensioned to firmly hold the occupant in place

SEATING CAPACITY

The seating capacity in the cab will be six (6).

DRIVER SEAT

A Pierce PS6® seat will be provided in the cab for the driver. The seat design will be a cam action type with air suspension. For increased convenience, the seat will include electric controls to adjust the rake

(15 degrees), height (1.75" travel) and horizontal (7.00" travel) position. Electric controls will be located below the forward part of the seat cushion. To provide flexibility for multiple driver configurations, the seat will have a reclining back, adjustable from 20 degrees back to 45 degrees forward. Providing for maximum comfort, the seat back will be a high back style with manual lumbar adjustment lever, for lower back support, and will include minimum 7.50" deep side bolster pads for maximum support. The lumbar adjustment lever will be easily located at the lower outboard position of the seat cushion. For optimal comfort, the seat will be provided with 17.00" deep dual density foam cushions designed with EVC (elastomeric vibration control).

The seat will include the following features incorporated into the side roll protection system:

- Side air curtain will be mounted integral to the outboard bolster of the seat back. The air curtain will be covered by a decorative panel when in the stowed position.
- A suspension seat safety system will be included. When activated in the event of a side roll, this system will pretension the seat belt and retract the seat to its lowest travel position.

The seat will be furnished with a 3-point, shoulder type seat belt. The seat belt will be furnished with dual automatic retractors that will provide ease of operation in the normal seating position.

OFFICER SEAT

A Pierce PS6® seat will be provided in the cab for the officer. The seat will be a cam action type, with air suspension. For increased convenience, the seat will include a manual control to adjust the horizontal position (6.00" travel). The manual horizontal control will be a towel-bar style located below the forward part of the seat cushion. To provide flexibility for multiple passenger configurations, the seat will have a reclining back adjustable from 20 degrees back to 0 degrees forward. The seat back will be a high back style with manual lumbar adjustment lever, and will include minimum 7.50" deep side bolster pads for maximum support. For optimal comfort, the seat will be provided with 17.00" deep dual density foam cushions designed with EVC (elastomeric vibration control). To ensure safe operation, the seat will be equipped with seat belt sensors in the seat cushion and belt receptacle that will activate an alarm indicating a seat is occupied but not buckled.

The seat will include the following features incorporated into the side roll protection system:

- Side air curtain will be mounted integral to the outboard bolster of the seat back. The air curtain will be covered by a decorative panel when in the stowed position.
- A suspension seat safety system will be included. When activated this system will pretension the seat belt and retract the seat to its lowest travel position.

The seat will be furnished with a 3-point, shoulder type seat belt. The seat belt will be furnished with dual automatic retractors that will provide ease of operation in the normal seating position.

RADIO COMPARTMENT

A compartment for the radio amplifier will be located on the floor of the cab behind the front passenger's seat. A lift-up door with a chrome plated lift and turn latch will be provided for access. The compartment will be constructed of smooth aluminum and painted to match the cab interior.

REAR FACING DRIVER SIDE OUTBOARD SEAT

There will be one (1) rear facing, Pierce PS6® seat provided at the driver side outboard position in the crew cab. The seat back will be a high back style with 7.50 degree fixed recline angle, and will include minimum 7.50" deep side bolster pads for maximum support. For optimal comfort, the seat will be provided with 17.00" deep dual density foam cushions designed with EVC. (elastomeric vibration control). To ensure safe operation, the seat will be equipped with seat belt sensors in the seat cushion and belt receptacle, that will activate an alarm indicating a seat is occupied but not buckled.

The seat will include the following features incorporated into the side roll protection system:

- Side air curtain will be mounted integral to the outboard bolster of the seat back. The air curtain will be covered by a decorative panel when in the stowed position.
- A seat safety system will be included. When activated, this system will pretension the seat belt around the occupant to firmly hold them in place in the event of a side roll.

The seat will be furnished with a 3-point, shoulder type seat belt. The seat belt will be furnished with dual automatic retractors that will provide ease of operation in the normal seating position.

REAR FACING PASSENGER SIDE OUTBOARD SEAT

There will be one (1) rear facing, Pierce PS6® seat provided at the passenger side outboard position in the crew cab. The seat back will be a high back style with 7.5 degree fixed recline angle, and will include minimum 7.50" deep side bolster pads for maximum support. For optimal comfort, the seat will be provided with 17.00" deep dual density foam cushions designed with EVC (elastomeric vibration control). To ensure safe operation, the seat will be equipped with seat belt sensors in the seat cushion and belt receptacle, that will activate an alarm indicating a seat is occupied but not buckled.

The seat will include the following features incorporated into the side roll protection system:

- Side air curtain will be mounted integral to the outboard bolster of the seat back. The air curtain will be covered by a decorative panel when in the stowed position.
- A seat safety system will be included. When activated, this system will pretension the seat belt around the occupant to firmly hold them in place in the event of a side roll.

The seat will be furnished with a 3-point, shoulder type seat belt. The seat belt will be furnished with dual automatic retractors that will provide ease of operation in the normal seating position.

FORWARD FACING LEFT SIDE CABINET

A forward facing cabinet will be provided in the crew cab located at the left side outboard position.

The cabinet will be 21.00" wide x 51.00" high x 14.00" deep. The interior door will be web netting. The netting will be made with 1.00" wide nylon material with 2.00" openings. The nylon webbing will be permanently fastened at the inboard side of the cabinet and have spring clip and hook fasteners on the opposite side to secure it. The clear door opening of the cabinet will be 18.50" wide x 48.00" high.

The cabinet will include two (2) infinitely adjustable shelves with a 1.25" up-turned lipped to match the cab interior.

The cabinet will include no louvers.

The cabinet will be constructed of smooth aluminum and painted to match the cab interior.

CABINET LIGHT

There will be one (1) white LED strip light installed on the left side of the interior cabinet door opening. The lighting will be controlled by a rocker switch on the front of the cabinet.

FORWARD FACING CENTER SEATS

There will be two (2) forward facing, Pierce PS6® seats provided at the center position in the crew cab. The seat backs will be a high back style with 7.50 degree fixed recline angle, and will include minimum 7.50" deep side bolster pads for maximum support. For optimal comfort, the seats will be provided with 17.00" deep dual density foam cushions designed with EVC (elastomeric vibration control). To ensure safe operation, the seats will be equipped with seat belt sensors in the seat cushion and belt receptacle that will activate an alarm indicating a seat is occupied but not buckled.

The seats will include the following feature incorporated into the side roll protection system:

- A seat safety system will be included. When activated, this system will pretension the seat belts around the occupants to firmly hold them in place in the event of a side roll.

The seats will be furnished with 3-point, shoulder type seat belts. The seat belts will be furnished with dual automatic retractors that will provide ease of operation in the normal seating position.

FORWARD FACING RIGHT SIDE CABINET

A forward facing cabinet will be provided in the crew cab located at the right side outboard position.

The cabinet will be 21.00" wide x 51.00" high x 14.00" deep. The interior door will be web netting. The netting will be made with 1.00" wide nylon material with 2.00" openings. The nylon webbing will be permanently fastened at the inboard side of the cabinet and have spring clip and hook fasteners on the opposite side to secure it. The clear door opening of the cabinet will be 18.50" wide x 48.00" high.

The cabinet will include three (3) infinitely adjustable shelves with a 0.75" up-turned lip painted to match the cab interior.

The cabinet will include no louvers.

The cabinet will be constructed of smooth aluminum, and painted to match the cab interior.

Cabinet Light

There will be one (1) white LED strip light installed on the right side of the interior cabinet door opening. The lighting will be controlled by a rocker switch on the front of the cabinet.

SEAT UPHOLSTERY

All seat upholstery will be leather grain 36 oz dark silver gray vinyl resistant to oil, grease and mildew. The cab will have six (6) seating positions.

SEAT BELTS

All seating positions in the cab, crew cab and tiller cab (if applicable) will have red seat belts.

Columbia Heights Bid 941 Full Specification

To provide quick, easy use for occupants wearing bunker gear, the female buckle and seat belt webbing length will meet or exceed the current edition of NFPA 1901 and CAN/ULC - S515 standards.

The 3-point shoulder type seat belts will also include the ReadyReach D-loop assembly to the shoulder belt system. The ReadyReach feature adds an extender arm to the D-loop location placing the D-loop in a closer, easier to reach location.

Any flip up seats will include a 3-point shoulder type belts only.

SHOULDER HARNESS HEIGHT ADJUSTMENT

All seating positions furnished with 3-point shoulder type seat belts will include a height adjustment. This adjustment will optimize the belts effectiveness and comfort for the seated firefighter.

A total of six (6) seating positions will have the adjustable shoulder harness.

HELMET STORAGE PROVIDED BY FIRE DEPARTMENT

NFPA 1901, 2016 edition, section 14.1.7.4.1 requires a location for helmet storage be provided.

There is no helmet storage on the apparatus as manufactured. The fire department will provide a location for storage of helmets.

CAB DOME LIGHTS

There will be four (4) dual LED dome lights with black bezels provided. Two (2) lights will be mounted above the inside shoulder of the driver and officer and two (2) lights will be installed and located, one (1) on each side of the crew cab.

The color of the LED's will be red and white.

The white LED's will be controlled by the door switches and the lens switch.

The color LED's will be controlled by the lens switch.

In order to ensure exceptional illumination, each white LED dome light will provide a minimum of 10.1 foot-candles (fc) covering an entire 20.00" x 20.00" square seating position when mounted 40.00" above the seat.

PORTABLE HAND LIGHTS, PROVIDED BY FIRE DEPARTMENT

NFPA 1901, 2016 edition, section 5.9.4 requires two portable hand lights mounted in brackets fastened to the apparatus.

The hand lights are not on the apparatus as manufactured. The fire department will provide and mount these hand lights.

CAB INSTRUMENTATION

The cab instrument panel will consist of gauges, an LCD display, telltale indicator lights, alarms, control switches, and a diagnostic panel. The function of instrument panel controls and switches will be identified by a label adjacent to each item. Actuation of the headlight switch will illuminate the labels in low light conditions. Telltale indicator lamps will not be illuminated unless necessary. The cab instruments and controls will be conveniently located within the forward cab section directly forward of

the driver. Gauge and switch panels will be designed to be removable for ease of service and low cost of ownership.

Gauges

The gauge panel will include the following ten (10) black gauges with black bezels to monitor vehicle performance:

- Voltmeter gauge (Volts)
 - Low volts (11.8 VDC)
 - Amber indicator on gauge assembly with alarm
 - High volts (15 VDC)
 - Amber indicator on gauge assembly with alarm
 - Very low volts (11.3 VDC)
 - Amber indicator on gauge assembly with alarm
 - Very high volts (16 VDC)
 - Amber indicator on gauge assembly with alarm
- Tachometer (RPM)
- Speedometer (Primary (outside) MPH, Secondary (inside) Km/H)
- Fuel level gauge (Empty - Full in fractions)
 - Low fuel (1/8 full)
 - Amber indicator on gauge assembly with alarm
 - Very low fuel (1/32) fuel
 - Amber indicator on gauge assembly with alarm
- Engine oil pressure gauge (PSI)
 - Low oil pressure to activate engine warning lights and alarms
 - Red indicator on gauge assembly with alarm
- Front air pressure gauge (PSI)
 - Low air pressure to activate warning lights and alarm
 - Red indicator on gauge assembly with alarm
- Rear air pressure gauge (PSI)
 - Low air pressure to activate warning lights and alarm
 - Red indicator on gauge assembly with alarm
- Transmission oil temperature gauge (Fahrenheit)
 - High transmission oil temperature activates warning lights and alarm
 - Amber indicator on gauge assembly with alarm
- Engine coolant temperature gauge (Fahrenheit)
 - High engine temperature activates an engine warning light and alarm
 - Red indicator on gauge assembly with alarm
- Diesel Exhaust Fluid Level Gauge (Empty - Full in fractions)
 - Low fluid (1/8 full)
 - Amber indicator on gauge assembly with alarm

All gauges and gauge indicators will perform prove out at initial power-up to ensure proper performance.

Indicator Lamps

To promote safety, the following telltale indicator lamps will be integral to the gauge assembly and are located above and below the center gauges. The indicator lamps will be "dead-front" design that is only visible when active. The colored indicator lights will have descriptive text or symbols.

The following amber telltale lamps will be present:

- Low coolant
- Trac cntl (traction control) (where applicable)
- Check engine
- Check trans (check transmission)
- Aux brake overheat (Auxiliary brake overheat)
- Air rest (air restriction)
- Caution (triangle symbol)
- Water in fuel
- DPF (engine diesel particulate filter regeneration)
- Trailer ABS (where applicable)
- Wait to start (where applicable)
- HET (engine high exhaust temperature) (where applicable)
- ABS (antilock brake system)
- MIL (engine emissions system malfunction indicator lamp) (where applicable)
- SRS (supplemental restraint system) fault (where applicable)
- DEF (low diesel exhaust fluid level)

The following red telltale lamps will be present:

- Warning (stop sign symbol)
- Seat belt
- Parking brake
- Stop engine
- Rack down

The following green telltale lamps will be provided:

- Left turn
- Right turn
- Battery on

The following blue telltale lamp will be provided:

- High beam

Alarms

Audible steady tone warning alarm: A steady audible tone alarm will be provided whenever a warning message is present.

Audible pulsing tone caution alarm: A pulsing audible tone alarm (chime/chirp) will be provided whenever a caution message is present without a warning message being present.

Alarm silence: Any active audible alarm will be able to be silenced by holding the ignition switch at the top position for three (3) to five (5) seconds. For improved safety, silenced audible alarms will intermittently chirp every 30 seconds until the alarm condition no longer exists. The intermittent chirp will act as a reminder to the operator that a caution or warning condition still exists. Any new warning or caution condition will enable the steady or pulsing tones respectively.

Indicator Lamp and Alarm Prove-Out

Telltale indicators and alarms will perform prove-out at initial power-up to ensure proper performance.

Control Switches

For ease of use, the following controls will be provided immediately adjacent to the cab instrument panel within easy reach of the driver.

Emergency master switch: A molded plastic push button switch with integral indicator lamp will be provided. Pressing the switch will activate emergency response lights and siren control. A green lamp on the switch provides indication that the emergency master mode is active. Pressing the switch again disables the emergency master mode.

Headlight / Parking light switch: A three (3)-position maintained rocker switch will be provided. The first switch position will deactivate all parking lights and the headlights. The second switch position will activate the parking lights. The third switch position will activate the headlights.

Panel backlighting intensity control switch: A three (3)-position momentary rocker switch will be provided. The first switch position decreases the panel backlighting intensity to a minimum level as the switch is held. The second switch position is the default position that does not affect the backlighting intensity. The third switch position increases the panel backlighting intensity to a maximum level as the switch is held.

The following standard controls will be integral to the gauge assembly and are located below the right hand gauges. All switches have backlit labels for low light applications.

High idle engagement switch: A two (2)-position momentary rocker switch with integral indicator lamp will be provided. The first switch position is the default switch position. The second switch position will activate and deactivate the high idle function when pressed and released. The "Ok To Engage High Idle" indicator lamp must be active for the high idle function to engage. A green indicator lamp integral to the high idle engagement switch will indicate when the high idle function is engaged.

"Ok To Engage High Idle" indicator lamp: A green indicator light will be provided next to the high idle activation switch to indicate that the interlocks have been met to allow high idle engagement.

The following standard controls will be provided adjacent to the cab gauge assembly within easy reach of the driver. All switches will have backlit labels for low light applications.

Ignition switch: A three (3)-position maintained/momentary rocker switch will be provided. The first switch position will deactivate vehicle ignition. The second switch position will activate vehicle ignition.

Columbia Heights Bid 941 Full Specification

The third momentary position will disable the Command Zone audible alarm if held for three (3) to five (5) seconds. A green indicator lamp will be activated with vehicle ignition.

Engine start switch: A two (2)-position momentary rocker switch will be provided. The first switch position is the default switch position. The second switch position will activate the vehicle's engine. The switch actuator is designed to prevent accidental activation.

4-way hazard switch: A two (2)-position maintained rocker switch will be provided. The first switch position will deactivate the 4-way hazard switch function. The second switch position will activate the 4-way hazard function. The switch actuator will be red and includes the international 4-way hazard symbol.

Heater, defroster, and optional air conditioning control panel: A control panel with membrane switches will be provided to control heater/defroster temperature and heater, defroster, and air conditioning fan speeds. A green LED status bar will indicate the relative temperature and fan speed settings.

Turn signal arm: A self-canceling turn signal with high beam headlight and windshield wiper/washer controls will be provided. The windshield wiper control will have high, low, and intermittent modes.

Parking brake control: An air actuated push/pull park brake control valve will be provided.

Chassis horn control: Activation of the chassis horn control will be provided through the center of the steering wheel.

Custom Switch Panels

The design of cab instrumentation will allow for emergency lighting and other switches to be placed within easy reach of the operator thus improving safety. There will be positions for up to four (4) switch panels in the overhead console on the driver's side, up to four (4) switch panels in the engine tunnel console facing the driver, up to four (4) switch panels in the overhead console on the officer's side and up to two (2) switch panels in the engine tunnel console facing the officer. All switches will have backlit labels for low light applications.

Diagnostic Panel

A diagnostic panel will be accessible while standing on the ground and located inside the driver's side door left of the steering column. The diagnostic panel will allow diagnostic tools such as computers to connect to various vehicle systems for improved troubleshooting providing a lower cost of ownership. Diagnostic switches will allow ABS systems to provide blink codes should a problem exist. The diagnostic panel will include the following:

- Engine diagnostic port
- Transmission diagnostic port
- ABS diagnostic port
- SRS diagnostic port (where applicable)
- Command Zone USB diagnostic port
- ABS diagnostic switch (blink codes flashed on ABS telltale indicator)
- Diesel particulate filter regeneration switch (where applicable)
- Diesel particulate filter regeneration inhibit switch (where applicable)

Cab LCD Display

A digital four (4)-row by 20-character dot matrix display will be integral to the gauge panel. The display will be capable of showing simple graphical images as well as text. The display will be split into three (3) sections. Each section will have a dedicated function. The upper left section will display the outside ambient temperature. The upper right section will display odometer, trip mileage, PTO hours, fuel consumption, engine hours, and other configuration specific information. The bottom section will display INFO, CAUTION, and WARNING messages. Text messages will automatically activate to describe the cause of an audible caution or warning alarm. The LCD will be capable of displaying multiple text messages should more than one caution or warning condition exist.

AIR RESTRICTION INDICATOR

A high air restriction warning indicator light LCD message with amber warning indicator and audible alarm will be provided.

"DO NOT MOVE APPARATUS" INDICATOR

A flashing red indicator light, located in the driving compartment, will be illuminated automatically per the current NFPA requirements. The light will be labeled "Do Not Move Apparatus If Light Is On."

The same circuit that activates the Do Not Move Apparatus indicator will activate a pulsing alarm when the parking brake is released.

DO NOT MOVE TRUCK MESSAGES

Messages will be displayed on the Command Zone™, color display located within sight of the driver whenever the Do Not Move Truck light is active. The messages will designate the item or items not in the stowed for vehicle travel position (parking brake disengaged).

The following messages will be displayed (where applicable):

- Do Not Move Truck
- DS Cab Door Open (Driver Side Cab Door Open)
- PS Cab Door Open (Passenger's Side Cab Door Open)
- DS Crew Cab Door Open (Driver Side Crew Cab Door Open)
- PS Crew Cab Door Open (Passenger's Side Crew Cab Door Open)
- DS Body Door Open (Driver Side Body Door Open)
- PS Body Door Open (Passenger's Side Body Door Open)
- Rear Body Door Open
- DS Ladder Rack Down (Driver Side Ladder Rack Down)
- PS Ladder Rack Down (Passenger Side Ladder Rack Down)
- Deck Gun Not Stowed
- Lt Tower Not Stowed (Light Tower Not Stowed)
- Fold Tank Not Stowed (Fold-A-Tank Not Stowed)
- Aerial Not Stowed (Aerial Device Not Stowed)
- Stabilizer Not Stowed
- Steps Not Stowed
- Handrail Not Stowed

Any other device that is opened, extended, or deployed that creates a hazard or is likely to cause major damage to the apparatus if the apparatus is moved will be displayed as a caution message after the parking brake is disengaged.

SWITCH PANELS

The emergency light switch panel will have a master switch for ease of use plus individual switches for selective control. Each switch panel will contain eight (8) membrane-type switches each rated for one million (1,000,000) cycles. Panels containing less than eight (8) switch assignments will include non-functioning black appliqué. Documentation will be provided by the manufacturer indicating the rated cycle life of the switches. The switch panel(s) will be located in the overhead position above the windshield on the driver and passenger side overhead to allow for easy access.

Additional switch panel(s) will be located in the overhead position(s) above the windshield or in designated locations on the lower instrument panel layout.

The switches will be membrane-type and also act as an integral indicator light. For quick, visual indication the entire surface of the switch will be illuminated white whenever back lighting is activated and illuminated green whenever the switch is active. An active illuminated switch will flash when interlock requirements are not met or device is actively being load managed. For ease of use, a two (2)-ply, scratch resistant laser engraved Gravoply label indicating the use of each switch will be placed in the center of the switch. The label will allow light to pass through the letters for ease of use in low light conditions.

WIPER CONTROL

For simple operation and easy reach, the windshield wiper control will be an integral part of the directional light lever located on the steering column. The wiper control will include high and low wiper speed settings, a one (1)-speed intermittent wiper control and windshield washer switch. The control will have a "return to park" provision, which allows the wipers to return to the stored position when the wipers are not in use.

SPARE CIRCUIT

There will be two (2) pair of wires, including a positive and a negative, installed on the apparatus.

The above wires will have the following features:

- The positive wire will be connected directly to the battery power
- The negative wire will be connected to ground
- Wires will be protected to 15 amps at 12 volts DC
- Power and ground will terminate officer side dash area
- Termination will be with heat shrinkable butt splicing
- Wires will be sized to 125 percent of the protection

The circuit(s) may be load managed when the parking brake is set.

SPARE CIRCUIT

There will be one (1) dual USB fast charge socket mounts installed on the apparatus.

Columbia Heights Bid 941 Full Specification

The above wires will have the following features:

- The positive wire will be connected directly to the battery switched power.
- The negative wire will be connected to ground.
- Wires will be protected to 4.8 amps at 12 volts DC.
- The USB socket mount will be LS rear engine tunnel.
- Termination will be a Blue Sea Systems part number 1045 dual USB charger socket.
- Wires will be sized to 125% of the protection.

This circuit(s) may be load managed when the parking brake is applied.

SPARE CIRCUIT

There will be one (1) dual USB fast charge socket mounts installed on the apparatus.

The above wires will have the following features:

- The positive wire will be connected directly to the battery power.
- The negative wire will be connected to ground.
- Wires will be protected to 4.8 amps at 12 volts DC.
- The USB socket mount will be officer side lower panel.
- Termination will be a Blue Sea Systems part number 1045 dual USB charger socket.
- Wires will be sized to 125% of the protection.

This circuit(s) may be load managed when the parking brake is applied.

INFORMATION CENTER

An LCD display integral to the cab gauge panel will be included as outlined in the cab instrumentation area.

ADDITIONAL INFORMATION CENTER

An information center employing a 7.00" diagonal touch screen color LCD display will be encased in an ABS plastic housing and will be located on the in view of the driver per the instrument panel layout diagram.

The information center will have the following specifications:

- Operate in temperatures from -40 to 185 degrees Fahrenheit
- An Optical Gel will be placed between the LCD and protective lens
- Five weather resistant user interface switches
- Grey with black accents
- Sunlight Readable
- Linux operating system
- Minimum of 1000nits rated display
- Display can be changed to an available foreign language.
- Programmed to read US Customary

GENERAL SCREEN DESIGN

Where possible, background colors will be used to provide "At a Glance" vehicle information. If information provided on a screen is within acceptable limits, a green background will be used.

If a caution or warning situation arises the following will occur:

- An amber background/text color will indicate a caution condition
- A red background/text color will indicate a warning condition
- The information center will utilize an "Alert Center" to display text messages for audible alarm tones. The text messages will be written to identify the item(s) causing the audible alarm to sound. If more than one (1) text message occurs, the messages will cycle every second until the problem(s) have been resolved. The background color for the "Alert Center" will change to indicate the severity of the "warning" message. If a warning and a caution condition occur simultaneously, the red background color will be shown for all alert center messages.
- A label for each button will exist. The label will indicate the function for each active button for each screen. Buttons that are not utilized on specific screens will have a button label with no text or symbol.

HOME/TRANSIT SCREEN

This screen will display the following:

- Vehicle Mitigation (if equipped)
- Water Level (if equipped)
- Foam Level (if equipped)
- Seat Belt Monitoring Screen
- Tire Pressure Monitoring (if equipped)
- Digital Speedometer
- Active Alarms

ON SCENE SCREEN

This screen will display the following and will be auto activated with pump engaged (if equipped):

- Battery Voltage
- Fuel
- Oil Pressure
- Coolant Temperature
- RPM
- Water Level (if equipped)
- Foam Level (if equipped)
- Foam Concentration (if equipped)
- Water Flow Rate (if equipped)
- Water Used (if equipped)
- Active Alarms

VIRTUAL BUTTONS

There will be four (4) virtual switch panel screens that match the overhead and lower lighting and HVAC switch panels.

PAGE SCREEN

The page screen will display the following and allow the user to progress into other screens for further functionality:

- Diagnostics
 - Faults
 - Listed by order of occurrence
 - Allows to sort by system
 - Interlock
 - Throttle Interlocks
 - Pump Interlocks (if equipped)
 - Aerial Interlocks (if equipped)
 - PTO Interlocks (if equipped)
 - Load Manager
 - A list of items to be load managed will be provided. The list will provide a description of the load.
 - The lower the priority numbers the earlier the device will be shed should a low voltage condition occur.
 - The screen will indicate if a load has been shed (disabled) or not shed.
 - "At a glance" color features are utilized on this screen.
 - Systems
 - Command Zone
 - Module type and ID number
 - Module Version
 - Input or output number
 - Circuit number connected to that input or output
 - Status of the input or output
 - Power and Constant Current module diagnostic information
 - Foam (if equipped)
 - Pressure Controller (if equipped)
 - Generator Frequency (if equipped)
 - Live Data
 - General Truck Data
- Maintenance
 - Engine oil and filter
 - Transmission oil and filter
 - Water pump oil (if equipped)
 - Foam (if equipped)
 - Aerial (if equipped)
- Setup

Columbia Heights Bid 941 Full Specification

- Clock Setup
- Date & Time
 - 12 or 24 hour format
 - Set time and date
- Backlight
 - Daytime
 - Night time
 - Sensitivity
- Unit Selection
- Home Screen
- Virtual Button Setup
- On Scene Screen Setup
- Configure Video Mode
 - Set Video Contrast
 - Set Video Color
 - Set Video Tint
- Do Not Move
 - The screen will indicate the approximate location and type of item that is open or is not stowed for travel. The actual status of the following devices will be indicate
 - Driver Side Cab Door
 - Passenger's Side Cab Door
 - Driver Side Crew Cab Door
 - Passenger's Side Crew Cab Door
 - Driver Side Body Doors
 - Passenger's Side Body Doors
 - Rear Body Door(s)
 - Ladder Rack (if applicable)
 - Deck Gun (if applicable)
 - Light Tower (if applicable)
 - Hatch Door (if applicable)
 - Stabilizers (if applicable)
 - Steps (if applicable)
- Notifications
 - View Active Alarms
 - Shows a list of all active alarms including date and time of the occurrence is shown with each alarm
 - Silence Alarms - All alarms are silenced
- Timer Screen
- HVAC (if equipped)
- Tire Information (if equipped)
- Ascendant Set Up Information (if equipped)

Button functions and button labels may change with each screen.

COLLISION MITIGATION

There will be a HAAS Alert®, Model HA5 Responder-to-Vehicle (R2V) collision avoidance system provided on the apparatus. The HA5 cellular transponder module will be installed behind the cab windshield, as high and near to the center as practical, to allow clear visibility to the sky. The module dimensions are 5.40" long x 2.70" wide x 1.30" high, and operating temperature range is -40 degree C to 85 degree C.

The transponder will be connected to the vehicle's emergency master circuit and battery direct power and ground.

While responding with emergency lights on, the HA5 transponder sends alert messages via cellular network to motorists in the vicinity of the responding truck that are equipped with the WAZE app.

While on scene with emergency lights on, the HA5 transponder sends road hazard alerts to motorists in the vicinity of the truck that are equipped with the WAZE app.

The HA5 Responder-to-Vehicle (R2V) collision avoidance system will include the transponder and a 5 year cellular plan subscription.

Activation of the HAAS Alert system requires a representative of the customer to accept the End User License Agreement (EULA) via an on-line portal.

VEHICLE DATA RECORDER

There will be a vehicle data recorder (VDR) capable of reading and storing vehicle information provided.

The information stored on the VDR can be downloaded through a USB port mounted in a convenient location determined by cab model. A USB cable can be used to connect the VDR to a laptop to retrieve required information. The program to download the information from the VDR will be available to download on-line.

The vehicle data recorder will be capable of recording the following data via hardwired and/or CAN inputs:

- Vehicle Speed - MPH
- Acceleration - MPH/sec
- Deceleration - MPH/sec
- Engine Speed - RPM
- Engine Throttle Position - % of Full Throttle
- ABS Event - On/Off
- Seat Occupied Status - Yes/No by Position
- Seat Belt Buckled Status - Yes/No by Position
- Master Optical Warning Device Switch - On/Off
- Time - 24 Hour Time
- Date - Year/Month/Day

Seat Belt Monitoring System

A seat belt monitoring system (SBMS) will be provided on the Command Zone™ color display. The SBMS will be capable of monitoring up to 10 seating positions indicating the status of each seat position per the following:

- Seat Occupied & Buckled = Green LED indicator illuminated
- Seat Occupied & Unbuckled = Red LED indicator with audible alarm
- No Occupant & Buckled = Red LED indicator with audible alarm
- No Occupant & Unbuckled = No indicator and no alarm

The seat belt monitoring screen will become active on the Command Zone color display when:

- The home screen is active:
 - and there is any occupant seated but not buckled or any belt buckled with an occupant.
 - and there are no other Do Not Move Apparatus conditions present. As soon as all Do Not Move Apparatus conditions are cleared, the SBMS will be activated.

The SBMS will include an audible alarm that will warn that an unbuckled occupant condition exists and the parking brake is released, or the transmission is not in park.

TWO-WAY RADIO CABLE INSTALLATION

There will be one (1) customer supplied two-way radio remote head cable(s) sent to the apparatus manufacturers preferred radio installer for installation. The cable will be run tbd.

Specific shipping requirements will be followed.

TWO WAY RADIO SPEAKER INSTALLATION

There will be one (1) customer supplied two way radio speakers sent to the apparatus manufacturers preferred third party installer to be installed tbd.

Specific shipping requirements will be followed.

TWO WAY RADIO INSTALLATION

There will be one (1) customer supplied two way radio(s) sent to the apparatus manufacturers preferred radio installer to be installed tbd per the shipping document.

No antenna mount or whip will be included in this option.

Specific radio shipping requirements will be followed.

RADIO ANTENNA MOUNT

There will be one (1) standard 1.125", 18 thread antenna-mounting base(s) installed Right Side on the cab roof with high efficiency, low loss, coaxial cable(s) routed to behind the officer seat. A weatherproof cap will be installed on the mount.

VEHICLE CAMERA SYSTEM

There will be a color vehicle camera system provided with the following:

Columbia Heights Bid 941 Full Specification

- One (1) camera located at the rear of the apparatus, pointing rearward, displayed automatically with the vehicle in reverse

The camera images will be displayed on the driver's vehicle information center display. Audio from the microphone on the active camera will be not provided.

The following components will be included:

- One (1) SV-CW134639CAI, camera
- One (1) amplified speaker (if applicable)
- All necessary cables

ELECTRICAL POWER CONTROL SYSTEM

The primary power distribution will be located forward of the officer's seating position and be easily accessible while standing on the ground for simplified maintenance and troubleshooting. Additional electrical distribution centers will be provided throughout the vehicle to house the vehicle's electrical power, circuit protection, and control components. The electrical distribution centers will be located strategically throughout the vehicle to minimize wire length. For ease of maintenance, all electrical distribution centers will be easily accessible. All distribution centers containing fuses, circuit breakers and/or relays will be easily accessible.

Distribution centers located throughout the vehicle will contain battery powered studs for supplying customer installed equipment thus providing a lower cost of ownership.

Circuit protection devices, which conform to SAE standards, will be utilized to protect electrical circuits. All circuit protection devices will be rated per NFPA requirements to prevent wire and component damage when subjected to extreme current overload. General protection circuit breakers will be Type-I automatic reset (continuously resetting). When required, automotive type fuses will be utilized to protect electronic equipment. Control relays and solenoid will have a direct current rating of 125 percent of the maximum current for which the circuit is protected per NFPA.

SOLID-STATE CONTROL SYSTEM

A solid-state electronics based control system will be utilized to achieve advanced operation and control of the vehicle components. A fully computerized vehicle network will consist of electronic modules located near their point of use to reduce harness lengths and improve reliability. The control system will comply with SAE J1939-11 recommended practices.

The control system will operate as a master-slave system whereas the main control module instructs all other system components. The system will contain patented Mission Critical software that maintains critical vehicle operations in the unlikely event of a main controller error. The system will utilize a Real Time Operating System (RTOS) fully compliant with OSEK/VDX™ specifications providing a lower cost of ownership.

For increased reliability and simplified use the control system modules will include the following attributes:

- Green LED indicator light for module power

Columbia Heights Bid 941 Full Specification

- Red LED indicator light for network communication stability status
- Control system self test at activation and continually throughout vehicle operation
- No moving parts due to transistor logic
- Software logic control for NFPA mandated safety interlocks and indicators
- Integrated electrical system load management without additional components
- Integrated electrical load sequencing system without additional components
- Customized control software to the vehicle's configuration
- Factory and field re programmable to accommodate changes to the vehicle's operating parameters
- Complete operating and troubleshooting manuals
- USB connection to the main control module for advanced troubleshooting

To assure long life and operation in a broad range of environmental conditions, the solid-state control system modules will meet the following specifications:

- Module circuit board will meet SAE J771 specifications
- Operating temperature from -40C to +70C
- Storage temperature from -40C to +70C
- Vibration to 50g

IP67 rated enclosure (Totally protected against dust and also protected against the effect of temporary immersion between 15 centimeters and one (1) meter)

Operating voltage from eight (8) volts to 16 volts DC

The main controller will activate status indicators and audible alarms designed to provide warning of problems before they become critical.

CIRCUIT PROTECTION AND CONTROL DIAGRAM

Copies of all job-specific, computer network input and output (I/O) connections will be provided with each chassis. The sheets will indicate the function of each module connection point, circuit protection information (where applicable), wire numbers, wire colors and load management information.

ON-BOARD ADVANCED/VISUAL ELECTRICAL SYSTEM DIAGNOSTICS

The on-board information center will include the following diagnostic information:

- Text description of active warning or caution alarms
- Simplified warning indicators
- Amber caution indication with intermittent alarm
- Red warning indication with steady tone alarm

All control system modules, with the exception of the main control module, will contain on-board visual diagnostic LEDs that assist in troubleshooting. The LEDs will be enclosed within the sealed, transparent module housing near the face of the module. One LED for each input or output will be provided and will illuminate whenever the respective input or output is active. Color-coded labels within

the modules will encompass the LEDs for ease of identification. The LED indicator lights will provide point of use information for reduced troubleshooting time without the need for an additional computer.

TECH MODULE WITH WIFI

An in cab module will provide WiFi wireless interface and data logging capability. The WiFi interface will comply with IEEE 802.11 b/g/n capabilities while communicating at 2.4 Gigahertz. The module will provide an external antenna connection allowing a line of site communication range of up to 300 feet with a roof mounted antenna.

The module will transmit a password protected web page to a WiFi enabled device (i.e. most smart phones, tablets or laptops) allowing two levels of user interaction. The firefighter level will allow vehicle monitoring of the vehicle and firefighting systems on the apparatus. The technician level will allow diagnostic access to inputs and outputs installed on the Command Zone™, control and information system.

The data logging capability will record faults from the engine, transmission, ABS and Command Zone™, control and information systems as they occur. No other data will be recorded at the time the fault occurs. The data logger will provide up to 2 Gigabytes of data storage.

A USB connection will be provided on the Tech Module. It will provide a means to download data logger information and update software in the device.

PROGNOSTICS

A software based vehicle tool will be provided to predict remaining life of the vehicles critical fluid and events.

The system will send automatic indications to the Command Zone, color display and/or wireless enabled device to proactively alert of upcoming service intervals.

Prognostics will include:

- Engine oil and filter
- Transmission oil and filter
- Pump oil (if equipped)
- Foam oil (if equipped)
- Aerial oil and filter (if equipped)

ADVANCED DIAGNOSTICS

An advanced, Windows-based, diagnostic software program will be provided for this control system. The software will provide troubleshooting tools to service technicians equipped with a Windows-based computer or wireless enabled device.

The service and maintenance software will be easy to understand and use and have the ability to view system input/output (I/O) information.

INDICATOR LIGHT AND ALARM PROVE-OUT SYSTEM

A system will be provided which automatically tests basic indicator lights and alarms located on the cab instrument panel.

VOLTAGE MONITOR SYSTEM

A voltage monitoring system will be provided to indicate the status of the battery system connected to the vehicle's electrical load. The system will provide visual and audible warning when the system voltage is below or above optimum levels.

The alarm will activate if the system falls below 11.8 volts DC for more than two (2) minutes.

DEDICATED RADIO EQUIPMENT CONNECTION POINTS

There will be three (3) studs provided in the primary power distribution center located in front of the officer for two-way radio equipment.

- The studs will consist of the following:
- 12-volt 40-amp battery switched power
- 12-volt 60-amp ignition switched power
- 12-volt 60-amp direct battery power

There will also be a 12-volt 100-amp ground stud located in or adjacent to the power distribution center.

ENHANCED SOFTWARE

The solid-state control system will include the following software enhancements:

All perimeter lights and scene lights (where applicable) will be deactivated when the parking brake is released.

Cab and crew cab dome lights will remain on for ten (10) seconds for improved visibility after the doors close. The dome lights will dim after ten (10) seconds or immediately if the vehicle is put into gear.

Cab and crew cab perimeter lights will remain on for ten (10) seconds for improved visibility after the doors close. The dome lights will dim after ten (10) seconds or immediately if the vehicle is put into gear.

EMI/RFI PROTECTION

To prevent erroneous signals from crosstalk contamination and interference, the electrical system will meet, at a minimum, SAE J551/2, thus reducing undesired electromagnetic and radio frequency emissions. An advanced electrical system will be used to ensure radiated and conducted electromagnetic interference (EMI) or radio frequency interference (RFI) emissions are suppressed at their source.

The apparatus will have the ability to operate in the electromagnetic environment typically found in fire ground operations to ensure clean operations. The electrical system will meet, without exceptions, electromagnetic susceptibility conforming to SAE J1113/25 Region 1, Class C EMR for 10KHz-1GHz to 100 Volts/Meter. The vehicle OEM, upon request, will provide EMC testing reports from testing

conducted on an entire apparatus and will certify that the vehicle meets SAE J551/2 and SAE J1113/25 Region 1, Class C EMR for 10KHz-1GHz to 100 Volts/Meter requirements.

EMI/RFI susceptibility will be controlled by applying appropriate circuit designs and shielding. The electrical system will be designed for full compatibility with low-level control signals and high-powered two-way radio communication systems. Harness and cable routing will be given careful attention to minimize the potential for conducting and radiated EMI/RFI susceptibility.

ELECTRICAL

All 12-volt electrical equipment installed by the apparatus manufacturer will conform to modern automotive practices. All wiring will be high temperature crosslink type. Wiring will be run, in loom or conduit, where exposed and have grommets where wire passes through sheet metal. Automatic reset circuit breakers will be provided which conform to SAE Standards. Wiring will be color, function and number coded. Function and number codes will be continuously imprinted on all wiring harness conductors at 2.00" intervals. Exterior exposed wire connectors will be positive locking, and environmentally sealed to withstand elements such as temperature extremes, moisture and automotive fluids.

Electrical wiring and equipment will be installed utilizing the following guidelines:

1. All holes made in the roof will be caulked with silicon. Large fender washers, liberally caulked, will be used when fastening equipment to the underside of the cab roof.
2. Any electrical component that is installed in an exposed area will be mounted in a manner that will not allow moisture to accumulate in it. Exposed area will be defined as any location outside of the cab or body.
3. Electrical components designed to be removed for maintenance will not be fastened with nuts and bolts. Metal screws will be used in mounting these devices. Also a coil of wire will be provided behind the appliance to allow them to be pulled away from mounting area for inspection and service work.
4. Corrosion preventative compound will be applied to all terminal plugs located outside of the cab or body. All non-waterproof connections will require this compound in the plug to prevent corrosion and for easy separation (of the plug).
5. All lights that have their sockets in a weather exposed area will have corrosion preventative compound added to the socket terminal area.
6. All electrical terminals in exposed areas will have silicon (1890) applied completely over the metal portion of the terminal.

All lights and reflectors, required to comply with Federal Motor Vehicle Safety Standard #108, will be furnished. Rear identification lights will be recessed mounted for protection. Lights and wiring mounted in the rear bulkheads will be protected from damage by installing a false bulkhead inside the rear compartments.

An operational test will be conducted to ensure that any equipment that is permanently attached to the electrical system is properly connected and in working order.

The results of the tests will be recorded and provided to the purchaser at time of delivery.

BATTERY SYSTEM

There will be four (4) 12 volt Exide®, Model 31S950X3W, batteries that include the following features will be provided:

- 950 CCA, cold cranking amps
- 190 amp reserve capacity
- High cycle
- Group 31
- Rating of 3800 CCA at 0 degrees Fahrenheit
- 760 minutes of reserve capacity
- Threaded stainless steel studs

Each battery case will be a black polypropylene material with a vertically ribbed container for increased vibration resistance. The cover will be manifold vented with a central venting location to allow a 45 degree tilt capacity.

The inside of each battery will consist of a "maintenance free" grid construction with poly wrapped separators and a flooded epoxy bottom anchoring for maximum vibration resistance.

BATTERY SYSTEM

There will be a single starting system with an ignition switch and starter button provided and located on the cab instrument panel.

MASTER BATTERY SWITCH

There will be a master battery switch provided within the cab within easy reach of the driver to activate the battery system.

An indicator light will be provided on the instrument panel to notify the driver of the status of the battery system.

BATTERY COMPARTMENTS

The batteries will be stored in well-ventilated compartments that are located under the cab and bolted directly to the chassis frame. The battery compartments will be constructed of 3/16" steel plate and be designed to accommodate a maximum of three (3) group 31 batteries in each compartment. The compartments will include formed fit heavy-duty roto-molded polyethylene battery tray inserts with drains on each side of the frame rails. The batteries will be mounted inside of the roto-molded trays.

JUMPER STUDS

One (1) set of battery jumper studs with plastic color-coded covers will be installed on the battery box on the driver's side. This will allow enough room for easy jumper cable access.

BATTERY CHARGER/ AIR COMPRESSOR

There will be a Kussmaul™ Pump Plus 1200, Model # 52-21-1100, single output battery charger/air compressor system will be provided. A display bar graph indicating the state of charge will be included.

The automatic charger will maintain one (1) set of batteries with a maximum output current of 40 amps.

Columbia Heights Bid 941 Full Specification

The 12-volt air compressor will be installed to maintain the air system pressure when the vehicle is not in use.

There will be an auto pump timer installed between the pressure switch and the pump that will allow the pump to run for one hour than shut down for one hour.

The battery charger will be wired to the AC shoreline inlet through an AC receptacle adjacent to this battery charger.

Battery charger/compressor will be located behind the driver's seat.

The battery charger indicator will be located behind the driver's door on the outside of the cab.

SHORELINE

There will be a 20 amp 120 volt AC straight blade shoreline inlet provided to operate the dedicated 120 volt AC circuits on the apparatus without the use of the generator.

The shoreline inlet will include a red flip up cover.

The shoreline(s) will be connected to battery charger.

There will be a mating connector body supplied with the loose equipment.

There will be a label installed near the inlet(s) that state the following:

- Line Voltage
- Current Rating (amps)
- Phase
- Frequency

The shoreline receptacle will be located in the driver side lower step well of cab.

GENERATOR TO SHORELINE TRANSFER SWITCH

There will be an automatic transfer switch between the onboard generator and the shoreline inlet. The loads connected to the transfer switch will be power from the onboard generator when the generator is running.

ALTERNATOR

A Delco Remy®, Model 55SI, alternator will be provided. It will have a rated output current of 430 amps, as measured by SAE method J56. The alternator will feature an integral regulator and rectifier system that has been tested and qualified to an ambient temperature of 257 degrees Fahrenheit (125 degrees Celsius). The alternator will be connected to the power and ground distribution system with heavy-duty cables sized to carry the full rated alternator output.

ELECTRONIC LOAD MANAGER

An electronic load management (ELM) system will be provided that monitors the vehicles 12-volt electrical system, automatically reducing the electrical load in the event of a low voltage condition, and

automatically restoring the shed electrical loads when a low voltage condition expires. This ensures the integrity of the electrical system.

For improved reliability and ease of use, the load manager system will be an integral part of the vehicle's solid state control system requiring no additional components to perform load management tasks. Load management systems which require additional components will not be allowed.

The system will include the following features:

- System voltage monitoring.
- A shed load will remain inactive for a minimum of five minutes to prevent the load from cycling on and off.
- Sixteen available electronic load shedding levels.
- Priority levels can be set for individual outputs.
- High Idle to activate before any electric loads are shed and deactivate with the service brake.
 - If enabled:
 - "Load Man Hi-Idle On" will display on the information center.
 - Hi-Idle will not activate until 30 seconds after engine start up.
- Individual switch "on" indicator to flash when the particular load has been shed.
- The information center indicates system voltage.

The information center, where applicable, includes a "Load Manager" screen indicating the following:

- Load managed items list, with priority levels and item condition.
- Individual load managed item condition:
 - ON = not shed
 - SHED = shed

SEQUENCER

A sequencer will be provided that automatically activates and deactivates vehicle loads in a preset sequence thereby protecting the alternator from power surges. This sequencer operation will allow a gradual increase or decrease in alternator output, rather than loading or dumping the entire 12 volt load to prolong the life of the alternator.

For improved reliability and ease of use, the load sequencing system will be an integral part of the vehicle's solid state control system requiring no additional components to perform load sequencing tasks. Load sequencing systems which require additional components will not be allowed.

Emergency light sequencing will operate in conjunction with the emergency master light switch. When the emergency master switch is activated, the emergency lights will be activated one by one at half-second intervals. Sequenced emergency light switch indicators will flash while waiting for activation.

When the emergency master switch is deactivated, the sequencer will deactivate the warning light loads in the reverse order.

Sequencing of the following items will also occur, in conjunction with the ignition switch, at half-second intervals:

Columbia Heights Bid 941 Full Specification

- Cab Heater and Air Conditioning
- Crew Cab Heater (if applicable)
- Crew Cab Air Conditioning (if applicable)
- Exhaust Fans (if applicable)
- Third Evaporator (if applicable)

HEADLIGHTS

There will be a HiViz part number FT-4X6-4KIT, that includes four (4) 4.00" high x 6.00" long rectangular LED lights with parking lamp illumination around the outside of the lamps mounted in the front quad style, chrome housing on each side of the cab grille:

- the outside lamp on each side will contain a part number FT-4X6-HL with low beam LEDs
- the inside lamp on each side will contain a part number FT-4X6-H with high beam LEDs
- the lights will be controlled through the headlight switch

DIRECTIONAL LIGHTS

There will be two (2) Whelen 600® series, LED combination directional/marker lights provided. The lights will be located on the outside cab corners, next to the headlights.

The color of the lenses will be clear.

INTERMEDIATE LIGHT

There will be two (2) Weldon, Model 9186-8580-29, amber LED turn signal marker lights furnished, one (1) each side, in the rear fender panel. The light will double as a turn signal and marker light.

CAB CLEARANCE/MARKER/ID LIGHTS

There will be seven (7) amber LED lights provided to indicate the presence and overall width of the vehicle in the following locations:

- Three (3) amber LED identification lights will be installed in the center of the cab above the windshield.
- Two (2) amber LED clearance lights will be installed, one (1) on each outboard side of the cab above the windshield.
- Two (2) amber LED marker lights will be installed, one (1) on each side above the cab doors.

REAR CLEARANCE/MARKER/ID LIGHTING

There will be a three (3) LED light bar used as identification lights located at the rear of the apparatus per the following:

- As close as practical to the vertical centerline
- Centers spaced not less than 6.00" or more than 12.00" apart
- Red in color
- All at the same height

Columbia Heights Bid 941 Full Specification

There will be two (2) LED lights installed at the rear of the apparatus used as clearance lights located at the rear of the apparatus per the following:

- To indicate the overall width of the vehicle
- One (1) each side of the vertical centerline
- As near the top as practical
- Red in color
- To be visible from the rear
- All at the same height

There will be two (2) LED lights installed on the side of the apparatus used as marker lights as close to the rear as practical per the following:

- To indicate the overall length of the vehicle
- One (1) each side of the vertical centerline
- As near the top as practical
- Red in color
- To be visible from the side
- All at the same height

There will be two (2) red reflectors located on the rear of the truck facing to the rear. One (1) each side, as far to the outside as practical, at a minimum of 15.00", but no more than 60.00", above the ground.

There will be two (2) red reflectors located on the side of the truck facing to the side. One (1) each side, as far to the rear as practical, at a minimum of 15.00", but no more than 60.00", above the ground.

Per FMVSS 108 and CMVSS 108 requirements.

REAR FMVSS LIGHTING

The rear stop/tail and directional LED lighting will consist of the following:

- Two (2) Whelen®, Model M6BTT, red LED stop/tail lights
- Two (2) Whelen, Model M6T, amber LED arrow turn lights

The lights will be provided with clear lenses.

The lights will be mounted in a polished combination housing.

There will be two (2) Whelen Model M6BUW, LED backup lights provided in the tail light housing.

LICENSE PLATE BRACKET

One (1) license plate bracket constructed of stainless steel will be provided at the rear of the apparatus.

One (1) white LED light will be provided to illuminate the license plate. A stainless steel light shield will be provided over the light that will direct illumination downward, preventing white light to the rear.

LIGHTING BEZEL

There will be two (2) Whelen, Model M6FCV4P, four (4) place chromed ABS housings with Pierce logos provided for the rear M6 series stop/tail, directional, back up, scene lights or warning lights.

BACK-UP ALARM

A PRECO, Model 1040, solid-state electronic audible back-up alarm that actuates when the truck is shifted into reverse will be provided. The device will sound at 60 pulses per minute and automatically adjust its volume to maintain a minimum ten (10) dBA above surrounding environmental noise levels.

CAB PERIMETER SCENE LIGHTS

There will be four (4) Amdor, Model AY-LB-12HW020, 350 lumens each, 20.00" white LED strip lights provided, one (1) for each cab door.

These lights will be activated automatically when the battery switch is on and the exit doors are opened or by the same means as the body perimeter scene lights.

PUMP HOUSE PERIMETER LIGHTS

There will be two (2) Amdor, Model AY-LB-12HW020, 350 lumens each, 20.00" LED weatherproof strip lights with brackets provided under the pump panel running boards, one (1) each side.

If the combination of options in the vehicle does not permit clearance for a 20.00" light, a 12.00" version of the Amdor light will be installed.

The lights will be controlled by the same means as the body perimeter lights.

BODY PERIMETER SCENE LIGHTS

There will be two (2) Amdor, Model AY-LB-12HW020, 350 lumens, 20.00" long, white LED's, 12 volt DC lights provided at the rear step area of the body, one (1) each side shining to the rear.

The perimeter scene lights will be activated when the parking brake is applied.

STEP LIGHTS

There will be four (4) white LED, step lights provided. One (1) step light will be provided on each side, on the front compartment face and two (2) step lights at the rear to illuminate the tailboard.

In order to ensure exceptional illumination, each light will provide a minimum of 25 foot-candles (fc) covering an entire 15" x 15" square placed ten (10) inches below the light and a minimum of 1.5 fc covering an entire 30" x 30" square at the same ten (10) inch distance below the light.

These step lights will be actuated when the ignition switch is on and the parking brake is set.

All other steps on the apparatus will be illuminated per the current edition of NFPA 1901.

LIGHT GUARD

There will be two (2) aluminum treadplate guard(s), provided to protect the HiViz light bar(s), LS and RS catwalks .

12 VOLT LIGHTING

There will be one (1) HiViz Model FT-MB-33-**-*, 2.56" high x 42.44" long x 2.45" deep 12,210 effective lumens 12 volt DC LED light(s) with a combination of flood and spot optics provided on the front visor, centered.

The painted parts of the light housing and brackets to be white.

The light(s) will be controlled by a switch at the driver's side switch panel.

The light(s) may be load managed when the parking brake is applied.

12 VOLT LIGHTING

There will be one (1) HiViz®, Model FT-GESM, 12,290 effective lumens 8.65" high x 10.61" wide x 2.78" deep light(s) with white LEDs installed on the cab high and aft LS crew door. The light(s) to include white bezel and chrome optic holder.

The light(s) will be activated by a switch at the driver's side switch panel and by a switch at the driver's side pump panel.

The light(s) may be load managed when the parking brake is applied.

12 VOLT LIGHTING

There will be one (1) HiViz®, Model FT-GESM, 12,290 effective lumens 8.65" high x 10.61" wide x 2.78" deep light(s) with white LEDs installed on the cab high and aft RS crew door. The light(s) to include white bezel and chrome optic holder.

The light(s) will be activated by a switch at the driver's side switch panel and by a switch at the driver's side pump panel.

The light(s) may be load managed when the parking brake is applied.

12 VOLT LIGHTING

There will one (1) HiViz Model FT-MB-2.18-**-*, 11,386 effective lumens 2.75" high x 20.60" long x 3.31" deep light(s) with white LEDs and a combination of flood and spot optics located, catwalk above RS2.

The painted parts of the light housing and brackets to be white.

The light(s) will be controlled by the same switching that has been selected for the other side scene light(s) on the apparatus.

The light(s) may be load managed when the parking brake is applied.

12 VOLT LIGHTING

There will one (1) HiViz Model FT-MB-2.18-**-*, 11,386 effective lumens 2.75" high x 20.60" long x 3.31" deep light(s) with white LEDs and a combination of flood and spot optics located, catwalk above LS2.

The painted parts of the light housing and brackets to be white.

Columbia Heights Bid 941 Full Specification

The light(s) will be controlled by the same switching that has been selected for the other side scene light(s) on the apparatus.

The light(s) may be load managed when the parking brake is applied.

HOSE BED LIGHTS

There will be white 12 volt DC LED light strips with stainless steel protective cover, provided to light the hose bed area. Hose Bed lights will meet the photometric levels listed in NFPA 1901 for Hose Bed lighting requirements.

- Light strip(s) will be installed along the upper edge of the left side of the hose bed.
- Light strip(s) will be installed along the upper edge of the right side of the hose bed.

The lights will be activated by a cup switch at the rear of the apparatus no more than 72.00" from the ground.

REAR SCENE LIGHT(S)

There will be two (2) HiViz item FT-GSMJR-*, 5.04" high x 7.40" wide x 1.54" deep 5,000 raw lumens light(s) with white LEDs chrome trim and chrome optic holder(s) surface mounted at the rear of the apparatus, LS and RS Rear bulkhead .

The light(s) will be controlled by a switch at the driver's side switch panel, by a switch at the driver's side pump panel and by a cup switch at the driver's side rear bulkhead.

The light(s) may be load managed when the parking brake is applied.

WALKING SURFACE LIGHT

There will be Model FRP, 4" round black 12 volt DC LED floodlight(s) with bolt mount provided to illuminate the entire designated walking surface on top of the body.

The light(s) will be activated when the body step lights are on.

WATER TANK

Booster tank will have a capacity of 500 gallons and be constructed of polypropylene plastic by United Plastic Fabricating, Incorporated.

Tank joints and seams will be nitrogen welded inside and out.

Tank will be baffled in accordance with NFPA Bulletin 1901 requirements.

Baffles will have vent openings at both the top and bottom to permit movement of air and water between compartments.

Longitudinal partitions will be constructed of .38" polypropylene plastic and will extend from the bottom of the tank through the top cover to allow for positive welding.

Transverse partitions will extend from 4.00" off the bottom of the tank to the underside of the top cover.

All partitions will interlock and will be welded to the tank bottom and sides.

Columbia Heights Bid 941 Full Specification

Tank top will be constructed of .50" polypropylene. It will be recessed .38" and will be welded to the tank sides and the longitudinal partitions.

Tank top will be sufficiently supported to keep it rigid during fast filling conditions.

Construction will include 2.00" polypropylene dowels spaced no more than 30.00" apart and welded to the transverse partitions. Two (2) of the dowels will be drilled and tapped (.50" diameter, 13.00" deep) to accommodate lifting eyes.

A sump that will be sized dependent on the tank to pump plumbing will be provided at the bottom of the water tank.

Sump will include a drain plug and the tank outlet.

Tank will be installed in a fabricated cradle assembly constructed of structural steel.

Sufficient crossmembers will be provided to properly support bottom of tank. Crossmembers will be constructed of steel bar channel or rectangular tubing.

Tank will "float" in cradle to avoid torsional stress caused by chassis frame flexing. Rubber cushions, .50" thick x 3.00" wide, will be placed on all horizontal surfaces that the tank rests on.

Stops or other provision will be provided to prevent an empty tank from bouncing excessively while moving vehicle.

Mounting system will be approved by the tank manufacturer.

Fill tower will be constructed of .50" polypropylene and will be a minimum of 8.00" wide x 14.00" long.

Fill tower will be furnished with a .25" thick polypropylene screen and a hinged cover.

An overflow pipe, constructed of 4.00" schedule 40 polypropylene, will be installed approximately halfway down the fill tower and extend through the water tank and exit to the rear of the rear axle.

SLEEVE, PLUMBING, THROUGH TANK

Two (2) sleeves will be provided in the water tank for a 3.00" pipe to the rear.

HOSE BED

The hose bed will be fabricated of .125"-5052 aluminum with a nominal 38,000 psi tensile strength.

Upper and rear edges of side panels will have a double break for rigidity.

The upper inside area of the beavertails will be covered with brushed stainless steel to prevent damage to painted surface when hose is removed.

Flooring of the hose bed will be removable aluminum grating with the top surface corrugated to aid in hose aeration. The grating slats will be a minimum of 0.50" x 4.50" with spacing between slats for hose ventilation.

Hose bed will accommodate HB#1 800' 5", HB#2 500' 2.5", HB#3 200' 2.5" pre-connected BlitzFire.

HOSE BED DIVIDER

Two (2) adjustable hosebed dividers will be furnished for separating hose.

Each divider will be constructed of a .125" brushed aluminum sheet fitted and fastened into a slotted, 1.50" diameter radiused extrusion along the top, bottom, and rear edge.

Divider will be fully adjustable by sliding in tracks, located at the front and rear of the hose bed.

Divider will be held in place by tightening bolts, at each end.

Acorn nuts will be installed on all bolts in the hose bed which have exposed threads.

MONITOR STORAGE IN HOSEBED

A storage compartment, constructed from aluminum treadplate will be furnished in the hosebed for storage of a Blitzfire XXC-32 portable monitor. The compartment dimensions will be 10"x10"x32". The front of the compartment will be beveled at 45 degrees. A strap will be furnished at the rear to keep the monitor in the stored position.

The compartment will be located in Hosebed #3.

A cross-divider will be provided just behind the fill tower. The divider will be bolted to the side sheet.

HOSE BED COVER

A two (2) section hose bed cover, constructed of .125" bright aluminum treadplate will be furnished. The cover will be hinged with full length stainless steel piano hinge. The sides will be slanted down.

The cover will be reinforced so that it can support the weight of a man walking on the cover.

The cover is designed with the left cover opening first.

If access to the water tank fill tower is blocked by the hose bed cover, then a hinged door will be provided in it so that the tank may be filled without raising cover doors.

Chrome grab handles and four (4) gas filled cylinders will be provided to assist in opening and closing the cover. A handrail is to be provided at the rear, in the center of the support, to assist in opening the cover.

HOSEBED END FLAP

A pair of black vinyl flaps will be installed on the rear, one (1) for each of the aluminum treadplate hose bed covers.

Each vinyl flap will have three (3) nylon tie down straps, with quick release thumb spring buckles. Fasnep model 207668 stainless steel buckles will be attached to the flaps. These vinyl end skirts will be installed directly to the hosebed frame.

Rubber coated hooks and stainless steel footman loops will secure the end skirts/bed covers to the main body.

RUNNING BOARDS

Running boards will be fabricated of .125" bright aluminum treadplate.

Each running board will be supported by a welded 2.00" square tubing and channel assembly, which will be bolted to the pump compartment substructure.

Running boards will be 12.75" deep and spaced .50" away from the pump panel.

A splash guard will be provided above the running board treadplate.

TAILBOARD

The tailboard will also be constructed of .125" bright aluminum treadplate and spaced .50" from the body, as well as supported by a structural steel assembly.

The tailboard area will be 24.00" deep in the center area and 8.00" deep to the rear of the side compartments. The tailboard will be T-shaped. The outboard sides of the tailboard will be angled at 45 degrees beginning at the point where the body meets the tailboard at the outboard edge angling rearward to the rear edge of the tailboard.

The exterior side will be flanged down and in for increased rigidity of tailboard structure.

REAR WALL, SMOOTH ALUMINUM/BODY MATERIAL

The rear facing surfaces of the center rear wall will be smooth aluminum.

The bulkheads, the surface to the rear of the side body compartments, will be smooth and the same material as the body.

Any inboard facing surfaces below the height of the hosebed will be aluminum diamondplate.

TOW BAR

A tow bar will be installed under the tailboard at center of truck.

Tow bar will be fabricated of 1.00" CRS bar rolled into a 3.00" radius.

Tow bar assembly will be constructed of .38" structural angle. When force is applied to the bar, it will be transmitted to the frame rail.

Tow bar assembly will be designed and positioned to allow up to a 30-degree upward angled pull of 17,000 lb, or a 20,000 lb straight horizontal pull in line with the centerline of the vehicle.

Tow bar design will have been fully tested and evaluated using strain gauge testing and finite element analysis techniques.

RUNNING BOARD HOSE RESTRAINT

A pair of 2.00" wide black nylon straps with Velcro fasteners will be provided for each hose tray to secure the hose during travel. There will be One (1) hose tray located in the right side running board.

HOSE TRAY

One (1) hose tray will be recessed in the right side running board.

Capacity of the tray will be 25' of 5.00" hose.

Rubber matting will be installed on the floor of the tray to provide proper ventilation.

COMPARTMENTATION

Body and compartments will be fabricated of .125", 5052-H32 aluminum.

Side compartments will be an integral assembly with the rear fenders.

Circular fender liners will be provided for prevention of rust pockets and ease of maintenance.

Side compartment flooring will be of the sweep out design with the floor higher than the compartment door lip.

The side compartment door opening will be framed by flanging the edges in 1.75" and bending out again .75" to form an angle.

Drip protection will be provided above the doors by means of bright aluminum extrusion, formed bright aluminum treadplate or polished stainless steel.

The top of the compartment will be covered with bright aluminum treadplate rolled over the edges on the front, rear and outward side. These covers will have the corners welded.

Side compartment covers will be separate from the compartment tops.

Front facing compartment walls will be covered with bright aluminum treadplate.

All screws and bolts which protrude into a compartment will have acorn nuts on the ends to prevent injury.

UNDERBODY SUPPORT SYSTEM

Due to the severe loading requirements of this pumper a method of body and compartment support suitable for the intended load will be provided.

The backbone of the support system will be the chassis frame rails which is the strongest component of the chassis and is designed for sustaining maximum loads.

The support system will include .375" thick steel vertical angle supports bolted to the chassis frame rails with .625" diameter bolts.

Attached to the bottom of the steel vertical angles will be horizontal angles, with gussets welded to the vertical members, which extend to the outside edge of the body.

A steel frame will be mounted on the top of these supports to create a floating substructure which will result in a 500 lb equipment support rating per lower compartment.

The floating substructure will be separated from the horizontal members with neoprene elastomer isolators. These isolators will reduce the natural flex stress of the chassis from being transmitted to the body.

Isolators will have a broad load range, proven viability in vehicular applications, be of a fail safe design and allow for all necessary movement in three (3) transitional and rotational modes.

The neoprene isolators will be installed in a modified V three (3)-point mounting pattern to reduce the natural flex of the chassis being transmitted to the body.

AGGRESSIVE WALKING SURFACE

All exterior surfaces designated as stepping, standing, and walking areas will comply with the required average slip resistance of the current NFPA standards.

LOUVERS

Louvers will be stamped into compartment walls to provide the proper airflow inside the body compartments and to prevent water from dripping into the compartment. Where these louvers are provided, they will be formed into the metal and not added to the compartment as a separate plate.

TESTING OF BODY DESIGN

Body structural analysis has been fully tested. Proven engineering and test techniques such as finite element analysis, stress coating and strain gauging have been performed with special attention given to fatigue, life and structural integrity of the cab, body and substructure.

Body will be tested while loaded to its greatest in-service weight.

The criteria used during the testing procedure will include:

- Raising opposite corners of the vehicle tires 9.00" to simulate the twisting a truck may experience when driving over a curb.
- Making a 90 degree turn, while driving at 20 mph to simulate aggressive driving conditions.
- Driving the vehicle at 35 mph on a washboard road.
- Driving the vehicle at 55 mph on a smooth road.
- Accelerating the vehicle fully, until reaching the approximate speed of 45 mph on rough pavement.

Evidence of actual testing techniques will be made available upon request.

LEFT SIDE COMPARTMENTATION

The left side compartmentation will consist of three rollup door compartments.

A full height, rollup door compartment ahead of the rear wheels will be provided. The interior dimensions of this compartment will be 34.50" wide x 65.13" high x 25.88" deep. The clear door opening will be a minimum of 28.75" wide x 56.88" high.

A rollup door compartment over the rear wheels will be provided. The interior dimensions of this compartment will be 66.50" wide x 31.38" high x 25.88" deep. The clear door opening will be a minimum of 58.25" wide x 23.13" high.

A full height, rollup door compartment behind the rear wheels will be provided. The interior dimensions of this compartment will be 47.75" wide x 66.13" high x 25.88" deep. The clear door opening will be a minimum of 44.75" wide x 57.88" high.

Columbia Heights Bid 941 Full Specification

The interior height of the compartments will be measured from the compartment floor to the ceiling. The spool of the rollup door at the top of the compartment takes up some usable space. The depth of the compartments will be measured from the back wall to the inside of the door frame.

Closing of the door will not require releasing, unlocking, or unlatching any mechanism and will easily be accomplished with one hand.

RIGHT SIDE COMPARTMENTATION

The right side compartmentation will consist of three rollup door compartments.

A full height, rollup door compartment ahead of the rear wheels will be provided. The interior dimensions of this compartment will be 34.50" wide x 66.63" high x 25.88" deep in the lower 25.00" of the compartment and 12.00" deep in the remaining upper portion. The clear door opening will be a minimum of 28.75" wide x 56.88" high.

A rollup door compartment over the rear wheels will be provided. The interior dimensions of this compartment will be 66.50" wide x 32.88" high x 12.00" deep. The clear door opening will be a minimum of 58.25" wide x 23.13" high.

A full height, rollup door compartment behind the rear wheels will be provided. The interior dimensions of this compartment will be 47.75" wide x 67.63" high x 25.88" deep in the lower 26.00" of height and 12.00" deep in the remaining upper section of the compartment. The clear door opening will be a minimum of 44.75" wide x 57.88" high.

The interior height of the compartments will be measured from the compartment floor to the ceiling. The spool of the rollup door at the top of the compartment takes up some usable space. The depth of the compartments will be measured from the back wall to the inside of the door frame.

Closing of the door will not require releasing, unlocking, or unlatching any mechanism and will easily be accomplished with one hand.

SIDE COMPARTMENT ROLLUP DOOR(S)

There will be six (6) compartment doors installed on the side compartments. The doors will be double faced aluminum construction, painted one (1) color to match the lower portion of the body and manufactured by Gortite®.

Lath sections will be an interlocking rib design and will be individually replaceable without complete disassembly of door.

Between each slat at the pivoting joint will be a PVC inner seal to prevent metal to metal contact and prevent dirt or moisture from entering the compartments. Seals will allow door to operate in extreme temperatures ranging from 180 to -40 degrees Fahrenheit. Side, top and bottom seals will be provided to resist ingress of dirt and weather and be made of Santoprene.

All hinges, barrel clips and end pieces will be nylon 66. All nylon components will withstand temperatures from 300 to -40 degrees Fahrenheit.

Columbia Heights Bid 941 Full Specification

A polished stainless steel lift bar to be provided for each roll-up door. Lift bar will be located at the bottom of door and have latches on the outer extrusion of the doors frame. A ledge will be supplied over lift bar for additional area to aid in closing the door.

Doors will be constructed from an aluminum box section. The exterior surface of each slat will be flat. The interior surfaces will be concave to provide strength and prevent loose equipment from jamming the door from inside.

To conserve space in the compartments, the spring roller assembly will not exceed 3.00" in diameter.

The header for the rollup door assembly will not exceed 4.00".

A heavy-duty magnetic switch will be used for control of open compartment door warning lights.

REAR COMPARTMENTATION

A roll-up door compartment above the rear tailboard will be provided.

The interior dimensions of this compartment will be 40.00" wide x 33.63" high x 25.88" deep. The spool of the rollup door at the top of the compartment takes up some usable space. The depth of the compartment will be calculated with the compartment door closed.

A louvered, removable access panel will be furnished on the back wall of the compartment.

The rear compartment will be open into the rear side compartments.

The clear door opening of this compartment will be a minimum of 33.25" wide x 23.88" high.

Closing of the door will not require releasing, unlocking, or unlatching any mechanism and will easily be accomplished with one hand.

ROLLUP REAR COMPARTMENT DOOR

There will be a rear rollup door. The door will be double faced aluminum construction, an anodized satin finish and manufactured by Gortite®.

Lath sections will be an interlocking rib design and will be individually replaceable without complete disassembly of door.

Between each slat at the pivoting joint will be a PVC inner seal to prevent metal to metal contact and prevent dirt or moisture from entering the compartments. Seals will allow door to operate in extreme temperatures ranging from 180 to -40 degrees Fahrenheit. Side, top and bottom seals will be provided to resist ingress of dirt and weather and be made of Santoprene.

All hinges, barrel clips and end pieces will be nylon 66. All nylon components will withstand temperatures from 300 to -40 degrees Fahrenheit.

A polished stainless steel lift bar to be provided for each roll-up door. Lift bar will be located at the bottom of door and have latches on the outer extrusion of the doors frame. A ledge will be supplied over lift bar for additional area to aid in closing the door.

Columbia Heights Bid 941 Full Specification

Door will be constructed from an aluminum box section. The exterior surface of each slat will be flat. The interior surface will be concave to provide strength and prevent loose equipment from jamming the door from inside.

To conserve space in the compartments, the spring roller assembly will not exceed 3.00" in diameter.

The header for the rollup door assembly will not exceed 4.00".

A heavy-duty magnetic switch will be used for control of open compartment door warning lights.

DOOR GUARD

There will be seven (7) compartment doors that will include a guard/drip pan designed to protect the rollup door from damage when in the retracted position and contain any water spray. The guard will be fabricated from stainless steel and installed left side rearward compartment, left side over the wheel compartment, left side forward compartment, right side rearward compartment, right side over the wheel compartment, right side forward compartment and rear compartment.

COMPARTMENT LIGHTING

There will be seven (7) compartment(s) with two (2) white 12 volt DC LED compartment light strips. The dual light strips will be centered vertically along each side of the door framing. There will be two (2) light strips per compartment. The dual light strips will be in all body compartment(s).

Any remaining compartments without light strips will have a 6.00" diameter Truck-Lite, Model: 79384 light. Each light will have a number 1076 one filament, two wire bulb.

Opening the compartment door will automatically turn the compartment lighting on.

MOUNTING TRACKS

There will be seven (7) sets of tracks for mounting shelf(s) in LS1, LS2, LS3, RS1, RS2, RS3 and B1. These tracks will be installed vertically to support the adjustable shelf(s), and will be full height of the compartment. The tracks will be painted to match the compartment interior.

ADJUSTABLE SHELVES

There will be six (6) shelves with a capacity of 500 lb provided.

The shelf construction will consist of .188" aluminum painted spatter gray with 2.00" sides.

Each shelf will be infinitely adjustable by means of a threaded fastener, which slides in a track.

The shelves will be held in place by .12" thick stamped plated brackets and bolts.

The location(s) will be determined at a later date.

SLIDE-OUT/TILT-DOWN TRAY FOR SCBA PACKS

Slide-out/tilt-down SCBA tray assemblies will be provided. One assembly will consist of a partition and two trays. A quantity of one (1) will be provided. A partition will be installed in the center of the compartment. A tilt-down tray will be installed on each side of the partition. Each pair of trays will be designed for the installation of a total of 4 (four) SCBA packs.

Columbia Heights Bid 941 Full Specification

The bottom of each tray will be constructed of 0.188" thick aluminum while painted spatter gray special aluminum extrusions will be utilized for the tray sides, ends, and tracks. The corners will be welded to form a rigid unit.

A spring loaded lock will be provided on each side at the front of the tray. Releasing the locks will allow the tray to slide out approximately two-thirds (2/3) of its length from the stowed position and tip down from horizontal to an easily reachable height. The tray will be equipped with ball bearing rollers for smooth operation.

Rubber padded stops will be provided for the tray in the extended position.

The capacity rating of the tray will be a minimum of 215 lb in the extended position.

The vertical position of the tray within the compartment will be adjustable.

Shelf track will be installed in the bottom of the tray to allow installation of an air bottle bracket.

The tray(s) will be located LS2.

SLIDE-OUT FLOOR MOUNTED TRAY

There will be two (2) floor mounted slide-out tray(s) provided.

Each tray will have 2.00" high sides and a minimum capacity rating of 500 lb in the extended position.

Each tray will be constructed of aluminum painted spatter gray

There will be two undermount-roller bearing type slides rated at 250lb each provided. The pair of slides will have a safety factor rating of 2.

To ensure years of dependable service, the slides will be coated with a finish that is tested to withstand a minimum of 1,000 hours of salt spray per ASTM B117.

To ensure years of easy operation, the slides will require no more than a 50lb force for push-in or pull-out movement when fully loaded after having been subjected to a 40 hour vibration (shaker) test under full load. The vibration drive file will have been generated from accelerometer data collected from a heavy truck chassis driven over rough gravel roads in an unloaded condition. Proof of compliance will be provided upon request.

Automatic locks will be provided for both the "in" and "out" positions. The trip mechanism for the locks will be located at the front of the tray for ease of use with a gloved hand.

The location(s) will be RS1 and B1.

SLIDE-OUT TOOLBOARD

There will be three (3) slide-out toolboard(s) provided.

The toolboard will be a minimum of 0.188" thick with .203" diameter holes in a pegboard pattern with 1.00" centers between holes.

Columbia Heights Bid 941 Full Specification

A 1.00" x 1.00" aluminum tube frame will be welded to the edge of the pegboard.

The board will be mounted on an under-mount roller bearing type slide rated at 250 lb with a factor of safety of 2.

To ensure years of dependable service the slides will be coated with a finish that is tested to withstand a minimum of 1,000 hours of salt spray per ASTM B117.

To ensure years of easy operation, the slides will require no more than a 50 pound force for push-in or pull-out movement when fully loaded after having been subjected to a 40 hour vibration (shaker) test under full load. The vibration drive file will have been generated from accelerometer data collected from a heavy truck chassis driven over rough gravel roads in an unloaded condition. Proof of compliance will be provided upon request.

The slide will be mounted on adjustable tracks side to side within the compartment.

The board will have positive lock in the stowed and extended position.

The toolboard(s) will be spatter gray painted and installed in LS1, 18.00" from the forward door frame, in LS1, 28.00" from the forward door frame and in LS1, 8.00" from the forward door frame.

DRAWER ASSEMBLY

A slideout drawer assembly will be installed LS3.

The clear dimensions starting at the top of the cabinet with the first drawer will be 3.00" with a face plate that is 4.00" high x 21.00" deep. The clear dimensions of the second drawer will be 4.75" with a face plate that is 5.00" high x 21.00" deep. The clear dimensions of the third drawer will be 5.75" with a face plate that is 6.00" high x 21.00" deep. The clear dimensions of the fourth drawer will be 9.75" with a face plate that is 10.00" high x 21.00" deep. Each drawer will be the same width and not exceed 36.00".

The drawers will have a capacity of 250 pounds.

The drawers will be mounted in a cabinet housing constructed of light gray powder coated aluminum with anodized aluminum frames. The housing will be 24.00" deep, and completely enclose the drawer.

A full-length aluminum extruded rail will be provided at the top edge of each drawer. This rail will act as the latching mechanism as well as the handle for each drawer.

There will be a total of one (1) provided.

RUB RAIL

Bottom edge of the side compartments will be trimmed with a bright aluminum extruded rub rail.

Trim will be 2.12" high with 1.38" flanges turned outward for rigidity.

The rub rails will not be an integral part of the body construction, which allows replacement in the event of damage.

BODY FENDER CROWNS

Polished stainless steel fender crowns will be provided around the rear wheel openings with a dielectric barrier will be provided between the fender crown and the fender sheet metal to prevent corrosion.

The fender crowns will be held in place with stainless steel screws that thread directly into a composite nut and not directly into the parent body sheet metal to eliminate dissimilar metals contact and greatly reduce the chance for corrosion. Rubber welting will be provided between the body and crown.

BODY FENDER LINER

A painted fender liner will be provided. The liners will be removable to aid in the maintenance of rear suspension components.

HARD SUCTION HOSE

Hard suction hose will not be required.

HANDRAILS

The handrails will be 1.25" diameter anodized aluminum extrusion, with a ribbed design, to provide a positive gripping surface.

Chrome plated end stanchions will support the handrail. Plastic gaskets will be used between end stanchions and any painted surfaces.

Drain holes will be provided in the bottom of all vertically mounted handrails.

Handrails will be provided to meet NFPA 1901 section 15.8 requirements. The handrails will be installed as noted on the sales drawing.

HANDRAILS

One (1) vertical handrail will be located on each rear beavertail.

HANDRAIL

One (1) full width horizontal handrail will be provided below the hose bed at the rear of the apparatus.

EXTINGUISHER/AIR BOTTLE/ STORAGE (TRIANGULAR)

A total of one (1) extinguisher/air bottle/storage compartments will be provided RS rear. The triangular shaped compartment will be sized to fit a 8.00" diameter extinguisher in the lower area and a 8.00" diameter extinguisher in the upper area. The compartment will be approximately 25.50" deep. A partition will be provided to separate the compartment. Also inside the compartment, black rubber matting will be provided. The compartment will be furnished with a drain hole. A polished stainless steel, triangular shaped door with a Southco raised trigger C2 chrome lever latch will be provided to contain the air bottles. A dielectric barrier will be provided between the door hinge, hinge fasteners and the body sheet metal.

AIR BOTTLE COMPARTMENT STRAP

A strap will be provided in the air bottle compartment(s) to help contain the bottles when the vehicle is parked on an incline. The strap will wrap around the neck and attach to the wall of the compartment.

AIR BOTTLE STORAGE (TRIPLE)

A quantity of two (2) air bottle compartments designed to hold (3) air bottles up to 7.25" in diameter x 26.00" deep will be provided on the left side forward of the rear wheels and on the right side forward of the rear wheels. A polished stainless steel door with a Southco raised trigger C2 chrome lever latch will be provided to contain the air bottle. A dielectric barrier will be provided between the door hinge, hinge fasteners and the body sheet metal.

Inside the compartment, black rubber matting will be provided.

AIR BOTTLE COMPARTMENT STRAP

A strap will be provided in the air bottle compartment(s) to help contain the air bottles when the vehicle is parked on an incline. The strap will wrap around the neck and attach to the wall of the compartment.

AIR BOTTLE HOLDERS

Six (6) brackets will be provided for mounting air bottles. Each bracket will be a Ziamatic, model UH-5-30-3-SF. Install (4) on trays in LS2 (2) on frwd tank wall of RS2.

EXTENSION LADDER

There will be a 24' two-section aluminum Duo-Safety Series 900-A extension ladder provided.

ROOF LADDER

There will be a 14' aluminum Duo-Safety Series 775-A roof ladder provided.

HYDRAULIC LADDER RACK

Ground ladders will be mounted above the right side of the hose body in a specially designed swing-down cradle. This cradle will be electric/hydraulic operated. The system design will have been life cycle tested for at least 14 years of dependable service.

An independent hydraulic pump powered by a 12-volt electric motor will operate the hydraulics. The hydraulic pump and reservoir will be accessible from the ground through a stainless steel inspection door.

The ladder rack will incorporate two hydraulic rotary actuators, one each located inside the front compartment and the rear compartment. The actuators will be completely enclosed within each compartment to eliminate any pinch points while operating the ladder rack. Lifting arms will be attached outside the compartment body to the front and rear actuator.

The rack can be designed in certain situations to provide lifting capabilities up to 500 lb.

The maximum height of the rack from the ground in the lowered position will be no more than 47.00".

The electric control panel will have a master switch on/off switch, an actuation switch, an operation indicator light and operation instructions. The electric controls will be located in such a manner to allow the operator full view of the area into which the ladders will be lowered.

Two (2) air operated safety locks will be furnished to securely maintain the ladder bracket assembly in the travel position. These air operated safety locks will be controlled from the ladder rack control panel.

A polished stainless steel enclosure shall be provided over the hydraulic ladder rack lock at the rear on the right side to cover the ladder rack lock (1) and provide mounting for any rear warning lights.

Ladders will be secured to the brackets with two (2) locks retaining the roof ladder and the extension ladder. The locks will be such that when the roof ladder is removed, the clamps can be moved a half turn to hold the extension ladder in place.

LADDER RACK INTERLOCK AND NOT STOWED INDICATOR LIGHT

An interlock will be provided to prevent operation of the ladder rack unless the apparatus parking brake has been activated.

A steady red indicator light will be located on the cab instrument panel and illuminated when the hydraulic ladder rack is not in the stowed position. The light will be labeled "Ladder Rack". In addition, the "Do Not Move Apparatus" light located in the cab will be activated when the hydraulic ladder rack is not in the stowed position.

HYDRAULIC LADDER RACK DEPLOYED LIGHTS

There will be two (2) Truck-Lite catalog number 15***, 1.20" high x 2.49" wide x 0.94" deep lights with chrome trim, amber flashing LEDs and, provided per the following:

- One (1) light installed on the front of the hydraulic ladder rack
- One (1) light installed on the rear of the hydraulic ladder rack
- The warning light lens color(s) to be clear

The lights will be activated when the battery switch is on and the hydraulic ladder rack is not in the stowed position.

FOLDING LADDER

One (1) 10.00' aluminum, Series 585-A, Duo-Safety folding ladder will be installed on the inboard side of the hydraulic ladder rack .

HYDRAULIC LADDER RACK PUMP LOCATION

The hydraulic pump for the ladder rack will be located RS pump panel. An access door will be provided to fill the pump.

PIKE POLE PROVIDED BY FIRE DEPARTMENT

NFPA 1901, 2016 edition, Section 5.9.4 requires one (1) 8 ft or longer pike pole mounted in a bracket fastened to the apparatus.

The pike pole is not on the apparatus as manufactured. The fire department will provide and mount the pike pole.

The pike pole(s) will be a Duo-Safety 10' pike pole.

6' PIKE POLE PROVIDED BY FIRE DEPARTMENT

NFPA 1901, 2016 edition, Section 5.9.4 requires one (1) 6' pike pole or plaster hook mounted in a bracket fastened to the apparatus.

The pike pole is not on the apparatus as manufactured. The fire department will provide and mount the pike pole.

The pike pole(s) will be a Duo-Safety 6' pike pole.

PIKE POLE STORAGE

Aluminum tubing will be used for the storage of two (2) pike poles and will be located on hydraulic ladder rack. If the head of a pike pole can come in contact with a painted surface, a stainless steel scuffplate will be provided.

FOLDING STEPS FRONT OF BODY

Folding steps will be provided full height on the left side body compartments to provide access to the cargo bed. Steps will be spaced evenly on the sales drawing. Actual quantity may vary due to pump panel interferences but will meet the NFPA required maximum stepping height.

The Trident steps will be bright finished, non-skid with a black coating.

The step will incorporate an LED light to illuminate the stepping surface.

The steps can be used as a hand hold with two openings wide enough for a gloved hand.

REAR FOLDING STEPS

Bright finished, non-skid folding steps with a black coating will be provided at the rear. Each step will incorporate an LED light to illuminate the stepping surface. The steps can be used as a hand hold with two openings wide enough for a gloved hand.

There will be one (1) bright aluminum treadplate cover/step/s provided and installed LS rear within the cargo area over the pump. The step will be reinforced for walking.

PUMP

Pump will be a Waterous CSU, 1500 gpm single (1) stage midship mounted centrifugal type.

Pump will be the class "A" type.

Pump will deliver the percentage of rated discharge at pressures indicated below:

- 100% of rated capacity at 150 psi net pump pressure.
- 70% of rated capacity at 200 psi net pump pressure.
- 50% of rated capacity at 250 psi net pump pressure.

Pump body will be close-grained gray iron, bronze fitted, and horizontally split in two (2) sections for easy removal of the entire impeller shaft assembly (including wear rings).

Pump will be designed for complete servicing from the bottom of the truck, without disturbing the pump setting or apparatus piping.

Columbia Heights Bid 941 Full Specification

Pump case halves will be bolted together on a single horizontal face to minimize chance of leakage and facilitate ease of reassembly. No end flanges will be used.

Discharge manifold of the pump will be cast as an integral part of the pump body assembly and will provide a minimum of three (3) 3.50" openings for flexibility in providing various discharge outlets for maximum efficiency.

The three (3) 3.50" openings will be located as follows: one (1) outlet to the right of the pump, one (1) outlet to the left of the pump, and one (1) outlet directly on top of the discharge manifold.

Impeller shaft will be stainless steel, accurately ground to size. It will be supported at each end by sealed, anti-friction ball bearings for rigid precise support. Impeller will have flame plated hubs assuring maximum pump life and efficiency despite any presence of abrasive matter in the water supply.

Bearings will be protected from water and sediment by suitable stuffing boxes, flinger rings, and oil seals. No special or sleeve type bearings will be used.

Pump will be equipped with a self-adjusting, maintenance-free, mechanical shaft seal.

The mechanical seal will consist of a flat, highly polished, spring fed carbon ring that rotates with the impeller shaft. The carbon ring will press against a highly polished stainless steel stationary ring that is sealed within the pump body.

In addition, a throttling ring will be pressed into the steel chamber cover, providing a very small clearance around the rotating shaft in the event of a mechanical seal failure. The pump performance will not deteriorate, nor will the pump lose prime, while drafting if the seal fails during pump operation.

Wear rings will be bronze and easily replaceable to restore original pump efficiency and eliminate the need to replace the entire pump casing due to wear.

PUMP TRANSMISSION

The pump transmission will be made of a three (3) piece, aluminum, horizontally split casing. Power transfer to pump will be through a high strength Morse HY-VO silent drive chain. By the use of a chain rather than gears, 50% of the sprocket will be accepting or transmitting torque, compared to two (2) or three (3) teeth doing all the work.

Drive shafts will be 2.35" diameter hardened and ground alloy steel and supported by ball bearings. The case will be designed to eliminate the need for water cooling.

PUMPING MODE

An interlock system will be provided to ensure that the pump drive system components are properly engaged so that the apparatus can be safely operated. The interlock system will be designed to allow stationary pumping only.

AIR PUMP SHIFT

Pump shift engagement will be made by a two (2) position sliding collar, actuated pneumatically (by air pressure), with a three (3) position air control switch located in the cab. A manual back-up shift control will also be located on the left side pump panel.

Two (2) indicator lights will be provided adjacent to the pump shift inside the cab. One (1) green light will indicate the pump shift has been completed and be labeled "pump engaged". The second green light will indicate when the pump has been engaged, and that the chassis transmission is in pump gear. This indicator light will be labeled "OK to pump".

The pump shift will be interlocked to prevent the pump from being shifted out of gear when the chassis transmission is in gear to meet NFPA requirements.

The pump shift control in the cab will be illuminated to meet NFPA requirements.

TRANSMISSION LOCK-UP

The direct gear transmission lock-up for the fire pump operation will engage automatically when the pump shift control in the cab is activated.

AUXILIARY COOLING SYSTEM

A supplementary heat exchange cooling system will be provided to allow the use of water from the discharge side of the pump for cooling the engine water. The heat exchanger will be cylindrical type and will be a separate unit. The heat exchanger will be installed in the pump or engine compartment with the control located on the pump operator's control panel. Exchanger will be plumbed to the master drain valve.

INTAKE RELIEF VALVE

One (1) Trident Air Max intake relief valve(s) will be installed on the suction side of the pump preset at 125 psig.

The relief valve will have a working range of 50 PSI to 350 PSI.

The outlet will terminate below the frame rails with a 2.50" National Standard hose thread adapter and will have a "do not cap" warning tag.

One (1) adjustable air regulator and pressure indicating gauge will be located on a common bezel on the left side pump panel to control the intake valve(s).

PRESSURE CONTROLLER

A Pierce Pump Boss Model PBA300 pressure governor will be provided.

A pressure transducer will be installed in the water discharge manifold on the pump.

The display panel will be located at the pump operator's panel.

PRIMING PUMP

The priming pump will be a Trident Emergency Products compressed air powered, high efficiency, multistage venturi based AirPrime System, conforming to standards outlined in the current edition of NFPA 1901.

All wetted metallic parts of the priming system are to be of brass and stainless steel construction.

One (1) priming control will open the priming valve and start the pump primer.

PUMP MANUALS

There will be a total of two (2) pump manuals provided by the pump manufacturer and furnished with the apparatus. The manuals will be provided by the pump manufacturer in the form of two (2) electronic copies. Each manual will cover pump operation, maintenance, and parts.

PLUMBING, STAINLESS STEEL AND HOSE

All inlet and outlet lines will be plumbed with either stainless steel pipe, flexible polypropylene tubing or synthetic rubber hose reinforced with hi-tensile polyester braid. All hose's will be equipped with brass or stainless steel couplings. All stainless steel hard plumbing will be a minimum of a schedule 10 wall thickness.

Where vibration or chassis flexing may damage or loosen piping or where a coupling is required for servicing, the piping will be equipped with victaulic or rubber couplings.

Plumbing manifold bodies will be ductile cast iron or stainless steel.

All piping lines are to be drained through a master drain valve or will be equipped with individual drain valves. All drain lines will be extended with a hose to drain below the chassis frame.

All water carrying gauge lines will be of flexible polypropylene tubing.

All piping, hose and fittings will have a minimum of a 500 PSI hydrodynamic pressure rating.

FOAM SYSTEM PLUMBING

All piping that is in contact with the foam concentrate or foam/water solution will be stainless steel. The fittings will be stainless steel or brass. Cast iron pump manifolds will be allowed.

MAIN PUMP INLETS

A 6.00" pump manifold inlet will be provided on each side of the vehicle. The suction inlets will include removable die cast zinc screens that are designed to provide cathodic protection for the pump, thus reducing corrosion in the pump.

INLET VALVES WITH INTAKE RELIEF VALVE

There will be Two (2) Task Force Tips (TFT) AB Series aluminum ball intake valve(s) provided at LS and RS MIV .

The inlet connection will be 1ST (5.0" Rigid Storz) with a cap and the outlet connection will be NX (6.0" Threaded Swivel) . There will be an eight-position adjustable 30 degree swiveling detent elbow on the inlet side of the ball intake valve.

The ball intake valve will be controlled with a(n) standard crank on the left side .

If ball intake valve is to be controlled with a manual handwheel, the handwheel will be controlled with a NFPA compliant slow-close hand wheel. A position indicator will be provided to allow for a quick visualization of the status of the valve in the open, closed or transition position.

If the ball intake valve is to be electrically controlled, the ball intake valve will be controlled by a remote panel-mounted push-button switch with LED lights for a quick visualization of the status of the valve in

the open, closed or transition position. The push button switch will be mounted on the pump operator's panel.

The ball intake valve will be equipped with a standard adjustable pressure relief valve preset at. The relief valve will have a working range of 90 PSI to 300 PSI.

A 3/4" TFT bleeder/drain valve will be provided on the ball intake valve to exhaust excess air or water from the valve.

For corrosion protection the aluminum casting will have a hard coat anodized finish, with a powder coated internal and external finish. All the components facing the wet side of the valve will be constructed from stainless steel.

SHORT SUCTION TUBE(S)

The suction tube(s) on the water pump will have short suction tube(s) installed to allow for installation of adapters, elbows or intake valves without excessive overhang.

VALVES

All ball valves will be Akron® Brass. The Akron valves will be the 8000 series heavy-duty style with a stainless steel ball and a simple two-seat design. No lubrication or regular maintenance is required on the valve.

Valves will have a **ten (10) year** warranty.

LEFT SIDE INLET

There will be one (1) auxiliary inlet with a 2.50" valve at the left side pump panel, terminating with a 2.50" (F) National Standard hose thread adapter.

The auxiliary inlet will be provided with a strainer, chrome swivel and plug.

The location of the valve for the one (1) inlet will be recessed behind the pump panel.

ANODE, INLET

A pair of sacrificial zinc anodes will be provided in the water pump inlets to protect the pump from corrosion.

INLET CONTROL

The side auxiliary inlet(s) will incorporate a quarter-turn ball valve with the control located at the inlet valve. The valve operating mechanism will indicate the position of the valve.

INLET BLEEDER VALVE

A 0.75" bleeder valve will be provided for each side gated inlet. The valves will be located behind the panel with a swing style handle control extended to the outside of the panel. The handles will be chrome plated and provide a visual indication of valve position. The swing handle will provide an ergonomic position for operating the valve without twisting the wrist and provides excellent leverage. The water discharged by the bleeders will be routed below the chassis frame rails.

TANK TO PUMP

The booster tank will be connected to the intake side of the pump with stainless steel piping and a quarter turn 3.00" full flow line valve with the control remotely located at the operator's panel. Tank to pump line will run straight (no elbows) from the pump into the front face of the water tank and angle down into the tank sump. A rubber coupling will be included in this line to prevent damage from vibration or chassis flexing.

A check valve will be provided in the tank to pump supply line to prevent the possibility of "back filling" the water tank.

TANK REFILL

There will be one (1) 2.50" combination tank refill and pump recirculation line provided. The tank refill will incorporate a quarter-turn ball valve with the control located at the pump operator's panel.

LEFT SIDE DISCHARGE OUTLETS

There will be One (1) discharge outlet with a 2.50" valve on the left side of the apparatus, terminating with a 2.50" (M) National Standard hose thread adapter.

RIGHT SIDE DISCHARGE OUTLETS

There will be One (1) discharge outlet with a 2.50" valve on the right side of the apparatus, terminating with a 2.50" (M) National Standard hose thread adapter.

LARGE DIAMETER DISCHARGE OUTLET

There will be a 4.00" discharge outlet with a 4.00" Akron valve installed on the right side of the apparatus, terminating with a 4.00" (M) National Standard hose thread adapter. This discharge outlet will be actuated with a handwheel control at the pump operator's control panel.

An indicator will be provided to show when the valve is in the closed position.

FRONT DISCHARGE OUTLET

There will be one (1) 1.50" discharge outlet piped to the front of the apparatus and located in the center bumper tray.

Plumbing will consist of 2.00" piping and flexible hose with a 2.00" ball valve with control at the pump operator's panel. A fabricated weldment made of stainless steel pipe will be used in the plumbing where appropriate. The piping will terminate with a 1.50" NST with 90 degree stainless steel swivel.

There will be automatic drains provided at all low points of the piping.

REAR DISCHARGE OUTLET

There will be Two (2) discharge outlets piped to the rear of the hose bed, one (1) each side, installed so proper clearance is provided for spanner wrenches or adapters. Plumbing will consist of 2.50" piping along with a 2.50" full flow ball valve with the control from the pump operator's panel.

FRONT OF HOSE BED DISCHARGE OUTLET

There will be One (1) discharge outlet discharge(s) piped to the front of the hose bed and located RS hose bed . Plumbing will consist of 2.50" piping with a 2.50" full-flow ball valve controlled at the pump

operator's panel. The discharge(s) will terminate with a 2.50" (M) National Standard hose thread adapter.

DISCHARGE CAPS/ INLET PLUGS

Chrome plated, rocker lug, caps with chain will be furnished for all discharge outlets 1.00" thru 3.00" in size, besides the pre-connected hose outlets.

Chrome plated, rocker lug, plugs with chain will be furnished for all auxiliary inlets 1.00" thru 3.00" in size.

The caps and plugs will incorporate a thread design to automatically relieve stored pressure in the line when disconnected.

OUTLET BLEEDER VALVE

A 0.75" bleeder valve will be provided for each outlet 1.50" or larger. Automatic drain valves are acceptable with some outlets if deemed appropriate with the application.

The valves will be located behind the panel with a swing style handle control extended to the outside of the side pump panel. The handles will be chrome plated and provide a visual indication of valve position. The swing handle will provide an ergonomic position for operating the valve without twisting the wrist and provides excellent leverage. Bleeders will be located at the bottom of the pump panel. They will be properly labeled identifying the discharge they are plumbed in to. The water discharged by the bleeders will be routed below the chassis frame rails.

LEFT SIDE OUTLET ELBOWS

The 2.50" discharge outlets located on the left side pump panel will be furnished with a 2.50" (F) National Standard hose thread x 2.50" (M) National Standard hose thread, chrome plated, 45 degree elbow.

The elbow will be Pierce VLH, which incorporates an exclusive thread design to automatically relieve stored pressure in the line when disconnected.

RIGHT SIDE OUTLET ELBOWS

The 2.50" discharge outlets located on the right side pump panel will be furnished with a 2.50" (F) National Standard hose thread x 2.50" (M) National Standard hose thread, chrome plated, 45 degree elbow.

The elbow will be Pierce VLH, which incorporates an exclusive thread design to automatically relieve stored pressure in the line when disconnected.

REAR OUTLET ELBOWS

The 2.50" discharge outlets located at the rear of the apparatus will be furnished with a 2.50" (F) National Standard hose thread x 2.50" (M) National Standard hose thread, chrome plated, 45 degree elbow.

The elbow will be Pierce VLH, which incorporates an exclusive thread design to automatically relieve stored pressure in the line when disconnected.

LARGE DIAMETER OUTLET ELBOWS

The 4.00" outlet(s) will be furnished with one (1) 4.00" (F) National Standard hose thread x 5.00" Storz elbow adapter with Storz cap.

DISCHARGE OUTLET CONTROLS

The discharge outlets will incorporate a quarter-turn ball valve with the control located at the pump operator's panel. The valve operating mechanism will indicate the position of the valve.

If a handwheel control valve is used, the control will be a minimum of a 3.9" diameter stainless steel handwheel with a dial position indicator built in to the center of the handwheel.

Any 3.00 inch or larger discharge valve will be a slow-operating valve in accordance with NFPA 16.7.5.3.

DELUGE RISER

A 3.00" deluge riser will be installed above the pump in such a manner that a monitor can be mounted and used effectively. Piping will be rigidly braced and installed securely so no movement develops when the line is charged. The riser will be gated and controlled at the pump operator's panel. The outlet will include an Akron valve with a handwheel control.

MONITOR

An Akron Model 3431 Apollo Hi-Riser monitor will be properly installed on the deluge riser.

Included will be a fixed mounting base.

The monitor will be painted to match the body .

NOZZLE, DELUGE

An Akron Akromatic model 5160 1250 GPM Master Stream Nozzle with 2.50" swivel will be provided. The nozzle will have a range of 250 to 1250 GPM and have a built in stream shaper.

The deluge riser will have male National Pipe Threads for mounting the monitor.

SPEEDLAYS WITH ALUM TRAYS

Ahead of the pump enclosure will be two (2) 1.75" and one (1) 2.50" speedlay hose beds. Two (2) speedlay compartments will have a 2.00" preconnect line with a 2.00" quarter turn ball valve and terminate with a 1.50" National Standard hose thread 90 degree swivel. One (1) speedlay compartment will have a 2.50" preconnect with a 2.50" quarter turn ball valve and terminate with a 2.50" National Standard hose thread 90 degree swivel.

Individual controls for the speedlays will be at the pump operator's panel.

Each compartment will be capable of carrying 200 feet of double jacketed hose with the one (1) compartment located above the other. The lower compartments will carry 1.75" hose and the upper compartment will carry 2.50" hose.

A removable tray will be provided for each speedlay hosebed. The speedlay trays will be constructed of 0.19 brushed finished aluminum with two (2) hand holes for easy removal from the compartment.

The bottom of the speedlay compartments will be lined with stainless steel. Nylon runners will be used on the bottom of the trays to allow for a skid resistant surface. The floor of the trays will be perforated brushed aluminum to allow for drainage and hose drying. Scuffplates will be provided on both sides, at the sides and bottom of each opening.

SPEEDLAY HOSE RESTRAINT

A 2.00" black nylon webbing design restraint will be provided across the ends of speedlay(s) to secure the hose during travel. The webbing assembly is to be attached at the bottom of the speedlay(s) with footman loops as a permanent attachment and is attached at the top with 2.00" cam buckle fastener(s).

HUSKY 3 FOAM PROPORTIONER

A Pierce Husky® 3 foam proportioning system will be provided. The Husky 3 is an on demand, automatic proportioning, single point, direct injection system suitable for all types of Class A and B foam concentrates, including the high viscosity (6000 cps), alcohol resistant Class B foams. Operation will be based on direct measurement of water flow, and remain consistent within the specified flows and pressures. The system will automatically proportion foam solution at rates from .1 percent to 3 percent regardless of variations in water pressure and flow, up to the maximum rated capacity of the foam concentrate pump.

The design of the system will allow operation from draft, hydrant, or relay operation.

System Capacity

The system will have the ability to deliver the following minimum foam solution flow rates at accuracies that meet or exceed NFPA requirements at a pump rating of 150 psi.

100 gpm @ 3 percent

300 gpm @ 1 percent

600 gpm @ 0.5 percent

Class A foam setting in .1 percent increments from .1 percent to 1 percent. Typical settings of 1 percent, .5 percent and .3 percent (maximum capacity will be limited to the plumbing and water pump capacity).

Control System

The system will be equipped with a digital electronic control display located on the pump operators panel. Push button controls will be integrated into the panel to turn the system on/off, control the foam percentage, and to set the operation modes.

The percent of injection will have a preset. This preset can be changed at the fire department as desired. The percent of injection will be able to be easily changed at the scene to adjust to changing demands.

Three (3) .50 tall LEDs will display the foam percentage in numeric characters. Three (3) indicator LEDs will also be included, one (1) green, one (1) red, and one (1) yellow. The LEDs will indicate various system operation or error states.

The indications will be:

- Solid Green - System On
- Solid Red - Valve Position Error
- Solid Yellow - Priming System
- Flashing Green - Injecting Foam
- Flashing Red - Low Tank Level
- Flashing Yellow - Refilling Tank

The control display will house a microprocessor, which receives input from the systems water flow meter while also monitoring the position of the foam concentrate pump. The microprocessor will compare the values of the water flow versus the position/rate of the foam pump, to ensure the proportion rate is accurate. One (1) check valve will be installed in the plumbing to prevent foam from contaminating the water pump.

Hydraulic Drive System

The foam concentrate pump will be powered by an electric over hydraulic drive system. The hydraulic system and motor will be integrated into one (1) unit.

Foam Concentrate Pump

The foam concentrate pump will be of positive displacement, self-priming; linear actuated design, driven by the hydraulic system. The pump will be constructed of brass body; chrome plated stainless steel shaft, with a stainless steel piston. In order to increase longevity of the pump, no aluminum will be present in its construction.

A relief system will be provided which is designed to protect the drive system components and prevent over pressuring the foam concentrate pump

The foam concentrate pump will have minimum capacity for 3 gpm with all types of foam concentrates with a viscosity at or below 6000 cps including protein, fluoroprotein, AFFF, FFFP, or AR-AFFF. The system will deliver only the amount of foam concentrate flow required, without recirculating foam back to the storage tank. Recirculating foam concentrate back to the storage tank can cause agitation and premature foaming of the concentrate, which can result in system failure. The foam concentrate pump will be self-priming and have the ability to draw foam concentrate from external supplies such as drums or pails.

External Foam Concentrate Connection

An external foam pick-up will be provided to enable use of a foam agent that is not stored on the vehicle. The external foam pick-up will be designed to allow continued operation after the on-board foam tank is empty, or the use of foam different than the foam in the foam tank.

Panel Mounted External Pick-Up Connection / Valve

A bronze three (3)-way valve will be provided. The unit will be mounted to the pump panel. The valve unit will function as the foam system tank to pump valve and external suction valve. The external foam pick-up will be one (1) 0.75" male connection GHT (garden hose thread) with a cap.

Pick-Up Hose

A 0.75" flexible hose with an end for insertion into foam containers will be provided. The hose will be supplied with a 0.75" female swivel GHT (garden hose thread) swivel connector. The hose will be shipped loose.

Discharges

The foam system will be plumbed to the center of front bumper, left rear outlet, front crosslay and rear crosslay.

System Electrical Load

The maximum current draw of the electric motor and system will be no more than 55 amperes at 12 VDC.

SINGLE FOAM TANK REFILL

The foam system's proportioning pump will be used to fill the foam tank. This will allow use of the auxiliary foam pick-up to pump the foam from pails or a drum on the ground into the foam tank. A foam shut-off switch will be installed in the fill dome of the tank to shut the system down when the tank is full. The fill operation will be controlled by a mode in the foam system controller. While the proportioner pump is filling the tank, the controller will display a flashing yellow LED to indicate that the tank is filling. When the tank is full, as determined by the float switch in the tank dome, the pump will stop and the controller will shut the yellow LED off. If it attempted to use tank fill and the refill valve and suction valve are in the wrong position(s), then a red LED will illuminate to indicate the improper valve position(s). When the valves are positioned properly, then filling will commence.

FOAM TANK

The foam tank will be an integral portion of the polypropylene water tank. The cell will have a capacity of 20 gallons of foam with the intended use of Class A foam. The foam cell will not reduce the capacity of the water tank. The foam cell will have a screen in the fill dome and a breather in the lid.

FOAM TANK DRAIN

The foam tank drain will be a 1.00" quarter turn drain valve located inside the pump/plumbing compartment.

PUMP COMPARTMENT

The pump compartment will be separate from the hose body and compartments so that each may flex independently of the other. It will be a fabricated assembly of steel tubing, angles and channels which supports both the fire pump and the side running boards.

The pump compartment will be mounted on the chassis frame rails with rubber biscuits in a four point pattern to allow for chassis frame twist.

Pump compartment, pump, plumbing and gauge panels will be removable from the chassis in a single assembly.

PUMP MOUNTING

Pump will be mounted to a substructure which will be mounted to the chassis frame rail using rubber isolators. The mounting will allow chassis frame rails to flex independently without damage to the fire pump.

LEFT SIDE PUMP CONTROL PANELS

All pump controls and gauges will be located at the left side of the apparatus and properly identified.

Layout of the pump control panel will be ergonomically efficient and systematically organized.

The pump operator's control panel will be removable in two (2) main sections for ease of maintenance:

The upper section will contain sub panels for the mounting of the pump pressure control device, engine monitoring gauges, electrical switches, and foam controls (if applicable). Sub panels will be removable from the face of the pump panel for ease of maintenance. Below the sub panels will be located all valve controls and line pressure gauges.

The lower section of the panel will contain all inlets, outlets, and drains.

All push/pull valve controls will have 1/4 turn locking control rods with polished chrome plated zinc tee handles. Guides for the push/pull control rods will be chrome plated zinc castings securely mounted to the pump panel. Push/pull valve controls will be capable of locking in any position. The control rods will pull straight out of the panel and will be equipped with universal joints to eliminate binding.

IDENTIFICATION TAGS

The identification tag for each valve control will be recessed in the face of the tee handle.

All discharge outlets will have color coded identification tags, with each discharge having its own unique color. Color coding will include the labeling of the outlet and the drain for each corresponding discharge.

All line pressure gauges will be mounted directly above the corresponding discharge control tee handles and recessed within the same chrome plated casting as the rod guide for quick identification. The gauge and rod guide casting will be removable from the face of the pump panel for ease of maintenance. The casting will be color coded to correspond with the discharge identification tag.

All remaining identification tags will be mounted on the pump panel in chrome plated bezels.

The pump panel on the right side will be removable with lift and turn type fasteners.

Trim rings will be installed around all inlets and outlets.

The trim rings for the side discharge outlets will be color coded and labeled to correspond with the discharge identification tag.

The following drawing(s) will be provided for approval by the customer. The drawing(s) will be made for up One (01) Truck apparatus and/or similar Pierce job number.

PUMP OPERATOR'S PANEL DRAWING

A detailed drawing to scale of the pump operator's panel will be provided for the customer to review. The drawing will include all of the gauges, controls, switching, etc., located on the pump operator's panel. The customer will be allowed to make changes and/or mark-ups to this approval drawing. The fire apparatus manufacturer will make revisions (If needed) to the drawing per the customer changes and/or mark-ups as long as the changes are physically possible within a specific product line.

The finalized and signed customer approved pump operator's panel drawing will become part of the contract documents.

Due to the way drain(s), bleeder(s), operational/maintenance tag(s) and NFPA required warning tag(s) are placed on pump panel(s), these items will NOT be shown on any pump panel approval drawing(s). These item(s) will be placed on pump panel(s) at the fire apparatus manufacturer discretion.

COLOR CODED TAGS

A detailed drawing/chart of the colors used on all of the inlet(s) and outlet(s) will be provided for the customer to review. The customer will be allowed to make changes and/or mark-ups to this approval drawing/chart. The fire apparatus manufacturer will make revisions (If needed) to the drawing per the customer changes and/or mark-ups as long as the changes are physically possible within a specific product line.

The finalized and signed customer approved drawing/chart of the colors will become part of the contract documents.

SPECIAL TEXT/VERBIAGE TAGS

A detailed drawing/chart of the text/verbiage used on all of the inlet(s) and outlet(s) will be provided for the customer to review. The customer will be allowed to make changes and/or mark-ups to this approval drawing/chart. The fire apparatus manufacturer will make revisions (If needed) to the drawing per the customer changes and/or mark-ups as long as the changes are physically possible within a specific product line.

The finalized and signed customer approved drawing/chart of the text/verbiage will become part of the contract documents.

PUMP PANEL CONFIGURATION

The pump panel configuration will be arranged and installed in an organized manner that will provide user-friendly operation.

PUMP AND GAUGE PANEL

The pump and gauge panels will be constructed of aluminum with a black vinyl finish. A polished aluminum trim molding will be provided around each panel.

The right side pump panel will be removable and fastened with swell type fasteners.

PUMP COMPARTMENT LIGHT

There will be one (1) Whelen®, Model 3SC0CDCR, 3.00" white 12 volt DC LED light(s) with Whelen, Model 3FLANGEC, flange(s) installed in the pump compartment.

There will be a switch accessible through a door on the pump panel included with this installation.

Engine monitoring graduated LED indicators will be incorporated with the pressure controller.

Also provided at the pump panel will be the following:

- Master Pump Drain Control

THROTTLE READY GREEN INDICATOR LIGHT

There will be a green indicator light integrated with the pressure governor and/or engine throttle installed on the pump operators panel that is activated when the pump is in throttle ready mode.

OK TO PUMP INDICATOR LIGHT

There will be a green indicator light installed on the pump operators panel that is activated when the pump is in Ok To Pump mode.

ALUMINUM HEAT ENCLOSURE

A heat enclosure will be installed, trapping hot air radiated from the engine exhaust system, which will warm the fire pump. The enclosure will consist of an aluminum understructure, with easily removable aluminum panels. Also a covering above the pump will be provided, so warm air cannot escape freely.

ELECTRIC GAUGE HEATER

A 12v electric gauge heater will be provided for all water carrying gauges.

PUMP COMPARTMENT HEATER

A hot water heater shall be installed in the pump compartment.

Controls for the heater shall be located at the pump operator's panel.

RUBBER BOOT

The front and rear of the pump house will be enclosed to contain the heat. The rear will have openings for the plumbing only. A rubber boot will be supplied around the plumbing, at the front, sides and rear of the pump house, the boot will allow the plumbing to flex and keep cold air out.

VACUUM AND PRESSURE GAUGES

The pump vacuum and pressure gauges will be liquid filled and manufactured by Class 1 Incorporated ©.

The gauges will be a minimum of 4.00" in diameter and will have white faces with black lettering, with a pressure range of 30.00"-0-600#.

Gauge construction will include a Zytel nylon case with adhesive mounting gasket and threaded retaining nut.

The pump pressure and vacuum gauges will be installed adjacent to each other at the pump operator's control panel.

Test port connections will be provided at the pump operator's panel. One will be connected to the intake side of the pump, and the other to the discharge manifold of the pump. They will have 0.25 in.

standard pipe thread connections and non-corrosive polished stainless steel or brass plugs. They will be marked with a label.

This gauge will include a 10 year warranty against leakage, pointer defect, and defective bourdon tube.

PRESSURE GAUGES

The individual "line" pressure gauges for the discharges will be Class 1© interlube filled.

They will be a minimum of 2.00" in diameter and have white faces with black lettering.

Gauge construction will include a Zytel nylon case with adhesive mounting gasket and threaded retaining nut.

Gauges will have a pressure range of 30"-0-400#.

The individual pressure gauge will be installed as close to the outlet control as practical.

This gauge will include a 10 year warranty against leakage, pointer defect, and defective bourdon tube.

WATER LEVEL GAUGE

There will be an electronic water level gauge provided on the operator's panel that registers water level by means of five (5) colored LED lights. The lights will be durable, ultra-bright five (5) LED design viewable through 180 degrees. The water level indicators will be as follows:

- 100 percent = Green
- 75 percent = Yellow
- 50 percent = Yellow
- 25 percent = Yellow
- Refill = Red

The light will flash when the level drops below the given level indicator to provide an eighth of a tank indication. To further alert the pump operator, the lights will flash sequentially when the water tank is empty.

The level measurement will be based on the sensing of head pressure of the fluid in the tank.

The display will be constructed of a solid plastic material with a chrome plated die cast bezel to reduce vibrations that can cause broken wires and loose electronic components. The encapsulated design will provide complete protection from water and environmental elements. An industrial pressure transducer will be mounted to the outside of the tank. The field calibratable display measures head pressure to accurately show the tank level.

There will be a Hale part number 106877, 4-light driver module included with this installation to power additional water level gauges.

The system(s) will be energized when pump is in gear.

WATER LEVEL GAUGE

There will be two (2) additional water level indicator(s), Whelen®, Model PSTANK2, LED module with chrome trim, installed one (1) each side rearward of crew cab doors.

This light module(s) will include four (4) colored levels, and function similar to the water level indicator located at the operators panel:

- First green module indicates a full water level
- Second blue module indicates a water level above 3/4 full
- Third amber module indicates a water level above 1/2 full
- Last red module indicates a water level above 1/4 full and empty
 - Above 1/4 this light will be steady burning
 - At empty this light will be flashing

The flash rate will be determined by the main water level tank sensor.

This module will be activated when the pump is in gear.

FOAM LEVEL GAUGE

An electronic foam level gauge will be provided on the operator's panel that registers foam level by means of five (5) colored LED lights. The lights will be durable, ultra-bright five (5) LED design viewable through 180 degrees. The foam level indicators will be as follows:

- 100 percent = Green
- 75 percent = Yellow
- 50 percent = Yellow
- 25 percent = Yellow
- Refill = Red

The light will flash when the level drops below the given level indicator to provide an eighth of a tank indication. To further alert the pump operator, the lights will flash sequentially when the foam tank is empty.

The level measurement will be based on the sensing of head pressure of the fluid in the tank.

The display will be constructed of a solid plastic material with a chrome plated die cast bezel to reduce vibrations that can cause broken wires and loose electronic components. The encapsulated design will provide complete protection from foam and environmental elements. An industrial pressure transducer will be mounted to the outside of the tank. The display will be able to be calibrated in the field and will measure head pressure to accurately show the tank level.

LIGHT SHIELD

There will be a polished, 16 gauge stainless steel light shield installed over the pump operator's panel.

- There will be 12 volt DC white LED lights installed under the stainless steel light shield to illuminate the controls, switches, essential instructions, gauges, and instruments necessary for

the operation of the apparatus. These lights will be activated by the pump panel light switch. Additional lights will be included every 18.00" depending on the size of the pump house.

- One (1) pump panel light will come on when the pump is in ok to pump mode.

There will be a light activated above the pump panel light switch when the parking brake is set. This is to afford the operator some illumination when first approaching the control panel.

AIR HORN SYSTEM

There will be two (2) Grover air horns recessed in the front bumper. The horn system will be piped to the air brake system wet tank utilizing 0.38" tubing. A pressure protection valve will be installed in-line to prevent loss of air in the air brake system.

Air Horn Location

The air horns will be located on each side of the bumper, towards the outside.

Air Horn Control

The air horns will be actuated by a chrome push button located on the officer's side of the engine tunnel and by the horn button in the steering wheel. The driver will have the option to control the air horns or the chassis horns from the horn button by means of a selector switch located on the instrument panel.

ELECTRONIC SIREN

A Whelen®, Model 295SLSA1, electronic siren with noise canceling microphone will be provided.

This siren to be active when the battery switch is on and that emergency master switch is on.

Electronic siren head will be recessed in the driver side center switch panel.

SIREN CONTROL

The electronic siren will be controllable on the siren head and horn ring only. No foot switches will be required.

The driver will have the option to control the siren or the chassis horns from the horn button by means of a selector switch located on the instrument panel.

The switch for the electronic siren will default to siren operation when the emergency master switch is activated.

SPEAKER

There will be one (1) Whelen®, Model SA315P, black nylon composite, 100-watt, speaker with through bumper mounting brackets and polished stainless steel grille provided. The speaker will be connected to the siren amplifier.

The speaker will be recessed in the right side of the front bumper, just outside of the frame rail.

AUXILIARY MECHANICAL SIREN

A Federal Q2B® siren will be furnished.

The control solenoid will be powered up after the emergency master switch is activated.

Columbia Heights Bid 941 Full Specification

The mechanical siren will be mounted on the bumper deck plate. It will be mounted on the left side. A reinforcement plate will be furnished to support the siren.

The mechanical siren will be actuated by a foot switch on the officer's side and by a push button in the steering wheel.

A momentary chrome push button switch will be included in the right side dash panel to activate the siren brake.

FRONT ZONE UPPER WARNING LIGHTS

There will be one (1) 72.00" Whelen Freedom IV LED lightbar mounted on the cab roof.

The lightbar will include the following:

- One (1) red flashing LED module in the driver's side end position.
- One (1) red flashing LED module in the driver's side front corner position.
- One (1) red flashing LED module in the driver's side first front position.
- One (1) white flashing LED module in the driver's side second front position.
- One (1) blue flashing LED module in the driver's side third front position.
- One (1) red flashing LED module in the driver's side fourth front position.
- Open in the driver's side fifth front position.
- One (1) 795 LED traffic light controller sent to national standard high priority in the center positions.
- Open in the passenger's side fifth front position.
- One (1) red flashing LED module in the passenger's side fourth front position.
- One (1) blue flashing LED module in the passenger's side third front position.
- One (1) white flashing LED module in the passenger's side second front position.
- One (1) red flashing LED module in the passenger's side first front position.
- One (1) red flashing LED module in the passenger's side front corner position.
- One (1) red flashing LED module in the passenger's side end position.

There will be clear lenses included on the lightbar.

The following switches may be installed in the cab on the switch panel to control the lightbar:

- a switch to control the flashing LED modules.
- the traffic light controller will be activated by a cab switch with emergency master control,
- and there will no momentary switch to activate the traffic light controller.

The two (2) white flashing LED modules and the traffic light controller will be disabled when the parking brake is applied.

The two (2) red and two (2) blue flashing LED modules in the front positions may be load managed when the parking brake is applied.

CAB FACE WARNING LIGHTS

There will be four (4) Whelen®, Model M6*C, LED flashing warning lights installed on the cab face, above the headlights, mounted in a common bezel.

- The driver's side front outside warning light to be red
- The driver's side front inside warning light to be red
- The passenger's side front inside warning light to be red
- The passenger's side front outside warning light to be red

All four (4) lights will include a clear lens.

There will be a switch located in the cab, on the switch panel, to control the four (4) lights.

The inside lights may be load managed if colored or disabled if white, when the parking brake is set.

HEADLIGHT FLASHER

The high beam headlights will flash alternately between the left and right side.

There will be a switch installed in the cab on the switch panel to control the high beam flash. This switch will be live when the battery switch and the emergency master switches are on.

The flashing will automatically cancel when the hi-beam headlight switch is activated or when the parking brake is set.

SIDE ZONE LOWER LIGHTING

There will be four (4) Whelen®, Model M6*C, flashing LED warning lights with chrome trim installed per the following:

- Two (2) lights, one (1) each side on the bumper extension. The side front lights to be red.
- Two (2) lights, one (1) each side above rear wheels. The side rear lights to be red.
- The lights will include a clear lenses.

There will be a switch in the cab on the switch panel to control the lights.

REAR ZONE LOWER LIGHTING

There will be two (2) Whelen®, Model M6*C, LED flashing warning lights located at the rear of the apparatus.

- The driver's side rear light to be red
- The passenger's side rear light to be red

Both lights will include a lens that is clear.

There will be a switch located in the cab on the switch panel to control the lights.

The rear warning light on the side of the hydraulic rack will be recessed into the rear bulkhead to allow the ladder rack arm to clear the light lens.

REAR/SIDE ZONE UPPER WARNING LIGHTS

There will be two (2) Whelen®, Model L31H*FN, LED warning beacons provided at the rear of the truck, located one (1) each side. There will be a switch located in the cab on the switch panel to control the beacons.

The color of the lights will be red LEDs with both domes clear.

The rear warning lights will be mounted on top of the compartmentation with all wiring totally enclosed. The rear deck lights will be mounted on the beavertails as high as possible.

TRAFFIC DIRECTING LIGHT

There will be one (1) Whelen®, Model TAL65, 36.00" long x 2.87" high x 2.25" deep, amber LED traffic directing light installed at the rear of the apparatus.

The Whelen, Model TACTL5, control head will be included with this installation.

The controller will be energized when the battery switch is on.

The auxiliary flash not activated.

This traffic directing light will be recessed with a stainless steel trim plate at the rear of the apparatus as high as practical.

The traffic directing light control head will be located in the driver side overhead switch panel in the right panel position.

ELECTRICAL SYSTEM GENERAL DESIGN FOR ALTERNATING CURRENT

The following guidelines will apply to the 120/240 VAC system installation:

General

Any fixed line voltage power source producing alternating current (ac) line voltage will produce electric power at 60 cycles plus or minus 3 cycles.

Except where superseded by the requirements of NFPA 1901, all components, equipment and installation procedures will conform to NFPA 70, National Electrical Code (herein referred to as the NEC).

Line voltage electrical system equipment and materials included on the apparatus will be listed and installed in accordance with the manufacturer's instructions. All products will be used only in the manner for which they have been listed.

Grounding

Grounding will be in accordance with Section 250-6 "Portable and Vehicle Mounted Generators" of the NEC. Ungrounded systems will not be used. Only stranded or braided copper conductors will be used for grounding and bonding.

An equipment grounding means will be provided in accordance with Section 250-91 (Grounding Conductor Material) of the NEC.

Columbia Heights Bid 941 Full Specification

The grounded current carrying conductor (neutral) will be insulated from the equipment grounding conductors and from the equipment enclosures and other grounded parts. The neutral conductor will be colored white or gray in accordance with Section 200-6 (Means of Identifying Grounding Conductors) of the NEC.

In addition to the bonding required for the low voltage return current, each body and driving or crew compartment enclosure will be bonded to the vehicle frame by a copper conductor. This conductor will have a minimum amperage rating of 115 percent of the nameplate current rating of the power source specification label as defined in Section 310-15 (amp capacities) of the NEC. A single conductor properly sized to meet the low voltage and line voltage requirements will be permitted to be used.

All power source system mechanical and electrical components will be sized to support the continuous duty nameplate rating of the power source.

Operation

Instructions that provide the operator with the essential power source operating instructions, including the power-up and power-down sequence, will be permanently attached to the apparatus at any point where such operations can take place.

Provisions will be made for quickly and easily placing the power source into operation. The control will be marked to indicate when it is correctly positioned for power source operation. Any control device used in the drive train will be equipped with a means to prevent the unintentional movement of the control device from its set position.

A power source specification label will be permanently attached to the apparatus near the operator's control station. The label will provide the operator with the following information:

- Rated voltage(s) and type (ac or dc)
- Phase
- Rated frequency
- Rated amperage
- Continuous rated watts
- Power source engine speed

Direct drive (PTO) and portable generator installations will comply with Article 445 (Generators) of the NEC.

Overcurrent protection

The conductors used in the power supply assembly between the output terminals of the power source and the main over current protection device will not exceed 144.00" (3658 mm) in length.

For fixed power supplies, all conductors in the power supply assembly will be type THHW, THW, or use stranded conductors enclosed in nonmetallic liquid tight flexible conduit rated for a minimum of 194 degree Fahrenheit (90 degrees Celsius).

Columbia Heights Bid 941 Full Specification

For portable power supplies, conductors located between the power source and the line side of the main overcurrent protection device will be type SO or type SEO with suffix WA flexible cord rated for 600-volts at 194 degrees Fahrenheit (90 degrees Celsius).

Wiring Methods

Fixed wiring systems will be limited to the following:

- Metallic or nonmetallic liquid tight flexible conduit rated at not less than 194 degrees Fahrenheit (90 degrees Celsius)
- or
- Type SO or Type SEO cord with a WA suffix, rated at 600 volts at not less than 194 degrees Fahrenheit (90 degrees Celsius)

Electrical cord or conduit will not be attached to chassis suspension components, water or fuel lines, air or air brake lines, fire pump piping, hydraulic lines, exhaust system components, or low voltage wiring. In addition the wiring will be run as follows.

- Separated by a minimum of 12.00" (305 mm), or properly shielded, from exhaust piping
- Separated from fuel lines by a minimum of 6.00" (152 mm) distance

Electrical cord or conduit will be supported within 6.00" (152 mm) of any junction box and at a minimum of every 24.00" (610 mm) of continuous run. Supports will be made of nonmetallic materials or corrosion protected metal. All supports will be of a design that does not cut or abrade the conduit or cable and will be mechanically fastened to the vehicle.

Wiring Identification

All line voltage conductors located in the main panel board will be individually and permanently identified. The identification will reference the wiring schematic or indicate the final termination point. When prewiring for future power sources or devices, the unterminated ends will be labeled showing function and wire size.

Wet Locations

All wet location receptacle outlets and inlet devices, including those on hardwired remote power distribution boxes, will be of the grounding type provided with a wet location cover and installed in accordance with Section 210-7 "Receptacles and Cord Connections" of the NEC.

All receptacles located in a wet location will be not less than 24.00" (610 mm) from the ground. Receptacles on off-road vehicles will be a minimum of 30.00" (762 mm) from the ground.

The face of any wet location receptacle will be installed in a plane from vertical to not more than 45 degrees off vertical. No receptacle will be installed in a face up position.

Dry Locations

All receptacles located in a dry location will be of the grounding type. Receptacles will be not less than 30.00" (762 mm) above the interior floor height.

All receptacles will be marked with the type of line voltage (120-volts or 240-volts) and the current rating in amps. If the receptacles are direct current, or other than single phase, they will be so marked.

Listing

All receptacles and electrical inlet devices will be listed to UL 498, Standard for Safety Attachment Plugs and Receptacles, or other appropriate performance standards. Receptacles used for direct current voltages will be rated for the appropriate service.

Electrical System Testing

The wiring and associated equipment will be tested by the apparatus manufacturer or the installer of the line voltage system.

The wiring and permanently connected devices and equipment will be subjected to a dielectric voltage withstand test of 900-volts for one (1) minute. The test will be conducted between live parts and the neutral conductor, and between live parts and the vehicle frame with any switches in the circuit(s) closed. This test will be conducted after all body work has been completed.

Electrical polarity verification will be made of all permanently wired equipment and receptacles to determine that connections have been properly made.

Operational Test per Current NFPA 1901 Standard

The apparatus manufacturer will perform the following operation test and ensure that the power source and any devices that are attached to the line voltage electrical system are properly connected and in working order. The test will be witnessed and the results certified by an independent third-party certification organization.

The prime mover will be started from a cold start condition and the line voltage electrical system loaded to 100 percent of the nameplate rating.

The power source will be operated at 100 percent of its nameplate voltage for a minimum of two (2) hours unless the system meets category certification as defined in the current NFPA 1901 standard.

Where the line voltage power is derived from the vehicle's low voltage system, the minimum continuous electrical load as defined in the current NFPA 1901 standard will be applied to the low voltage electrical system during the operational test.

GENERATOR

The apparatus will be equipped with an alternating current (AC) electrical power system. The generator will be a Harrison, 6,000 watt (120/240 volts AC, 50/25 amps), Stinger, hydraulic driven unit. The generator will be driven by a transmission power take off unit, through a hydraulic pump and motor.

The hydraulic engagement supply will be operational at any time (no interlocks).

To properly monitor the generator performance, a digital voltage, frequency, hour meter will be provided.

GENERATOR LOCATION

The generator will be mounted in the in the area over the pump on the left side. The flooring in this area will be either reinforced or constructed in such a manner that it will handle the additional weight of the generator.

GENERATOR START

There will be a switch provided on the cab instrument panel to engage the generator.

GENERATOR REMOTE START

There will be one (1) remote start switch provided on the pump panel to engage the hydraulic generator PTO and field. A light at each switch location will be provided to indicate that the generator is running.

CIRCUIT BREAKER PANEL

The circuit breaker panel will be located high on the left wall of compartment LS3.

ELECTRIC CORD REEL

Furnished with the 120 volt AC electrical system will be a Hannay, Series 1600, cord reel. The reel will be provided with a 12-volt electric rewind switch, that is guarded to prevent accidental operation and labeled for its intended use. The switch will be protected with a fuse and installed at a height not to exceed 72.00" above the operators standing position.

The exterior finish of the reel(s) will be painted #269 gray from the reel manufacturer.

A captive roller assembly to be provided to aid in the payout and loading of the reel. A ball stop will be provided to prevent the cord from being wound on the reel.

A label will be provided in a readily visible location adjacent to the reel. The label will indicate current rating, current type, phase, voltage and total cable length.

A total of one (1) cord reel will be provided one (1) above the pump area, opposite side of the generator.

The cord reel will be configured with three (3) conductors.

CORD

Provided for electric distribution will be one (1) length installed on the reel of 200 feet of yellow 10/3 electrical cord, weather resistant 105 degree Celsius to -50 degree Celsius, 600 volt jacketed SOOW cord. No connector will be installed on the end of the cord.

PORTABLE JUNCTION BOX

There will be one (1) Akron EJBX electric junction box(es) provided.

There will be a cable strain relief and direct connection, no plug provided for each box.

Each box will be provided with the following:

- two (2) 15/20 amp 120 volt AC duplex straight blade receptacle with flip up covers
- two (2) 20 amp 120 volt AC twist lock single receptacles with flip up covers

- a 120 volt AC light inside the box

JUNCTION BOX HOLDER

There will be an aluminum junction box holder installed adjacent to the cord reel. A total of one (1) will be mounted at pick-up.

POWER OUTLET STRIP

There will be one (1) receptacle strip(s) with six (6) 15 amp 120 volt AC straight blade receptacles provided DS engine tunnel.

The strip(s) selected will be powered from the shoreline inlet through a receptacle located adjacent to the strip(s).

There will be a label installed near the strip(s) that state the following:

- Line Voltage
- Current Rating (amps)
- Phase
- Frequency

POWER OUTLET STRIP

There will be one (1) receptacle strip(s) with six (6) 20 amp 120 volt AC straight blade receptacles provided LS2 low forward bulkhead.

The strip(s) selected will be powered from the onboard generator to shoreline power transfer switch through a receptacle located adjacent to the strip(s).

There will be a label installed near the strip(s) that state the following:

- Line Voltage
- Current Rating (amps)
- Phase
- Frequency

120 VOLT RECEPTACLE

There will be one (1), 4-place receptacle box(es) with four (4) 15/20 amp 120 volt AC three (3) wire straight blade receptacles with an interior stainless steel wall plate installed RS1. The NEMA configuration for the receptacles will be 5-20R.

The receptacle(s) will be powered from the shoreline inlet.

There will be a label installed near the receptacle(s) that state the following:

- Line Voltage
- Current Rating (amps)
- Phase
- Frequency

LOOSE EQUIPMENT

The following equipment will be furnished with the completed unit:

- One (1) bag of chrome, stainless steel, or cadmium plated screws, nuts, bolts and washers, as used in the construction of the unit.

NFPA REQUIRED LOOSE EQUIPMENT PROVIDED BY FIRE DEPARTMENT

The following loose equipment as outlined in NFPA 1901, 2016 edition, section 5.9.3 and 5.9.4 will be provided by the fire department.

- 800 ft (60 m) of 2.50" (65 mm) or larger fire hose.
- 400 ft (120 m) of 1.50" (38 mm), 1.75" (45 mm), or 2.00" (52 mm) fire hose.
- One (1) handline nozzle, 200 gpm (750 L/min) minimum.
- Two (2) handline nozzles, 95 gpm (360 L/min) minimum.
- One (1) smoothbore or combination nozzle with 2.50" shutoff that flows a minimum of 250 gpm.
- One (1) SCBA complying with NFPA 1981 for each assigned seating position, but not fewer than four (4), mounted in brackets fastened to the apparatus or stored in containers supplied by the SCBA manufacturer.
- One (1) spare SCBA cylinder for each SCBA carried, each mounted in a bracket fastened to the apparatus or stored in a specially designed storage space(s).
- One (1) first aid kit.
- Four (4) combination spanner wrenches.
- Two (2) hydrant wrenches.
- One (1) double female 2.50" (65 mm) adapter with National Hose threads.
- One (1) double male 2.50" (65 mm) adapter with National Hose threads.
- One (1) rubber mallet, for use on suction hose connections.
- Two (2) salvage covers each a minimum size of 12 ft x 14 ft (3.7 m x 4.3 m).
- One (1) traffic vest for each seating position, each vest to comply with ANSI/ISEA 207, *Standard for High Visibility Public Safety Vests*, and have a five-point breakaway feature that includes two (2) at the shoulders, two (2) at the sides, and one (1) at the front.
- Five (5) fluorescent orange traffic cones not less than 28.00" (711 mm) in height, each equipped with a 6.00" (152 mm) retro-reflective white band no more than 4.00" (152 mm) from the top of the cone, and an additional 4.00" (102 mm) retro-reflective white band 2.00" (51 mm) below the 6.00" (152 mm) band.
- Five (5) illuminated warning devices such as highway flares, unless the five (5) fluorescent orange traffic cones have illuminating capabilities.
- One (1) automatic external defibrillator (AED).
- Four (4) ladder belts meeting the requirements of NFPA 1983, *Standard on Fire Service Life Safety Rope and System Components* (if equipped with an aerial device).
- If the supply hose carried does not use sexless couplings, an additional double female adapter and double male adapter, sized to fit the supply hose carried, will be carried mounted in brackets fastened to the apparatus.
- If none of the pump intakes are valved, a hose appliance that is equipped with one or more gated intakes with female swivel connection(s) compatible with the supply hose used on one

side and a swivel connection with pump intake threads on the other side will be carried. Any intake connection larger than 3.00" (75 mm) will include a pressure relief device that meets the requirements of 16.6.6.

- If the apparatus does not have a 2.50" National Hose (NH) intake, an adapter from 2.50" NH female to a pump intake will be carried, mounted in a bracket fastened to the apparatus if not already mounted directly to the intake.
- If the supply hose carried has other than 2.50" National Hose (NH) threads, adapters will be carried to allow feeding the supply hose from a 2.50" NH thread male discharge and to allow the hose to connect to a 2.50" NH female intake, mounted in brackets fastened to the apparatus if not already mounted directly to the discharge or intake.

SOFT SUCTION HOSE PROVIDED BY FIRE DEPARTMENT

NFPA 1901, 2016 edition, section 5.8.2.1 requires a minimum of 20' of suction hose or 15' of supply hose will be carried.

Hose is not on the apparatus as manufactured. The fire department will provide suction or supply hose.

DRY CHEMICAL EXTINGUISHER PROVIDED BY FIRE DEPARTMENT

NFPA 1901, 2016 edition, section 5.9.4 requires one (1) approved dry chemical portable fire extinguisher with a minimum 80-B:C rating mounted in a bracket fastened to the apparatus.

The extinguisher is not on the apparatus as manufactured. The fire department will provide and mount the extinguisher.

WATER EXTINGUISHER PROVIDED BY FIRE DEPARTMENT

NFPA 1901, 2016 edition, section 5.9.4 requires one (1) 2.5 gallon or larger water extinguisher mounted in a bracket fastened to the apparatus.

The extinguisher is not on the apparatus as manufactured. The fire department will provide and mount the extinguisher.

FLATHEAD AXE PROVIDED BY FIRE DEPARTMENT

NFPA 1901, 2016 edition, Section 5.9.4 requires one (1) flathead axe mounted in a bracket fastened to the apparatus.

The axe is not on the apparatus as manufactured. The fire department will provide and mount the axe.

PICKHEAD AXE PROVIDED BY FIRE DEPARTMENT

NFPA 1901, 2016 edition, Section 5.9.4 requires one (1) pickhead axe mounted in a bracket fastened to the apparatus.

The axe is not on the apparatus as manufactured. The fire department will provide and mount the axe.

PAINT - BODY PAINTED TO MATCH CAB

The exterior custom cab and body painting procedure will consist of a seven (7) step finishing process as follows:

Columbia Heights Bid 941 Full Specification

1. Manual Surface Preparation - All exposed metal surfaces on the custom cab and body will be thoroughly cleaned and prepared for painting. Imperfections on the exterior surfaces will be removed and sanded to a smooth finish. Exterior seams will be sealed before painting. Exterior surfaces that will not be painted include; chrome plating, polished stainless steel, anodized aluminum and bright aluminum treadplate.
2. Chemical Cleaning and Pretreatment - All surfaces will be chemically cleaned to remove dirt, oil, grease, and metal oxides to ensure the subsequent coatings bond well. The aluminum surfaces will be properly cleaned and treated using a high pressure, high temperature 4 step Acid Etch process. The steel and stainless surfaces will be properly cleaned and treated using a high temperature 3 step process specifically designed for steel or stainless. The chemical treatment converts the metal surface to a passive condition to help prevent corrosion. A final pure water rinse will be applied to all metal surfaces.
3. Surfacer Primer - The Surfacer Primer will be applied to a chemically treated metal surface to provide a strong corrosion protective basecoat. A minimum thickness of 2 mils of Surfacer Primer is applied to surfaces that require a Critical aesthetic finish. The Surfacer Primer is a two-component high solids urethane that has excellent sanding properties and an extra smooth finish when sanded.
4. Finish Sanding - The Surfacer Primer will be sanded with a fine grit abrasive to achieve an ultra-smooth finish. This sanding process is critical to produce the smooth mirror like finish in the topcoat.
5. Sealer Primer - The Sealer Primer is applied prior to the Basecoat in all areas that have not been previously primed with the Surfacer Primer. The Sealer Primer is a two-component high solids urethane that goes on smooth and provides excellent gloss hold out when topcoated.
6. Basecoat Paint - Two coats of a high performance, two component high solids polyurethane basecoat will be applied. The Basecoat will be applied to a thickness that will achieve the proper color match. The Basecoat will be used in conjunction with a urethane clear coat to provide protection from the environment.
7. Clear Coat - Two (2) coats of Clear Coat will be applied over the Basecoat color. The Clear Coat is a two-component high solids urethane that provides superior gloss and durability to the exterior surfaces. Lap style and roll-up doors will be Clear Coated to match the body. Paint warranty for the roll-up doors will be provided by the roll-up door manufacture.

Each batch of basecoat color is checked for a proper match before painting of the cab and the body. After the cab and body are painted, the color is verified again to make sure that it matches the color standard. Electronic color measuring equipment is used to compare the color sample to the color standard entered into the computer. Color specifications are used to determine the color match. A Delta E reading is used to determine a good color match within each family color.

All removable items such as brackets, compartment doors, door hinges, and trim will be removed and separately if required, to ensure paint behind all mounted items. Body assemblies that cannot be finish painted after assembly will be finish painted before assembly.

Pierce Manufacturing paint finish quality levels for critical areas of the apparatus (cab front and sides, body sides and doors, and boom lettering panels) meet or exceed the Cadillac/General Motors GMW15777 global paint requirements. Orange peel levels meet or exceed the #6 A.C.T. standard in

critical areas. These requirements are met in order for the exterior paint finish to be considered acceptable. The Pierce Manufacturing written paint standards will be available upon request.

The cab and body will be two-tone, with the upper section painted 101 black along with a shield design on the cab face and lower section of the cab and body painted 90 red.

PAINT - ENVIRONMENTAL IMPACT

Contractor will meet or exceed all current State regulations concerning paint operations. Pollution control will include measures to protect the atmosphere, water and soil. Controls will include the following conditions:

- Topcoats and primers will be chrome and lead free.
- Metal treatment chemicals will be chrome free. The wastewater generated in the metal treatment process will be treated on-site to remove any other heavy metals.
- Particulate emission collection from sanding operations will have a 99.99% efficiency factor.
- Particulate emissions from painting operations will be collected by a dry filter or water wash process. If the dry filter is used, it will have an efficiency rating of 98.00%. Water wash systems will be 99.97% efficient
- Water from water wash booths will be reused. Solids will be removed on a continual basis to keep the water clean.
- Paint wastes are disposed of in an environmentally safe manner.
- Empty metal paint containers will be to recover the metal.
- Solvents used in clean-up operations will be recycled on-site or sent off-site for distillation and returned for reuse.

Additionally, the finished apparatus will not be manufactured with or contain products that have ozone depleting substances. Contractor will, upon demand, present evidence that the manufacturing facility meets the above conditions and that it is in compliance with his State EPA rules and regulations.

PAINT CHASSIS FRAME ASSEMBLY

The chassis frame assembly will be finished with a single system black top coat before the installation of the cab and body, and before installation of the engine and transmission assembly, air brake lines, electrical wire harnesses, etc.

Components treated with epoxy E-coat protection prior to paint:

- Two (2) C-channel frame rails

Components that are included with the chassis frame assembly that will be painted not e-coated are:

- Cross members
- Axles
- Suspensions
- Steering gear
- Battery boxes
- Bumper extension weldment

- Frame extensions
- Body mounting angles
- Rear Body support substructure (front and rear)
- Pump house substructure
- Air tanks
- Steel fuel tank
- Castings
- Individual piece parts used in chassis and body assembly

The E-coat process will meet the technical properties shown.

AXLE HUB PAINT

All axle hubs will be painted black #101.

PAINT HYDRAULIC LADDER RACK 2-TONE

The hydraulic ladder rack will be painted 101 black and 90 red color.

COMPARTMENT INTERIOR PAINT

The interior of all compartments will be painted with a gray spatter finish for ease of cleaning and to make it easier to touch up scratches and nicks.

REFLECTIVE STRIPES

Three (3) reflective stripes will be provided across the front of the vehicle and along the sides of the body. The reflective band will consist of a 1.00" white stripe at the top with a 1.00" gap then a 6.00" white stripe with a 1.00" gap and a 1.00" white stripe on the bottom.

The reflective band provided on the cab face will be below the headlights on the fiberglass.

REAR CHEVRON STRIPING

There will be alternating chevron striping located on the rear-facing vertical surface of the apparatus. The rear surface, excluding the rear compartment door, will be covered.

The colors will be red and fluorescent yellow green diamond grade.

Each stripe will be 6.00" in width.

This will meet the requirements of the current edition of NFPA 1901, which states that 50% of the rear surface will be covered with chevron striping.

JOG IN REFLECTIVE STRIPE

There will be one (1) "Hockey Stick" style jog(s) in the reflective stripe located each side of the vehicle. Each stripe will be angled upward at approximately a 45 degree angle.

CAB DOOR REFLECTIVE STRIPE

A 6.00" x 16.00" white reflective stripe will be provided across the interior of each cab door. The stripe will be located approximately 1.00" up from the bottom, on the door panel.

This stripe will meet the NFPA 1901 requirement.

LETTERING

The lettering will be totally encapsulated between two (2) layers of clear vinyl.

LETTERING

Sixty-one (61) to eighty (80) genuine gold leaf lettering, 3.00" high, with outline and shade will be provided.

LETTERING

There will be genuine gold leaf lettering, 10.00" high, with outline and shade provided. There will be four (4) letters provided.

MALTESE CROSS INSTALLATION

There will be one (1) pair of maltese crosses, comprised of reflective material, provided and installed cab doors.

E-COATING OF STEEL COMPONENTS

The following components will be treated with an epoxy E-coat to provide resistance to corrosion and chemicals:

Cross members

TAK-4® weldments (side plates and side plate interconnecting structure members) (if applicable)

Torsion bar anchor weldments (if applicable)

Battery boxes

Bumper extension weldment

Frame extensions

Body mounting angles

Rear body support weldment

Under body support weldments (front and rear)

Pump house substructure (walkway if applicable)

The following components will not be e-coated:

Air tanks

Fuel tank

Castings

Individual piece parts used in chassis and body assembly

The e-coated parts will have a black top coat as well to provide an additional layer of protection and provide a consistent finish.

UNDERCOATING, CAB & BODY

The apparatus will be properly treated by an authorized Ziebart dealer.

The underside of the apparatus will be undercoated with an asphalt petroleum based material, dark in color.

Columbia Heights Bid 941 Full Specification

The undercoating material utilized on the apparatus will be formulated to resist corrosion and deaden unwanted sound or road noise.

Coating texture will appear firm, flexible, and resistant to abrasion. Minimum dry film thickness will be in the range of 8.00 to 12.00 mils.

The material will be applied to the following areas:

Body and cab wheel well fender liners, on the back side only.

Underside of body and cab sheet metal, and structural components.

Underside and vertical sides of all sheet metal compartmentation, including support angles.

Structural support members under running boards, rear platforms, battery boxes, walkways, etc.

Inside surfaces of the pump heat enclosure, (when installed).

FIRE APPARATUS PARTS MANUAL

There will be one (1) custom parts manual(s) in USB flash drive format for the complete fire apparatus provided.

The manual(s) will contain the following:

- Job number
- Part numbers with full descriptions
- Table of contents
- Parts section sorted in functional groups reflecting a major system, component, or assembly
- Parts section sorted in alphabetical order
- Instructions on how to locate parts

Each manual will be specifically written for the chassis and body model being purchased. It will not be a generic manual for a multitude of different chassis and bodies.

Service Parts Internet Site

The service parts information included in these manuals are also available on the Pierce website. The website offers additional functions and features not contained in this manual, such as digital photographs and line drawings of select items. The website also features electronic search tools to assist in locating parts quickly.

CHASSIS SERVICE MANUALS

There will be one (1) chassis service manuals on USB flash drives containing parts and service information on major components provided with the completed unit.

The manual will contain the following sections:

- Job number
- Table of contents

- Troubleshooting
- Front Axle/Suspension
- Brakes
- Engine
- Tires
- Wheels
- Cab
- Electrical, DC
- Air Systems
- Plumbing
- Appendix

The manual will be specifically written for the chassis model being purchased. It will not be a generic manual for a multitude of different chassis and bodies.

CHASSIS OPERATION MANUAL

The chassis operation manual will be provided on one (1) USB flash drive.

ONE (1) YEAR MATERIAL AND WORKMANSHIP

A Pierce basic apparatus limited warranty certificate, WA0008, is included with this proposal.

THREE (3) YEAR MATERIAL AND WORKMANSHIP

The Pierce custom chassis limited warranty certificate, WA0284, is included with this proposal.

ENGINE WARRANTY

A Cummins **five (5) year** limited engine warranty will be provided. A limited warranty certificate, WA0181, is included with this proposal.

STEERING GEAR WARRANTY

A Sheppard **three (3) year** limited steering gear warranty will be provided. A copy of the warranty certificate will be submitted with the bid package.

FIFTY (50) YEAR STRUCTURAL INTEGRITY

The Pierce custom chassis frame and crossmembers limited warranty certificate, WA0038, is included with this proposal.

FRONT AXLE THREE (3) YEAR MATERIAL AND WORKMANSHIP WARRANTY

The Pierce TAK-4 suspension limited warranty certificate, WA0050, is included with this proposal.

SINGLE REAR AXLE FIVE (5) YEAR MATERIAL AND WORKMANSHIP WARRANTY

A Meritor™ Axle 5 year limited warranty will be provided.

ABS BRAKE SYSTEM THREE (3) YEAR MATERIAL AND WORKMANSHIP WARRANTY

A Meritor Wabco™ ABS brake system limited warranty certificate, WA0232, is included with this proposal.

TEN (10) YEAR STRUCTURAL INTEGRITY

The Pierce custom cab limited warranty certificate, WA0012, is included with this proposal.

TEN (10) YEAR PRO-RATED PAINT AND CORROSION

A Pierce cab limited pro-rated paint warranty certificate, WA0055, is included with this proposal.

FIVE (5) YEAR MATERIAL AND WORKMANSHIP

The Pierce Command Zone electronics limited warranty certificate, WA0014, is included with this proposal.

CAMERA SYSTEM WARRANTY

A Pierce fifty four (54) month warranty will be provided for the camera system.

COMPARTMENT LIGHT WARRANTY

The Pierce 12 volt DC LED strip lights limited warranty certificate, WA0203, is included with this proposal.

TRANSMISSION WARRANTY

The transmission will have a **five (5) year/unlimited mileage** warranty covering 100 percent parts and labor. The warranty will be provided by Allison Transmission.

Note: The transmission cooler is not covered under any extended warranty you may be getting on your Allison Transmission. Please review your Allison Transmission warranty for coverage limitations.

TRANSMISSION COOLER WARRANTY

The transmission cooler will carry a five (5) year parts and labor warranty (exclusive to the transmission cooler). In addition, a collateral damage warranty will also be in effect for the first three (3) years of the warranty coverage and will not exceed \$10,000 per occurrence. A copy of the warranty certificate will be submitted with the bid package.

WATER TANK WARRANTY

A UPF poly water tank limited warranty certificate, WA0195, is included with this proposal.

TEN (10) YEAR STRUCTURAL INTEGRITY

The Pierce apparatus body limited warranty certificate, WA0009, is included with this proposal.

ROLL UP DOOR MATERIAL AND WORKMANSHIP WARRANTY

A Gortite roll-up door limited warranty will be provided. The mechanical components of the roll-up door will be warranted against defects in material and workmanship for the lifetime of the vehicle. A **six (6) year** limited warranty will be provided on painted and satin roll up doors.

The limited warranty certificate, WA0190, is included with this proposal.

PUMP WARRANTY

The Waterous pump will be provided with a Seven (7) year material and workmanship limited warranty.

A copy of the warranty certificate will be submitted with the bid package (no exception).

TEN (10) YEAR PUMP PLUMBING WARRANTY

The Pierce apparatus plumbing limited warranty certificate, WA0035, is included with this proposal.

FOAM SYSTEM WARRANTY

The Husky 3 foam system limited warranty certificate, WA0231, is included with this proposal.

SIX (6) YEAR GENERATOR MATERIAL AND WORKMANSHIP WARRANTY

A Harrison Hydra-Gen limited warranty certificate, WA0285, is included with this proposal.

TEN (10) YEAR PRO-RATED PAINT AND CORROSION

A Pierce body limited pro-rated paint warranty certificate, WA0057, is included with this proposal.

THREE (3) YEAR MATERIAL AND WORKMANSHIP

The Pierce Goldstar gold leaf lamination limited warranty limited warranty certificate, WA0018, is included with this proposal.

VEHICLE STABILITY CERTIFICATION

The fire apparatus manufacturer will provide a certification stating the apparatus complies with NFPA 1901, current edition, section 4.13, Vehicle Stability. The certification will be provided at the time of bid.

ENGINE INSTALLATION CERTIFICATION

The fire apparatus manufacturer will provide a certification, along with a letter from the engine manufacturer stating they approve of the engine installation in the bidder's chassis. The certification will be provided at the time of delivery.

POWER STEERING CERTIFICATION

The fire apparatus manufacturer will provide a certification stating the power steering system as installed meets the requirements of the component supplier. The certification will be provided at the time of bid.

CAB INTEGRITY CERTIFICATION

The fire apparatus manufacturer will provide a cab integrity certification with this proposal. The certification will state that the cab has been tested and certified by an independent third-party test facility. Testing events will be documented with photographs, real-time and high-speed video, vehicle accelerometers, cart accelerometers, and a laser speed trap. The fire apparatus manufacturer will provide a state-licensed professional engineer to witness and certify all testing events. Testing will meet or exceed the requirements below:

- European Occupant Protection Standard ECE Regulation No.29.
- SAE J2422 Cab Roof Strength Evaluation - Quasi-Static Loading Heavy Trucks.
- SAE J2420 COE Frontal Strength Evaluation - Dynamic Loading Heavy Trucks.

Roof Crush

The cab will be subjected to a roof crush force of 22,500 lb. This value meets the ECE 29 criteria and is equivalent to the front axle rating up to a maximum of 10 metric tons.

Additional Roof Crush

The same cab will be subjected to a roof crush force of 100,000 lbs. This value exceeds the ECE 29 criteria by nearly 4.5 times.

Side Impact

The same cab will be subjected to dynamic preload where a 13,275 lb moving barrier slams into the side of the cab at 5.5 mph at a force of 13,000 ft-lbs. This test is part of the SAE J2422 test procedure and more closely represents the forces a cab will see in a rollover incident.

Frontal Impact

The same cab will withstand a frontal impact of 32,600 ft-lbs of force using a moving barrier in accordance with SAE J2420.

Additional Frontal Impact

The same cab will withstand a frontal impact of 65,200 ft-lbs of force using a moving barrier, (twice the force required by SAE J2420).

The same cab will withstand all tests without any measurable intrusion into the survival space of the occupant area.

CAB DOOR DURABILITY CERTIFICATION

Robust cab doors help protect occupants. Cab doors will survive a 200,000 cycle door slam test where the slamming force exceeds 20 G's of deceleration. The bidder will certify that the sample doors similar to those provided on the apparatus have been tested and have met these criteria without structural damage, latch malfunction, or significant component wear.

WINDSHIELD WIPER DURABILITY CERTIFICATION

Visibility during inclement weather is essential to safe apparatus performance. Windshield wipers will survive a 3 million cycle durability test in accordance with section 6.2 of SAE J198 *Windshield Wiper Systems - Trucks, Buses and Multipurpose Vehicles*. The bidder will certify that the wiper system design has been tested and that the wiper system has met these criteria.

ELECTRIC WINDOW DURABILITY CERTIFICATION

Cab window roll-up systems can cause maintenance problems if not designed for long service life. The window regulator design will complete 30,000 complete up-down cycles and still function normally when finished. The bidder will certify that sample doors and windows similar to those provided on the apparatus have been tested and have met these criteria without malfunction or significant component wear.

SEAT BELT ANCHOR STRENGTH

Seat belt attachment strength is regulated by Federal Motor Vehicle Safety Standards and should be validated through testing. Each seat belt anchor design will withstand 3000 lb of pull on both the lap and shoulder belt in accordance with FMVSS 571.210 Seat Belt Assembly Anchorages. The bidder will certify that each anchor design was pull tested to the required force and met the appropriate criteria.

SEAT MOUNTING STRENGTH

Seat attachment strength is regulated by Federal Motor Vehicle Safety Standards and should be validated through testing. Each seat mounting design will be tested to withstand 20 G's of force in accordance with FMVSS 571.207 Seating Systems. The bidder will certify that each seat mount and cab structure design was pull tested to the required force and met the appropriate criteria.

PERFORMANCE CERTIFICATIONS

Cab Air Conditioning

Good cab air conditioning temperature and air flow performance keeps occupants comfortable, reduces humidity, and provides a climate for recuperation while at the scene. The cab air conditioning system will cool the cab from a heat-soaked condition at 100 degrees Fahrenheit to an average of 78 degrees Fahrenheit in 30 minutes. The bidder will certify that a substantially similar cab has been tested and has met these criteria.

Cab Defroster

Visibility during inclement weather is essential to safe apparatus performance. The defroster system will clear the required windshield zones in accordance with SAE J381 Windshield Defrosting Systems Test Procedure And Performance Requirements - Trucks, Buses, And Multipurpose Vehicles. The bidder will certify that the defrost system design has been tested in a cold chamber and passes the SAE J381 criteria.

Cab Auxiliary Heater

Good cab heat performance and regulation provides a more effective working environment for personnel, whether in-transit, or at a scene. An auxiliary cab heater will warm the cab 77 degrees Fahrenheit from a cold-soak, within 30 minutes when tested using the coolant supply methods found in SAE J381. The bidder will certify, at time of delivery, that a substantially similar cab has been tested and has met these criteria.

AMP DRAW REPORT

The bidder will provide, at the time of bid and delivery, an itemized print out of the expected amp draw of the entire vehicle's electrical system.

The manufacturer of the apparatus will provide the following:

- Documentation of the electrical system performance tests.
- A written load analysis, which will include the following:
 - The nameplate rating of the alternator.
 - The alternator rating under the conditions specified per:
 - Applicable NFPA 1901 or 1906 (Current Edition).
 - The minimum continuous load of each component that is specified per:
 - Applicable NFPA 1901 or 1906 (Current Edition).
 - Additional loads that, when added to the minimum continuous load, determine the total connected load.
 - Each individual intermittent load.

Columbia Heights Bid 941 Full Specification

All of the above listed items will be provided by the bidder per the applicable NFPA 1901 or 1906 (Current Edition).