

GapVax[®]



INDUSTRIES

PREPARED BY

WECO INDUSTRIES

Noah Johnson - noahjohnson@wecoind.com

PREPARED FOR

JEREMY / TIM

CITY OF COLUSA
840 MAIN STREET
COLUSA, CA 95932

QUOTE

GapVax[®]



QUOTE ID
120325

UPDATED:
2/25/2025



2025 MC1510-3S3X COMBINATION JET/VAC

QUOTE ID: 120325

December 12, 2025

NOTE: THE GAPVAX MC UNIT MAY EXCEED FEDERAL BRIDGE ALLOWABLE WEIGHTS WHEN LOADED WITH WATER, OR DEBRIS, AND/OR BOTH WATER AND DEBRIS COMBINED. PLEASE CONSULT FACTORY.

| | OPTION DESCRIPTION | NOTES | QTY |
|----------------------------|--|------------------------------|----------|
| CHASSIS OPTIONS | | | |
| CHA001 | WESTERN STAR 47X-SF (6 X 4) - 370 HP - 62,000 LB. GVWR - AUTO | MODEL YEAR 2024 | 1 |
| | CUMMINS L9 RATED FOR 370 HP | CONSULT FACTORY | |
| | ALLISON 6 SPEED AUTOMATIC | PRICES MAY VARY | |
| | 22,000 LB FRONT AXLE | | |
| | 46,000 LB REAR AXLE | | |
| DEBRIS BODY OPTIONS | | | |
| STD | 10 USABLE YARD DEBRIS TANK MADE OF 3/16" ASTM A-572 GRADE 50 EXTEN STEEL | | STANDARD |
| STD | FULL-OPENING REAR TAILGATE | | STANDARD |
| STD | STAINLESS STEEL TAILGATE SEALING ROD | | STANDARD |
| STD | FOUR HYDRAULIC REAR DOOR LOCKS | | STANDARD |
| STD | DUAL TAILGATE LIFT CYLINDERS | | STANDARD |
| STD | FRONT MOUNTED HOIST CYLINDER, POWER UP AND DOWN, 55,000 LB CAPACITY | | STANDARD |
| STD | THREE TIE-OFF ANCHORS ON TOP OF BODY | | STANDARD |
| STD | FIVE YEAR WARRANTY ON DEBRIS TANK AGAINST RUST THROUGH, DISTORTION AND CRACKS | | STANDARD |
| STD | THREE TIE-OFF ANCHORS ON TOP OF THE BODY 6' APART | | STANDARD |
| A1C | STAINLESS DEBRIS BODY FLUSH OUT SYSTEM, MOUNTED AT MID-LEVEL IN DEBRIS TANK | INCLUDES LOW POINT DRAIN | 1 |
| A2A | DRAIN AT BOTTOM OF TAILGATE - 6" BRASS LEVER VALVE WITH 15' OF LAYFLAT HOSE | VALVE IS NOT 100% LEAK PROOF | 1 |
| A3-CS | FLOAT TYPE LIQUID LEVEL INDICATOR ON SIDE OF DEBRIS TANK | | 1 |
| A6AX | TRASH PUMP - SETUP ONLY | PUMP NOT INCLUDED | 1 |
| A12A | FILTER SCREEN FOR DRAIN VALVE (LONG BOX) | REQUIRES A2 | 1 |
| A21 | CURBSIDE LADDER TO PORT INSPECTION AREA | | 1 |
| A21B | ADD FOLDING LADDER EXTENSION | REQUIRES A21 | 1 |
| A18 | PURGE VALVE AT GRAVITY DRAIN (1-1/4" BALL VALVE) | | 1 |
| A22A | GALVANIZED BOLT ON TAILGATE SPLASH SHIELDS | | 1 |
| A37A | UPGRADE BODY INLET CANNON TO HX STYLE WITH CLEANOUT | | 1 |
| A44 | PNEUMATIC TAILGATE PROP (IN ADDITION TO STANDARD TAILGATE PROP ROD) | | 1 |

| WATER TANK OPTIONS | | |
|------------------------------|---|-----------------|
| STD | 1500 GALLON WATER TANK MADE OF 3/16" 304 STAINLESS STEEL | STANDARD |
| STD | 4" HIGH ANTI-SIPHON RING WITH (4) 2-1/2" HOLES | STANDARD |
| STD | WATER TANK LEVEL SIGHT TUBE ON CURBSIDE | STANDARD |
| STD | DRAIN VALVE AT BOTTOM OF WATER TANK | STANDARD |
| STD | 3" FILL LINE WITH 2-1/2" FIRE HOSE CONNECTION CURBSIDE | STANDARD |
| STD | 3" WATER STRAINER WITH STAINLESS STEEL SCREEN ON WATER TANK FILL LINE | STANDARD |
| STD | 3" SUPPLY LINE TO WATER PUMP MOUNTED AT REAR HINGE PIN | STANDARD |
| STD | FIVE YEAR WARRANTY ON WATER TANK AGAINST RUST THROUGH, DISTORTION AND CRACKS | STANDARD |
| B23A | GALVANIZED BAFFLES IN THE WATER TANK | 1 |
| B30 | UPGRADE TO BUTTERFLY VALVE IN 3" SUPPLY LINE | STANDARD |
| VACUUM SYSTEM OPTIONS | | |
| STD | TRUE 8" DIAMETER VACUUM SYSTEM | STANDARD |
| STD | VACUUM PUMP DRIVEN VIA MID-SHIP MOUNTED SPLIT SHAFT TRANSFER CASE GEARBOX (PTO) | STANDARD |
| STD | NOISE & VIBRATION DAMPENING MOUNTS ON VACUUM PUMP AND TRANSFER CASE | STANDARD |
| STD | NOISE ATTENUATED VACUUM PUMP DISCHARGE SILENCER WITH RAIN CAP AND DRAIN | STANDARD |
| STD | 24" CENTRIFUGAL CYCLONE SEPARATOR WITH 20" CHAMBER | STANDARD |
| STD | DUAL STAINLESS STEEL SHUTOFF FLOAT BALLS MOUNTED AT THE REAR OF DEBRIS TANK | STANDARD |
| STD | STAINLESS STEEL VEE-WIRE SAFETY SCREEN | STANDARD |
| STD | 6" SAFETY VACUUM RELIEF | STANDARD |
| STD | PANIC SWITCH FUNCTION FOR VACUUM | STANDARD |
| C8 | UPGRADE TO ROOTS TYPE VACUUM PUMP 4,500 CFM AND 18" HG (4) 18" Hg VACUUM RELIEF VALVES | 1 |
| WATER SYSTEM OPTIONS | | |
| STD | TRI-PLEX WATER PUMP SYSTEM | STANDARD |
| STD | AIR PURGE SYSTEM FOR PRIMARY CIRCUIT | STANDARD |
| STD | LOW POINT DRAIN VALVES ON WATER LINES | STANDARD |
| D4 | MULTIFLOW CONTROL AND SAFETY REGULATOR VALVE (MSUV) | 1 |
| STD | WASHDOWN CIRCUIT WITH 50' X 1/2" HOSE, QUICK CONNECT, AND WASHDOWN HAND GUN 50-FT HOSE REEL | STANDARD |
| STD | WASHDOWN CIRCUIT(S) WILL INCLUDE A SAFETY FLOW RESTRICTOR (1/4" HOSE) | STANDARD |
| D7A | HOSE REEL FOR STANDARD WASHDOWN CIRCUIT, 50' X 1/2" | 1 |
| D5A | GIANT GP8000 SERIES WATER PUMP RATED AT 63 GPM @ 3000 PSI (P/N: PUM022800) | 1 |
| D-GPVC | VIBRATION DAMPENING COUPLER - WATER PUMP | REQUIRED |
| D4-GUARD | STAINLESS BRANCH GUARD (P/N: F017493-SS) FOR THE MULTIFLOW CONTROL AND SAFETY REGULATOR VALVE (MSUV) | 1 |
| D21 | WATER RECIRCULATION VIA AUTOMATIC TRANSMISSION (INCLUDES WASHDOWN, ADDITIONAL CIRCUITS, AND LATERAL REEL) JETTER SYSTEM ONLY | 1 |

| | | | |
|--|--|--|----------|
| D27A | 10 GPM / 2,500 PSI HYDRAULICALLY DRIVEN PUMP (COMMON WITH BODY HYDRAULIC SYSTEM) | REQUIRES OPTION J303 HYDRAULIC OIL COOLER | 1 |
| D4-HX+RA | PNEUMATICALLY OPERATED HX WATER PRESSURE RELIEF VALVE WITH ACTUATED HOSE REEL VALVE (P/N: VAL022790) (G2B) | HX SYSTEM | 1 |
| D25B | 100' X 1/2" HOSE GUN REEL FOR HX SYSTEM | | 1 |
| D18 | AIR OUT FOR HX SYSTEM / HX CIRCUIT | | 1 |
| D35B | 1/2" HX LANCE WITH 6' EXTENSION AND RIPSAW NOZZLE | | 1 |
| BOOM OPTIONS | | | |
| STD | 8" FRONT MOUNTED TELESCOPING BOOM WITH 26' REACH AND 180 DEG. ROTATION | | STANDARD |
| STD | 180 DEGREE POWER ROTATION VIA WORM DRIVE | | STANDARD |
| STD | DUAL 4" LIFT CYLINDERS | | STANDARD |
| STD | CAB PROTECTION RACK | | STANDARD |
| E6 | REMOTE LUBE FOR BOOM LIFT AND ROTATION | | 1 |
| E7 | 3/16" HEAVY DUTY BOOM ELBOW WITH 6" FORMED CHANNEL RADIUS | | 1 |
| HOSE REEL OPTIONS | | | |
| STD | FRONT FRAME MOUNTED HOSE REEL WITH 180 DEGREE ARTICULATION | | STANDARD |
| STD | HOSE REEL RATED FOR 800' OF HOSE AND 3,000 PSI | | STANDARD |
| STD | EXTERIOR HOSE EXPANSION RIBS | | STANDARD |
| F1C | DIGITAL FOOTAGE COUNTER - SHAFT-MOUNTED | | 1 |
| F6 | UPGRADE FRONT HOSE REEL TO POWER ARTICULATE VIA HYDRAULICS | | 1 |
| F11 | AUTOMATIC HOSE LEVEL WINDER (INCLUDES "J-HOOK" STLYE HOSE GUIDE) | | 1 |
| F16A | DOUBLE ROLLER UPGRADE ON AUTO LEVEL WIND | | 1 |
| CONTROLS, GAUGES, ACCESSORIES OPTIONS | | | |
| STD | CAB-MOUNTED CONTROLS FOR BLOWER AND HYDRAULICS | | STANDARD |
| STD | CONTROL PANEL MOUNTED AT FRONT HOSE REEL WITH WATER PUMP CONTROLS | | STANDARD |
| STD | OPERATOR CONTROL PANEL INCLUDES GAUGES FOR ENGINE, HYDRAULICS, VACUUM, AND WATER PUMP | | STANDARD |
| STD | PANIC SWITCH TO RELIEVE WATER PRESSURE AND VACUUM ON FRONT PANEL AND CURB SIDE OF UNIT | | STANDARD |
| G2B | G2B CONTROL SYSTEM WITH DM430 DISPLAY INCLUDES: | WIRELESS CONTROL REQUIRED | 1 |
| | LOW WATER SHUTDOWN PROTECTION | | 1 |
| | HIGH WATER TEMPERATURE SHUTDOWN PROTECTION | | 1 |
| | ENGINE OVERSPEED PROTECTION | | 1 |
| | ON-SCREEN DIAGNOSTICS FOR WATER, PTO AND ENGINE LEVELS | | 1 |
| G16 | BOOM UP WARNING | | 1 |
| G19 | WIRELESS REMOTE WITH BOOM, VACUUM, AND WATER PRESSURE FUNCTIONS | STANDARD | 1 |
| NOTE: | WIRELESS TO INCLUDE HX WATER PRESSURE (ON/OFF) CONTROL | | 1 |

| | | | |
|------------------------|---|--|----------|
| G21-TD | AARCOMM TRIDENT REMOTE | | 1 |
| G21-AWR | ADDITIONAL WIRELESS TRANSMITTER | | 1 |
| G30-FHR | ADD SWITCH ON CAB CONSOLE FOR FRONT HOSE REEL ARTICULATE (LEFT/RIGHT) | REQUIRES OPTION F6 | 1 |
| LIGHTING | | | |
| STD | TRUCK-LITE LED RUNNING (MARKER) LIGHTS | | STANDARD |
| STD | LED STOP/TAIL/TURN LIGHT WITH POLISHED STAINLESS STEEL BOXES | | STANDARD |
| H2C | ONE LED STROBE BEACON LIGHT - REAR (CALIFORNIA TITLE-13 COMPLIANT) | (HELLA K-LED 100 LED OR EQUAL) (P/N: LHT022550) | 1 |
| H5B | (2) BOOM WORK LIGHTS - HELLA LED WORK LIGHTS (PN: LHT022429) | | 1 |
| H6B | (2) REAR WORK LIGHTS - HELLA LED WORK LIGHTS (PN: LHT022429) | | 1 |
| H7BA | (2) SIDE WORK LIGHTS - HELLA LED WORK LIGHTS (PN: LHT022429) (1 PER SIDE) | | 1 |
| H38 | CORDLESS RECHARABLE LED LIGHT | | 1 |
| H15B | WHELEN ION SUPER LED FLASHERS - 12 LIGHT HEADS | | 1 |
| | 2 ON EACH SIDE FRONT @ 90 DEGREES, 2 ON EACH SIDE MIDDLE @ 45 DEGREES, 2 ON EACH SIDE REAR (1 @ 45 DEGREES) | | 1 |
| H33 | REAR ARROW LIGHT - LOW PROFILE LED (CA TITLE-13 COMPLIANT) TRAFFIC ADVISOR | (LHT022544, CODE 3 TORUS NARROWSTIK OR EQUAL) | 1 |
| H39B | TWO HIGH INTENSITY LED WORK LIGHTS (HELLA PB1500) ON FRONT HOSE REEL TO SHINE INTO MANHOLE | | 1 |
| STORAGE OPTIONS | | | |
| STD | 25' FIRE HOSE BASKET | | STANDARD |
| I22 | UPGRADE TUBE TRAYS TO STAINLESS STEEL | | 1 |
| I8C-DS | 30" TOOL BOX - STAINLESS STEEL, 30" WIDE X 24" HIGH X 24" DEEP, MOUNTED ON THE DRIVER'S SIDE | | 1 |
| I9C | 48" TOOL BOX - STAINLESS STEEL, 48" WIDE X 24" HIGH X 24" DEEP, MOUNTED ON THE CURBSIDE | | 1 |
| I14 | TRAFFIC CONE HOLDER ON DRIVER'S SIDE | | 1 |
| I16A | WHEEL CHOCK HOLDER (PER SIDE) - DRIVER'S SIDE | | 1 |
| I16B | WHEEL CHOCK HOLDER (PER SIDE) - CURBSIDE | | 1 |
| I17B | NOZZLE RACK - SIX (6) NOZZLES, 3/4" | | 1 |
| I20A | REAR DRAIN HOSE RACK FOR 6" LAYFLAT HOSE X 15' LONG | | 1 |
| I26C | TWO BUMPER TOOL BOXES - STAINLESS STEEL, 16" HIGH X 12" WIDE X 18" DEEP WITH FOLD DOWN DOOR | | 1 |
| CHASSIS OPTIONS | | | |
| STD | DOT LIGHTING / FENDERS / MUD FLAPS / TAILGATE SAFETY PROP, ICC LIGHTS | | STANDARD |
| STD | REMOTE ACTUATED BODY SAFETY PROP | | STANDARD |
| STD | 70 GALLONS AW-46 HYDRAULIC OIL, LEVEL/TEMPERATURE GAUGE, SHUTOFF ON SUCTION | | STANDARD |
| STD | REAR BUMPER, TRIANGLE KIT, FIRE EXTINGUISHER, BACKUP ALARM | | STANDARD |
| STD | ALLISON 10-BOLT PTO UPGRADE | | STANDARD |
| J000 | MID-SHIP MOUNTED (SPLIT-SHAFT) TRANSFER CASE WITH TOP DISCONNECT | | 1 |
| J001 | MUST BE "OMSI" BRAND TRANSFER CASE | | 1 |
| J0B | FRONT BUMPER - CALIFORNA FRONT BUMPER | | 1 |

| | | | |
|------------------------------|--|--|----------|
| J3 | TOW HOOKS FRONT | | 1 |
| J4B | TOW HOOKS REAR - FRAME MOUNTED | | 1 |
| J12-SS | STAINLESS STEEL METAL MUD FLAPS IN FRONT OF REAR TIRES | SS MUD FLAP UPGRADE | 1 |
| J303 | ADD HYDRAULIC OIL COOLER TO CIRCUIT | REQUIRED WITH OPTION D301* OR OPTION D27* | 1 |
| PAINT OPTIONS | | | |
| STD | PAINTED WITH PPG URETHANE PAINT | | STANDARD |
| STD | PAINT BODY WHITE | | STANDARD |
| STD | PAINT FRAME AND PARTS BLACK | | STANDARD |
| STD | PAINT HOSE REEL AND BOOM BLACK | | STANDARD |
| STD | FLEET FINISH | | STANDARD |
| MISCELLANEOUS OPTIONS | | | |
| STD | 25 FEET OF VACUUM TUBING (5) AND CLAMPS | | STANDARD |
| STD | TIGER TAIL HOSE GUIDE | | STANDARD |
| STD | TWO SEWER CLEANING NOZZLES | | STANDARD |
| M3 | FILL HOSE 25' X 2 1/2" | | 1 |
| M5B | LEADER HOSE 10' X 3/4" | | 1 |
| M9F | 3/4" COBRA SEWER HOSE - 3,000 PSI X 800 FT PLASTIC (BLUE) (PN: HOS022495) | | 1 |
| M12 | MANHOLE LIFTING HOOK | | 1 |
| M13 | HYDRANT WRENCH | | 1 |
| M27 | TIGER TAIL (TOTAL OF TWO) | | 1 |
| M28 | (5) TRAFFIC CONES - 28" LIME GREEN WITH REFLECTIVE STRIPE | | 1 |
| M29B | TWO CAMERA - BACK-UP CAMERA SYSTEM WITH 7" COLOR MONITOR (RV-505A), INCLUDES DVR-916 REAR AND DVR-921 FRONT CAMERA | | 1 |
| M35 | ADDITIONAL 8" TUBE CLAMP, EACH (P/N: CLA000978) | STANDARD 8" VAC CLAMP | 1 |
| M36 | HEAVY DUTY ALUMINUM HX TUBE, 8" X 6-FT LONG X 0.090" WALL WITH PRESSED IN STEEL ENDS AND SOFT TIP CUFF END (P/N: PIP008558 & GAS023037) | SOFT TIP | 1 |



PRICING SUMMARY

| | | |
|---|--------------------------|----------------------|
| PRICE OF BASE UNIT WITH OPTIONS: | | \$ 637,517.00 |
| DELIVERY: (\$1,000.00 MINIMUM) | @ \$4.00 PER MILE | \$ 13,000.00 |
| ESTIMATED SUBTOTAL: | | \$ 650,517.00 |
| SALES TAX: | | \$ 49,407.57 |
| TOTAL PRICE (PER UNIT): | | \$ 699,924.57 |

ALL PRICES ARE IN US DOLLARS

ALL ORDERS ARE SUBJECT TO CURRENT PRICES IN EFFECT AT THE TIME OF ORDER ACKNOWLEDGMENT. PRICES AND SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. PRICING DISCLAIMER: WHILE WE MAKE EVERY EFFORT TO MAINTAIN AND PRESERVE PRICING ACCURACY, ALL COST INCREASES INCURRED AFTER ORDER ACKNOWLEDGMENT FOR MAJOR COMPONENTS AND GOVERNMENT MANDATED REQUIREMENTS, TARIFFS, AND RAW MATERIAL SURCHARGES WILL BE PASSED THROUGH AND ADDED TO CUSTOMER INVOICES WITH OR WITHOUT NOTICE. ALTHOUGH THE INFORMATION ON THIS QUOTATION IS PRESENTED IN GOOD FAITH AND BELIEVED TO BE CORRECT AT THE TIME OF PRINTING, WE MAKE NO REPRESENTATIONS OR WARRANTIES AS TO THE COMPLETENESS OR ACCURACY OF THIS INFORMATION. WE RESERVE THE RIGHT TO CHANGE, DELETE, OR OTHERWISE MODIFY THE PRICING INFORMATION WHICH IS REPRESENTED HEREIN WITHOUT ANY PRIOR NOTICE. WE CAREFULLY CHECK PRICING SPECIFICATIONS, BUT OCCASIONALLY ERRORS CAN OCCUR, THEREFORE WE RESERVE THE RIGHT TO CHANGE SUCH PRICES WITHOUT NOTICE. WE DISCLAIM ALL LIABILITY FOR ANY ERRORS OR OMISSIONS IN THE MATERIALS. IN NO EVENT WILL WE BE RESPONSIBLE FOR ANY DAMAGES OF ANY NATURE WHATSOEVER FROM THE RELIANCE UPON INFORMATION FROM THESE MATERIALS. PLEASE CHECK YOUR ORDER TO CONFIRM YOUR PRICING INFORMATION