



600 Knightsbridge Parkway, Lincolnshire, Illinois 60069
 (847) 537-8800 | Fax (847) 520-1147
 turnvalves.com

Quotation

Page 1 of 1

TO: **Mike Stanton**
 Field Operations Supervisor
 City of Cooper City
 11791 SW 49TH ST.
 Cooper City, FL 33330

Date: 10/18/2023
 Quotation Number: HC204537
 Payment Terms: Net 30 Days
 Shipping Terms: FCA Origin
 Valid Through: 12/17/2023
 Estimated Delivery: 8 Weeks ARO
 Reference: BuyBoard#685-22

E.H. Wachs is pleased to offer the following quotation.

Item Number	Description	Qty	U/M	Unit Price (USD)	Disc%	Line Total (USD)
1	77-000-36 Standard LX (Gas) – VMT (RH): Single turner valve maintenance trailer; includes Wachs 750 Ft/lb (1020 Nm) Extended Reach Valve operator for those preventive maintenance activities, telescoping valve key and Wachs ruggedized TC-100 with GPS controller/datalogger. A 27 HP (20 kW) gasoline powered Kohler overhead cam air cooled engine provides ample power for all contained functions, including an auxiliary HTMA Class II circuit; 10 gallon (38 L) reservoir, fan cooled heat exchanger, continuous duty rated for 8 GPM (30.3 LPM) @ 2,000 PSI (140 bar). A positive displacement blower provides 500 CFM (14.2 cmm)-11" (280mm) Hg vacuum, with spoils containment provided by a 250 (950 L) gallon tank with power hydraulic dump (rear discharge) and latching rear door. Also driven from the common power train is a 2.5 GPM (9.5 LPM) @ 3000 PSI (210 bar) pressure washer system with 3 gallon (11.4 L) anti-freeze tank and 95 gallon (360 L) water tank. Includes 2-1/2" (63.5mm), 1-1/4" (31.75mm) & 7/8" (22mm) suction wands and one each short and long wash-down guns. The LX package bundles the service light bar with arrow board, 45' (14 M) auxiliary hydraulic hose reel for operation of hydraulic power tools & Bluetooth tethering module (installed in ERV-750) for wireless communication between the exerciser and Controller/Data Logger and 24" (61cm) X 18" (46cm) x 18" (46cm) aluminum job box.	1	EA	81,995.00	1.5%	80,765.07
2	11-409-00 Telescopic Valve Key - 2" AWWA (Warmer Climate). Manufactured from high-strength steel, adjustable from 3 ft (.91 M) to 8ft (2.44 M) with spring loaded pin to eliminate loss. Rated to 800 lb-ft (1,085 Nm) of torque for use with the Wachs P/2 and RS/2 valve operators and ERV 750. Weighs only 24 lbs (10.9 kg). Add the Tee Handle adapter (11-408-10) for manual functionality when machine is not in use.	1	EA	645.00	1.5%	635.32
3	79-430-20 Field training - 1 day program. Training topics range from field operation of the mechanical systems like hydro-excavation and Valve operator; to training of computerized controllers and preventive maintenance software like VITALS. Field crews and participants will be shown, in detail, standard procedures for safe and efficient operation and use of valve maintenance tools.	1	EA	2,495.00	100.0%	0.00
Subtotal						81,400.39
Motor Freight, Including Handling						2,730.00
Total (USD)						\$84,130.39

We will prepay and add shipping charges to your order, or we can ship collect via your choice of carrier service. If you have any questions please feel free to call Hassan Cruz at 847-778-8824 or call me at 847-484-2773.

If you are tax exempt, please supply your identification number and certificate with your order. If your exempt number is not on file, tax will be added to your invoice.

Please reference this quote number when placing your order. Thank you.

Ken Redding
 Technical Service Rep
 847-484-2773
 ken.redding@ehwachs.com

Sales of E.H. Wachs products and services are expressly limited to and made conditional on acceptance of its current Terms and Conditions of Sale, found at www.ehwachs.com ("Terms"). Any additional or different terms are hereby rejected. Commencement of work by E.H. Wachs or acceptance of delivery of products by you constitutes your acceptance of the Terms.