

-- Standard Features --

-- Custom Options --



S Series

SVL75-3HFWVC

*** EQUIPMENT IN STANDARD MACHINE ***

FEATURES

Vertical Lift Path Loader Frame
Standard Front Quick Coupler,
Float Standard
Hydraulic Quick Coupler Option
Selector Loader Arm Self-
Leveling
Loader Boom Lock
Open ROPS & Air Conditioned
ROPS/FOPS Cab Models
High Back, Adjustable, Vinyl,
Suspension Seat
2" Retractable Seat Belt and 2-
Piece Seat Bar
12V Electric Outlet
19.2 gpm Auxiliary Hydraulics
standard, 29.8 gpm Option
Direct To Tank Return Line
Rigid Mounted Undercarriage, 4
Lower Track Rollers
Rubber Tracks, 12.6" Standard,
15" Optional
Two Speed Travel System
Automatic Wet Disk Parking
Brake
Kubota 4 Hydraulic Pump Load
Sensing System
2 Gear, 2 Variable
Displacement Pumps
Hydraulic Joystick Controls,
Optional Multi-Functional Grips
ISO Operating Pattern
Hand And Foot Throttle
Controls
Electronic Travel Torque
Management
Automatic Glow Plugs
7" Multifunction Touch Screen
Integrated Rear Camera
Keyless Start
Self Bleed Fuel System
2 Front and 2 Rear Working
Lights
Hour Meter, Engine
Temperature and Fuel
Gauges and Warning Lights
Horn and Backup Alarm
Lockable Fuel Cap
Bolt On Grab Handles to enter
machine
KubotaNOW Telematics

BASIC UNITS

SVL75-3, 15.8" Rubber Tracks,
Open ROPS/FOPS Cab
Hydraulic Quick Coupler
High Flow Hydraulics & MF Grips
14-Pin Coupler
Reversing Fan

ENGINE
V3307 Kubota CR-TE4, Tier 4
Diesel Engine
4 Cylinder, 4 Cycle, Turbo Charged
74.3 Gross HP @ 2400 rpm

DIMENSIONS

Cab Height 81.8"
Width (without attachment) 65.9"
Width with wide track option
(without attachment) 69.1"
Length (without attachment) 112.0"
Length of Track on Ground 56.5"

OPERATIONAL

DIMENSIONS
Operating Weight*, SVL75H, 12.6"
Rubber Tracks, Open
ROPS/FOPS Cab, Mechanical
Quick Coupler 9,190 lbs.
Rated Operating Capacity (@ 35%
of Tipping Load) 2,490 lbs.
Rated Operating Capacity (ROC)
@ 35% of Tipping Load complies
with ISO 14397-1and SAE J 818
for crawler loaders
Rated Operating Capacity (ROC)
@ 50% of Tipping Load 3,557 lbs.
Tipping Load 7,112 lbs.
Auxiliary Hydraulics Flow 192/
29.8 gpm
Travel Speed (Low / High)
5.6 /8.6 mph
Reach @ Maximum Height 39.6"
Height to Hinge Pin 122.7"
Ground Pressure (Standard Track)
5.8 psi
Ground Pressure (Wide Track) 4.7
psi
Traction Force 9,678 lbf.

* Includes operator's weight, 175
lbs.

SVL75-3HFWVC Base Price: \$82,784.00

| | |
|---|--------------------|
| (1) AT&T TELEMATICS MODEM DCU6700-AT&T TELEMATICS MODEM | \$449.00 |
| (1) 74" Heavy Duty Low Profile, Long Floor, Teeth, Side Cutter, 19.2 cu-ft heaped capacity AP-HD74LLT-74" Heavy Duty Low Profile, Long Floor, Teeth, Side Cutter, 19.2 cu-ft heaped capacity | \$2,515.00 |
| Configured Price: | \$85,748.00 |
| Sourcewell Discount: | (\$20,579.52) |
| SUBTOTAL: | \$65,168.48 |
| Dealer Assembly: | \$14.67 |
| Freight Cost: | \$831.25 |
| PDI: | \$400.00 |

Total Unit Price: \$66,414.40
Quantity Ordered: 1
Final Sales Price: \$66,414.40

Purchase Order Must Reflect Final Sales Price.

To order, place your Purchase Order directly with the quoting dealer

*Some series of products are sold out for 2022. All equipment specifications are as complete as possible as of the date on the quote. Additional attachments, options, or accessories may be added (or deleted) at the discounted price. All specifications and prices are subject to change. Taxes are not included. The PDI fees and freight for attachments and accessories quoted may have additional charges added by the delivering dealer. These charges will be billed separately. Prices for product quoted are good for 60 days from the date shown on the quote. All equipment as quoted is subject to availability.