

- Epoke North America
- Products
- Dealer Locations
- Contact Us
- Login

H

SKE 20



Products > Towed Spreaders > SKE 20



SKE 20 Towed Spreader

Epoke SKE 20 - road speed related towed spreader

with the following standard features and included options:

- · Spring base and spring base adjustment
- Transmission
- Solid support wheel
- 3" draweye
- · Rubber base for salt
- One-sided transmission
- 24% reduction
- Lights
- Electric remote
- Agitator
- · Delivery roller with 3 mm cams
- 7.5 X 10/14 ply tires



TECHNICAL DATA:

Metric]

Imperial

Capacity	1.65 cubic meters	2.16 cubic yard
Total Width	2195 mm	86.4 inches
Track Gauge	1530 mm	60 inches
Spreading Width	1918 mm	75.5 inches
Weight	720 kg	1588 lbs.
Linear Working Range (Salt) @ typical application rates	52.1 km	32.4 miles

Need a Parts Book or Operation Manual?

CLICK HERE TO REQUEST A MANUAL

Contact Us


1-888-334-2464

Product Information Canadian Sales Canadian Dealers

Sourcewell Awarded Contract: 080818-EPK



- Canadian Dealers
- · Canadian Sales Inquiries
- Product Information
- USA Inquiries





THE EPOKE ADVANTAGE

epoke is innovation

From the original spinner disc through ongoing advancements in runway, walkway and road maintenance, Epoke is innovation!

environment

Epoke's advanced control system ensures accurate rates and precise placement of material- reducing environmental impact!

ease of use

Compact size, big results!

endurance

We build it. We Back it! Manufactured to ISO standards with quality components - Epoke spreaders are built to last and backed with an industry best warranty!

economy

From reductions in material use to long life components... save money on materials, save money on your spreader life cycle cost!

Epoke dealers are chosen because of their expertise and commitment to providing superior customer service and solutions. Our dealer program provides comprehensive and ongoing training as well as integrated customer support. Service you can rely on, equipment you can depend on - a team you can trust!

Epoke North America Inc.

2458 Huntley Road, Stittsville, ON Canada, K2S 1B8 Tel. 613 838-2300 Toll Free 888 334-2464 Fax 613 838-2336

www.epokena.com

TK, TMK & PSL Series

TKB12-280

epoke

TMK10-275



Towed- road speed related Municipal Grade Spreads when driving forward and backward Optional hopper empty sensor



Towed- road speed related Contractor Grade Spreads when driving forward (only) Optional hopper empty sensor

Capacity	1.2 m ³	1.6 cubic yard
Total Width	2800 mm	110″
Track Gauge	1800 mm	71"
Spreading Width	2500 mm	98″
Weight	710 kg	1565 lbs

Capacity	1.0 m ³	1.3 cubic yard
Total Width	2750 mm	108″
Track Gauge	2330 mm	92"
Spreading Width	2000 mm	79″
Weight	400 kg	882 lbs

PSL 6.5

Capacity	600 liters	3/4 cubic yard
Total Width	1980 mm	78"
Spreading Width	1770 mm	70"
Weight	315 kg	695 lbs

3 Point Hitch Mount Self Loading Requires 2 tractor hydraulic circuits:

> Loading Spreader operation



SKE 15

SKE 8



- Towed- road speed related
- Municipal Grade
- Optional Combi Liquid Kit:
 - On new builds or can be retrofit on existing units
 - 360 liter (95 gallon) liquid tanks



Capacity	750 liters	1 cubic yard
Total Width		
Track Gauge	790 mm	31"
Spreading Width	1008 mm	40"
Weight	400 kg	880 lbs



- Towed- road speed related
- Municipal Grade
- Optional 0.5 m³ (0.7 cubic yards) hopper extension

Capacity	1.25 m ³	1.64 cubic yard
Total Width	1665 mm	
Track Gauge	1000 mm	31″
Spreading Width	1390 mm	
Weight	600 kg	1323 lbs
AND ARROWS A SECURITION OF THE PARTY OF THE		

SKE 20



	2.16 cubic yard
2195 mm	816"
1530 mm	60"
1920 mm	76"
720 kg	1588 lbs
	1530 mm