



1051 W 7th Street
Monroe, WI 53566
Sales Rep: Rick Nafzger
Ph: (608) 558-0285
www.MonroeTruck.com

J.O. #

Quotation ID: 9KB2000321
Date: 12/8/2025
Valid thru: 1/7/2026
Terms: NET 30
Quoted by: Kevin Book
Ph/Fax: 608-329-8158 /

Quoted to:

HALLADA MOTORS (FORD) (ATTN: TED JACKSON)
306 E LEFFLER
PO BOX 329
DODGEVILLE, WI 53533
Ph: 608-935-2352 / Fax: 608-935-5973
Email: ted@hallada.com

CITY OF DODGEVILLE

Chassis Information

Year: 2026	Make: FORD		Model: F-550		Chassis Color:	Cab Type: REGULAR
Single/Dual: DRW	CA: 60.0	CT: -1.0	Wheelbase: 145.0	Engine: DIESEL	F.O. Number #:	Vin:

Notes:

Monroe Truck Equipment, Inc. is pleased to offer the following quote for your review:

Description	Amount
MONROE SNOW FIGHTER PACKAGE	

9', MTE D-SERIES, 7 GA. STAINLESS STEEL, 3-4 YD CAPACITY, RIGID SIDE, DUMP BODY W/ AR FLOORING

- 7 GA. AR-400 (ABRASIVE RESISTANCE), 145,000 PSI YIELD STRENGTH FLOOR
- 7 GA., 45,000 PSI YIELD STRENGTH STAINLESS STEEL SIDES & ENDS
- 16" H DOUBLE WALL SIDES, 22" H TAILGATE
- HEAVY DUTY FRONT BULKHEAD WITH INTEGRAL 12" TAPERED CAB SHIELD & TAPERED LASER CUT WINDOW
- INTERNAL DIRT SHEDDING TOP RAILS & TAILGATE
- CROSS-MEMBERLESS UNDERSTRUCTURE W/ STAINLESS STEEL LONG SILLS
- SINGLE-LEVER RELEASE, QUICK DROP TAILGATE
- L.E.D. FMVSS108 LIGHTS & REFLECTORS
- LONG LIFE & CORROSION RESISTANT
- UNDERCOATED

MONROE HYDRAULICS PKG WITH FORCE AMERICA SSC5100EX SPREADER CONTROL (STAINLESS STEEL)

- 12.5 GP MANIFOLD VALVE ASSY
- OPEN CENTER, 2500 P.S.I. PRE-SET SYSTEM RELIEF, 20 GPM CAPABLE
- PRIORITY FLOW FOR PLOW
- DOUBLE ACTING ELECTRIC PROPORTIONAL CONTROL HOIST SECTION WITH A 500 P.S.I. DOWN PORT RELIEF
- BOSS DOUBLE ACTING ELECTRIC CONTROL PLOW LIFT WITH FLOAT & SMART HITCH
- BOSS DOUBLE ACTING ELECTRIC PROPORTIONAL CONTROL PLOW ANGLE
- ELECTRIC PROPORTIONAL AUGER FUNCTION, 14 GPM
- ELECTRIC PROPORTIONAL SPINNER FUNCTION, 5 GPM
- MUNCIE PTO/PUMP

HYDRAULIC RESERVOIR/ENCLOSURE

- 13 GALLON CAPACITY
- FILLER/BREATHING CAP, LEVEL/TEMP SIGHT GLASS, 3/4" MAGNETIC PLUG
- IN-TANK FILTER, 10 MICRON, 60 P.S.I. CONDITION INDICATOR
- IN-TANK BAFFLE
- VALVE WILL BE INSTALLED IN A WEATHER-TIGHT COMPARTMENT ON RESERVOIR
- HYDRAULIC RESERVOIR/ENCLOSURE WILL BE MOUNTED ON FRAME RAIL
- STAINLESS STEEL

CONTROLS

- DASH MOUNTED MOMENTARY ROCKER SWITCH FOR HOIST CONTROL



Description	Amount
FORCE SSC5100EX SPREADER CONTROL	
- MAINTAINS CONSTANT APPLICATION BASED ON VEHICLE SPEED - EASILY CHOOSE BETWEEN MANUAL AND GROUND-BASED SPREADING APPLICATIONS - CREATES REPEATABLE PRECISE CONTROL OF SPREADER AND SPINNER SETTINGS - INTEGRATED SPINNER/BLAST DIALS THAT PROVIDE SIMULTANEOUS SPINNER ADJUSTMENT WHILE BLAST IS ACTIVATED - A MOMENTARY OR TIMED PREFERENCE CAN BE TAILORED FROM 0-15 SECONDS FOR THE INDIVIDUAL OPERATOR - SELECTABLE VALVE DRIVE FREQUENCY - OPERATE SPREADER STANDBY AND BLAST FUNCTIONS THROUGH FRONT PANEL - MANUAL RESET CIRCUIT BREAKERS - REVERSE POLARITY AND OVER-VOLTAGE PROTECTION - COLOR-CODED WIRING - MOUNTED WITHIN EASY REACH OF OPERATOR	
MISCELLANEOUS HOSES & FITTINGS	
- HYDRAULIC HOSES & FITTINGS; RUN TO REAR FOR SPREADER - HYDRAULIC HOSES & FITTINGS; PTO MOUNTED KIT - MANIFOLD PLATE, RUBRAIL MOUNTED (BOTH SIDES); INSTL - DUST COVERS FOR ALL QUICK COUPLERS	
10' BOSS POWER-V-DXT SNOWPLOW	
STANDARD EQUIPMENT:	
- HIGH PERFORMANCE HYDRAULIC PACKAGE - ENCLOSED HYDRAULICS - CHAINLESS HYDRAULIC CYLINDER LIFTING SYSTEM - DUAL-TRIP DESIGN - FLARED WINGS - RUBBER SNOW DEFLECTOR - REINFORCED MOLDBOARD - HEAVY-DUTY PUSH FRAME AND QUADRANT - INSTALLED - TWO-YEAR LIMITED WARRANTY	
MONROE 6" ONE-WAY FLIGHT UNDER-TAILGATE SPREADER	
STANDARD EQUIPMENT:	
- 7 GA. TROUGH - 1/4" END PLATES - FULL OPENING TOP AND BOTTOM CLEAN-OUT DOORS - 6" AUGER DIAMETER - DUAL DISCHARGE - STAINLESS STEEL QUICK DETACH MOUNTING BRACKETS - STAINLESS STEEL TAILGATE SHIELDS - BARE STAINLESS FINISH (NOT PAINTED) - 18" POLY SPINNER DISC - SELF LEVELING SPINNER ASSEMBLY WITHOUT STABILIZER RODS - INSTALLED	
LIGHTING AND ELECTRIC	
- MONROE/WHELEN RESPONDER SERIES L.E.D. MINI LIGHT BAR; AMBER; MTR1LP - SELF-LEVELING BRACKET FOR MINI LIGHT BAR - (2) VTX609A STROBES ON REAR CORNER POST ABOVE STOP/TAIL/TURN LIGHTS - (2) VTX609A STROBES MOUNTED TO CAB SHIELD SIDES - *** STAINLESS VGUARD TO PREVENT STROBE FLASH IN MIRRORS - (2) VTX609A STROBES IN FRONT GRILL ON SEPERATE SWITCH - ALL BODY LIGHTS TO BE L.E.D. - L.E.D. CLEAR SPREADER LIGHT MOUNTED ON SPREADER W/ WEATHER PACK CONNECTOR	
Quote Total:	\$58,427.00