



Quoted For: City of Forest Park
 Dealer: Reynolds-Warren

Date: 1/23/24

SOURCEWELL Contract #: **060122-VTL**

Tack Distributor

Tack Distributors include: Single nozzle 6-ft handspray wand, with 40-ft hose reel, and 1 propane burner w/5 pass flue. All trailer-mounted units include safety chains and pintle eye standard, and are pre-wired for towing. The L300T is equipped with single axle electric brakes and emergency break-away switches; the L600 is equipped with electric brakes on both axles & emergency break away switches and waste bucket mount.

TOTAL LIST PRICE BASE UNIT:	300 Trailer	\$	22,204.00
Options:			
TOTAL:		\$	22,204.00
SOURCEWELL DISCOUNT (10%)	-	\$	2,220.40
TOTAL SOURCEWELL LIST PRICE:		\$	19,983.60
FREIGHT SPECIAL ONE TIME PRICING (good for 2 days from the date quoted):		\$	2,000.00
TOTAL PRICING DELIVERED TO AGENCY:		\$	21,983.60

POSSIBLE OPTIONS, MANUFACTURE LIST PRICE:

(Options do qualify for the Sourcewell Discount with machine order)

150 Skid	\$	18,616.00
150 Trailer	\$	20,049.00
300 Skid	\$	20,773.00
300 Trailer	\$	22,204.00
600 Skid	\$	27,076.00
600 Trailer	\$	28,509.00
6 HP Hatz Diesel Engine (electric start)	\$	4,203.00
4.8 HP Gas Engine (electric start)	\$	1,449.00
12 HP Gas Engine (electric Start)	\$	2,899.00
Diesel Burner w/Auto Ignition Burner w/Outfire Protection *only w/Elec. Start Engine	\$	2,825.00
Insulated Tank (150 Gallon)	\$	3,525.00
Insulated Tank (300 Gallon)	\$	3,917.00
insulated Tank (600 Gallon)	\$	4,701.00
12 ft Spray Bar	\$	2,355.00
12 ft Spray Bar with Cab Controls - Includes Remote	\$	2,820.00
12 ft Spray Bar with Spray Bar Lift - Includes Remote	\$	5,362.00

12 ft Spray Bar with Cab Controls and Lift - Includes Remote	\$	6,921.00
Surge Brakes for L150T/L300T	\$	2,807.00
Surge Brakes for L600T	\$	3,362.00

L300 Tack Tank

LeeBoy



Performance Features:

Perfect for the all-inclusive commercial paving contractor, the L300 Tack Distributor provides a perfectly sized tank for small to large projects including parking lots, patching, driveways or soil stabilization. Daily task can be completed with ease by relying on the trouble-free Honda powered engine and the proven reliable user-friendly design. Uniquely configurable, the customizable options give the contractor the ability to create a solution specific to their exact needs.

- 300 Gallon (1,136 l) Capacity Tank
- 4.8 hp (3.6 kw) Honda Engine
- 6' (1.8 m) Wand with On/Off Valve
- 40' (12.19 m) Heavy-Duty Recoil Hose Reel
- 4,210 lbs (1,909 kg) Loaded Weight
- 1" (25 mm) Rear Tank Sampling Valve
- One 300,000 BTU Propane Burner
- Trailer-Mounted or Skid-Mounted Configurations
- Electric brakes
- Emergency Brake-Away System
- Optional Accessories Available



L300 Tack Distributor Specifications



Tank Size	300 gallons (1,136 l)	Wand	- 6' (1.829 m) wand with cold handles - On/off valve - Removable spray tip
Dimensions (Trailer Configuration)	- Length: 12' 1" (3.68 m) - Width: 6' 4" (1.94 m) - Height: 5' 9" (1.76 m) - Shipping Weight: 1,760 lbs (798 kg)	Manhole	- 20" (508 mm) diameter - 10" (254 cm) diameter fill hole - 3 psi (2.1 bar) pressure relief
Dimensions (Skid Configuration)	- Length: 8' 10" (2.69 m) - Width: 4' 3" (1.28 m) - Height: 4' 9" (1.45 m)	Clean Out	- 4" (102 mm)
Engine	Honda – 4.8 hp (3.6 kw)	Sampling Valve	- 1" (25 mm)
Capacities	- Fuel: 1 gallon (3.79 l)	Additional Standard Equipment	- Waste bucket mount (trailer only) - 1" rear tank return - 2" in-tank overflow
Tank Dimensions	- Length: 52" (1.32 m) - Width: 54.125" (1.37 m) - Height: 36.25" (.92 m)	Optional Equipment	Engines - Honda gas - 4.8 hp (3.6 kW) electric start - Hatz diesel - 7.2 hp (5.4 kW) pull start or electric start Fuel: 1.32 gallons (5.0 l) Heat Systems - Diesel Burner One 300,000 BTU diesel burner (only available with electric start engines) 7 gallon (26.5 l) fuel tank Auto ignition diesel burner with outfire - Overnight Heat 120 volt/1500 watt Immersion element Spray bar - Spray width: 12' (3.65 m) - Spray Bar Controls: In-tank wireless remote controls (requires spray bar option) - Spray bar lift with wireless remote control Insulated Tank 2-5/16" ball hitch
Asphalt Pump	- Specially designed 7 gallons per minute (26.5 lmp) pump		
Heat System	- One 300,000 BTU propane burner - One start burner - 40 lbs (18.1 kg) propane fuel tank		
Temperature Gauge	- 50 - 300° F (10 - 149° C) - Adjustable angle faceplate		
Flush Tank	- 7 gallons (26.5 l) tank with suck back valve		
Hose and Reel	- .5" x 40' (13 mm x 12.19 m) heavy-duty recoil hose reel		



ST Engineering LeeBoy, Inc. ■ 500 Lincoln County Parkway Extension ■ Lincolnton, NC 28092 ■ 704.966.3300
www.LeeBoy.com

LeeBoy and the LeeBoy logo are registered trademarks of ST Engineering LeeBoy, Inc. Equipment model names, slogans and subsidiary logos appearing in this collateral may be registered trademarks or the trademarks of ST Engineering LeeBoy, Inc. The technical data contained herein is subject to change due to continuous engineering and development. Accordingly, LeeBoy reserves the right to modify at any time. © 2020 ST Engineering LeeBoy, Inc. All rights reserved. BR-4004.6-EN

