

## **INTRODUCING: PULASTIC CLASSIC 110**

A seamless multi-purpose sports floor that provides strength and performance for all levels of play and competition



Pulastic Classic 110 is approved according to the EN 14904 Standard - Category P1

3rd PARTY

- Approved by FIBA, FIVB, and IHF
- Manufactured under ISO 9001, ISO 14001, and CSR Level 3 (ISO 26000)
- Good resiliency for comfort and injury prevention
- Seamless, non-porous and smooth surface for easy maintenance, repair and resurface options
- Excellent contact noise reduction for outstanding acoustic isolation
- Sustainability through high content of recycled and rapidly renewable raw materials
- Water based finish for very low odor during installation and maximum indoor clean air protection during use
- Outstanding mechanical strength and wear resistance for optimal life cycle cost and maximum usability





## INDOOR | MULTI- PURPOSE | BASKETBALL | VOLLEYBALL AEROBICS | TRAINING FACILITY | COMPETITION LEVEL

## **Product Specifications**

<del>-</del>		
Nominal Thickness	11 mm	
Character	Point-Elastic	
Shock Absorption	28%	EN 14808
Vertical Deformation	1.4 mm	EN 14809
Ball Bounce	98%	EN 12235
Resistance to Rolling Load	≥ 1500 N	EN 1569
Resistance to Impact	≥800 gr @ 10°C	EN 1517
	≥ 1200 gr @ 17°C	EN 1517
Resistance to Indentation	0.35 mm @ 5 min	EN 1516
	0.15 mm @ 24 hrs	EN 1516
V.O.C. Content- Adhesive	Solvent Free	
V.O.C. Content-Finish	45 gr/lit	ASTM D 3960
Elongation at break-Structure	150%	DIN 53455
Tensile Strength- Structure	8 N/mm²	DIN 53455
Tear Strength- Structure	25 N/mm	DIN 53515
Warranty	Standard 2 year manufacturer's	
Egis	warranty with optional Extended	
FLOORLIFE	Warranty Program ( <i>Egis Floorlife</i> )	

## 16 Classic Colors to Choose From



\*Custom color options available. Due to printer variation, actual floor colors may be slightly different from colors above. Consult your dealer for color accuracy.



robbinsfloor.com | 1.800.543.1913