

PROPOSAL **ARCHITECTURAL GLASS AND METAL**

3 Liebich Lane, Suite #1
Clifton Park, New York 12065
P: (518) 371-7007 x 130
F: (518) 371-0767
E-mail – mseymour@agmglass.com

PROPOSAL SUBMITTED TO
building@townofhalfmoon.org

PHONE
Paul Maiello

FAX

STREET
1 Town Park Plaza
Clifton Park, NY 12065

JOB NAME
Town of Halfmoon
Clerk Window

DATE
9/3/25

We hereby submit specifications and estimates for:

PO #

Base Bid:

Remove existing 1/4" glass and trim and dispose of
Install new 1.25" Level 3 Laminated Polycarbonate Acrylic as requested
Trim and seal as required
Includes : 2 Voice Ports and 2 15"x3" pass-thru cut-outs
**Measurements for pass thru are from existing countertop that is not to change
and will be modified by others for 2nd pass-thru opening to match existing as per Paul

Additional Exclusions:

6-8 week +/- LEAD TIME

We propose hereby to furnish material and labor -- complete in accordance with above specifications, for the sum of:

Base Bid \$ 11,000.00 + TAX IF YOU ARE EXEMPT PLEASE FORWARD A COPY WITH THIS SIGNED QUOTE

All work is to be completed in a workmanlike manner according to standard practices. Any alteration or deviation from the above specifications, involving extra cost, will be executed only upon written orders, and will become an extra charge over and above the base proposal. All agreements are contingent upon strikes, accidents, or delays beyond our control. The owner is to carry all necessary insurances. Our workers all fully covered by Workers Compensation Insurance.

Authorized Signature: Mike Seymour

Note: This proposal may be withdrawn by AGM if it is not accepted within **14** days from the date of sending.

Acceptance of Proposal -- The above prices, specifications, and conditions are satisfactory and are hereby accepted. You are authorized to do the work as specified. Payment will be made as outlined above.

Date of Acceptance: _____

Signature _____

Signature _____

COMPONENTS

Threat Layer 1: 1/8" Mar Resistant Polycarbonate
Layer 2: .025 Urethane
Layer 3: 1" Acrylic
Layer 4: .025 Urethane
Secure Layer 5: 1/8" Mar Resistant Polycarbonate

LAMINATED POLYCARBONATE

PRODUCT: LP 1250 BR 1 1/4"



PROPERTIES & SPECIFICATIONS

Protection	.44 Mag
Ballistic Data	Velocity 1: 1350 ft/s Velocity 2: 1485 ft/s
Shots	3
Light Transmission	77.00%
Thickness	1.25 "
Weight	7.7 lbs/sqft
Dimensional Tolerance	ASTM C 1349

STANDARDS

- NSI Z971-1984 Safety Glazing Materials for Building
- ASTM C 1036 Standard Specifications for Flat Glass
- ASTM C 1172 Standard Specification for Laminated Architectural Flat Glass

HANDLING INFORMATION

It is imperative to clean the glazing unit during and after the construction period to maintain optimum performance and aesthetic properties. To clean, use a soft, clean cloth and a mild soap, detergent, or slightly acidic cleaning solution (such as vinegar). Wipe with a clean, lint-free cloth.

STANDARD WARRANTY

12-month limited warranty. Does not cover damage from neglect, abuse, vandalism, improper maintenance, or any other cause not arising out of defects in material or workmanship. The warranties stated replace and exclude all other warranties. The warranty is limited to replacing products that fail to meet specification, defective in quality, or workmanship at time of delivery. TSS is not responsible for (re)installation expenses or any direct or indirect losses which may result from a defective product. TSS reserves the right to field inspect any product alleged to be defective. Buyer is responsible for any consequences from product use.

BALLISTIC AND FORCED ENTRY RATING

- H.P. White TP-0500.01 Level IV –Forced Entry
- H.P. White Level C Ballistics - .44 Mag
- U.L. Level 3 – .44 Mag
- U.L. Level 6 – 9 mm Rifle
- NIJ STD-0108.01 Level IIIA - .44 Mag
- WMFL Level - .44 Mag

TOTAL SECURITY SOLUTIONS

P: 517.223.7807 | info@tssbulletproof.com | F. 517.223.0805 | 935 Garden Lane, Fowlerville, MI

Proprietary information not for public distribution