

Premium Wood

Collection	Living Local
Style Name	Premium Wood
Style Number	C0194
Product Type	LVT
Size	7.72 in X 51.97 in
Installation	Brick Ashlar

Feature	Description
Overall Thickness	2.5 mm
Wear Layer	20 mil (0.5 mm)
Finish	M-Force™ Ultra
Surface Profile	Overall Emboss
Edge Profile	Micro-beveled Edge
Squareness	(ASTM F2421) Passes
Square Ft per Carton	36.22
Pounds per Carton	30.42
Pieces per Carton	13
Classification	ASTM F1700 - Class III, Type B - Embossed
Size and Tolerance	(ASTM F2055) Passes
Recommended Adhesive	M95.0, M99, M700 Plus, or Total Bond Adhesive
Type of Construction	Commercial Grade Luxury Vinyl Tile
Thickness	(ASTM F386) Passes
Installation Method (Click or Glue)	Glue Down




Recommended Installation Methods



Brick Ashlar



Brick Ashlar



Brick Ashlar

Colorways



Studio

Color code: 095
Style number: C0194



Shadow

Color code: 096
Style number: C0194



Western Woods

Color code: 123
Style number: C0194



Fawn

Color code: 210
Style number: C0194



Scone

Color code: 235
Style number: C0194



Almond

Color code: 330
Style number: C0194

Colorways



Cedar

Color code: 332
Style number: C0194



Brick

Color code: 358
Style number: C0194



Bisque Ware

Color code: 560
Style number: C0194



Tan Tone

Color code: 812
Style number: C0194



Sandy

Color code: 829
Style number: C0194



Beagle

Color code: 838
Style number: C0194



Cocoa

Color code: 889
Style number: C0194



Silver

Color code: 918
Style number: C0194



Bay Leaf

Color code: 939
Style number: C0194



Gorgeous Gray

Color code: 949
Style number: C0194



Two Tone

Color code: 958
Style number: C0194



Lead

Color code: 989
Style number: C0194

Performance

Feature	Description
Static Load	(ASTM F970) 1000 psi
Dimensional Stability	(ASTM F2199) Passes
Residual Indentation	(ASTM F1914) Passes
Resistance to Chemicals	ASTM F925 - Passes - No more than a slight change
Resistance to Heat	ASTM F1514 - Passes -ΔE <8
Resistance to Light	ASTM F1515 - Passes -ΔE <8
Critical Radiant Flux	ASTM E648 - Class 1 (>0.45 W/cm2)
Smoke Density	(ASTM E-662) ≤ 450
Flexibility	(ASTMF137) Passes
Thickness	(ASTM F386) Passes

Sustainability

Feature	Description
Floor Score	Floor Score Certified
Certification Detail	Utilizes 100% closed-loop pre-consumer recycled content allocation
Country of Origin	USA
Environmental Product Declaration	Flex 2.5 LVT EPD (Made in the USA)
Beyond Carbon Neutral	This product is 100% carbon neutral plus an additional 5% offset
Carbon Handprint	-0.03 kg CO2e/ft2
Embodied Carbon	0.6 kg CO2e/ft2

Warranties

Limited 20 Year M-Force Ultra Commercial Warranty