DEVELOPMENT STANDARDS IN RESIDENTIAL ZONES							
		Zones					
Development Standard	R1-25	R1-15	R1-10	R1-8	RM-1	RM-2	RM-3
Lot standards:							
Average lot area ²	15,000 sq. ft.	15,000 sq. ft.	10,000 sq. ft.	8,000 sq. ft.	n/a	n/a	n/a
Minimum lot area or acreage	12,000 sq. ft.	12,000 sq. ft.	8,000 sq. ft.	6,400 sq. ft.	10,000 sq. ft.	1 acre	1 acre
Minimum lot width and/or project frontage	89 ft.	90 ft.	80 ft.	70 ft.	80 ft. project	100 ft. project	200 ft. proje
					30 ft. unit	30 ft. unit	30 ft. unit
/	n/a	n/a	n/a	n/a	6 units/lots	10 units/lots	15 units/lot
Building standards:							
Maximum height, main building ³	34 ft.	35 ft.	35 ft.				
Maximum height, accessory building ⁴	19 ft.	20 ft.	20 ft.				
Maximum size, accessory building	1,200 sq. ft.	1,200 sq. ft.	1,200 sq. ft.	500 sq. ft.	1,000 sq. ft.	1,000 sq. ft.	500 sq. ft.
Building coverage: See subsection 10-37-12I of this title	50% of lot	50% of lot					
Distance between buildings	No requirement	No requirement	No requirement	No requirement	20 ft.	20 ft.	20 ft.
Setback standards - front yard:							
Any building ⁵	24 ft.	25 ft.	25 ft.				
Setback standards - rear yard:							
Main building	19 ft.	20 ft.	20 ft.	10 ft.	10 ft.	10 ft.	10 ft.
Accessory building, including private garage ⁶	19 ft.	20 ft.	20 ft.	10 ft.	10 ft.	10 ft.	10 ft.
Setback standards - interior side yard:							
Main building	9 ft.	10 ft.	10 ft.	10 ft.	10 ft.	10 ft.	10 ft.
Accessory building, including private garage	See note 6	See note 6					
Setback standards - street side yard:							
Main building ⁷	19 ft.	20 ft.	20 ft.				
Accessory building	See note 6	See note 6					

Notes:

- 1. Duplex only permitted on first 10,000 square feet. Any additional units must meet density per acre standards.
- 2. "Average size" means the total acreage devoted to lots divided by the number of lots. Net density definition shall apply.

- 3. Except as otherwise permitted by subsection 152-13-7C of this chapter.
- 4. Except as otherwise permitted by subsection 152-13-7B of this chapter.
- 5. Except as modified by the provisions of subsection 152-37-12F, "Setback Measurement", of this chapter.
- 6. If located at least 10 feet from main building, 2 feet from the dripline of the roof. Otherwise, same as for main building.
- 7. When this side setback is required, rear setback may be reduced to 10 feet.