



Newport™

SCONCE/OUTDOOR

FEATURES


- THE NEWPORT SCONCE FEATURES SOLID ALUMINUM DIE-CAST ENDS WITH A DOMED TOP AND A DISTINCTIVE TAPERING ARCH DESIGN
- 0.125" THICK, MATTE ANODIZED, ALUMINUM EXTRUDED BACK CHANNEL
- 3/16" THICK EXTRUDED VIRGIN WHITE ACRYLIC IS 45% DR HIGH IMPACT, UV STABLE, F1 RATED, AND UL-94 HB FLAME CLASS RATED
- NEWPORT CAN BE MOUNTED VERTICALLY OR HORIZONTALLY
- HINGED FRONT FACE SIMPLIFIES MAINTENANCE



CATALOG CODES

NP1	-	B	-	C	-	D	-	E	-	F	-	UNV	-	DM1	-	I
SERIES		HANGING SYSTEM		SIZE		DIFFUSER		FINISH		LIGHT SOURCE		VOLTAGE		CONTROL		OPTIONS

SPECIFY CATALOG CODE

A	B	C	D	E
SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH
 <p>NP1 NEWPORT</p>	S1SA INDOOR ADA COMPLIANT SCONCE	18	MW MATTE WHITE	POWDER COAT FINISHES BKP BLACK BMP BRASS METALLIC BNP BRONZE BTP BLACK TEXTURED GRP GRAPHITE GLP GOLDTASTIC MWP MATTE WHITE SGP STEEL GRAY SMP SILVER METALLIC SWP SKY WHITE WTP WHITE TEXTURED
	O10A OUTDOOR ADA COMPLIANT SCONCE	24	GW GLOSS WHITE (REQUIRED FOR O10A)	
		36		
		48		

F	G	H	I
LIGHT SOURCE	VOLTAGE	CONTROL	OPTIONS
LED OUTPUT LED1 LED2	UNV 120-277 DM1 0-10V DIMMING 1%		ULD DAMP LABEL (S1SA ONLY) BIOS BIOS SKYBLUE™ OR BIOS SKLYBLUE™ DYNAMIC LIGHT ENGINE* MOD MODIFIED LUMINAIRE (CONTACT LOCAL REP)

SAMPLE CODE: NP1-S1SA-24-GW-BKP-LED1/27K-UNV-DM1

*Contact factory for BIOS SkyBlue® or BIOS SkyBlue® Dynamic light engine and control options. Visit ocl.com/BIOS for more information.

MODS, NOTES, & COMMENTS

UP TO 58 LM/W

LUMENS AND WATTAGE CHART

		18"	24"	36"	48"
LED1	LUMENS DELIVERED	1050	1600	2600	3700
	SYSTEM WATTAGE	20	30	45	65
LED2	LUMENS DELIVERED	1350	2000	3250	4600
	SYSTEM WATTAGE	25	35	60	80

This chart was created for a 35K color temp. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp. Wattage and lumen data approx. pending LM-79 testing.