



imageRUNNER
ADVANCE DX
C3935i/C3930i
C3926i

imageRUNNER ADVANCE DX C3900 Series

Color
Low- to Mid-volume
Multifunction

Print up to 35 ppm (BW/color)

Scan up to 270 ipm (300 dpi) (BW/color, duplex)

Print up to 12" x 18"

2,300-sheet maximum paper capacity

Canon's comprehensive portfolio of imageRUNNER ADVANCE DX multifunction printers and integrated solutions can help **simplify** the end user experience and management of technology, better **control** sensitive information and print-related costs, and help ensure that technology investments proactively **evolve** with changing needs.



WORKFLOW EFFICIENCY

- A large, 10.1" responsive and intuitive touchscreen with smartphone-like usability, making operation clear and virtually seamless.
- Consistent interface across the imageRUNNER ADVANCE DX product line, allowing work to proceed effortlessly and with a minimal learning curve.
- A unique, customized experience that can be tailored to individual preferences using My ADVANCE.
- Supports mobile solutions and integration with many popular cloud services like Google Drive.¹
- Scan and convert documents to searchable digital files in a variety of file formats.
- Integration with Canon and various third-party software with embedded application platform.



SECURITY

- Advanced standard security feature set to help safeguard sensitive information and assist in regulatory compliance.
- Integrates with existing, third-party SIEM*² systems to help provide real-time, comprehensive insights into potential threats to the network and printers.
- Technology to verify that the device boot process, firmware, and applications initialize without alteration at setup. Includes automatic recovery of boot process for self resiliency.
- McAfee Embedded Control³ utilizes whitelisting to help protect against malware and tampering of firmware and applications.
- Security settings can be established at once by selecting the environment type in Recommended Security Settings. Security policy settings can be configured from a central location and exported to other supported devices.
- Control access to the device and specific features using a host of flexible authentication methods—PIN code, user name/password, or card access.⁴



QUALITY AND RELIABILITY

- Canon's signature reliability and engine technologies help keep productivity high and minimize the impact on support resources.
- Outstanding imaging technologies and toner allow for consistently striking images, thanks to Canon's V² color profile.
- Designed to achieve maximum uptime with status notifications that help keep supplies replenished and intuitive maintenance videos for consumables replacement.
- imageRUNNER ADVANCE models have received many awards and recognition from leading industry analysts, often referencing strong reliability. This includes the 2022-2024 BLI Most Reliable A3 Brand Award from Keypoint Intelligence.

* Security Information and Event Management



DEVICE AND FLEET MANAGEMENT

- Designed for quick, easy deployment.
- Remote diagnostics and parts life management for proactive maintenance and rapid fixes.
- Easy and intuitive to monitor device status and consumable levels, turn off devices remotely, observe meter readings, manage settings, and implement security policies.
- Common firmware and regular updates with Unified Firmware Platform (UFP) for continuous improvements and consistency across a fleet.



COST MANAGEMENT

- Track and assess print, copy, scan, and fax usage and allocate costs to departments or projects.
- Apply print policies and restrict usage by user to help reduce unnecessary printing and contribute to cost efficiency.
- Standard cloud-based solution provides a centralized dashboard with up-to-the-minute insights into printer activity.
- Upgrade to uniFLOW server or cloud-based solutions for full accounting and reporting for compatible Canon and third-party devices, pull printing, job routing, and powerful scan workflows.




SUSTAINABILITY

- A combination of fusing technologies and lower-melting-point toner minimizes power requirements and helps achieve low energy consumption.
- Environmentally friendly packaging utilizes recyclable cardboard.
- Drum covers are constructed of regrind plastic, helping to lower environmental impact.
- ENERGY STAR® certified and rated EPEAT® Gold.⁵

CONFIGURATION OPTIONS

imageRUNNER ADVANCE DX C3900 Series



* Staple-Free stapling, up to 10 pages of 17 lb. Bond.

Main Unit**Type**

Color Laser Multifunctional

Core FunctionsStandard: Print, Copy, Scan, Send, Store
Optional: Fax**Processor**

1.8 GHz Dual Core Processor

Control Panel

10.1" TFT LCD WSVGA Color Touch-panel

Memory

3.5 GB RAM

Solid State Drive

Standard: 256 GB/Maximum: 1 TB

Interface Connection

Network: 1000Base-T/100Base-TX/10Base-T,

Optional: Wireless LAN Board F-1

OthersStandard: USB 2.0 x1 (Host), USB 3.0 x1 (Host),
USB 2.0 x1 (Device)

Optional: Copy Control Interface, Serial Interface

Paper Capacity (LTR, 20 lb. Bond)

Standard: 1,200 Sheets

Maximum: 2,300 Sheets

Paper Sources (LTR, 20 lb. Bond)Standard: Dual 550-sheet Paper Cassettes,
100-sheet Multipurpose TrayOptional: Dual 550-sheet Paper Cassettes
(Cassette Feeding Unit-AW1)**Paper Output Capacity (LTR, 20 lb. Bond)**

Standard: 250 Sheets

Maximum: 3,450 Sheets

(with Staple Finisher-AE1/Booklet
Finisher-AE1 and Copy Tray-T1)**Finishing Capabilities**

Standard: Collate, Group

With Finishers: Collate, Group, Offset, Staple, Saddle-Stitch,
Hole Punch, Eco Staple, Staple On Demand**Supported Media Types**Multi-purpose Tray: Thin, Plain, Heavy, Recycled, Coated,
Color, Tracing, Bond, Transparency,
Label, Pre-punched, Envelope,
Postcard, LetterheadUpper Cassette: Thin, Plain, Heavy, Recycled, Color,
Tracing, Bond, Transparency, Pre-
punched, Envelope, Postcard, LetterheadLower Cassette: Thin, Plain, Heavy, Recycled, Color,
Bond, Transparency, Pre-punched,
Envelope⁵, Postcard, Letterhead**Supported Media Sizes**Multi-purpose Tray: 12"x18", 11"x17", Legal, Letter, Letter-R,
Executive, Statement, Statement-R
Custom Size/Free Size: 4" x 5-7/8" to
12" x 18", Envelopes (COM10 No.10,
Monarch, ISO-C5, DL), Envelope Custom
Size (3-7/8" x 3-7/8" to 12-5/8" x 18")Upper Cassette: Letter, Executive, Statement-R
Custom Size (4-1/8" x 5-7/8" to 11-3/4" x
8-1/2"), Envelopes (ISO-C5)Lower Cassette: 12" x 18", 11" x 17", Legal, Letter, Letter-R,
Executive, Statement-R, Custom Size
(4-1/8" x 5-7/8" to 12" x 18"), Envelopes⁵
(COM10 No.10, Monarch, DL)**Supported Media Weights**Cassettes: 14 lb. Bond to 140 lb. Index (52 to 256 g/m²)Multipurpose Tray: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m²)**Tray:**Duplexing: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m²)**Print/Copy Speed (BW and Color)**C3935i: Up to 35 ppm (Letter); Up to 23 ppm
(Letter-R); Up to 17 ppm (Legal/11" x 17")C3930i: Up to 30 ppm (Letter); Up to 20 ppm
(Letter-R); Up to 15 ppm (Legal/11" x 17")C3926i: Up to 26 ppm (Letter); Up to 20 ppm
(Letter-R); Up to 15 ppm (Legal/11" x 17")**Warm-up Time**From Power On: Approx. 10 Seconds⁷From Sleep Mode: Approx. 10 Seconds⁸Quick Startup Mode: Approx. 4 Seconds⁹**Dimensions (W x D x H)**22-1/4" x 28-1/2" x 35-3/8" (565 mm x 722 mm x 897 mm)¹⁰**Installation Space (W x D)**Basic: 38-1/2" x 44-1/8" (978 mm x 1119 mm)¹¹Fully Configured: 65" x 44-1/8" (1651 mm x 1119 mm)¹²**Weight**

Approx. 187.4 lb. (85 kg) including toner

Print Specifications**Print Resolution (dpi)**

1200 x 600, 1200 x 1200

Standard Page Description LanguagesUFR II, PCL[®]6, Adobe[®] PS[®] 3**Supported File Types**

PDF, TIFF, JPEG, EPS, XPS

Printing from Mobile Devices and Cloud-based ServicesA range of standard and optional software and MEAP-
based solutions (including AirPrint, Mopria, Universal
Print by Microsoft[®], Canon PRINT Business, and uniFLOW
Online) are available to provide printing from mobile
devices or internet-connected devices and cloud-based
services depending on your requirements. Please contact
your sales representative for further information.**Fonts**PCL: 93 Roman, 10 Bitmap fonts, 2 OCR fonts,
Andalé Mono WT J/K/S/T (Japanese,
Korean, Simplified and Traditional
Chinese),¹³ Barcode Fonts¹⁴

PS: 136 Roman

Operating System¹⁵UFR/II/PS: Windows[®] 10/11/Server 2012/Server 2012
R2/Server 2016/Server 2019/Server 2022,
macOS (10.13 or later)PCL: Windows[®] 10/11/Server 2012/Server 2012
R2/Server 2016/Server 2019/Server 2022PS: Windows[®] 10/11/Server 2012/Server 2012
R2/Server 2016/Server 2019/Server 2022,
macOS (10.13 or later)PPD: Windows[®] 10/11, macOS (10.13 or later)**Copy Specifications****First-Copy-Out Time (LTR)**C3935i: Approx. 5.5 seconds (BW)/
7.4 seconds (Color)C3930i/ C3926i: Approx. 6.1 seconds (BW)/
8.4 seconds (Color)**Copy Resolution (dpi)**

600 x 600

Multiple Copies

Up to 999

Magnification

25%-400% (1% Increments)

Preset Reduction/Enlargement25%, 50%, 64%, 73%, 78%, 100% (1:1), 121%, 129%, 200%,
400%**Scan Specifications****Type**Single-pass Duplexing Automatic Document Feeder¹⁶**Document Feeder Paper Capacity**

Up to 200 Sheets (20 lb. Bond)

Document Feeder Supported Media Sizes11" x 17", Legal, Letter, Letter-R, Statement, Statement-R,
Custom Size: 2-3/4" x 5-1/2" to 12" x 17" (69.9 mm x 139.7
mm to 304.8 mm x 431.8 mm)**Document Feeder Supported Media Weights**BW/Color: 13.3 lb. Bond to 80 lb. Cover (50 to
Original: 220 g/m²)**Platen Acceptable Originals**

Sheet, Book, 3-Dimensional Objects

Platen Maximum Scanning Size

Up to 11-3/4" x 17" (297.0 mm x 431.8 mm)

Pull ScanColor Network ScanGear2 for both Twain and WIA
Supported OS: Windows[®] 8.1/10/Server 2012/Server 2012
R2/Server 2016**Scan Resolution (dpi)**

Scan for Copy: 600 x 600

Scan for Send: Push (600 x 600), SMB/FTP/WebDAV,

Pull (600 x 600)

Scan for Fax: 600 x 600

Scan to Mobile Devices and Cloud-based ServicesA range of solutions is available to provide scanning to
mobile devices and cloud-based services depending on
your requirements.**Scan Speed (LTR) (BW/CL)**

Single-sided: 135 ipm (300 dpi)/80 ipm (600 dpi)

Scanning:

Double-sided: 270 ipm (300 dpi)/160/90 ipm (600 dpi)

Scanning:

Send Specifications**Destination**Standard: E-mail/Internet FAX (SMTP), SMB 3.0,
FTP, WebDAV, Mail Box

Optional: Super G3 FAX, IP Fax

Address Book

LDAP (2,000)/Local (1,600)/Speed Dial (200)

Send Resolution (dpi)

Push: Up to 600 x 600 dpi

Pull: Up to 600 x 600 dpi

Communication Protocol

File: FTP (TCP/IP), SMB 3.0 (TCP/IP), WebDAV

Email: SMTP, POP3

File FormatTIFF, JPEG, PDF(Compact, Searchable, Apply Policy,
Optimize for Web, PDF/A-1b, Trace & Smooth, Encrypted,
Device Signature, User Signature), XPS (Compact,
Searchable, Device Signature, User Signature), Office
Open XML (PowerPoint, Word)**Fax Specifications****Maximum Number of Connection Lines**

2

Modem Speed

Super G3: 33.6 Kbps

G3: 14.4 Kbps

Compression Method

MH, MR, MMR, JBIG

Resolution (dpi)

400 x 400, 200 x 400, 200 x 200, 200 x 100

Sending/Receiving Size

Statement-R to 11" x 17"

Fax Memory

Up to 30,000 Pages (2,000 Jobs)

Speed Dials

Max. 200

Group Dials/Destinations

Max. 199 Dials

Sequential Broadcast

Max. 256 Addresses

Memory Backup

Yes

Store Specifications

Box (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, Maximum 10,000 Pages (2,000 Jobs Stored)

Advanced Box

Communication Protocol: SMB or WebDAV Supported

Client PC: Windows® 10/11

Concurrent Connections (Max.)

SMB: 64

WebDAV: 3 (Active Sessions)

Advanced Box Available Disc Space

Standard: 16 GB (With Option: max. 480 GB)

Security Specifications

Authentication and Access Control

User Authentication (Picture Login, Picture and PIN Login, Card Login, Username and Password Login, Function Level Login, Mobile Login), Department ID Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online Express¹⁷ (PIN Login, Picture Login, Picture and PIN Login, Card Login, Card and PIN Login, Username and Password Login, Department ID and PIN Login, Function Level Login), Access Management System (Access Control)

Document Security

Print Security (Secure Print, Encrypted Secure Print, Forced Hold Printing, uniFLOW Secure Print¹⁸), Receive Data Security (Confidential Fax Inbox Forwarding Received Documents Automatically), Scan Security (Encrypted PDF, Device Signature PDF/XPS, User Signature PDF/XPS, Adobe LiveCycle® Rights Management ES2.5 Integration), BOX Security (Mail Box Password Protected, Advanced Space Access Control), Send Data Security (Setting for requesting password input per transmission, Restricted E-mail/File send functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support), Document Tracking (Secure Watermark)

Network Security

TLS 1.3, IPSec, IEEE802.1X authentication, SNMP V3.0, Firewall Functionality (IP/MAC Address Filtering), Dual Network Support (Wired LAN/Wireless LAN, Wired LAN/Wired LAN), WPA3 support (Wi-Fi), Disabling Unused Functions (Enabling/Disabling Protocols/Applications, Enabling/Disabling Remote UI, Enabling/Disabling USB Interface), Communication Line Separation (G3 FAX, USB Port, Advanced Space, Scan and Send-Virus Concerns for E-mail Reception)

Device Security

Protecting SSD Data [SSD Data Encryption (FIPS140-2 Validated), SSD Lock], Standard SSD Initialize, Trusted Platform Module (TPM), Job Log Conceal Function, Protecting MFP Software Integrity, Automatic Recovery, Checking MFD Software Integrity (Verify System at Startup, Runtime Intrusion Detection)

Device Management and Auditing

Administrator Password, Digital Certificate and Key Management, Audit Log, Cooperating with External Security Audit System (Security Information and Event Management), Image Data Logging, Security Policy Setting

Environmental Specifications

Operating Environment

Temperature: 50 to 86 °F

Humidity: 20 to 80 % RH (Relative Humidity)

Power Requirements

110V-127V, 60Hz, 8.5A

Power Consumption

Maximum: Approx. 1,500 W

Sleep Mode: Approx. 0.8 W¹⁹

Typical Electricity Consumption (TEC) Rating²⁰

C3935i: 0.33 kWh

C3930i: 0.29 kWh

C3926i: 0.26 kWh

Standards

ENERGY STAR® Certified

Rated EPEAT® Gold⁵

Consumables

Toner²¹

GPR-66 Toner BK/C/M/Y

GPR-66L Toner C/M/Y

Toner Yield (Estimated @ 5% Coverage)

GPR-66 Toner

BK: 38,000 pages

GPR-66 Toner

C/M/Y: 25,500 pages

GPR-66L Toner

C/M/Y: 11,000 pages

¹ Subscription to a third-party cloud service required. Subject to third-party cloud service providers' Terms and Conditions.

² Third-party SIEM system required. Subject to third-party SIEM system's Terms and Conditions. Canon cannot ensure compatibility with all third-party SIEM systems.

³ This feature is off by default and must be turned on by the user. Warm-up times are affected once turned on.

⁴ Requires additional option.

⁵ For current EPEAT rating (Gold/Silver/Bronze), please visit www.epeat.net.

⁶ Envelope Feeder Attachment A (standard) is required.

⁷ Time from device power-on until copy ready (not print reservation).

⁸ Time from exiting Sleep mode to when printing is operational.

⁹ Time from device power-on to when the copy icon appears and is enabled to operate on the touch panel display.

¹⁰ Includes Single Pass DADF.

¹¹ With right cover open + Multi-purpose tray extension extended + paper cassette open.

¹² Includes Staple Finisher-AE1/Booklet Finisher-AE1 + Copy Tray-T1 extension extended + paper cassette open.

¹³ Requires the optional PCL International Font Set-A1.

¹⁴ Requires the optional Barcode Printer Kit-D1.

¹⁵ Other operating systems and environments, including AS/400, UNIX, Linux, and Citrix, may be supported. Some solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.

¹⁶ Detect Feeder Multi Sheet Feed is supported.

¹⁷ No charge for this solution; however, activation is required.

¹⁸ Requires uniFLOW Online/uniFLOW.

¹⁹ 0.8 W Sleep mode not available in all circumstances due to certain settings.

²⁰ Based on ENERGY STAR Product Specification for Imaging Equipment Version 3.0.

²¹ GPR-66L Toner also available for Color (C, M, Y).

Yield (estimated @ 5% coverage) is 11,000 images.

USA.CANON.COM/SIMPLYADVANCED



As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. AirPrint and the AirPrint logo are trademarks of Apple Inc. Canon, imageRUNNER, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon does not warrant that use of its features will prevent security issues. Some security features may impact functionality/performance; you may want to test these settings in your environment. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. McAfee and the McAfee logo are trademarks of McAfee LLC in the US and/or other countries. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Dealer for details. Products shown with optional accessories. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors.

©2023 Canon U.S.A., Inc. All rights reserved.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.

04/23-0345-8064




To learn about Canon's many awards, visit usa.canon.com/awards.