CONSTRUCTION STANDARDS WALL LEGEND/INFORMATION SEE ADDITIONAL WALL DETAILS ELSEWHERE MINIMUM STANDARDS THESE CONSTRUCTIONS DOCUMENTS REQUIRED LARGER SIZES, GREATER QUANTITIES, MORE PROTECTION AND REQUIREMENTS THAN THE GOVERNING BUILDING CODES. THE CONTRACTOR IS RESPONSIBLE FOR CARRYING OUT ALL OF THE PROVISIONS AND REQUIREMENTS INCLUDED IN THESE PLANS AND SPECIFICATIONS. SUBSTITUTIONS, NEW FIRE RATED PARTITION NON-BEARING, NON FIRE RATED NEW INTERIOR PARTITION INSULATED INTERIOR PARTITION NEW INTERIOR PARTITION ALTERNATES OR CHANGES REQUESTED TO MATCH LOWER STANDARDS PERMITTED BY THE BUILDING CODE WILL NOT NON-BEARING, NON FIRE RATED NEW EXTERIOR WALL NEW 5' HIGH PARTITION BETWEEN CANINE RUNS WITH STEEL FRAMEWORK AND CEMENT BOARD BOTH SIDES, EPOXY FLOOR FINISH TO RUN UP WALLS AND OVER THE TOP. REAR WALL OF RUN SHALL HAVE SAME EPOXY FINISH UP TO 5', SEE DETAIL ELSEWHERE FOR ADDITIONAL CONSTRUCTION INFO. EXISTING FULL HEIGHT PARTITION WALL TO BE ACCEPTED. NO ADDITIONAL PAYMENTS SHALL BE MADE TO THE CONTRACTOR TO CORRECT WORK THAT DOES NON-BEARING, NON FIRE RATED NON-BEARING, NON FIRE RATED NON-BEARING, NON FIRE RATED ALL EXTERIOR WALLS SHALL HAVE 5/8" GWB NEW LOW HEIGHT PARTITION HEIGHT NOT MEET ALL OF THE REQUIREMENTS SET FORTH IN THESE CONSTRUCTION DOCUMENTS. EXTEND TO UNDERSIDE OF ROOF DECK OR VARIES, SEE PLAN FOR ADDITIONAL HEIGHT INFO, SEE DETAIL ELSEWHERE FOR ADDITIONAL CONSTRUCTION INFO, NEW FULL HEIGHT PARTITION WALL TO OVER NOMINAL | 5/8" METAL HAT CHANNEL NEW FULL HEIGHT PARTITION WALL TO NEW FULL HEIGHT PARTITION WALL TO TO FIRE RATED CEILING. SEE DETAIL EXTEND 6" ABOVE THE ACOUSTICAL <u>SUBSTITUTIONS</u> FURRING WITH R-4.1 FOIL BACK INSULATION. SEE EXTEND 6" ABOVE THE ACOUSTICAL EXTEND 6" ABOVE THE ACOUSTICAL ELSEWHERE CEILING. 1/16" LEAD SHIELDING TO A HEIGHT SUBSTITUTIONS OR DEVIATIONS FROM THE PLANS AND SPECIFICATIONS DURING BIDDING OR CONSTRUCTION ARE NOT STRUCTURAL SHEETS FOR DETAILS. CEILING WITH BATT-19 SOUND INSULATION. CEILING. SEE DETAIL ELSEWHERE OF 7'-0" AFF. SEE DETAIL ELSEWHERE PERMITTED WITHOUT PRIOR WRITTEN AUTHORIZATION FROM THE OWNER AND/OR ARCHITECT. FAILURE TO COMPLY WITH SEE DETAIL ELSEWHERE THIS PROVISION WILL RESULT IN THE REJECTION OF THE WORK IN QUESTION. THE CONTRACTOR WILL NOT BE COMPENSATED FOR UNAUTHORIZED SUBSTITUTIONS OR DEVIATIONS FROM THE PLAN AND WILL HAVE TO TAKE CORRECTIVE MEASURES AT HIS OWN EXPENSE. 84'-9" 3. <u>ALTERNATES</u> REQUEST FOR PRODUCT ALTERNATES OR SUBSTITUTIONS WILL ONLY BE CONSIDERED BY THE ARCHITECT WHEN SUBMITTED WITH A LETTER OF EXPLANATION. WHEN APPLICABLE THE REQUEST SHALL INCLUDE: A COST 8'-1 1/4" 21'-3 3/4" COMPARISON: DRAWINGS AND/OR BROCHURE CUT SHEET DEMONSTRATING THAT THE SUBSTITUTION OR ALTERNATE MEETS THE INTENDED PERFORMANCE AND QUALITY OF THE ORIGINAL SPECIFICATION 4. <u>CHANGE ORDERS</u> ALL CHANGE ORDERS SHALL BE SIGNED BY THE OWNER PRIOR TO COMMENCEMENT OF THE WORK TO BE CHANGED 5. DISCREPANCIES FIRE SPRINKLER WHEN IN THE OPINION OF THE CONTRACTOR A DISCREPANCY EXISTS, HE/SHE SHALL PROMPTLY REPORT IT IN WRITING RISER TO THE ARCHITECT PRIOR TO THE COMMENCEMENT OF THE WORK IN THE AREA OF QUESTION. NO ADDITIONAL 13Ø OFFICE PAYMENT SHALL BE MADE FOR THE CONTRACTOR'S FAILURE TO CORRECT CONFLICTING FIELD CONDITIONS 6. CONSTRUCTION MEANS AND METHODS MANAGER ERIC TREBBIEN, ARCHITECT, AND/OR ENGINEER(6) SHALL NOT HAVE CHARGE, CONTROL OR BE RESPONSIBLE FOR RESTROOM - 4 129 **STORAGE** CONSTRUCTION MEANS, METHODS, SEQUENCES, PROCEDURES OR FOR SAFETY PRECAUTIONS AND PROGRAMS.IT IS UNDERSTOOD AND AGREED THAT THE ARCHITECT HAS NO CONSTRUCTIVE USE OF THE OWNER'S SITE: HAS NO 132 128 CONTROL OR AUTHORITY OVER THE MEANS, METHODS, AND SEQUENCES OF CONSTRUCTION: AND THEREFORE HAS NO **STORAGE** ONGOING RESPONSIBILITY WHATSOEVER FOR CONSTRUCTION SITE SAFETY: A RESPONSIBILITY WHOLLY VESTED IN THE CONTROL GENERAL CONTRACTOR, NOTWITHSTANDING THE ABOVE, THE ARCHITECT HAS A DUTY TO PRESERVE AND PROTECT SUBSTANCE BOX PUBLIC HEALTH, SAFETY, AND WELFARE. ACCORDINGLY, IT IS ERIC TREBBIEN, ARCHITECT'S PROFESSIONAL RESPONSIBILITY TO TAKE WHAT HE BELIEVES ARE PRUDENT MEASURES SHOULD THE ARCHITECT ENCOUNTER **AUNDRY** SITUATIONS THAT HE BELIEVES CREATE A DANGER TO PUBLIC HEALTH, SAFETY, OR WELFARE. THE CLIENT/OWNER **CLOSET-**UNDERSTANDS THIS SITUATION AND AGREES TO DEFEND ERIC TREBBIEN, ARCHITECT AND HOLD THE ARCHITECT 126 HARMLESS FROM THE ARCHITECT'S CLAIMS ARISING FROM THE ARCHITECT'S EXERCISE OF PROFESSIONAL RESPONSIBILITY IN THIS REGARD. - REFRIG -GENERAL CONSTRUCTION NOTES 3'-Ø" 5'-6" 5'-1 3/4" - -5'-6-1/4" **RESTROOM** -WORK SHALL INCLUDE ALL ITEMS (BUILDING AND SITE) AS INDICATED ON THIS SET OF DRAWINGS UNLESS NOTED OTHERWISE. _=== DEPOSITS AND FEES: DEPOSITS FOR UTILITIES INCLUDING WATER METER, TELEPHONE AND ELECTRICAL SERVICE TO BE MADE BY THE GENERAL 123 10 CAGE BANK 1 14'-4" |30" DEEP CONTRACTOR: PERMIT FEES, AS REQUIRED, SHALL BE PAID BY THE CONTRACTOR FOR THAT PORTION OF THE WORK. 7'-3 1/2" 6'-11 1/2" 4'-Ø" 4'-6" GENERAL CONTRACTOR SHALL MAINTAIN TEMPORARY ELECTRICAL, WATER, AND SANITARY FACILITIES AS REQUIRED FOR THE DURATION OF 2'-8" CONSTRUCTION. PRIOR TO STARTING WORK, THE GENERAL CONTRACTOR SHALL NOTIFY ARCHITECT OF ANY DISCREPANCIES IN THE PLANS. WRITTEN FIGURES CAT ROOM INDICATING DIMENSIONS SHALL BE USED INSTEAD OF SCALING THE DRAWINGS. MEASUREMENTS BY SCALING SHALL NOT BE USED AS DIMENSIONS BENCH BENCH TO WORK BY, FIELD MEASUREMENTS ARE THE RESPONSIBILITY OF THE GENERAL CONTRACTOR, SHOP DRAWINGS MUST BE FIELD VERIFIED. 122 **CORRIDOR 5** ALL WORK SHALL BE PERFORMED IN ACCORDANCE WITH ALL CODES, RULES AND REGULATIONS OR RESTRICTIONS HAVING JURISDICTION. GENERAL CONTRACTOR SHALL PROMPTLY NOTIFY ARCHITECT UPON THE OBSERVANCE OF ANY VARIATION BETWEEN THESE DOCUMENTS AND ANY COR5 APPLICABLE CODES OR ORDINANCES. ALL CONSTRUCTION MATERIALS SHALL BE NEW AND SHALL BEAR UNDERWRITER'S LABELS WHERE APPLICABLE. CORRIDOR: ALL PIERS, SUPPORTS, SHELVING, FOUNDATIONS, ANCHOR BOLTS, HANGERS, WHICH ARE REQUIRED BY A SUBCONTRACTORS FOR THE SUPPORT OR HYDRAULIC HYDRAULIC COR3 ROOM-5 ROOM-4 HANGING OF THEIR EQUIPMENT SHALL BE SUPPLIED BY THE CONTRACTOR REQUIRING SAME. **COMFORT EXAM** FREEZER 42" SILL 96" HEADER LIFT TABLE LIFT TABLE FOR CONVENIENCE IN DESCRIPTION 4 AS A STANDARD FOR GRADE, TYPE, QUALITY AND PERFORMANCE CHARACTERISTICS, PROPRIETARY NAMES ROOM-6 -108--107-ARE INCLUDED WITH SOME DESCRIPTIONS. THIS DOES NOT IMPLY ANY PREFERENCE TO A PARTICULAR MANUFACTURER, BUT MINIMUM REQUIREMENTS, WITH FINAL DECISIONS BEING MADE BY THE OWNER AND ARCHITECT. 109 ARRANGE FOR SUITABLE STORAGE SPACE FOR MATERIALS TO PREVENT INCLUSION OF FOREIGN MATERIALS AND DELIVER AT SUCH TIMES AS NOT TO INTERFERE WITH OTHER OPERATIONS. MATERIALS ON SITE SHALL BE KEPT IN UNOPENED, ORIGINAL CONTAINERS OR PACKAGES THAT 9'-9 1/2" 9'-10 1/2" 4'-Ø" 8'-9" 9'-10 1/2" BEAR IDENTIFYING LABELS WHICH ARE NOT TO BE REMOVED UNTIL THEIR IMMEDIATE USE. PROTECT ALL MATERIALS FROM MINOR ABRASIONS 6'-4" AND HANDLE MASONRY PRODUCTS WITH CARE TO PREVENT CHIPPING AND DAMAGE. ~~~---- 10. GENERAL CONTRACTOR SHALL REMOVE ALL CONSTRUCTION DEBRIS FROM THE JOB SITE & LEAVE BUILDING BROOM CLEAN. ALL GLASS SHALL BE THOROUGHLY CLEANED AT COMPLETION OF WORK. ANY PAINT SPECKS & OTHER CONSTRUCTION MARKS SHALL BE REMOVED FROM ALL SOLID WITH ----FINISHED SURFACES. GENERAL CONTRACTOR SHALL GUARANTEE ALL MATERIALS AND WORKMANSHIP TO BE FREE OF DEFECTS FOR A PERIOD OF NOT LESS THAN (1) RELOCATED YEAR FROM THE DATE OF ACCEPTANCE. CORRECTION OF DEFECTS SHALL BE COMPLETED IN A TIMELY MANNER WITHOUT ADDITIONAL CHARGE. SCALE THIS SHALL INCLUDE ELEMENTS WHICH ARE DAMAGED BY SAID DEFECTS. 12. ALL LUMBER SHALL BE DOUGLAS FIR WITH A MINIMUM FIBER STRESS OF 1,000 PS1, OR NO. 2 SOUTHERN PINE, UNLESS NOTED OTHERWISE. ALL RESTROOM - 2 LUMBER IN CONTACT WITH CONCRETE OR MASONRY SHALL BE PRESSURE TREATED. 13. ALL METAL USED FOR CONNECTING WOOD MEMBERS SHALL BE GALVANIZED. ALL NAILS, BOLTS OR OTHER METAL CONNECTORS SHALL BE PORCELAIN EPOXY ----**KENNELS** GALVANIZED OR SHALL BE CORROSION RESISTANT. TILE FLOOR FLOOR 115 FINISH GENERAL PROJECT NOTES HI/LOW DRINKING ALL EXISTING EXTERIOR WALLS 8" CMU W/ EXISTING 5/8" GWB OVER 1 1/2" METAL HAT CHANNEL @ 24" O.C. WITH REQUIRED BY R4.I FOIL BACK INSULATION TO REMAIN AS IS. CONTRACTOR TO PATCH AS NECESSARY. COMBUSTIBLE MATERIALS ARE PERMITTED ABOVE THE CEILING IN LIEU OF THE PLENUM. 8'-8 3/4" 2'-10 1/2" , 3'-3 3/4" 6'-6" PVC IS ALLOWED TO BE USED ABOVE THE CEILING IN LIEU OF THE PLENUM EXISTING BUILDING SHELL AND ENTRANCE SHALL COMPLY WITH NFPA 101 AND FACBC CURRENT ED. ALL NEW 114 INTERIOR BUILD-OUT SHALL COMPLY WITH NFPA AND FACBC CURRENT ED. CHECK-IN/OUT RESTROOM -ALL FLOOR LEVEL TO COMPLY WITH FBC. NO CHANGES OF LEVEL SHALL EXCEED 1/2" ON AN ACCESSIBLE ROUTE. RUN THE LAYOUT AND DESIGN OF SPACES DEPICTED IN THESE PLANS COMPLY WITH THE REQUIREMENTS OF THE FLORIDA ACCESSIBILITY CODE FOR BUILDING CONSTRUCTION. 4'-9 1/2" CONTRACTOR TO PROVIDE SUBMITTALS FOR ARCHITECTS AND 7. OWNERS APPROVAL PRIOR TO PURCHASING / INSTALLING ANY AND ALL HARDWARE 112 8. ALL DIMENSIONS ARE TO FINISHED FACE OF G.W.B. UNLESS OTHERWISE NOTED. WHERE DIMENSIONS ARE NOTED TO ROOM-3 BE "CLEAR" OR "MIN." THEY REFER TO THE FINISHED FACE OF WALL. PROVIDE WOOD BLOCKING IN WALLS FOR SHELVING, MIRRORS, AND CABINET WORK AS REQUIRED TO 106 ACCOMMODATE INSTALLATION. COORDINATE WITH CABINET MANUFACTURER AND OWNER PRIOR TO ANY CONSTRUCTION. SEE DETAIL ELSEWHERE. 10. ALL WOOD BLOCKING AND FURRING SHALL VERIFIED PRIOR TO INSTALLATION FIRE EXTINGUISHERS SHALL BE LARSEN'S MODEL No. MP-10, MULTI-PURPOSE ABC, COMPLETE WITH MOUNTING BRACKET, OR APPROVED SIMILAR. CONTRACTOR TO VERIFY FIRE EXTINGUISHER LOCATIONS WITH FIRE MARSHAL BEFORE INSTALLATION. FIELD VERIFY ALL CONDITIONS AND DIMENSIONS PRIOR TO FABRICATION OR INSTALLATION OF ANY ITEM. 8'-2" 9'-4 1/2" 113 10'-5 3/4" BUILD OUT SHALL COMPLY WITH F.B.C. 2023 8TH EDITION FOR FABRICATION OR INSTALLATION OF ANY ITEM. **TREATMENT** REFER TO PERMIT DRAWINGS ON FILE WITH THE CITY FOR SHELL BUILDING AND SITE INFORMATION. 16. EXIT DOORS SHALL COMPLY WITH FLORIDA FIRE PREVENTION CODE, NFPA 101, SECTION 1.2.1.5 LOCKS, IF PROVIDED, 4'-9" SHALL NOT REQUIRE THE USE OF A KEY, A TOOL, OR SPECIAL KNOWLEDGE OR EFFORT FOR OPERATION FROM THE 114 EGRESS SIDE. VERIFY WITH BUILDING SHELL DESIGN. 4'-9" X 2'-6 RUN GENERAL NOTES GOVERNING CODE: FLORIDA BUILDING CODE (FBC 2023 8TH EDITION), 1TH EDITION OF THE FLORIDA FIRE PREVENTION CODE AS WELL AS THE ANSI / ASCE 1-16 FOR WIND LOADS. (175 MPH WIDESPREAD EXPOSURE 'C') 4'-9" X 3'-6" REFERENCE STANDARDS: REFERENCE TO ASTM AND OTHER STANDARDS SHALL MEAN THE LATEST EDITION IN EFFECT ON THE **EXAM** BID DATE OR DATE OF OWNER-CONTRACTOR AGREEMENT UNLESS NOTED IN THESE DOCUMENTS OR DESIGNATED BY THE ROOM-2 NOTES: NOTES ON THE INDIVIDUAL STRUCTURAL DRAWINGS SHALL TAKE PRIORITY OVER STRUCTURAL NOTES ON THIS SHEET. 105 REFRIG <u>SPECIFICATIONS:</u> REFER TO THE SPECIFICATIONS FOR INFORMATION IN ADDITION TO THESE NOTES AND THE STRUCTURAL _ _ _ _ ARCHITECTURAL: REFER TO THE ARCHITECTURAL DRAWINGS FOR ELEVATIONS, DOORS, WINDOWS, NONBEARING WALLS, CONTROL 3'-10" CURTAIN WALLS, ELEVATORS, STAIRS, SLOPES, CURBS, DRAINS, DEPRESSIONS, RAILINGS, WATERPROOFING, FINISHES, ETC. SUBSTANCE BOX 6. <u>DISCREPANCIES:</u> IN CASE OF DISCREPANCIES BETWEEN THE PLANS, SPECIFICATIONS, REFERENCE STANDARDS & GOVERNING PORCELAIN EPOXY DOG ROOM CODE, THE MORE STRINGENT REQUIREMENTS SHALL GOVERN. ALL DISCREPANCIES SHALL BE BROUGHT TO THE ATTENTION OF TILE FLOOR FLOOR (A-3) FINISH 5'-Ø" FINISH 18'-9 3/4" - 10'-5" THE ARCHITECT BEFORE PROCEEDING WITH WORK. 116 1. SITE VERIFICATION: THE CONTRACTOR SHALL VERIFY ALL DIMENSIONS, ELEVATIONS AND SITE CONDITIONS BEFORE STARTING 4' CAGE BANK **CORRIDOR 1** 4' ICAGE BAN WORK, AND THE ARCHITECT SHALL BE IMMEDIATELY NOTIFIED, IN WRITING, OF ANY DISCREPANCIES. IN NO CASE CASE SHALL 24" DEEP .'-⊘" |30" DEEP 3'-9" 3'-Ø" DIMENGIONG BE SCALED FROM PLANG, SECTIONG, OR DETAILS ON THE STRUCTURAL DRAWINGG. 5'-5" 9'-2 1/4" CORI WAITING ROOM OMISSIONS/CONFLICTS: IN CASE OF OMISSIONS AND CONFLICTS BETWEEN THE PLANS, SPECIFICATIONS AND SITE CONDITIONS, THE ARCHITECT SHALL BE NOTIFIED BEFORE PROCEEDING WITH THE WORK. 100 9. <u>CONTRACTOR RESPONSIBILITIES:</u> THE CONTRACTOR IS RESPONSIBLE FOR SAFETY AT THE SITE AND FOR THE STRENGTH AND 2" SILL 96" HEADER DOOR /W HALF WINDOW STABILITY OF ALL PARTLY COMPLETED STRUCTURES. 6'-0" 10. LOAD LIMITS: LOADS ON THE STRUCTURE SHALL NOT EXCEED THE DESIGN LOADS SHOWN UNDER "DESIGN CRITERIA". SUBMITTALS: WHERE SHOP DRAWINGS, MILL TESTS, OR OTHER ITEMS ARE REQUESTED, SUBMITTAL SHALL BE MADE TO THE PRE- OPERATORY CENTER ARCHITECT PRIOR TO FABRICATION OR INSTALLATION IN THE STRUCTURE, UNLESS SPECIFICALLY NOTED. **OPERATORY** ALTERNATES: ALTERNATES FOR SPECIFIED ITEMS SHALL BE SUBMITTED TO ARCHITECT FOR APPROVAL. CONTRACTOR SHALL 120 CORRIDOR 4 BUDGET FOR ARCHITECTURAL/ENGINEERING FEES ASSOCIATED WITH THE REVIEW OF THESE MATERIALS. COR4 FOLD DOWN ROOM-1 2023 FBC, ACCESSIBILITY SECTION 611: X-RAY 104 119 WASHING MACHINES AND CLOTHES DRYERS SHALL COMPLY WITH 611. BEVERAGES 611.2 CLEAR FLOOR SPACE. A CLEAR FLOOR OR GROUND SPACE COMPLYING WITH 305 POSITIONED FOR PARALLEL FRIDGE APPROACH SHALL BE PROVIDED. THE CLEAR FLOOR OR GROUND SPACE SHALL BE CENTERED ON THE APPLIANCE. 611.3 OPERABLE PARTS. OPERABLE PARTS, INCLUDING DOORS, LINT SCREENS, AND DETERGENT AND BLEACH COMPARTMENTS SHALL COMPLY WITH 309. 8'-5" 12'-10" 13'-11 1/4" 3'-2" 3'-3 3/4" TOP LOADING MACHINES SHALL HAVE THE DOOR TO THE LAUNDRY COMPARTMENT LOCATED 36 INCHES (915 MM) MAXIMUM ABOVE THE FINISH FLOOR, FRONT LOADING MACHINES SHALL HAVE THE BOTTOM OF THE OPENING TO THE LAUNDRY COMPARTMENT LOCATED 15 INCHES

(380 MM) MINIMUM AND 36 INCHES (915 MM) MAXIMUM ABOVE THE FINISH FLOOR.

86'-1"



Treb *Arc*, Inc architecture design studio 7501 NW 4th Street #212e Plantation, FL 33317



954.530.1765

Digitally signed by Eric R Trebbien Date: 2025.04.11 18:03:59 -04'00'

osed Floor F egend, and

7

REVISIONS:

RELEASED FOR: 02/04/2025 PROJECT MGR.: PROJECT NO.: