



HV607 SBA

Sales Proposal For:
TOWN OF JEROME

Presented By:
RWC Group



Prepared For:
 TOWN OF JEROME
 BRETT KLEIN
 600 CLARK STREET
 Jerome, AZ 86331-
 (928)634 - 7943
 Reference ID: N/A

Presented By:
 RWC Group
 Mary R Wilson
 600 North 75th Avenue
 PHOENIX AZ 85043 -
 (602)307-1050

Thank you for the opportunity to provide you with the following quotation on a new International truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

Model Profile
2027 HV607 SBA (HV607)

AXLE CONFIG: 6X4
APPLICATION: Rear Loader
MISSION: Requested GVWR: 56000. Calc. GVWR: 56000. Calc. GCWR: 80000
 Calc. Start / Grade Ability: 24.36% / 1.25% @ 55 MPH
 Calc. Geared Speed: 78.2 MPH
DIMENSION: Wheelbase: 232.00, CA: 164.90, Usable CA: 161.90, Axle to Frame: 75.00
ENGINE, DIESEL: {Cummins L9 300} EPA 2024, 300HP @ 2200 RPM, 860 lb-ft Torque @ 1200 RPM, 2200 RPM
 Governed Speed, 300 Peak HP (Max)
TRANSMISSION, AUTOMATIC: {Allison 3500 RDS} 6th Generation Controls, Wide Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor, with 60,000-lb GVW Max, Refuse/Mixer Omit Item (Clutch & Control)
CLUTCH: {Meritor MFS-16-133A} Wide Track, I-Beam Type, 16,000-lb Capacity
AXLE, FRONT NON-DRIVING: {Meritor MT-40-14X-4DFR} Single Reduction, 40,000-lb Capacity, .433"(11mm) Wall Housing
AXLE, REAR, TANDEM: Thickness, R Wheel Ends Gear Ratio: 5.29
CAB: Conventional, Day Cab
TIRE, FRONT: (2) 315/80R22.5 Load Range L HAU 3 WT (CONTINENTAL), 480 rev/mile, 68 MPH, All-Position
TIRE, REAR: (8) 11R22.5 Load Range H HDR2+ (CONTINENTAL), 491 rev/mile, 75 MPH, Drive
SUSPENSION, REAR, AIR, TANDEM: {Hendrickson PRIMAAX EX} 46,000-lb Capacity, 56" Axle Spacing, 9.0" Ride Height, with Shock Absorbers
PAINT: Cab schematic 100WL
 Location 1: 9219, Winter White (Std)
 Chassis schematic N/A

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
HV60700	Base Chassis, Model HV607 SBA with 232.00 Wheelbase, 164.90 CA, 161.90 Usable CA, and 75.00 Axle to Frame.	6136/3544	9680

AXLE CONFIGURATION

1AND	AXLE CONFIGURATION 6x4	0/0	0
<u>Notes</u> : Pricing may change if axle configuration is changed.			

ENGINE

12EYW	ENGINE, DIESEL {Cummins L9 300} EPA 2024, 300HP @ 2200 RPM, 860 lb-ft Torque @ 1200 RPM, 2200 RPM Governed Speed, 300 Peak HP (Max)	557/7	564
12VKL	EMISSION, CALENDAR YEAR {Cummins L9} EPA, OBD and GHG Certified for Calendar Year 2026	0/0	0
12WZY	CARB EMISSION WARR COMPLIANCE for Cummins L9 Engines	0/0	0
12WZJ	CARB IDLE COMPLIANCE Low NOx Idle Engine, Complies with California Clean Air Regulations; Includes "Certified Clean Idle" Decal located on Driver Door	0/0	0
12WVG	EPA IDLE COMPLIANCE Low NOx Idle Engine, Complies with EPA Clean Air Regulations; Includes "Certified Clean Idle" Decal on Hood	0/0	0
10UAV	VEHICLE REGISTRATION IDENTITY ID for Non-CARB Omnibus and/or Non-ACT Adopting State or Exempt Vehicle. Not for use on vehicles registering in CA. Contains non-mitigated legacy engine & cannot be registered in CA unless exempt. You may be held liable under state law for failure to properly register vehicle.	0/0	0

Notes
: CANNOT BE REGISTERED IN CA. For vehicles that will be registered in States other than CA.

12UWZ	RADIATOR Aluminum, Cross Flow, Front to Back System, 1228 SqIn, with 1167 SqIn Charge Air Cooler, Includes In-Tank Oil Cooler	22/-4	18
<u>Includes</u>			

: DEAERATION SYSTEM with Surge Tank
: HOSE CLAMPS, RADIATOR HOSES Gates Shrink Band Type; Thermoplastic Coolant Hose Clamps
: RADIATOR HOSES Premium, Rubber

12THT	FAN DRIVE {Horton Drivemaster} Two-Speed Type, Direct Drive, with Residual Torque Device for Disengaged Fan Speed	0/0	0
<u>Includes</u>			

: FAN Nylon

12VBG	AIR CLEANER Dual Element, with Integral Pre-Cleaner	12/0	12
12703	ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection	0/0	0

12WUL	BLOCK HEATER, ENGINE {Phillips} 120V/1000W, with "Y" Cord for Dealer Installed 120V/300W Oil Pan Heater	0/0	0
<u>Includes</u>			

: BLOCK HEATER SOCKET Receptacle Type; Mounted below Drivers Door

12XBM	ENGINE CONTROL, REMOTE MOUNTED Provision for; Includes Wiring for Body Builder Installation of PTO Controls and Starter Lockout, with Ignition Switch Control, for Cummins B6.7 and L9 Engines	0/0	0
<u>Includes</u>			

: THROTTLE, HAND CONTROL Engine Speed Control; Electronic, Stationary,

12VXT	Variable Speed; Mounted on Steering Wheel	0/0	0
<u>Includes</u>			

TRANSMISSION

13BDP	TRANSMISSION, AUTOMATIC {Allison 3500 RDS} 6th Generation Controls, Wide Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor, with 60,000-lb GVW Max, Refuse/Mixer	234/49	283
<u>Includes</u>			

Code	Description	F/R Wt	Tot Wt
		(lbs)	(lbs)
13WUJ	ALLISON SPARE INPUT/OUTPUT for Rugged Duty Series (RDS), Front Loaders, Rear Loaders, Recycling/Packer Trucks, Package Number 142	0/0	0
13XAN	PTO LOCATION Customer Does Not Intend to Install PTO	0/0	0
13XBG	SHIFT CONTROL PARAMETERS {Allison} 3000 or 4000 Series Transmissions, with DynActive, Dynamic Shift Sensing, Neutral at Stop-Premium, with Coast Mode and Acceleration Rate Management (FuelSense 2.0 Max)	0/0	0
13WLP	TRANSMISSION OIL Synthetic; 29 thru 42 Pints	0/0	0
13WET	TRANSMISSION SHIFT CONTROL Column Mounted Stalk Shifter, Not for Use with Allison 1000 & 2000 Series Transmission	1/0	1

CLUTCH

11001	CLUTCH Omit Item (Clutch & Control)	0/0	0
-------	-------------------------------------	-----	---

REAR AXLES, SUSPENSIONS

14GVY	AXLE, REAR, TANDEM {Meritor MT-40-14X-4DFR} Single Reduction, 40,000-lb Capacity, .433"(11mm) Wall Housing Thickness, R Wheel Ends . Gear Ratio: 5.29	0/2101	2101
14UNX	SUSPENSION, REAR, AIR, TANDEM {Hendrickson PRIMAXX EX} 46,000-lb Capacity, 56" Axle Spacing, 9.0" Ride Height, with Shock Absorbers	0/1089	1089
14WMJ	AXLE, REAR, LUBE {EmGard FE-75W-90} Synthetic Oil; 50 thru 64.99 Pints	0/0	0
14899	SUSPENSION AIR CONTROL VALVE Pressure Release Control In Cab	0/1	1

FRONT AXLES

2AUR	AXLE, FRONT NON-DRIVING {Meritor MFS-16-133A} Wide Track, I-Beam Type, 16,000-lb Capacity	186/0	186
------	---	-------	-----

FRONT SUSPENSIONS

3ADE	SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 16,000-lb Capacity, with Shock Absorbers	44/0	44
3770	SPRINGS, FRONT AUXILIARY Rubber	10/0	10

CABS, COWLS, BODIES

16030	CAB Conventional, Day Cab	0/0	0
16ZBT	ACCESS, CAB Steel, Driver & Passenger Sides, Two Steps per Door, for use with Day Cab and Extended Cab	0/0	0
16BAM	AIR CONDITIONER with Integral Heater and Defroster	0/0	0
16WBY	ARM REST, RIGHT, DRIVER SEAT	3/0	3
16VKK	CAB INTERIOR TRIM Diamond, for Day Cab	6/1	7
	<u>Includes</u>		
	: CONSOLE, OVERHEAD Molded Plastic with Dual Storage Pockets, Retainer Nets and CB Radio Pocket; Located Above Driver and Passenger		
	: DOME LIGHT, CAB Door Activated and Push On-Off at Light Lens, Timed Theater Dimming, Reading Lights; Integral to Overhead Console, Center Mounted		
	: SUN VISOR (3) Padded Vinyl; 2 Moveable (Front-to-Side) Primary Visors, Driver Side with Vanity Mirror and Toll Ticket Strap, plus 1 Auxiliary Visor (Front Only), Driver Side		
16WSK	CAB REAR SUSPENSION Air Bag Type	0/0	0
16WLS	FRESH AIR FILTER Attached to Air Intake Cover on Cowl Tray in Front of Windshield Under Hood	0/0	0
16GEG	GAUGE CLUSTER Premium Level; English with English Electronic Speedometer	0/0	0
	<u>Includes</u>		
	: GAUGE CLUSTER DISPLAY: Base Level (3" Monochromatic Display), Premium Level (5" LCD Color Display); Odometer, Voltmeter, Diagnostic Messages, Gear		

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
	Indicator, Trip Odometer, Total Engine Hours, Trip Hours, MPG, Distance to Empty/ Refill for : GAUGE CLUSTER Speedometer, Tachometer, Engine Coolant Temp, Fuel Gauge, DEF Gauge, Oil Pressure Gauge, Primary and Secondary Air Pressure : WARNING SYSTEM Low Fuel, Low DEF, Low Oil Pressure, High Engine Coolant Temp, Low Battery Voltage (Visual and Audible), Low Air Pressure (Primary and Secondary)		
16WHJ	HOSE CLAMPS, HEATER HOSE {Breeze} Belleville Washer Type	0/0	0
16XJN	INSTRUMENT PANEL Flat Panel	0/0	0
16HKT	IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster	0/0	0
16SNP	MIRRORS (2) C-Loop, Power Adjust, Heated, Black Heads and Arms, 7.5" x 14" Flat Glass, Includes 7.5" x 7" Convex Mirrors, for 102" Load Width	8/0	8
	<u>Notes</u> : Mirror Dimensions are Rounded to the Nearest 0.5"		
16SJW	MIRROR, CONVEX, HOOD MOUNTED {Lang Mekra} (2) Right and Left Sides, Black, Heated, 7.5" Sq.	9/0	9
16VLV	MONITOR, TIRE PRESSURE Omit	-10/-1	-11
16VCC	SEAT BELT All Orange; 1 to 3	0/0	0
16KBM	SEAT, DRIVER {National 2000 195} Air Suspension, High Back with Integral Headrest, Mordura Cloth, Isolator, 8" Adjuster, 1 Chamber Lumbar, 2 Position Front Cushion Adjust, 6-23 Degree Seat Back Adjust	0/0	0
16SMZ	SEAT, PASSENGER {Seats, Inc.} Non Suspension, High Back, Fixed Back, Integral Headrest, Mordura Cloth, for use with Batteries in Cab	35/9	44
16HCH	SEATBELT WARNING LIGHT IND. Mounted in Dash, Will Flash when Park Brake is Disengaged and Driver Seatbelt Unfastened, Audible Alarm to Remind Driver to Fasten Seatbelt	0/0	0
16WJU	WINDOW, POWER (2) and Power Door Locks, Left and Right Doors, Includes Express Down Feature	0/0	0

FRAMES

1CAJ	FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.866" x 3.622" x 0.437" (276.0mm x 92.0mm x 11.1mm); 456.0" (11582mm) Maximum OAL	281/549	830
1LLA	BUMPER, FRONT Swept Back, Steel, Heavy Duty	0/0	0
1MEJ	FRAME DIMPLE Dimple on Left and Right Top Flange of Frame Rail to Reference Rear Axle Centerline	0/0	0
1570	TOW HOOK, FRONT (2) Frame Mounted	8/0	8
1LEH	LICENSE PLATE HOLDER Single Plate, Swing Type, Mounted Below Front Bumper	3/0	3
1WGY	WHEELBASE RANGE 221" (560cm) Through and Including 262" (665cm)	495/-495	0

BRAKES

4091	BRAKE SYSTEM, AIR Dual System for Straight Truck Applications <u>Includes</u> : BRAKE LINES Color and Size Coded Nylon : DRAIN VALVE Twist-Type : GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster : PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel : PARKING BRAKE VALVE For Truck : QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4 : SPRING BRAKE MODULATOR VALVE R-7 for 4x2, SR-7 with relay valve for 6x4/8x6	0/0	0
------	---	-----	---

Code	Description	F/R Wt	Tot Wt
		(lbs)	(lbs)
4AZJ	AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Full Vehicle Wheel Control System, with Automatic Traction Control	0/0	0
4GBM	BRAKE, PARKING Manual Push-Pull Pneumatic Parking Brake	1/0	1
4XCJ	BRAKES, FRONT {Bendix Spicer ADB22X} Air Disc Type, Extended Service, Size 22.5", 23,000-lb Capacity	0/0	0
4XDX	BRAKE CHAMBERS, FRONT AXLE 20 SqIn, for Air Disc Brakes	1/0	1
4XCK	BRAKES, REAR {Bendix Spicer ADB22X} Air Disc Type, Extended Service, Size 22.5", 26,000-lb Capacity per Axle	0/0	0
4XEA	BRAKE CHAMBERS, REAR AXLE 18/24 SqIn Spring Brake, Double Diaphragm, for Air Disc Brakes	0/0	0
4XEE	PARK BRAKE CHAMBERS,ADDITIONAL (2) Spring Brake Type	0/60	60
4SPA	AIR COMPRESSOR {Cummins} 18.7 CFM	0/0	0
4EBT	AIR DRYER {Bendix AD-IP} with Heater	15/12	27
4VKC	AIR DRYER LOCATION Mounted Inside Left Rail, Back of Cab	15/6	21
4WZJ	AIR TANK LOCATION (2) : One Mounted Under Each Rail, Front of Rear Suspension, Parallel to Rail	-24/43	19
4722	DRAIN VALVE {Bendix DV-2} Automatic, with Heater, for Air Tank	1/0	1

STEERING

5PTB	STEERING GEAR (2) {Sheppard M100/M80} Dual Power	101/-5	96
5710	STEERING COLUMN Tilting and Telescoping	18/1	19
5CAW	STEERING WHEEL 4-Spoke; 18" Dia., Black	0/0	0

DRIVELINES

6DGS	DRIVELINE SYSTEM {Dana Spicer} SPL140 Main Driveline with SPL170 Interaxle Shaft, for 6x4	4/20	24
------	---	------	----

EXHAUST SYSTEMS

7BLW	EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Right Side Under Cab, for Single Vertical Tail Pipe, Frame Mounted Right Side Back of Cab	145/32	177
7BEV	AFTERTREATMENT COVER Steel, Black	11/2	13
7SCP	ENGINE EXHAUST BRAKE for Cummins ISB/B6.7/ISL/L9 Engine with Variable Vane Turbo Charger	0/0	0
7WCK	EXHAUST HEIGHT 12' 6"	24/10	34
7WDN	MUFFLER/TAIL PIPE GUARD (1) Aluminum	11/5	16
7WAZ	TAIL PIPE (1) Turnback Type	7/3	10

ELECTRICAL SYSTEMS

8000	ELECTRICAL SYSTEM 12-Volt, Standard Equipment <u>Includes</u> : DATA LINK CONNECTOR For Vehicle Programming and Diagnostics In Cab : HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel : HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever : PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light : STARTER SWITCH Electric, Key Operated : STOP, TURN, TAIL & B/U LIGHTS Dual, Rear, Combination with Reflector : TURN SIGNAL SWITCH Self-Cancelling for Trucks, Manual Cancelling for Tractors, with Lane Change Feature : WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever : WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted : WIRING, CHASSIS Color Coded and Continuously Numbered	0/0	0
------	---	-----	---

Code	Description	F/R Wt	Tot Wt
		(lbs)	(lbs)
8XLT	ALARM, PARK BRAKE, TIMER Programmable Parameter to Change Alarm Trigger Time	0/0	0
8XHC	ALARM, PARKING BRAKE Electric Horn Sounds in Repetitive Manner when Vehicle Park Brake is "NOT" Set, with Ignition "ON" or "OFF" and any Door Opened and Brake Pedal Released	0/0	0
8GXC	ALTERNATOR {Leece-Neville AVI160P2007} Brush Type, 12 Volt, 210 Amp Capacity, Pad Mount, with Remote Sense	1/0	1
8RPR	ANTENNA for Increased Roof Clearance Applications	1/0	1
8THB	BACK-UP ALARM Electric, 102 dBA	0/3	3
8XDZ	BATTERY BOX Steel, 2-3 Battery Capacity, Mounted Inside the Cab, Under Passenger Seat	-25/9	-16
8MMZ	BATTERY SYSTEM {Fleetrite AGM-GP31} Maintenance-Free, (3) AGM 12-Volt 2475CCA Total, Top Threaded Stud	65/41	106
8HAB	BODY BUILDER WIRING Back of Day Cab at Left Frame or Under Sleeper, Extended or Crew Cab at Left Frame; Includes Sealed Connectors for Tail/Amber Turn/Marker/ Backup/Accessory Power/Ground and Sealed Connector for Stop/Turn	2/0	2
8XAH	CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses	0/0	0
8WPH	CLEARANCE/MARKER LIGHTS (5) {Truck Lite} Amber LED Lights, Flush Mounted on Cab or Sunshade	0/0	0
8XMB	CONNECTOR, DASH, CENTER PANEL Cab Wiring for TMC RP1226 Vehicle Accessory Connector; Includes 14-pin Connector with Switched Power, Battery Power, Ignition Power, Ground & Body 250K Datalink, Connector Located Behind Instrument Panel Center Console	3/0	3
8XKC	HEADLIGHTS Halogen, with Daytime Running Lights, Automatic Twilight Controlled	0/0	0
8WRB	HEADLIGHTS ON W/WIPERS Headlights Will Automatically Turn On if Windshield Wipers are Turned On	0/0	0
8XHN	HORN, AIR Single Trumpet, Black, with Lanyard Pull Cord	3/0	3
8VAY	HORN, ELECTRIC Disc Style	0/0	0
8WWJ	INDICATOR, LOW COOLANT LEVEL with Audible Alarm	0/0	0
8899	JUMP START STUD (2) 12V, Remote Mounted	1/0	1
8RPS	RADIO AM/FM/WB/Clock/Bluetooth/USB Input/Auxiliary Input	3/0	3
8RMZ	SPEAKERS (2) 6.5" Dual Cone Mounted in Both Doors, (2) 5.25" Dual Cone Mounted in Both B-Pillars	6/2	8
8WXG	STARTING MOTOR {Mitsubishi Electric Automotive America 105P} 12-Volt, with Soft-Start	10/0	10
8WPZ	TEST EXTERIOR LIGHTS Pre-Trip Inspection will Cycle all Exterior Lamps Except Back-up Lights	0/0	0
8XGT	TURN SIGNALS, FRONT Includes LED Side Turn Lights Mounted on Fender	0/0	0
8WGL	WINDSHIELD WIPER SPD CONTROL Force Wipers to Slowest Intermittent Speed When Park Brake Set and Wipers Left on for a Predetermined Time	0/0	0

FRONT END

9WBC	FRONT END Tilting, Fiberglass, with Three Piece Construction, for WorkStar/HV	0/0	0
9WAC	BUG SCREEN Mounted Behind Grille	5/0	5
9585	FENDER EXTENSIONS Rubber	6/0	6
9HBM	GRILLE Stationary, Chrome	0/0	0
9AAB	LOGOS EXTERIOR Model Badges	0/0	0
9AAE	LOGOS EXTERIOR, ENGINE Badges	0/0	0

SPEEDOMETER, TOOLS, MISC

10AGB	CONNECTED PLATFORM Includes Connectivity Module and Five Year Data Plan	1/0	1
10RHG	DUAL DRIVE Customer Does Not Intend to Convert to In-Cab Dual Drive Positions	0/0	0

Code	Description	F/R Wt	Tot Wt
		(lbs)	(lbs)
10WKN	KEYS - ALL ALIKE, ID I-1624 Compatible with Z-250	0/0	0
10BAE	LABEL, DEF "DEF ONLY"	0/0	0
10WWP	MUD FLAPS, FRONT WHEELS (2) Rubber, Mounted on Fender Extension, for Tire Size 425/445	3/0	3
10060	PAINT SCHEMATIC, PT-1 Single Color, Design 100 <u>Includes</u> : PAINT SCHEMATIC ID LETTERS "WL"	0/0	0
10761	PAINT TYPE Base Coat/Clear Coat, 1-2 Tone	0/0	0
10WCY	SAFETY TRIANGLES	6/0	6

FUEL TANKS

15SGD	FUEL TANK Top Draw, Non-Polished Aluminum, D-Style, 19" Tank Depth, 100 US Gal (379L), Mounted Left Side, Under Cab	37/22	59
15WHV	ANTI-SIPHON DEVICE for Single Tank; 2-Inch Diameter; Located inside Fuel Tank Fill Neck	1/0	1
15WDG	DEF TANK 7 US Gal (26L) Capacity, Frame Mounted Outside Left Rail, Under Cab	0/0	0
15924	FUEL TANK STRAPS Bright Finish Stainless Steel	0/0	0
15LNS	FUEL/WATER SEPARATOR {Racor 400 Series} 12 VDC Electric Heater, Includes Pre-Heater, with Primer Pump, Includes Water-in-Fuel Sensor, Mounted on Engine	-2/-3	-5

WHEELS, TIRES - FRONT

27DPN	WHEELS, FRONT {Accuride 29039} DISC; 22.5x9.00 Rims, Powder Coat Steel, 5-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs, Non-Standard Offset, with .5" Thick Disc	62/0	62
7792545437	(2) TIRE, FRONT 315/80R22.5 Load Range L HAU 3 WT (CONTINENTAL), 480 rev/mile, 68 MPH, All-Position	62/0	62

WHEELS, TIRES - REAR

28DTT	WHEELS, REAR {Accuride 28828} DUAL DISC; 22.5x8.25 Rims, Powder Coat Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with .472" Thick Increased Capacity Disc and with Steel Hubs	0/56	56
7382135444	(8) TIRE, REAR 11R22.5 Load Range H HDR2+ (CONTINENTAL), 491 rev/mile, 75 MPH, Drive	0/40	40

WHEELS MISC OPTIONS

29WLK	WHEEL BEARING, FRONT, LUBE {EmGard FE-75W-90} Synthetic Oil Cab schematic 100WL Location 1: 9219, Winter White (Std) Chassis schematic N/A	0/0	0
-------	---	-----	---

Services Section:**WARRANTY**

40128	WARRANTY Standard for HV507/HV509, HV50B, HV607/HV609 Models, Effective with Vehicles Built July 1, 2017 or Later, CTS-2025A	0/0	0
40NSG	CARB COMPANION PLAN for CARB B6.7 and L9 Engines	0/0	0

Total Component Weight:
8621/7209 **15830**
 (lbs) (lbs)

Code	Description	F/R Wt	Tot Wt
		(lbs)	(lbs)
1	<p>AMHRL25</p> <p>Furnish and Install: One (1) Amrep Hardox Rear Loader Full Push Out AMHRL-25 on Your 3-Axle Cab & Chassis</p> <p>See Standard Specification Sheet - 25-yard Elliptical Body Style - 3.5 Cubic Yard Hopper, Full Push-Out Ejection, Body Material:</p> <p>Body Floor - 3/16 In Hardox 450 Side Walls - 1/8" Hardox AR450 Roof - 1/8" Hardox AR450</p> <p>Packer Shoes: UHMW Polyethylene</p> <p>Body Door: Large Street Side Service Door</p> <p>Hopper Floor Liner: 1/8" Hardox 450</p> <p>Sweep Cylinders 4 in. bore x 3 in. rod, 3/16" Hardox AR450</p> <p>Slide Cylinder 4-1/2 in. bore x 3-1/2 in. rod x 32-1/2 in. stroke</p> <p>Controls: Dual Lever Controls Outside LH Side Control Valves Primary; Parker VA35</p> <p>Paint: Single Color - Body to Match Cab, Unless Otherwise Noted</p> <p>Color Code: Default Match Cab White</p> <p>Additional Items: Broom & Shovel Mounted on Body Shell, Fire Extinguisher 20lb on Tandem Fender Work Light</p> <p>Standard 12 Month Warranty on Workmanship and Materials (More Warranty Options Below)</p> <p>Body Mounted Fire Extinguisher 20lb</p> <p>LED Body Side Backing Assist Lights - reverse activated</p> <p>Dual Strobe Lights, Amber - upper LH & RH on tailgate - in-cab switch</p> <p>Tool Box (18 x 18 x 24) - frame mounted</p> <p>Left Hand Buzzer Kit</p> <p>Dual Broom and Shovel Rack - mounted on both sides of tailgate</p> <p>Hopper Floor Kit (1/4 - 150,000 psi in lieu of standard 3/16 150,000 psi)</p> <p>Adjustable Roll Bar with Control Kit</p> <p>Dual Hopper Work Light Kit - two lights - switch in cab</p>	0/0	0
2	State Contract CTR069476 2%	0/0	0
Total Body Allied:		0/0	0
		(lbs)	(lbs)

The weight calculations included in this proposal are an estimate of future vehicle weight. The actual weight as manufactured may be different from the estimated weight. Navistar, Inc. shall not be liable for any consequences resulting from any differences between the estimated weight of a vehicle and the actual weight.

Description	(US DOLLAR)	Price
Total Factory List Price Including Options:		\$180,985.00
Freight Charge	\$3,100.00	
Total Freight:		\$3,100.00
Total Factory List Price Including Freight:		\$184,085.00
Less Customer Allowance:		(\$51,965.95)
Total Vehicle Price:		\$132,119.05
Total Body/Allied Equipment:		\$150,427.35
Total Sale Price:		\$282,546.40
Total Per Vehicle Sales Price:		\$282,546.40
Total Net Sales Excluding Taxes:		\$282,546.40
Arizona Tire Tax, 10 Tires 4.66x10	\$46.66	
Sales Tax, Pima County	\$17,235.33	
Total Taxes:		\$17,281.99
Net Sales Price:		\$299,828.39

State Contract CTR069476

If applicable, Federal Excise Tax (FET) is included in the net sales price above.

Terms of payment are cash on delivery and prices quoted are FOB Phoenix, AZ (unless otherwise noted).

This quote is good for 30 days. All inventory units are subject to prior sale. Unless otherwise noted, the quote above does NOT include title and licensing charges or Arizona state sales tax.

Please feel free to contact me regarding these specifications should your interests or needs change. I am confident you will be pleased with the quality and service of an International vehicle.

Approved by Seller:

Official Title and Date

Authorized Signature

Accepted by Purchaser:

Firm or Business Name

Authorized Signature and Date

**This proposal is not binding upon the seller without
Seller's Authorized Signature**

Official Title and Date

If you haven't added a planned maintenance service contract to your proposal yet, please get in touch with your local dealer, International or IC Bus Sales Representative to learn more about the benefits when ordering together with the vehicle.

International® Financial offers loans, a full line up of lease options, and can establish a line of credit for use towards the purchase of International and IC Bus vehicles. Ask your dealer, International® or IC Bus® Sales Representative about completing an International Financial credit application and any promotional offers that may be available. International Financial services are provided by Navistar Financial Corporation.

The TOPS FET Calculation is an estimate for reference purposes only. The seller is responsible for calculating and reporting/paying appropriate FET to the IRS.

The limited warranties applicable to the vehicles described here in are International Motors, LLC* standard printed warranties which are incorporated herein by reference and to which you have been provided a copy and hereby agree to their terms and conditions.

International Motors, LLC d/b/a International Motors USA LLC in Illinois and Ohio.