

April 15, 2024

Juneau Historic Resources Advisory Committee Attn: Forrest Courtney, Planner I 155 Heritage Way Juneau, AK 99801 907-586-0753 ext. 4208 forrest.courtney@juneau.gov

Gastineau Channel Historical Society Attn: Gary Gillette, President P.O. Box 21264 Juneau, Alaska 99802 907-586-5338 juneauhistory@gmail.com

Subject: Invite to Comment

Juneau Harbor

230 South Franklin Street, Juneau City and Borough, AK 99801

EBI Project No.: 011039-PR

Pursuant to Section 106 of the National Historic Preservation Act, the regulations promulgated thereunder and interagency agreements developed thereto, EBI Consulting, Inc., on behalf of AT&T Mobility, LLC, provides this notice of a proposed telecommunications facility installation at the address listed above.

EBI would like to inquire if you would be interested in commenting on this proposed project. Please refer to the attached plans for additional details.

Please note that we are requesting your review of the attached information as part of the Section 106 process only and not as part of the local zoning process. We are only seeking comments related to the proposed project's potential effect to historic properties.

Please submit your comments regarding the proposed project's potential effect on historic properties to EBI Consulting, to my attention at 21 B Street, Burlington, MA 01803, or contact me via telephone at the number listed below. Please reference the EBI project number. We would appreciate your comments as soon as possible within the next 30 days.

Note that this project will be entered into the Federal Communication Commission's e106 System, which will send notifications of the project throughout the Section 106 process.



Sincerely,

Chris Robinson Architectural Historian II 978.877.3493 crobinson@ebiconsulting.com

Appendices: Maps and Project Drawings






Figure 1: Site Location Map

Juneau Harbor 230 South Franklin Street Juneau, AK 99801







Figure 2: Topographic Map

Juneau Harbor 230 South Franklin Street Juneau, AK 99801





JN3073 JUNEAU HARBOR MARINE VIEW NSB

FA LOCATION CODE: 14738339 230 S. FRANKLIN STREET, JUNEAU, AK 99801

S-1

S-2

S-4

S-5

CUT SHEETS

PROJECT INFORMATION

PROJECT DESCRIPTION:

SCOPE OF WORK FOR NEW SITE BUILD (NSB): TO BE PROVIDED BY MASTEC SCOPING

MASTEC NETWORK SOLUTIONS - ALASKA 2240 E. DOWLING ROAD ANCHORAGE, AK 99507

CODE INFORMATION:

253-709-0317

MIXED USE (MU) ZONING CLASSIFICATION: INTERNATIONAL BUILDING CODE BUILDING CODE:

PARCEL NUMBER:

CONSTRUCTION TYPE:

1C070K820010

II-B

CURRENT CODE 2021

TELECOM FACILITY

58° 17' 57.8112" N

JURISDICTION: BOROUGH OF JUNEAU

LOT SIZE: TBD

CURRENT USE: COMMERCIAL RETAIL

OFFICE SPACE & RESIDENTIAL APARTMENTS

PROPOSED USE:

POWER SERVICE: KODIAK ELECTRIC GCI ACS

TELCO SERVICE: SITE LOCATION:


LATITUDE:

58.299392

LONGITUDE: 134° 24' 17.262" W -134.404795

EXISTING ROOF DECK: OVERALL HEIGHT AGL:

125.8' 134'-0" BASE OF STRUCTURE AMSL:



DRIVING DIRECTIONS

JUNEAU INTERNATIONAL AIRPORT

HEAD SOUTH ON SHELL SIMMONS DR TOWARD YANDUKIN DR 0.2 MI

TURN RIGHT ONTO YANDUKIN DR 0.9 MI SLIGHT RIGHT ONTO EGAN DR 1.1 MI CONTACT: PAT HINMAN

SELECT SITE ACQUISITION LLC 425-306-2733

PROPERTY OWNER:

JUNEAU, AK 98225

TOWER OWNER:

JUNEAU, AK 98225

CONTACT: ANITA BAUER

PHONE: 907-586-4990

CONTACT: JUSTIN ABBOTT

OFFICE: 907-336-1300

MOBILE: 907-351-3886

SELECT SITE ACQUISITION LLC

#170A

PERMITTING:

ALASKA

206-790-4655

SITE ACQUISTION:

CONTACT: ANITA BAUER

PHONE: 907-586-4990

ROBBINS-HATTRUP PARTNERSHIP

ROBBINS-HATTRUP PARTNERSHIP

9105 MENDENHALL MALL ROAD

PROPERTY MANAGER

PROPERTY MANAGER

9105 MENDENHALL MALL ROAD

CONSTRUCTION: CONTACT: TODD RICHARDSON

MASTEC NETWORK SOLUTIONS

2240 E. DOWLING ROAD ANCHORAGE, AK 99507

JUNEAU, AK 99801

PROJECT TEAM

PROJECT ARCHITECT:

PROJECT CONSULTANT:


DAVID H. DEAN, ARCHITECT 13424 246TH AVE SE

DHD ARCHITECTURE PLLC:

ISSAQUAH, WA 98027 425.503.0637 P DAVIDHDEAN@MSN.COM

MASTEC NETWORK SOLUTIONS - ALASKA 2240 E. DOWLING ROAD ANCHORAGE, AK 99507 253-709-0317

VICINITY MAP



1873 SHELL SIMMONS DR, JUNEAU, AK 99801

KEEP LEFT TO STAY ON EGAN DR 6.2 MI

CONTINUE ONTO MARINE WAY 0.2 MI

SHARP LEFT ONTO S FRANKLIN ST 72 FT

SLIGHT RIGHT TO STAY ON S FRANKLIN ST DESTINATION WILL BE ON THE LEFT

230 S FRANKLIN ST

DRAWING INDEX

SHEET **DESCRIPTION** TITLE SHEET GENERAL NOTES SITE PLAN ENLARGED PLANS A-2.2BUILDING EXTERIOR ELEVATIONS ENLARGED EXTERIOR ELEVATIONS DETAILS DETAILS RF-1ANTENNA CONFIGURATION & SCHEDULE RF-2SIGNAGE - RADIO FREQUENCY INFORMATION STRUCTURAL T-1TITLE SHEET MODIFICATION INSPECTION CHECKLIST NOTES N-2

MODIFICATION SCHEDULE

PLATFORM FRAMING PLAN

PLATFORM ROOFTOP PLACEMENT

PLATFORM INSTALLATION DETAIL

PLATFORM LADDER DETAILS

BRODUCT INFORMATION

APPROVALS LIST

APPROVAL	DATE	SIGNATURE
MNS ENGINEERING — SSA		
MNS SCOPING MANAGER		
MNS SAQ PROJECT MANAGER		
MNS CONSTRUCTION MANAGER		
AT&T SAQ PROJECT MANAGER		
AT&T CONSTRUCTION MANAGER		
CONSTRUCTION DOCUMENTS REVIEW APPROPRIATE TITLE BLOCK ABOVE.		DER. REVIEWERS MUST STAMP THEIR NAME ON THE

LEGAL DESCRIPTION

PROPERTY ID: 14257 LEGAL DESCRIPTION: LOT 3 BLOCK 4, AIRPARK SUBDIVISION, KODIAK,

SITE ACCESS REQUIREMENTS

GATE CODES:	TBD
DOOR CODES:	TBD
POINT OF CONTACT FOR FACILITIES:	
SITE TECH CONTACT - NUMBER:	TBD
SITE ACCESS TIME FRAME:	TBD


TILITIES PRIOR <u>to diggin</u>

CALL 911

811 OR (800) 478-3121 (ALASKA) **EMERGENCY:**







ISSUED DATE:

01-05-2024

l⊹MasTec

Select Site Acquisition

24009 E ALKI LANE LIBERTY LAKE, WA 99019

SHEET TITLE:

TITLE SHEET

GENERAL NOTES:

- DRAWINGS ARE NOT TO BE SCALED, WRITTEN DIMENSIONS TAKE PRECEDENCE, THIS SET OF DOCUMENTS IS INTENDED TO BE USED FOR DIAGRAMMATIC PURPOSES ONLY, UNLESS NOTED OTHERWISE. THE GENERAL CONTRACTOR'S SCOPE OF WORK SHALL INCLUDE FURNISHING ALL MATERIALS, EQUIPMENT, LABOR, AND ANY REQUIREMENTS DEEMED NECESSARY TO COMPLETE PROJECT AS DESCRIBED IN THE DRAWINGS AND OWNER'S PROJECT MANUAL.
- 2. PRIOR TO THE SUBMISSION OF BIDS, CONTRACTORS INVOLVED SHALL VISIT THE JOB SITE TO FAMILIARIZE THEMSELVES WITH ALL CONDITIONS AFFECTING THE PROPOSED PROJECT. CONTRACTORS SHALL VISIT THE CONSTRUCTION SITE WITH THE CONSTRUCTION/CONTRACT DOCUMENTS TO VERIFY FIELD CONDITIONS AND CONFIRM THAT THE PROJECT WILL BE ACCOMPLISHED AS SHOWN. PRIOR TO PROCEEDING WITH CONSTRUCTION, ANY ERRORS, OMISSIONS, OR DISCREPANCIES SHALL BE BROUGHT TO THE ATTENTION OF THE ARCHITECT/ENGINEER VERBALLY AND IN WRITING.
- 3. THE ARCHITECTS/ENGINEERS HAVE MADE EVERY EFFORT TO SET FORTH IN THE CONSTRUCTION AND CONTRACT DOCUMENTS THE COMPLETE SCOPE OF WORK. CONTRACTORS BIDDING THE JOB ARE NEVERTHELESS CAUTIONED THAT MINOR OMISSIONS OR ERRORS IN THE DRAWINGS AND OR SPECIFICATIONS SHALL NOT EXCUSE SAID CONTRACTOR FROM COMPLETING THE PROJECT AND IMPROVEMENTS IN ACCORDANCE WITH THE INTENT OF THESE DOCUMENTS. THE BIDDER SHALL BEAR THE RESPONSIBILITY OF NOTIFYING (IN WRITING) THE ARCHITECT/ENGINEER OF ANY CONFLICTS, ERRORS, OR OMISSIONS PRIOR TO SUBMISSION OF CONTRACTOR'S PROPOSAL. IN THE EVENT OF DISCREPANCIES THE CONTRACTOR SHALL PRICE THE MORE COSTLY OR EXTENSIVE WORK, UNLESS DIRECTED OTHERWISE.
- 4. THE CONTRACTOR SHALL SUPERVISE AND DIRECT THE PROJECT DESCRIBED IN THE CONTRACT DOCUMENTS. THE CONTRACTOR SHALL BE SOLELY RESPONSIBLE FOR ALL CONSTRUCTION MEANS, METHODS, TECHNIQUES, SEQUENCES, AND PROCEDURES FOR COORDINATING ALL PORTIONS OF THE WORK UNDER THE CONTRACT.
- THE CONTRACTOR SHALL INSTALL ALL EQUIPMENT AND MATERIALS ACCORDING TO MANUFACTURER'S/VENDOR'S SPECIFICATIONS UNLESS NOTED OTHERWISE OR WHERE LOCAL CODES OR ORDINANCES TAKE PRECEDENCE.
- ALL WORK PERFORMED ON THE PROJECT AND MATERIALS INSTALLED SHALL BE IN STRICT ACCORDANCE WITH ALL APPLICABLE CODES, REGULATIONS, AND ORDINANCES. CONTRACTOR SHALL GIVE ALL NOTICES AND COMPLY WITH ALL LAWS, ORDINANCES, RULES, REGULATIONS AND LAWFUL ORDERS OF ANY PUBLIC AUTHORITY, MUNICIPAL AND UTILITY COMPANY SPECIFICATIONS, AND LOCAL AND STATE JURISDICTIONAL CODES BEARING ON THE PERFORMANCE OF THE WORK.
- GENERAL CONTRACTOR SHALL PROVIDE, AT THE PROJECT SITE, A FULL SET OF CONSTRUCTION DOCUMENTS UPDATED WITH THE LATEST REVISIONS AND ADDENDA OR CLARIFICATIONS FOR USE BY ALL PERSONNEL INVOLVED WITH THE PROJECT. THIS SET IS A VALID CONTRACT DOCUMENT ONLY IF THE TITLE SHEET IS STAMPED "FOR CONSTRUCTION" AND EACH SUCCESSIVE SHEET BEARS THE ARCHITECT'S SIGNED WET STAMP.
- 8. THE STRUCTURAL COMPONENTS OF ADJACENT CONSTRUCTION OR FACILITIES ARE NOT TO BE ALTERED BY THIS CONSTRUCTION PROJECT UNLESS NOTED OTHERWISE.
- 9. SEAL ALL PENETRATIONS THROUGH FIRE-RATED AREAS WITH U.L. LISTED OR FIRE MARSHALL APPROVED MATERIALS IF APPLICABLE TO THIS FACILITY AND OR PROJECT SITE
- 10. CONTRACTOR TO PROVIDE A PORTABLE FIRE EXTINGUISHER WITH A RATING OF NOT LESS THAN 2-A OR 2-A10BC WITHIN 75 FEET TRAVEL DISTANCE TO ALL PORTIONS OF PROJECT AREA DURING CONSTRUCTION.
- 11. CONTRACTOR SHALL MAKE NECESSARY PROVISIONS TO PROTECT EXISTING IMPROVEMENTS, EASEMENTS, PAVING, CURBING, ETC. DURING CONSTRUCTION. UPON COMPLETION OF WORK, CONTRACTOR SHALL REPAIR ANY DAMAGE THAT MAY HAVE OCCURRED DUE TO CONSTRUCTION ON OR ABOUT THE PROPERTY.
- 12. CONTRACTOR SHALL KEEP GENERAL WORK AREA CLEAN AND HAZARD FREE DURING CONSTRUCTION AND DISPOSE OF ALL DIRT, DEBRIS, AND RUBBISH. CONTRACTOR SHALL REMOVE EQUIPMENT NOT SPECIFIED AS REMAINING ON THE PROPERTY OR PREMISES. SITE SHALL BE LEFT IN CLEAN CONDITION AND FREE FROM PAINT SPOTS, DUST, OR SMUDGES OF ANY NATURE.
- 13. THE GENERAL CONTRACTOR SHALL RECEIVE WRITTEN AUTHORIZATION TO PROCEED WITH CONSTRUCTION PRIOR TO STARTING WORK ON ANY ITEM NOT CLEARLY DEFINED BY THE CONSTRUCTION DRAWINGS/CONTRACT DOCUMENTS.
- 14. THE CONTRACTOR SHALL PERFORM WORK DURING OWNER'S PREFERRED HOURS TO AVOID DISTURBING NORMAL BUSINESS.
- 15. THE CONTRACTOR SHALL PROVIDE AT&T WIRELESS, LLC. PROPER INSURANCE CERTIFICATES NAMING AT&T WIRELESS, LLC. AS ADDITIONAL INSURED, AND AT&T WIRELESS, LLC. PROOF OF LICENSE(S) AND PE & PD INSURANCE.
- CONTRACTOR SHALL BE RESPONSIBLE FOR SCHEDULING AND COORDINATING ALL INSPECTIONS.
- 17. CAUTION! CALL BEFORE YOU DIG! BURIED UTILITIES EXIST IN THE AREA AND UTILITY INFORMATION SHOWN MAY NOT BE COMPLETE. CONTACT THE ONE-CALL UTILITY LOCATE SERVICE A MINIMUM OF 48 HOURS PRIOR TO CONSTRUCTION. DIAL 811
- 18. CONTRACTOR TO DOCUMENT ALL WORK PERFORMED WITH PHOTOGRAPHS AND SUBMIT TO AT&T WIRELESS, LLC. ALONG WITH REDLINED CONSTRUCTION SET.
- 19. CONTRACTOR TO DOCUMENT ALL CHANGES MADE IN THE FIELD BY MARKING UP (REDLINING) THE APPROVED CONSTRUCTION SET AND SUBMITTING THE REDLINED SET TO AT&T WIRELESS, LLC. UPON COMPLETION.
- 20. FOR COLLOCATION SITES: CONTACT TOWER OWNER REPRESENTATIVE FOR PARTICIPATION IN BID WALK.
- 21. GENERAL CONTRACTOR IS TO COORDINATE ALL POWER INSTALLATION WITH POWER COMPANY AS REQUIRED. CONTRACTOR TO REPORT POWER INSTALLATION COORDINATION SOLUTION(S) TO NETWORK CARRIER REPRESENTATIVE, PROJECT CONSTRUCTION MANAGER AND ARCHITECT.
- 22. ANY SUBSTITUTIONS OF MATERIALS AND/OR EQUIPMENT, MUST BE APPROVED BY AT&T CONSTRUCTION MANAGER.
- 23. IN THE CASE OF ROOFTOP SOLUTIONS FOR EQUIPMENT AND/OR ANTENNA FRAMES WHERE PENETRATION OF EXISTING ROOFING MATERIALS OCCUR, THE GENERAL CONTRACTOR SHALL COORDINATE WITH BUILDING OWNER AND BUILDING ROOFING CONTRACTOR OF RECORD FOR INSTALLATION, PATCH, REPAIR OR ANY AUGMENTATION TO THE ROOF, AND HAVE THE WORK GUARANTEED UNDER THE ROOFING CONTRACTOR'S WARRANTY FOR MOISTURE PENETRATION OR AND OTHER FUTURE BREACH OF ROOFING INTEGRITY.
- 24. IN THE CASE OF ROOFTOP SOLUTIONS WITH THE INSTALLATION OF ANTENNAS WITHIN CONCEALED (SHROUDED) SUPPORT FRAMES OR TRIPODS, THE GENERAL CONTRACTOR SHALL COORDINATE WITH THE FRP DESIGNER/FABRICATOR TO ENSURE THAT THE FINAL FRP SHROUD IS SIMULATING (IN APPEARANCE) DESIGNATED EXISTING EXTERIOR BUILDING FACADE MATERIALS, TEXTURES, AND COLORS. THE CONTRACTOR SHALL FURTHERMORE ENSURE THE USE OF COUNTERSUNK FASTENERS IN ALL FRP CONSTRUCTION. WHEN PHOTO SIMULATIONS ARE PROVIDED, THE CONTRACTOR SHALL ENSURE THAT FINAL CONSTRUCTION REPRESENTS WHAT IS INDICATED IN PHOTO SIMULATIONS. SHOP DRAWINGS SHALL BE PROVIDED TO THE GENERAL CONTRACTOR, CONSTRUCTION COORDINATOR, AND ARCHITECT PRIOR TO FABRICATION AND CONSTRUCTION.

GENERAL NOTES (CONT'D):

- 25. IN THE CASE OF ROOFTOP SOLUTIONS FOR EQUIPMENT AND/OR ANTENNA FRAMES WHERE ANCHORING TO A CONCRETE ROOF SLAB IS REQUIRED, CONTRACTORS SHALL CONFIRM (PRIOR TO SUBMITTING BID) WITH CONSULTING CONSTRUCTION COORDINATOR AND ARCHITECT THE PRESENCE OF POST TENSION TENDONS WITHIN THE ROOF SLAB RESULTING FROM AN UNDOCUMENTED DESIGN CHANGE IN THE EXISTING BUILDING "AS-BUILT DRAWING SET" HAVING INDICATED AN ORIGINAL DESIGN SOLUTION OF REINFORCED CONCRETE W/ EMBEDDED STEEL REBAR. IN THE EVENT POST TENSION SLAB SOLUTION IS PRESENT, CONTRACTOR SHALL INCLUDE PROVISIONS FOR X-RAY PROCEDURES (INCLUDED IN BID) FOR ALL PENETRATION AREAS WHERE ANCHORING OCCURS.
- 26. GENERAL & SUB CONTRACTORS SHALL USE STAINLESS STEEL METAL LOCKING TIES FOR ALL CABLE TRAY TIE DOWNS AND ALL OTHER GENERAL TIE DOWNS (WHERE APPLICABLE). PLASTIC ZIP TIES SHALL NOT BE PERMITTED FOR USE ON AT&T PROJECTS. RECOMMENDED MANUFACTURE SHALL BE: PANDUIT CORP. METAL LOCKING TIES MODEL NO. MLT4S-CP UNDER SERIES-304 (OR EQUAL). PANDUIT PRODUCT DISTRIBUTED BY TRIARC OF TACOMA, WA.

DESIGN CRITERIA:

1. THE STRUCTURAL DESIGN OF THIS PROJECT IS IN ACCORDANCE WITH THE INTERNATIONAL BUILDING CODE 2018

2. **DESIGN LOADS**:

-ROOF SNOW LOAD	PER STRUCTURAL
-BASIC WIND SPEED	PER STRUCTURAL
-WIND EXPOSURE	PER STRUCTURAL

CONCRETE NOTES:

- 1. ALL CONCRETE CONSTRUCTION SHALL BE IN ACCORDANCE WITH ACI-318.
- CONCRETE SHALL BE MIXED, PROPORTIONED, CONVEYED AND PLACED IN ACCORDANCE WITH CHAPTER 19 OF THE IBC 2021. STRENGTHS AT 28 DAYS AND MIX CRITERIA SHALL BE AS FOLLOWS.

TYPE OF CONSTRUCTION	28 DAY STRENGTHS (fc)	W/C RATIO	MINIMUM CEMENT CONTENT
A. SLABS ON GRADE TOPPING SLABS			PER CUBIC YARD
CONCRETE PIERS	3,000 PSI	≤ .45	5 1/2 SACKS
B. ALL STRUCTURAL CONCRETE EXCEPT WALLS	4,000 PSI	≤ .45	6 1/2 SACKS
C. CONCRETE WALLS	4,000 PSI	≤ .45	6 1/2 SACKS

CEMENT SHALL BE ASTM C150, PORTLAND CEMENT TYPE II U.N.O.

- THE GENERAL CONTRACTOR SHALL SUPERVISE AND BE RESPONSIBLE FOR THE METHODS AND PROCEDURES OF CONCRETE PLACEMENT.
- 4. ALL CONCRETE WITH SURFACES EXPOSED TO STANDING WATER SHALL BE AIR-ENTRAINED WITH AN AIR-ENTRAINING AGENT CONFORMING TO ASTM C260, C494, C618, C989 AND C1017. TOTAL AIR CONTENT SHALL BE IN ACCORDANCE WITH TABLE 1904 2.1 OF THE IRC 2021
- 5. REINFORCING STEEL SHALL CONFORM TO ASTM A615 (INCLUDING SUPPLEMENT S1), GRADE 60, fy=60,000 PSI. EXCEPTIONS: ANY BARS SPECIFICALLY SO NOTED ON THE DRAWINGS SHALL BE GRADE 40, fy=40,000 PSI. GRADE 60 REINFORCING BARS INDICATED ON DRAWINGS TO BE WELDED SHALL CONFORM TO ASTM A706. REINFORCING COMPLYING WITH ASTM A615(S1) MAY BE WELDED ONLY IF MATERIAL PROPERTY REPORTS INDICATING CONFORMANCE WITH WELDING PROCEDURES SPECIFIED IN A.W.S. D14 ARE SUBMITTED.
- 6. REINFORCING STEEL SHALL BE DETAILED (INCLUDING HOOKS AND BENDS) IN ACCORDANCE WITH AC1 315 AND 318. LAP ALL CONTINUOUS REINFORCEMENT AT LEAST 30 BAR DIAMETERS OR A MINIMUM OF 2'-0". PROVIDE CORNER BARS AT ALL WALL AND FOOTING INTERSECTIONS. LAP CORNER BARS AT LEAST 30 BAR DIAMETERS OR A MINIMUM OF 2'-0". LAP ADJACENT MATS OF WELDED WIRE FABRIC A MINIMUM OF 8" AT SIDES AND ENDS.
- 7. WELDED WIRE FABRIC SHALL CONFORM TO ASTM A-185.
- SPIRAL REINFORCEMENT SHALL BE PLAIN WIRE CONFORMING TO ASTM A615, GRADE 60, fy=60,000 PSI.
- 9. NO BARS PARTIALLY EMBEDDED IN HARDENED CONCRETE SHALL BE FIELD BENT UNLESS SPECIFICALLY SO DETAILED OR APPROVED BY THE CONSULTANT.
- 10. CONCRETE PROTECTION (COVER) FOR REINFORCING STEEL SHALL BE AS FOLLOWS:
- FOOTINGS AND OTHER UNFORMED SURFACES, EARTH FACE 3"

 FORMED SURFACES EXPOSED TO EARTH OR WEATHER (#6 BARS OR LARGER) 2" (#5 BARS OR SMALLER) 1 1/2"

3/4"

- 11. BARS SHALL BE SUPPORTED ON CHAIRS OR DOBIE BRICKS.
- 12. ANCHOR BOLTS TO CONFORM TO ASTM A307.

SLABS AND WALLS (INTERIOR FACE)

- 13. NON-SHRINK GROUT SHALL BE FURNISHED BY AN APPROVED MANUFACTURER AND SHALL BE MIXED AND PLACED IN STRICT ACCORDANCE WITH THE MANUFACTURER'S PUBLISHED RECOMMENDATIONS. GROUT STRENGTH SHALL BE AT LEAST EQUAL TO THE MATERIAL ON WHICH IT IS PLACED (3,000 PSI MINIMUM).
- 14. ALL EXPANSION ANCHORS TO BE HILTI BRAND. ADHESIVE ANCHORS REQUIRE TESTING TO CONFIRM CAPACITY UNLESS WAIVED BY ENGINEER.

STRUCTURAL STEEL NOTES:

- 1. SHOP DRAWINGS FOR STRUCTURAL STEEL SHALL BE SUBMITTED TO THE CONSULTANT FOR REVIEW PRIOR TO FABRICATION.
- 2. STRUCTURAL STEEL DESIGN, FABRICATION AND ERECTION (INCLUDING FIELD WELDING, HIGH STRENGTH FIELD BOLTING, EXPANSION BOLTS, AND THREADED EXPANSION ANCHORS) SHALL BE BASED ON THE A.I.S.I. "SPECIFICATION FOR THE DESIGN, FABRICATION, AND ERECTION OF STRUCTURAL STEEL FOR BUILDINGS" LATEST EDITION. SUPERVISION SHALL BE IN ACCORDANCE WITH IBC 2021 CHAPTER 22, BY A QUALIFIED TESTING AGENCY DESIGNATED BY THE CONSULTANT. THE CONSULTANT SHALL BE FURNISHED WITH A COPY OF ALL INSPECTION REPORTS AND TEST RESULTS.
- 3. STRUCTURAL STEEL SHALL CONFORM TO THE FOLLOWING REQUIREMENTS

TYPE OF MEMBER

A. WIDE FLANGE SHAPE	ASTM A992, Fy 50 KSI
B. OTHER SHAPE, PLATES AND ROD	ASTM A36, Fy 36 KSI
C. PIPE COLUMNS	ASTM A53, Fy 35 KSI
D. STRUCTURAL TUBING	ASTM A500, Fy 46 KSI
E. ANCHOR BOLTS	ASTM A307
F. CONNECTION BOLTS	ASTM A325

- 4. ALL MATERIAL TO BE HOT DIPPED GALVANIZED AFTER FABRICATION PER A123/A123M-00.
- 5. ALL WELDING SHALL BE IN CONFORMANCE WITH A.I.S.I. AND AWS STANDARDS AND SHALL BE PERFORMED BY W.A.B.O. CERTIFIED WELDERS USING E70 XX ELECTRODES. ONLY PREQUALIFIED WELDS (AS DEFINED BY AWS) SHALL BE USED. WELDING OF GRADE 60 REINFORCING BARS (IF REQUIRED) SHALL BE PERFORMED USING LOW HYDROGEN ELECTRODES. WELDING OF GRADE 40 REINFORCING BARS (IF REQUIRED) SHALL BE PERFORMED USING E70 XX ELECTRODES. WELDING WITHIN 4" OF COLD BENDS IN REINFORCING STEEL IS NOT PERMITTED. SEE REINFORCING NOTE FOR MATERIAL REQUIREMENTS OF WELDED BARS.
- 6. COLD-FORMED STEEL FRAMING MEMBERS SHALL BE OF THE SHAPE, SIZE, AND GAGE SHOWN ON THE PLANS. PROVIDE MINIMUM SECTION PROPERTIES INDICATED. ALL COLD-FORMED STEEL FRAMING SHALL CONFORM TO THE A.I.S.I. "SPECIFICATION FOR THE DESIGN OF COLD-FORMED STEEL STRUCTURAL MEMBERS."
- 7. BOLTED CONNECTIONS SHALL USE BEARING TYPE ASTM A325 BOLTS (3/4" DIA.) AND SHALL HAVE A MINIMUM OF TWO BOLTS UNLESS NOTED OTHERWISE.
- NON-STRUCTURAL CONNECTIONS FOR STEEL GRATING MAY USE 5/8" DIA. ASTM A307 BOLTS UNLESS NOTED OTHERWISE.
- 9. ALL STEEL WORK SHALL BE PAINTED IN ACCORDANCE WITH THE DESIGN & CONSTRUCTION SPECIFICATION AND IN ACCORDANCE WITH ASTM A36 UNLESS NOTED OTHERWISE
- 10. ALL WELDS TO BE 1/4" FILLET UNLESS NOTED OTHERWISE.
- 11. TOUCH UP ALL FIELD DRILLING AND WELDING WITH 2 COATS OF GALVACON (ZINC RICH PAINT) OR APPROVED EQUAL.

TOWER/POLE NOTES:

- 1. VERIFICATION THAT THE PROPOSED TOWER/POLE CAN SUPPORT THE PROPOSED ANTENNA LOADING IS TO BE DONE BY OTHERS.
- PROVIDE SUPPORTS FOR THE ANTENNA COAX CABLES TO THE ELEVATION OF ALL INITIAL AND FUTURE ANTENNAS. ANTENNA COAX CABLES ARE TO BE SUPPORTED AND RESTRAINED AT THE CENTERS SUITABLE TO THE MANUFACTURER'S REQUIREMENTS.

ABBREVIATED ROOF TOP SAFETY PROCEDURES (WHEN APPLICABLE):

FALL PROTECTION METHODS AND EQUIPMENT ROOF TOP INSTALLATIONS

- 1. FOR WORK IS BEING PERFORMED WITHIN 25' OF AN UNPROTECTED ROOF EDGE, THE CONSTRUCTION SUPERVISOR SHALL DESIGNATE A TRAINED SAFETY MONITOR TO OBSERVE THE MOVEMENTS AND ACTIVITIES OF THE CONSTRUCTION
- 2. SAFETY MONITOR SHALL WARN CONSTRUCTION WORKERS OF HAZARDS (I.E., BACKING UP TOWARD A ROOF EDGE, ETC.) OR UNSAFE ACTIVITIES. THE SAFETY MONITOR MUST BE ON THE SAME ROOF AND WITHIN VISUAL AND VERBAL DISTANCE OF THE CONSTRUCTION WORKERS.
- 3. CONSTRUCTION INVOLVING WORKERS TO APPROACH WITHIN 6' OR LESS OF AN UNPROTECTED ROOF EDGE, REQUIRES WORKERS TO USE SAFETY LINE.
- 4. SAFETY LINE SHALL BE MINIMUM ½" DIAMETER NYLON, WITH A NOMINAL TENSILE STRENGTH OF 5400 LBS.
- 5. SAFETY LINE SHALL BE ATTACHED TO A SUBSTANTIAL MEMBER OF THE STRUCTURE.
- 6. SAFETY LINE LENGTH SHALL BE SET ALLOWING CONSTRUCTION WORKER TO REACH EDGE OF ROOF, BUT NOT BEYOND.
- 7. SAFETY BELTS SHALL BE WORN BY ALL CONSTRUCTION WORKERS.
- MONTHLY SAFETY INSPECTION AND MAINTENANCE OF THE FALL PROTECTION EQUIPMENT SHALL OCCUR BY THE SAFETY COMMITTEE REPRESENTATIVES, INCLUDING:

INSPECTION OF CONSTRUCTION AREA FOR HAZARDS
USE OF AN INSPECTION CHECKLIST
INTERVIEWING COWORKERS REGARDING SAFETY CONCERNS
REPORTING AND DOCUMENTING ANY HAZARDS
REPORTING HAZARDS TO THE SAFETY COMMITTEE FOR CONSIDERATION
POSTING RESULTS OF INSPECTION AND ANY ACTION TAKEN
RECEIVING AN UNBIASED REVIEW OF ONE'S OWN WORK AREA BY ANOTHER

REFER TO ROOFTOP WORK AREA SAFETY PROTOCOL
NATIONAL ASSOCIATION OF TOWER ERECTORS 2000 PUBLICATION

COWORKER SAFETY REPRESENTATIVE


REFERENCED OSHA REGULATION/STANDARDS SHALL BE REVIEWED BY TOWER

ERECTORS,
EQUIPMENT INSTALLERS, AND TOWER/ROOF TOP CONTRACTORS/SUBCONTRACTORS

29 CFR 1926.500 - SCOPE, APPLICATION, AND DEFINITIONS
29 CFR 1926.501 - DUTY TO HAVE FALL PROTECTION
19 CFR 1926.502 - FALL PROTECTION SYSTEMS CRITERIA AND PRACTICES

SYMBOLS AND ABBREVIATIONS

A/C AGL	AIR CONDITIONING ABOVE GRADE LEVEL	LBS MAX	POUNDS MAXIMUM
APPROX	APPROXIMATELY	MECH	MECHANICAL
		MTL	METAL
BLDG	BUILDING	MFR	MANUFACTURE
BLK	BLOCKING	MGR	MANAGER
		MIN	MINIMUM
CLG	CEILING	MISC	MISCELLANEOUS
CLR	CLEAR		
CONC	CONCRETE	NA	NOT APPLICABLE
CONST	CONSTRUCTION	NIC	NOT IN CONTRACT
CONT	CONTINUOUS	NS NTS	NEAR SIDE NOT TO SCALE
DBL	DOUBLE	NIS	NOT TO SCALE
DIA	DIAMETER	ОС	ON CENTER
DIAG	DIAGONAL	OD	OUTSIDE DIAMETER
DIAG	DOWN	OD	OUTSIDE DIAMETER
DET	DETAIL	PLYWD	PLYWOOD
DWG	DRAWING	PROJ	PROJECT
5110	DI V WII CO	PROP	PROPERTY
EA	EACH	PT	PRESSURE TREATE
EL .	ELEVATION	REQ	REQUIRED
ELEC	ELECTRICAL	RM	ROOM
EQ	EQUAL	RO	ROUGH OPENING
EQUIP	EQUIPMENT		
EXT	EXTERIOR	SHT	SHEET
		SIM	SIMILAR
FIN	FINISH	SPEC	SPECIFICATION
FLUOR	FLUORESCENT	SF	SQUARE FOOT
FLR	FLOOR	SS	STAINLESS STEEL
FS 	FAR SIDE	STL	STEEL
FT	FOOT	STRUCT	STRUCTURAL
0.4	041105	STD	STUD
GA OALV	GAUGE	SUSP	SUSPENDED
GALV	GALVANIZED	TUDU	TUDOUCU
GC GRND	GENERAL CONTRACTOR GROUND	THRU TNNG	THROUGH TINNED
GKND GYP BD	GYPSUM WALL BOARD	TYP	TYPICAL
317 00	GTF 30W WALL BOAND	111	TIFICAL
HORZ	HORIZONTAL	UNO	UNLESS NOTED
HR	HOUR		OTHERWISE
HT	HEIGHT		
HVAC	HEATING	VERT	VERTICAL
	VENTILATION	VIF	VERIFY IN FIELD
	AIR CONDITIONING		
		W/	WITH
ID IN	INSIDE DIAMETER	W/O	WITHOUT
NEO	INCH	WP	WATER PROOF
INFO	INFORMATION		
INSUL	INSULATION		
INT IBC	INTERIOR INTERNATIONAL		
IDC	BUILDING CODE		
		TELEPHO	DNE
	——————————————————————————————————————	POWER	



TRANSMITTING NOTES:

APPLICABLE BUILDING CODES AND STANDARDS:

- ALL TRANSMITTING ANTENNAS WILL BE INSTALLED IN A MANNER AS SET FORTH BY THE MANUFACTURER AND BY THE FEDERAL COMMUNICATIONS COMMISSION AS MEETING THE CURRENT AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI) STANDARD FOR NONIONIZING ELECTROMAGNETIC RADIATION (NIER).

- TELECOMMUNICATIONS INDUSTRY ASSOCIATION, (TIA) 222-G, STRUCTURAL STANDARD FOR STRUCTURAL ANTENNA TOWER AND ANTENNA SUPPORTING STRUCTURES.

- INSTITUTE FOR ELECTRICAL AND ELECTRONICS ENGINEERS (IEEE) 81, GUIDE FOR MEASURING EARTH RESISTIVITY, GROUND IMPEDANCE, AND EARTH SURFACE POTENTIALS OF A GROUND SYSTEM IEEE 1000 (1999) RECOMMENDED PRACTICE FOR POWERING AND GROUNDING OF ELECTRONIC EQUIPMENT.

- IEEE C62.41, RECOMMENDED PRACTICES ON SURGE VOLTAGES IN LOW VOLTAGE AC POWER CIRCUITS (FOR LOCATION CATEGORY "C3" AND "HIGH SYSTEM EXPOSURE").

- TIA 607 COMMERCIAL BUILDING GROUNDING AND BONDING REQUIREMENTS FOR TELECOMMUNICATIONS.



*MasTec
Network Solutions

Select Site Acquisition, LLC

24009 E ALKI LANE LIBERTY LAKE, WA 99019

ARCHITECTURE PLLC
13424 246TH AVE SE
ISSAQUAH, WA, 98027
PHONE: 425.657.0552
EMAIL: davidhdean@outlook.com

JUNEAU HARBOR
MARINE VIEW NSB
230 S FRANKLIN STREET

15SUE BLOCK

6-22 TURF4:NSB 1C RFDS DATED 04-08-22

6-23 REV TO PENTHOUSE EQUIPMENT

3-23 ADD SCHEMATIC CONDUIT RUN INFO


9-23 ANTENNA MOUNT REVS

4-23 EQUIPMENT REVISIONS

5-24 TURF4:REV TO EQUIPMENT PLATFORM

ISSUED DATE:

01 - 05 - 2024



SHEET TITLE:

GENERAL NOTES

CBJ GIS LOT LINE —

NOTES:

- THE PURPOSE OF THIS SURVEY IS TO PROVIDE AS-BUILT LOCATIONS OF THE ROOF/PENTHOUSE AND ALL PROTRUDING EQUIPMENT ON THE ROOF OF THE MARINEVIEW APARTMENTS.
- THE FIELD WORK FOR THIS SURVEY WAS CONDUCTED IN SEPTEMBER, 2022.
- THE HORIZONTAL POSITIONS OF SURVEY CONTROL POINTS WERE ESTABLISHED WITH A COMBINATION OF HIGH PRECISION STATIC GPS AND CONVENTIONAL TOTAL STATION METHODS.
- PROPERTY LINES DERIVED FROM CITY AND BOROUGH OF JUNEAU PUBLISHED GIS DATA. PROPERTY LINES SHOWN ARE GRAPHICAL REPRESENTATIONS AND ARE NOT INTENDED TO REPRESENT ACTUALLY PROPERTY LOCATIONS.
- MARINE VIEW ROOF ELEVATION DERIVED FROM AVERAGED SHOT POINTS. ROOF ELEVATION = 107.3'
- ELEVATOR SHAFT BUILDING (PENTHOUSE ROOF) DERIVED FROM AVERAGE SHOT ELEVATIONS. PENTHOUSE ROOF ELEVATION = 124.3'

HORIZONTAL CONTROL STATEMENT

THE BASIS OF COORDINATES IS THE NAD83 ALASKA STATE PLANE ZONE 1 COORDINATES FOR THE CP-1, SET SPIKE. THESE NAD83 ALASKA STATE PLANE ZONE 1 COORDINATES ARE 2,362,083.82 NORTH, 2,541,967.25 EAST, U.S. SURVEY FEET (58°17'55.3695" NORTH, 134°24'53.8941" WEST). CP-1 IS LOCATED ON THE NW CORNER OF "TRACY'S CRAB SHACK" PARKING LOT.

VERTICAL CONTROL STATEMENT

VERTICAL DATUM BASED ON NAVD88 ELEVATIONS EXPRESSED IN US FEET. THE BASE OF ELEVATION IS CONTROL POINT CP-1, A SET SPIKE, HAVING AN ELEVATION OF 22.25'. THE ELEVATIONS FOR ALL OTHER POINTS WERE DETERMINED USING REAL TIME KINEMATIC SURVEYING TECHNIQUES AND DERIVED USING GEOID12B.




SCALE IN FEET


NAME OF SURVEYOR: RESPEC 1028 AURORA DR. FAIRBANKS, AK 99709 **PHONE**: 907.452.1414 **FAX**: 907.4562707 AECC163270


ROOF SURVEY MARINE VIEW APARTMENTS

LOCATED WITHIN LOTS 1 & 2, BLOCK 82 **TIDELANDS ADDITION RECORDED PLAT 340** JUNEAU RECORDING DISTRICT, JUNEAU, AK CITY AND BOROUGH OF JUNEAU, JUNEAU, AK

OWNER:	SCALE		1	" = 10
MasTec Network Solutions	SURVEYOR			ΕV
2240 E. DOWLING RD.	DRAWN			CES
ANCHORAGE, AK 99515	CHECKED			KHE
907.336.1300	DATE		9/30	0/2022
	PROJECT NO.		10944.	22001
	SHEET NUMBER	1	OF	1







*MasTec
Network Solutions

Select Site Acquisition, LLC 24009 E ALKI LANE LIBERTY LAKE, WA 99019


URE PLLC

AVE SE
(AA, 98027
657.0552
n@outlook.com


ARCHITECTURE PLI
13424 246TH AVE SE
1SSAQUAH, WA, 98027
PHONE: 425.657.0552
EMAIL: davidhdean@outlook.com
HTTP://www.DHDARCHITECTURE.BI

JUNEAU HARBOR MARINE VIEW NSB

05-26-22 TURF4:NSB 1C RFD
02-16-23 REV TO PENTHOUSE
02-23-23 ADD SCHEMATIC CO
04-19-23 ANTENNA MOUNT RE
05-24-23 EQUIPMENT REVISION
01-05-24 TURF4:REV TO EQUI



SHEET TITLE: EXTERIOR ELEVATIONS



⊹MasTec **Network Solutions**


Select Site Acquisition,

24009 E ALKI LANE LIBERTY LAKE, WA 99019


73 RBOR EW NSB N STREET 99801

JUNEAU,

ISSUED DATE: 01-05-2024



SHEET TITLE: EXTERIOR **ELEVATIONS**



Network Solutions

Select Site Acquisition,


24009 E ALKI LANE LIBERTY LAKE, WA 99019


JU MA 230


ISSUED DATE: 01-05-2024




ENLARGED EXTERIOR ELEVATIONS









*MasTec
Network Solutions

Select Site Acquisition, LLC 24009 E ALKI LANE LIBERTY LAKE, WA 99019


ACHITECTURE PLLC
13424 246TH AVE SE
ISSAQUAH, WA, 98027
PHONE: 425.657.0552
EMAIL: davidhdean@outlook.com

JN3073 NEAU HARBOR RINE VIEW NSB

REV TO PENTHOUSE EQUIPMENT
ADD SCHEMATIC CONDUIT RUN INFO
ANTENNA MOUNT REVS
EQUIPMENT REVISIONS
TURF4:REV TO EQUIPMENT PLATFORM

SHEET TITLE:

EQUIPMENT DETAILS



*MasTec
Network Solutions

Select Site Acquisition, LLC 24009 E ALKI LANE

24009 E ALKI LANE LIBERTY LAKE, WA 99019

ARCHITECTURE PLLC
13424 246TH AVE SE
1SSAQUAH, WA, 98027
PHONE: 425.657.0552
EMAIL: davidhdean@outlook.com
HTTP://www.DHDARCHITECTURE.BIZ

JN3073
JUNEAU HARBOR
AARINE VIEW NSB
30 S FRANKLIN STREET
JUNEAU, AK 99801

5–26–22 TURF4:NSB 1C RFDS DATED 04–08–22

2–16–23 REV TO PENTHOUSE EQUIPMENT

2–23–23 ADD SCHEMATIC CONDUIT RUN INFO

1–19–23 ANTENNA MOUNT REVS

5–24–23 EQUIPMENT REVISIONS

1–05–24

1–05–24

1–05–24

1–05–24

1–05–24

1–05–24

1–05–24

1–05–24

1–05–24

1–05–24

1–05–24

1–05–24

1–05–24

1–05–24

1–05–24

1–05–25

1–05–24

1–05–25

1–05–25

1–05–25

1–05–25

1–05–26

1–05–26

1–05–26

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27

1–05–27


1–05–27


ISSUED DATE:



SHEET TITLE: ANTENNA

CONFIGURATION





SIGNAGE

NO SCALE


SIGNS AND PLACEMENT:

1. LOW LEVEL BLUE NOTICE SIGNS - PLACE AT SITE ENTRY / ACCESS POINTS ONLY.

- ROOFTOPS: PLACE SIGNS ON THE INSIDE OF ROOF HATCH; PLACE ON ACCESS DOOR UNLESS DOOR IS USED BY GENERAL PUBLIC OR BUILDING TENANTS ON A REGULAR BASIS FOR ACCESS — IN THESE CASES CONSULT CONSTRUCTION MANAGER.
- WATER TANKS: PLACE SIGNS ON COMPOUND GATE.
- NETWORK CARRIER OWNED SITES: PLACE ONE SIGN ON COMPOUND GATE; ALL SIGNS SHALL BE SECURED WITH EITHER STAINLESS STEEL ZIP TIES OR STAINLESS TECH SCREWS.
- 2. CONSTRUCTION COORDINATOR PARTICIPATION IN SIGN LOCATION: NETWORK CARRIER CONSTRUCTION MANAGER SHALL MEET WITH ALL CONSTRUCTION COORDINATOR'S TO OUTLINE CRITERIA FOR SIGN PLACEMENT. EMPHASIS SHALL BE PLACED ON "CHALLENGING" SITES, WHERE THE NETWORK CARRIER CONSTRUCTION MANAGERS SHALL GIVE CONSTRUCTION COORDINATOR'S AS MUCH GUIDANCE ON EACH SPECIFIC SITUATION AS POSSIBLE, HOWEVER, CONSTRUCTION COORDINATOR'S SHALL BE ENCOURAGED TO PARTNER WITH NETWORK CARRIER CONSTRUCTION MANAGER IN DECIDING PLACEMENT PERTAINING TO CHALLENGING SITES. A SITE VISIT MAY BE REQUIRED TO FULFILL REQUIREMENTS. CONSTRUCTION COORDINATOR SHALL IDENTIFY ALL SIGN LOCATIONS AT THE A&E WALK. PLEASE SEE SIGN DETAIL AND SIZE.
- 3. SIGN DISBURSEMENT FROM WAREHOUSE: SIGN INVENTORY SHALL BE ACCESSIBLE AT NETWORK CARRIER WAREHOUSE

GENERAL SIGNAGE NOTES

1. FOR AT&T LOGO SEE AT&T LOGO DESIGN SPECIFICATIONS 2. ALL TEXT FONT IS ARIAL U.N.O. 3. CONTRACTOR TO PROCURE FCC NO. FROM AT&T COMPLIANCE MANAGER PH: 425-580-8860 4. TEXT FOR SIGNAGE SHALL INDICATE CORRECT SITE NAME AND NUMBER AS PER AT&T CONSTRUCTION MANAGER RECOMMENDATIONS 5. CABINET MOUNTING APPLICATION REQUIRES ADHERING PLATE TO FACE OF CABINET WITH WATERPROOFING POLYURETHANE ADHESIVE 6. AT&T MOBILITY COMPLIANCE STATEMENT: BASED ON THE INFORMATION COLLECTED, AT&T MOBILITY WILL BE COMPLIANT WITH FCC RULES AND REGULATIONS AT THE NEAREST WALKING SURFACE II RECOMMENDATIONS IN THE COMPLIANCE SUMMARY



NO SCALE

JU MA MA 230

ISSUED DATE:

01-05-2024

SHEET TITLE: EQUIPMENT DETAILS

SHEET NUMBER:

SIGNAGE

ARE IMPLEMENTED. REFER TO RFSSRP REPORT AND TO REFERENCE IT FOR SPECIFIC SIGNAGE REQUIREMENTS.

TO BE DISBURSED AS PART OF THE GENERAL CONTRACTOR BOM AS CALLED OUT IN A&E DRAWINGS FOR EACH SITE.

NO SCALE

NOTES:

PLATFORM INSTALLATION DRAWINGS PREPARED FOR AT&T

SITE NAME: JUNEAU HARBOR NUMBER: JN3073 FA NUMBER: 14738339

SITE ADDRESS: 230 S. FRANKLIN STREET, JUNEAU, JUNEAU BOROUGH, AK 99801

PROJECT CONTACTS:

- PROJECT MANAGER TODD RICHARDSON 907-336-3886 TODD.RIHARDSON@MASTEC.COM
- DESIGN ENGINEER MAIN RFI CONTACT RAHUL MANGARI, EI RAHUL.MANGARI@MASTEC.COM
- **ENGINEER OF RECORD** RAPHAEL I. MOHAMED, PE, PEng 919-674-5895 1151 SE CARY PKWY, SUITE 101 CARY, NC 27518 RAPHAEL. MOHAMED@MASTEC.COM
- FOR FABRICATION AND CONSTRUCTION RELATED INQUIRIES: CONTACT MASTEC

BUILDING INFORMATION

BUILDING HEIGHT / TYPE: 107.3 FT BUILDING ROOFTOP W/ 18.5

PENTHOUSE

*MasTec
Network Solutions

107 FT (PLATFORM) MOUNT HEIGHT/TYPE:


BUILDING LOCATION: LAT: 58.2993° -134.4047° LONG:

PASSING ANALYSIS FIRM NAME: MASTEC NETWORK SOLUTIONS

PROJECT NUMBER: 45903-MOD2

CODE COMPLIANCE

ANSI/TIA-222-H 2021 INTERNATIONAL BUILDING CODE



QUALIFIED ENGINEERING SERVICES ARE AVAILABLE FROM MASTEC NETWORK SOLUTIONS TO ASSIST CONTRACTORS IN CLASS IV RIGGING PLAN REVIEWS. FOR REQUESTED QUALIFIED ENGINEERING SERVICES, PLEASE CONTACT RAPHAEL MOHAMED AT (919) 244-5207.

ISTRUCTION/INSTALLATION SPECTIONS AND TESTING JIRED (COMPLETED BY EOR)	REPORT ITEM
	PRE-CONSTRUCTION
X	MI CHECKLIST DRAWING
N/A	EOR APPROVAL
N/A	FABRICATION INSPECTION
N/A	FABRICATOR CERTIFIED WELD INSPECTION
N/A	MATERIAL TEST REPORT (MTR)
N/A	FABRICATOR NDE INSPECTION
N/A	NDE REPORT OF BASE PLATE
X	PACKING SLIPS
	CONSTRUCTION
	CONSTRUCTION
X	CONSTRUCTION INSPECTIONS
X N/A	
	CONSTRUCTION INSPECTIONS
N/A	CONSTRUCTION INSPECTIONS CONTINUOUS FOUNDATION INSPECTIONS
N/A N/A	CONSTRUCTION INSPECTIONS CONTINUOUS FOUNDATION INSPECTIONS CONCRETE COMP. STRENGTH AND SLUMP TESTS
N/A N/A N/A	CONSTRUCTION INSPECTIONS CONTINUOUS FOUNDATION INSPECTIONS CONCRETE COMP. STRENGTH AND SLUMP TESTS GROUT COMP. STRENGTH (ASTM C109) POST INSTALLED ANCHOR ROD VERIFICATION BASE PLATE GROUT VERIFICATION
N/A N/A N/A N/A	CONSTRUCTION INSPECTIONS CONTINUOUS FOUNDATION INSPECTIONS CONCRETE COMP. STRENGTH AND SLUMP TESTS GROUT COMP. STRENGTH (ASTM C109) POST INSTALLED ANCHOR ROD VERIFICATION BASE PLATE GROUT VERIFICATION
N/A N/A N/A N/A N/A	CONSTRUCTION INSPECTIONS CONTINUOUS FOUNDATION INSPECTIONS CONCRETE COMP. STRENGTH AND SLUMP TESTS GROUT COMP. STRENGTH (ASTM C109) POST INSTALLED ANCHOR ROD VERIFICATION BASE PLATE GROUT VERIFICATION CONTRACTOR'S CERTIFIED WELD INSPECTION AND
N/A N/A N/A N/A N/A N/A	CONSTRUCTION INSPECTIONS CONTINUOUS FOUNDATION INSPECTIONS CONCRETE COMP. STRENGTH AND SLUMP TESTS GROUT COMP. STRENGTH (ASTM C109) POST INSTALLED ANCHOR ROD VERIFICATION BASE PLATE GROUT VERIFICATION CONTRACTOR'S CERTIFIED WELD INSPECTION AND NOT REPORTS
N/A N/A N/A N/A N/A N/A N/A	CONSTRUCTION INSPECTIONS CONTINUOUS FOUNDATION INSPECTIONS CONCRETE COMP. STRENGTH AND SLUMP TESTS GROUT COMP. STRENGTH (ASTM C109) POST INSTALLED ANCHOR ROD VERIFICATION BASE PLATE GROUT VERIFICATION CONTRACTOR'S CERTIFIED WELD INSPECTION AND NOT REPORTS EARTHWORK: LIFT AND DENSITY
N/A N/A N/A N/A N/A N/A N/A X	CONSTRUCTION INSPECTIONS CONTINUOUS FOUNDATION INSPECTIONS CONCRETE COMP. STRENGTH AND SLUMP TESTS GROUT COMP. STRENGTH (ASTM C109) POST INSTALLED ANCHOR ROD VERIFICATION BASE PLATE GROUT VERIFICATION CONTRACTOR'S CERTIFIED WELD INSPECTION AND NOT REPORTS EARTHWORK: LIFT AND DENSITY ON SITE COLD GALVANIZING VERIFICATION
N/A N/A N/A N/A N/A N/A N/A N/A N/A	CONSTRUCTION INSPECTIONS CONTINUOUS FOUNDATION INSPECTIONS CONCRETE COMP. STRENGTH AND SLUMP TESTS GROUT COMP. STRENGTH (ASTM C109) POST INSTALLED ANCHOR ROD VERIFICATION BASE PLATE GROUT VERIFICATION CONTRACTOR'S CERTIFIED WELD INSPECTION AND NOT REPORTS EARTHWORK: LIFT AND DENSITY ON SITE COLD GALVANIZING VERIFICATION GUY WIRE TENSION REPORT GC AS-BUILT DOCUMENTS
N/A N/A N/A N/A N/A N/A N/A N/A X N/A X ITIONAL TESTING AND IN	CONSTRUCTION INSPECTIONS CONTINUOUS FOUNDATION INSPECTIONS CONCRETE COMP. STRENGTH AND SLUMP TESTS GROUT COMP. STRENGTH (ASTM C109) POST INSTALLED ANCHOR ROD VERIFICATION BASE PLATE GROUT VERIFICATION CONTRACTOR'S CERTIFIED WELD INSPECTION AND NOT REPORTS EARTHWORK: LIFT AND DENSITY ON SITE COLD GALVANIZING VERIFICATION GUY WIRE TENSION REPORT GC AS-BUILT DOCUMENTS
N/A N/A N/A N/A N/A N/A N/A N/A X N/A X ITIONAL TESTING AND IN	CONSTRUCTION INSPECTIONS CONTINUOUS FOUNDATION INSPECTIONS CONCRETE COMP. STRENGTH AND SLUMP TESTS GROUT COMP. STRENGTH (ASTM C109) POST INSTALLED ANCHOR ROD VERIFICATION BASE PLATE GROUT VERIFICATION CONTRACTOR'S CERTIFIED WELD INSPECTION AND NDE REPORTS EARTHWORK: LIFT AND DENSITY ON SITE COLD GALVANIZING VERIFICATION GUY WIRE TENSION REPORT GC AS-BUILT DOCUMENTS
N/A N/A N/A N/A N/A N/A N/A N/A X N/A X ITIONAL TESTING AND IN	CONSTRUCTION INSPECTIONS CONTINUOUS FOUNDATION INSPECTIONS CONCRETE COMP. STRENGTH AND SLUMP TESTS GROUT COMP. STRENGTH (ASTM C109) POST INSTALLED ANCHOR ROD VERIFICATION BASE PLATE GROUT VERIFICATION CONTRACTOR'S CERTIFIED WELD INSPECTION AND NDE REPORTS EARTHWORK: LIFT AND DENSITY ON SITE COLD GALVANIZING VERIFICATION GUY WIRE TENSION REPORT GC AS-BUILT DOCUMENTS SPECTIONS:

NOTE: X DENOTES A DOCUMENT NEEDED FOR THE PMI REPORT

N/A DENOTES A DOCUMENT THAT IS NOT REQUIRED FOR THE PMI REPORT

ADDITIONAL TESTING AND INSPECTIONS:

MODIFICATION INSPECTION NOTES:

GENERAL:

- 1. THE MODIFICATION INSPECTION (MI) IS A VISUAL INSPECTION OF THE TOWER MODIFICATIONS AND A REVIEW OF CONSTRUCTION INSPECTIONS AND OTHER REPORTS TO ENSURE THE INSTALLATION WAS CONSTRUCTED IN ACCORDANCE WITH THE CONTRACT DOCUMENTS, NAMELY THE MODIFICATION DRAWINGS, AS DESIGNED BY THE ENGINEER OF RECORD (EOR)
- 2. THE MI IS TO CONFIRM INSTALLATION CONFIGURATION AND WORKMANSHIP ONLY AND IS NOT A REVIEW OF THE MODIFICATION DESIGN ITSELF, NOR DOES THE MI INSPECTOR TAKE OWNERSHIP OF THE MODIFICATION DESIGN.

 OWNERSHIP OF THE STRUCTURAL MODIFICATION DESIGN EFFECTIVENESS AND INTEGRITY RESIDES WITH THE EOR AT ALL TIMES.
- 3. TO ENSURE THAT THE REQUIREMENTS OF THE MI ARE MET IT IS VITAL THAT THE GENERAL CONTRACTOR (GC) AND THE MI INSPECTOR BEGIN COMMUNICATING AND COORDINATING AS SOON AS A PO IS RECEIVED. IT IS EXPECTED THAT EACH PARTY WILL BE PROACTIVE IN REACHING OUT TO THE OTHER PARTY. IF CONTACT INFORMATION IS NOT KNOWN, CONTACT YOUR POINT OF CONTACT (POC).

MI INSPECTOR:

- 1. THE MI INSPECTOR IS REQUIRED TO CONTACT THE GC AS SOON AS RECEIVING A PO FOR THE MI TO, AT A MINIMUM
 - REVIEW THE REQUIREMENTS OF THE MI CHECKLIST WORK WITH THE GC TO DEVELOP A SCHEDULE TO CONDUCT ON-SITE INSPECTIONS, INCLUDING FOUNDATION INSPECTIONS.
- 2. THE MI IS RESPONSIBLE FOR COLLECTING ALL GENERAL CONTRACTORS (GC) INSPECTION AND TEST REPORTS, REVIEWING THE DOCUMENTS FOR ADHERENCE TO THE CONTRACT DOCUMENTS, CONDUCTING THE IN-FIELD INSPECTIONS. AND SUBMITTING THE MI REPORT.

GENERAL CONTRACTOR:

- 1. THE GC IS REQUIRED TO CONTACT THE MI INSPECTOR AS SOON AS RECEIVING A PO FOR THE MODIFICATION INSTALLATION OR TURNKEY PROJECT TO, AT A MINIMUM:
- REVIEW THE REQUIREMENTS OF THE MI CHECKLIST.
- WORK WITH THE MI INSPECTOR TO DEVELOP A SCHEDULE TO CONDUCT
- ON-SITE MI INSPECTIONS, INCLUDING FOUNDATION INSPECTIONS.
- BETTER UNDERSTAND ALL INSPECTION AND TESTING REQUIREMENTS.
- 2. THE GC SHALL PERFORM AND RECORD THE TEST AND INSPECTION RESULTS IN ACCORDANCE WITH THE REQUIREMENTS OF THE MI CHECKLIST.

MI VERIFICATION INSPECTIONS:

VERIFICATION INSPECTION MAY BE CONDUCTED BY AN INDEPENDENT FIRM AFTER A MODIFICATION PROJECT IS COMPLETED, AS MARKED BY THE OF AN ACCEPTED "PASSING MI" OR "PASS AS NOTED MI" REPORT FOR THE ORIGINAL PROJECT.

REQUIRED PHOTOS:

BETWEEN THE GC AND THE MI INSPECTOR THE FOLLOWING PHOTOGRAPHS, AT A MINIMUM. ARE TO BE TAKEN AND INCLUDED IN THE MI REPORT:

- PRE-CONSTRUCTION GENERAL SITE CONDITION
- PHOTOGRAPHS DURING THE REINFORCEMENT MODIFICATION CONSTRUCTION/ERECTIONS AND INSPECTION:
- RAW MATERIALS
- PHOTOS OF ALL CRITICAL DETAILS
- FOUNDATION MODIFICATIONS
- WELD PREPARATION
- BOLT INSTALLATION AND TORQUE
- FINAL INSTALLED CONDITION
- SURFACE COATING REPAIR
- POST CONSTRUCTION PHOTOGRAPHS
- FINAL IN FIELD CONDITIONS

PHOTOS OF ELEVATED MODIFICATION TAKEN FROM THE GROUND SHALL BE CONSIDERED INADEQUATE.

CORRECTION OF FAILING MI'S:

IF THE MODIFICATION INSTALLATION WOULD FAIL THE MI ("FAILED MI"), THE GC SHALL WORK WITH THE TOWER OWNER TO COORDINATE A REMEDIATION PLAN IN ONE OF TWO WAYS:

- CORRECT FAILING ISSUES TO COMPLY WITH THE SPECIFICATIONS CONTAINED IN THE ORIGINAL CONTRACT DOCUMENTS AND COORDINATE A SUPPLEMENT MI.
- OR, THE GC MAY WORK WITH THE EOR TO RE-ANALYZE THE MODIFICATION/ENFORCEMENT USING THE AS-BUILT CONDITION.


RECOMMENDATIONS:

THE FOLLOWING RECOMMENDATIONS AND SUGGESTIONS ARE OFFERED TO ENHANCE THE EFFICIENCY AND EFFECTIVENESS OF DELIVERING A MI REPORT:

- IT IS SUGGESTED THAT THE GC PROVIDE A MINIMUM OF 5 BUSINESS DAYS NOTICE, PREFERABLY 10, TO THE MI INSPECTOR AS TO WHEN THE SITE WILL BE READY FOR THE MI TO BE CONDUCTED.
- THE GC AND MI INSPECTOR COORDINATE CLOSELY THROUGHOUT THE ENTIRE PROJECT.
- WHEN POSSIBLE IT IS PREFERRED TO HAVE THE GC AND MI INSPECTOR ON-SITE SIMULTANEOUSLY FOR ANY GUY WIRE TENSIONING OR RE-TENSIONING OPERATIONS.
- IT MAY BE BENEFICIAL TO INSTALL ALL TOWER MODIFICATIONS PRIOR TO CONDUCTING THE FOUNDATION INSPECTIONS TO ALLOW FOUNDATION AND MI INSPECTION(S) TO COMMENCE WITH ONE SITE VISIT.
- WHEN POSSIBLE, IT IS PREFERRED TO HAVE THE GC AND MI INSPECTOR ON-SITE DURING THE MI TO HAVE ANY DEFICIENCIES CORRECTED DURING THE INITIAL MI, THEREFORE, THE GC MAY CHOOSE TO COORDINATE THE MI CAREFULLY TO ENSURE ALL CONSTRUCTION FACULTIES ARE AT THEIR DISPOSAL WHEN THE MI INSPECTOR IS ON SITE.

CANCELLATION OR DELAYS IN SCHEDULED MI:

IF THE GC AND MI INSPECTOR AGREE TO A DATE ON WHICH THE MI WILL BE CONDUCTED, AND EITHER PARTY CANCELS OR DELAYS, TOWER OWNER SHALL NOT BE RESPONSIBLE FOR ANY COSTS, FEES, LOSS OF DEPOSITS AND/OR OTHER PENALTIES RELATED TO THE CANCELLATION OR DELAY INCURRED BY EITHER PARTY FOR ANY TIME (E.G. TRAVEL AND LODGING, COSTS OF KEEPING EQUIPMENT ON-SITE, ETC.). IF TOWER OWNER CONTRACTS DIRECTLY FOR A THIRD PARTY MI, EXCEPTIONS MAY BE MADE IN THE EVENT THAT THE DELAY/CANCELLATION IS CAUSED BY WEATHER OR OTHER CONDITIONS THAT MAY COMPROMISE THE SAFETY OF THE PARTIES INVOLVED.



GENERAL NOTES:

- 1. ALL WORK PRESENTED IN THESE DRAWINGS MUST BE COMPLETED BY THE CONTRACTOR UNLESS OTHERWISE SPECIFIED.
- 2. THE CONTRACTOR MUST HAVE A MINIMUM OF 5 YEARS OF EXPERIENCE IN TOWER ERECTION AND RETROFIT SIMILAR TO THAT DESCRIBED HEREIN.
- 3. ALL CONSTRUCTION IS TO BE COMPLETE IN ACCORDANCE WITH THE ANSI/ASSE A10.48 AND ANSI/TIA-322 STANDARDS. THE CONTRACTOR MUST HAVE CONSIDERABLE WORKING KNOWLEDGE IN THESE STANDARDS TO ACCEPT THIS WORK. BY ACCEPTING THIS PROJECT, THE CONTRACTOR IS ATTESTING THAT HE HAS SUFFICIENT EXPERIENCE, ABILITY, AND KNOWLEDGE OF THE WORK TO BE PERFORMED AND IS PROPERLY LICENSED AND REGISTERED TO COMPLETE THIS WORK.
- 4. THE CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFYING ALL DIMENSIONS, ELEVATIONS, AND EXISTING CONDITIONS PRIOR TO BEGINNING ANY MATERIAL ORDERS, FABRICATION OR CONSTRUCTION WORK ON THIS PROJECT. ANY DISCREPANCIES SHALL BE IMMEDIATELY BROUGHT TO THE ATTENTION OF THE EOR. THE DISCREPANCIES MUST BE RESOLVED BEFORE THE CONTRACTOR MAY PROCEED WITH THE PROJECT.
- 5. ANY WORK PERFORMED WITHOUT A PREFABRICATION MAPPING IS DONE AT THE RISK OF THE CONTRACTOR AND/OR FABRICATOR.
- 6. ALL MANUFACTURERS' INSTRUCTIONS FOR INSTALLATION MUST BE FOLLOWED EXACTLY AS SPECIFIED. WHEN CONFLICTING WITH THESE DRAWINGS. THE MANUFACTURER SPECIFICATIONS SHALL GOVERN.
- 7. ALL MATERIALS AND EQUIPMENT USED IN THE INSTALLATION OF THESE DRAWINGS SHALL BE IN NEW OR GOOD WORKING QUALITY, FREE FROM DEFECTS AND FAULTS AND IN CONFORMANCE WITH THE CONTRACT DOCUMENTS. ALL SUBSTITUTIONS MUST BE GIVEN WRITTEN APPROVAL FROM THE EOR PRIOR TO INSTALLATION. ALL MATERIALS SHALL BE WARRANTED FOR ONE YEAR FROM ACCEPTANCE DATE.
- 8. THE CONTRACTOR IS RESPONSIBLE FOR COORDINATING ALL INTENDED CONSTRUCTION ACTIVITY INCLUDING MATERIALS, ACCESS AND WORK SCHEDULE. THE CONTRACTOR IS RESPONSIBLE FOR OBTAINING ALL PERMITS AND WILL BE RESPONSIBLE FOR ABIDING BY ALL REQUIREMENTS AND CONDITIONS OF THE PERMITS. WHEN APPLICABLE, THE CONTRACTOR MUST NOTIFY THE APPLICABLE JURISDICTION PRIOR TO BEGINNING OF ANY CONSTRUCTION.
- 9. THE CONTRACTOR IS RESPONSIBLE FOR ALL CONSTRUCTION MEANS AND METHODS. INCLUDING BUT NOT LIMITED TO, ERECTION PLANS, RIGGING PLANS, CLIMBING PLANS, AND RESCUE PLANS.

 CONSTRUCTION OF THE PROPOSED WORK SHALL MEET ANSI/ASSE A10.48, OSHA, AND GENERAL INDUSTRY STANDARDS. ALL RIGGING PLANS SHALL ADHERE TO ANSI/TIA-322 INCLUDING THE REQUIRED INVOLVEMENT OF A QUALIFIED ENGINEER FOR CLASS IV CONSTRUCTION.

- 10. IT IS THE CONTRACTOR'S SOLE RESPONSIBILITY TO DETERMINE INSTALLATION PROCEDURE AND SEQUENCE TO INSURE THE SAFETY OF THE STRUCTURE AND ITS COMPONENTS DURING ERECTION AND/OR FIELD ALTERATIONS. THIS INCLUDES, BUT IS NOT LIMITED TO, THE ADDITION OF TEMPORARY BRACING, GUYS OR TIE-DOWNS THAT MAY BE NECESSARY; SUCH MATERIAL SHALL BE REMOVED AFTER THE COMPLETION OF THE PROJECT.
- 11. THE CONTRACTOR SHALL BE RESPONSIBLE FOR INITIATING, MAINTAINING, AND SUPERVISING ALL SAFETY PRECAUTIONS AND PROGRAMS IN CONNECTION WITH THIS PROJECT. THE CONTRACTOR IS RESPONSIBLE FOR ENSURING THAT THIS PROJECT AND RELATED WORK COMPLIES WITH ALL APPLICABLE LOCAL, STATE, AND FEDERAL SAFETY CODES AND REGULATIONS GOVERNING THIS WORK.
- 12. THE CLIMBING FACILITIES, SAFETY CLIMB AND ALL PARTS THEREOF SHALL NOT BE IMPEDED, MODIFIED OR ALTERED WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE EOR.
- 13. INCORRECTLY FABRICATED, DAMAGED, MIS-FITTING, OR NON-CONFORMING MATERIALS AND CONDITIONS SHALL BE REPORTED TO THE EOR PRIOR TO ANY REMEDIAL OR CORRECTING ACTION. ALL ACTIONS SHALL REQUIRE EOR APPROVAL.

STEEL:

- 1. THE FABRICATION AND ERECTION OF STRUCTURAL STEEL SHALL CONFORM TO THE LATEST AISC CODE AND ASTM SPECIFICATIONS.
- 2. HOLES SHALL NOT BE TORCH CUT THROUGH STRUCTURAL STEEL FOR FABRICATION. ALL STEEL FABRICATION MUST FOLLOW AISC SPECIFICATIONS.
- 3. HOT-DIP GALVANIZE ALL ITEMS AFTER FABRICATION IN COMPLIANCE WITH ASTM A-123 UNLESS OTHERWISE SPECIFIED. ALL NEW STEEL IS TO BE PAINTED TO MATCH THE EXISTING STEEL.
- 4. NEW STEEL MEMBERS MUST HAVE SINGLE DRILLED HOLES. SLOTTED AND DOUBLY DRILLED HOLES ARE NOT ACCEPTABLE MEANS OF FABRICATION UNLESS OTHERWISE SPECIFIED.
- 5. ALL CONNECTIONS NOT DETAILED IN THESE DRAWINGS MUST BE DETAILED BY THE STEEL FABRICATOR IN ACCORDANCE WITH THE LATEST AISC SPECIFICATIONS.
- 6. ALL BOLTED CONNECTIONS MUST BE INSTALLED TO A SNUG-TIGHTENED CONDITION PER AISC "SPECIFICATION FOR STRUCTURAL JOINTS USING ASTM 325 OR A490 BOLTS" SECTION 8.1 UNLESS OTHERWISE SPECIFIED.
- 7. CONTRACTOR MAY BE REQUIRED TO STACK WASHERS FOR BOLTS WHERE THREADS ARE EXCLUDED FROM SHEAR PLANE TO OBTAIN SNUG TIGHT INSTALLATION. A NUT LOCKING DEVICE MUST BE INSTALLED ON ALL PROPOSED AND/OR REPLACED BOLTS. GALVANIZED ASTM 325 OR A490 BOLTS SHALL NOT BE REUSED.

COLD GALVANIZATION:

- 1. ALL DAMAGED SURFACES SHALL BE REPAIRED WITH A COLD-GALVANIZING COATING CONFORMING TO ASTM 780. THIS COATING SHALL BE APPLIED BY BRUSH. THE GALVANIZING COMPOUND SHALL CONTAIN A MINIMUM OF 95% ± PURE ZINC. THE FINISHED COATING SHALL BE A MINIMUM THICKNESS OF 4 MILS.
- 2. CONTRACTOR TO USE ZINGA OR ZRC COLD GALVANIZATION COMPOUNDS OR APPROVED EQUIVALENTS.
- 3. CLEAN AREAS TO BE PREPARED AND REMOVE SLAG FROM WELDS FOR TREATMENT ACCORDING TO MANUFACTURER'S RECOMMENDATIONS.
- 4. IF THE TOWER IS PAINTED, ALL TREATED AREAS ARE TO BE BRUSH PAINTED TO MATCH THE TOWER AFTER COLD GALVANIZING COMPOUND IS ALLOWED TO CURE.


U-BOLTS:

- 1. ALL U-BOLTS ARE TO BE ASTM A36/A307, SAE 429 GR. 2 UNLESS OTHERWISE SPECIFIED.
- 2. U-BOLTS SHALL MEET REQUIREMENTS OF ASME B18.31.5-2011 BENT BOLTS.
- 3. U-BOLT ASSEMBLY SHALL COME COMPLETE WITH NUTS (ASTM A563), WASHERS (ASTM F436), AND LOCK WASHERS.
- 4. FULL U-BOLT ASSEMBLY TO BE HOT-DIP GALVANIZED PER ASTM A153/A153M OR A123, AS APPLICABLE.


NOTES:

- 1. APPURTENANCES MAY INTERFERE WITH PROPOSED MODIFICATIONS.
- 2. ALL MODIFICATIONS TO BE INSTALLED CONTINUOUSLY THROUGH EXISTING EQUIPMENT. ALL EXISTING EQUIPMENT MUST NOT BE DAMAGED OR TAKEN OFF AIR DURING INSTALLATION OF PROPOSED MODIFICATIONS.
- 3. ANTENNA AND COAX NOT SHOWN FOR CLARITY. SEE STRUCTURAL ANALYSIS REPORT FOR EXISTING ANTENNA LOADING AND COAX CONFIGURATION.
- 4. PRIOR TO FABRICATION AND INSTALLATION, CONTRACTOR SHALL FIELD VERIFY ALL LENGTHS AND QUANTITIES GIVEN. INFORMATION PROVIDED IS FOR QUOTING PURPOSES ONLY, AND SHALL NOT BE USED FOR FABRICATION.
- 5. EXISTING RRU'S AND ANCILLARY EQUIPMENT MAY NEED TO BE TEMPORARILY RELOCATED AS NECESSARY TO COMPLETE THIS MODIFICATION. EQUIPMENT IS NOT TO BE TAKEN OFF AIR AT ANY TIME DURING INSTALLATION. PLEASE CONTACT EOR IF THIS CANNOT BE MET.
- 6. CONTACT EOR IF PROPOSED MOUNT REINFORCEMENT DIMENSIONS CANNOT BE MET.


MODIFICATION MATERIALS **ULTIMATE STRENGTH (Fu)** SCOPE **YIELD STRENGTH (Fy)** SHAPE GRADE **PIPE** A53 GR. B 60 KSI ALL 35 KSI ALL **U-BOLT** SAE J429 GR. 2 57 KSI 74 KSI



MODIFICATION SCHEDULE						
SCOPE NO.	MODIFICATION DESCRIPTION	BOTTOM ELEVATION	TOP ELEVATION	SHEET NO.		
1	INSTALLATION OF NEW PLATFORM BEAMS	_	117'-0" ±	S-2 TO S-4		
2	INSTALLATION OF NEW PLATFORM BRACINGS	_	117'-0" ±	S-2 TO S-4		
3	INSTALLATION OF NEW PLATFORM SUPPORTS	_	117'-0" ±	S-2 TO S-4		










NOTES:


- CONTRACTOR TO FIELD VERIFY THE REQUIRED LENGTH OF THE NEW PIPES MAY CUT ENDS AS REQUIRED TO AVOID UNNECESSARY OVERHANG AND OVERLAP.
- 2. TWO COATS OF COLD GALVANIZING COATING MUST BE APPLIED TO ALL CUT ENDS IN ACCORDANCE TO ASTM A780 PRIOR TO INSTALLATION.

PLATFORM BILL OF MATERIAL				
MARK	QUANTITY	DESCRIPTION		
(WF)	3	PLATFORM WIDE FLANGE, W12X26		
(CS)	2	PLATFORM BRACING, C8 X 11.5		
(HSS)	2	PLATFORM VERTICAL SUPPORT, HSS6X6X3/8		
(CP)	2	CAP PLATE, 14" X 10" X 1/2"		
(AP)	2	ANCHOR PLATE, 14" X 10" X 1/2"		
(GP)	4	GUSSET PLATE, 4" X 6" X 3/8"		
	24	CONNECTION BOLTS, 3/4"Ø A325 W/ NUT-LKW EA.		
2018444	8	HILTI HIT-Z 1/2 (ELEMENT)		
2334276	8	HILTI HIT-HY200 V3 (ADHESIVE)		
MAT18	5	RUBBER MATS, SITE PRO 1 1/2" X 18" X 48"		












CAP PLATE DETAIL




ADAOPHEIRA PEADTETTALL TAIL











B-B LADDER SECTION VIEW
S-5 NTS














TOL	.ER	AN	CE	N	OT	ES
-----	-----	----	----	---	----	----

TOLERANCES ON DIMENSIONS, UNLESS OTHERWISE NOTED ARE: SAWED, SHEARED AND GAS CUT EDGES $(\pm 0.030")$ DRILLED AND GAS CUT HOLES $(\pm 0.030")$ - NO CONING OF HOLES LASER CUT EDGES AND HOLES $(\pm 0.010")$ - NO CONING OF HOLES BENDS ARE $\pm 1/2$ DEGREE ALL OTHER MACHINING $(\pm 0.030")$

ALL OTHER MACHINING (± 0.030")
ALL OTHER ASSEMBLY (± 0.060")

PROPRIETARY NOTE:
THE DATA AND TECHNIQUES CONTAINED IN THIS DRAWING ARE PROPRIETARY INFORMATION OF VALMONT INDUSTRIES AND CONSIDERED A TRADE SECRET. ANY USE OR DISCLOSURE WITHOUT THE CONSENT OF VALMONT INDUSTRIES IS STRICTLY PROHIBITED.

DESCRIPTION

3' STAND-OFF ANTENNA WAL MOUNT



Engineering Support Team: 1-888-753-7446


Locations:
New York, NY
Atlanta, GA
Los Angeles, CA
Plymouth, IN
Salem, OR
Dallas, TX

A valmont ♥ COMBANY



U-bolts

A **valmont T** COMPANY





Features: Includes nuts, locks, and flat washers, long thread lengths. Hot-dip galvanized.

Construction: SAE J429 Gr. 2. Coarse threads.

Design Criteria: Conforms to the minimum requirements as stated in SAE J429 (Latest Revision) Grade 2 Stud, Rolled or Cut CNC threads. SAE J429 Grade 2 (Yield Fy = 57 ksi / Tensile Fu = 74 ksi). All finished goods are Hot Dip Galvanized in accordance with ASTM A123 requirements.

Part #	Diameter (D)	Width (W)	Length (L)	Thread (T)	Weight
UB3200	3/8"	2"	3"	1-1/4"	0.40 lb.
UB3212	3/8"	2-1/2"	3-5/8"	1-3/4"	0.45 lb.
UB3300	3/8"	3"	4-1/4"	2"	0.50 lb.
UB3312	3/8"	3-1/2"	4-3/4"	2"	0.50 lb.
UB3418	3/8"	4"	5-3/4"	2-1/2"	0.60 lb.
UB1400	1/2"	2"	4"	2"	0.65 lb.
UB1212	1/2"	2-1/2"	4-1/2"	2"	0.65 lb.
UB1300	1/2"	3"	5"	2"	0.70 lb.
UB1358	1/2"	3-5/8"	5-1/2"	3"	0.75 lb.
UB1306	1/2"	3-5/8"	<mark>6"</mark>	3"	0.80 lb.
UB1418	1/2"	4-1/8"	6"	3"	0.90 lb.
UB1458	1/2"	4-5/8"	7"	3"	0.90 lb.
UB5258	5/8"	2-5/8"	4-1/2"	2"	1.20 lb.
UB5358	5/8"	3-5/8"	6"	3"	1.45 lb.
UB5458	5/8"	4-5/8"	7"	3"	1.60 lb.



