ATTACHMENT 4 RURAL SETBACK STANDARDS

Zoning	Minimum Setbacks (ft) ^(b)								Minimum	Maximum Build	
District	Principal Residential Building				Detached		Hard or Gravel		Principal	Principal , Building	
	including Attached Garage				Accessory		Surface ^(d)		Building		
					Building ^(a)				Separation		
	Front ^(a)	Street	Interior	Rear	Interior	Rear	Interior	Front	(ft)	Feet	Floors
		Side ^(a)	Side	1 '	Side ^(c)	1 '	Side or	or	1	1 '	
		<u> </u>		<u> </u>		<u> </u>	Rear	Street ^(a)		<u> </u>	
AR	50	30	20	40	12	12	0	0	10	35	2.5
RR-5	50	30	20	25	12	12	6	10	15	35	2.5
RR-2	50	30	20	25	12	12	6	10	15	35	2.5
PR	30	30	12	20	12	12	6	10	30	35	2.5
SF	50	25	12	12	5	5	6	10	20	35	2.5
2F(e)	30	30	8	12	5	5	6	10	20	35	2.5
MF(f)	30	30	8	12	5	5	6	10	20	40	3
MH	20(g)	20(g)	8	12	5	5	6	10	10	20	1

Figure V(2): Rural, Open Space and Residential District Setback and Height Standards

NOTES:

- (a) See section 520-27.B for standards related to detached accessory buildings located within front yard areas, minimum separation requirements associated with detached accessory buildings, and other standards associated with detached accessory structures.
- (b) Additional setbacks may be required along zoning district boundaries for buffer yards, if required for the particular land use under article IV or section 520-79.C(4).
- (c) Minimum streetside yard setbacks are equal to the minimum streetside setback for the principal structure.
- (d) Includes all gravel and hard surfaces as defined in section 520-138, along with recreational vehicles. This setback excludes intrusions required for driveway entrances and permitted or required for crossaccess driveways and pedestrian ways; shared driveways; and shared parking lots.
- (e) Single-family detached residences shall comply with the requirements for the SF District. <u>No interior</u> <u>side yard setbacks for zero lot line structures.</u>
- (f) Single-family detached residences shall comply with the requirements of the SF District. Two-family residences shall comply with the requirements for the 2F District.
- (g) A minimum one-hundred-foot-wide buffer must be provided around the perimeter of each mobile home community.

(Ord. No. 16-07, 6-20-2016)

Created: 2025-01-15 08:34:41 [EST]