457 **EXHIBIT G** 458 459 460 Chapter 23 461 462 LAND DEVELOPMENT REGULATIONS ARTICLE 6 "ENVIRONMENTAL 463 464 **REGULATIONS**" 465 466 Sec. 23.6-1. - Landscape regulations. 467 Landscape design standards. The following are the minimum standards for the 468 design and installation of all landscaping within the City of Lake Worth Beach: 469 470 471 472 473 (15) Artificial turf. 474 a. All installation of artificial turf shall require a landscape permit. The use and location of artificial turf shall be limited to the following: 475 476 (1) Single family and duplex properties in the rear yard only and not visible from the right of way. 477 478 (2) Between parking strips in the front yard of non-conforming properties 479 previously constructed with off-street parking utilizing sixty percent (60%) or 480 more of the width of the front yard. This application of artificial turf shall be approved by the Development Review Official or applicable review board, 481 which shall review the proposed application for consistency with the City's 482 land development regulations, visual appropriateness, enhanced site design 483 and appearance, and improved drainage. Properties located in historic 484 districts will require a Certificate of Appropriateness from the HRPB. 485 (3) On roof top terraces. 486 (4) As part of a planned development in a recreation or amenity area. 487 b. In all areas of installation, artificial turf shall be treated as a semi-pervious 488 489 surface. The quantity of artificial turf to be incorporated into a project shall be limited by the maximum percentage of impervious surface for the subject 490 property within the applicable zoning district. 491 c. Artificial turf shall not be installed: 492 (1) as part of any landscape buffer or landscape area required by this article; 493 494 (2) within permanent drainage features (e.g., ponds, swales); or 495 (3) in any public right of way. d. Minimum material standards. All artificial turf shall comply with each of the 496 following minimum standards: 497 498 (1) Artificial turf shall consist of green lifelike individual blades of grass that 499 emulate natural turf in look and color and shall have a minimum pile height of

540

500 501	9	one- and one-half inches and shall have a minimum tufted weight of 80 ounces per square yard.
502 503	<u>(2)</u>	Artificial turf installations shall have a minimum permeability of 30 inches per hour per square yard.
504 505	<u>(3)</u>	All artificial turf shall have a minimum ten-year manufacturer's warranty that protects against color fading and a decrease in pile height.
506 507	<u>(4)</u>	Artificial turf shall be lead free and be partially or wholly manufactured from recyclable materials.
508 509 510 511 512	<u>(5)</u>	All materials must include test documentation which declares that the artificial turf yarn and backing materials are disposable under normal conditions, at any U.S. landfill station (Total Content Leach Protocol (TCLP) test). Documentation must also be provided that identifies all components that are recyclable and all components that consist of recycled material.
513 514	<u>(6)</u>	The use of indoor or outdoor plastic or nylon carpeting as a replacement for artificial turf or natural turf shall be prohibited.
515 516 517 518	<u>(7)</u>	The artificial turf system shall utilize organic plant-derived and other natural infill components, including, but not limited to, cork, coconut, corn husk, rice husk, and sand. The use of crumb rubber and other synthetic materials shall be prohibited in all applications except for sports fields.
519 520	<u>(8)</u>	Artificial Turf shall not be treated as a fill in material, but rather as a planned element of the site or yard outside of required landscape areas and buffers
521	<u>e. Inst</u>	allation, maintenance and repair.
522 523	<u>(1)</u>	All artificial turf shall, at a minimum, be installed according to the manufacturer's specifications.
524 525	(2)	All artificial turf installations shall be anchored to ensure that the turf will withstand the effects of wind.
526 527	(3)	All seams shall be secured and edges shall be trimmed to fit against all regular and irregular edges to resemble a natural look.
528 529 530 531	<u>(4)</u>	If artificial turf is planned to be installed immediately adjacent to a seawall, the artificial turf shall be pinned or staked behind the seawall. No artificial turf or installation mechanism shall be attached directly to or placed on a seawall or seawall cap.
532 533 534 535 536	<u>(5)</u>	All artificial turf shall be installed over a subgrade prepared to provide positive drainage and an evenly graded mass of compacted, porous crushed rock aggregate material. Base comprising of sand only is not permitted. Proper drainage shall be provided for all Artificial Turf installations to prevent runoff or pooling of water.
537 538	<u>(6)</u>	Artificial turf shall be visually level, with the grain pointing in a single direction.
539 540	<u>(7)</u>	An appropriate solid barrier device (e.g., concrete mow strip, bender board or other barrier with a minimum of 38" thickness) is required to separate

Pg. 15, Ord. 2020-15 541 artificial turf from soil and live vegetation and to prevent intrusion of living 542 plant material. Artificial turf shall not be installed directly against the trunk of trees and/or 543 (8) 544 palms. A 3-foot mulch bed measured from the base of the tree or palm must 545 be maintained around all tress and or palms. Precautions for installation 546 around existing trees shall be monitored and may be restricted to ensure 547 tree roots are not damaged with the installation of the base material and that the overall health of the tree will not be compromised. 548 549 All artificial turf shall be maintained in a green fadeless condition and shall 550 be maintained free of dirt, mud, stains, weeds, debris, tears, holes, and impressions. Maintenance shall include, but not be limited to cleaning, 551 brushing, debris removal; repairing of depressions and ruts to maintain a 552 553 visually-level surface; elimination of any odors, flat or matted areas, weeds, 554 and invasive roots; and all edges of the artificial turf shall not be loose and 555 must be maintained with appropriate edging or stakes. There shall be no parking on artificial turf. 556 (10)557 Artificial turf shall not be visible from public rights-of-way except where it is installed between parking strips or approved as part of a planned 558 559 development. 560 (12) All other landscape requirements must be meet. 561 Applicants shall provide an owner affidavit agreeing to perpetually maintain 562 the artificial turf system in good working order to ensure that there is 563 continued permeability. If the artificial turf falls into disrepair with fading or holes or loose areas. The replacement and/or repairs shall be done with like 564 565 for like materials from the same manufacturer and done so in a manner that 566 results in a repair that blends in with the existing artificial turf. 567 f. A landscape permit shall be obtained from the City prior to the installation of any artificial turf. The permit application shall include the following material 568 569 specifications and plans. (1) A landscape plan showing the area of synthetic turf, area of living plant 570 material, and separation between these areas; 571 572 (2) A dimensioned cross section of proposed materials and installation details, including subgrade, drainage, base or leveling layer, and infill: 573 574 (3) Edge material and detail for seams: 575 (4) Material description and specifications, including manufacturer, (5) Installer (with contact information), and warranty information. 576 577 (6) A sample of the artificial turf proposed that meets these standards. 578 (7) Product specifications that demonstrate compliance the requirements for 579 artificial turf in this article and the ability to be warrantied in the United States 580 of America.

(8) The plan shall demonstrate conformance with the City's landscape

581

582

requirements.

Pg. 16, Ord. 2020-15

583 g. Inspections. An in-progress inspection shall be required to ensure that the

appropriate base material has been installed in accordance to the

manufactures' specifications. A final inspection shall also be required.