

APPROVAL/REVIEW:

DRAWINGS, ETC.

LICENSE NUMBER

CALGREEN 4.408.2

WINDOW/DOOR PACKAGE

MECHANICAL DUCTING PLAN

MISC. STEEL SHOP DRAWINGS

STAIR AND RAIL SHOP DRAWINGS

LOT COVERAGE: LAND AREA COVERED BY ALL STRUCTURES THAT ARE OVER 6 FEET IN HEIGHT

MEASURED TO THE OUTSIDE SURFACES OF EXTERIOR WALLS

Patrick Way

ASSESSOR'S PARCEL MAP

HACIENDA WAY PETER SWALL TRACT

SQUARE FOOTAGE BREAKDOWN

Maximum lot coverage: 30% for site with two-story structures pursuant to LAMC Section 14.06.060.C

ARCHITECTURE

1000 S Winchester Blvd San Jose, CA 95128 P: (408) 998 - 0983

Kielty Arborist Services attn Kevin Kielty email kkarbor0476@yahoo.com

CIVIL ENGINEER **WEC & Associates** attn Ed Wu email ed@weceng.com

ARBORIS

AR1.0-1

C.2

LANDSCAPE

REQ'D CONTRACTOR

SUBMITTALS TO ARCHITECT

NOTE: SEE STRUCTURAL PLANS FOR ADDITIONAL REQUIRED SUBMITTALS FOR SHOP

REQ'D CONTRACTOR SUBMITTALS TO BUILDING

DEPT. PRIOR TO PERMIT ISSUANCE

CONSTRUCTION WASTE MANAGEMENT PLAN IN ACCORDANCE WITH

APPLICABLE CODES

THE FOLLOWING ARE REQUIRED TO BE SUBMITTED TO THE ARCHITECT FOR

CABINET SHOP DRAWINGS AND FINISH SAMPLES

INSURANCE AND WORKER'S COMP POLICIES

APPLICABLE CODES (with Los Altos Amendments)

CONSTRUCTION STAGING PLAN

-2019 CALIFORNIA ADMINISTRATIVE CODE, CAC -2019 CALIFORNIA BUILDING CODE, CBC

-2019 CALIFORNIA ELECTRICAL CODE, CEC -2019 CALIFORNIA MECHANICAL CODE, CMC

-2019 CALIFORNIA PLUMBING CODE, CPC

-2019 CALIFORNIA EXISTING BUILDING CODE -2019 CALIFORNIA GREEN BUILDING STANDARDS -2019 CALIFORNIA REFERENCED STANDARDS

-2019 CALIFORNIA ENERGY CODE, CEnC -2019 CALIFORNIA HISTORICAL CODE, CHC

-2019 CALIFORNIA FIRE CODE, CFC

-2019 CALIFORNIA RESIDENTIAL BUILDING CODE, CRC

ARBORIST REPORT

TOPO SURVEY

LANDSCAPE PLAN

IRRIGATION PLAN

DETAILS

GRADING & DRAINAGE PLAN

LANDSCAPE LEGEND & NOTES PLAN


IRRIGATION LEGEND & NOTES PLAN


EROSION CONTROL PLAN

GEOTECHNICAL ENGINEER Romig Engineers, Inc. attn Lucas Ottoboni ph 650 591 5224 email lucas@romigengineers.com

LANDSCAPE ARCHITECT Studio S Squared Architecture, Inc. 1000 S Winchester Blvd San Jose, CA 95128 attn Greg Ing email greg@studios2arch.com

COVER SHEET










Residence Way 540 Patrick

narng-Chow Altos, Los





FLOOR AREA CALCULATION









Residence


Los Altos, 540 Patrick Way




-	<u>-</u>		
PROJECT NO.			21-020
REVISION	DATE	DESCRIPTION	DRAWN BY
	01.31.2021	PLANNING PERMIT SUBMITTAL	AA/IG
	04.05.2022	P. PACKAGE RESUBMITTAL	AA/IG
2	07.06.2022	P. PACKAGE RESUBMITTAL	IG/AD

DAYLIGHT PLANE









530 PATRICK









491 PATRICK



521 PATRICK





500 PATRICK












490 PATRICK


STREETSCAPE ELEVATION 1/8" 2





NEIGHBORHOOD CONTEXT







SSIGENCE
IDENCE
CK Way

NEW SINGLE FAMILY RESIDENCE
Los Altos, 540 Patrick Way

SEO ARCHITECTOR A

DATE DESCRIPTION


01.31.2022 PLANNING PERMIT SUBMITTAL AA/IG

04.05.2022 P. PACKAGE RESUBMITTAL JB


07.06.2022 P. PACKAGE RESUBMITTAL IG/AD

SITE PLAN

DEMO SITE PLAN



© STUDIO S SQUARED ARCHITECTURE, INC.





Charng-Chow Residence

New SINGLE FAMILY RESIDENCE
Los Altos, 540 Patrick Way



PROJECT NO.

REVISION DATE DESCRIPTION


O1.31.2022 PLANNING PERMIT SUBMITTAL AA/IG


1 04.05.2022 P. PACKAGE RESUBMITTAL JB

2 07.06.2022 P. PACKAGE RESUBMITTAL IG/AD

1ST

FLOOR PLAN







Charng-Chow Residence

NEW SINGLE FAMILY RESIDENCE
Los Altos, 540 Patrick Way

PCKMIN REVIEW

21-020

SVISION DATE DESCRIPTION


01.31.2022 PLANNING PERMIT SUBMITTAL AA/IG

1 04.05.2022 P. PACKAGE RESUBMITTAL JB


2 07.06.2022 P. PACKAGE RESUBMITTAL IG/AD

2ND

FLOOR PLAN



© STUDIO S SQUARED ARCHITECTURE, IN




STUDIO S SQUARED
ARCHITECTURE


1000 S Winchester Blvd San Jose, CA 95128 P: (408) 998 - 0983

Charng-Chow Residenc Los Altos, 540 Patrick Way

LOWER

ROOF PLAN









/ Residence

540 Patrick Way Los Altos, 3

UPPER

ROOF PLAN







P : (408) 998 - (

G-Chow Residence AMILY RESIDENCE AND A NEW DETACH ACCESSORY DWELLING UNIT

SED ARCHITECTURE C27,719 EN ★ 12-31-23 50 ★ OF CALIFORN

Description

Description

Description

Description

Description

Description

AA/IG

AA/IG

DESCRIPTION


DESCRIPTION


AA/IG

DESCRIPTION

DESCRIPTIO

EXTERIOR ELEVATIONS







1 . (400) 778 - 0

SINGLE FAMILY RESIDENCE AND A NEW DETACHE
ACCESSORY DWELLING UNIT

 PROJECT NO.
 21-020


 REVISION
 DATE
 DESCRIPTION
 DRAWN BY


 01.31.2021
 PLANNING PERMIT SUBMITTAL
 AA/IG

 1
 04.05.2022
 P. PACKAGE RESUBMITTAL
 AA/IG

 2
 07.06.2022
 P. PACKAGE RESUBMITTAL
 IG/AD

EXTERIOR ELEVATIONS







1 . (400) 770 - 0

19-Chow Residence Family residence and a new detacher Accessory dwelling unit

Los Altos, 540 Patri


 PROJECT NO.
 DATE
 DESCRIPTION
 DRAWN BY

 01.31.2021
 PLANNING PERMIT SUBMITTAL
 AA/IG

 1
 04.05.2022
 P. PACKAGE RESUBMITTAL
 AA/IG

 2
 07.06.2022
 P. PACKAGE RESUBMITTAL
 IG/AD

EXTERIOR ELEVATIONS



© STUDIO S SQUARED ARCHITECTURE, INC.






PERSPECTIVE EXTERIOR FRONT LEFT

PERSPECTIVE EXTERIOR REAR RIGHT

EXTERIOR PERSPECTIVES



PERSPECTIVE EXTERIOR FRONT RIGHT 5


PERSPECTIVE EXTERIOR BACKYARD

PERSPECTIVE EXTERIOR REAR LEFT

Los Altos, 540 Patrick Way


CONSTRUCTION





1000 S. Winchester Blvd

EXTERIOR PERSPECTIVES



PERSPECTIVE EXTERIOR BACKYARD LEFT

5


PERSPECTIVE EXTERIOR RIGHT

PERSPECTIVE EXTERIOR BACKYARD HIGH -


PERSPECTIVE EXTERIOR BACKYARD HIGH


PERSPECTIVE EXTERIOR BACKYARD RIGHT

PERSPECTIVE EXTERIOR BACKYARD



530 PATRICK WAY









R PERMIT APROV	DRAWN BY	AA/IG	AA/IG	IG/AD		
<u>م</u> /						
∠]		МПТАГ	.AL	Je.		
		PLANNING PERMIT SUBMITTAL	P. PACKAGE RESUBMITTAL	P. PACKAGE RESUBMITTAL		
R	NOIL	ING PER	KAGE RI	KAGE RI		
ЬЕ	DESCRIPTION	PLANN	P. PAC	P. PAC		
~		2021	2022	2022		
		2	12	12		

-	<u>`</u>)
ROJECT NO.			21
REVISION	DATE	DESCRIPTION	DRAWN BY
	01.31.2021	PLANNING PERMIT SUBMITTAL	AA/IG
	04.05.2022	P. PACKAGE RESUBMITTAL	AA/IG
2	07.06.2022	P. PACKAGE RESUBMITTAL	IG/AD

STUDIO S SQUARED

1000 S. Winchester Blvd


Charng-Chow Residence

NEW SINGLE FAMILY RESIDENCE AND A NEW DETACHED

ACCESSORY DWELLING UNIT

Los Altos, 540 Patrick Way

DATE	01.31.2021	04.05.2022	07.06.2023				
REVISION			2				
SECOND STORY							



SECOND STORY VIEWS FROM SUBJECT PROPERTY - NIEGHBOR (550 PATRICK WAY) -


master br

SECOND STORY FLOOR PLAN

550 PATRICK WAY 540 PATRICK WAY SUBJECT PROPERTY

STREETSCAPE ELEVATION | 1/8" | 3


1 2






1000 S. Winchester Blvd

Residence E AND A NEW DETACHED ELLING UNIT



PROJECT NO.			
REVISION	DATE	DESCRIPTION	DRAWN B
	01.31.2021	PLANNING PERMIT SUBMITTAL	AA/IG
	04.05.2022	P. PACKAGE RESUBMITTAL	AA/IG
2	07.06.2022	P. PACKAGE RESUBMITTAL	IG/AD

SECTIONS



Kielty Arborist Services LLC Certified Arborist WE#0476A TRAQ Qualified P.O. Box 6187 San Mateo, CA 94403

650- 532-4418 August 17th, 2021, Revised May 9th, 2022

Alvin Chow & Ann Charng,

Site: 540 Patrick Way, Los Altos CA

Dear Alvin Chow & Ann Charng,

As requested on Monday, July 26th, 2021, I visited the above site for the purpose of inspecting and commenting on the trees. A new 2 story home is proposed for the property, and as required by the City of Los Altos, a survey of the trees and a tree protection plan will be provided within this report. The entire 23-page building plan set dated 4/5/22 was reviewed for writing this report. This report will go over the existing health of the protected trees and give recommendations for construction as needed.

Method:

The significant trees on this site were located on a map provided by you. Each tree was given an identification number. This number can be found on the provided tree location map seen on page 3 of this report. The trees were then measured for diameter at 48 inches above ground level (DBH or diameter at breast height). Each tree was put into a health class using the following rating system:

- F- Very PoorD- Poor
- C- Fair
- B- GoodA- Excellent

The height of each tree was estimated, and the spread was paced off. Lastly, a comments section is provided.

Survey Key:

DBH-Diameter at breast height (54" above grade)
CON- Condition rating (1-100)
HT/SP- Tree height/ canopy spread
*indicates neighbor's trees
P-Indicates protected tree by city ordinance

R-Indicates proposed removal

540 Patrick



Protected tree—Magnolia tree #2 is in poor condition. The tree has been topped in the past and the poor pruning practices have likely led to the tree's decline. Areas of dead wood and die back were observed. The tree is also under severe drought stress. This tree is recommended for removal as it is in decline and likely to be further impacted by the proposed construction. No mitigation measures within ANSI A300 Pruning Standards are expected to improve the tree's condition rating.

Showing Magnolia tree #2

Mayten tree #8, and pittosporum trees #9, 14, and 15 are proposed for removal to facilitate the construction of the proposed landscape. These trees are in fair condition. These trees are not of a protected size in the city of Los Altos.



Trees to be retained:

Neighboring Privet tree #3 is in fair condition. A limited visual assessment was conducted. The tree is located 1 foot from the property line. Neighboring Spanish Dagger tree #4 is in poor condition. Large areas of dead wood were observed. This tree is not expected to improve. Both neighboring trees #3 and #4 are not of a protected size in the city of Los Altos.

Showing trees #3 and #4

540 Patrick

Survey:
Tree# Species

DBH CON HT/SPComments

1R Crape myrtle 8.4 B 20/15 Good vigor, good form. (Lagerstroemia sp.)

(2)

2P/R Magnolia 20.5 I (Magnolia grandiflora)

(Pittosporum eugenioides)

20.5 D 30/20 Fair to poor vigor, poor form, topped in past, drought stressed, abundance of dead wood, in decline.

Privet 8-8est C 30/20 Fair vigor, fair form, limited visual assessment, 1 foot from property line.

Spanish dagger (Yucca gloriosa) 12est F 25/12 Poor vigor, fair form, limited visual assessment, abundance of dead wood.

5 Pittosporum 4"x6 C 12/12 Fair vigor, poor form, multi leader at grade. (Pittosporum undulatum)

6* Red flowering gum 12est C 35/20 Fair vigor, fair form, limited visual

(Eucalyptus ficifolia) assessment, 5 feet from property line.

7* Pittosporum 8-8est D 30/15 Fair to poor vigor, poor form, in decline.

8R Mayten 4.5 C 12/10 Fair vigor, fair form, minor dead wood. (Maytenus boaria)

9R Pittosporum 5.0 C 30/15 Fair vigor, fair form, screening material. (Pittosporum eugenioides)

10*P Redwood 48est B 90/30 Fair vigor, good form, thinned out in past. (Sequoia sempervirens)

11*P Redwood 30est B 90/30 Fair vigor, good form, thinned out in past. (Sequoia sempervirens)

12 Strawberry tree 9.0 B 12/12 Fair vigor, fair form. (Arbutus unedo)

13* Plum 12est D 14/14 Fair to poor vigor, poor form, mature, decay on trunk abundance of dead wood, 4 feet from property line.

14R Pittosporum 3.0 C 12/6 Fair vigor, fair form, hedge material. (Pittosporum eugenioides)

540 Patrick

Pittosporum tree #5 is in fair condition. The tree acts as a large screen at the back of the property. Many other small Pittosporum trees were observed at the back property fence line. These trees were all under 4" in diameter and not surveyed as a part of this report. The Pittosporum trees together create a nice dense screen at the back of the property. Pittosporum tree #5 is not of a protected size in the city of Los Altos.



Neighboring Red Flowering Gum Eucalyptus tree #6 is in fair condition. A limited visual assessment was conducted. The tree is located 5 feet from the property line fence. This tree is not of a protected size in the city of Los Altos.

Neighboring Pittosporum tree #7 is in poor condition. The tree is showing signs of decline through large areas of deadwood and die back observed within the canopy. This tree is not expected to improve. Root rot is likely the culprit of the observed decline. This tree is not of a protected size in the city of Los Altos.

Showing tree #7

Strawberry tree #12 is in fair condition. This tree is not of a protected size in the city of Los Altos. Neighboring plum tree #13 is in poor condition. The tree is overmature for the species. Large areas of dead wood and decline were observed. Decay on the trunk was observed. The tree is located 4 feet from the property line. This tree is not of a protected size in the city of Los Altos.




<u>Protected trees-</u> Neighboring Redwood trees #10 and #11 are in good condition. Both trees have been thinned out in the past to reduce wind sail. These trees are well placed far back on the neighboring lot. These trees are protected in the city of Los Altos.

Showing Redwood trees #10 and #11

540 Patrick

atrick (3)

Tree#SpeciesDBHCONHT/SP Comments15RPittosporum3.0C12/6Fair vigor, fair form, hedge material.(Pittosporum eugenioides)





Site observations:

The existing landscape is in fair condition. The site is flat, and irrigation is currently being provided for the trees and shrubs on the site. Four out of the fifteen trees surveyed are in poor condition.

Trees proposed for removal:

Crape myrtle tree #1 is in good condition and is not of a protected size in the city of Los Altos. The tree is located close to the existing home on site. This tree is proposed for removal as the new home is within the tree's footprint.

Showing Crape Myrtle tree #1


540 Patrick

Impacts/recommendations:

No impacts are expected for the retained trees. It is recommended to install tree protection fencing at the driplines where possible to reduce risk of compacting soil within the tree root zones. Irrigation every 2 weeks during the dry season is recommended to be provided within the tree protection zones for the trees. 20 gallons water is recommended within the tree protection zones. The tree protection zone for the neighboring Redwood trees is recommended to be irrigated using 50 gallons of water every 2 weeks.

Tree Protection Plan:

Tree Protection Zones Tree protection zones should be installed and maintained throughout the entire length of the project. Prior to the commencement of any Development Project, a chain link fence shall be installed at the drip line(canopy spread) of any protected tree which will or will not be affected by the construction. Non-protected trees to be retained shall also be protected in the same way. The drip line shall not be altered in any way so as to increase the encroachment of the construction. When work is to take place underneath a trees dripline, fencing must be placed as close as possible to the tree proposed work. If an area of access is needed underneath a trees canopy, the area shall be protected by a landscape barrier. Fencing for the protection zones should be 6-foot-tall metal chain link type supported my 2 inch metal poles pounded into the ground by no less than 2 feet. The support poles should be spaced no more than 10 feet apart on center. Signs should be placed on fencing signifying "Tree Protection Zone - Keep Out". No materials or equipment should be stored or cleaned inside the tree protection zones. Excavation, grading, soil deposits, drainage and leveling is prohibited within the tree protection zones without the project arborist consent. No wires, signs or ropes shall be attached to the protected trees on site. Utility services and irrigation lines shall all be place outside of the tree protection zones when possible. When access is needed and tree protection fencing restricts access a landscape barrier shall be installed to protected the



Red lines showing the recommended tree protection fencing locations

STUDIO S SQUARED
ARCHITECTURE

1000 S Winchester Blvd San Jose, CA 95128 P: (408) 998 - 0983

P: (408) 998 - 0983

Chow Residence
NEW SINGLE FAMILY RESIDENCE
Los Altos, 540 Patrick Way

SZO

ARCHITEC ARCHITEC A SAKAI, 4 FC SAKAI, 4

PERMIT REVIEW

DESCRIPTION

2021 PLANNING PERMIT SUBMITTAL

AA/IG

2022 P. PACKAGE RESUBMITTAL

AA/IG

AA/IG


AA/IG

IG/AD

| DESCRIPTIC | DESCRIPTIC | DESCRIPTIC | O1.31.2021 | PLANNIN | O4.05.2022 | P. PACKA | O7.06.2022 | O7.06.2022 | P. PACKA | O7.06.2022 |

ARBORIST

REPORT



© STUDIO S SQUARED ARCHITECTURE, INC.

(7)

Landscape Barrier zone

If for any reason a smaller tree protection zone is needed for access, a landscape buffer consisting of wood chips spread to a depth of six inches with plywood or steel plates placed on top will be placed where tree protection fencing is required. The landscape buffer will help to reduce compaction to the unprotected root zone.

Inspections

The site arborist will need to verify that tree protection fencing has been installed before the start of construction. The site arborist must inspect the site anytime excavation work is to take place underneath a protected trees dripline. It is the contractor's responsibility to contact the site arborist if excavation work is to take place underneath the protected trees on site. Kielty Arborist Services can be reached at kkarbor0476@yahoo.com or by phone at (650) 515-9783 (Kevin), or (650) 532-4418 (David).

Root Cutting and Grading

If for any reason roots are to be cut, they shall be monitored and documented. Large roots (over 2" diameter) or large masses of roots to be cut must be inspected by the site arborist. The site arborist, at this time, may recommend irrigation or fertilization of the root zone. All roots needing to be cut should be cut clean with a saw or lopper. Roots to be left exposed for a period of time should be covered with layers of burlap and kept moist. The site arborist must first give consent if roots over 2 inches in diameter are to be cut.

Trenching and Excavation

Trenching for foundation, irrigation, drainage, electrical or any other reason shall be done by hand when inside the dripline of a protected tree. Hand digging and the careful placement of pipes below or besides protected roots will significantly reduce root loss, thus reducing trauma to the tree. All trenches shall be backfilled with native materials and compacted to near its original level, as soon as possible and if possible. Trenches to be left open for a period of time, will require the covering of all exposed roots with burlap and be kept moist. The trenches will also need to be covered with plywood to help protect the exposed roots.

Pruning

At this time no pruning is proposed. If during the project pruning is needed, it shall be under the direction of the Project Arborist. All pruning must follow ANSI A300 pruning standards.

Irrigation

Normal irrigation shall be maintained on this site at all times. The imported trees will require normal irrigation. On a construction site, I recommend irrigation during winter months, 1 time per month. Seasonal rainfall may reduce the need for additional irrigation. During the warm season, April – November, my recommendation is to use heavy irrigation, 2 times per month. This type of irrigation should be started prior to any excavation. The irrigation will improve the vigor and water content of the trees. The on-site arborist may make adjustments to the irrigation recommendations as needed. The foliage of the trees may need cleaning if dust levels are extreme. Removing dust from the foliage will help to reduce mite and insect infestation.

540 Patrick

The information included in this report is believed to be true and based on sound arboricultural principles and practices. Sincerely,

(8)

David Beckham

Certified Arborist WE#10724A TRAQ Qualified David Beckham

Kielty Arborist Services P.O. Box 6187

San Mateo, CA 94403 650-532-4418

ARBORIST DISCLOSURE STATEMENT

Arborists are tree specialists who use their education, knowledge, training and experience to examine trees, recommend measures to enhance the beauty and health of trees, and attempt to reduce the risk of living near trees. Clients may choose to accept or disregard the recommendations of the arborist, or seek additional advice.

Arborists cannot detect every condition that could possibly lead to the structural failure of a tree. Trees are living organisms that fail in ways we do not fully understand. Conditions are often hidden within trees and below ground. Arborists cannot guarantee that a tree will be healthy or safe under all circumstances, or for a specified period of time. Likewise, remedial treatments, like a medicine, cannot be guaranteed.

Treatment, pruning, and removal of trees may involve considerations beyond the scope of the arborist's services such as property boundaries, property ownership, site lines, disputes between neighbors, landlord-tenant matters, etc. Arborists cannot take such issues into account unless complete and accurate information is given to the arborist. The person hiring the arborist accepts full responsibility for authorizing the recommended treatment or remedial measures.

Trees can be managed, but they cannot be controlled. To live near a tree is to accept some degree of risk. The only way to eliminate all risks is to eliminate all trees.

David Beckham

David Beckham

STUDIO S SQUARED ARCHITECTURE

1000 S Winchester Blvd San Jose, CA 95128 P: (408) 998 - 0983

Charng-Chow Residence New SINGLE FAMILY RESIDENCE


ONSTRUC


540 Patrick Way Altos, Los

_	- ∠)		^
PROJECT NO.			21-020
REVISION	DATE	DESCRIPTION	DRAWN BY
	01.31.2021	PLANNING PERMIT SUBMITTAL	AA/IG
	04.05.2022	P. PACKAGE RESUBMITTAL	AA/IG
2	07.06.2022	P. PACKAGE RESUBMITTAL	IG/AD

ARBORIST

REPORT





NEW RESIDENCE

540 PATRICK WAY LOS ALTOS, CA APN: 167-27-014

& ASSOCIATES



LICENSE STAMPS AND SIGNATURE



No.	Description	Date
DAT	.E.	
	JULY 30, 2021	
SCA	1"=10'	
DRA	BG	
JOB:	10078	

TOPOGRAPHIC SURVEY

SHEET NO.

GRADING AND DRAINAGE NOTES: 1. CONTRACTOR TO VERIFY ALL CONTROLLING DIMENSIONS WITH ARCHITECTURAL PLANS AND SHALL VISIT THE SITE AND FAMILIARIZE THEMSELVES WITH ALL EXISTING CONDITIONS. THEY SHALL BRING ANY DISCREPANCIES TO THE ATTENTION OF THE ENGINEER PRIOR TO PROCEEDING. VERIFY THE LOCATIONS OF ALL UNDERGROUND UTILITIES BEFORE STARTING CONSTRUCTION. ANY SITE WORK THAT DEVIATES FROM WHAT IS SHOWN ON THE PLANS SHALL HAVE THE ENGINEER'S APPROVAL PRIOR TO PROCEEDING WITH THE DEVIATING WORK ITEM. CONTRACTOR SHALL CALL "UNDERGROUND SERVICE ALERT" (800) 642-2444 PRIOR TO EXCAVATION. 2. THE SITE SHALL BE FINE GRADED TO PROVIDE A MINIMUM OF 5% ACROSS VEGETATED OR DIRT AREA AND 2% ACROSS HARDSCAPED AREA, AWAY FROM THE BUILDING PERIMETER. EXISTING DRAINAGE COMING FROM ADJACENT PROPERTIES SHALL BE MAINTAINED. IN NO CASE SHALL THE FINAL GRADING INCREASE SHEET FLOW ONTO ADJACENT PROPERTIES. 3. UNLESS SHOWN ON THE PLAN OTHERWISE, HOUSE AND GARAGE MUST HAVE DOWN SPOUTS THAT ARE DIRECTED TO SPLASH BLOCKS (2 FEET LONG) THAT DEFLECT THE WATER AWAY FROM BUILDING FOUNDATION BY SURFACE DRAINAGE. ALL DOWNSPOUT AND GUTTER SHALL BE GALV. SHEET METAL. 4. CONTRACTOR SHALL OBTAIN A STREET WORK PERMIT FROM PUBLIC WORKS ENGINEERING FOR ANY PROPOSED CONSTRUCTION WHICH WILL IMPACT THE USE OF THE SIDEWALK, STREET AND ALLEY OR ON THE PROPERTY IN WHICH THE CITY HOLDS AN INTEREST. 5. ANY CONSTRUCTION WITHIN THE CITY RIGHT-OF WAY MUST HAVE AN APPROVED PERMIT FOR CONSTRUCTION IN THE PUBLIC STREET PRIOR TO COMMENCEMENT OF THIS WORK. THE PERFORMANCE OF THIS WORK IS NOT AUTHORIZED BY THE BUILDING PERMIT ISSUANCE BUT SHOWN ON THE BUILDING PERMIT FOR INFORMATION ONLY. 6. IF GROUNDWATER OR RUNOFF WATER IS ENCOUNTERED AND REQUIRES REMOVAL FROM THE EXCAVATION AREA, ALL EXCAVATION AND/OR BUILDING ACTIVITIES MUST IMMEDIATELY STOP. THE PLAN FOR THE DEWATERING OF THE EXCAVATION MUST BE DESIGNED AND SUBMITTED FOR APPROVAL TO THE PUBLIC WORKS-ENGINEERING DIVISION. ONCE APPROVAL OF THE PLAN DESIGN HAS BEEN RECEIVED, IMPLEMENTATION OF THE PLAN IS REQUIRED PRIOR

UTILITY NOTES:

1. CONTRACTOR SHALL PREPARE AN ACCURATE COMPOSITE UTILITY PLAN THAT TAKES INTO ACCOUNT THE ACTUAL LOCATION OF EXISTING UTILITIES. CONTRACTOR SHALL VERIFY (POTHOLE IF NECESSARY) SIZE, MATERIAL, LOCATION AND DEPTH OF ALL GRAVITY SYSTEMS THAT ARE TO BE CONNECTED TO OR CROSSED PRIOR TO THE TRENCHING OR INSTALLATION. ALL WORK FOR GRAVITY SYSTEMS SHALL BEGIN AT THE 1. DOWNSTREAM CONNECTION POINT. ALL DIRECTION CHANGES SHALL BE MADE WITH A WYE CONNECTION. ELBOWS AND TEE SHOULD BE AVOIDED.


TO THE COMMENCEMENT OF THE EXCAVATION AND/OR BUILDING ACTIVITIES.

2. CLEANOUTS, CATCH BASINS AND AREA DRAINS ARE TO BE ACCURATELY LOCATED BY THEIR RELATIONSHIP TO THE BUILDING, FLATWORK, ROOF DRAINS, AND/OR CURB LAYOUT, NOT BY THE LENGTH OF PIPE SPECIFIED IN THE DRAWINGS.

3. A MINIMUM OF SIX (6) INCHES VERTICAL CLEARANCE SHALL BE PROVIDED BETWEEN CROSSING UTILITY PIPES, EXCEPT THAT THE MINIMUM VERTICAL CLEARANCE BETWEEN WATER AND SANITARY SEWER PIPELINES SHALL BE 12 INCHES AND ALL NEW WATER PIPES SHALL BE TYPICALLY INSTALLED TO CROSS ABOVE/OVER EXISTING SANITARY SEWER PIPELINES.

4. A MINIMUM HORIZONTAL SEPARATION BETWEEN NEW PIPELINES AND ANY EXISTING UTILITIES SHALL BE FIVE (5) FEET, EXCEPT THAT THE MINIMUM HORIZONTAL SEPARATION FOR WATER AND SANITARY SEWER PIPELINES SHALL BE 10 FEET MINIMUM, UNLESS OTHERWISE NOTED. A MINIMUM HORIZONTAL SEPARATION BETWEEN NEW PIPELINES AND JOINT TRENCH SHALL BE 5 FEET.

AND JOINT TRENCH SHALL BE 5 FEET. **GENERAL NOTES** AGGREGATE BASE GB GRADE BREAK ASPHALT CONCRETE GM GAS METER AREA DRAIN GR GRATE ELEVATION BOTTOM OF WALL HP HIGH POINT CATCH BASIN INV INVERT ELEVATION CAST IRON PIPE JT JOINT TRENCH CENTER LINE JP JOINT POLE CONC CONCRETE LD LANDSCAPE DRAIN CRAWL SPACE ELEV. LINEAR FEET DD DECK DRAIN (N) NEW DUCT IRON PIPE RIM RIM ELEVATION DOWNSPOUT S SLOPE DRIVEWAY SD STORM DRAIN LINE **EXISTING** SDCO STORM DRAIN CLEANOUT EXISTING GRADING SDFM STORM DRAIN FORCED MAIN ELECTRICAL METER SS SANITARY SEWER EDGE OF PAVEMENT SSCO SANITARY SEWER CLEANOUT FINISH FLOOR ELEVATION TW TOP OF WALL ELEVATION FINISHED GROUND ELEV. TYP TYPICAL FINISHED PAVEMENT W DOMESTIC WATER LINE FS FINISH SURFACE ELEV WM WATER METER **ABBREVIATION**



LEGEND


EATHWORK QUANTITIES:

CUT(OUTSIDE BLDG FOOTPRINT) 350 C.Y.
CUT(INSIDE BLDG FOOTPRINT) 1350 C.Y.
FILL 355 C.Y.

BALANCE 1345 C.Y.

EARTHWORK QUANTITIES SHOWN ARE FOR PLANNING PURPOSES ONLY. CONTRACTOR SHALL PERFORM THEIR OWN EARTHWORK QUANTITY CALCULATION AND USE THEIR CALCULATION FOR BIDDING AND COST ESTIMATING PURPOSES.

CUT AND FILL EST.



NEW RESIDENC

540 PATRICK WAY LOS ALTOS, CA APN: 167-27-014

WEC & ASSOCIATES



LICENSE STAMPS AND SIGNATURE



No.	Description	Date
DAT	F:	
	FEB 10, 2022	
SCA.	LE: AS SHOWN	
DRA	WN: J	
JOB:	10078	

GRADING & DRAINAGE

PLAN

SHEET NO.

C. 1



1. CONTRACTOR SHALL ASSUME THE CONCEPTS ON THE EROSION CONTROL PLAN/NOTES, IF PROVIDED, ARE MINIMUM REQUIREMENTS, THE FULL EXTENTS OF WHICH ARE TO BE DETERMINED BY CONTRACTOR. CONTRACTOR IS RESPONSIBLE FOR THE EXACT DESIGN AND EXTENT OF CONTRACTOR'S INTENDED USE AND MANAGEMENT OF THE CONSTRUCTION SITE.

2. ALL EROSION CONTROL FACILITIES SHALL BE INSPECTED BY THE CONTRACTOR AND REPAIRED AS REQUIRED AT THE CONCLUSION OF EACH WORKING DAY DURING THE RAINY SEASON. REPAIRS TO DAMAGED FACILITIES SHALL BE MADE IMMEDIATELY UPON DISCOVERY.

3. THE CONTRACTOR SHALL REMOVE ANY ACCUMULATION OF SILT OR DEBRIS FROM THE EROSION CONTROL SEDIMENT BASINS FOLLOWING EACH STORM AND SHALL CLEAR THE OUTLET PIPES OF ANY BLOCKAGE.

4. STOCKPILED MATERIAL SHALL BE COVERED WITH VISQUEEN OR TARPAULIN UNTIL THE MATERIAL IS REMOVED FROM THE SITE. ANY REMAINING BARE SOIL THAT EXISTS AFTER THE STOCKPILE HAS BEEN REMOVED SHALL BE COVERED UNTIL A NATURAL GROUND COVER IS ESTABLISHED OR IT MAY BE SEEDED OR PLANTED TO PROVIDE GROUND COVER PRIOR TO THE FALL RAINY SEASON.


5. PROTECT ADJACENT PROPERTIES AND UNDISTURBED AREAS FROM CONSTRUCTION IMPACTS USING VEGETATIVE BUFFER STRIPS, SEDIMENT BARRIERS OR FILTER, DIKES, MULCHING OR OTHER MEASURES AS APPROPRIATE.

6. CONTRACTOR SHALL MAINTAIN ADJACENT STREETS IN A NEAT, CLEAN, DUST FREE AND SANITARY CONDITION AT ALL TIMES. CONTRACTOR SHALL BE RESPONSIBLE FOR ANY CLEAN UP ON ADJACENT STREETS AFFECTED BY THEIR CONSTRUCTION. NO STOCKPILING OF BUILDING MATERIALS WITHIN THE PUBLIC RIGHT—OF WAY IS

7. PROTECT DOWN SLOPE DRAINAGE COURSES, STREAMS AND STORM DRAINS WITH ROCK FILLED SAND BAGS, TEMPORARY DRAINAGE SWALES, SILT FENCES, EARTH BERMS, STORM DRAIN INLET FILTERS AND/OR STRAW BALES USED ONLY IN CONJUNCTION WITH PROPERLY INSTALLED SILT FENCES. PROVIDE ROCKED DRIVEWAY FOR SITE ACCESS DURING CONSTRUCTION.

GENERAL NOTES


2



NEW RESIDENCE

540 PATRICK WAY LOS ALTOS, CA APN: 167-27-014

W E C & ASSOCIATES



LICENSE STAMPS AND SIGNATURE




No.	Description	l	Date
DAT	E:		
	Fl	EB 10, 2022	
SCA	LE: A	S SHOWN	
DRA	WN:	J	
JOB:		10078	

SHEET TITLE:

EROSION CONTROL PLAN

SHEET NO.


C.2



NEW RESIDENCE

540 PATRICK WAY LOS ALTOS, CA APN: 167-27-014

WEC & ASSOCIATES



LICENSE STAMPS AND SIGNATURE




No.	Description	Dat
DAT	r.	
DAT	FEB 10, 2022	
SCA	LE: AS SHOWN	
DRA		
JOB:	•	
	10078	

DETAILS

SHEET NO.

C.3



PLANT LEGEND

SYM.	QTY.	SIZE	BOTANICAL NAME	COMMON NAME	COMMENTS	WATE USAC
			TREES			
AP	×	24" box	Acer palmatum	Japanese Maple	Multi trunk. Dbl. stakd	me
LF	X		Lagerstroemia f. 'Tuscarora'	Rose Hybrid Crape Myrtle	Dbl. staked	low
			SHRUBS & PERENNIALS			
Ad	Х	15 gal	Acer dissectum	Laceleaf Japanese Maple		me
Сс	X	15 gal	Cotinus coggygria 'Royal Purple'	R.P. Smoke Tree		lov
Ce	X	5 gal	Cordyline 'Electric Pink'	Electric Pink Dracena		lov
Ct	X	5 gal	Chondropetalum tectorum	Small Cape Rush		lov
Db	X	5 gal	Dietes bicolor	Yellow Fortnight Lily		lov
Do	X		Dodonea v. 'Purpurea' stkd.	Purple Hopseed Bush	Tree form. Min. 8' PLANTED height.	lov
Dv	X	5 gal	Dietes v. 'variegata'	White Variegated Fortnight Lily		lov
Fg	X	1 gal	Festuca g. 'Elijah Blue'	Elijah Blue Common Fescue		lov
Fs	X	5 gal	Feijoa sellowiana	Pineapple Guava		lov
Lc	X	5 gal	Loropetalum c. 'Purple Diamond'	Purple Diamond Fringe Flower		lov
Li	X	5 gal	Lavendula intermedia 'Provence'	Provence Hybrid Lavender		lov
LI†	X	5 gal	Lomandra 'Lime Tuff'	Lime Tuff Mat Rush		lov
Lp	X	1 gal	Limonium perezii	Sea Lavender		lov
Lpb	X	5 gal	Lomandra 'Platinum Beauty'	Platinum Beauty Mat Rush		lov
Lv	X	5 gal	Lavendula 'Hidcote'	Hidcote English Lavender		lov
Мр	X	1 gal	Myoporum parvifolia prostratum	No Common Name	B' o.c. spacing. Min4' from paved edge	lov
Pe	X	5 gal	Pennisetum A. 'Hameln'	Hameln Fountain Grass		lov
Pm	X	24" box	Podocarpus macro. 'column'	Yew Pine	Column form.	me
Pυ	Х	5 gal	Punica granatum 'nana'	Dwarf Pomegranate		lov
Rb	Х	15 gal	Rosa banksiae 'white'	White Lady Banks Rose	Tie to arbor posts	lov
Rje	Х	15 gal	Rhamnus a. 'John Edwards' stkd.	John Edwards Buckthorn stkd.	Min. 6' PLANTED height.	lov
Rm	Х	5 gal	Rhaphiolepis u. 'Minor'	Dwarf Yeddo Hawthorn		lov
Rs	Х	5 gal	Rosemarinus 'Blue Spires'	Blue Spires Rosemary		lov
Sg	Х	5 gal	Salvia gregii	Autumn Sage		lov
SI	Х	5 gal	Salvia leucantha 'Santa Barbara'	S.B. Mexican Sage		lov
Sm	Х	5 gal	Salvia microphylla 'Bezerkeley'	Bezerkeley Sage		lov
Sr	Х	5 gal	Sarcococca rustifolia	Fragrant Sarcococca	after future ADU	lov
VI	X	5 gal	Vitus labrusca	American Grape	secure vine to posts in raised planter.	lov
Wf	Х	5 gal	Woodwardia fimbriata	Giant Chain Fern	after future ADU	me
_awnG		Sod	'90/10'	90% Tall Fescue / 10% Bluegrass	from Delta Bluegrass.com	hig
or SynT			'Evernatural Premium'	Ever. Prem. Synthetic Turf	from Watersavers.com	n.c

GENERAL NOTES

- 1. ALL MEASUREMENTS SHOULD BE CONFIRMED PRIOR TO ANY WORK. NOTIFY LANDSCAPE ARCHITECT FOR ANY DISCREPANCIES.
- 2. CONTRACTOR TO VERIFY ALL UNDERGROUND UTILITIES WITH OWNER AND CALL '811 UNDERGROUND SERVICE ALERT' PRIOR TO ANY WORK.

PLANTING NOTES

- 1) CONTRACTOR TO VERIFY ALL UNDERGROUND UTILITIES WITH OWNER AND CALL '811 UNDERGROUND SERVICE ALERT', PRIOR TO ANY WORK.
- 2) EXACT LOCATION OF PLANTS ON SITE TO BE ADJUSTED SO AS TO BEST COORDINATE WITH SPRINKLER HEAD LOCATIONS, LIGHTS, DRAINAGE FEATURES, AND
- 3) DON'T PUT PLANTS IN BOTTOM OF SWALES.
- 4) DON'T MULCH FLOW LINES OF SWALES SUCH THAT MULCH BLOCKS FLOW OF WATER.
- 5) USE 3" DEEP MULCH IN ALL PLANTING AREAS WITH MAHOGONY 'PRO CHIP' RECYCLED WOOD MULCH. 'GORILLA HAIR' WILL NOT BE ACCEPTED. PROVIDE 3"
- 6) ANY PLANTS WITH BUBBLERS MUST HAVE PERMANENTLY MAINTAINED WATERING BASINS 4" HIGH.
- 7) INSTALL PLANTS FOR ALL PLANT CIRCLES SHOWN ON THE PLAN EVEN IF THEY AREN'T LABELED. CALL FOR CLARIFICATION. PLANT QUANTITIES IN THE LEGEND ARE TO BE VERIFIED BY CONTRACTOR.
- 8) THE PLAN IS SCHEMATIC. DON'T INSTALL PLANTS CLOSE TO EDGES OF PAVING OR BUILDINGS. BE SURE PLANTS ARE NOT BLOCKING SPRINKLER SPRAY EXCESSIVELY.
- 9) FINE GRADING IS THE RESPONSIBILITY OF THE LANDSCAPE CONTRACTOR. INSURE ADEQUATE WATER FLOW AWAY FROM BUILDING WALLS, TO DRAINS, AND
- THROUGH SWALES. PROVIDE WATER WASHED COBBLES / PEBBLES AT ENDS OF DRAIN SPOUTS TO PREVENT SOIL EROSION.
- 10) CONTRACTOR TO INVESTIGATE EXISTING SOIL CONDITIONS AND BE RESPONSIBLE FOR PROPER SOIL PREPARATION AND AMENDING TO INSURE VIGOROUS
- 11) PESTICIDES/FERTILIZER REDUCTION: IF FERTILIZERS AND PESTICIDES ARE USED DURING THE CONSTRUCTION PHASE, CONTRACTOR MUST PROPERLY DISPOSE OF EXCESS OR SPILLED FERTILIZERS AND PESTICIDES. CONTRACTOR MUST NOT WASH SPILLED FERTILIZERS OR PESTICIDES DOWN THE STORM DRAINS OR BURY THEM IN OF EXCESS FERTILIZERS OR PESTICIDES BY RECYCLING THEM, REUSING THEM OR DISPOSING OF THEM AS HAZARDOUS WASTE.
- 12) NO GRADING, PLANTING, IRRIGATION, TRENCHING, UTILITIES, MATERIAL STORAGE, EQUIPMENT TRAVEL UNDER THE DRIP LINES OF EXISTING TREES, IF POSSIBLE (OR OTHERWISE NOTED).
- 13) PRUNING NOTE: ALLOW ALL PLANTS TO GROW INTO THEIR NATURAL GROWTH FORM. DO NOT SHEAR ANY PLANTS INTO 'BALLS', FLAT TOPPED OR TOPIARY, ETC. WAYWARD BRANCHES MAYBE CUT BACK OR PLANT BRANCHES OR FOLIAGE MAY BE CUT BACK INDIVIDUALLY FOR WALKWAY ACCESS, IF NEED BE. EXCEPTIONS: ornamental grasses in winter can be cut nearly to the ground. REMOVE SPENT FLOWERS (DEAD HEAD) 1-2 TIMES A YEAR AS NEEDED.

WATER EFFICENT LANDSCAPE ORDINANCE STATEMENT

"I HAVE COMPLIED WITH THE CRITERIA OF THE MODEL WATER EFFICIENT LANDSCAPE ORDINANCE AND HAVE

APPLIED THEM FOR THE EFFICIENT USE OF WATER IN THE LANDSCAPE DESIGN PLAN."

GREG G. ING, PROJECT LANDSCAPE ARCHITECT

STUDIO S SQUARED ARCHITECTURE


1000 S Winchester Blvd San Jose, CA 95128 P: (408) 998 - 0983

RESIDENCE


540 Patrick Way ARNG-CHOW

NEW SINGLE FAMILY F Altos, Los

LANDSCAPE



LANDSCAPE PLAN



IRRIGATION LEGEND

_	KEY	MANUF.	MODEL NO.	DESCRIPTION
		AGRIFIM	PC PLUS	PRESSURE COMPENSATING EMITTER. SEE EMITTER SCHEDULE.
	1	HUNTER	MP-1000-90, 210 W/ PROS-06-PRS40-CV	MP ROTOR (90-210, 210-270 DEGREE ARC) GPM: .19, .37, .43, .57 WITH 6" POP UP & DRAIN CHECK VALVE RAD: 8'-15' PRECIP: .39
	2	HUNTER	MP-2000-90, 180 W/ PROS-06-PRS40-CV	MP ROTOR (90-210 DEGREE ARC) GPM: .40, .74, .86 RAD: 13'-21' WITH 6" POP UP & DRAIN CHECK VALVE PRECIP: .39
	\oplus	RAINBIRD	ASVF SERIES	ELECTRIC VALVE W/ ANTISYPON FOR SPRAY IRRIGATION INSTALL ABOVE GRADE 6" ABOVE HIGHEST OUTLET.
	•	RAINBIRD	XACZ-075-PRF SERIES	3/4" CONTROL ZONE KIT W/ ANTI SYPON FOR DRIP IRRIGATION. LOW FLOW ELECTRIC VALVE W/ PRESS. REG AND FILTER INSTALL ABOVE GRADE 6" ABOVE HIGHEST OUTLET.
		RAINBIRD	HV SERIES	1" MASTER SHUT OFF VALVE AT POINT OF CONNECTION INSTALL BELOW GRADE IN A VALVE BOX.
	H	-	-	1" BRASS SHUT OFF VALVE - SAME SIZE AS MAINLINE INSTALL BELOW GRADE IN A VALVE BOX.
	C	HUNTER	PHC-12	PRO-HC WIFI - 12 STATION OUTDOOR HYDRAWISE CONTROLLER. SEE NOTE #11.
	R	HUNTER	WR-CLIK	WIRELESS RAIN CLIK
	fM	HUNTER	HC-100-FLOW	FLOW METER. INSTALL BELOW GRADE IN VALVE/METER BOX
	#			3/4" HOSE BIB ON HOUSE WALL OR IN VEGETABLE GARDEN.
	—	-	-	AUTOMATIC FLUSH VALVE AT ENDS OF DRIP IRRIGATION PETUBING.

SEE EMITTER SCHEDULE. SEE EMITTER SCHEDULE. 15 GAL. OR 24" BOX TREE LOCATION. ✓ ✓ ✓ OR 3/4" PE DRIP TUBING W/ COMPRESSION FITTINGS - SEE DRIP NOTES INSTALL FLUSH VALVE AT END. DO NOT TRENCH UNDER EXISTING TREE CANOPIES, IF NOT POSSIBLE, INSTALL ON TOP OF SOIL UNDER MULCH.

✓ "EMITTER TUBING W/ COMPRESSION FITTINGS - 18" EMITTER SPACING AND 18"-24" ROW SPACING. 1 GALLON PER HR. EMITTER. 'RAINBIRD XFS SUBSURFACE DRIPLINE' OR APPROVED EQUAL. SEE DRIP NOTES. INSTALL AUTOMATIC FLUSH VALVE AT END. DO NOT TRENCH UNDER

NON PRESSURE LINE - CLASS 200 PVC - 3/4" UNLESS OTHERWISE LABELED

EXISTING TREE CANOPIES, INSTALL ON TOP OF SOIL UNDER MULCH.

PRESSURE LINE - SCH. 40 PVC

ALL PIPING 24" UNDER PAVING: PRESSURE LINE, NONPRESSURE LINE, CONTROL WIRE SLEEVE, OR EXTRA LINE FOR FUTURE USE - MIN 2" OR LARGER AS NOTED. CLASS 315 PVC. TWICE THE SIZE OF THE PIPE INSIDE. INSTALL A 2" SCH. 40 PVC GREY ELECTRICAL CONDUIT AT ALL PRESSURE LINE PAVING CROSSINGS.

EMITTER SCHEDULE:

LANT	NO. OF	EMITTER	PLANT	EMITTER
IZE	EMITTERS	SIZE	DESCRIPTION	LOCATION
GAL.	1	1 GPH	SMALL SHRUBS	AT PLANT
GAL.	2	1 GPH	MEDIUM SHRUBS	6"-12"
5 GAL.	2	2 GPH	TREES	1' FROM TREE
4" BOX	3	2 GPH	TREES	2' APART

DRIP IRRIGATION NOTES

1) COVER TUBING WITH SOIL AND MULCH (MULCH ONLY UNDER EXISTING TREES) AND INSTALL FLUSH VALVES AT ENDS
OF TUBING AND MARK THEM SO THEY CAN BE FOUND EASILY.
2) RUN LARGE TUBING CLOSE TO PLANTS TO MINIMIZE LENGTH OF SMALLER X" TUBING. SECURE EMITTERS DIRECTLY ON X" TUBING AT PLANT
ROOTBALLS. WHEN NECESSARY RUN SHORT LENGTHS OF X" TUBING FROM EMITTERS TO PLANT ROOT BALL EDGES. INSTALL STAKES ON X"
TUBING AT 12" ON CENTER AND COVER TUBING WITH 1" OF SOIL PLUS MULCH. IN EXISTING TREE AREAS COVER WITH MULCH ONLY.
3) INSTALL PRESSURE COMPENSATING EMITTERS (MINIMAL DIFFERENCE IN PLOW BETWEEN 10 PS) AND 40 PSI) AT EACH PLANT ON ROOTBALL EDGE, NOT RIGHT AT STEM. USE AGRIFIM PC PLUS (PRESSURE COMPENSATING EMITTERS) THAT CAN ACCOMODATE X" TUBING. OTHER EMITTERS MAY HAVE A HIGHER DISCHARGE RATE AT STARTUP REQUIRING LARGER PIPE SIZES.

4) WHEN LOCATING EMITTERS AROUND A NEW PLANT INSTALL THREE EMITTERS ON THE ROOTBALL, BUT CLOSE TO THE EDGE OF THE ROOTBALL, EVENLY SPACED ALL AROUND THE PLANT.

5) AS THE PLANT AND PLANT ROOTBALL INCREASES IN SIZE, THE LOCATION OF THE EMITTERS MAY NEED TO BE ADJUSTED SO THEY ARE EVENLY SPACED AROUND THE ROOT ZONE. 6) INSTALL RAINBIRD DIFFUSER BUG CAPS ON ALL EMITTERS (EXCEPT IN LINE EMITTERS) OR END OF EACH 1/4" TUBE

IRRIGATION NOTES

- 1) CONTRACTOR SHALL VERIFY ALL EXISTING UTILITIES PRIOR TO THE START OF WORK. CALL 811 UNDERGROUND SERVICE ALERT AND OWNER FOR AS-BUILT DOCUMENTS FOR LAYOUT OF UTILITIES AND TAKE PRECAUTIONS TO NOT DAMAGE OR DISTURB EXISTING UTILITIES.
- 2) THIS SYSTEM IS DESIGNED TO OPERATE WITH A MAX 5.1 GPM AT MIN 40 P.S.I. AT THE POINT OF CONNECTION. IF THIS CONDITION IS NOT MET CONTACT THE LANDSCAPE ARCHITECT FOR POSSIBLE REDESIGN. IF STATIC PRESSURE EXCEEDS 85 PSI AT THE POINT OF CONNECTION
- 3) THE ROUTING OF SPRINKLER LINES IS SCHEMATIC ON THE PLAN, DO NOT PUT VALVES TOO CLOSE TO TREE. STAY 8'-10' AWAY IF POSSIBLE, DO NOT PUT PRESSURE LINES UNDER TREES, INSTALL LINES IN PLANTING AREAS INSTEAD OF UNDER PAVING WHENEVER
- POSSIBLE. STAKE TREE LOCATIONS PRIOR TO INSTALLING IRRIGATION. 4) CONTROLLER TO BE SET TO WATER BETWEEN THE HOURS OF 11:00 P.M. AND 5:00 A.M.
- 5) THE IRRIGATION SYSTEM SHALL BE INSPECTED BI-MONTHLY FOR THE LIFE OF THE SYSTEM. THIS 'WET CHECK' INSPECTION CONSISTS OF OPERATING THE VALVES AND OBSERVING THE PERFORMANCE OF EACH IRRIGATION ZONE.
- 6) THE IRRIGATION SYSTEM SHALL BE KEPT CLEAN AND PROPERLY ADJUSTED. DAMAGED EQUIPMENT SHALL BE REPAIRED PROMPTLY WITH IDENTICAL EQUIPMENT TO MAINTAIN THE ORIGINAL DESIGN INTEGRITY.
- 7) CONTRACTOR TO PRESSURIZE AND TEST THE ENTIRE SYSTEM FOR LEAKS. CHECK THE WATER USE TWICE A MONTH TO NOTICE SPIKES IN WATER USE THAT COULD INDICATE A LEAK OR MALFUNCTION.
- 8) DON'T TRENCH UNDER EXISTING TREE CANOPIES.
- 9) THE SYSTEM TO BE INSTALLED AS PER LOCAL BUILDING AND PLUMBING CODES.
- 10) INSTALL IN LINE CHECK VALVES TO PREVENT LOW HEAD/EMITTER DRAINAGE.
- 11) Irrigation controller: Automatic Controller to be weather based system with Rain Sensor and Solar Sync which connects or communicates with the controller. It also shall have flow sensor and master valve compatibility.

WATER EFFICIENT LANDSCAPE NOTES

- 1) CERTIFICATION OF INSTALLATION: TO BE PROVIDED BY THE PROJECT LANDSCAPE ARCHITECT.
- 2) IRRIGATION SCHEDULING: FINAL SCHEDULING SHALL BE PROVIDED BY A CERTIFIED WATER AUDITOR.
- 3) SCHEDULE OF LANDSCAPE AND IRRIGATION MAINTENANCE: N.A.
- 4) LANDSCAPE IRRIGATION AUDIT REPORT: OWNER OR CONTRACTOR TO PROVIDE AN REPORT FROM A CERTIFIED WATER AUDITOR.
- 5) SOIL MANAGEMENT REPORT: LANDSCAPE CONTRACTOR TO PROVIDE A SOILS FERTILITY REPORT FROM SOIL & PLANT LABORATORY, SAN JOSE. THE RECOMMENDATIONS AS PER THE REPORT SHALL SUPERCEED THE SOIL AMENDMENT SPECIFICATIONS OR NOTES ON

WATER EFFICENT LANDSCAPE ORDINANCE STATEMENT

"I HAVE COMPLIED WITH THE CRITERIA OF THE MODEL WATER EFFICIENT LANDSCAPE ORDINANCE AND APPLIED THEM FOR THE EFFICIENT USE OF WATER IN THE IRRIGATION DESIGN PLAN."

GREG G. ING, PROJECT LANDSCAPE ARCHITECT


ARCHITECTURE

1000 S Winchester Blvd San Jose, CA 95128

P: (408) 998 - 0983

RESIDENCE Patrick ' 540 Altos, Los

IRRIGATION PLAN



IRRIGATION PLAN