





ABBREVIATIONS		GENERAL NOTES	
A	ABOVE	N	NEW
ABV	ASPHALT CONCRETE	(N)	NORTH
AC	AREA DRAIN	NIC	NOT IN CONTRACT
AD	ADDITIONAL	NOM	NOMINAL
ADDL	ABOVE FINISH FLOOR	NP	NO PARKING
AFF	ASPHALT	NR	NON-RATED
ASPH		NTS	NOT TO SCALE
B	BITUMINOUS	O	OVERALL
BKG	BACKING	OA	ON CENTER
BLDG	BUILDING	OC	OUTSIDE DIAMETER/ DIMENSION
BM	BEAM	OD	OWNER FURNISHED CONTRACTOR
BR	BACKER ROD	OFCI	INSTALLED
BUR	BUILT-UP-ROOF	OFOI	OWNER FURNISHED OWNER INSTALL
BDR	BEDROOM	P	PENETRATION
BW	BOTTOM OF WALL	PENN	PERFORATED
C	CABINET	PERF	PERPENDICULAR
CB	CATCH BASIN	PL	PLATE
CEM	CEMENT	PLAS	PROPERTY LINE
CF	CUBIC FEET	PLBG	PLASTER
CJ	CONTROL JOINT	PLWD	PLYWOOD
CL	CLOSET	PNL	PANEL
CTL	CENTERLINE	POC	POINT OF CONNECTION
CLG	CEILING	PP	PERMEABLE PAVERS
CONC	CONCRETE	PREFAB	PREFABRICATED
CPT	CARPET	PSF	POUNDS PER SQUARE FOOT
D	DECK	PSI	POUNDS PER SQUARE INCH
D	DRAIN	PTD	PAINTED
DR		PTR	PRESSURE TREATED
E	EXISTING	PTRWDQ	PRESSURE TREATED WOOD
(E)	EAST	Q	QUANTITY
ELEC	ELECTRICAL	R	REVEAL OR RISER
EP	ELECTRICAL PANEL	RAD	RADIUS
EXT	EXTERIOR	RCP	REINFORCED CONCRETE PIPE
F	FOUNDATION	RD	ROOF DRAIN
FH	FIRE HYDRANT	REF	REFERENCE
FIN	FINISH	REFL	REFLECTED
FF	FINISH FLOOR	REFR	REFRIGERATOR
FL	FLOW LINE	RET	RETAINING OR RETARDANT
FLUOR	FLUORESCENT	REG	REGISTER
FOC	FACE OF CONCRETE	RO	ROUGH OPENING
FOF	FACE OF FINISH	S	SEE CIVIL DRAWINGS
FOS	FACE OF STUD	SCD	SCHEDULE
FR	FIRE RATED	SD	STORM DRAIN
FS	FLOOR SINK	SECT	SECTION
FSL	FIRE SPRINKLER	SED	SEE ELECTRICAL DRAWINGS
FTG	FOOTING	SF	SQUARE FOOT OR FEET
FURR	FUllING	SHT	SHOWER
G	GALVANIZED	SHT	SHEET
GC	GENERAL CONTRACTOR	SHTG	SHEATHING
GL	GLASS	SIM	SIMILAR
GND	GROUND	SJ	SEISMIC JOINT
GW	GYPSUM WALL BOARD	SL	SEALANT
GYP	GYPSUM	SLD	SEE LANDSCAPE DRAWINGS
H	HARDBOARD	SM	SHEET METAL
HDBD	HEADER	SMD	SEE MECHANICAL DRAWINGS
HDR	HARDWARE	SOF	SOFFIT
HDWR	HARDWOOD	SOG	SLAB ON GRADE
HWD	HEATER	SPD	SEE PLUMBING DRAWINGS
HTR	HEATING, VENT. & A.C.	SPEC/S	SPECIFICATION
HVAC		SQ	SQUARE
I	INCH	SS	SANITARY SEWER
IN	INCANDESCENT	SSD	SEE STRUCTURAL DRAWINGS
INSUL	INSULATION	STC	SOUND TRANSMISSION COEFFICIENT
INT	INTERIOR	STD	STANDARD
INV	INVERT	STL	STEEL
J	JOIST	STOR	STORAGE
JST	JOINT	STR	STRUCTURAL
JT		SY	SQUARE YARD
K	KIPS	T	TOP AND BOTTOM
K	KITCHEN	T&B	TONGUE AND GROOVE
KIT	KICK PLATE	T&G	TOP OF CURB
KP		TC	TOP OF CONCRETE
L	LOCATION	TOC	TOP OF PAVING
LOC	LIGHT	TOP	TOP OF STEEL
LT		TOS	TREAD
U	UL	TRD	TOP OF WALL
M	MACHINE BOLT	UL	UNDERWRITERS LABORATORIES
MB	MEDIUM DENSITY FIBERBOARD	UTIL	UTILITIES
MDF		V	VITREOUS CLAY PIPE
MECH	MECHANICAL	VCP	VERTICAL
MEMB	MEMBRANE	VERT	VENT THROUGH ROOF
MET	METAL	VTR	
MH	MANHOLE	W	WEST OR WIDTH
MSC	MISCELLANEOUS	W	WATER CLOSET
MTD	MOUNTED	WC	WOOD
MTL	METAL	WD	WINDOW
		WDW	WITHOUT
		W/O	WATER PROOF
		WP	WORKING POINT
		WPT	
		WR	WATER RESISTANT

GENERAL NOTES

- IT IS THE RESPONSIBILITY OF THE CONTRACTOR AND SUBCONTRACTORS TO CHECK AND VERIFY ALL DIMENSIONS AND CONDITIONS INDICATED ON THESE DRAWINGS AND MAKE KNOWN ANY DISCREPANCIES PRIOR TO COMMENCING THEIR WORK.
- ALL WORK SHALL BE PERFORMED IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS INCLUDING BUT NOT LIMITED TO NATIONAL, CITY, STATE, LOCAL CODES AND ORDINANCES WHICH MAY BE IN EFFECT. ALL MATERIALS, INSTALLATION PROCEDURES AND PLANS SHALL BE APPROVED BY ALL APPLICABLE CODE ENFORCEMENT AUTHORITIES HAVING JURISDICTION, AND IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN AND PAY FOR ALL NECESSARY PERMITS AND APPROVALS FOR THE WORK.
- THESE DRAWINGS ARE INTENDED FOR USE IN A NEGOTIATED CONSTRUCTION CONTRACT AND THEREFORE, MAY NOT SPECIFICALLY DETAIL OR SPECIFY MATERIAL AND / OR MANUFACTURERS. THE CONTRACTOR SHALL PROVIDE ALL SAMPLES AND OR CUTS AS REQUIRED TO ASSIST OWNER OR HIS AGENT IN MAKING MATERIAL SELECTIONS. FOR THE PURPOSE OF ESTIMATING, THE CONTRACTORS SHALL USE THE MATERIALS SELECTED BY THE OWNER, OR IN ABSENCE OF SAME, SHALL PROVIDE AN ALLOWANCE AMOUNT AND SO CONDITION ANY COST ESTIMATE. ALL MATERIALS SPECIFIED IN THESE DRAWINGS SHALL BE INCLUDED IN SUCH ESTIMATE.
- NO GUARANTEE OF QUALITY OF CONSTRUCTION IS IMPLIED OR INTENDED BY THE ARCHITECTURAL DOCUMENTS, AND THE CONTRACTOR SHALL ASSUME FULL RESPONSIBILITY FOR ANY OR ALL CONSTRUCTION DEFICIENCIES.
- THE GENERAL CONTRACTOR SHALL HOLD HARMLESS, INDEMNIFY AND DEFEND THE ARCHITECT FROM ANY ACTION INITIATED BY THE OWNER OR ANY SUBSEQUENT OWNERS FOR CONSTRUCTION DEFICIENCIES, MODIFICATIONS OR SUCH CONDITIONS WHICH MAY BE BEYOND THE CONTROL OF THE ARCHITECT.
- ALL WORK SHALL COMPLY WITH AND RECORD THE CONDITIONS OF ALL EXISTING SITE IMPROVEMENTS INCLUDING PAVED AREAS. THE GENERAL CONTRACTOR SHALL MAKE KNOWN ALL EXISTING DAMAGED OR DISPAIR ITEMs AND CONDITIONS THAT MAY WORSEN DUE TO THE CONSTRUCTION. ALL ITEMS IN GOOD CONDITION SHALL BE MAINTAIN IN THEIR PRESENT CONDITION AND ANY REPAIR OR DAMAGE WHICH OCCURS DURING CONSTRUCTION SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR.
- CONTRACTOR SHALL THOROUGHLY EXAMINE THE SITE AND SATISFY HIM OR HERSELF AS OF THE CONDITIONS UNDER WHICH THE WORK IS TO BE PERFORMED. THE CONTRACTOR SHALL VERIFY AT THE SITE ALL MEASUREMENTS AFFECTING HIS OR HER WORK AND SHALL BE RESPONSIBLE FOR THE CORRECTNESS OF SAME. NO EXTRA COMPENSATION WILL BE ALLOWED TO THE CONTRACTOR FOR THE EXPENSES DUE TO HIS OR HER NEGLECT TO EXAMINE OR FAILURE TO DISCOVER CONDITIONS WHICH MAY AFFECT HIS OR HER WORK.
- ALL WORK SHALL BE COORDINATED WITH THE STRUCTURAL, MECHANICAL, ELECTRICAL, PLUMBING, ARCHITECTURAL, FIRE PROTECTION AND LIGHTING DRAWINGS APPLYING TO THIS PROJECT PRIOR TO SUBMITTING SHOP DRAWINGS FOR FABRICATION APPROVAL.
- IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO COORDINATE WITH ALL INVOLVED PARTIES AND PREPARE SHOP DRAWINGS.
- ALL NEW INTERIOR PAINT COLOR, FLOOR, WALLS AND CEILING FINISHES SHALL BE SELECTED BY OWNER AT THE TIME WHEN IT IS NECESSARY FOR THE COMPLETION OF THE PROJECT.
- THE CONTRACTOR SHALL PERFORM ALL CUTTING AND PATCHING REQUIRED TO COMPLETE THE WORK OR TO MAKE ITS PARTS FIT TOGETHER PROPERLY WITHOUT COMPROMISING THE QUALITY OF THE WORK.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR ADEQUATE BRACING, SHORING, AND PROTECTING ALL WORK DURING CONSTRUCTION, AGAINST DAMAGE, BREAKAGE, COLLAPSE, DISTORTIONS, AND OFF ALIGNMENTS ACCORDING TO CODES AND STANDARDS OF GOOD PRACTICE.
- ALL PUBLIC IMPROVEMENTS SHALL BE MADE IN ACCORDANCE WITH THE LATEST ADOPTED CITY STANDARDS. THE STORING OF GOOD AND MATERIALS ON SIDEWALK AND/ OR STREET SHALL NOT BE ALLOWED UNLESS THE CONTRACTOR HAS APPLIED AND SECURED A SPECIAL PERMIT WHICH ALLOW SUCH STORAGE TO BE PLACED.
- OWNERSHIP OF DRAWINGS: THESE DRAWINGS ARE THE PROPERTY OF GKW ARCHITECTS - GORDON WONG, ARCHITECT, THE DRAWINGS SHALL NOT BE USED FOR ANY OTHER PURPOSE EXCEPT AS APPROVED BY THE ARCHITECT.
- LIMITATION OF THE WORK: THE LIMITS OF THE WORK ARE ESTABLISHED BY THE DRAWINGS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING TRADESMEN WITH THESE LIMITS.
- ANY EXISTING TO REMAIN SHALL BE IN GOOD CONDITION PRIOR TO THE PLANNING FINAL INSPECTION.
- NEW LANDSCAPING SHALL COMPLY WITH STATE WATER EFFICIENCY STANDARDS.

GRAPHIC SYMBOLS



## HISTORICAL REPORT

History of 14340 Browns Lane, Los Gatos, CA 95032  
APN 409-14-010

Bonnie Montgomery, Historical Consultant  
421 N 5<sup>th</sup> St  
San Jose, CA 95112  
bayandvalleybooks@gmail.com  
408-439-9073

The parcel 409-14-010 was in unincorporated Santa Clara County until it came under the jurisdiction of the Town of Los Gatos on February 23, 1979, with the Wedgewood No. 9 annexation. Only two County documents were available upon request: (1) the Assessor's Residential Unit Property Record, which documented changes from 1966 to 1998, and (2) a single county building permit from 1974 for a new water heater. A search of Town of Los Gatos building department microfilm yielded documents from 1979 to 1998. These documents will be included in the chronology that follows.

Being so recently annexed into the Town of Los Gatos, this parcel did not appear during a search at the Los Gatos Public Library on the Los Gatos Sanborn maps available between 1884 and 1944. Likewise, it is absent from the 1941 Tax Assessment. The property does not appear on the 1989 Anne Bloomfield Historic Resource Survey forms.

The history prepared here relies on Polk's directory listings, county assessor's records, county official records, recorded maps, aerial photographs, newspaper articles, Town of Los Gatos and County of Santa Clara building permits, and genealogical resources as referenced in the footnotes and attached to this history as figures.

The property's legal description places it in a portion of Lot 10 of the Wedgewood Subdivision of the Maud L. Parr Tract, surveyed in February 1889 (Figure 1).<sup>3</sup> In 1903, the San Jose-Los Gatos Interurban Railway Company purchased the right-of-way across the Wedgewood Subdivision, creating a triangle of land bounded by Smith Creek on the west, the railroad to the north, and Wedgewood Avenue on the south, as shown on the 1929 McMillan and McMillan Official Map of Santa Clara County (Figure 2).<sup>4</sup>

The Santa Clara County Assessor gives 1936 as the build date for this property, but an aerial photograph taken on August 1, 1939, shows that this parcel was still orchard land (Figure 3).<sup>5</sup> To the west of this parcel was a recently surveyed cul-de-sac, La Rinconada Drive, as shown on the subdivision map of Tract No. 10, La Rinconada Acres (Figure 4).<sup>6</sup> Mrs. E. I. Barron subdivided this tract, and she also owned the portions of Lots 10 and 11 east of this subdivision. On December 20, 1939, Ethel I. Barron and her husband William S. Barron sold 10 acres of Lots 8, 9,

<sup>3</sup> Santa Clara County [hereafter SCC] Recorded Map Book E, Page 73.

<sup>4</sup> SCC Deeds Book 248, Page 270, McMillan and McMillan, Official Map of Santa Clara County, California (San Francisco: Wall-Up Map Company, 1929), [https://archive.org/details/smap\\_santaclaracounty\\_1929](https://archive.org/details/smap_santaclaracounty_1929).

<sup>5</sup> UC Santa Barbara Geospatial Collection, August 1, 1939, aerial photograph, Flight C, 5750, Frame 286-19, [https://mlibrary.ucs.edu/dap\\_index/frameFinder/](https://mlibrary.ucs.edu/dap_index/frameFinder/). Photograph superimposed on Santa Clara County Surveyor Record Index map, <https://scplanning.maps.arcgis.com/apps/webappviewer/index.html#/bc21a949580746968cb7139386996978>.

<sup>6</sup> SCC Recorded Maps Book 3, Page 58, May 15, 1939.

10, and 11 of the Wedgewood Subdivision, including the subject parcel, to the San Jose Abstract and Title Insurance Company.<sup>7</sup>

The parcel appears to have been exclusively a rental property and difficult to trace through official record documents from 1939 to 1978. Aerial photographs, census records, directory listings, and newspaper articles suggest that at least some part of the dwelling had been built by 1955.

On an aerial photograph taken on April 25, 1948 (Figure 5), Browns Lane and some neighboring houses are visible, but the resolution is not adequate to determine whether trees or structures are on the parcel.<sup>8</sup> On the 1950 census, John W. Brown, his wife Mary Vera, and their six daughters are living on a rural route along Wedgewood Avenue. One of their neighbors is Bedford Forrest and his family. Like John W. Brown, Bedford was a carpenter born in Texas. The Bedford Forrest family was reported living at 14340 Browns Lane in a blurb published in the July 7, 1955, issue of the *Los Gatos Times-Saratoga Observer*, which announced their son Olson's service in the Navy.<sup>9</sup>

A June 9, 1956, aerial photograph also has poor resolution (Figure 6). A May 15, 1965, aerial

photograph clearly shows the house to the south and the garage to the north (Figure 7). The house was advertised for rent as a three-bedroom unfurnished house in the March 24, 1961, issue of the San Jose Evening News. Starting with the 1962 Los Gatos city directory, the property is listed in the reverse Los Gatos city directory. The tenants were in 1962, Pierre and Gabby Leidelmeyer; in 1964, Willy F. and Mira A. Ferns; in 1965, "no return"; and in 1967, Richard Dalton. The address is listed in the Los Gatos section of the San Jose Suburban city directory between 1968 and 1974. The tenants were: in 1968, 1969, and 1970, Wesley E. Chambers, a carpenter, and his wife Sharon; in 1971, 1972, and 1974, Kenneth Wratous, an employee for the Coca-Cola Bottling Company, and his wife Bonnie.

In 1966, the County Assessor visited the parcel, measured the buildings on the site, and took a photo of the front elevation. According to the Residential Unit Property Record (Figure 8), the house was 748 square feet with a living room, kitchen, bathroom, and two bedrooms. It was of wood-frame construction on a raised concrete foundation. It had a side-gable roof with a front porch under the eaves. The detached garage was 440 square feet with a garage door along the full width of the front elevation and a front-facing gable roof. A shed or garage in the backyard was not measured, because no tax was assessed (NTA).<sup>10</sup>

On October 16, 1974, then-owner Francisco Diaz received a building permit from the County of Santa Clara (No. 20204) for a new water heater. That is the only building permit in the records of the Santa Clara County Planning Department. On January 6, 1978, Francisco and Zulima Diaz granted the parcel to Louis C. and Marilyn D. Franckx.<sup>11</sup> Mr. and Mrs. Franckx lived in Saratoga, and this property continued as a rental property.<sup>12</sup>

On February 23, 1979, the Wedgewood No. 9 annexation placed this parcel under the jurisdiction of the Town of Los Gatos. Soon afterward, the tenants complained to the Town of Los Gatos about the condition of the property. The building department inspected the property on March 21, 1979. The inspector described a one-story wood-frame dwelling with at least two rear additions. The garage had been converted to a separate living unit around March 1978, not long after the Franckxs became the new landlords. The space between the dwelling and garage had been filled in with a kitchen. The structure in the backyard labeled "a shed, garage" on the assessor's Residential Unit Property Record was described by the inspector as "a large wood frame metal roof patio cover, with open gas barbecue." The 21 code deficiencies and violations observed are listed in Figure 9. Mr. and Mrs. Franckx received an electrical permit on September 13, 1990 (No. E 18124) for outlets, appliances, and service equipment (Figure 10). Mr. Franckx died on September 5, 1994, in San Francisco. On August 3, 1995, Marilyn D. Franckx sold the property to Peter Miklos Vadasz and Cathleen Joyce Vadasz.<sup>13</sup>

On March 11, 1998, Peter and Cathleen Vadasz received Permit No. B98-00206 to "repair & replace sheetrock, insulate exterior wall (Figure 1); Permit No. E98-00103 for "electrical for rewiring" (Figure 12); Permit No. P98-000105 for "plumbing to remove furnace, replace old plumbing (Figure 13); and Permit No. M98-00075 for "mechanical for furnace" (Figure 14). A hand-drawn floor plan was also approved, presumably to show how the interior spaces would be reconfigured with new sheetrock. The extensive remodel did not entirely match the plans; for example, the front entry is in the space between the original house and the garage instead of from the kitchen. On August 7, 2019, Peter Miklos Vadasz granted the parcel to the current owner, Cathleen Joyce Vadasz, as her sole and separate property.<sup>14</sup>

## FIGURES



Figure 1. Wedgewood Subdivision, 1889.



Figure 2. Wedgewood Subdivision, 1929.




Figure 3. August 1, 1939, aerial photograph superimposed on Santa Clara County Surveyor Record Index map. Parcel is highlighted in red.

Figure 4. La Rinconada Acres tract map, just west of the property, 1939.

Figure 5. April 25, 1948, aerial photograph with parcel highlighted in red.

Figure 6. June 9, 1956, aerial photograph with parcel highlighted in red.

Figure 7. May 15, 1965, aerial photograph with parcel highlighted in red.

SANTA CLARA COUNTY RESIDENTIAL UNIT PROPERTY RECORD											
ADDRESS: 14340 BROWNS LANE, LOS GATOS, CA 95032		TRACT NO: 409-14-010		LOT: 10		BLOCK: 1		RECORD DATA			
								20 MULTIPLE FAMILIES 21 CO-OP 22 CONDOMINIUM 23 TRACT NO. 24 AREA 25 EMPLOYEE NO. 26 27 APN: 409-00-010 28 COST DATE: 1966 29 CONSTRUCTION DATE: 1936 30 DESIGN: 1936 31 EFFECTIVE YEAR: 1956 32 LIFE TABLE: 1956 33 DEPREC. TABLE: 1956 34 35 FINANCIAL THINNPLN: 1 2 3 4 36 37 WISMANSHIP: 1 2 3 38 TOTAL ROOMS: 3 39 DINING 40 FAM-RUMPUS DEN 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 			

Figure 9. Page 2

**Inspection Report - 14340 Browns Lane**

1

Figure 10

# TOWN OF LOS GATOS

BUILDING INSPECTION DEPARTMENT • PHONE 364-8878  
INSPECTION REQUESTS PHONE 364-8877

E 18124

1

ITEM	NO. OF ITEMS	AMOUNT	I	PER
OUTDOOR LIGHTS		.75 EA.		
INDOOR LIGHTS		.75 EA.		
SWITCHES		.75 EA.		
RECEPTACLES, OUTLETS	3	.75 EA	2	25
RESIDENTIAL:				
OVEN, COOK TOP, RANGE, WALL AIR-COND., SPACE HEATER, DISPOSER, DISHWASHER, WATER HEATER, WASHING MACH, CLOTHES DRYERS, OTHER SMALL APPLIANCES, 1 KW OR LESS	2			
MEDICAL & DENTAL DEVICES, FOOD & BEVERAGE CABINETS, ILLUMINATED SHOW CASES, DRINK FOUNTAINS, VENDING MACH, LAUNDRY MACH, OTHER SMALL APPLIANCES 1 KW OR LESS	2	3.00 EA.	6	15
LARGE APPLIANCES, POWER APPARATUS, HEATING & AIR COND. EQUIP., COOKING & BAKING EQUIP., OTHER LARGE APPLIANCES & APPARATUS OVER 1 KW		3.00 EA.		
OVER 10 KW		15.00 EA.		
OVER 50 KW		30.00 EA.		
OVER 100 KW		45.00 EA.		
BUSWAY (PER 100 FEET)		4.50 EA.		
SIGNS		15.00 EA.		
SERVICE EQUIP. NOT OVER 200 AMPS		18.50 EA.	18	15
SERVICE EQUIP. OVER 200 AMPS	2	37.50 EA.		
SERVICE EQUIP. OVER 500 VOLTS		75.00 EA.		
SUBPANEL		11.00 EA.		
MISC APPARATUS CONDUITS & CONDUCTORS		11.00 EA.		
TEMPORARY POWER POLE		15.00 EA.		
TEMPORARY LIGHTING SYSTEM		7.50 EA.		
SHIMMING POOL SYSTEM		30.00 EA.		
NEW RESIDENTIAL CONST.	50 FT X \$0.35			
ELECTRICAL PLAN CHECK FEE				
ISSUANCE OF PERMIT			15.00	
<b>TOTAL FEES</b>			111.00	
<b>CONTRACTORS DECLARATION</b>				
I CERTIFY THAT I AM PROPERLY LICENSED BY THE STATE OF CALIFORNIA CONTRACTOR'S LICENSE LAW				
SIGNATURE X	<i>Karl Stuhler</i>			
<b>COMPLETE A OR B</b>				
<b>WORKER'S COMPENSATION DECLARATION</b>				
<p><b>A</b> I HEREBY affirm that I have a policy of worker's compensation insurance A CERTIFIED COPY OR A CERTIFICATE OF THAT INSURANCE IS HEREBY TURNED IN AND ON FILE WITH THE TOWN. I FURTHER affirm that I shall keep the insurance in effect THROUGHOUT THE JOB.</p>				
SIGNATURE X	<i>Karl Stuhler</i>			
<b>CERTIFICATE OF EXEMPTION FROM WORKER'S COMPENSATION INSURANCE</b>				
<p><b>B</b> I CERTIFY THAT IN THE PERFORMANCE OF THE WORK FOR WHICH THIS PERMIT IS ISSUED, I SHALL NOT EMPLOY ANY PERSON IN ANY MANNER SO AS TO BECOME SUBJECT TO THE WORKER'S COMPENSATION LAWS OF CALIFORNIA.</p>				
SIGNATURE X				
<p>I CERTIFY THAT I HAVE READ THIS APPLICATION AND STATE THAT THE ABOVE INFORMATION IS CORRECT. I AGREE TO COMPLY WITH ALL TOWN ORDINANCES AND STATE LAWS RELATING TO MECHANICAL CONSTRUCTION AND MINERALLY AUTHORIZE REPRESENTATIVES OF THIS CITY TO ENTER UPON THE ABOVE MENTIONED PROPERTY FOR INSPECTION PURPOSES.</p>				
SIGNATURE X	<i>Karl Stuhler</i>			

BUILDING ADDRESS  
14340 BROWNS LANE

USE OF BUILDING  
RESIDENTIAL

OWNER  
BROWNS 415-921-3401

MAIL ADDRESS  
2750 GREENWICH ST

CITY  
SAN FRANCISCO ZIP  
CONTRACTOR  
ALUMINUM ELECTRIC 370-7545

MAIL ADDRESS  
190 DUNONIA UNIT F

CITY  
CAMPBELL, CA ZIP  
STATE  
LICENSE # 136788 C-10 TOWN  
LICENSE 1382

**NOTICE:**

1. SIGNS ARE REGULATED, SEE PLANNING DEPT.
2. OUTDOOR LIGHTS ARE REGULATED AGAINST SHINING  
ON OTHER PROPERTIES, AND PUBLIC RIGHT-OF-WAYS  
SHOESTRING LIGHTING NOT PERMITTED.

GROUP USE ZONE PROCESSED BY

### INSPECTION RECORD

### VALIDATION

5310A111 09/13/9010AM. 41.00  
16:01

### APPROVALS

	DATE	INSPECTOR'S SIG
CONDUIT	9/14/90	
ROUGH WIRING	9/14/90	
SERVICE EQUIP.	9/14/90	
FIXTURES	9/14/90	
GROUNDING	9/14/90	
UTILITY CO. NOTIFIED	9/14/90	
FINAL	9/14/90	

Figure 11.

**TOWN OF LOS GATOS  
BUILDING INSPECTION DEPARTMENT**

Permit Number: B98-000206

Description: REPAIR & REPLACE SHEETROCK, INSULATE EXTERIOR WALL

Building Address:	14340 BROWNS LN	Status...: ISSUED
.....	VADASZ PETER MIKLOS & CATHLEEN	Applied.: 03/11/1998
Address.....:	14340 BROWNS LN	Approved: 03/11/1998
City.....:	LOS GATOS CA	Issued..: 03/11/1998
Actor.....:	OWNER/BUILDER	Expires.: 09/07/1998
Ense.....:	000000	
ress.....:	SAME	

Business Lic...:

Eng\Design...:

Ense.....:

ress.....:

Y.....:

tion/.....:

10,000.00

Sq.Ft.....	Livable Sq.Ft.:		
Code.....	Bldg Count:	001	Unit Count: 000
*****	*****	*****	*****
Issuance.: 25.00	Park Tax.....: .00		
ng Permit.: 163.00	Planning Plan Ck.: .00		
24.....: .00	Micro Planning...: .00		
c Tax.....: 1.00	Storm Drain Eng.: .00		
Check.....: 105.95	Road Impact Fee.: 36.99		
Building..: .00	Computer Services: 6.52		
duction Tax.: .00	Electrical Fee...: .00		
y Tax.....: .00	Plumbing Fee....: .00		
n Updt...: .00	Mechanical Fee...: .00		
*****	*****	*****	*****
Total Calculated Fees: 301.47			
Total Additional Fees: .00			
Total Fees Due.....: 301.47			
Total Payments.....: .00			
BALANCE DUE.....: 301.47			

**CONTRACTOR'S DECLARATION**

I declare that I am properly licensed by the State of California Contractors License Law.

OR B

**COMPENSATION DECLARATION**

I affirm that I have a policy of Worker's Compensation Insurance. A certified copy of a certificate of that is herewith furnished, and on file with the Town. I further affirm that I shall keep the insurance in effect the job.

**OP OF EXEMPTION FROM WORKER'S COMPENSATION INSURANCE**

I declare that in the performance of the work for which this permit is issued, I shall not employ any person in any capacity, subject to the Worker's Compensation Laws of the State of California.

**ON OF PERMIT ISSUANCE**

I have read this application and state that the above information is correct. I agree to comply with all Local and State Laws relating to building construction, and hereby authorize representatives of this Town to inspect the above mentioned property for inspection purposes.

Figure 1

ermit Number: E98-000103

ork Description: ELEC FOR REWIRING

uilding Address: 14340 BROWNS LN  
 Owner.....: VADASZ PETER MIKLOS & CATHLEEN  
 Address.....: 14340 BROWNS LN  
 City.....: LOS GATOS CA  
 Zip.....: 95030  
 Contractor.....: OWNER/BUILDER  
 License.....: 000000  
 Address.....: SAME  
 City.....:  
 Zip.....:  
 Business Lic...:

New Residence: --Square Footage--  
 Remodel: Commercial:

\*\*\*\*\* PERMIT FEES \*\*\*\*\*

Permit Issuance.....:	25.00
Plan Check Fee.....:	16.81
New Resident.....:	.00
Remodel.....:	.00
Commercial.....:	.00
Detail Electrical Fee:	67.25

\*\*\*\*\* \*\*\*\*\*

Total Calculated Fees:	109.06
Total Additional Fees:	.00
Total Fees Due.....:	109.06
Total Payments.....:	.00
BALANCE DUE.....:	109.06

STRUCTOR'S DECLARATION  
 I certify that I am properly licensed by the State of California Contractors license law.  
 Signature X \_\_\_\_\_

WORKER'S COMPENSATION DECLARATION  
 I hereby affirm that I have a policy of Worker's Compensation insurance. A certified copy of a certificate of that insurance is herewith furnished, and on file with the Town. I further affirm that I shall keep the insurance in effect throughout the job.  
 Signature X \_\_\_\_\_

CERTIFICATE OF EXEMPTION FROM WORKER'S COMPENSATION INSURANCE  
 I certify that in the performance of the work for which this permit is issued, I shall not employ any person in any manner so as to become subject to the Worker's Compensation Laws of the State of California.  
 Signature X \_\_\_\_\_ *Cathy Vedas*

IFICATION OF PERMIT ISSUANCE  
 I certify that I have read this application and state that the above information is correct. I agree to comply with all ordinances and State Laws relating to building construction, and hereby authorize representatives of this Town to inspect upon the above mentioned property for inspection purposes.  
 Signature X \_\_\_\_\_ *Cathy Vedas*

NOTICE:  
 1. Signs are regulated, See Planning Dept. for requirements  
 2. Outdoor lights are regulated against shining on other properties, shoestring lighting is not permitted.

# Residential Remodel & Addition

BROWNS 640622

Figure 1.

370

Permit Number: P98-000105	Permit Number: M98-000075																									
Work Description: PLUM TO REMODEL FURNACE REPLACE OLD PLUM	Work Description: MICH FOR FURNANCE																									
Building Address: 14340 BROWNS LN Owner.....: VADASZ PETER MIKLOS & CATHLEEN Address.....: 14340 BROWNS LN City.....: LOS GATOS CA Zip.....: 95030 Contractor.....: OWNER/BUILDER License.....: 000000 Address.....: SAME City.....: Zip.....: Business Lic...:	Building Address: 14340 BROWNS LN Owner.....: VADASZ PETER MIKLOS & CATHLEEN Address.....: 14340 BROWNS LN City.....: LOS GATOS CA Zip.....: 95030 Contractor.....: OWNER/BUILDER License.....: 000000 Address.....: SAME City.....: Zip.....: Business Lic...:																									
Status...: ISSUED. Applied.: 03/11/1998 Approved: 03/11/1998 Issued.: 03/11/1998 Expires.: 09/07/1998	Status...: ISSUED. Applied.: 03/11/1998 Approved: 03/11/1998 Issued.: 03/11/1998 Expires.: 09/07/1998																									
<p><b>--Square Footage--</b></p> <table border="0"> <tr> <td>New Residence:</td> <td>Remodel:</td> <td>Commercial:</td> </tr> </table> <p>***** PERMIT FEES *****</p> <table border="0"> <tr> <td>Permit Issuance.....</td> <td>25.00</td> </tr> <tr> <td>Plan Check Fee.....</td> <td>13.00</td> </tr> <tr> <td>New Residential.....</td> <td>.00</td> </tr> <tr> <td>Remodel.....</td> <td>.00</td> </tr> <tr> <td>Commercial.....</td> <td>.00</td> </tr> <tr> <td>Detail Plumbing Fee..</td> <td>52.00</td> </tr> <tr> <td> Total Calculated Fees:</td> <td>90.00</td> </tr> <tr> <td>Total Additional Fees:</td> <td>.00</td> </tr> <tr> <td>Total Fees Due.....</td> <td>90.00</td> </tr> <tr> <td>Total Payments.....</td> <td>.00</td> </tr> <tr> <td>BALANCE DUE.....</td> <td>90.00</td> </tr> </table> <p>CONTRACTOR'S DECLARATION I certify that I am properly licensed by the State of California Contractors license law. Signature X</p> <p>COMPLETE A or B</p> <p>WORKER'S COMPENSATION DECLARATION I hereby affirm that I have a policy of Worker's Compensation insurance. A certified copy of a certificate of that insurance is herewith furnished, and on file with the Town. I further affirm that I shall keep the insurance in effect throughout the job. Signature X</p> <p>CERTIFICATE OF EXEMPTION FROM WORKER'S COMPENSATION INSURANCE I certify that in the performance of the work for which this permit is issued, I shall not employ any person in any manner so as to become subject to the Worker's Compensation laws of the State of California. Signature X</p> <p>CERTIFICATION OF PERMIT ISSUANCE I certify that I have read this application and state that the above information is correct. I agree to comply with all ordinances and State laws relating to building construction, and hereby authorize representatives of this Town to enter upon the above mentioned property for inspection purposes. Signature X</p> <p>NOTICE: All new mechanical equipment shall be screened and the screening shall match the building in terms of material and color. Noise levels from the equipment shall not exceed what is permitted by the Town of Los Gatos.</p>		New Residence:	Remodel:	Commercial:	Permit Issuance.....	25.00	Plan Check Fee.....	13.00	New Residential.....	.00	Remodel.....	.00	Commercial.....	.00	Detail Plumbing Fee..	52.00	 Total Calculated Fees:	90.00	Total Additional Fees:	.00	Total Fees Due.....	90.00	Total Payments.....	.00	BALANCE DUE.....	90.00
New Residence:	Remodel:	Commercial:																								
Permit Issuance.....	25.00																									
Plan Check Fee.....	13.00																									
New Residential.....	.00																									
Remodel.....	.00																									
Commercial.....	.00																									
Detail Plumbing Fee..	52.00																									
 Total Calculated Fees:	90.00																									
Total Additional Fees:	.00																									
Total Fees Due.....	90.00																									
Total Payments.....	.00																									
BALANCE DUE.....	90.00																									
<p><b>--Square Footage--</b></p> <table border="0"> <tr> <td>New Residence:</td> <td>Remodel:</td> <td>Commercial:</td> </tr> </table> <p>***** PERMIT FEES *****</p> <table border="0"> <tr> <td>Permit Issuance.....</td> <td>25.00</td> </tr> <tr> <td>Plan Check Fee.....</td> <td>10.25</td> </tr> <tr> <td>New Residential.....</td> <td>.00</td> </tr> <tr> <td>Remodel.....</td> <td>.00</td> </tr> <tr> <td>Commercial.....</td> <td>.00</td> </tr> <tr> <td>Detail Mechanical Fee:</td> <td>41.00</td> </tr> <tr> <td> Total Calculated Fees:</td> <td>76.25</td> </tr> <tr> <td>Total Additional Fees:</td> <td>.00</td> </tr> <tr> <td>Total Fees Due.....</td> <td>76.25</td> </tr> <tr> <td>Total Payments.....</td> <td>.00</td> </tr> <tr> <td>BALANCE DUE.....</td> <td>76.25</td> </tr> </table> <p>CONTRACTOR'S DECLARATION I certify that I am properly licensed by the State of California Contractors license law. Signature X</p> <p>COMPLETE A or B</p> <p>WORKER'S COMPENSATION DECLARATION A I hereby affirm that I have a policy of Worker's Compensation insurance. A certified copy of a certificate of that insurance is herewith furnished, and on file with the Town. I further affirm that I shall keep the insurance in effect throughout the job. Signature X</p> <p>CERTIFICATE OF EXEMPTION FROM WORKER'S COMPENSATION INSURANCE B I certify that in the performance of the work for which this permit is issued, I shall not employ any person in any manner so as to become subject to the Worker's Compensation laws of the State of California. Signature X</p> <p>CERTIFICATION OF PERMIT ISSUANCE I certify that I have read this application and state that the above information is correct. I agree to comply with all Town ordinances and State laws relating to building construction, and hereby authorize representatives of this Town to enter upon the above mentioned property for inspection purposes. Signature X</p> <p>NOTICE: All new mechanical equipment shall be screened and the screening shall match the building in terms of material and color. Noise levels from the equipment shall not exceed what is permitted by the Town of Los Gatos.</p>		New Residence:	Remodel:	Commercial:	Permit Issuance.....	25.00	Plan Check Fee.....	10.25	New Residential.....	.00	Remodel.....	.00	Commercial.....	.00	Detail Mechanical Fee:	41.00	 Total Calculated Fees:	76.25	Total Additional Fees:	.00	Total Fees Due.....	76.25	Total Payments.....	.00	BALANCE DUE.....	76.25
New Residence:	Remodel:	Commercial:																								
Permit Issuance.....	25.00																									
Plan Check Fee.....	10.25																									
New Residential.....	.00																									
Remodel.....	.00																									
Commercial.....	.00																									
Detail Mechanical Fee:	41.00																									
 Total Calculated Fees:	76.25																									
Total Additional Fees:	.00																									
Total Fees Due.....	76.25																									
Total Payments.....	.00																									
BALANCE DUE.....	76.25																									

TOWN OF LOS GATOS  
OWNER-BUILDER VERIFICATION

**ATTENTION OWNER-BUILDERS!**

IF YOU PLAN TO IMPROVE YOUR PROPERTY AND EMPLOY PERSONS OTHER THAN YOUR IMMEDIATE FAMILY, THE FOLLOWING INFORMATION WILL BE OF BENEFIT TO YOU. STATE AND FEDERAL LAWS REQUIRE THAT YOU:

1. REGISTER WITH THE STATE AND FEDERAL GOVERNMENTS AS AN EMPLOYER.
2. WITHHOLD AND REMIT INCOME TAX FOR EACH EMPLOYEE.
3. PAY SOCIAL SECURITY COSTS ON EACH EMPLOYEE.
4. WITHHOLD AND REMIT SOCIAL SECURITY COSTS ON EACH EMPLOYEE.
5. PAY WORKER'S COMPENSATION INSURANCE COSTS ON EACH EMPLOYEE.
6. WITHHOLD AND REMIT DISABILITY INSURANCE COSTS FOR EACH EMPLOYEE.
7. PAY UNEMPLOYMENT INSURANCE COSTS ON EACH EMPLOYEE.

YOU MAY CONSTRUCT IMPROVEMENTS FOR SALE ONLY UNDER SPECIFIC, LIMITED CONDITIONS.

YOU MAY CONSTRUCT IMPROVEMENTS FOR RENTAL-OCCUPANCY ONLY UNDER SPECIFIC, LIMITED CONDITIONS.

YOU MAY SUBCONTRACT PORTIONS OF THE CONSTRUCTION TO ANY PERSON OR FIRM, BUT THEY MUST BE LICENSED BY THE STATE OF CALIFORNIA.

INFORMATION ABOUT INSURANCE, LIEN LAWS, AND OTHER CONSTRUCTION MATTERS MAY BE OBTAINED FROM THE CONTRACTORS STATE LICENSE BOARD AND VARIOUS BUSINESS AND TRADE ASSOCIATIONS.

Please complete and return this information at your earliest opportunity to avoid unnecessary delay in processing and issuing your Building Permit.

1. I personally plan to provide the major labor and materials for construction of the proposed property improvement:  or   
(yes)  (no)
2. I have signed an application for a Building permit for the proposed work:  
 or   
(yes)  (no)

I AGREE TO CHECK THAT EACH SUBCONTRACTOR HAS A VALID TOWN OF LOS GATOS BUSINESS LICENSE BEFORE THEY BEGIN WORK. (YOU MAY VERIFY BUSINESS LICENSE STATUS WITH THE FINANCE DEPARTMENT AT 354-6835).

*Cathy Vadasz*  
(SIGNATURE)

*3-11-98*  
(DATE)

Property Owner: Vadasz  
Address: 14340 Brown  
(Of job site)

COMMUNITY DEVELOPMENT  
PLANNING DIVISION  
APPROVED

7/24/2025

## PLAN REVIEW APPROVAL

07.31.2025

G2.1

SCALE AS INDICATED

0/12/2023 3:45:50 PM

THESE PLANS HAVE BEEN APPROVED AS SHOWN. ANY MODIFICATION TO WHAT HAS BEEN PROPOSED OR TO WHAT IS SHOWN AS EXISTING MAY REQUIRE A SEPARATE APPROVAL.







California

# 2022 CALIFORNIA GREEN BUILDING STANDARDS CODE

## RESIDENTIAL MANDATORY MEASURES, SHEET 2 (January 2023)

REVIEWED

FOR

CODE COMPLIANCE

Jul 25, 2025

INTERWEST CONSULTING GROUP

YES  
NOT APPLICABLE  
RESPONSIBLE PARTY (i.e. ARCHITECT, ENGINEER,  
OWNER, CONTRACTOR, INSPECTOR ETC.)

Y N/A RESPON. PARTY		<p><b>MAXIMUM INCREMENTAL REACTIVITY (MIR).</b> The maximum change in weight of ozone formed by adding a compound to the "Base Reactant Organic Gas (ROG) Mixture" per weight of compound added, expressed to hundredths of a gram (g O<sub>3</sub>/g ROC). Note: MIR values for individual compounds and hydrocarbon solvents are specified in CCR, Title 17, Sections 94700 and 94701.</p> <p><b>MOISTURE CONTENT.</b> The weight of the water in wood expressed in percentage of the weight of the oven-dry wood.</p> <p><b>PRODUCT-WEIGHTED MIR (PVMIR).</b> The sum of all weighted-MIR for all ingredients in a product subject to this article. The PVMIR is the total product reactivity expressed to hundredths of a gram of ozone formed per gram of product (excluding container and packaging). Note: PVMIR is calculated according to equations found in CCR, Title 17, Section 94521 (a).</p> <p><b>REACTIVE ORGANIC COMPOUND (ROC).</b> Any compound that has the potential, once emitted, to contribute to ozone formation in the troposphere.</p> <p><b>VOC.</b> A volatile organic compound (VOC) broadly defined as a chemical compound based on carbon chains or rings with vapor pressures greater than 0.1 millimeters of mercury at room temperature. These compounds typically contain hydrogen and may contain oxygen, nitrogen and other elements. See CCR Title 17, Section 94508(a).</p> <p><b>4.503 FIREPLACES</b></p> <p><b>4.503.1 GENERAL.</b> Any installed gas fireplace shall be a direct-vent sealed-combustion type. Any installed woodstove or pellet stove shall comply with U.S. EPA New Source Performance Standards (NSPS) emission limits as applicable, and shall have a permanent label indicating they are certified to meet the emission limits. Woodstoves, pellet stoves and fireplaces shall also comply with applicable local ordinances.</p> <p><b>4.504 POLLUTANT CONTROL</b></p> <p><b>4.504.1 COVERING OF DUCT OPENINGS &amp; PROTECTION OF MECHANICAL EQUIPMENT DURING CONSTRUCTION.</b> At the time of rough installation, during storage on the construction site and until final startup of the heating, cooling and ventilating equipment, all duct and other related air distribution component openings shall be covered with tape, plastic, sheet metal or other methods acceptable to the enforcing agency to reduce the amount of water, dust or debris which may enter the system.</p> <p><b>4.504.2 FINISH MATERIAL POLLUTANT CONTROL.</b> Finish materials shall comply with this section.</p> <p><b>4.504.2.1 Adhesives, Sealants and Caulks.</b> Adhesives, sealant and caulk used on the project shall meet the requirements of the following standards unless more stringent local or regional air pollution or air quality management district rules apply:</p> <ol style="list-style-type: none"> <li>1. Adhesives, adhesive bonding primers, adhesive primers, sealants, sealant primers and caulk shall comply with local or regional air pollution control or air quality management district rules where applicable or SCAQMD Rule 1168 VOCs, as shown in Table 4.504.1 or 4.504.2, as applicable. Comply with SCAQMD Rule 1168 provisions on the use of certain toxic compounds (chloroform, ethylene dichloride, methyl chloride, perchloroethylene and trichloroethylene), except for aerosol products, as specified in Subsection 2 below.</li> <li>2. Aerosol adhesives, and smaller unit sizes of adhesives, and sealant or caulk compounds (in units of product, less packaging, which do not weigh more than 1 pound and do not consist of more than 16 fluid ounces) shall comply with statewide VOC standards and other requirements, including prohibitions on use of certain toxic compounds, of California Code of Regulations, Title 17, commencing with section 94507.</li> </ol> <p><b>4.504.2.2 Paints and Coatings.</b> Architectural paints and coatings shall comply with VOC limits in Table 1 of the ARB Architectural Suggested Control Measure, as shown in Table 4.504.3, unless more stringent local limits apply. The VOC content limit for coatings that do not meet the definitions for the specialty coatings categories listed in Table 4.504.3 shall be determined by classifying the coating as a Flat, Nonflat or Nonflat-High Gloss coating, based on its gloss, as defined in subsections 4.21, 4.36, and 4.37 of the 2007 California Air Resources Board, Suggested Control Measure, and the corresponding Flat, Nonflat or Nonflat-High Gloss VOC limit in Table 4.504.3 shall apply.</p> <p><b>4.504.2.3 Aerosol Paints and Coatings.</b> Aerosol paints and coatings shall meet the Product-weighted MIR limits for ROC in Section 94522(a)(2) and other requirements, including prohibitions on use of certain toxic compounds and ozone depleting substances, in Sections 94522(e)(1) and (f)(1) of California Code of Regulations, Title 17, commencing with Section 94520; and in areas under the jurisdiction of the Bay Area Air Quality Management District additionally comply with the percent VOC by weight of product limits of Regulation 8, Rule 49.</p> <p><b>4.504.2.4 Verification.</b> Verification of compliance with this section shall be provided at the request of the enforcing agency. Documentation may include, but is not limited to, the following:           <ol style="list-style-type: none"> <li>1. Manufacturer's product specification.</li> <li>2. Field verification of on-site product containers.</li> </ol> </p> <p><b>TABLE 4.504.1 - ADHESIVE VOC LIMIT<sub>1,2</sub></b> (Less Water and Less Exempt Compounds in Grams per Liter)</p> <table border="1"> <thead> <tr> <th>ARCHITECTURAL APPLICATIONS</th> <th>VOC LIMIT</th> </tr> </thead> <tbody> <tr><td>INDOOR CARPET ADHESIVES</td><td>50</td></tr> <tr><td>CARPET PAD ADHESIVES</td><td>50</td></tr> <tr><td>OUTDOOR CARPET ADHESIVES</td><td>150</td></tr> <tr><td>WOOD FLOORING ADHESIVES</td><td>100</td></tr> <tr><td>RUBBER FLOOR ADHESIVES</td><td>60</td></tr> <tr><td>SUBFLOOR ADHESIVES</td><td>50</td></tr> <tr><td>CERAMIC TILE ADHESIVES</td><td>65</td></tr> <tr><td>VCT &amp; ASPHALT TILE ADHESIVES</td><td>50</td></tr> <tr><td>DRYWALL &amp; PANEL ADHESIVES</td><td>50</td></tr> <tr><td>COVE BASE ADHESIVES</td><td>50</td></tr> <tr><td>MULTIPURPOSE CONSTRUCTION ADHESIVE</td><td>70</td></tr> <tr><td>STRUCTURAL GLAZING ADHESIVES</td><td>100</td></tr> <tr><td>SINGLE-PLY ROOF MEMBRANE ADHESIVES</td><td>250</td></tr> <tr><td>OTHER ADHESIVES NOT LISTED</td><td>50</td></tr> <tr><td><b>SPECIALTY APPLICATIONS</b></td><td></td></tr> <tr><td>PVC WELDING</td><td>510</td></tr> <tr><td>CPVC WELDING</td><td>490</td></tr> <tr><td>ABS WELDING</td><td>325</td></tr> <tr><td>PLASTIC CEMENT WELDING</td><td>250</td></tr> <tr><td>ADHESIVE PRIMER FOR PLASTIC</td><td>550</td></tr> <tr><td>CONTACT ADHESIVE</td><td>80</td></tr> <tr><td>SPECIAL PURPOSE CONTACT ADHESIVE</td><td>250</td></tr> <tr><td>STRUCTURAL WOOD MEMBER ADHESIVE</td><td>140</td></tr> <tr><td>TOP &amp; TRIM ADHESIVE</td><td>250</td></tr> <tr><td><b>SUBSTRATE SPECIFIC APPLICATIONS</b></td><td></td></tr> <tr><td>METAL TO METAL</td><td>30</td></tr> <tr><td>PLASTIC FOAMS</td><td>50</td></tr> <tr><td>POROUS MATERIAL (EXCEPT WOOD)</td><td>50</td></tr> <tr><td>WOOD</td><td>30</td></tr> <tr><td>FIBERGLASS</td><td>80</td></tr> </tbody> </table> <p>1. IF AN ADHESIVE IS USED TO BOND DISSIMILAR SUBSTRATES TOGETHER, THE ADHESIVE WITH THE HIGHEST VOC CONTENT SHALL BE ALLOWED.</p> <p>2. FOR ADDITIONAL INFORMATION REGARDING METHODS TO MEASURE THE VOC CONTENT SPECIFIED IN THIS TABLE, SEE SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT RULE 1168.</p> <p><b>TABLE 4.504.2 - SEALANT VOC LIMIT</b> (Less Water and Less Exempt Compounds in Grams per Liter)</p> <table border="1"> <thead> <tr> <th>SEALANTS</th> <th>VOC LIMIT</th> </tr> </thead> <tbody> <tr><td>ARCHITECTURAL</td><td>250</td></tr> <tr><td>MARINE DECK</td><td>760</td></tr> <tr><td>NONMEMBRANE ROOF</td><td>300</td></tr> <tr><td>ROADWAY</td><td>250</td></tr> <tr><td>SINGLE-PLY ROOF MEMBRANE</td><td>450</td></tr> <tr><td>OTHER</td><td>420</td></tr> <tr><td><b>SEALANT PRIMERS</b></td><td></td></tr> <tr><td>ARCHITECTURAL</td><td>250</td></tr> <tr><td>NON-POROUS</td><td>250</td></tr> <tr><td>POROUS</td><td>775</td></tr> <tr><td>MODIFIED BITUMINOUS</td><td>500</td></tr> <tr><td>MARINE DECK</td><td>760</td></tr> <tr><td>OTHER</td><td>750</td></tr> </tbody> </table> <p><b>TABLE 4.504.3 - VOC CONTENT LIMITS FOR ARCHITECTURAL COATINGS<sub>2,3</sub></b> (GRAMS OF VOC PER LITER OF COATING, LESS WATER &amp; LESS EXEMPT COMPOUNDS)</p> <table border="1"> <thead> <tr> <th>COATING CATEGORY</th> <th>VOC LIMIT</th> </tr> </thead> <tbody> <tr><td>FLAT COATINGS</td><td>50</td></tr> <tr><td>NON-FLAT COATINGS</td><td>100</td></tr> <tr><td>NONFLAT-HIGH GLOSS COATINGS</td><td>150</td></tr> <tr><td><b>SPECIALTY COATINGS</b></td><td></td></tr> <tr><td>ALUMINUM ROOF COATINGS</td><td>400</td></tr> <tr><td>BASEMENT SPECIALTY COATINGS</td><td>400</td></tr> <tr><td>BITUMINOUS ROOF COATINGS</td><td>50</td></tr> <tr><td>BITUMINOUS ROOF PRIMERS</td><td>350</td></tr> <tr><td>BOND BREAKERS</td><td>350</td></tr> <tr><td>CONCRETE CURING COMPOUNDS</td><td>350</td></tr> <tr><td>CONCRETE/MASONRY SEALERS</td><td>100</td></tr> <tr><td>DRIVEWAY SEALERS</td><td>50</td></tr> <tr><td>DRY FOG COATINGS</td><td>150</td></tr> <tr><td>FAUX FINISHING COATINGS</td><td>350</td></tr> <tr><td>FIRE RESISTIVE COATINGS</td><td>350</td></tr> <tr><td>FLOOR COATINGS</td><td>100</td></tr> <tr><td>FORM-RELEASE COMPOUNDS</td><td>250</td></tr> <tr><td>GRAPHIC ARTS COATINGS (SIGN PAINTS)</td><td>500</td></tr> <tr><td>HIGH TEMPERATURE COATINGS</td><td>420</td></tr> <tr><td>INDUSTRIAL MAINTENANCE COATINGS</td><td>250</td></tr> <tr><td>LOW SOLIDS COATINGS<sub>1</sub></td><td>120</td></tr> <tr><td>MAGNESITE CEMENT COATINGS</td><td>450</td></tr> <tr><td>MASTIC TEXTURE COATINGS</td><td>100</td></tr> <tr><td>METALLIC PIGMENTED COATINGS</td><td>500</td></tr> <tr><td>MULTICOLOR COATINGS</td><td>250</td></tr> <tr><td>PRETREATMENT WASH PRIMERS</td><td>420</td></tr> <tr><td>PRIMERS, SEALERS, &amp; UNDERCOATERS</td><td>100</td></tr> <tr><td>REACTIVE PENETRATING SEALERS</td><td>350</td></tr> <tr><td>RECYCLED COATINGS</td><td>250</td></tr> <tr><td>ROOF COATINGS</td><td>50</td></tr> <tr><td>RUST PREVENTATIVE COATINGS</td><td>250</td></tr> <tr><td>SHELLAC<sub>1</sub></td><td></td></tr> <tr><td>CLEAR</td><td>730</td></tr> <tr><td>OPAQUE</td><td>550</td></tr> <tr><td>SPECIALTY PRIMERS, SEALERS &amp; UNDERCOATERS</td><td>100</td></tr> <tr><td>STAINS</td><td>250</td></tr> <tr><td>STONE CONSOLIDANTS</td><td>450</td></tr> <tr><td>SWIMMING POOL COATINGS</td><td>340</td></tr> <tr><td>TRAFFIC MARKING COATINGS</td><td>100</td></tr> <tr><td>TUB &amp; TILE REFINISH COATINGS</td><td>420</td></tr> <tr><td>WATERPROOFING MEMBRANES</td><td>250</td></tr> <tr><td>WOOD COATINGS</td><td>275</td></tr> <tr><td>WOOD PRESERVATIVES</td><td>350</td></tr> <tr><td>ZINC-RICH PRIMERS</td><td>340</td></tr> </tbody> </table> <p>1. GRAMS OF VOC PER LITER OF COATING, INCLUDING WATER &amp; EXEMPT COMPOUNDS</p> <p>2. THE SPECIFIED LIMITS REMAIN IN EFFECT UNLESS REVISED LIMITS ARE LISTED IN SUBSEQUENT COLUMNS IN THE TABLE.</p> <p>3. VALUES IN THIS TABLE ARE DERIVED FROM THOSE SPECIFIED BY THE CALIFORNIA AIR RESOURCES BOARD, ARCHITECTURAL COATINGS SUGGESTED CONTROL MEASURE, FEB. 1, 2008. MORE INFORMATION IS AVAILABLE FROM THE AIR RESOURCES BOARD.</p> <p><b>TABLE 4.504.5 - FORMALDEHYDE LIMITS</b> (MAXIMUM FORMALDEHYDE EMISSIONS IN PARTS PER MILLION)</p> <table border="1"> <thead> <tr> <th>PRODUCT</th> <th>CURRENT LIMIT</th> </tr> </thead> <tbody> <tr><td>HARDWOOD PLYWOOD VENEER CORE</td><td>0.05</td></tr> <tr><td>HARDWOOD PLYWOOD COMPOSITE CORE</td><td>0.05</td></tr> <tr><td>PARTICLE BOARD</td><td>0.09</td></tr> <tr><td>MEDIUM DENSITY FIBERBOARD</td><td>0.11</td></tr> <tr><td>THIN MEDIUM DENSITY FIBERBOARD<sub>2</sub></td><td>0.13</td></tr> </tbody> </table> <p>1. VALUES IN THIS TABLE ARE DERIVED FROM THOSE SPECIFIED BY THE CALIF. AIR RESOURCES BOARD, AIR TOXICS CONTROL MEASURE FOR COMPOSITE WOOD AS TESTED IN ACCORDANCE WITH ASTM E 1333. FOR ADDITIONAL INFORMATION, SEE CALIF. CODE OF REGULATIONS, TITLE 17, SECTIONS 93120 THROUGH 93120.12.</p> <p>2. THIN MEDIUM DENSITY FIBERBOARD HAS A MAXIMUM THICKNESS OF 5/16" (8 MM).</p> <p><b>CHAPTER 7</b> <b>INSTALLER &amp; SPECIAL INSPECTOR QUALIFICATIONS</b></p> <p><b>702 QUALIFICATIONS</b></p> <p><b>702.1 INSTALLER TRAINING.</b> HVAC system installers shall be trained and certified in the proper installation of HVAC systems including ducts and equipment by a nationally or regionally recognized training or certification program. Uncertified persons may perform HVAC installations when under the direct supervision and responsibility of a person trained and certified to install HVAC systems or contractor licensed to install HVAC systems. Examples of acceptable HVAC training and certification programs include but are not limited to the following:</p> <ol style="list-style-type: none"> <li>1. State certified apprenticeship programs.</li> <li>2. Public utility training programs.</li> <li>3. Training programs sponsored by trade, labor or statewide energy consulting or verification organizations.</li> <li>4. Programs sponsored by manufacturing organizations.</li> <li>5. Other programs acceptable to the enforcing agency.</li> </ol> <p><b>702.2 SPECIAL INSPECTION [HCD].</b> When required by the enforcing agency, the owner or the responsible entity acting as the owner's agent shall employ one or more special inspectors to provide inspection or other duties necessary to substantiate compliance with this code. Special inspectors shall demonstrate competence to the satisfaction of the enforcing agency for the particular type of inspection or task to be performed. In addition to other certifications or qualifications acceptable to the enforcing agency, the following certifications or education may be considered by the enforcing agency when evaluating the qualifications of a special inspector:</p> <ol style="list-style-type: none"> <li>1. Certification by a national or regional green building program or standard publisher.</li> <li>2. Certification by a statewide energy consulting or verification organization, such as HERS raters, building performance contractors, and home energy auditors.</li> <li>3. Successive completion of a third party apprentice training program in the appropriate trade.</li> <li>4. Other programs acceptable to the enforcing agency.</li> </ol> <p><b>703 VERIFICATIONS</b></p> <p><b>703.1 DOCUMENTATION.</b> Documentation used to show compliance with this code shall include but is not limited to, construction documents, plans, specifications, builder or installer certifications, inspection reports, or other methods acceptable to the enforcing agency which demonstrate substantial conformance. When specific documentation or special inspection is necessary to verify compliance, that method of compliance will be specified in the appropriate section or identified applicable checklist.</p> <p><b>703.2 DOCUMENTATION.</b> Documentation used to show compliance with this code shall include but is not limited to, construction documents, plans, specifications, builder or installer certifications, inspection reports, or other methods acceptable to the enforcing agency which demonstrate substantial conformance. When specific documentation or special inspection is necessary to verify compliance, that method of compliance will be specified in the appropriate section or identified applicable checklist.</p> <p><b>COMMUNITY DEVELOPMENT PLANNING DIVISION APPROVED</b></p> <p>07/31/2025</p> <p>PLAN REVIEW APPROVAL</p> <p>07.31.2025</p> <p>TOWN OF LOS GATOS BUILDING DIVISION</p> <p><b>THESE PLANS HAVE BEEN APPROVED AS SHOWN, ANY MODIFICATION TO WHAT HAS BEEN PROPOSED OR TO WHAT IS SHOWN AS EXISTING MAY REQUIRE A SEPARATE APPROVAL</b></p> <p>G3.1</p>	ARCHITECTURAL APPLICATIONS	VOC LIMIT	INDOOR CARPET ADHESIVES	50	CARPET PAD ADHESIVES	50	OUTDOOR CARPET ADHESIVES	150	WOOD FLOORING ADHESIVES	100	RUBBER FLOOR ADHESIVES	60	SUBFLOOR ADHESIVES	50	CERAMIC TILE ADHESIVES	65	VCT & ASPHALT TILE ADHESIVES	50	DRYWALL & PANEL ADHESIVES	50	COVE BASE ADHESIVES	50	MULTIPURPOSE CONSTRUCTION ADHESIVE	70	STRUCTURAL GLAZING ADHESIVES	100	SINGLE-PLY ROOF MEMBRANE ADHESIVES	250	OTHER ADHESIVES NOT LISTED	50	<b>SPECIALTY APPLICATIONS</b>		PVC WELDING	510	CPVC WELDING	490	ABS WELDING	325	PLASTIC CEMENT WELDING	250	ADHESIVE PRIMER FOR PLASTIC	550	CONTACT ADHESIVE	80	SPECIAL PURPOSE CONTACT ADHESIVE	250	STRUCTURAL WOOD MEMBER ADHESIVE	140	TOP & TRIM ADHESIVE	250	<b>SUBSTRATE SPECIFIC APPLICATIONS</b>		METAL TO METAL	30	PLASTIC FOAMS	50	POROUS MATERIAL (EXCEPT WOOD)	50	WOOD	30	FIBERGLASS	80	SEALANTS	VOC LIMIT	ARCHITECTURAL	250	MARINE DECK	760	NONMEMBRANE ROOF	300	ROADWAY	250	SINGLE-PLY ROOF MEMBRANE	450	OTHER	420	<b>SEALANT PRIMERS</b>		ARCHITECTURAL	250	NON-POROUS	250	POROUS	775	MODIFIED BITUMINOUS	500	MARINE DECK	760	OTHER	750	COATING CATEGORY	VOC LIMIT	FLAT COATINGS	50	NON-FLAT COATINGS	100	NONFLAT-HIGH GLOSS COATINGS	150	<b>SPECIALTY COATINGS</b>		ALUMINUM ROOF COATINGS	400	BASEMENT SPECIALTY COATINGS	400	BITUMINOUS ROOF COATINGS	50	BITUMINOUS ROOF PRIMERS	350	BOND BREAKERS	350	CONCRETE CURING COMPOUNDS	350	CONCRETE/MASONRY SEALERS	100	DRIVEWAY SEALERS	50	DRY FOG COATINGS	150	FAUX FINISHING COATINGS	350	FIRE RESISTIVE COATINGS	350	FLOOR COATINGS	100	FORM-RELEASE COMPOUNDS	250	GRAPHIC ARTS COATINGS (SIGN PAINTS)	500	HIGH TEMPERATURE COATINGS	420	INDUSTRIAL MAINTENANCE COATINGS	250	LOW SOLIDS COATINGS <sub>1</sub>	120	MAGNESITE CEMENT COATINGS	450	MASTIC TEXTURE COATINGS	100	METALLIC PIGMENTED COATINGS	500	MULTICOLOR COATINGS	250	PRETREATMENT WASH PRIMERS	420	PRIMERS, SEALERS, & UNDERCOATERS	100	REACTIVE PENETRATING SEALERS	350	RECYCLED COATINGS	250	ROOF COATINGS	50	RUST PREVENTATIVE COATINGS	250	SHELLAC <sub>1</sub>		CLEAR	730	OPAQUE	550	SPECIALTY PRIMERS, SEALERS & UNDERCOATERS	100	STAINS	250	STONE CONSOLIDANTS	450	SWIMMING POOL COATINGS	340	TRAFFIC MARKING COATINGS	100	TUB & TILE REFINISH COATINGS	420	WATERPROOFING MEMBRANES	250	WOOD COATINGS	275	WOOD PRESERVATIVES	350	ZINC-RICH PRIMERS	340	PRODUCT	CURRENT LIMIT	HARDWOOD PLYWOOD VENEER CORE	0.05	HARDWOOD PLYWOOD COMPOSITE CORE	0.05	PARTICLE BOARD	0.09	MEDIUM DENSITY FIBERBOARD	0.11	THIN MEDIUM DENSITY FIBERBOARD <sub>2</sub>	0.13
			ARCHITECTURAL APPLICATIONS	VOC LIMIT																																																																																																																																																																																														
INDOOR CARPET ADHESIVES	50																																																																																																																																																																																																	
CARPET PAD ADHESIVES	50																																																																																																																																																																																																	
OUTDOOR CARPET ADHESIVES	150																																																																																																																																																																																																	
WOOD FLOORING ADHESIVES	100																																																																																																																																																																																																	
RUBBER FLOOR ADHESIVES	60																																																																																																																																																																																																	
SUBFLOOR ADHESIVES	50																																																																																																																																																																																																	
CERAMIC TILE ADHESIVES	65																																																																																																																																																																																																	
VCT & ASPHALT TILE ADHESIVES	50																																																																																																																																																																																																	
DRYWALL & PANEL ADHESIVES	50																																																																																																																																																																																																	
COVE BASE ADHESIVES	50																																																																																																																																																																																																	
MULTIPURPOSE CONSTRUCTION ADHESIVE	70																																																																																																																																																																																																	
STRUCTURAL GLAZING ADHESIVES	100																																																																																																																																																																																																	
SINGLE-PLY ROOF MEMBRANE ADHESIVES	250																																																																																																																																																																																																	
OTHER ADHESIVES NOT LISTED	50																																																																																																																																																																																																	
<b>SPECIALTY APPLICATIONS</b>																																																																																																																																																																																																		
PVC WELDING	510																																																																																																																																																																																																	
CPVC WELDING	490																																																																																																																																																																																																	
ABS WELDING	325																																																																																																																																																																																																	
PLASTIC CEMENT WELDING	250																																																																																																																																																																																																	
ADHESIVE PRIMER FOR PLASTIC	550																																																																																																																																																																																																	
CONTACT ADHESIVE	80																																																																																																																																																																																																	
SPECIAL PURPOSE CONTACT ADHESIVE	250																																																																																																																																																																																																	
STRUCTURAL WOOD MEMBER ADHESIVE	140																																																																																																																																																																																																	
TOP & TRIM ADHESIVE	250																																																																																																																																																																																																	
<b>SUBSTRATE SPECIFIC APPLICATIONS</b>																																																																																																																																																																																																		
METAL TO METAL	30																																																																																																																																																																																																	
PLASTIC FOAMS	50																																																																																																																																																																																																	
POROUS MATERIAL (EXCEPT WOOD)	50																																																																																																																																																																																																	
WOOD	30																																																																																																																																																																																																	
FIBERGLASS	80																																																																																																																																																																																																	
SEALANTS	VOC LIMIT																																																																																																																																																																																																	
ARCHITECTURAL	250																																																																																																																																																																																																	
MARINE DECK	760																																																																																																																																																																																																	
NONMEMBRANE ROOF	300																																																																																																																																																																																																	
ROADWAY	250																																																																																																																																																																																																	
SINGLE-PLY ROOF MEMBRANE	450																																																																																																																																																																																																	
OTHER	420																																																																																																																																																																																																	
<b>SEALANT PRIMERS</b>																																																																																																																																																																																																		
ARCHITECTURAL	250																																																																																																																																																																																																	
NON-POROUS	250																																																																																																																																																																																																	
POROUS	775																																																																																																																																																																																																	
MODIFIED BITUMINOUS	500																																																																																																																																																																																																	
MARINE DECK	760																																																																																																																																																																																																	
OTHER	750																																																																																																																																																																																																	
COATING CATEGORY	VOC LIMIT																																																																																																																																																																																																	
FLAT COATINGS	50																																																																																																																																																																																																	
NON-FLAT COATINGS	100																																																																																																																																																																																																	
NONFLAT-HIGH GLOSS COATINGS	150																																																																																																																																																																																																	
<b>SPECIALTY COATINGS</b>																																																																																																																																																																																																		
ALUMINUM ROOF COATINGS	400																																																																																																																																																																																																	
BASEMENT SPECIALTY COATINGS	400																																																																																																																																																																																																	
BITUMINOUS ROOF COATINGS	50																																																																																																																																																																																																	
BITUMINOUS ROOF PRIMERS	350																																																																																																																																																																																																	
BOND BREAKERS	350																																																																																																																																																																																																	
CONCRETE CURING COMPOUNDS	350																																																																																																																																																																																																	
CONCRETE/MASONRY SEALERS	100																																																																																																																																																																																																	
DRIVEWAY SEALERS	50																																																																																																																																																																																																	
DRY FOG COATINGS	150																																																																																																																																																																																																	
FAUX FINISHING COATINGS	350																																																																																																																																																																																																	
FIRE RESISTIVE COATINGS	350																																																																																																																																																																																																	
FLOOR COATINGS	100																																																																																																																																																																																																	
FORM-RELEASE COMPOUNDS	250																																																																																																																																																																																																	
GRAPHIC ARTS COATINGS (SIGN PAINTS)	500																																																																																																																																																																																																	
HIGH TEMPERATURE COATINGS	420																																																																																																																																																																																																	
INDUSTRIAL MAINTENANCE COATINGS	250																																																																																																																																																																																																	
LOW SOLIDS COATINGS <sub>1</sub>	120																																																																																																																																																																																																	
MAGNESITE CEMENT COATINGS	450																																																																																																																																																																																																	
MASTIC TEXTURE COATINGS	100																																																																																																																																																																																																	
METALLIC PIGMENTED COATINGS	500																																																																																																																																																																																																	
MULTICOLOR COATINGS	250																																																																																																																																																																																																	
PRETREATMENT WASH PRIMERS	420																																																																																																																																																																																																	
PRIMERS, SEALERS, & UNDERCOATERS	100																																																																																																																																																																																																	
REACTIVE PENETRATING SEALERS	350																																																																																																																																																																																																	
RECYCLED COATINGS	250																																																																																																																																																																																																	
ROOF COATINGS	50																																																																																																																																																																																																	
RUST PREVENTATIVE COATINGS	250																																																																																																																																																																																																	
SHELLAC <sub>1</sub>																																																																																																																																																																																																		
CLEAR	730																																																																																																																																																																																																	
OPAQUE	550																																																																																																																																																																																																	
SPECIALTY PRIMERS, SEALERS & UNDERCOATERS	100																																																																																																																																																																																																	
STAINS	250																																																																																																																																																																																																	
STONE CONSOLIDANTS	450																																																																																																																																																																																																	
SWIMMING POOL COATINGS	340																																																																																																																																																																																																	
TRAFFIC MARKING COATINGS	100																																																																																																																																																																																																	
TUB & TILE REFINISH COATINGS	420																																																																																																																																																																																																	
WATERPROOFING MEMBRANES	250																																																																																																																																																																																																	
WOOD COATINGS	275																																																																																																																																																																																																	
WOOD PRESERVATIVES	350																																																																																																																																																																																																	
ZINC-RICH PRIMERS	340																																																																																																																																																																																																	
PRODUCT	CURRENT LIMIT																																																																																																																																																																																																	
HARDWOOD PLYWOOD VENEER CORE	0.05																																																																																																																																																																																																	
HARDWOOD PLYWOOD COMPOSITE CORE	0.05																																																																																																																																																																																																	
PARTICLE BOARD	0.09																																																																																																																																																																																																	
MEDIUM DENSITY FIBERBOARD	0.11																																																																																																																																																																																																	
THIN MEDIUM DENSITY FIBERBOARD <sub>2</sub>	0.13																																																																																																																																																																																																	

# Construction Best Management Practices (BMPs)

## Materials, Waste, and Sediment Management



### Construction Entrances and Perimeter

- Establish and maintain effective perimeter controls, and stabilize all construction entrances and exits to sufficiently control erosion, sediment discharges and tracking of sediment offsite.
- Sweep or vacuum immediately any tracking of sediment offsite and secure sediment source to prevent further tracking. Never hose down streets or sidewalks.

### Non-Hazardous Materials and Dust Control

- Berm and cover stockpiles of sand, dirt or other construction material with tarps when rain is forecast or when they are not in use. Weigh down and secure tarps for wind protection.
- Keep materials off the ground (e.g., store bagged materials on wood pallets, store loose materials on tarps not pavement, etc.).
- Use captured water from other activities (e.g., testing fire lines) for dust control.
- Ensure dust control water doesn't leave site or discharge to storm drains. Only use enough to control dust. Contain and dispose of excess water properly.

### Hazardous Materials

- Label all hazardous materials and hazardous wastes (such as pesticides, paints, thinners, solvents, fuel, oil, and antifreeze) in accordance with City, County, State and Federal regulations.
- Store hazardous materials and wastes in watertight containers, store in appropriate secondary containment, and cover them at the end of every workday, during wet weather or when rain is forecast.
- Follow manufacturer's application instructions for hazardous materials and do not use more than necessary. Do not apply chemicals outdoors when rain is forecast within 24 hours.
- Arrange for appropriate disposal of all hazardous wastes. Have all pertinent Safety Data Sheets (i.e., SDS/MSDS/PSDS) onsite.

### Waste Management

- Inform trash-hauling contractors that you will accept only watertight dumpsters for onsite use. Repair/replace any dumpster that is not watertight or leaking.
- Cover and maintain dumpsters. Check frequently for leaks. Place dumpsters under roofs or cover with tarps or plastic sheeting secured around the outside of the dumpster. If the dumpster leaks, place a plastic liner underneath the dumpster to collect leaks. Never clean out a dumpster by hosing it down on the construction site – clean with dry methods, clean offsite or replace dumpster.
- Place portable toilets and hand wash stations away from storm drains. Make sure they are equipped with containment pans (secondary containment) and are in good working order. Check frequently for leaks.
- Dispose of all wastes and demolition debris properly per SDS and applicable regulations. Recycle or compost materials and wastes as feasible and appropriate, including solvents, water-based paints, vehicle fluids, broken asphalt and concrete, wood, and cleared vegetation.
- Dispose of liquid residues from paints, thinners, solvents, glues, and cleaning fluids as hazardous waste per SDS.
- Keep site free of litter (e.g., lunch items, water bottles, cigarette butts and plastic packaging).
- Prevent litter from uncovered loads by covering loads that are being transported to and from site.

## Equipment Management & Spill Control



### Vehicle and Equipment Maintenance

- Designate an area of the construction site equipped with appropriate BMPs, well away from creeks or storm drain inlets, for auto and equipment parking and storage.
- Perform major maintenance, repair jobs, and vehicle/equipment washing offsite.
- If refueling or vehicle maintenance must be done onsite, work in a bermed area away from storm drains and over a drip pan or drop cloths big enough to collect fluids. Recycle or dispose of fluids as hazardous waste.
- If vehicle or equipment cleaning must be done onsite, clean with water only in a bermed area that will not allow rinse water to run into gutters, streets, storm drains, or creeks.
- Do not clean vehicles or equipment onsite using soaps, solvents, degreasers, or steam cleaning equipment, and do not use diesel oil to lubricate equipment or parts onsite.

### Spill Prevention and Control

- Always keep spill cleanup materials (e.g., rags, absorbents, and cat litter) available at the construction site.
- Maintain all vehicles and heavy equipment. Inspect frequently for leaks. Use drip pans to catch leaks until repairs are made.
- Clean up leaks, drips and other spills immediately using dry cleanup methods whenever possible (absorbent materials, cat litter and/or rags) and dispose of cleanup materials properly.
- Sweep up spilled dry materials immediately. Never attempt to "wash them away" with water or bury them.

- Clean up spills on dirt areas by digging up and properly disposing of contaminated soil.
- Report significant spills to the appropriate local spill response agencies immediately. If the spill poses a significant hazard to human health and safety, property or the environment, report it to the State Office of Emergency Services at (800) 852-7550 (24 hours).

## Earthmoving



### Grading and Earthwork

- Schedule grading and excavation work during dry weather.
- Prevent sediment from migrating offsite and protect storm drain inlets, drainage courses and creeks by installing and maintaining appropriate BMPs tailored to the site's specific characteristics and conditions. Examples of such BMPs may include silt fences, gravel bags, fiber rolls, temporary swales, compost socks, etc. Ensure that BMPs are installed in accordance with manufacturer's specifications and properly maintained throughout the duration of construction activities.
- Stabilize all denuded areas and install and maintain temporary erosion controls (such as erosion control fabric or bonded fiber matrix) until vegetation is established.
- Remove existing vegetation only when necessary. Plant temporary vegetation to prevent erosion on slopes or in areas where construction is not immediately planned.
- Keep excavated soil and/or transfer it to dump trucks, onsite, not in the streets.
- Ensure all subcontractors working onsite are implementing appropriate BMPs.


### Contaminated Soils

- If any of the following conditions are observed, test for contamination and contact the [Regional Water Quality Control Board](#) and the local agency:
  - 1) Unusual soil conditions, discoloration, or odor.
  - 2) Abandoned underground tanks.
  - 3) Abandoned wells.
  - 4) Buried barrels, debris, or trash.
- If the above conditions are observed, document any signs of potential contamination, clearly mark areas and fence/tape them off so they are not disturbed by construction activities.

### Landscaping

- Protect stockpiled landscaping materials from wind and rain by storing them under tarps year-round.
- Stack bagged material on pallets and under cover.
- Discontinue application of any erodible landscape material within 2 days before a forecast rain event or during wet weather.
- Store materials onsite, not in the street.

## Concrete Management & Dewatering



### Concrete Management

- Store both dry and wet concrete-related materials under cover, protected from rainfall and runoff and away from storm drains or creeks. Store materials off the ground on pallets. Protect dry materials from wind.
- Avoid pouring concrete in wet weather or when rainfall is imminent to prevent concrete that has not cured from contacting stormwater runoff.
- Wash out concrete equipment/mixers/trucks offsite, or onsite only in designated washout containers/areas where the water will flow into a temporary lined waste pit and in a manner that will prevent leaching into the underlying soils. (See CASQA Construction Stormwater BMP Handbook for temporary concrete washout facility details).
- Do not wash sweepings from exposed aggregate concrete into the street or storm drain. Collect and return sweepings to aggregate base stockpile or dispose properly.
- Make sure that construction waste (e.g., concrete, stucco, cement wastewater, or residual materials) is collected, removed, and disposed of only at authorized disposal areas. Do not dispose of construction waste in storm drains, ditches, streets, creeks, dirt areas, or the sanitary sewer.

### Dewatering

- Discharges of groundwater or captured runoff from dewatering operations must be properly managed and disposed. When possible, send dewatering discharge to landscaped area or sanitary sewer. If discharging to the sanitary sewer, obtain permission from the local wastewater treatment plant.
- Divert water originating from offsite away from all onsite disturbed areas.
- When dewatering, notify and obtain approval from the local municipality before discharging water to a street gutter or storm drain. Filtration or diversion through a basin, tank, or sediment trap may be required.
- In areas of known or suspected contamination, call the local agency to determine whether the groundwater must be tested. Pumped groundwater may need to be collected and hauled offsite for treatment and proper disposal.
- For additional information, refer to the CASQA's Sheet NS-2 "Dewatering Operations."

## Paving/Asphalt Work



### Paving

- Avoid paving and seal coating in wet weather or when rain is forecast to prevent materials that have not cured from contacting with stormwater runoff.
- Cover storm drain inlets and manholes when applying seal coat, slurry seal, fog seal, or similar materials.
- When construction is complete, remove all covers from storm drain inlets and manholes.
- Collect and recycle or properly dispose of excess abrasive gravel or sand. Do NOT sweep or wash it into gutters, storm drains, streets, dirt areas, or the sanitary sewer.

### Sawcutting & Asphalt/Concrete Removal

- Protect storm drain inlets during saw cutting.
- When making saw cuts, use as little water as possible.
- Residue from saw cutting, coring and grinding operations shall be picked up by means of a vacuum device.
- Shovel, absorb, or vacuum saw cut slurry deposits and dispose of all waste properly and as soon as reasonably possible. Sawcutting residue should not be left on pavement surface.
- If saw cut slurry enters a storm drain inlet, clean it up immediately and notify the local municipality.



## Copper Architectural Features

Discharges to storm drains generated by installing, cleaning, treating or washing copper architectural features, is a violation of the municipal stormwater ordinance and may be subject to a fine. These BMPs must be implemented to prevent prohibited discharges to storm drains:

### During Installation

- If possible, purchase copper materials that have been pre-patinated at the factory.
- If patination done on site, implement one or more of the following BMPs:
  1. Discharge the rinse water to landscaping. Ensure that the rinse water does not flow to the street or storm drain. Block off storm drain inlet if needed.
  2. Collect rinse water in a tank and pump to the sanitary sewer. Contact your local sanitary sewer agency before discharging to the sanitary sewer.
  3. Collect the rinse water in a tank and haul off-site for proper disposal.

### COMMUNITY DEVELOPMENT PLANNING DIVISION

### APPROVED

07/31/2025

PLAN REVIEW APPROVAL


- Block storm drain inlets as needed to prevent runoff from entering storm drains.
- Discharge the wash water to landscaping or to the sanitary sewer (with permission from the local sanitary sewer agency). If this is not an option, haul the wash water off-site for proper disposal.

THESE PLANS HAVE BEEN APPROVED AS SHOWN. ANY MODIFICATION TO WHAT HAS BEEN PROPOSED OR TO WHAT IS SHOWN AS EXISTING MAY REQUIRE A SEPARATE APPROVAL.


TOWN OF LOS GATOS  
BUILDING DIVISION

Storm drain polluters may be liable for fines of up to \$10,000 per day!





**REVIEWED  
FOR  
CODE COMPLIANCE**




General, Technical Demolition Diagram

STEVEN RAMIREZ  
PROJECT REPRESENTATIVES  
710E MCGLINCY LANE SUITE 109  
CAMPBELL, CA 95121  
(408)796-1845

GORDON K WONG, ARCHITECT  
710E MCGLINCY LANE SUITE 109  
CAMPBELL, CA 95121  
(408) 796-1845 LIC# 34045  
GKW Architects.com

**Residential Remodel & Addition**  
**14340 Browns Ln**  
**Los Gatos, CA 95032**



## 1 F.F, Technical Demolition Diagram 1/4" = 1'-0"

TECHNICAL DEMOLITION ANALYSIS

	EXISTING FOOTPRINT (FT)	WIDTH OF PRESERVED WALL FRAMING IN LINEAR FEET (INCLUDING EXISTING OPENINGS)	WIDTH OF DEMOLISHED WALL FRAMING IN LINEAR FEET (INCLUDING NW AND ENLARGED OPENINGS)
1ST FLOOR	174 FT	92 FT	84 FT
<b>TOTAL :</b>	<b>174 FT</b>	<b>92 FT</b>	<b>84 FT</b>

SINCE 92' IS GREATER THAN 84', THEN NO TECH DEMO

# COMMUNITY DEVELOPMENT PLANNING DIVISION APPROVED

07/31/2025


## PLAN REVIEW APPROVAL

07.31.2025

SCALE AS INDICATED

THESE PLANS HAVE BEEN APPROVED AS SHOWN. ANY MODIFICATION TO WHAT HAS BEEN PROPOSED OR TO WHAT IS SHOWN AS EXISTING MAY REQUIRE A SEPARATE APPROVAL.

# TOWN OF LOS GATOS BUILDING DIVISION



**REVIEWED  
FOR  
CODE COMPLIANCE**

**STEVEN RAMIREZ**  
PROJECT REPRESENTATIVES  
710E MCGLINCY LANE SUITE 109  
CAMPBELL, CA 95121  
(408)796-1845

**GORDON K WONG, ARCHITECT  
710 E MCGLINCY LANE SUITE 110  
CAMPBELL, CA 95121  
(408) 796-1845 LIC# 34045  
GKW Architects.com**

An architectural rendering of a modern building complex. The central feature is a tall, rectangular tower with a flat roof. To its left is a lower building with a curved facade and large windows. To its right is another building with a more traditional, multi-story design. The entire complex is set against a background of a rising sun over a body of water, with a few clouds in the sky. The overall style is clean and modern, with a focus on geometric shapes and natural light.

# 14340 Browns Ln

Los Gatos, CA 95032

## Architectural, 1st Level, Existing

## FLOOR PLAN, EXISTING, KEYNOTES:

## 1 DEMOLISH ROOF OVERHANG

### **FLOOR PLAN, EXISTING, LEGEND:**

AA | ATTIC ACCESS

(T) TEMPERED  
(EG) EGRESS

**COMMUNITY DEVELOPMENT  
PLANNING DIVISION  
APPROVED**

07/31/2025

## PLAN REVIEW APPROVAL


07.31.2025

THESE PLANS HAVE BEEN APPROVED AS SHOWN. ANY MODIFICATION TO WHAT HAS BEEN PROPOSED OR TO WHAT IS SHOWN AS EXISTING MAY REQUIRE A SEPARATE APPROVAL.

# TOWN OF LOS GATOS BUILDING DIVISION

## Architectural, 1st Level, Existing


SCALE AS INDICATED



REVIEWED  
FOR  
CODE COMPLIANCE  
Jul 25, 2025  
INTERWEST CONSULTING GROUP




STEVEN RAMIREZ  
PROJECT REPRESENTATIVE  
701 E MCGINNIX AVE, SUITE 109  
CAMPBELL, CA 95022  
(408)961-1845  
GKW Architects.com



Residential Remodel & Addition  
14340 Browns Ln  
Los Gatos, CA 95032

## Architectural, Roof Plan, Existing & Proposed




**ROOF PLAN, EXISTING, KEYNOTES**

- [1] BUILDING OUTLINE
- [2] SKYLIGHTS
- [3] COMPOSITION ROOF SHINGLES
- [4] FASCIA & GUTTER

**ROOF PLAN, EXISTING, NOTES**

- 1. ELEMENTS IN BLUE DASH LINES ARE TO BE DEMOLISHED
- 2. ELEMENTS IN BLACK LINE ARE EXISTING TO REMAIN



**② Roof Plan, Proposed**  
1/8" = 1'-0"

**ROOF PLAN, PROPOSED, KEYNOTES**

- [1] BUILDING OUTLINE
- [2] SKYLIGHTS
- [3] COMPOSITION ROOF SHINGLES
- [4] FASCIA & GUTTER

**NOTE:**

- 1. PARTIAL ROOF IS VAULTED, SPRAY FOAM INSULATION APPLIED DIRECTLY TO UNDERSIDE ROOF FRAMING. PER CRC R806.5

**ROOF PLAN, PROPOSED, KEYNOTES**

- STATE LAW REQUIRES A FIRE RATING OF CLASS C OR BETTER
- ALL PROPOSED GUTTERS & DOWNSPOUTS TO BE GSW PAINTED
- D.S. INDICATES 2' X 3' G.A. DOWNSPOUTS LOCATED AS SHOWN

**(P) ATTIC VENTILATION CALCULATIONS**

(P) TOTAL ATTIC AREA = 37.33 SF  
37.33 SF / 150 = .25 SF X 144 SF = 36 SF (REQ)

COMMUNITY DEVELOPMENT  
PLANNING DIVISION  
APPROVED  
07/26/2025

PLAN REVIEW APPROVAL  
07.31.2025

(A) TOTAL VENTILATION PROVIDED = 21.2 SF + 126 SF = 147.2 > 36 SF (REQ) = OK

THESE PLANS HAVE BEEN APPROVED AS  
SHOWN. ANY MODIFICATION TO WHAT HAS  
BEEN PROPOSED OR TO WHAT IS SHOWN AS  
EXISTING MAY REQUIRE A SEPARATE  
APPROVAL.

TOWN OF LOS GATOS  
BUILDING DIVISION



Revision Schedule		
Number	Description	Date


Architectural, Roof Plan, Existing & Proposed


SCALE AS INDICATED

6/12/2025 5:44:41 PM

A102









SHINGLE ROOF  
RADIANT BARRIER ROOF SHEATHING  
7.25" THICK (MIN) SPRAY FOAM INSULATION R-30  
ROOF RAFTER, S.S.D.  
DRIP EDGE  
FASCIA  
COPPER GUTTER

⑤ Roof Eave @ Vaulted Ceiling  
1 1/2" = 1'-0"




SHINGLE ROOF  
RADIANT BARRIER ROOF SHEATHING  
INSULATION R-11  
EAVE VENT  
ROOF RAFTER, S.S.D.  
DRIP EDGE  
FASCIA  
COPPER GUTTER

① Roof Eave @ Flat Ceiling  
1 1/2" = 1'-0"




SHEATHING, S.S.D.  
2 LAYER BUILDING PAPER  
JAMES HARDIE SIDING SEE ELEVATIONS  
SEALANT  
2X4 REDWOOD TRIM  
2X6 REDWOOD TRIM  
INSULATION  
GYP BD  
INTERIOR TRIM  
BITUTHENE & CAULK BEHIND BUILDING PAPER PRIOR TO INSTALLING DOOR  
TYP. 24 GA. G.S.M. FLASHING  
SEALANT AT ALL EDGES  
EXTERIOR DOOR, PER SPECS.

⑥ Exterior Door/Trim  
3" = 1'-0"




JAMES HARDIE SIDING, SEE ELEVATIONS  
HARDIE WRAP OR EQUIVALENT  
FLASH  
BITUTHENE & CAULK BEHIND NAIL FIN PRIOR TO INSTALL WINDOW  
2X4 WITH DRIP  
2X6 EXTERIOR TRIM  
INSULATION  
GYP BD  
SHIM GAP  
SEALANT  
WINDOW, PER SCHEDULE

② Window Head & Jamb / Trim  
3" = 1'-0"



GRADE 'D' PAPER OR METAL FLASHING AT A MINIMUM OF 12" HIGH  
METAL LATH  
HARDIE SIDING  
PERFORATED CORROSION RESISTANT WEEP SCREED 26 GALV. 3 1/2" VERTICAL  
MIN. 4" ABOVE EARTH  
MIN. 2" ABOVE PAVED AREAS  
FINISH GRADE  
FOUNDATION


⑦ Hardie Weep Screeed  
1 1/2" = 1'-0"



WALL FRAMING  
PLATE  
1 1/8" PLY WD.  
FLOOR JOIST, SEE STRUCT.  
SIMP., SEE STRUCT.  
INSUL., SEE PLANS & ENERGY COMPLIANCE DWGS.  
GYP. BD. CLG.  
2x FRAMING AT ATTIC ACCESS  
5/8" GYP. BD.  
FOAM WEATHER-STRIPPING  
WOOD CASING, LOCATE FOR REQ'D. CLEARANCES


NOTE 1:  
C.R.C. R007-ROUGH FRAMED OPENING  
30" R.O. MIN.  
22" R.O. MIN.

③ Attic Access  
3" = 1'-0"




HEADER  
TYP. GYP. BD.  
2-2X STUDS @ JAMB  
WOOD TRIM, OWNER FURNISHED  
TYP. 1 3/8" SOLID WD DOOR  
MANUFACTURER MODEL # THRESHOLD  
MANUFACTURER MODEL # SILL NOSING  
TYP. FLOOR FINISH  
(E) EXTERIOR CONC. SLAB  
TYP. 24 GA. G.S.M. FLASHING

⑧ Interior Door/Trim  
3" = 1'-0"



1.5 MAX

④ Exterior Door Sill  
3" = 1'-0"




Door Schedule

Mark	Count	Width	Height	Tempered
D1	1	2' - 8"	6' - 8"	YES
D2	1	2' - 8"	6' - 8"	
D3	3	2' - 6"	6' - 8"	
D4	3	2' - 4"	6' - 8"	
D5	1	2' - 4"	6' - 8"	
D6	1	2' - 4"	6' - 8"	
D7	2	5' - 0"	6' - 8"	
D8	1	3' - 0"	6' - 8"	
D9	1	2' - 8"	6' - 8"	
D10	1	12' - 0"	6' - 8"	YES
D11	1	5' - 0"	6' - 8"	YES
D12	2	6' - 0"	6' - 8"	YES
D13	1	16' - 0"	6' - 8"	

① REQUIRED EGRESS DOORWAYS SHALL HAVE A MINIMUM 32" CLEAR WIDTH (MEASURED WITH DOOR OPEN 90° AND NOT LESS THAN 6'-6" CLEAR IN HEIGHT. CRC R31.2


② REVIEWED FOR CODE COMPLIANCE  
Jul 25, 2025  
INTERWEST CONSULTING GROUP



DOOR NOTES:

- REQUIRED EGRESS DOORWAYS SHALL HAVE A MINIMUM 32" CLEAR WIDTH (MEASURED WITH DOOR OPEN 90° AND NOT LESS THAN 6'-6" CLEAR IN HEIGHT. CRC R31.2


③ REVIEWED FOR CODE COMPLIANCE  
Jul 25, 2025  
INTERWEST CONSULTING GROUP



DOOR NOTES:

- EVERY SLEEPING ROOM, HABITABLE ATTICS, AND BASEMENTS SHALL HAVE AT LEAST ONE OPERABLE EGRESS WINDOW OR DOOR APPROVED FOR EMERGENCY ESCAPE. EMERGENCY ESCAPE AND RESCUE OPENINGS SHALL OPEN DIRECTLY INTO A PUBLIC WAY OR TO A YARD OR COURT THAT OPENS TO A PUBLIC WAY. EGRESS WINDOWS SHALL HAVE A MIN NET CLEAR OPENING AREA OF 5.7 SF, MIN NET CLEAR OPENING HEIGHT 24", MIN NET CLEAR OPENING WIDTH 20". EGRESS WINDOWS SHALL HAVE THE BOTTOM OF THE CLEAR OPENING NOT GREATER THAN 44" MEASURED FROM THE FINISH FLOOR. EXCEPTION: GRADE FLOOR OPENINGS MAY HAVE A MINIMUM NET CLEAR OPENING OF 5 SF.

④ COMMUNITY DEVELOPMENT PLANNING DIVISION APPROVED  
PLAN REVIEW APPROVAL  
W7/31/2025  
W9/31/2025  
W10/31/2025  
W11/31/2025



Window Schedule

Type	Mark	Count	Width	Height	Sill Height	Head Height	Tempered
W1	2	5' - 0"	5' - 0"	2' - 8"	7' - 8"	7' - 8"	
W2	3	2' - 6"	5' - 0"	2' - 8"	7' - 8"	7' - 8"	
W3	1	3' - 0"	5' - 0"	2' - 8"	7' - 8"	7' - 8"	
W4	1	2' - 6"	5' - 0"	2' - 8"	7' - 8"	7' - 8"	
W5	1	3' - 0"	5' - 0"	2' - 8"	7' - 8"	7' - 8"	
W6	1	1' - 6"	4' - 0"	3' - 0"	7' - 8"	7' - 8"	
W7	1	1' - 6"	4' - 0"	3' - 0"	7' - 8"	7' - 8"	
W8	1	1' - 6"	1' - 2"	8' - 0"	9' - 2"	9' - 2"	
W9	1	3' - 0"	1' - 2"	8' - 0"	9' - 2"	9' - 2"	
W10	2	3' - 0"	1' - 4"	5' - 4"	6' - 8"	6' - 8"	
W11	1	6' - 0"	1' - 4"	5' - 4"	6' - 8"	6' - 8"	
WS1	1	2' - 0"	2' - 0"	2' - 0"	2' - 0"	2' - 0"	

⑤ THESE PLANS HAVE BEEN APPROVED AS SHOWN. ANY MODIFICATION TO WHAT HAS BEEN PROPOSED OR TO WHAT IS SHOWN AS EXISTING MAY REQUIRE A SEPARATE APPROVAL.  
TOWN OF LOS GATOS BUILDING DIVISION  
6/12/2025 5:44:53 PM

Residential Remodel & Addition  
14340 Browns Ln  
Los Gatos, CA 95032

Architectural, Window, Door & Details

Revision Schedule

Number	Description	Date
1	Building Revision 1	2025-04-16

Architectural, Window, Door & Details

A400  
SCALE AS INDICATED  
6/12/2025 5:44:53 PM



# COMMUNITY DEVELOPMENT PLANNING DIVISION APPROVED

07/31/2025

## PLAN REVIEW APPROVAL

07.31.2025

# TOWN OF LOS GATOS BUILDING DIVISION

THESE PLANS HAVE BEEN APPROVED AS SHOWN. ANY MODIFICATION TO WHAT HAS BEEN PROPOSED OR TO WHAT IS SHOWN AS EXISTING MAY REQUIRE A SEPARATE APPROVAL.

A 3D isometric architectural rendering of a modern two-story house. The house features a dark brown shingled roof with a prominent gabled end and a large overhanging eave. The exterior walls are a combination of light grey horizontal siding on the main section and dark grey vertical siding on the gabled end. A large glass door is located on the ground floor of the main section. The house is surrounded by a dark brown wooden fence. In the foreground, there is a green lawn and a paved driveway leading to a garage on the right side. The rendering shows the house from a high angle, highlighting its design and the surrounding landscape.

**REVIEWED  
FOR  
CODE COMPLIANCE  
Jul 25, 2025**



STEVEN RAMIREZ  
PROJECT REPRESENTATIVES  
710B MCGLINCY LANE SUITE 109  
CAMPBELL, CA 95121  
(408)796-1845

**GORDON K WONG, ARCHITECT**  
7100 MCGLINCY LANE SUITE 109  
CAMPBELL, CA 95121  
(408) 796-1845 LIC# 34045  
**gkw Architects.com**

14340 Browns Ln  
Los Gatos, CA 95032

## 3-D VIEWS

A500

---

SCALE AS INDICATED

---

/12/2025 5:45:00 PM



REVIEWED  
FOR  
CODE COMPLIANCE  
Jul 25, 2025  
INTERWEST CONSULTING GROUP



RESIDENTIAL LIGHTING REQUIREMENTS CA ENERGY CODE SECTION 150(K)

1.A. LUMINAIRE REQUIREMENTS: LUMINAIRE EFFICACY - ALL INSTALLED LUMINAIRES SHALL BE HIGH-EFFICACY IN ACCORDANCE WITH TABLE 150.0-A.1.C. RECESSED DOWNLIGHT LUMINAIRES IN CEILINGS, LUMINAIRES RECESSED INTO CEILINGS SHALL MEET ALL THE FOLLOWING REQUIREMENTS SECTION 150(K)1.F. LIGHTING INTEGRAL TO EXHAUST FANS. LIGHTING INTEGRAL TO EXHAUST FANS SHALL MEET THE APPLICABLE REQUIREMENTS OF SECTION 150(K).

1.G. SCREW BASED LUMINAIRES. SCREW BASED LUMINAIRES SHALL MEET ALL OF THE FOLLOWING REQUIREMENTS: THE LUMINAIRES SHALL NOT BE RECESSED DOWNLIGHT LUMINAIRES IN CEILINGS; AND THE LUMINAIRES SHALL CONTAIN LAMPS THAT COMPLY WITH REFERENCE JOINT APPENDIX JA8, AND THE INSTALLED LAMPS SHALL BE MARKED WITH 'JA8-2016' OR 'JA8-2016-E' AS SPECIFIED IN REFERENCE JOINT APPENDIX JA8.

1.H. ENCLOSED LUMINAIRES. LIGHT SOURCES THAT ARE NOT MARKED 'JA8-2016-E' SHALL NOT BE INSTALLED IN ENCLOSED LUMINAIRES.

1.I. TAMPER RESISTANT RECEPTACLES ALL NEW AND REPLACED DUPLEX RECEPTACLES SHALL BE LISTED 'TAMPER-RESISTANT RECEPTACLES. CEC ART. 406.21 J. ARC-FAULT ALL 120-VOLT, SINGLE PHASE, 15 AND 20 AMPERE BRANCH CIRCUITS SUPPLYING OUTLETS INSTALLED IN DWELLING UNIT FAMILY ROOMS, DINING ROOMS, LIVING ROOMS, PARLORS, LIBRARIES, DENS, BEDROOMS, SUNROOMS, RECREATION ROOMS, CLOSETS, HALLWAYS, OR SIMILAR ROOMS OR AREAS SHALL BE PROTECTED BY A LISTED ARC-FAULT CIRCUIT INTERRUPTER, COMBINATION-TYPE, INSTALLED TO PROVIDE PROTECTION OF THE BRANCH CIRCUIT.

2.J. PLANS TO COMPLY WITH INTERIOR LIGHTING SWITCHING DEVICES AND CONTROLS. IN BATHROOMS, GARAGES, LAUNDRY ROOMS, AND UTILITY ROOMS, AT LEAST ONE LUMINAIRE IN EACH OF THESE SPACES SHALL BE CONTROLLED BY A VACANCY SENSOR. 2.K. DIMMERS OR VACANCY SENSORS SHALL CONTROL ALL LUMINAIRES REQUIRED TO HAVE LIGHT SOURCES COMPLIANT WITH REFERENCE JOINT APPENDIX JA8.  
EXCEPTION 1 TO SECTION 150.0(K)2K: LUMINAIRES IN CLOSETS LESS THAN 70 SQUARE FEET.  
EXCEPTION 2 TO SECTION 150.0(K)2K: LUMINAIRES IN HALLWAYS.

GENERAL NOTES

1. CONTRACTOR AND OWNER TO VERIFY ALL DESIGNS AND DIMENSIONS ON SITE.
2. OWNER MAY USE ALTERNATIVE COMPLIANT EQUIPMENT/FIXTURES
3. RECEPTACLE OUTLETS, SWITCHES, THERMOSTATS, AND CONTROLS USED BY THE OCCUPANTS SHALL BE LOCATED A MINIMUM OF 15 INCHES MEASURED TO THE BOTTOM OF THE OUTLET BOX, AND MAXIMUM 48 INCHES MEASURED TO THE TOP OF THE OUTLET BOX, ABOVE FINISH FLOOR, PER CRC 327.1.2
4. PERMANENTLY MOUNTED OUTDOOR LIGHTING IS TO BE HIGH-EFFICACY, TO BE CONTROLLED BY AN ON/OFF SWITCH, AND INCLUDE ONE (1) OF THE FOLLOWING ADDITIONAL CONTROL TYPES PER CEC SECTION 150.0(K)3A:
  - A. PHOTOCELL AND MOTION SENSOR
  - B. PHOTOCELL AND AUTOMATIC TIME SWITCH CONTROL
  - C. ASTRONOMICAL TIME CLOCK CONTROL
  - D. ENERGY MANAGEMENT CONTROL SYSTEM
5. GFCI PROTECTION SHALL BE PROVIDED FOR OUTLETS THAT SUPPLY DISHWASHERS (CEC 210.8(D))
6. RECEPTACLES ARE TO BE LOCATED NO MORE THAN 12' BELOW THE COUNTERTOP WHERE THE COUNTERTOP DOES NOT EXTEND MORE THAN 6' BEYOND ITS SUPPORT BASE (CEC 210.52(C)(2))
7. GFCI RECEPTACLES WITHIN 24" OF BOTH SIDES OF THE KITCHEN SINK. THE MAXIMUM SPACING BETWEEN RECEPTACLES ON THE SAME COUNTERTOP SPACE IS 4 FT. MEASURED ALONG THE WALL LINE.
- 8.

COMMUNITY DEVELOPMENT  
PLANNING DIVISION  
APPROVED

07/31/2025

PLAN REVIEW APPROVAL

07.31.2025

THESE PLANS HAVE BEEN APPROVED AS  
SHOWN. ANY MODIFICATION TO WHAT HAS  
BEEN PROPOSED OR TO WHAT IS SHOWN AS  
EXISTING MAY REQUIRE A SEPARATE  
APPROVAL.


TOWN OF LOS GATOS  
BUILDING DIVISION

SCALE AS INDICATED

7/22/2025 2:31:57 PM

STEVEN RAMIREZ  
PROJECT REPRESENTATIVE  
CAMPBELL, CA 95021  
(408)966-1845  
GKW Architects.com

GORDON K. WONG, ARCHITECT  
701 MCGINNIS AVE., SUITE 109  
(408)785-5465 Lic.# 36456  
GKW Architects.com




Residential Remodel & Addition  
14340 Browns Ln  
Los Gatos, CA 95032

Revision Schedule		
Number	Description	Date
1	Building Revision 1	2025.04.16
2	Building Revision 2	2025.06.12
3	Building Revision 3	2025.07.01
4	Building Revision 4	2025.07.22


Electrical

E1



SCALES AS INDICATED

7/22/2025 2:31:57 PM



# COVER SHEET

## GENERAL NOTES AND SPECIFICATIONS

REVIEWED  
FOR  
CODE COMPLIANCE  
Jul 25, 2025  
INTERWEST CONSULTING GROUP

**OSHPD**

14340 Browns Ln, Los Gatos, CA 95032, USA  
Latitude, Longitude: 37.2599198, -121.9719412

**Map**

**Design Code Reference Document**: California Building Code CBC 2022

**Risk Category**: II

**Site Class**: Default

**Type Value Description (Data)**

- $S_0 = 2.45$  The MCE<sub>g</sub> spectral response acceleration at 0.2 seconds for Site Class BC, in units of g.
- $S_1 = 0.98$  The MCE<sub>g</sub> spectral response acceleration at 1 second for Site Class BC, in units of g.
- $S_{NS} = 2.56$   $S_{NS} = 1.5 \times S_0$  The Risk-Targeted Maximum Considered Earthquake (MCE<sub>g</sub>) spectral response acceleration for short periods (of the two-period spectrum) and the user-specified Site Class.
- $S_{NS} = 2.32$   $S_{NS} = 1.5 \times S_1$  The MCE<sub>g</sub> spectral response acceleration for 1 second (of the two-period spectrum) and the user-specified Site Class.
- $S_{NS} = 1.7$  The design spectral response acceleration for short periods (of the two-period spectrum) and the user-specified Site Class, in units of g.
- $S_{NS} = 1.55$  The design spectral response acceleration for 1 second (of the two-period spectrum) and the user-specified Site Class, in units of g.

**Type Value Description (Data Cont.)**

- $PG_{AM} = 0.91$   $PG_{AM}$ , the Geometric-Mean Maximum Considered Earthquake (MCE<sub>g</sub>) peak ground acceleration for the user-specified Site Class, in units of g.
- $T_0 = 0.99$   $T_0 = S_0/S_{NS}$  in seconds, for construction of the two-period design spectrum
- $T_0 = 0.162$   $T_0 = 0.2 \times T_0$  in seconds, for construction of the two-period design response spectrum
- $T_L = 12$   $T_L$ , the long-period transition period, in seconds, for construction of the two-period design response spectrum

**STRUCTURAL DESIGN CRITERIA - INFORMATION TO BE INCLUDED ON PLANS**

<b>LOADING</b>	<b>Floor dead load(s) and live load(s) used in design including any live load reductions applied (itemize by area).</b>	<b>DL=12PSF LL=40PSF NO LIVE LOAD REDUCTION</b>
	<b>Roof dead and live loads</b>	<b>DL=15PSF LL=20PSF NO LIVE LOAD REDUCTION</b>
	<b>Guardrails</b>	<b>N/A</b>

**WIND**

<b>Ultimate design wind speeds:</b>	<b>95 mph for risk category II buildings &amp; other structures.</b>
<b>Wind exposure category</b>	<b>B</b>
<b>Applicable internal pressure coefficient</b>	<b>0.18</b>
<b>Components and cladding wind pressure (psf)</b>	<b>16.2</b>

**SEISMIC**

<b>Seismic importance factor</b>	<b>I</b>
<b>Mapped spectral response accelerations, <math>S_s</math> &amp; <math>S_1</math></b>	<b><math>S_s = 2.45</math>, <math>S_1 = 0.98</math></b>
<b>Site class</b>	<b>D</b>
<b>Spectral response coefficients, <math>S_{NS}</math> &amp; <math>S_{NS}</math></b>	<b><math>S_{NS} = 1.7</math>, <math>S_{NS} = 1.55</math></b>
<b>Seismic design category: SDC</b>	<b>E <math>S_1 &gt; 0.75</math></b>
<b>Basic seismic force resisting system(s)</b>	<b>BEARING WALL SYSTEM Light frame (wood) walls sheathed w/wood structural panels rated for shear resistance</b>
<b>Design base shear (kips)</b>	<b>15.08kips</b>
<b>Seismic response coefficient(s), Cs</b>	<b>0.3015</b>
<b>Response modification factor(s), R</b>	<b>R=6.5 W=3.0 Cd= 4.0</b>
<b>Seismic analysis procedure used</b>	<b>The "Equivalent Lateral Force Procedure" According to the Provisions of ASCE 7-16 Section 12.8</b>

**PROJECT WIND DATA**

**WIND FORCE APPLICATION:** WIND PER SIMPLIFIED PROVISIONS FOR LOW RISE BUILDINGS Section 16-9.6.4 main wind force resisting system

**Section 1609 Wind Loads:**

- Basic Wind Speed (3-Seconds Gust),  $= 110\text{mph}$
- Wind Importance factor, I  $= 1.0$
- Wind Exposure  $= B$
- Minimum wind pressure:  $= 18.2\text{psf}$

**LIST OF STRUCTURAL OBSERVATION**

**SPECIAL INSPECTION FORM**

1-SHEAR WALLS FOR TYPE 4 AND LESS  
2-STEEL VELDS LARGER THAN 3/16" (CONTINUOUS INSPECTIONS)  
BOTTOM OF FOUTING (PERIODIC)  
HOLDOWNS IN PLACE (PERIODIC)

**SECTION: 1.0 - INDEX TO STRUCTURAL DRAWING:**

**DWG. NO.** **TITLE**

S-1 GENERAL NOTES & SPECIFICATIONS  
S-2 COVER SHEET, GENERAL NOTES & SPECIFICATIONS  
S-3 PLANS:  
S-1 PLAN-FND AND WALL FRAMING  
S-2 PLAN - ROOF FRAMING  
S-3 FOUNDATION DETAILS  
S-2 ROOF FRAMING DETAILS  
S-3 SHEAR WALL SCHEDULE SECTIONS & DETAILS  
S-5 TYPICAL FRAMING DETAILS

**WSW1 SIMPSON STRONG WALL TYP DETAILS**

**WSW2 SIMPSON STRONG WALL TYP. FRAMING DETAILS**

## GENERAL NOTES AND SPECIFICATIONS

### 2. LUMBER FRAMING NOTES:

#### PRESSURE TREATED LUMBER:

a) ALL SILL PLATES WHICH REST ON CONCRETE SLAB OR MASONRY, END OF WOOD GIRDERS, OR BEAMS HAVING CLEARANCE OF LESS THAN 1/2" ON TOP, SIDES, AND ENDS, WOOD SIDING, SHEATHING, AND WOOD FRAMING HAVING CLEARANCE OF LESS THAN 6" FROM GROUND.

b) ALL SILLS IN CONTACT WITH GROUND WHICH SUPPORTS PERMANENT STRUCTURE(S). c) MEMBERS SUPPORTING BALCONIES, PORCHES, OR SIMILAR APPURTENACES WHEN EXPOSED TO THE WEATHER AND ELEMENTS.

**REMOVAL OF DEBRIS:**  
THE UNDER-FLOOR GRADE SHALL BE CLEANED OF ALL VEGETATION AND ORGANIC MATERIALS.

### 24. DETAILS:

FRAMING DETAILS NOT SHOWN ON THE DRAWINGS SHALL BE FRAMED SIMILAR TO TECHNICAL DETAIL AS SHOWN ON THE DRAWINGS.

### 25. STRUCTURAL LUMBER GRADES:

IF LUMBER IS DRY: STRUCTURAL LUMBER SHALL CONFORM TO FOLLOWING WCLB MINIMUM GRADES, UNLESS NOTED OTHERWISE:

- a) HORIZONTAL 2x FRAMING.....#2 OR BETTER
- b) 4x BEAMS, HEADERS, SPECIAL MEMBERS.....#1
- c) STUDS.....#2 OR BETTER
- d) 4x & 6x POSTS.....#1

MAXIMUM MOISTURE CONTENT SHALL BE 19% AT TIME OF INSTALLATION. LUMBER OF 1 INCH AND LESS NOMINAL THICKNESS DRIED TO 15% MOISTURE CONTENT PRIOR TO DELIVERY TO SITE.

### 26. NAILING:

FOR MODULE OF MINIMUM NAILING, SEE TABLE 2304.10.2 CBC OR DESIGN DRAWINGS. NAILING SHALL BE WITH COMMON WIRE NAILS, UNLESS NOTED OTHERWISE. MACHINE-DRIVEN MAY BE USED ONLY WITH PERMISSION OF THE ENGINEER. NAILS AND FASTENERS FOR USE IN PRESSURE-TREATED LUMBER SHALL BE HOT-DIPPED (HDG 200) GALVANIZED PER ASTM A153 SPECIFICATIONS.

### 27. FASTENERS:

BOLTS AND LAG SCREWS BEARING ON WOOD SHALL HAVE WASHERS. BOLTS IN CONNECTION SHALL BE RE-TIGHTENED JUST BEFORE CLOSING IN OF WALLS.

### 28. EXTERIOR METAL CONNECTORS AND HARDWARE USED IN CONJUNCTION WITH UNTREATED WOOD

ALL EXTERIOR METAL CONNECTORS AND HARDWARE USED IN CONJUNCTION OF UNTREATED WOOD SHALL BE GALVANIZED (G185) 1.85 OZ. OF ZINC PER SQUARE FOOT OF SURFACE(HOT-DIPPED GALVANIZED PER ASTM A653 TOTAL BOTH SIDES). FASTENERS USED WITH SUCH DEVICES SHALL BE HOT-DIPPED GALVANIZED PER ASTM A153 SPECIFICATION.

### 29. METAL CONNECTORS AND HARDWARE USED IN CONJUNCTION WITH TREATED WOOD:

ALL EXTERIOR METAL CONNECTORS AND HARDWARE USED IN CONJUNCTION OF TREATED WOOD SHALL BE 14 GA. AND THICKER, WITH MINIMUM COATING WEIGHT OF 2.0 OZ. OF ZINC PER SQUARE FOOT OF SURFACE (HOT-DIPPED GALVANIZED PER ASTM A123 TOTAL BOTH SIDES). FASTENERS USED WITH SUCH DEVICES SHALL BE HOT-DIPPED GALVANIZED PER ASTM A153 SPECIFICATION.

### 30. BOLTS IN CONCRETE OR CONCRETE SLAB:

LENGTH OF EMBEDMENT OF ANCHOR BOLTS IN CONCRETE, OTHER THAN COLUMN ANCHOR BOLTS, SHALL BE AS FOLLOWS, UNLESS OTHERWISE NOTED, OR UNLESS DETAILED OTHERWISE ON THE STRUCTURAL DRAWINGS:

SIZE OF BOLT LENGTH OF EMBEDMENT  
5/8" 3/4" 7"  
3/4" 12"

### 31. DRILLED AND DRYPACKED OR GROUTED BOLTS:

DRILLED AND DRYPACKED OR GROUTED BOLTS SHALL HAVE 1" CLEAR FROM BOLT TO EDGE OF HOLE.

### 32. CHAMFER:

ALL EXPOSED CONCRETE CORNERS SHALL HAVE 3/4" CHAMFER UNLESS NOTED OTHERWISE.

### 33. FORMS (IF USED):

FORMS SHALL BE OF SUBSTANTIALLY BUILT AND OF SUFFICIENT STRENGTH AND RIGIDITY TO PROVIDE SAFE WORKING CONDITIONS AT ALL TIMES, AND TO PRODUCE FINISHED CONCRETE OF PRECISE SIZE AND SHAPE AS SHOWN ON DRAWINGS. THEIR ASSEMBLY SHALL PERMIT REMOVAL IN PROPER SEQUENCE WITHOUT DAMAGE TO CONCRETE. FORM WORK SHALL BE CLEAN AND FREE OF SAW DUST, PAPER, DIRT, AND DEBRIS WHEN CONCRETE IS PLACED THEREIN.

### 34. CONCRETE:

#### 35. STRENGTH & QUALITY:

CONCRETE STRENGTHS AT 28 DAYS SHALL BE  $f_c = 2500 \text{ psi}$ , OR AS INDICATED AS FOLLOWS:

CONCRETE USE	STRENGTH	SLUMP	AGG. SIZE
STEPS & PATES	2500 PSI @ 28 DAYS	4 1/2"	
FOUNDATIONS	2500 PSI @ 28 DAYS	1 1/2"	3/4"
CONCRETE STOOPS	2500 PSI @ 28 DAYS	4 1/2"	3/4"
LEAN CONCRETE	2000 PSI @ 28 DAYS	4"	3/4"

### 36. CEMENT:

ALL CEMENT SHALL CONFORM TO ASTM C-150, TYPE II, UNLESS ALKALINE SOILS ARE PRESENT.

### 37. AGGREGATES:

ALL CONCRETE, UNLESS OTHERWISE NOTED, SHALL BE REGULAR WEIGHT HARD ROCK TYPE (150 #/CF). AGGREGATES SHALL CONFORM TO ASTM C-33 WITH PROVEN SHRINKAGE CHARACTERISTICS OF LESS THAN .005. CONCRETE MIX SHALL CONTAIN UP TO 15% ASH.

### 38. CURING:

CONCRETE SHALL BE MAINTAINED IN A MOIST CONDITION FOR A MINIMUM OF FIVE (5) DAYS AFTER PLACEMENT. APPROVED CURING COMPOUNDS MAY BE USED IN LIEU OF MOIST CURING.

### 39. KEYED CONSTRUCTION JOINTS:

KEYED CONSTRUCTION JOINTS SHALL BE USED IN ALL CASES. ALL CONSTRUCTION JOINTS SHALL BE THOROUGHLY CLEARED AND ALL LITTER SHALL BE REMOVED. ALL VERTICAL JOINTS SHALL BE THOROUGHLY WETTED AND SLUSHED WITH A COAT OF NEAT CEMENT IMMEDIATELY BEFORE PLACING NEW CONCRETE.

### 40. SLEEVES:

SLEEVES NOT SPECIFICALLY SHOWN ON THE DRAWINGS SHALL BE LOCATED BY THE TRADES INVOLVED AND SHALL BE CHECKED WITH ALL TRADES TO INSURE PROPER PLACEMENT OF OPENING, SLEEVES, CONDUITS, ETC., RELATING TO THE WORK.

### 41. INSERTS:

ALL ITEMS TO BE CAST IN CONCRETE, SUCH AS REINFORCING BARS, DOWELS, BOLTS, ANCHORS, PIPES, SLEEVES, ETC., SHALL BE SECURELY POSITIONED IN THE FORMS BEFORE PLACING THE CONCRETE.

EXPANSION BOLTS FOR MUD SILL MAY BE USED IN LIEU OF EMBEDDED BOLTS, AS PER ENGINEER'S DIRECTION ONLY.

### 42. SEGREGATION OF AGGREGATES:

SEGREGATION OF AGGREGATES SHALL NOT OCCUR. USE HOPPERS, CHUTES, OR TRUCKS OF VARYING LENGTHS SO THAT THE FREE, UNCONFINED FALL OF CONCRETE SHALL NOT EXCEED FIVE FEET, AND A SUFFICIENT NUMBER SHALL BE USED TO ENSURE THE CONCRETE SHALL BE KEPT LEVEL AT ALL TIMES.

### 43. DOWELING:

ALL SLABS SHALL BE DOWELLED INTO FOUNDATIONS WITH BARS OF THE SAME SIZE AND SPACING AS THE FOUNDATION BARS, EXCEPT WHERE SPECIFICALLY INDICATED OTHERWISE.

### 44. SPLICES:

SPLICES IN CONTINUOUS REINFORCEMENT AS USED, SHALL HAVE A LAP OF 30 BAR DIAMETERS BUT NOT LESS THAN 18 INCHES, AND THE SPLICES IN ADJACENT BARS SHALL NOT BE LESS THAN 5-4" APART. ALL REINFORCING STEEL SHALL BE SECURELY WIRED AND PROPERLY SUPPORTED ABOVE GROUND AND AWAY FROM THE FORMS.

### 45. CHAIRS:

PROVIDE CONCRETE CHAIRS TO SUPPORT BOTTOM OR TOP BARS AND HOLD THE SAME IN SECURED POSITIONS.

### 46. CONSTRUCTION JOINTS:

CONSTRUCTION JOINTS SHALL HAVE ENTIRE SURFACE REMOVED TO EXPOSE CLEAN AGGREGATE SOLIDLY EMBEDDED. THE CONTRACTOR SHALL OBTAIN THE ENGINEER'S APPROVAL FOR CONSTRUCTION JOINT LOCATION OTHER THAN DETAILED OR SPECIFIED IN ALL SLABS AND EQUIPMENT FOUNDATIONS.

### 47. PIPES:

PIPES, OTHER THAN ELECTRICAL CONDUITS, SHALL NOT BE EMBEDDED IN STRUCTURAL CONCRETE, EXCEPT WHERE SPECIFICALLY APPROVED BY THE ENGINEER.

### 48. GROUT:

GROUT, IF USED, SHALL BE COMPOSED OF ONE PART PORTLAND CEMENT TO NOT MORE THAN TWO PARTS SAND. DRYPACKING OR NON-SHRINK GROUTING SHALL HAVE MIN. ULTIMATE COMPRESSIVE STRENGTH OF 5000 PSI @ 7 DAYS.

### 49. MISCELLANEOUS ITEMS:

REFER TO ARCHITECTURAL, MECHANICAL, AND ELECTRICAL DRAWINGS FOR MISCELLANEOUS ITEMS TO BE CAST INTO CONCRETE. DO NOT CUT OR DEFORM PRIMARY REINFORCING BARS WITHOUT CONSENT OF THE ENGINEER.

### 50. FINISH:

EXPOSED EXTERIOR SLABS AND RAMPS ON GRADE SHALL HAVE A BROOMED FINISH. CONCRETE TO RECEIVE REINFORCING TILE OR DUSTPROOFING SHALL RECEIVE A STEEL TIEWELD, OR INTEGRAL LAB BOND, WHICH IS A HIGHLY MOISTURE-RESISTANT, THOROUGHLY CONSOLIDATED, AND VIBRATING ANCHOR. THE CONCRETE SHALL BE BROUGHT TO PROPER ELEVATION BY SCREEDING, TAMPING, AND FLOATING. THE SURFACE SHALL BE TROWELED UNTIL SMOOTH AND RELATIVELY FREE OF DEFECTS AND TROWELED MARKS.

### 51. BOLTS:

BOLTS EMBEDDED IN CONCRETE SHALL BE ASTM A-307, UNLESS NOTED OTHERWISE.

### 52. VIBRATION:

VIBRATION OF CONCRETE SHALL BE IN ACCORDANCE WITH THE GENERAL PROVISIONS OUTLINED IN PORTLAND CEMENT ASSOCIATION SPECIFICATIONS ST26. PLACEMENT OF CONCRETE SHALL BE IN CONFORMANCE WITH THE ACI SPEC. 301.

### 53. REBAR COVER:


MINIMUM COVERAGE SHALL BE AS FOLLOWS:

- 3" WHERE CONCRETE IS DEPOSITED DIRECTLY AGAINST GROUND, EXCEPT SLABS ON GRADE.
- 2" WHERE CONCRETE IS EXPOSED TO GROUND BUT PLACED IN FORMS.
- 1 1/2" FOR MARS BARS IN RETAINING WALLS
- 1 1/2" FOR BARS IN STEPS
- 1 1/2" FOR BARS IN SLABS ON GRADE.

### 54. BOLTS IN CONCRETE OR CONCRETE SLAB:

LENGTH OF EMBEDMENT OF ANCHOR BOLTS IN CONCRETE, OTHER THAN COLUMN ANCHOR BOLTS, SHALL BE AS FOLLOWS, UNLESS OTHERWISE NOTED, OR UNLESS DETAILED OTHERWISE ON THE TEH STRUCTURAL DRAWINGS:

### 55. DRILLED AND DRYPACKED OR GROUTED BOLTS:



PLAN - FOUNDATION & WALL FRAMING

0 10 20 FT

**1. FASTENERS & CONNECTION HARDWARE:**  
BOLTS AND LAG SCREWS BEARING ON WOOD SHALL HAVE WASHERS. BOLTS IN CONNECTIONS SHALL BE RE-TIGHTENED JUST BEFORE CLOSING IN OF WALLS.

**2. METAL CONNECTORS AND HARDWARE USED IN CONJUNCTION WITH UNTREATED WOOD:**

ALL EXTERIOR METAL CONNECTORS AND HARDWARE USED IN CONJUNCTION WITH UNTREATED WOOD SHALL BE GALVANIZED (G185) 1.55 OZ. OF ZINC PER SQUARE FOOT OF SURFACE (HOT-DIPPED GALVANIZED ER ASTM S3 TOTAL BOTH SIDES) FASTENERS USED WITH SUCH DEVICES SHALL BE HOT-DIPPED GALVANIZED PER ASTM A153 SPECIFICATION

**3. METAL CONNECTORS AND HARDWARE USED IN CONJUNCTION WITH TREATED WOOD:**  
ALL EXTERIOR & INTERIOR METAL CONNECTORS AND HARDWARE USED IN CONJUNCTION WITH TREATED WOOD SHALL BE 14 GA. AND THICKER, WITH MINIMUM COATING WEIGHT OF 2.0 OZ. OF ZINC PER SQUARE FOOT OF SURFACE (HOT- DIPPED GALVANIZED PER ASTM A123 TOTAL BOTH SIDES) FASTENERS USED WITH SUCH DEVICES SHALL BE HOT-DIPPED GALVANIZED PER ASTM A153 SPECIFICATION.

**4. PRESSURE TREATED WOOD:**  
PRESSURE TREATED WOOD SHALL HAVE ACTUAL RETENTION LEVELS GREATER THAN 0.40 PCF FOR AC AND MCQ AND 0.41 PCF FOR CBA, A OR 0.21 PCF FOR CA-B GROUND CONTACT LEVEL. BORATE TREATED WOODS SHALL NOT BE USED FOR OUTDOOR USE. TREATED WOOD HAVING EXCESS SURFACE CHEMICALS ARE CORROSIVE. USE STAINLESS STEEL HARDWARE AND CONNECTORS IN CONJUNCTION WITH SUCH WOOD ELEMENTS

**5. ICC-ESR CURRENT REPORT:**

a) ALL CONNECTORS AND HARDWARE SHALL HAVE CURRENT ICC-ESR REPORT.  
b) FASTENERS ARE DESIGNED BASED ON COMMON NAILS. USE OF NAILS OTHER THAN AS SPECIFIED SHALL REQUIRE REDESIGN RECONSIDERATION OF THE NAILS SPACING AND LENGTH OF PENETRATION

**2. TOP PLATE NOTES:**  
2.1 ALL TOP PLATES SHALL BE MIN. TWO- 2X AND MATCH THE WIDTH OF STUDS IN CONNECTION.  
2.2 ALL WALL STUDS SHALL BE CAPPED WITH DOUBLE TOP PLATES INSTALLED TO PROVIDE OVERLAPPING AT CORNERS AND AT INTERSECTIONS WITH OTHER PARTITIONS. END JOINTS IN DOUBLE TOP PLATES SHALL BE OFFSET AT LEAST 48 INCHES.  
2.3 FOR TOP PLATE SPLICE DETAIL SEE DWG "TYPICAL SECTIONS & DETAILS" DWG. SD-3

**CORNER REINFORCING STRAPS:**  
2.4 ALL BUILDING EXTERIOR CORNERS SHALL BE REINFORCED AT TOP PLATES LEVEL PER "TYPICAL PLATE @ CORNERS & INTERSECTIONS" SHOWN ON "TYPICAL SECTIONS & DETAILS" DWG. SD-5  
3.0 STUD NOTES:  
3.1 ALL EXTERIOR STUDS SHALL BE 2X4 AT 16" O.C., UNLESS NOTED OTHERWISE ON THE PLANS. LISTED HEIGHTS ARE DISTANCES BETWEEN POINTS OF LATERAL SUPPORTS PLACED PERPENDICULAR TO THE PLANE OF WALL. "HINGED" STUDS ARE NOT PERMITTED.

**3.2 GABLE WALL STUD NOTE:**  
GABLE STUDS SHALL BE CONTINUOUS FROM TOP OF FLOOR SOLE PLATE TO THE BOTTOM OF THE TOP PLATES. ALL GABLE WALL TOP PLATES SHALL BE LATERALLY SUPPORTED. HINGING OF THE STUDS IS NOT PERMITTED. TYPICAL.

THIS DOCUMENT IS PROPERTY OF A.S. ASSOCIATES. THE TECHNICAL INFORMATION, IDEAS AND DESIGN METAL HEREIN MAY BE USED ONLY BY THE GOVERNMENT, CONTRACTORS, AND OTHER INDIVIDUALS IN THE EXERCISE OF THEIR DUTIES. THESE PLANS MAY NOT BE REPRODUCED, COPIED, OR DISCLOSED IN WHOLE OR IN PART, IN ANY FORM OR MANNER, WHETHER BY MEANS OF MICROFILM, MICROGRAPH, OR ANY OTHER PROCESS, WITHOUT THE EXPRESSED WRITTEN CONSENT OF A.S. ASSOCIATES.

**A. S. Associates**  
ENGINEERS & PLANNERS  
88 EAST 6TH STREET, UNIT 404  
PITTSBURG, CA. 94565  
(408) 666-5933  
a.s.associates@gmail.com

GRID	WALL LENGTH & TOP PLATE HEIGHT in ft	SHEAR WAL CONNECTORS	BASE SHEAR & SHEAR TYPE
1	L1=24.1	A35@16"OC 5/8" A.B @32" HDU2	Type 6
2	L2= 13.24 L3= 7.33 $\Sigma=20.57$	A35@16"OC 5/8" A.B @24" HDU2	Type 6
2A	L4=2.8' pier W=9 L5=2.67 pier $\Sigma= 14.47$	A35@16"OC 5/8" A.B @24" HDU2	Type 6
3	L6=9.5', H=8' L7=3', pier H=9 W=5' L8=3' pier $\Sigma= 20.5'$	A35@16"OC 5/8" A.B @24" HDU2	Type 4
4	L9=19, H=9	A35@16"OC 5/8" A.B @32" HDU2	Type 6
5	L10=12.5', H=8' L11=not used $\Sigma=12.5'$	A35@16"OC 5/8" A.B @32" HDU2	Type 6
A	L12=5.67, H=8 L13=6.67' $\Sigma=12.33'$	A35@16"OC 5/8" A.B @16" HDU2	Type 6
B	L15=4', H=8 L14=5.2' $\Sigma=9.2'$	A35@16"OC 5/8" A.B @16" HDU2	Type 2
F	L16=17.67, H=8	A35@16"OC 5/8" A.B @32" HDU2	Type 6
G	L17=2', H=9' WSWH24X9		SEE FNDL17
I	L18=4.5', H=9 L19=4.5' $\Sigma= 9.0'$	A35@16"OC 5/8" A.B @24" HDU2	Type 6

**NOTE #6:**  
FOR SAW LUMBER JOIST HANGER SEE DWG SD-5.

**NOTE #7:**  
FOR NOTCHING WOOD STUDS, SOLE PLATES, TOP PLATES AND PIPES IN WALL SEE DETAILS ON DWG SD-5.

**NOTE #8:**  
1.0 **HEADER NOTES:**  
1.1 ALL OPENINGS SHALL BE FRAMED WITH A HEADER. HEADER SIZE SHALL BE PER "HEADER" SHOWN ON THE ROOF FRAMING PLAN.

1.2 MIN. HEADER WIDTH DIMENSION SHALL BE THE SAME AS THE WALL STUD.

2.0 **TOP PLATE NOTES:**

2.1 ALL TOP PLATES SHALL BE MIN. TWO- 2X AND MATCH THE WIDTH OF STUD IT IS BEARING ON.

2.2 ALL WALL STUDS SHALL BE CAPPED WITH DOUBLE TOP PLATES INSTALLED TO PROVIDE OVERLAPPING AT CORNERS AND AT INTERSECTIONS WITH OTHER PARTITIONS. END JOINTS IN DOUBLE TOP PLATES SHALL BE OFFSET AT LEAST 48 INCHES.

2.3 FOR TOP PLATE SPLICE DETAIL SEE DWG "TYPICAL SECTIONS & DETAILS" DWG. SD-5

**NOTE #9:**

**CORNER REINFORCING STRAPS:**

2.4 ALL BUILDING EXTERIOR CORNERS SHALL BE REINFORCED AT TOP PLATES LEVEL PER "TYPICAL PLATE @ CORNERS & INTERSECTIONS" SHOWN ON "TYPICAL SECTIONS & DETAILS" DWG. SD-5

**3.0 STUD NOTES:**

3.1 ALL EXTERIOR STUDS SHALL BE 2X4 AT 24" O.C., UNLESS NOTED OTHERWISE ON THE PLANS. LISTED HEIGHTS ARE DISTANCES BETWEEN POINTS OF LATERAL SUPPORTS PLACED PERPENDICULAR TO THE PLANE OF WALL. "HINGED" STUDS ARE NOT PERMITTED.

3.2 **GABLE WALL STUD NOTE:**

GABLE STUDS SHALL BE CONTINUOUS FROM TOP OF FLOOR SOLE PLATE

TO THE BOTTOM OF THE TOP PLATES. ALL GABLE WALL TOP PLATES SHALL BE LATERALLY SUPPORTED. HINGING OF THE STUDS IS NOT PERMITTED. TYPICAL.

**NOTE #10:**

**ADU SLAB ON GRADE:**

1. 8"-THICK CONCRETE SLAB W/ # 4 REINF. BARS @ 12" INCH ON CENTERS EACH WAY. PLACE 1-#4 CONTINUOUS BAR AT ALL SLAB EDGES AND AT THE VICINITY OF THE CONTINUOUS JOINTS. TYPICAL.

2. ALL CONT. JOINTS SHALL BE IN PLACE NO LATER THAN 24 HOURS FROM START OF PLACING OF CONCRETE.

3. SLAB ON GRADE SHALL NOT BE CONNECTED TO THE FOUNDATIONS U.N.O. ON THE PLANS. SEE "DETAIL SG" ON DWG SD-1.


5. SUB-BASE SHALL BE CRUSHED STONE 3/4" MAX & 5" THICK PLACED ON COMPAKTED SOIL WITH 2" WASHED SAND & E.P.D.M. MEMBRANE WATERPROOFING OR ENGINEER APPROVED EQUAL

**NOTE:**  
WOOD FOUNDATION OF ANY SORT IS NOT PERMITTED FOR THIS PROJECT

**REVIEWED**  
FOR  
CODE COMPLIANCE  
Jul 25, 2025  
INTERWEST CONSULTING GROUP

**LEGEND**

**SHEAR WALL NOTATIONS:**



**NOTE:**

- INDICATES TYPE OF SHEAR WALL INCLUDING CONNECTION OF:
- a. BLOCKING TO TOP PLATES
- b. BLOCKING TO SILL OR SOLE PLATE
- c. SILL PLATE ANCHOR BOLT SPACING
- d. SIZE OF SILL PLATE
- e. SOLE PLATE NAILING
- f. SHEAR PLYWOOD NAILING
- g. SOLE PLATE NAILING

- h. ALL OTHER REQUIREMENTS PERTAINING TO SHEAR WALL AS NOTED IN SHEAR WALL SCHEDULE SHOWN ON DWG SD-3. WORK THIS SYMBOL ○ WITH "SHEAR" WALL TABLE I.O. SCHEDULE SHOWN ON DWG SD-3.

**PLAN REVIEW APPROVAL**  
WORK STRUCTURAL DRAWINGS WITH  
ARCHITECTURAL DRAWINGS. DO NOT SCALE FROM  
STRUCTURAL DRAWINGS. FOR 07/14/2025, REFER  
TO ARCHITECTURAL PLANS & DETAILS.

DATE: FEB 1-2025  
SCALE: AS NOTED  
DRAWN BY: H.S.  
CHECKED BY: A.S.

PROJECT NO: 025046.45  
DRAWING NO. FND & WALL  
FRAMING PLAN

Page 1 of 1

**COMMUNITY DEVELOPMENT  
PLANNING DIVISION  
APPROVED**  
07/31/2025

THESE PLANS HAVE BEEN APPROVED AS  
SHOWN. ANY MODIFICATION TO WHAT HAS  
BEEN PROPOSED OR TO WHAT IS SHOWN AS  
EXISTING MAY REQUIRE A SEPARATE  
APPROVAL.

TOWN OF LOS GATOS  
BUILDING DIVISION

FND & WALL  
FRAMING PLAN

S-1



PLAN - CEILING FRAMING

COMMUNITY DEVELOPMENT  
PLANNING DIVISION  
APPROVED

07/31/2025

PLAN REVIEW APPROVAL  
WORK STRUCTURAL DRAWINGS WITH  
ARCHITECTURAL DRAWINGS. DO NOT SCALE FROM  
STRUCTURAL DRAWINGS. FOR 07/31/2025, REFER  
TO ARCHITECTURAL PLANS & DETAILS.

THESE PLANS HAVE BEEN APPROVED AS  
SHOWN. ANY MODIFICATION TO WHAT HAS  
BEEN PROPOSED OR TO WHAT IS SHOWN AS  
EXISTING MAY REQUIRE A SEPARATE  
APPROVAL.


TOWN OF LOS GATOS  
BUILDING DIVISION

STRUCTURAL  
CEILING FRAMING PLAN

REVIEWED  
FOR  
CODE COMPLIANCE  
Jul 25, 2025  
INTERWEST CONSULTING GROUP

THIS DOCUMENT IS PROPERTY OF A.S. ASSOCIATES. THE TECHNICAL  
INFORMATION, IDEAS, AND DESIGN DETAILS HEREIN MAY BE DISCLOSED  
ONLY TO THOSE GOVERNMENTAL AGENCIES, HAVING JURISDICTION  
OVER THE PROJECT, WHICH HAVE BEEN PROVIDED WITH A COPY  
OF THE DRAWINGS. THESE PLANS MAY NOT BE REPRODUCED, COPIED,  
OR  
WHATEVER, NOR ARE THEY TO BE ASSIGNED TO ANY THIRD PARTY  
WITHOUT THE EXPRESSED WRITTEN CONSENT OF A.S. ASSOCIATES.

A. S. Associates  
ENGINEERS & PLANNERS  
88 EAST 6TH STREET, UNIT 404  
PITTSBURG, CA. 94565  
(408) 666-5933  
a.s.associates@gmail.com




MAC-NOLAD RESIDENCE  
RESIDENTIAL REMODEL  
14340 BROWNS LANE  
LOS GATOS, CA 95032



025046.45

DRAWING NO.

S-2



PLAN - ROOF FRAMING

SCHEDULE OF ROOF/CEILING RAFTERS & HANGERS		
JOIST / RAFTER SIZE	SIMPSON - FACE MOUNT HANGER FOR SOLID SAWN D/F LUMBER ONLY	NOTES
2X6	LU26	
2-2X6	LU26-2	
2X8	LU26	
2-2X8	HU28-2	
2X10	LU210	
2-2X10	U210-2	
2X12	LU210	
4X6	U46	
4X8	HU48	
4X10	HU410	
4X12	HU412	

**NOTES:**

1. See plans where sloped/ hangers are required
2. For specification of sloped/skewed hangers see structural plans
3. **FILL ALL ROUND & TRIANGULAR NAIL HOLES**
4. All steel connectors shall be Simpson product. For use of other product written approval of the engineer of the record is required.

SCHEDULE OF CEILING AND ROOF BEAMS AND RELATED STEEL HARDWARE			
LOCATION	MEMBER SIZE	RELATED HARDWARE	NOTES
ROOF	RAFTER: 2X10	LU28	
ROOF	RB1: 3 1/2 X 9 1/2, 1.55E TIMBERSTAND LSL	MIT49.5	
ROOF	BB2: 3 1/2 X 9 1/2, 2.2E PARALLAM PSL	THA413	
ROOF	VALLEY 1: 3 1/2X 9 1/2, 1.55E, TS, PSL	LSSR410Z	
ROOF	VALLEY 2: 3 1/2X 9 1/2, 1.55E, TS, PSL	LSSR410Z	
ROOF	HIP1: 3 1/2X 9 1/2, 1.55E, TS, PSL	LSSR410Z	
ROOF	HIP2: 3 1/2X 9 1/2, 1.55E, TS, PSL	LSSR410Z	
ROOF	GIRDER G1: HSS9X5X16	WELDED STEEL PLATE	SUPPORTED BY POSTS

SCHEDULE OF THE HEADERS			
MEMBER	HEADER NUMBER & SIZE	SUPPORT	NOTES
HEADER	H1: 3 1/2X11 7/8 1.55E TS LSL	4X4 POSTS	GRID LINE 3.7
HEADER	H2: 3 1/2X9 1/2, 1.55E TS LSL	4X4 POST	GRID LINE 1
HEADER	H3: 3 1/2X9 1/2, 1.55E TS LSL	4X4 POST	GRID LINE B
HEADER	H4 & H5: 4X10 DF No. 1	2-2X4 TRIMMER	GRID LINE E

#### ROOF DIAPHRAGM SPECIFICATION:


##### ROOF DIAPHRAGM SPECIFICATION:

ROOF DIAPHRAGM SHALL BE **UNBLOCKED**, (UNLESS NOTED OTHERWISE ON THE ROOF FRAMING PLAN) DOC SP-1 OR SP-2 (APA OR TECO PERFORMANCE RATED, 15/32-INCH THICK, STRAIGHT C-DX, PLYWOOD PANEL RATING 48/16, WITH 8d COMMON NAILS WITH MIN 1 5/8" PENETRATION, SPACED AT 6" O.C. AT DIAPHRAGM BOUNDARIES, ROOF SHEAR COLLECTOR MEMBERS & AT CONTINUOUS PANEL EDGES, & 6" O.C. NAIL SPACING AT OTHER PLYWOOD EDGES & 12" O.C. @ FIELD.

PLYWOOD JOINTS SHALL OCCUR AT THE CENTER OF FRAMING MEMBERS OR BLOCKING. THE MINIMUM EDGE DISTANCE FOR NAILS IN RECEIVING MEMBERS AND PLYWOOD SHALL BE 3/8- INCH FOR 2-INCH NOMINAL RECEIVING MEMBERS & 1 1/2-INCH FOR 3-INCH NOMINAL RECEIVING MEMBERS.

FLAT BLOCKING RECEIVING 10d NAILS SHALL BE 3-INCH BY 4-INCH NOMINAL OR LARGER.

NO PANEL SHALL BE LESS THAN 24" IN WIDTH. PROVIDE 1/8" GAP BETWEEN ALL PLYWOOD EDGES. SEE DETAIL ON DWG SD-1



THESE PLANS HAVE BEEN APPROVED AS SHOWN. ANY MODIFICATION TO WHAT HAS BEEN PROPOSED OR TO WHAT IS SHOWN AS EXISTING MAY REQUIRE A SEPARATE APPROVAL.

COMMUNITY DEVELOPMENT  
PLANNING DIVISION  
APPROVED  
07/31/2025  
07.31.2025

TOWN OF LAGOS  
BUILDING DIVISION  
FRAMING PLAN  
S-3

#### STRUCTURAL STEEL SPECIFICATIONS

- ASTM DESIGNATION:
- HOT ROLLED SHAPES: WIDE FLANGES, CHANNELS, ANGLES & SECTIONS SHALL CONFORM TO ASTM A992 FY=50-60, FU=65 GR50 UNLESS NOTED OTHERWISE.
- ROUND, RECTANGULAR, & SQUARE STRUCTURAL TUBING (TS) SHALL CONFORM TO ASTM A500, GRADE "B" (FY = 50 KSI) SPECIFICATION.
- BASE PLATES SHALL CONFORM TO ASTM A36.
- BASE PLATE ANCHOR BOLTS SHALL CONFORM TO ASTM A36.
- STIFF & GUSSET PLATES SHALL CONFORM TO ASTM A36.
- WORKMANSHIP:
- ALL MATERIALS AND WORKMANSHIP SHALL CONFORM WITH THE REQUIREMENTS OF THE CURRENT ISSUE OF THE A.I.S.C. SPECIFICATIONS.
- ALL SHOP CONNECTIONS SHALL BE WELDED. WELDING SHALL BE DONE IN ACCORDANCE WITH THE CURRENT REQUIREMENTS OF THE AMERICAN WELDING SOCIETY SPECIFICATIONS AND RECOMMENDATIONS.
- ALL WELDING SHALL BE PERFORMED BY CERTIFIED WELDERS & SUBJECT TO "SPECIAL INSPECTION" BY AN AUTHORIZED SPECIAL INSPECTION AGENCY.
- THE INSPECTION OF WELDING SHALL BE PERFORMED IN STRICT ACCORDANCE WITH THE PROVISIONS OF SECTION 6 OF THE AWS STRUCTURAL WELDING CODE - STEEL, D1.1.
- 1.11 BURNING FOR ENLARGEMENT OF HOLES IN CONNECTIONS AND BASE PLATES IS NOT PERMITTED.
- SUBMITTALS:
- SUBMIT SHOP DRAWINGS & MATERIAL CERTIFICATES, IN TRIPPLATES, TO THE ENGINEER OF THE RECORD FOR REVIEW AND ACCEPTANCE PRIOR TO FABRICATION.

THIS DOCUMENT IS PROPERTY OF A.S. ASSOCIATES. THE TECHNICAL INFORMATION, IDEAS AND DESIGN DETAILS HEREIN MAY BE DISCLOSED ONLY TO THOSE GOVERNMENTAL AGENCIES, HAVING JURISDICTION OVER THE PROJECT, WHICH MAY REQUIRE THE INFORMATION FOR OFFICIAL USE. THESE PLANS MAY NOT BE COPIED, REPRODUCED, OR DISCLOSED IN WHOLE OR PART, OR PART THEREOF, TO ANY THIRD PARTY WHATSOEVER, NOR ARE THEY TO BE ASSIGNED TO ANY OTHER PARTY WITHOUT THE EXPRESSED WRITTEN CONSENT OF A.S. ASSOCIATES.

**A. S. Associates**  
ENGINEERS & PLANNERS  
88 EAST 6TH STREET, UNIT 404  
PITTSBURGH, CA. 94565  
(408) 666-5933  
a.s.associates@gmail.com

REVIEWED  
FOR  
CODE COMPLIANCE  
Jul 25, 2025  
INTERWEST CONSULTING GROUP

#### LEGEND

INDICATES BEARING WALL BELLOW

INDICATES CS14 ROOF DRAG SEE DETAIL FD14/SD-3.1

REB INDICATES ROOF EDGE BEAM

RB INDICATES ROOF BEAM

B INDICATES FLOOR BEAM

EB EDGE BEAM (@ SECOND FLOOR & LOWER ROOF)


HDR INDICATES HEADER, SEE HEADER SCHEDULE DWG SD-5 FOR SIZE

NOTE:


INDICATES TYPE OF SHEAR WALL INCLUDING


CONNECTION OF:

- BLOCKING TO TOP PLATES
- BLOCKING TO SILL OR SOLE PLATE
- SILL PLATE ANCHOR BOLT SPACING
- SIZE OF SILL PLATE
- SOLE PLATE NAILING
- SHEAR PLATE NAILING
- SOLID PLATE NAILING

AND  
ALL OTHER REQUIREMENTS PERTAINING TO SHEAR WALL AS NOTED IN SHEAR WALL SCHEDULE SHOWN ON DWG SD-3. WORK THIS SYMBOL  WITH "SHEAR WALL TABLE 1.0" SCHEDULE SHOWN ON DWG SD-1.


DATE: FEB 1-2025  
SCALE: AS NOTED  
JOB TITLE: MAC-NOLAD RESIDENCE  
CIVIL  
PROFESSIONAL SHAMAN  
STATE OF CALIFORNIA  
CIVIL  
EXPIRE DATE: 02-27-2026  
PROJECT NO: 025046.45  
DRAWING NO. S-3  
CHECKED BY: A. S.






**DETAIL R-1**

ROOF EAVE @ FLAT CEILING  
NOT ALL POSSIBLE CONFIGURATIONS SHOWN  
NOT TO SCALE




**DETAIL R-2**

ROOF EAVE @ VAULTED CEILING  
NOT ALL POSSIBLE CONFIGURATIONS SHOWN  
NOT TO SCALE




**DETAIL R-3**

RIDGE BEAM FRAMING  
NOT ALL POSSIBLE CONFIGURATIONS SHOWN  
NOT TO SCALE




**DETAIL R-4**

TY. RAKE DETAIL  
NOT ALL POSSIBLE CONFIGURATIONS SHOWN  
NOT TO SCALE




**DETAIL R-6**  
TYPICAL CRIPPLE POST OVER HEADER  
NOT TO SCALE  
NOT ALL POSSIBLE CONF. SHOWN




**DETAIL RD-1**

TYP. ROOF DIAPHRAGM LAYOUT



**DETAIL R-5**


STEEL BEND FRAME  
NOT ALL POSSIBLE CONFIGURATIONS SHOWN  
NOT TO SCALE  
VERIFY DIMENSIONS WITH ARCHITECTURAL PLANS



**DETAIL CF**


TYP. CALIFORNIA FRAMING DETAIL

NOTE: NOT ALL POSSIBLE CONFIGURATIONS SHOWN



**DETAIL R-5.1**

ISOMETRIC VIEW STEEL BEND FRAME  
NOT ALL POSSIBLE CONFIGURATIONS SHOWN  
NOT TO SCALE



**DETAIL R-21**

STEEL FRAME CONNECTION TO  
TOP PLATES @ GRIDLINE F.5  
NOT TO SCALE  
NOT ALL POSSIBLE CONF. SHOWN

COMMUNITY DEVELOPMENT  
PLANNING DIVISION  
APPROVED  
07/31/2025

PLAN REVIEW APPROVAL

07.31.2025

TOWN OF LOS GATOS  
BUILDING DIVISION

THESE PLANS HAVE BEEN APPROVED AS  
SHOWN. ANY MODIFICATION TO WHAT HAS  
BEEN PROPOSED OR TO WHAT IS SHOWN AS  
EXISTING MAY REQUIRE A SEPARATE  
APPROVAL.

REVIEWED  
FOR  
CODE COMPLIANCE  
Jul 25, 2025  
INTERWEST CONSULTING GROUP

A. S. Associates  
ENGINEERS & PLANNERS  
88 EAST 6TH STREET, UNIT 404  
PITTSBURG, CA. 94565  
(408) 666-5933  
a.s.associates@gmail.com



SD-2

025046.45

DRAWING NO.

DATE:

SCALE:

AS NOTED

NO.:

DATE:

ISSUED FOR COORDINATION

NO.:

DATE:

ISSUED FOR PLAN REVIEW

NO.:

DATE:

ISSUED FOR PLAN ARCHITECTURAL CHANGES

NO.:

DATE:

ISSUED FOR GRIDLINE F.5




NO.:

DATE:

ISSUED FOR GRID

**SHEAR WALL NOTES:**

1. SHEAR WALL PLYWOOD PANEL GRADE: SHEAR WALL OR SHEAR PANEL SHALL BE EITHER PLYWOOD SHEATHING THICKNESS SHALL BE AS SHOWN IN THE SHEAR WALL SCHEDULE. SHEAR PLYWOOD SHALL BE C-DX, STRUCTURAL GRADE II, OR OSB ENGINEERED WOOD. OSB SHALL HAVE I.C.B.O. APPROVED TESTING FOR CYCLIC LATERAL FORCE. OSB SHALL NOT BE USED IN WET SEASONS OR UNDER WET CONDITIONS.
2. NAILS SHALL BE COMMON NAILS OR GALVANIZED COMMON NAILS
3. NAIL SIZE AND SPACING SHALL BE AS PER SHEAR WALL SCHEDULE. NAILING SHALL BE APPLIED TO ALL DIAPHRAGM BOUNDARIES AND PLYWOOD PANEL EDGES. NAIL SPACING AT INTERMEDIATE FRAMING MEMBERS SHALL BE AT 12" O.C. UNLESS NOTED OTHERWISE.
4. FLOOR DIAPHRAGM SHALL BE NAILED INDEPENDENT FROM SOLE PLATE NAILING.
5. PROVIDE (SEE SCHEDULE) NOMINAL OR WIDER BLOCKING AT ALL UNSUPPORTED PANEL EDGES OF SHEAR WALLS.
6. UNLESS NOTES OR SHOWN OTHERWISE ON THE PLANS, WALLS BETWEEN SHEAR WALLS OR SHEAR PANELS SHALL RECEIVE PLYWOOD (THICKNESS TO MATCH SHEAR PLYWOOD) WITH (SEE SCHEDULE) NAILS AT 6" O.C. AT ALL PANEL EDGES AND 12" O.C. AT FIELD.
7. WHERE 16d NAILS ARE USED AND SUCH NAIL SPACING IS 3" O.C. OR LESS USE 3-INCH NOMINAL.
8. NAIL HEAD SHALL NOT PENETRATE THE EXTREME FIBER OF PLYWOOD PANEL. (SEE DETAIL W-1)
9. IN-HORIZ. PLYWOOD DIAPHRAGM NO PANEL LESS THAN 24" WIDE MAY BE USED.
10. SHEAR WALL MATERIAL SHALL EXTEND TO THE EDGE OF DOOR AND WINDOW OPENINGS. USE "C" CUT AT DOORWAY AND WINDOWS.
11. WHEN STUDS ARE DIRECTLY PLACED ON TOP OF SILL AND/OR SOLE PLATE AND THE SHEAR PANEL IS SHEARED AT EACH FACE, THE WIDTH OF THE SILL OR SOLE PLATE SHALL BE THE SAME AS THE STUD WIDTH.
12. SHEAR WALL PENETRATION SHALL BE SUBJECT TO OBTAINING PRIOR APPROVAL FROM ENGINEER. (FOR SMALL OPENINGS SEE DETAIL W-4)
13. SHEAR PANEL STUD SHALL BE 2X4 (MIN) SPACED @ 16" O.C., EXCEPT AS NOTED ON THE SHEAR WALL SCHEDULE.



**INSTALLATION:**

- DRILL HOLE TO SPECIFIED DIAMETER AND DEPTH.
- REMOVE DUST FROM HOLE WITH OIL-FREE COMPRESSED AIR.
- CLEAN WITH NYLON BRUSH AND BLOW OUT REMAINING DUST.
- DUST LEFT IN HOLE WILL REDUCE EPOXY'S HOLDING CAPACITY.
- DIPSENE A BEAD OF EPOXY-1" OFF TO THE SIDE TO EJECT FOR EXCESS EPOXY. USE EPOXY OF UNIFORM GRAY COLOR BEFORE USING.
- WITHDRAW NOZZLE AS HOLE FILLS UP.
- ANCHORS MUST BE CLEAN AND OIL FREE.
- INSERT ANCHOR, TURNING SLOWLY UNTIL ANCHOR HITS THE BOTTOM OF THE HOLE. DO NOT DISTURB WHILE SETTING.

TABLE A

	40° F	60° F	80° F	100° F
SET	72 HRS	24 HRS	20 HRS	16 HRS

TABLE B

STUD DIA.	DRILL BIT DIA.	MIN. EMBED.	EDGE DIST.	END DIST.	AVG. ULT. SHEAR LOAD	
					PARALLEL TO PLATE	PERPENDICULAR TO PLATE
5/8	3/4	5	1 3/4	7 1/2	8000	2000
5/8	3/4	5	1 3/4	7 1/2	2360	590

1. THE ALLOWABLE LOAD FOR THE CONNECTOR WILL BE THE LESSER OF THE WOOD BEARING CAPACITY OR CONCRETE STRENGTH.

TABLE C

TENSION LOADS FOR THREADED ROD ANCHORS IN CONCRETE FOUNDATION STEMWALL INSTALLATION						
STUD DIA.	DRILL BIT DIA.	MIN. EMBED.	MIN. WALL THICKNESS	MIN. EDGE DIST.	MIN. END DIST.	AVG. ULT. TENSION LOAD
5/8	3/4	10	6	1 3/4	5	22000 5750
7/8	1	15	8	1 3/4	5	33600 8400 11200


DETAIL RFB-1

TYP. INSTALLATION OF RETROFIT BOLTS FOR HOLDOWNS & SILL PLATE ANCHOR BOLTS

NOTE:  
1. SPECIAL INSPECTION IS REQUIRED FOR ALL EPOXYED BOLTS.  
2. USE SIMPSON HIGH STRENGTH EPOXY TYPE "SET", XPC-ES ESR 2508

NOTE: NOT ALL POSSIBLE CONFIGURATIONS ARE SHOWN

SD-07174a



DETAIL WC-1


PLAN-SHEAR WALL CORNER

NOTE: NOT ALL POSSIBLE CONFIGURATIONS ARE SHOWN

HOLDOWN MODEL	STEMWALL WIDTH	SSTB DIA.	SDS SCREWS	MIN. WOOD MEMBER THICKNESS
HDU2	8"	5/8" SSTB20	6-SDS 1 4" X 2 1/2"	3"
HDU4	8"	5/8" SSTB20	10-SDS 1 4" X 2 1/2"	3"
HDU4	8"	5/8" SSTB24	14-SDS 1 4" X 2 1/2"	3"

NOTE:  
1. LOCATE THE BOLT FOR THE CENTERLINE DISTANCE OFF THE FACE OF THE STUD (CL) AND THE APPROPRIATE LENGTH NEED TO CLEAR THE STAND OFF DISTANCE (SO).  
2. STEMWALL FOUNDATION SHALL BE MONO POUR

TABLE 2.1



COMMUNITY DEVELOPMENT  
PLANNING DIVISION  
APPROVED

07/31/2025

PLAN REVIEW APPROVAL


07.31.2025

TOWN OF LOS GATOS  
BUILDING DIVISION

SCHEDULE, SECTIONS  
& DETAILS

THIS DOCUMENT IS PROPERTY OF A.S. ASSOCIATES. THE TECHNICAL INFORMATION, IDEAS AND DESIGN DETAILS HEREIN MAY BE DISCLOSED ONLY TO THOSE GOVERNMENT OFFICIALS, ENGINEERS, HAVING JURISDICTION OVER THE PROJECT. THESE PLANS MAY NOT BE REPRODUCED, COPIED, OR DISCLOSED IN WHOLE OR PART, IN ANY FORM OR BY ANY MEANS, WHETHER BY ELECTRONIC, MECHANICAL, OR OTHERWISE, WITHOUT THE EXPRESSED WRITTEN CONSENT OF A.S. ASSOCIATES.



**A. S. Associates**  
ENGINEERS & PLANNERS  
88 EAST 16TH STREET, SUITE 104  
PITTSBURG, CA. 94565  
amn@associates@gmail.com




TYPICAL SHEAR WALL TABLE 2-6 (SCHEDULE OF FASTENERS)					
<b>Shear wall designation</b>	Type 6	Type 4	Type 3	Type 2	NOTES
Shear value per foot of wall	260 plf (panels applied directly to framing)	380 plf (panels applied directly to framing)	490 plf (panels applied directly to framing)	640 plf (panels applied directly to framing)	
Panel grade (LAYER PLY WOOD)	Structural Panels	Structural Panels	Structural Panels	Structural Panels	SHEAR WALL PANEL SHALL BE PLYWOOD, BLOCKED, DOC SP-1 OR SP-2 (APA OR TECO PERFORMANCE RATED, 15/32 INCH THICK STRUCTURAL C-DX PLYWOOD PANELS) AND OSB 4/8". OSB shall not be used in moist conditions
Use of OSB is subject to express approval of the Engineer.					
Panel thickness	15/32"	15/32"	15/32"	15/32"	
Panel nailing	8d (2 1/2" x 0.131 common)	8d (2 1/2" x 0.131 common)	8d (2 1/2" x 0.131 common)	8d (2 1/2" x 0.131 common)	RIM JOIST OR BLOCKING RECEIVING SDS 250X500 SCREWS SHALL BE (TJ) ENGINEERED WOOD 3/12" X THICK MINIMUM.
A35 steel to sole plate or sole/sill plate	20° O/C	16° O/C	12° O/C	10° O/C	
Sill plate size & fastener penetration (13/8")	2x with 16d @ 6" O/C	2x with 16d @ 6" O/C	3x with SDS25X500	2x with SDS25X500	Rim joist receiving SDS25X500 shall be 3" member
Sole plate size & fastener spacing (11/2")	2x with 16d @ 6" O/C	2x with 16d @ 6" O/C	3x (see note a)	3x (see note a)	
Sill plate size (DF/PT) placed on concrete	2X	2X	3X (see note a)	3X (see note a)	3X SILL PLATE SHALL NOT BE LESS THAN A SINGLE 3X MEMBER
Fastener members (min. size)	2-2X	2-2X	3X	3X	3X SILL PLATE SHALL NOT BE LESS THAN A SINGLE 3X MEMBER
Sill Plate Anchor bolt size, length & spacing	5/8" Øx10" @ 48" O/C	5/8" Øx10" @ 28" O/C	5/8" Øx12" @ 22" O/C	5/8" Øx12" @ 16" O/C	

NOTE: WHERE PANELS ARE APPLIED ON BOTH FACES OF A WALL AND FASTENERS SPACING IS LESS THAN 6" O/C, OM EITHER SIDE , PANEL JOINTS SHALL BE OFFSET TO FALL ON DIFFERENT FRAMING MEMBERS, OR FRAMING SHALL BE 3-INCH NOMINAL OR THICKER AT ADJOINING PANEL EDGES.

NOTE: NOT ALL POSSIBLE CONFIGURATIONS SHOWN



LOAD-PATH FASTENERS:  
DIAPHRAGM SHEATHING NAILS OR OTHER APPROVED  
CONNECTORS SHALL BE DRIVEN SO THAT THEIR HEAD OR CROWN IS FLUSH WITH SURFACE OF SHEATHING.



DETAIL W-5

TYP. OPENING DETAIL IN FLOOR AND ROOF DIAPHRAGM



NOTE: NOT ALL POSSIBLE CONFIGURATIONS SHOWN

DETAIL AB-1  
SILL PLATE & ANCHOR BOLTS

NOTE: NOT ALL POSSIBLE CONFIGURATIONS SHOWN

DETAIL AB-1  
TYP. EPOXY ANCHOR BOLT SPACING  
SILL PLATE & ANCHOR BOLTS

NOTE: NOT ALL POSSIBLE CONFIGURATIONS SHOWN



DETAIL HB-1  
TYP. HOLDOWN ANCHOR BOLT INSTALLATION

07/31/2025

NOTE: ALL HOLDOWN INSTALLATION AND PARTS THEREOF SHALL BE PER MANUFACTURER'S SPECIFICATIONS

THESE PLANS HAVE BEEN APPROVED AS SHOWN. ANY MODIFICATION TO WHAT HAS BEEN PROPOSED OR TO WHAT IS SHOWN AS EXISTING MAY REQUIRE A SEPARATE APPROVAL.


07.31.2025

TOWN OF LOS GATOS  
BUILDING DIVISION  
SCHEDULE, SECTIONS  
& DETAILS

SD-3

DATE: FEB 1-2025  
SCALE: AS NOTED  
DRAWN BY: H.S.  
CHECKED BY: A.S.  
PROJECT NO: 025046.45  
DRAWING NO: 025046.45  
DATE: FEB 19-2025  
SCALE: AS NOTED  
DRAWN BY: H.S.  
CHECKED BY: A.S.  
PROJECT NO: 025046.45  
DRAWING NO: 025046.45  
DATE: APR 19-2025  
SCALE: AS NOTED  
DRAWN BY: H.S.  
CHECKED BY: A.S.  
PROJECT NO: 025046.45  
DRAWING NO: 025046.45  
DATE: MAY 19-2025  
SCALE: AS NOTED  
DRAWN BY: H.S.  
CHECKED BY: A.S.<






STRONG-WALL® WSWH ANCHORAGE – TYPICAL SECTIONS 1 WSWH ANCHOR BOLTS 3 WSWH ANCHOR BOLT EXTENSION 4 WSWH ANCHOR BOLT TEMPLATES 6

WSWH ANCHORAGE SOLUTIONS FOR 2500 PSI CONCRETE					
DESIGN CRITERIA	CONCRETE CONDITION	ANCHOR STRENGTH	WSWH-AB1 ANCHOR BOLT		
			ASD ALLOWABLE UPLIFT (lbs)	W (in)	d <sub>e</sub> (in)
SEISMIC	CRACKED	STANDARD	16,000	33	11
		HIGH STRENGTH	17,100	35	12
	UNCRACKED	STANDARD	34,100	52	18
		HIGH STRENGTH	36,800	55	19
WIND	CRACKED	STANDARD	15,700	28	10
		HIGH STRENGTH	17,100	30	10
		STANDARD	33,500	45	15
		HIGH STRENGTH	36,800	48	16
		STANDARD	6,200	16	6
		HIGH STRENGTH	11,400	24	8
	UNCRACKED	STANDARD	17,100	32	11
		HIGH STRENGTH	21,100	36	12
		STANDARD	27,300	42	14
		HIGH STRENGTH	34,100	48	16
		STANDARD	36,800	51	17
		HIGH STRENGTH	6,400	14	6

WSWH ANCHORAGE SOLUTIONS FOR 3000 PSI CONCRETE					
DESIGN CRITERIA	CONCRETE CONDITION	ANCHOR STRENGTH	WSWH-AB1 ANCHOR BOLT		
			ASD ALLOWABLE UPLIFT (lbs)	W (in)	d <sub>e</sub> (in)
SEISMIC	CRACKED	STANDARD	16,000	31	11
		HIGH STRENGTH	17,100	33	11
	UNCRACKED	STANDARD	33,900	49	17
		HIGH STRENGTH	36,800	52	18
WIND	CRACKED	STANDARD	16,300	27	9
		HIGH STRENGTH	17,100	28	10
		STANDARD	34,000	43	15
		HIGH STRENGTH	36,800	46	16
		STANDARD	5,600	14	6
		HIGH STRENGTH	10,200	21	7
	UNCRACKED	STANDARD	17,100	30	10
		HIGH STRENGTH	20,000	33	11
		STANDARD	26,500	39	13
		HIGH STRENGTH	33,600	45	15
		STANDARD	36,800	48	16
		HIGH STRENGTH	6,200	13	6

WSWH ANCHORAGE SOLUTIONS FOR 4500 PSI CONCRETE					
DESIGN CRITERIA	CONCRETE CONDITION	ANCHOR STRENGTH	WSWH-AB1 ANCHOR BOLT		
			ASD ALLOWABLE UPLIFT (lbs)	W (in)	d <sub>e</sub> (in)
SEISMIC	CRACKED	STANDARD	16,000	27	9
		HIGH STRENGTH	17,100	29	10
	UNCRACKED	STANDARD	34,700	44	15
		HIGH STRENGTH	36,800	46	16
WIND	CRACKED	STANDARD	15,700	23	8
		HIGH STRENGTH	17,100	25	9
		STANDARD	33,900	38	13
		HIGH STRENGTH	36,800	40	14
		STANDARD	6,800	14	6
		HIGH STRENGTH	11,600	20	7
	UNCRACKED	STANDARD	17,100	26	9
		HIGH STRENGTH	21,400	30	10
		STANDARD	28,400	36	12
		HIGH STRENGTH	32,400	39	13
		STANDARD	36,800	43	15
		HIGH STRENGTH	6,800	12	6



STRONG-WALL® HIGH STRENGTH WOOD SHEARWALL TENSION ANCHORAGE SCHEDULE 2,500, 3,000 AND 4,500 PSI 2 STRONG-WALL® WSWH SHEAR ANCHORAGE SCHEDULE AND DETAILS 5

NAME	DATE	REVISIONS
DATE	03-16-2021	FIRST RELEASE - 2018 BC
SCALE	N.T.S.	2021 BC REVISIONS
CHECKED		
SHEET		
WSWH1		
OF SHEETS		
JOB NO.		

**STRONG-WALL® ANCHORAGE DETAILS ENGINEERED DESIGNS**


**Strong-Tie** THERE IS NO EQUAL

## STRONG-WALL® HIGH STRENGTH WOOD SHEARWALL MODELS

MODEL NO.	W (in.)	H (in.)	ANCHOR BOLTS QUANTITY	DIA. (in.)	TOTAL WALL WEIGHT (lb.)
WSWH12x7	12	84	2	1	105
WSWH18x7	18	84	2	1	155
WSWH12x8	12	96	2	1	120
WSWH18x8	18	96	2	1	175
WSWH24x8	24	96	2	1	225
WSWH12x9	12	108	2	1	130
WSWH18x9	18	108	2	1	195
WSWH24x9	24	108	2	1	250
WSWH12x10	12	120	2	1	145
WSWH18x10	18	120	2	1	210
WSWH24x10	24	120	2	1	275
WSWH12x12	12	144	2	1	165
WSWH18x12	18	144	2	1	245
WSWH24x12	24	144	2	1	325
WSWH18x14	18	168	2	1	285
WSWH24x14	24	168	2	1	370
WSWH24x16	24	192	2	1	420
WSWH18x20	18	240	2	1	390
WSWH24x20	24	240	2	1	520

NOTES:  
1. FOR HEIGHTS NOT LISTED, ORDER THE NEXT TALLEST PANEL AND TRIM TO FIT.  
MINIMUM TRIMMED HEIGHT FOR ALL PANELS IS 74 1/2".  
2. ALL PANELS COME WITH PRE-ATTACHED HOLDOWNS, TWO HEAVY HEX NUTS, TWO  
HEAVY BEARING PLATES, ONE WSWH-TP TOP CONNECTION PLATE WITH REQUIRED  
FASTENERS AND INSTALLATION INSTRUCTIONS.  
3. ALL PANELS ARE 3 1/2" THICK.

PLACE STRONG-WALL® HIGH STRENGTH WOOD SHEARWALL OVER THE ANCHOR BOLTS AND SECURE WITH HEAVY BEARING PLATES AND HEAVY HEX NUTS (PROVIDED). DO NOT USE AN IMPACT WRENCH. USE 1 1/8" WRENCH FOR 1" NUT. TIGHTEN ANCHOR NUTS FINGER TIGHT + 1/2" TURN.



DESIGNER IS PERMITTED TO MODIFY DETAILS FOR SPECIFIC CONDITIONS.

WSWH-TP CONNECTION	FASTENER QUANTITY
MODEL NO.	
SWS16150	SDS25600
WSWH-TP12	14
WSWH-TP18	26
WSWH-TP24	46
	8

ATTACH WSWH-TP PLATE (PROVIDED) ON ONE SIDE ONLY WITH A COMBINATION OF SDS 1/4" x 6" AND SWS16150 CONNECTOR SCREWS.

ALIGN WSWH-TP NOTCHES WITH BOTTOM OF TOP PLATES

INSTALL SDS 1/4" x 6" SCREWS AT AN ANGLE THAT PREVENTS THEM FROM EXITING SIDE OF FRAMING; APPROX. 30 DEGREES (TYP.)

TOP PLATES  
SWS16150  
SDS25600

1" DIAMETER BY 1/4" DEEP COUNTERBORE  
STRONG-WALL® HIGH STRENGTH WOOD SHEARWALL

FURRING NOT REQUIRED EXCEPT AS REQUIRED FOR FINISH MATERIAL ATTACHMENT  
OPTIONAL 1" DIAMETER BY 1/4" DEEP COUNTERBORE  
SECTION 4x FRAMING

DESIGNER IS PERMITTED TO MODIFY DETAILS FOR SPECIFIC CONDITIONS.

LTP4 SPACING BY OTHERS

4x SHIM BLOCK

DESIGNER IS PERMITTED TO MODIFY DETAILS FOR SPECIFIC CONDITIONS.

INSTALL SDS 1/4" x 6" SCREWS (MIN.) FROM THE TOP SIDE OF THE PLATES PER QTY. AND SPACING REQUIREMENTS DETAILED IN 8/WSWH2.

FULL-HEIGHT ADJACENT FRAMING BY OTHERS  
SEE 6/WSWH2 FOR TOP CONNECTION  
STRONG-WALL® HIGH STRENGTH WOOD SHEARWALL

1" TO 4" SHIM BLOCK  
CRIPPLE SHEARWALL, BLOCKING AND STRAP BY OTHERS  
SEE 6/WSWH2 FOR TOP CONNECTION

FULL-HEIGHT ADJACENT FRAMING BY OTHERS  
CRIPPLE WALL  
STRONG-WALL® HIGH STRENGTH WOOD SHEARWALL

DESIGNER SHALL DESIGN AND DETAIL FOR:  
1. SHEAR TRANSFER  
2. OUT-OF-PLANE LOADING EFFECT  
3. INCREASED OVERTURNING AND DRIFT DUE TO ADDITIONAL HEIGHT



FOR 8" TO 12" BLOCK DEPTHS:  
ATTACH SIMPSON STRONG-TIE® CS16 STRAPS AT EDGE OF WSWH PANEL (EACH SIDE) USING 10dx1 1/2" NAILS  
SHIM BLOCK HEIGHTS GREATER THAN 8" AND UP TO 10":  
• 8 NAILS INTO BLOCK  
• 8 NAILS INTO WSWH PANEL  
SHIM BLOCK HEIGHTS GREATER THAN 10" AND UP TO 12":  
• 10 NAILS INTO BLOCK  
• 10 NAILS INTO WSWH PANEL

## STRONG-WALL® WSWH MODELS



### 1 STANDARD INSTALLATION BASE CONNECTION

### 4 TOP CONNECTION

### 9 TOP OF WALL HEIGHT ADJUSTMENTS



WSWH-TP CONNECTION	FASTENER QUANTITY
MODEL NO.	
SWS16150	SDS25600
WSWH-TP12	28
WSWH-TP18	52
WSWH-TP24	92
	16







## SINGLE STORY WSWH ON CONCRETE

### 2 WOOD FLOOR SYSTEM BASE CONNECTION

### 5 BACK-TO-BACK TOP CONNECTION

### 10 TRIM ZONE AND ALLOWABLE HOLES



## ALTERNATE WSWH GARAGE FRONT OPTIONS

### 3 RAKE WALL

### 11 NOTES

NO.	DATE	REVISIONS
0	11-20-2020	2021 IBC REVISIONS
1	03-16-2021	2021 IBC REVISIONS

REVIEWED FOR CODE COMPLIANCE  
Jul 25, 2025  
INTERWEST CONSULTING GROUP

SIMPSON Strong-Tie, Co. Inc.  
• 5956 W. Las Positas Blvd., Pleasanton, CA 94588  
• Tel: (800) 989-5099  
• Website: www.strongtie.com

SIMPSON Strong-Tie  
THERE IS NO EQUAL

COMMUNITY DEVELOPMENT PLANNING DIVISION APPROVED  
07/31/2025  
07.31.2025  
TOWN OF LOS GATOS BUILDING DIVISION  
EXISTING NOTES REQUIRE A SEPARATE APPROVAL

CERTIFICATE OF COMPLIANCE - RESIDENTIAL PERFORMANCE COMPLIANCE METHOD  
Project Name: Browns Lane Addition  
Calculation Description: Title 24 AnalysisCF1R-PRF-01-E  
Calculation Date/Time: 2025-05-27T10:49:12-07:00  
(Page 1 of 12)  
Input File Name: Browns Lane Addition (14340).rev.ribd22x

GENERAL INFORMATION											
01	Project Name	Browns Lane Addition									
02	Run Title	Title 24 Analysis									
03	Project Location	14340 Browns Lane									
04	City	Los Gatos	05	Standards Version	2022						
06	Zip code	95032	07	Software Version	EnergyPro 9.4						
08	Climate Zone	4	09	Front Orientation (deg/ Cardinal)	270						
10	Building Type	Single family	11	Number of Dwelling Units	1						
12	Project Scope	Addition and/or Alteration	13	Number of Bedrooms	3						
14	Addition Cond. Floor Area (ft <sup>2</sup> )	499	15	Number of Stories	1						
16	Existing Cond. Floor Area (ft <sup>2</sup> )	841	17	Penetration Average U-factor	0.3						
18	Total Cond. Floor Area (ft <sup>2</sup> )	1340	19	Glazing Percentage (%)	20.64%						
20	ADU Bedroom Count	n/a	21	ADU Conditioned Floor Area	n/a						
22	Fuel Type	Natural gas	23	No Dwelling Unit	No						

COMPRAUCE RESULTS											
01	Building Complies with Computer Performance										
02	Building does not require field testing or HERS verification										
03	This building incorporates one or more Special Features shown below										

Registration Number:  
CA Building Energy Efficiency Standards - 2022 Residential ComplianceRegistration Date/Time:  
Report Version: 2022.0.000  
Schema Version: rev.20220901HERS Provider:  
Report Generated: 2025-05-27 10:49:28CERTIFICATE OF COMPLIANCE - RESIDENTIAL PERFORMANCE COMPLIANCE METHOD  
Project Name: Browns Lane Addition  
Calculation Description: Title 24 AnalysisCF1R-PRF-01-E  
Calculation Date/Time: 2025-05-27T10:49:12-07:00  
(Page 4 of 12)  
Input File Name: Browns Lane Addition (14340).rev.ribd22x

OPAQUE SURFACES											
01	02	03	04	05	06	07	08	09	10	11	12
Name	Zone	Construction	Azimuth	Orientation	Gross Area (ft <sup>2</sup> )	Window and Door Area (ft <sup>2</sup> )	Tilt (deg)	Wall Exceptions	Status	Verified Existing Condition	
Front Wall	Existing Living Area	R-0 Wall	270	Front	40	0	90	none	Existing	No	
Left Wall	Existing Living Area	R-0 Wall	0	Left	80	6	90	none	Existing	No	
Rear Wall	Existing Living Area	R-0 Wall	90	Back	176	37.3	90	none	Existing	No	
Right Wall	Existing Living Area	R-0 Wall	180	Right	272	80	90	none	Existing	No	
Front Wall 2	New Living Area	R-15 Wall	270	Front	252	49.1	90	Extension	New	n/a	
Left Wall 2	New Living Area	R-15 Wall	0	Left	297	65	90	Extension	New	n/a	
Rear Wall 2	New Living Area	R-15 Wall	90	Back	99	4	90	Extension	New	n/a	
Right Wall 2	New Living Area	R-15 Wall	180	Right	261	25	90	Extension	New	n/a	
Interior Surface	Existing Living Area >> Garage	R-0 Wall1	n/a	n/a	136	17.8	n/a		Existing	No	
Interior Surface	New Living Area >> Garage	R-15 Wall1	n/a	n/a	32	0	n/a		New	n/a	
Interior Surface	New Living Area >> Existing Living Area	R-0 Wall1	n/a	n/a	320	0	n/a		New	n/a	
Roof 4	Existing Living Area	R-11 Roof Attic	n/a	n/a	827	n/a	n/a		Existing	No	
Front Wall 3	Garage	R-0 Wall	270	Front	160	0	90	none	Existing	No	
Left Wall 3	Garage	R-0 Wall	0	Left	192	0	90	none	Existing	No	
Rear Wall 3	Garage	R-0 Wall	90	Back	160	0	90	none	Existing	No	
Right Wall 3	Garage	R-0 Wall	180	Right	192	0	90	none	Existing	No	

Registration Number:  
CA Building Energy Efficiency Standards - 2022 Residential ComplianceReport Version: 2022.0.000  
Schema Version: rev.20220901HERS Provider:  
Report Generated: 2025-05-27 10:49:28CERTIFICATE OF COMPLIANCE - RESIDENTIAL PERFORMANCE COMPLIANCE METHOD  
Project Name: Browns Lane Addition  
Calculation Description: Title 24 AnalysisCF1R-PRF-01-E  
Calculation Date/Time: 2025-05-27T10:49:12-07:00  
(Page 7 of 12)  
Input File Name: Browns Lane Addition (14340).rev.ribd22x

OPAQUE DOORS											
01	02	03	04	05	06	07	08	09	10		
Name	Side of Building		Area (ft <sup>2</sup> )		U-factor		Status		Verified Existing Condition		
D1	Front Wall 2		17.8		0.2		New		n/a		
D2	Interior Surface		17.8		0.2		Altered		No		
SLAB FLOORS											
01	02	03	04	05	06	07	08	09	10		
Name	Zone	Area (ft <sup>2</sup> )	Perimeter (ft)	Edge Insul. R-value and Depth	Edge Insul. R-value and Depth	Carpeted Fraction	Heated	Status	Verified Existing Condition		
Slab	Existing Living Area	841	61	none	0	80%	No		Existing	No	
Slab 2	New Living Area	499	101	none	0	100%	No		New	n/a	
Slab 3	Garage	486	88	none	0	0%	No		Existing	No	
OPAQUE SURFACE CONSTRUCTIONS											
01	02	03	04	05	06	07	08				
Construction Name	Surface Type	Construction Type	Framing	Total Cavity R-value	Interior / Exterior Continuous R-value	U-factor	Assembly Layers				
R-0 Wall	Exterior Walls	Wood Framed Wall	2x4 @ 16 in. O. C.	R-0	None / None	0.484	Roofing: Light Roof (Asphalt Shingle) Roof Deck: Wood Siding/sheathing/decking Cavity / Frame: no insul. / 2x4 Inside Finish: Gypsum Board				
R-15 Wall	Exterior Walls	Wood Framed Wall	2x4 @ 16 in. O. C.	R-0	None / None	0.644	Roofing: Light Roof (Asphalt Shingle) Roof Deck: Wood Siding/sheathing/decking Cavity / Frame: R-15 / 2x4 Inside Finish: 3 Coat Stucco				
R-11 Roof Attic	Ceilings (below attic)	Wood Framed Ceiling	2x4 @ 24 in. O. C.	R-11	None / None	0.081	Roofing: Light Roof (Asphalt Shingle) Roof Deck: Wood Siding/sheathing/decking Cavity / Frame: R-11 / 2x4 Inside Finish: Gypsum Board				

Registration Number:  
CA Building Energy Efficiency Standards - 2022 Residential ComplianceReport Version: 2022.0.000  
Schema Version: rev.20220901HERS Provider:  
Report Generated: 2025-05-27 10:49:28CERTIFICATE OF COMPLIANCE - RESIDENTIAL PERFORMANCE COMPLIANCE METHOD  
Project Name: Browns Lane Addition  
Calculation Description: Title 24 AnalysisCF1R-PRF-01-E  
Calculation Date/Time: 2025-05-27T10:49:12-07:00  
(Page 2 of 12)  
Input File Name: Browns Lane Addition (14340).rev.ribd22x

ENERGY USE SUMMARY											
Energy Use	Standard Design Source Energy (EDR1) (kBtu/ft <sup>2</sup> - yr)	Standard Design TDV Energy (EDR2) (kBtu/ft <sup>2</sup> - yr)	Proposed Design Source Energy (EDR1) (kBtu/ft <sup>2</sup> - yr)	Proposed Design TDV Energy (EDR2) (kBtu/ft <sup>2</sup> - yr)	Margin (EDR1)	Margin (EDR2)					
Space Heating	0	36.92	0	36.62	0	0.3					
Space Cooling	0	49.55	0	48.93	0	0.62					
IAQ Ventilation	0	0	0	0	0	0					
Water Heating	0	49.14	0	49.14	0	0					
Self Utilization/Flexibility Credit					0	0					
Efficiency Compliance Total	0</td										

## CERTIFICATE OF COMPLIANCE - RESIDENTIAL PERFORMANCE COMPLIANCE METHOD

Project Name: Browns Lane Addition

CF1R-PRF-01-E  
Calculation Date/Time: 2025-05-27T10:49:12-07:00  
(Page 10 of 12)  
Input File Name: Browns Lane Addition (14340).rev.rbd22x

Calculation Description: Title 24 Analysis

## SPACE CONDITIONING SYSTEMS

01	02	03	04	05	06	07	08	09	10	11
Name	System Type	Heating Unit Name	Heating Equipment Count	Cooling Unit Name	Cooling Equipment Count	Fan Name	Distribution Name	Status	Verified Existing Condition	Existing HVAC System
HVAC System1	Heating and cooling system other	Heating Component 1	1	Cooling Component 1	1	HVAC Fan 1	Air Distribution System 1	Existing	No	

## HVAC - HEATING UNIT TYPES

01	02	03	04	05
Name	System Type	Number of Units	Heating Efficiency	Heating Unit Brand
Heating Component 1	Central gas furnace	1	AFUE - 80	n/a

## HVAC - DISTRIBUTION SYSTEMS

01	02	03	04	05	06	07	08	09	10	11	12	13	14	15	16
Name	Type	Design Type	Duct Ins. R-value	Duct Location	Surface Area	Bypass Duct	Duct Leakage	HERS Verification	Status	Verified Existing Condition	Existing Distribution System	New Ducts	≥ 25 ft		
Air Distribution System 1	Unconditioned attic	Non-Verified	R-6	R-6	Attic	Attic	n/a	n/a	No Bypass Duct	Existing (not specified)	Air Distribution System 1-hers-dist	Existing + New	No		No

## HVAC - FAN SYSTEMS

01	02	03	04
Name	Type	Fan Power (Watts/CFM)	Name
HVAC Fan 1	HVAC Fan	0.58	n/a

Registration Number:

Registration Date/Time:

HERS Provider:

CA Building Energy Efficiency Standards - 2022 Residential Compliance

Report Version: 2022.0.000

Report Generated: 2025-05-27 10:49:28

Schema Version: rev 20220901

Report Generated: 2025-05-27 10:49:28

## RESIDENTIAL MEASURES SUMMARY RMS-1

Project Name	Building Type	Single Family	Additional Alone	Date				
	Multi Family	Excluded Addition/Alteration						
Project Name: Browns Lane Addition	Building Type: Single Family	Excluded Addition/Alteration: 0		Date: 5/27/2025				
Project Address: 14340 Browns Lane Los Gatos	California Energy Zone: Zone 04	Total Square Footage: 1,340	Number of Units: 1					
<b>INSULATION</b>	<b>Area</b>	<b>Construction Type</b>	<b>Cavity (ft³)</b>	<b>Special Features</b>				
Wall	Wood Framed	- no insulation	40	Existing				
Wall	Wood Framed	- no insulation	74	Existing				
Wall	Wood Framed	- no insulation	139	Existing				
Wall	Wood Framed	- no insulation	102	Existing				
Roof	Wood Framed Attic	R-11	827	Existing				
Slab	Unheated Slab-on-Grade	- no insulation	841	Perim = 61'				
Densimg	Wood Framed	- no insulation	118	Existing				
Wall	Wood Framed	- no insulation	203	Existing				
<b>FENESTRATION</b>	<b>Total Area</b>	<b>Orientation</b>	<b>U-Fac</b>	<b>SHGC</b>	<b>Overhang</b>	<b>Sidedefs</b>	<b>Exterior Shades</b>	<b>Status</b>
27.1	27.1	Glassing Percentage:	20.6%	New/Altered	Average U-Factor:	0.30		
Left (E)	6.0							Altered
Right (E)	8.7	0.300	0.23	none	none	N/A		Altered
Right (S)	8.0	0.300	0.23	none	none	N/A		Altered
Skylight	14.0	1.190	0.83	none	none	N/A		Existing
Front (W)	45.3	0.300	0.23	none	none	N/A		New
Left (W)	65.0	0.300	0.23	none	none	N/A		New
Rear (E)	4.0	0.300	0.23	none	none	N/A		New
Right (S)	25.0	0.300	0.23	none	none	N/A		New
<b>HVAC SYSTEMS</b>	<b>Qty.</b>	<b>Heating</b>	<b>Min. Eff</b>	<b>Cooling</b>	<b>Min. Eff</b>	<b>Thermostat</b>	<b>Status</b>	
1	Gas Central Furnace	89% AFUE	No Cooling	14.9 SEER	Seaserv	Existing		
<b>HVAC DISTRIBUTION</b>	<b>Location</b>	<b>Heating</b>	<b>Cooling</b>	<b>Duct Location</b>	<b>Duct R-Value</b>	<b>Status</b>		
HVAC System	Ducted	Ducted	n/a	n/a	Altered			
<b>WATER HEATING</b>	<b>Qty.</b>	<b>Type</b>	<b>Gallons</b>	<b>Min. Eff</b>	<b>Distribution</b>	<b>Status</b>		

EnergyPro 9.4 by EnergySoft User Number: 6249 ID: 24-12032 Page 15 of 22

EnergyPro 9.4 by EnergySoft User Number: 6249 ID: 24-12032 Page 16 of 22

## 2022 Single-Family Residential Mandatory Requirements Summary

\$110.5:	Pilot Lights. Continuously burning pilot lights are prohibited for natural gas-type central furnaces, household cooking appliances (except appliances that heat pump systems) and electric water voltage connection with pilot lights that consume less than 150 Btu per hour; and pool and hot tub heating systems.
\$150.0(m):	Building Cooling and Heating Loads. Heating and/or cooling loads are calculated in accordance with the ASHRAE Handbook, Equipment Volume, Applications, Volume, and Fundamentals Volume of the SMACNA Residential Comfort System Installation Standard.
\$150.0(n):	Clearances. Air conditioners and heat pump condensing units must have a clearance of at least five feet from the outlet of any dryer.
\$150.0(n):	Leak Detection. Air conditioners and heat pump systems must be equipped with liquid line filter driers if required, as specified by the manufacturer's instructions.
\$150.0(n):	Water Pipe, Solar Water-heating System, Piping, and Space Conditioning System Line Installation. All domestic hot water piping must be insulated in accordance with § 105.0.10.
\$150.0(l):	Insulation Protection. Pipe insulation must be protected from damage, including that due to sunlight, moisture, equipment, and wind as required by § 129.3(b). Insulation exposed to weather must be water retardant and protected from UV light (no added UV protection required for pipe insulation that is exposed to weather and is not required to be water retardant).
\$150.0(l):	Insulation Protection. Pipe insulation must be protected from damage, including that due to sunlight, moisture, equipment, and wind as required by § 129.3(b). Insulation exposed to weather must be water retardant and protected from UV light (no added UV protection required for pipe insulation that is exposed to weather and is not required to be water retardant).
\$150.0(m):	Other Products. Piping, fittings, valves, and other components of piping systems must be protected from damage, including that due to sunlight, moisture, equipment, and wind as required by § 129.3(b).
\$150.0(n):	Leak Detection. Air conditioners and heat pump condensing units must be equipped with liquid line filter driers if required, as specified by the manufacturer's instructions.
\$150.0(n):	Water Pipe, Solar Water-heating System, Piping, and Space Conditioning System Line Installation. All domestic hot water piping must be insulated in accordance with § 105.0.10.
\$150.0(l):	Insulation Protection. Pipe insulation must be protected from damage, including that due to sunlight, moisture, equipment, and wind as required by § 129.3(b). Insulation exposed to weather must be water retardant and protected from UV light (no added UV protection required for pipe insulation that is exposed to weather and is not required to be water retardant).
\$150.0(l):	Insulation Protection. Pipe insulation must be protected from damage, including that due to sunlight, moisture, equipment, and wind as required by § 129.3(b). Insulation exposed to weather must be water retardant and protected from UV light (no added UV protection required for pipe insulation that is exposed to weather and is not required to be water retardant).
\$150.0(m):	Other Products. Piping, fittings, valves, and other components of piping systems must be protected from damage, including that due to sunlight, moisture, equipment, and wind as required by § 129.3(b).
\$150.0(n):	Leak Detection. Air conditioners and heat pump condensing units must be equipped with liquid line filter driers if required, as specified by the manufacturer's instructions.
\$150.0(n):	Water Pipe, Solar Water-heating System, Piping, and Space Conditioning System Line Installation. All domestic hot water piping must be insulated in accordance with § 105.0.10.
\$150.0(l):	Insulation Protection. Pipe insulation must be protected from damage, including that due to sunlight, moisture, equipment, and wind as required by § 129.3(b). Insulation exposed to weather must be water retardant and protected from UV light (no added UV protection required for pipe insulation that is exposed to weather and is not required to be water retardant).
\$150.0(l):	Insulation Protection. Pipe insulation must be protected from damage, including that due to sunlight, moisture, equipment, and wind as required by § 129.3(b). Insulation exposed to weather must be water retardant and protected from UV light (no added UV protection required for pipe insulation that is exposed to weather and is not required to be water retardant).
\$150.0(m):	Other Products. Piping, fittings, valves, and other components of piping systems must be protected from damage, including that due to sunlight, moisture, equipment, and wind as required by § 129.3(b).
\$150.0(n):	Leak Detection. Air conditioners and heat pump condensing units must be equipped with liquid line filter driers if required, as specified by the manufacturer's instructions.
\$150.0(n):	Water Pipe, Solar Water-heating System, Piping, and Space Conditioning System Line Installation. All domestic hot water piping must be insulated in accordance with § 105.0.10.
\$150.0(l):	Insulation Protection. Pipe insulation must be protected from damage, including that due to sunlight, moisture, equipment, and wind as required by § 129.3(b). Insulation exposed to weather must be water retardant and protected from UV light (no added UV protection required for pipe insulation that is exposed to weather and is not required to be water retardant).
\$150.0(l):	Insulation Protection. Pipe insulation must be protected from damage, including that due to sunlight, moisture, equipment, and wind as required by § 129.3(b). Insulation exposed to weather must be water retardant and protected from UV light (no added UV protection required for pipe insulation that is exposed to weather and is not required to be water retardant).
\$150.0(m):	Other Products. Piping, fittings, valves, and other components of piping systems must be protected from damage, including that due to sunlight, moisture, equipment, and wind as required by § 129.3(b).
\$150.0(n):	Leak Detection. Air conditioners and heat pump condensing units must be equipped with liquid line filter driers if required, as specified by the manufacturer's instructions.
\$150.0(n):	Water Pipe, Solar Water-heating System, Piping, and Space Conditioning System Line Installation. All domestic hot water piping must be insulated in accordance with § 105.0.10.
\$150.0(l):	Insulation Protection. Pipe insulation must be protected from damage, including that due to sunlight, moisture, equipment, and wind as required by § 129.3(b). Insulation exposed to weather must be water retardant and protected from UV light (no added UV protection required for pipe insulation that is exposed to weather and is not required to be water retardant).
\$150.0(l):	Insulation Protection. Pipe insulation must be protected from damage, including that due to sunlight, moisture, equipment, and wind as required by § 129.3(b). Insulation exposed to weather must be water retardant and protected from UV light (no added UV protection required for pipe insulation that is exposed to weather and is not required to be water retardant).
\$150.0(m):	Other Products. Piping, fittings, valves, and other components of piping systems must be protected from damage, including that due to sunlight, moisture, equipment, and wind as required by § 129.3(b).
\$150.0(n):	Leak Detection. Air conditioners and heat pump condensing units must be equipped with liquid line filter driers if required, as specified by the manufacturer's instructions.
\$150.0(n):	Water Pipe, Solar Water-heating System, Piping, and Space Conditioning System Line Installation. All domestic hot water piping must be insulated in accordance with § 105.0.10.
\$150.0(l):	Insulation Protection. Pipe insulation must be protected from damage, including that due to sunlight, moisture, equipment, and wind as required by § 129.3(b). Insulation exposed to weather must be water retardant and protected from UV light (no added UV protection required for pipe insulation that is exposed to weather and is not required to be water retardant).
\$150.0(l):	Insulation Protection. Pipe insulation must be protected from damage, including that due to sunlight, moisture, equipment, and wind as required by § 129.3(b). Insulation exposed to weather must be water retardant and protected from UV light (no added UV protection required for pipe insulation that is exposed to weather and is not required to be water retardant).
\$150.0(m):	Other Products. Piping, fittings, valves, and other components of piping systems must be protected from damage, including that due to sunlight, moisture, equipment, and wind as required by § 129.3(b).
\$150.0(n):	Leak Detection. Air conditioners and heat pump condensing units must be equipped with liquid line filter driers if required, as specified by the manufacturer's instructions.
\$150.0(n):	Water Pipe, Solar Water-heating System, Piping, and Space Conditioning System Line Installation. All domestic hot water piping must be insulated in accordance with § 1