

PLANNING COMMISSION – May 13, 2026
DRAFT CONDITIONS OF APPROVAL

116 Vallecitos Way
Architecture and Site Application S-25-046

Consider a Request for Approval to Demolish an Existing Single-Family Residence, Construct a New Two-Story Single-Family Residence, and Site Improvements Requiring a Grading Permit on Property Zoned R-1:10. APN 407-13-018. Categorically Exempt Pursuant to CEQA Guidelines Section 15303: New Construction or Conversion of Small Structures.

Property Owner: Eyal Tokman
Applicant: Michelle Miner
Project Planner: Ryan Safty

TO THE SATISFACTION OF THE COMMUNITY DEVELOPMENT DIRECTOR:

Planning Division

1. APPROVAL: This application shall be completed in accordance with all of the conditions of approval and in substantial compliance with the approved plans. Any changes or modifications to the approved plans and/or business operation shall be approved by the Community Development Director, DRC, or the Planning Commission depending on the scope of the changes.
2. EXPIRATION: The approval will expire two years from the approval date pursuant to Section 29.20.320 of the Town Code, unless the approval has been vested.
3. OUTDOOR LIGHTING: Exterior lighting shall be kept to a minimum, and shall be down directed fixtures that will not reflect or encroach onto adjacent properties. No flood lights shall be used unless it can be demonstrated that they are needed for safety or security.
4. TREE REMOVAL PERMIT: A Tree Removal Permit shall be obtained for any trees to be removed, prior to the issuance of a building or grading permit.
5. EXISTING TREES: All existing trees shown on the plan and trees required to remain or to be planted are specific subjects of approval of this plan, and must remain on the site.
6. ARBORIST REQUIREMENTS: The developer shall implement, at their cost, all recommendations identified in the Arborist's report dated December 16, 2025, prepared by Walter Levison Consulting Arborist. These recommendations must be incorporated in the building permit plans and completed prior to issuance of a building permit where applicable.
7. TREE FENCING: Protective tree fencing and other protection measures shall be placed at the drip line of existing trees prior to issuance of demolition and building permits and shall remain through all phases of construction. Include a tree protection plan with the construction plans.
8. TREE STAKING: All newly planted trees shall be double-staked using rubber tree ties.

9. FRONT YARD LANDSCAPE: Prior to issuance of a Certificate of Occupancy the front yard must be landscaped.
10. WATER EFFICIENCY LANDSCAPE ORDINANCE: The final landscape plan shall meet the Town of Los Gatos Water Conservation Ordinance or the State Water Efficient Landscape Ordinance, whichever is more restrictive. A review fee based on the current fee schedule adopted by the Town Council is required when working landscape and irrigation plans are submitted for review.
11. PROJECT IDENTIFICATION SIGNAGE: The project identification signage on the project site shall be removed within 30 days of approval of the Architecture and Site application.
12. TOWN INDEMNITY: Applicants are notified that Town Code Section 1.10.115 requires that any applicant who receives a permit or entitlement ("the Project") from the Town shall defend (with counsel approved by Town), indemnify, and hold harmless the Town, its agents, officers, and employees from and against any claim, action, or proceeding (including without limitation any appeal or petition for review thereof) against the Town or its agents, officers or employees related to an approval of the Project, including without limitation any related application, permit, certification, condition, environmental determination, other approval, compliance or failure to comply with applicable laws and regulations, and/or processing methods ("Challenge"). Town may (but is not obligated to) defend such Challenge as Town, in its sole discretion, determines appropriate, all at applicant's sole cost and expense.

Applicant shall bear any and all losses, damages, injuries, liabilities, costs and expenses (including, without limitation, staff time and in-house attorney's fees on a fully-loaded basis, attorney's fees for outside legal counsel, expert witness fees, court costs, and other litigation expenses) arising out of or related to any Challenge ("Costs"), whether incurred by Applicant, Town, or awarded to any third party, and shall pay to the Town upon demand any Costs incurred by the Town. No modification of the Project, any application, permit certification, condition, environmental determination, other approval, change in applicable laws and regulations, or change in such Challenge as Town, in its sole discretion, determines appropriate, all the applicant's sole cost and expense. No modification of the Project, any application, permit certification, condition, environmental determination, other approval, change in applicable laws and regulations, or change in processing methods shall alter the applicant's indemnity obligation.

13. COMPLIANCE MEMORANDUM: A memorandum shall be prepared and submitted with the building plans detailing how the Conditions of Approval will be addressed.

Building Division

14. PERMITS REQUIRED:
 - a. A Demolition Permit is required for the demolition of the existing single-family residence and attached garage.
 - b. A Building Permit is required for the construction of the new single-family residence and attached garage.

- c. A separate Building Permit will be required for the PV System and must be finalized prior to the issuance of Certificate of Compliance.
15. APPLICABLE CODES: The codes, as amended and adopted by the Town of Los Gatos as of January 1, 2026, are the 2025 California Building Standards Code, California Code of Regulations Title 24, Parts 1-12.
16. CONDITIONS OF APPROVAL: The Conditions of Approval must be included on plan sheets within the construction plans. A Compliance Memorandum detailing how the conditions of approval will be addressed shall be prepared and submitted with the building permit application.
17. BUILDING & SUITE NUMBERS: Submit requests for new building addresses to the Building Division prior to submitting for the building permit application process.
18. SIZE OF PLANS: Minimum size 24" x 36", maximum size 30" x 42".
19. REQUIREMENTS FOR COMPLETE DEMOLITION OF STRUCTURE: Obtain a Building Department Demolition Application and a Bay Area Air Quality Management District Application for the removal of each existing structure. Once the demolition form has been completed, all signatures obtained, and written verification from PG&E that all utilities have been disconnected, submit the completed form to the Building Department with the Air District's J# Certificate, PG&E verification, and site plans showing all existing structures, existing utility service lines such as water, sewer, and PG&E. No demolition work shall be done without first obtaining a permit from the Town.
20. SOILS REPORT: A Soils Report, prepared to the satisfaction of the Building Official, containing foundation and retaining wall design recommendations, shall be submitted with the Building Permit Application. This report shall be prepared by a licensed Civil Engineer specializing in soil mechanics.
21. FOUNDATION INSPECTIONS: A pad certificate prepared by a California-licensed civil engineer or land surveyor shall be submitted to the project Building Inspector at the foundation inspection. This certificate shall certify compliance with the recommendations as specified in the Soils Report and that the building pad elevations and on-site retaining wall locations and elevations have been prepared according to the approved plans. Horizontal and vertical controls shall be set and certified by a licensed surveyor or registered Civil Engineer for the following items:
 - a. Building pad elevation
 - b. Finish floor elevation
 - c. Foundation corner locations
 - d. Retaining wall(s) locations and elevations
22. TITLE 24 ENERGY COMPLIANCE: All required California Title 24 Energy Compliance Forms must be directly printed onto a plan sheet.
23. BACKWATER VALVE: As required by Town Ordinance 6.40.020, provide details for any required sanitary sewer backwater valve on the plans and provide its location. The Town of Los Gatos Ordinance and West Valley Sanitation District (WVSD) require backwater valves on drainage piping serving fixtures that have flood level rims less than 12 inches above the elevation of the next upstream manhole.
24. HAZARDOUS FIRE ZONE: All projects in the Town of Los Gatos require Class A roof assemblies.

25. SPECIAL INSPECTIONS: When a special inspection is required by CBC Section 1704, the Architect or Engineer of Record shall prepare an inspection program that shall be submitted to the Building Official for approval before issuance of the Building Permit. The Town Special Inspection form must be completely filled out and signed by all parties requested before the permit is issued. Special Inspection forms are available online at www.losgatosca.gov/building.
26. CONSTRUCTION BEST MANAGEMENT PRACTICES (BMPs): The Town standard West Valley Clean Water Authority Nonpoint Source Pollution Control Program Sheet (page size same as submitted drawings) shall be part of the plan submittal. The specification sheet is available online at www.losgatosca.gov/building.
27. APPROVALS REQUIRED: The project requires the following departments and agencies' approval before issuing a building permit:
 - a. Community Development – Planning Division: (408) 354-6874
 - b. Engineering/Parks & Public Works Department: (408) 399-5771
 - c. Santa Clara County Fire Department: (408) 378-4010
 - d. West Valley Sanitation District: (408) 378-2407
 - e. Local School District: The Town will forward the paperwork to the appropriate school district(s) for processing. A copy of the paid receipt is required prior to permit issuance.

TO THE SATISFACTION OF THE DIRECTOR OF PARKS AND PUBLIC WORKS:

Engineering Division:

THE FOLLOWING CONDITIONS SHALL BE ADDRESSED OR NOTED ON THE CONSTRUCTION PLANS SUBMITTED FOR ANY BUILDING OR GRADING PERMIT, OR IF ANOTHER DEADLINE IS SPECIFIED IN A CONDITION, AT THAT TIME.

28. PAYMENT OF PARKS AND PUBLIC WORKS (“PPW”) ENGINEERING PLAN CHECK FEE AND INSPECTION FEE – At the time of the first construction submittal, the Applicant shall submit to the Town Engineer for approval a detailed construction project cost estimate prepared and stamped by the Applicant’s civil engineer. The cost estimate shall break out on-site and off-site improvements separately. This cost estimate will be used to determine the Engineering Plan Check Fee. A final construction cost estimate shall be provided once the project plans are approved. This cost estimate will be used to determine the Engineering Inspection Fee. The Engineering Inspection Fee must be paid prior to the issuance of any construction related permit.
29. GRADING PERMIT – A grading permit is required for all site grading and drainage work that is outside the perimeter of a building, retaining wall footing, or other structure authorized by a valid building permit. The Applicant must submit a grading permit application after the appeal period of the entitlement approval process has passed. Submittals are accepted through Accela only. The grading permit application shall include detailed grading plans and associated required materials. Plan check fees are based on the scope of onsite work. Prior to approval of the grading permit, the Applicant shall pay all

fees due and provide faithful performance and payment securities for the performance of the work described and delineated on the approved grading plan, final erosion and sedimentation control plan, and interim erosion and sedimentation control plan (if required), in an amount to be set by the Town Engineer (but not to exceed one hundred (100) percent) of the approved estimated cost of the grading and erosion and sedimentation control measures. The form of security shall be one or a combination of the following to be determined by the Town Engineer and subject to the approval of the Town Attorney: (1) Bond or bonds issued by one or more duly authorized corporate sureties on a form approved by the Town; (2) Deposit with the Town, money, or negotiable bonds of the kind approved for securing deposits of public monies; or (3) other instrument of credit from one or more financial institutions subject to regulation by the State or Federal Government wherein such financial institution pledges funds are on deposit and guaranteed for payment. The grading permit shall be issued prior to the issuance of the building permit unless otherwise allowed by the Town Engineer. The permit shall be limited to work shown on the grading plans approved by the Town Engineer. In granting a permit, the Town Engineer may impose any condition deemed necessary to protect the health, safety, and welfare of the public, to prevent the creation of a nuisance or hazard to public or private property, and to assure proper completion of the grading including but not limited to: (1) Mitigation of adverse environmental impacts; (2) Improvement of any existing grading or correction of any existing grading violation to comply with Town Code; (3) Requirements for fencing or other protection of grading which would otherwise be hazardous; (4) Requirements for dust, erosion, sediment, and noise control, hours of operation and season of work, weather conditions, sequence of work, access roads, and haul routes; (5) Requirements for safeguarding watercourses from excessive deposition of sediment or debris in quantities exceeding natural levels; (6) Assurance that the land area in which grading is proposed and for which habitable structures are proposed is not subject to hazards of land slippage or significant settlement or erosion and that the hazards of seismic activity or flooding can be eliminated or adequately reduced; (7) Temporary and permanent landscape plans.

30. TREE REMOVAL PERMIT – The Applicant shall apply and obtain a Tree Removal Permit from the Parks and Public Works Department for the removal of existing trees on-site or in the public right-of-way prior to the issuance of a building permit or demolition building permit, whichever is issued first. Tree removals shall be consistent with the arborist report and approved entitlement plans.
31. EXISTING FACILITY PROTECTION AND REPAIR – All existing public utilities shall be either protected in place, relocated, or repaired. The Applicant shall repair or replace all existing improvements not designated for removal, and all new improvements that are damaged during construction or removed because of the Applicant’s operations. This includes sidewalk, curb and gutter, streetlights, valley gutters, curb ramps, and any other existing improvements in the area that are not intended to be removed and replaced. The Applicant shall request a walk-through with the PPW construction Inspector before the start of construction to verify existing conditions. Said repairs shall be completed prior to issuance of the first certificate of occupancy of the project.

32. UNDERGROUND UTILITIES – All new services to the development shall be placed underground in accordance with the various utility regulations. Underground utility plans must be submitted to the Town and approved by the Town Engineer prior to installation.
33. UTILITY RESPONSIBILITIES – The Applicant is responsible for the maintenance of existing stormwater drainage facilities, including piped and open channel stormwater conveyances in private areas. The Applicant is responsible for all expenses necessary to connect to the various utility providers. Currently, the public storm sewer system is owned and maintained by the Town of Los Gatos, the water system in Los Gatos is owned and maintained by San José Water Company, and the sanitary sewer system in Los Gatos is owned and maintained by West Valley Sanitation District. Any alterations of the approved utilities listed must be approved by the Town prior to any construction.
34. UTILITY COMPANY COORDINATION – The Applicant shall negotiate any necessary right-of-way or easements with the various utility companies in the area, subject to the review and approval by the Town Engineer and the utility companies. Prior to the approval of the site plan for construction, the Applicant shall submit “Will Serve” letters from PG&E, San José Water, West Valley Sanitation District, West Valley Collections and Recycling, and AT&T (or the current “Carrier of Last Resort”) with a statement indicating either a list of improvements necessary to serve the project or a statement that the existing network is sufficient to accommodate the project. Coordination of the stormwater conveyance system will be addressed during the Grading Permit review.
35. OFF-SITE DRAINAGE – The Applicant shall not alter any existing drainage patterns without an approved Grading Permit.
36. CLEAN, INSPECT, AND REPAIR STORM LINE – If the project will connect to the public storm drainage system, the Applicant is required to evaluate the conditions of the existing storm lines along the project frontage by videotaping and providing the result to the Town Engineer. The Applicant shall clean and inspect (via remote TV camera) the storm line from the manhole upstream to the manhole downstream of the project area. The video inspection shall be done by a professional video inspection company and be completed prior to building permit issuance. The video of the inspection shall be reviewed with PPW and any cracked, broken, or otherwise compromised integrity is found, the areas of the line along the project frontage shall be repaired by the Applicant at the applicant’s expense. The Applicant shall include the required repairs on the Improvement Plans submitted. All necessary repairs to the storm line shall be completed and approved prior to the project connecting to the storm drainage system
37. GRADING & DRAINAGE WINTER MORATORIUM – All grading activity shall comply with the Municipal Regional Stormwater Permit and Chapter 12 of the Town Code. There shall be no earthwork disturbance or grading activities between October 15th and April 15th of each year unless approved by the Town Engineer. In order to be considered for approval, the Applicant must submit a Winterization Erosion Control Plan certified by a California certified QSD to the Town Engineer for review and approval. If grading is allowed during the rainy season, a maximum of two (2) weeks is allowed between clearing of an area and stabilizing/building on the exposed area. The submission of a certified plan does not guarantee approval. Any approved and executed plan must be kept on-site while the project is in construction.

38. EROSION CONTROL – The Applicant shall prepare and submit interim and final erosion control plans to the Town Engineer for review and approval. The interim erosion control plan(s) shall include measures carried out during construction before final landscaping is installed. Multiple phases of interim erosion control plans may be necessary depending on the complexity of the project. Interim erosion control best management practices may include silt fences, fiber rolls, erosion control blankets, Town approved seeding mixtures, filter berms, check dams, retention basins, etc. The Applicant shall install, maintain, and modify the erosion control measures as needed to continuously protect downstream water quality. In the event an emergency modification is deemed necessary, the Applicant must implement necessary measures to protect downstream waterways immediately and then submit the changes made within 24-hours to the Town Engineer for review and approval. The erosion control plans shall be in compliance with applicable measures contained in the most current Santa Clara County National Pollutant Discharge Elimination System (NPDES) Municipal Regional Permit (MRP). Any fees or penalties assessed against the Town in response to the Applicant’s failure to comply with the Permit must be paid by the Applicant. The Applicant must permit Town staff onsite to conduct periodic NPDES inspections throughout the recognized storm season to verify compliance with the Construction General Permit and Stormwater ordinances and regulations.
39. SITE TRIANGLE AND TRAFFIC VIEW AREA – Fencing, landscaping, and permanent structures shall not visually obstruct line of sight between three-feet and 7.5-feet in height if located within the driveway view area, traffic view area, or corner sight triangle. The driveway and intersection site triangles are represented on Town Standard Drawing ST-231. The traffic view area and corner sight triangle are shown on Town Standard Drawing ST-232. This includes all above ground obstructions including utility structures, for example electric transformers. The various clearance lines shall be shown on the site plan to demonstrate compliance.
40. GEOTECHNICAL REVIEW – Prior to building permit issuance, the Applicant’s Geotechnical Engineer shall submit a design level geotechnical report. The report will require a peer review by the Town’s geological and geotechnical consultant. A deposit and fee for the peer review will be required per the Town’s current fee schedule, unless there are any remaining deposit funds from the entitlement phase. The Town will route the design level geotechnical report to the Town’s peer review consultant once the report is submitted and deposit and fee are available. Once approved, the geotechnical engineer shall review the grading and drainage plan and proposed pavement and foundation design to verify that the design is in accordance with their recommendations. The Applicant’s Geotechnical Engineer’s approval shall be conveyed to the Town either by letter or by signing and stamping the plans. All grading operations and soil compaction activities shall be per the approved project’s design level geotechnical report. The Applicant shall add this condition to the general notes on the grading plan.
41. GEOTECHNICAL ENGINEER OBSERVATION – All grading activities shall be conducted under the observation of, and tested by, a licensed geotechnical engineer. A report shall be filed with the Town of Los Gatos for each phase of construction stating that all grading activities were performed in conformance with the requirements of the project’s design level geotechnical report. The Applicant shall submit a Final Geotechnical Construction

Observation and Testing Summary in an “as-built” letter/report prepared and submitted to the Town prior to issuance of the certificate of occupancy. The Applicant shall add this condition to the general notes on the grading plan.

42. PRECONSTRUCTION MEETING – After the issuance of any Grading or Encroachment permit and before the commencement of any on or off-site work, the Applicant shall request a pre-construction meeting with the PPW Inspector to discuss the project conditions of approval, working hours, site maintenance, and other construction matters. At that meeting, the Applicant shall submit a letter acknowledging that:
 - a. They have read and understand these project Conditions of Approval;
 - b. They will require that all project sub-contractors read and understand these project Conditions of Approval; and,
 - c. They ensure a copy of these project Conditions of Approval will be posted on-site at all times during construction.
43. FLOOR DRAINS – All floor drains shall be plumbed to connect to the sanitary sewer system only. Site design must facilitate drainage away from building floor drains.
44. OVERHEAD UTILITY CLEARANCE – For projects that have overhead utility lines on-site that travel over new buildings, the Applicant shall obtain a letter from the utility company indicating that there is adequate overhead clearance from the utility to the proposed building. The letter shall be submitted with the first set of improvement plans submitted. The plans shall show the existing utility pole, any necessary proposed pole protection (including overhead clearance warning identification), and shall be confirmed satisfactory with the utility company. The letter shall be to the approval of the Town Engineer.

THE FOLLOWING CONDITIONS SHALL BE MET PRIOR TO RELEASE OF UTILITIES, FINAL INSPECTION, OR ISSUANCE OF A CERTIFICATE OF OCCUPANCY, WHICHEVER OCCURS FIRST, OR IF ANOTHER DEADLINE IS SPECIFIED IN A CONDITION, AT THAT TIME.

45. RECORD DRAWINGS – The Applicant shall submit a scanned PDF set of stamped record drawings and construction specifications for all off-site improvements to the Department of Parks and Public Works. All underground facilities shall be shown on the record drawings as constructed in the field. The Applicant shall also provide the Town with an electronic copy of the record drawings in the AutoCAD Version being used by the Town at the time of completion of the work. The Applicant shall also submit an AutoCAD drawing file of all consultants composite basemap linework showing all public improvements and utility layouts. This condition shall be met prior to the release of utilities, final inspection, or issuance of a certificate of occupancy, whichever occurs first.
46. RESTORATION OF PUBLIC IMPROVEMENTS – The Applicant shall repair or replace all existing improvements not designated for removal that are damaged or removed during construction. Improvements such as, but not limited to curbs, gutters, sidewalks, driveways, signs, streetlights, pavements, raised pavement markers, thermoplastic pavement markings, etc., shall be repaired or replaced to a condition equal to or better than the original condition. Any new concrete shall be free of stamps, logos, names, graffiti, etc. Existing improvement to be repaired or replaced shall be at the direction of the PPW Inspector and shall comply with all Title 24 Disabled Access provisions. The

restoration of all improvements identified by the PPW Inspector shall be completed before the issuance of a certificate of occupancy. The Applicant shall request a walk-through with the PPW Inspector before the start of construction to verify existing conditions.

47. PAVEMENT RESTORATION – Due to construction activities, new utility cuts along the project frontage, and the anticipated project’s truck traffic, the Applicant shall grind and provide a 2.5” overlay with asphalt concrete the south side of Los Gatos-Saratoga Road along the entire property length between the center median island and the property frontage. Prior to overlay, any base failure repair or required dig-outs identified by the PPW Inspector shall be completed. The Town Engineer shall approve the roadway repair prior to the release of utilities, final inspection, or issuance of a certificate of occupancy, whichever occurs first.

THE FOLLOWING CONDITIONS SHALL BE COMPLIED WITH AT ALL TIMES DURING THE CONSTRUCTION PHASE OF THE PROJECT, OR IF ANOTHER DEADLINE IS SPECIFIED IN A CONDITION, AT THAT TIME

48. PROJECT CONSTRUCTION SETUP – All storage and office trailers will be kept off the public right-of-way.
49. PUBLIC WORKS CONSTRUCTION NOTICE – The contractor shall notify the PPW Inspector at least ten (10) working days prior to the start of any construction work. At that time, the Contractor shall provide an initial project construction schedule and a 24-hour emergency telephone number list.
50. PROJECT CONSTRUCTION HANDOUT – The Contractor shall provide to the Town Engineer an approved construction information handout for the purpose of responding to questions the Town receives regarding the project construction.
51. PROJECT CONSTRUCTION SUPERVISION – The Contractor shall always provide a qualified supervisor on the job site during construction.
52. PUBLIC WORKS CONSTRUCTION INSPECTION – All work shown on the Improvement Plans shall be inspected to the approval of the Town Engineer. Uninspected work shall be removed as deemed appropriate by the Town Engineer.
53. PROJECT CONSTRUCTION HOURS – Construction activities related to the issuance of any PPW permit shall comply with Town Code Section 16.20.035 which restricts construction to the weekday between 8:00 a.m. and 6:00 p.m. and Saturday 9:00 a.m. to 4:00 p.m. No work shall be done on Sundays or on Town Holidays unless otherwise approved by the Town Engineer. Please note that no work shall be allowed to take place within the Town right-of-way after 5:00 p.m. Monday through Friday. In addition, no work being done under Encroachment Permit may be performed on the weekend unless prior approvals have been granted by the Town Engineer. The Town Engineer may apply additional construction period restrictions, as necessary, to accommodate standard commute traffic along arterial roadways and along school commute routes. Onsite project signage must state the project construction hours. The permitted construction hours may be modified if the Town Engineer finds that the following criteria is met:
 - a. Permitting extended hours of construction will decrease the total time needed to complete the project without an unreasonable impact to the neighborhood.

- b. Permitting extended hours of construction is required to accommodate a construction requirement such as a large concrete pour or major road closure. Such a need would be presented by the project's design engineer and require approval of the Town Engineer.
 - c. An emergency situation exists where the construction work is necessary to correct an unsafe or dangerous condition resulting in obvious and eminent peril to public health and safety. If such a condition exists, the Town may waive any of the remaining requirements outlined below.
 - d. The exemption will not conflict with any other condition of approval required by the Town to mitigate significant environmental impacts.
 - e. The contractor or property owner will notify residential and commercial occupants of adjacent properties of the modified construction work hours. This notification must be provided three days prior to the start of the extended construction activity.
 - f. The approved hours of construction activity will be posted at the construction site in a place and manner that can be easily viewed by any interested member of the public.
 - g. The Town Engineer may revoke the extended work hours at any time if the contractor or owner of the property fails to abide by the conditions of extended work hours or if it is determined that the peace, comfort, and tranquility of the occupants of adjacent residential or commercial properties are impaired because of the location and nature of the construction.
 - h. The waiver application must be submitted to the PPW Inspector ten (10) working days prior to the requested date of waiver.
54. PROJECT CONSTRUCTION BMPs – All construction activities shall conform to the latest requirements of the CASQA Stormwater Best Management Practices Handbooks for Construction Activities and New Development and Redevelopment, the Town's grading and erosion control ordinances, the project specific temporary erosion control plan, and other generally accepted engineering practices for erosion control as required by the Town Engineer when undertaking construction activities.
55. PROJECT CONSTRUCTION EXCAVATION – The following provisions to control traffic congestion, noise, and dust shall be followed during site excavation, grading, and construction:
- a. All construction vehicles should be properly maintained and equipped with exhaust mufflers that meet State standards.
 - b. Travel speeds on unpaved roads shall be limited to fifteen (15) miles per hour.
 - c. Blowing dust shall be reduced by timing construction activities so that paving and building construction begin as soon as possible after completion of grading, and by landscaping disturbed soils as soon as possible.
 - d. Water trucks shall be present and in use at the construction site. All portions of the site subject to blowing dust shall be watered as often as deemed necessary by the Town, or a minimum of three times daily, or apply (non-toxic) soil stabilizers on all unpaved access roads, parking areas, and staging areas at construction sites in order to ensure proper control of blowing dust for the duration of the project.
 - e. Watering on public streets and wash down of dirt and debris into storm drain systems is prohibited. Streets will be cleaned by street sweepers or by hand as often as

deemed necessary by the PPW Inspector, or at least once a day. Watering associated with on-site construction activity shall take place between the hours of 8 a.m. and 5 p.m. and shall include at least one late-afternoon watering to minimize the effects of blowing dust. Recycled water shall be used for construction watering to manage dust control where possible, as determined by the Town Engineer. Where recycled water is not available potable water shall be used. All potable construction water from fire hydrants shall be coordinated with the San José Water Company.

- f. All public streets soiled or littered due to this construction activity shall be cleaned and swept on a daily basis during the workweek to the satisfaction of the Construction Inspector.
 - g. Construction grading activity shall be discontinued in wind conditions in excess of 25 miles per hour, or that in the opinion of the PPW Inspector cause excessive neighborhood dust problems.
 - h. Site dirt shall not be tracked into the public right-of-way and shall be cleaned immediately if tracked into the public right-of-way. Mud, silt, concrete and other construction debris shall not be washed into the Town's storm drains.
 - i. Construction activities shall be scheduled so that paving and foundation placement begin immediately upon completion of grading operation.
 - j. All aggregate materials transported to and from the site shall be covered in accordance with Section 23114 of the California Vehicle Code during transit to and from the site.
 - k. Prior to issuance of any permit, the Applicant shall submit any applicable pedestrian or traffic detour plans to the satisfaction of the Town Engineer for any lane or sidewalk closures. The temporary traffic control plan shall be prepared by a licensed professional engineer with experience in preparing such plans and in accordance with the requirements of the latest edition of the California Manual on Uniform Traffic Control Devices (MUTCD) and standard construction practices. The Traffic Control Plan shall be approved prior to the commencement of any work within the public right-of-way.
 - l. During construction, the Applicant shall make accessible any or all public and private utilities within the area impacted by construction, as directed by the Town Engineer.
 - m. The minimum soils sampling and testing frequency shall conform to Chapter 8 of the Caltrans Construction Manual. The Applicant shall require the soils engineer submit to daily testing and sampling reports to the Town Engineer.
56. PROJECT CLOSE-OUT – Prior to requesting a Final Inspection, the Applicant shall submit to the Town Engineer a letter indicating that all project conditions have been met, and all improvements are complete. All work must be completed to the satisfaction of the Planning Director and Town Engineer prior to the first occupancy. All public improvements, including the complete installation of all improvements relative to streets, fencing, storm drainage, underground utilities, etc., shall be completed and attested to by the Town Engineer before approval of occupancy of any unit. Where facilities of other agencies are involved, including those for water and sanitary sewer services, such installation shall be verified as having been completed and accepted by those agencies. In addition, the Applicant shall submit an itemized final quantities list of all public

improvements constructed on-site and within the public right-of-way. The final quantities list shall be prepared by the project engineer and be to the approval of the Town Engineer. The final quantities list shall be broken out into on-site and off-site improvements based on the format provided by the Town. Until such time as all required improvements are fully completed and accepted by Town, the Applicant shall be responsible for the care, maintenance, and any damage to such improvements. Town shall not, nor shall any officer or employee thereof, be liable or responsible for any accident, loss or damage, regardless of cause, happening or occurring to the work or improvements required for this project prior to the completion and acceptance of the work or Improvements. All such risks shall be the responsibility of and are hereby assumed by the Applicant.

57. SITE WATER DISCHARGE – In accordance with the Town Code, Prohibition of Illegal Discharges (Los Gatos Town Code Section 22.30.015), the Town Engineer may approve in coordination West Valley Sanitation District the discharge of uncontaminated pumped ground waters to the sanitary sewer only when such source is deemed unacceptable by State and Federal authorities for discharge to surface waters of the United States, whether pretreated or untreated, and for which no reasonable alternative method of disposal is available. Following the verification of the applicable local, state and/or federal approvals, a Discharge Plan will be approved and monitored by the Town Engineer.

THE FOLLOWING CONDITIONS SHALL BE COMPLIED WITH AT ALL TIMES THAT THE USE PERMITTED BY THIS ENTITLEMENT OCCUPIES THE PREMISES

58. POST CONSTRUCTION BEST MANAGEMENT PRACTICES (BMP) – Post construction storm water pollution prevention requirements shall include:
- a. The Applicant shall be charged the cost of abatement for issues associated with, but not limited to, inspection of the private stormwater facilities, emergency maintenance needed to protect public health or watercourses, and facility replacement or repair if the treatment facility is no longer able to meet performance standards or has deteriorated. Any abatement activity performed on the Applicant's property by Town staff will be charged to the Applicant at the Town's adopted fully-loaded hourly rates.
 - b. Maintenance of the storm drain inlets "No Dumping – Drains to Bay" plaques to alert the public to the destination of storm water and to prevent direct discharge of pollutants into the storm drain. Template ordering information is available at www.flowstobay.org.
 - c. All process equipment, oils, fuels, solvents, coolants, fertilizers, pesticides, and similar chemical products, as well as petroleum based wastes, tallow, and grease planned for storage outdoors shall be stored in covered containers at all times.
 - d. All public outdoor spaces and trails shall include installation and upkeep of dog waste stations.
 - e. Garbage and recycling receptacles and bins shall be designed and maintained with permanent covers to prevent exposure of trash to rain. Trash enclosure drains shall be connected to the sanitary sewer system.

- f. It is the responsibility of the property owner(s)/homeowners association to implement a plan for street sweeping of paved private roads and cleaning of all storm drain inlets.

TO THE SATISFACTION OF THE SANTA CLARA COUNTY FIRE DEPARTMENT:

59. GENERAL: Review of this Developmental proposal is limited to acceptability of site access, water supply and may include specific additional requirements as they pertain to fire department operations, and shall not be construed as a substitute for formal plan review to determine compliance with adopted model codes. Prior to performing any work, the applicant shall make application to, and receive from, the Building Department all applicable construction permits. This review shall not be construed to be an approval of a violation of the provisions of the California Fire Code or of other laws or regulations of the jurisdiction. A permit presuming to give authority to violate or cancel the provisions of the fire code or other such laws or regulations shall not be valid. Any addition to or alteration of approved construction documents shall be approved in advance. [CFC, Ch.1, 105.3.6]
60. FIRE SPRINKLERS REQUIRED: (As noted on Sheet 1) Approved automatic sprinkler systems in new and existing buildings and structures shall be provided in the locations described in this Section or in Sections 903.2.1 through 903.2.12 whichever is the more restrictive and Sections 903.2.14 through 903.2.21. For the purposes of this section, firewalls and fire barriers used to separate building areas shall be constructed in accordance with the California Building Code and shall be without openings or penetrations.
61. REQUIRED FIRE FLOW: (Letter Received) The minimum required fire flow for this project is 875 Gallons Per Minute (GPM) at 20 psi residual pressure. This fire flow assumes installation of automatic fire sprinklers per CFC [903.3.1.3].
62. FIRE DEPARTMENT (ENGINE) ROADWAY TURNAROUND REQUIRED: (As noted on Sheet 4) Dead-end fire apparatus access roads in excess of 150 feet in length shall be provided with an approved area for turning around fire apparatus. Provide an approved fire department engine driveway turnaround with a minimum radius of 50 feet outside and 30 feet inside. Maximum grade in any direction shall be 5%. Installations shall conform with Fire Department Standard Details and Specifications D-1. [CFC Section 503.2.5].
63. WATER SUPPLY REQUIREMENTS: Potable water supplies shall be protected from contamination caused by fire protection water supplies. It is the responsibility of the applicant and any contractors and subcontractors to contact the water purveyor supplying the site of such project, and to comply with the requirements of that purveyor. Such requirements shall be incorporated into the design of any water-based fire protection systems, and/or fire suppression water supply systems or storage containers that may be physically connected in any manner to an appliance capable of causing contamination of the potable water supply of the purveyor of record. Final approval of the system(s) under consideration will not be granted by this office until compliance with the requirements of the water purveyor of record are documented by that purveyor as having been met by the applicant(s). 2022 CFC Sec. 903.3.5 and Health and Safety Code 13114.7.
64. ADDRESS IDENTIFICATION: New and existing buildings shall have approved address numbers, building numbers or approved building identification placed in a position that is

plainly legible and visible from the street or road fronting the property. These numbers shall contrast with their background. Where required by the fire code official, address numbers shall be provided in additional approved locations to facilitate emergency response. Address numbers shall be Arabic numbers or alphabetical letters. Numbers shall be a minimum of 6 inches high with a minimum stroke width of 0.5 inch (12.7 mm). Where access is by means of a private road and the building cannot be viewed from the public way, a monument, pole or other sign or means shall be used to identify the structure. Address numbers shall be maintained. CFC Sec. 505.1.

65. CONSTRUCTION SITE FIRE SAFETY: All construction sites must comply with applicable provisions of the CFC Chapter 33 and our Standard Detail and Specification S1-7. Provide appropriate notations on subsequent plan submittals, as appropriate to the project. CFC Chp. 33.

DRAFT