

PLANNING COMMISSION –December 9, 2020
CONDITIONS OF APPROVAL

62 Ellenwood Avenue
Architecture and Site Application S-20-008

**Requesting Approval for Demolition of an Existing Single-family Residence,
Construction of a New Single-family Residence, Removal of a Large Protected Tree,
and Site Improvements Requiring a Grading Permit on Property Zoned R-1:12.
APN 510-20-068**

PROPERTY OWNER: Lisa Nichols, Arcanum Architecture, Inc.
APPLICANT: Lisa and Case Swenson
PROJECT PLANNER: Sean Mullin

TO THE SATISFACTION OF THE DIRECTOR OF COMMUNITY DEVELOPMENT:

Planning Division

1. **APPROVAL:** This application shall be completed in accordance with all of the conditions of approval and in substantial compliance with the approved plans. Any changes or modifications to the approved plans and/or business operation shall be approved by the Community Development Director, DRC or the Planning Commission depending on the scope of the changes.
2. **EXPIRATION:** The approval will expire two years from the approval date pursuant to Section 29.20.320 of the Town Code, unless the approval has been vested.
3. **OUTDOOR LIGHTING:** Exterior lighting shall be kept to a minimum and shall be down directed fixtures that will not reflect or encroach onto adjacent properties. No flood lights shall be used unless it can be demonstrated that they are needed for safety or security.
4. **TREE REMOVAL PERMIT:** A Tree Removal Permit shall be obtained for any protected trees to be removed, prior to the issuance of a building or grading permit.
5. **EXISTING TREES:** All existing trees shown on the plan and trees required to remain or to be planted are specific subjects of approval of this plan and must remain on the site.
6. **TREE FENCING:** Protective tree fencing, and other protection measures shall be placed at the drip line of existing trees prior to issuance of demolition and building permits and shall remain through all phases of construction. Include a tree protection plan with the construction plans.
7. **TREE STAKING:** All newly planted trees shall be double-staked using rubber tree ties.
8. **FRONT YARD LANDSCAPE:** Prior to issuance of a Certificate of Occupancy the front yard must be landscaped.
9. **ARBORIST REQUIREMENTS:** The developer shall implement, at their cost, all recommendations identified in the Arborist's report. These recommendations must be incorporated in the building permit plans, and completed prior to issuance of a building permit where applicable. A Compliance Memorandum shall be prepared by the applicant

and submitted with the building permit application detailing how the recommendations have or will be addressed.

10. **WATER EFFICIENCY LANDSCAPE ORDINANCE:** The final landscape plan shall meet the requirements of the Town of Los Gatos Water Conservation Ordinance or the State Water Efficient Landscape Ordinance, whichever is more restrictive. Submittal of a Landscape Documentation Package pursuant to WELO is required prior to issuance of a building permit. A review fee based on the current fee schedule adopted by the Town Council is required when working landscape and irrigation plans are submitted for review. A completed WELO Certificate of Completion is required prior to final inspection/certificate of occupancy.
11. **SALVAGE OF BUILDING MATERIALS:** Prior to the issuance of a demolition permit, the developer shall provide the Community Development Director with written notice of the company that will be recycling the building materials. All wood, metal, glass, and aluminum materials generated from the demolished structure shall be deposited to a company which will recycle the materials. Receipts from the company(s) accepting these materials, noting the type and weight of materials, shall be submitted to the Town prior to the Town's demolition inspection.
12. **STORY POLES:** The story poles on the project site shall be removed within 30 days of approval of the Architecture & Site application.
13. **TOWN INDEMNITY:** Applicants are notified that Town Code Section 1.10.115 requires that any applicant who receives a permit or entitlement from the Town shall defend, indemnify, and hold harmless the Town and its officials in any action brought by a third party to overturn, set aside, or void the permit or entitlement. This requirement is a condition of approval of all such permits and entitlements whether or not expressly set forth in the approval and may be secured to the satisfaction of the Town Attorney.
14. **COMPLIANCE MEMORANDUM:** A memorandum shall be prepared and submitted with the building plans detailing how the Conditions of Approval will be addressed.

Building Division

15. **PERMITS REQUIRED:** A Demolition Permit is required for the demolition of the existing single-family residence. A separate Building Permit is required for the construction of the new single-family residence and attached garage. An additional Building Permit will be required for each separate structure that is not attached to another permitted structure (example: swimming pool, ground mount solar array, retaining walls, pool pavilion, etc.)
16. **APPLICABLE CODES:** The current codes, as amended and adopted by the Town of Los Gatos as of January 1, 2020, are the 2019 California Building Standards Code, California Code of Regulations Title 24, Parts 1-12, including locally adopted Energy Reach Codes.
17. **CONDITIONS OF APPROVAL:** The Conditions of Approval must be blue lined in full on the cover sheet of the construction plans. A Compliance Memorandum shall be prepared and submitted with the building permit application detailing how the Conditions of Approval will be addressed.
18. **BUILDING & SUITE NUMBERS:** Submit requests for new building addresses to the Building Division prior to submitting for the building permit application process.

19. **SIZE OF PLANS:** Submit four sets of construction plans, minimum size 24" x 36", maximum size 30" x 42".
20. **REQUIREMENTS FOR COMPLETE DEMOLITION OF STRUCTURE:** Obtain a Building Department Demolition Application and a Bay Area Air Quality Management District Application from the Building Department Service Counter. Once the demolition form has been completed, all signatures obtained, and written verification from PG&E that all utilities have been disconnected, return the completed form to the Building Department Service Counter with the Air District's J# Certificate, PG&E verification, and three (3) sets of site plans showing all existing structures, existing utility service lines such as water, sewer, and PG&E. No demolition work shall be done without first obtaining a permit from the Town.
21. **SOILS REPORT:** A Soils Report, prepared to the satisfaction of the Building Official, containing foundation and retaining wall design recommendations, shall be submitted with the Building Permit Application. This report shall be prepared by a licensed Civil Engineer specializing in soils mechanics.
22. **SHORING:** Shoring plans and calculations will be required for all excavations which exceed five (5) feet in depth or which remove lateral support from any existing building, adjacent property, or the public right-of-way. Shoring plans and calculations shall be prepared by a California licensed engineer and shall conform to the Cal/OSHA regulations.
23. **FOUNDATION INSPECTIONS:** A pad certificate prepared by a licensed civil engineer or land surveyor shall be submitted to the project Building Inspector at foundation inspection. This certificate shall certify compliance with the recommendations as specified in the Soils Report, and that the building pad elevations and on-site retaining wall locations and elevations have been prepared according to the approved plans. Horizontal and vertical controls shall be set and certified by a licensed surveyor or registered Civil Engineer for the following items:
 - a. Building pad elevation
 - b. Finish floor elevation
 - c. Foundation corner locations
 - d. Retaining wall(s) locations and elevations
24. **TITLE 24 ENERGY COMPLIANCE:** All required California Title 24 Energy Compliance Forms must be blue-lined (sticky-backed), i.e. directly printed, onto a plan sheet.
25. **TOWN RESIDENTIAL ACCESSIBILITY STANDARDS:** New residential units shall be designed with adaptability features for single-family residences per Town Resolution 1994-61:
 - a. Wood backing (2" x 8" minimum) shall be provided in all bathroom walls, at water closets, showers, and bathtubs, located 34 inches from the floor to the center of the backing, suitable for the installation of grab bars if needed in the future.
 - b. All passage doors shall be at least 32-inch wide doors on the accessible floor level.
 - c. The primary entrance door shall be a 36-inch-wide door including a 5' x 5' level landing, no more than 1 inch out of plane with the immediate interior floor level and with an 18-inch clearance at interior strike edge.
 - d. A door buzzer, bell or chime shall be hard wired at primary entrance.
26. **BACKWATER VALVE:** The scope of this project may require the installation of a sanitary sewer backwater valve per Town Ordinance 6.50.025. Please provide information on the plans if a backwater valve is required and the location of the installation. The Town of Los

Gatos Ordinance and West Valley Sanitation District (WVSD) requires backwater valves on drainage piping serving fixtures that have flood level rims less than 12 inches above the elevation of the next upstream manhole.

27. HAZARDOUS FIRE ZONE: All projects in the Town of Los Gatos require Class A roof assemblies.
28. WILDLAND-URBAN INTERFACE: This project is located in a Wildland-Urban Interface High Fire Area and must comply with Section R337 of the 2019 California Residential Code, Public Resources Code 4291 and California Government Code Section 51182.
29. PROVIDE DEFENSIBLE SPACE/FIRE BREAK LANDSCAPING PLAN: Prepared by a California licensed Landscape Architect in conformance with California Public Resources Code 4291 and California Government Code Section 51182.
30. PRIOR TO FINAL INSPECTION: Provide a letter from a California licensed Landscape Architect certifying the landscaping and vegetation clearance requirements have been completed per the California Public Resources Code 4291 and Government Code Section 51182.
31. SPECIAL INSPECTIONS: When a special inspection is required by CBC Section 1704, the Architect or Engineer of Record shall prepare an inspection program that shall be submitted to the Building Official for approval prior to issuance of the Building Permit. The Town Special Inspection form must be completely filled-out and signed by all requested parties prior to permit issuance. Special Inspection forms are available from the Building Division Service Counter or online at www.losgatosca.gov/building.
32. BLUEPRINT FOR A CLEAN BAY SHEET: The Town standard Santa Clara Valley Nonpoint Source Pollution Control Program Sheet (page size same as submitted drawings) shall be part of the plan submittal as the second page. The specification sheet is available at the Building Division Service Counter for a fee of \$2 or at ARC Blueprint for a fee or online at www.losgatosca.gov/building.
33. APPROVALS REQUIRED: The project requires the following departments and agencies approval before issuing a building permit:
 - a. Community Development – Planning Division: (408) 354-6874
 - b. Engineering/Parks & Public Works Department: (408) 399-5771
 - c. Santa Clara County Fire Department: (408) 378-4010
 - d. West Valley Sanitation District: (408) 378-2407
 - e. Local School District: The Town will forward the paperwork to the appropriate school district(s) for processing. A copy of the paid receipt is required prior to permit issuance.

TO THE SATISFACTION OF THE DIRECTOR OF PARKS & PUBLIC WORKS:

Engineering Division

34. GENERAL: All public improvements shall be made according to the latest adopted Town Standard Plans, Standard Specifications and Engineering Design Standards. All work shall conform to the applicable Town ordinances. The adjacent public right-of-way shall be kept clear of all job-related mud, silt, concrete, dirt and other construction debris at the end of the day. Dirt and debris shall not be washed into storm drainage facilities. The storing of goods and materials on the sidewalk and/or the street will not be allowed unless an encroachment permit is issued by the Engineering Division of the Parks and Public Works

Department. The Owner, Applicant and/or Developer's representative in charge shall be at the job site during all working hours. Failure to maintain the public right-of-way according to this condition may result in the issuance of correction notices, citations, or stop work orders and the Town performing the required maintenance at the Owner, Applicant and/or Developer's expense.

35. APPROVAL: This application shall be completed in accordance with all the conditions of approval listed below and in substantial compliance with the latest reviewed and approved development plans. Any changes or modifications to the approved plans or conditions of approvals shall be approved by the Town Engineer.
36. CONSTRUCTION PLAN REQUIREMENTS: Construction drawings shall comply with Section 1 (Construction Plan Requirements) of the Town's Engineering Design Standards, which are available for download from the Town's website.
37. PRIOR APPROVALS: All conditions per prior approvals shall be deemed in full force and affect for this approval.
38. CHANGE OF OCCUPANCY: Prior to initial occupancy and any subsequent change in use or occupancy of any non-residential condominium space, the buyer or the new or existing occupant shall apply to the Community Development Department and obtain approval for use determination and building permit and obtain inspection approval for any necessary work to establish the use and/or occupancy consistent with that intended.
39. ENCROACHMENT PERMIT: All work in the public right-of-way will require a Construction Encroachment Permit. All work over \$5,000 will require construction security. It is the responsibility of the Owner/Applicant/Developer to obtain any necessary encroachment permits from affected agencies and private parties, including but not limited to, Pacific Gas and Electric (PG&E), AT&T, Comcast, Santa Clara Valley Water District, California Department of Transportation (Caltrans). Copies of any approvals or permits must be submitted to the Town Engineering Division of the Parks and Public Works Department prior to releasing any permit.
40. PRIVATE IMPROVEMENTS IN THE PUBLIC RIGHT-OF-WAY (INDEMNITY AGREEMENT): The property owner shall enter into an agreement with the Town for all existing and proposed private improvements within the Town's right-of-way. The Owner shall be solely responsible for maintaining the improvements in a good and safe condition at all times and shall indemnify the Town of Los Gatos. The agreement must be completed and accepted by the Director of Parks and Public Works, and subsequently recorded by the Town Clerk at the Santa Clara County Office of the Clerk-Recorder, prior to the issuance of any grading or building permits. Please note that this process may take approximately six to eight (6-8) weeks.
41. GENERAL LIABILITY INSURANCE: The property owner shall provide proof of insurance to the Town on a yearly basis. In addition to general coverage, the policy must cover all elements encroaching into the Town's right-of-way.
42. PUBLIC WORKS INSPECTIONS: The Owner, Applicant and/or Developer or their representative shall notify the Engineering Inspector at least twenty-four (24) hours before starting any work pertaining to on-site drainage facilities, grading or paving, and all work in the Town's right-of-way. Failure to do so will result in penalties and rejection of any work that occurred without inspection.

43. RESTORATION OF PUBLIC IMPROVEMENTS: The Owner, Applicant and/or Developer or their representative shall repair or replace all existing improvements not designated for removal that are damaged or removed because of the Owner, Applicant and/or Developer or their representative's operations. Improvements such as, but not limited to: curbs, gutters, sidewalks, driveways, signs, pavements, raised pavement markers, thermoplastic pavement markings, etc., shall be repaired and replaced to a condition equal to or better than the original condition. Any new concrete shall be free of stamps, logos, names, graffiti, etc. Any concrete identified that is displaying a stamp or equal shall be removed and replaced at the Contractor's sole expense and no additional compensation shall be allowed therefore. Existing improvement to be repaired or replaced shall be at the direction of the Engineering Construction Inspector and shall comply with all Title 24 Disabled Access provisions. The restoration of all improvements identified by the Engineering Construction Inspector shall be completed before the issuance of a certificate of occupancy. The Owner, Applicant and/or Developer or their representative shall request a walk-through with the Engineering Construction Inspector before the start of construction to verify existing conditions.
44. SITE SUPERVISION: The General Contractor shall provide qualified supervision on the job site at all times during construction.
45. STREET/SIDEWALK CLOSURE: Any proposed blockage or partial closure of the street and/or sidewalk requires an encroachment permit. Special provisions such as limitations on works hours, protective enclosures, or other means to facilitate public access in a safe manner may be required.
46. PLAN CHECK FEES: Plan check fees associated with the Grading Permit shall be deposited with the Engineering Division of the Parks and Public Works Department prior to the commencement of plan check review.
47. INSPECTION FEES: Inspection fees shall be deposited with the Town prior to the issuance of any grading or building permits or recordation of the Parcel / Final Map.
48. DESIGN CHANGES: Any proposed changes to the approved plans shall be subject to the approval of the Town prior to the commencement of any and all altered work. The Owner, Applicant and/or Developer's project engineer shall notify, in writing, the Town Engineer at least seventy-two (72) hours in advance of all the proposed changes. Any approved changes shall be incorporated into the final "as-built" plans.
49. PLANS AND STUDIES: All required plans and studies shall be prepared by a Registered Professional Engineer in the State of California and submitted to the Town Engineer for review and approval. Additionally, any post-project traffic or parking counts, or other studies imposed by the Planning Commission or Town Council shall be funded by the Owner, Applicant and/or Developer.
50. GRADING PERMIT: A grading permit is required for all site grading and drainage work except for exemptions listed in Section 12.20.015 of The Code of the Town of Los Gatos (Grading Ordinance). After the preceding Architecture and Site Application has been approved by the respective deciding body, the grading permit application (with grading plans and associated required materials and plan check fees) shall be made to the Engineering Division of the Parks and Public Works Department located at 41 Miles Avenue. The grading plans shall include final grading, drainage, retaining wall location(s), driveway, utilities and interim erosion control. Grading plans shall list earthwork quantities and a table of existing

and proposed impervious areas. Unless specifically allowed by the Director of Parks and Public Works, the grading permit will be issued concurrently with the building permit. The grading permit is for work outside the building footprint(s). Prior to Engineering signing off and closing out on the issued grading permit, the Owner/Applicant/Developer's soils engineer shall verify, with a stamped and signed letter, that the grading activities were completed per plans and per the requirements as noted in the soils report. A separate building permit, issued by the Building Department, located at 110 E. Main Street, is needed for grading within the building footprint.

51. **ILLEGAL GRADING:** Per the Town's Comprehensive Fee Schedule, applications for work unlawfully completed shall be charged double the current fee. As a result, the required grading permit fees associated with an application for grading will be charged accordingly.
52. **DRIVEWAY:** The driveway conform to existing pavement on Ellenwood Avenue shall be constructed in a manner such that the existing drainage patterns will not be obstructed.
53. **CONSTRUCTION EASEMENT:** Prior to the issuance of a grading or building permit, it shall be the sole responsibility of the Owner, Applicant and/or Developer to obtain any and all proposed or required easements and/or permissions necessary to perform the grading herein proposed. Proof of agreement/approval is required prior to the issuance of any Permit.
54. **DRAINAGE STUDY:** Prior to the issuance of any grading or building permits, the following drainage studies shall be submitted to and approved by the Town Engineer: a drainage study of the project including diversions, off-site areas that drain onto and/or through the project, and justification of any diversions; a drainage study evidencing that the proposed drainage patterns will not overload the existing storm drain facilities; and detailed drainage studies indicating how the project grading, in conjunction with the drainage conveyance systems (including applicable swales, channels, street flows, catch basins, storm drains, and flood water retarding) will allow building pads to be safe from inundation from rainfall runoff which may be expected from all storms up to and including the theoretical 100-year flood.
55. **TREE REMOVAL:** Copies of all necessary tree removal permits shall be provided prior to the issuance of a grading permit/building permit.
56. **SURVEYING CONTROLS:** Horizontal and vertical controls shall be set and certified by a licensed surveyor or registered civil engineer qualified to practice land surveying, for the following items:
 - a. Retaining wall: top of wall elevations and locations.
 - b. Toe and top of cut and fill slopes.
57. **PRECONSTRUCTION MEETING:** Prior to issuance of any grading or building permits or the commencement of any site work, the general contractor shall:
 - a. Along with the Owner, Applicant and/or Developer, attend a pre-construction meeting with the Town Engineer to discuss the project conditions of approval, working hours, site maintenance and other construction matters;
 - b. Acknowledge in writing that they have read and understand the project conditions of approval and will make certain that all project sub-contractors have read and understand them as well prior to commencing any work, and that a copy of the project conditions of approval will be posted on-site at all times during construction.

58. **RETAINING WALLS:** A building permit, issued by the Building Department, located at 110 E. Main Street, may be required for site retaining walls. Walls are not reviewed or approved by the Engineering Division of Parks and Public Works during the grading permit plan review process.
59. **IMPROVEMENT AGREEMENT:** The Owner, Applicant and/or Developer shall enter into an agreement to construct public improvements in accordance with Town Code Section 24.40.020. The Owner, Applicant and/or Developer shall supply suitable securities for all public improvements that are part of the development in a form acceptable to the Town in the amount of 100% performance and 100% labor and materials prior to the issuance of any encroachment, grading or building permit. The Owner, Applicant and/or Developer shall provide two (2) copies of documents verifying the cost of the public improvements to the satisfaction of the Engineering Division of the Parks and Public Works Department. An electronic copy (PDF) of the executed agreement shall be submitted to the Engineering Division of the Parks and Public Works Department prior to the issuance of any encroachment, grading or building permit.
60. **WATER METER:** The existing water meter, currently located within the Ellenwood Avenue right-of-way, shall be relocated within the property in question, directly behind the public right-of-way line. The Owner, Applicant and/or Developer shall repair and replace to existing Town standards any portion of concrete flatwork within said right-of-way that is damaged during this activity prior to issuance of a certificate of occupancy.
61. **CERTIFICATE OF OCCUPANCY:** The Engineering Division of the Parks and Public Works Department will not sign off on a Temporary Certificate of Occupancy or a Final Certificate of Occupancy until all required improvements within the Town's right-of-way have been completed and approved by the Town.
62. **GREEN INFRASTRUCTURE MEASURES:** Projects which propose work within the Town's right-of-way, including but not limited to pavement restoration, street widening, construction of curb, gutter and/or sidewalk, right-of-way dedication, etc., will be evaluated by Staff to determine its potential for the implementation of Green Infrastructure measures and associated improvements.
63. **FRONTAGE IMPROVEMENTS:** The Owner and/or Applicant shall be required to improve the project's public frontage (right-of-way line to centerline and/or to limits per the direction of the Town Engineer) to current Town Standards. These improvements may include but not limited to curb, gutter, sidewalk, driveway approach(es), curb ramp(s), signs, pavement, raised pavement markers, thermoplastic pavement markings, storm drain facilities, traffic signal(s), street lighting (upgrade and/or repaint) etc. The improvements must be completed and accepted by the Town before a Certificate of Occupancy for any new building can be issued.
64. **UTILITIES:** The Owner, Applicant and/or Developer shall install all new, relocated, or temporarily removed utility services, including telephone, electric power and all other communications lines underground, as required by Town Code Section 27.50.015(b). All new utility services shall be placed underground. Underground conduit shall be provided for cable television service. The Owner, Applicant and/or Developer is required to obtain approval of all proposed utility alignments from any and all utility service providers before a

Certificate of Occupancy for any new building can be issued. The Town of Los Gatos does not approve or imply approval for final alignment or design of these facilities.

65. CONSTRUCTION VEHICLE PARKING: Construction vehicle parking within the public right-of-way will only be allowed if it does not cause access or safety problems as determined by the Town.
66. HAULING OF SOIL: Hauling of soil on- or off-site shall not occur during the morning or evening peak periods (between 7:00 a.m. and 9:00 a.m. and between 4:00 p.m. and 6:00 p.m.), and at other times as specified by the Director of Parks and Public Works. Prior to the issuance of a grading or building permit, the Owner and/or Applicant or their representative shall work with the Town Building Department and Engineering Division Inspectors to devise a traffic control plan to ensure safe and efficient traffic flow under periods when soil is hauled on or off the project site. This may include, but is not limited to provisions for the Owner and/or Applicant to place construction notification signs noting the dates and time of construction and hauling activities, or providing additional traffic control. Coordination with other significant projects in the area may also be required. Cover all trucks hauling soil, sand and other loose debris.
67. CONSTRUCTION HOURS: All subdivision improvements and site improvements construction activities, including the delivery of construction materials, labors, heavy equipment, supplies, etc., shall be limited to the hours of 8:00 a.m. to 8:00 p.m., weekdays and 9:00 a.m. to 7:00 p.m. weekends and holidays. The Town may authorize, on a case-by-case basis, alternate construction hours. The Owner, Applicant and/or Developer shall provide written notice twenty-four (24) hours in advance of modified construction hours. Approval of this request is at discretion of the Town.
68. CONSTRUCTION NOISE: Between the hours of 8:00 a.m. to 8:00 p.m., weekdays and 9:00 a.m. to 7:00 p.m. weekends and holidays, construction, alteration or repair activities shall be allowed. No individual piece of equipment shall produce a noise level exceeding eighty-five (85) dBA at twenty-five (25) feet from the source. If the device is located within a structure on the property, the measurement shall be made at distances as close to twenty-five (25) feet from the device as possible. The noise level at any point outside of the property plane shall not exceed eighty-five (85) dBA.
69. CONSTRUCTION MANAGEMENT PLAN SHEET: Prior to the issuance of any grading or building permits, the Owner and/or Applicant's design consultant shall submit a construction management plan sheet (full-size) within the plan set that shall incorporate at a minimum the Project Schedule, employee parking, construction staging area, materials storage area(s), concrete washout(s) and proposed outhouse locations. Please refer to the Town's Construction Management Plan Guidelines document for additional information.
70. WVSD (West Valley Sanitation District): Sanitary sewer laterals are televised by West Valley Sanitation District and approved by the Town of Los Gatos before they are used. A Sanitary Sewer Clean-out is required for each property at the property line, within one (1) foot of the property line per West Valley Sanitation District Standard Drawing 3, or at a location specified by the Town.
71. SANITARY SEWER BACKWATER VALVE: Drainage piping serving fixtures which have flood level rims less than twelve (12) inches (304.8 mm) above the elevation of the next upstream manhole and/or flushing inlet cover at the public or private sewer system serving such

drainage piping shall be protected from backflow of sewage by installing an approved type backwater valve. Fixtures above such elevation shall not discharge through the backwater valve, unless first approved by the Building Official. The Town shall not incur any liability or responsibility for damage resulting from a sewer overflow where the property owner or other person has failed to install a backwater valve as defined in the Uniform Plumbing Code adopted by the Town and maintain such device in a functional operation condition. Evidence of West Sanitation District's decision on whether a backwater device is needed shall be provided prior to the issuance of a building permit.

72. **BEST MANAGEMENT PRACTICES (BMPs):** The Owner, Applicant and/or Developer is responsible for ensuring that all contractors are aware of all storm water quality measures and that such measures are implemented. Best Management Practices (BMPs) shall be maintained and be placed for all areas that have been graded or disturbed and for all material, equipment and/or operations that need protection. Removal of BMPs (temporary removal during construction activities) shall be replaced at the end of each working day. Failure to comply with the construction BMP will result in the issuance of correction notices, citations, or stop work orders.
73. **NPDES STORMWATER COMPLIANCE:** In the event that, during the production of construction drawings for the plans approved with this application by the Town of Los Gatos, it is determined that the project will create and/or replace more than 2,500 square feet of impervious area, completion of the NPDES Stormwater Compliance Small Projects Worksheet and implementation of at least one of the six low impact development site design measures it specifies shall be completed and submitted to the Engineering Division before issuance of a grading/building permit.
74. **SITE DESIGN MEASURES:** All projects shall incorporate at least one of the following measures:
 - a. Protect sensitive areas and minimize changes to the natural topography.
 - b. Minimize impervious surface areas.
 - c. Direct roof downspouts to vegetated areas.
 - d. Use porous or pervious pavement surfaces on the driveway, at a minimum.
 - e. Use landscaping to treat stormwater.
75. **DUST CONTROL:** Blowing dust shall be reduced by timing construction activities so that paving and building construction begin as soon as possible after completion of grading, and by landscaping disturbed soils as soon as possible. Further, water trucks shall be present and in use at the construction site. All portions of the site subject to blowing dust shall be watered as often as deemed necessary by the Town, or a minimum of three (3) times daily, or apply (non-toxic) soil stabilizers on all unpaved access roads, parking areas, and staging areas at construction sites in order to insure proper control of blowing dust for the duration of the project. Watering on public streets shall not occur. Streets shall be cleaned by street sweepers or by hand as often as deemed necessary by the Town Engineer, or at least once a day. Watering associated with on-site construction activity shall take place between the hours of 8 a.m. and 5 p.m. and shall include at least one (1) late-afternoon watering to minimize the effects of blowing dust. All public streets soiled or littered due to this construction activity shall be cleaned and swept on a daily basis during the workweek to the satisfaction of the Town. Demolition or earthwork activities shall be halted when wind

speeds (instantaneous gusts) exceed twenty (20) miles per hour (MPH). All trucks hauling soil, sand, or other loose debris shall be covered.

76. CONSTRUCTION ACTIVITIES: All construction shall conform to the latest requirements of the CASQA Stormwater Best Management Practices Handbooks for Construction Activities and New Development and Redevelopment, the Town's grading and erosion control ordinance, and other generally accepted engineering practices for erosion control as required by the Town Engineer when undertaking construction activities.
77. WATER FEATURES: New swimming pools shall have a connection to the sanitary sewer system, subject to West Valley Sanitation District's authority and standards, to facilitate draining events. Discharges from this feature shall be directed to the sanitary sewer and are not allowed into the storm drain system.
78. SITE DRAINAGE: Rainwater leaders shall be discharged to splash blocks. No through curb drains will be allowed. Any storm drain inlets (public or private) directly connected to public storm system shall be stenciled/signed with appropriate "NO DUMPING - Flows to Bay" NPDES required language. On-site drainage systems for all projects shall include one of the alternatives included in section C.3.i of the Municipal Regional NPDES Permit. These include storm water reuse via cisterns or rain barrels, directing runoff from impervious surfaces to vegetated areas and use of permeable surfaces. If stormwater treatment facilities are to be used they shall be placed a minimum of ten (10) feet from the adjacent property line and/or right-of-way. Alternatively, the facility(ies) may be located with an offset between 5 and 10 feet from the adjacent property and/or right-of-way line(s) if the responsible engineer in charge provides a stamped and signed letter that addresses infiltration and states how facilities, improvements and infrastructure within the Town's right-of-way (driveway approach, curb and gutter, etc.) and/or the adjacent property will not be adversely affected. No improvements shall obstruct or divert runoff to the detriment of an adjacent, downstream or down slope property.
79. SILT AND MUD IN PUBLIC RIGHT-OF-WAY: It is the responsibility of Contractor and homeowner to make sure that all dirt tracked into the public right-of-way is cleaned up on a daily basis. Mud, silt, concrete and other construction debris SHALL NOT be washed into the Town's storm drains.
80. GOOD HOUSEKEEPING: Good housekeeping practices shall be observed at all times during the course of construction. All construction shall be diligently supervised by a person or persons authorized to do so at all times during working hours. The Owner, Applicant and/or Developer's representative in charge shall be at the job site during all working hours. Failure to maintain the public right-of-way according to this condition may result in penalties and/or the Town performing the required maintenance at the Owner, Applicant and/or Developer's expense.
81. COVERED TRUCKS: All trucks transporting materials to and from the site shall be covered.

TO THE SATISFACTION OF THE SANTA CLARA COUNTY FIRE DEPARTMENT:

82. GENERAL: Review of this Developmental proposal is limited to acceptability of site access, water supply and may include specific additional requirements as they pertain to fire department operations, and shall not be construed as a substitute for formal plan review to

determine compliance with adopted model codes. Prior to performing any work, the applicant shall make application to, and receive from, the Building Department all applicable construction permits.

83. FIRE SPRINKLERS REQUIRED: (As noted on Sheet A0.0 and L0.0) An automatic residential fire sprinkler system shall be installed in one- and two-family dwellings as follows: 1) In all new one- and two-family dwellings and in existing one- and two-family dwellings when additions are made that increase the building area to more than 3,600 SF whether by increasing the area of the primary residence or by creation of an attached Accessory Dwelling Unit. 2) In all new basements and in existing basements that are expanded by more than 50%. 3) In all attached ADUs, additions or alterations to an existing one- and two-family dwelling that have an existing fire sprinkler system. Exceptions: 1) One or more additions made to a building after January 1, 2011 that does not total more than 1,000 square feet of building area and meets all access and water supply requirements of Chapter 5 and Appendix B and C of the 2019 California Fire Code. Sprinklers are required for both structures.
84. WATER SUPPLY REQUIREMENTS: (As noted on Sheet L0.0) Potable water supplies shall be protected from contamination caused by fire protection water supplies. It is the responsibility of the applicant and any contractors and subcontractors to contact the water purveyor supplying the site of such project, and to comply with the requirements of that purveyor. Such requirements shall be incorporated into the design of any water-based fire protection systems, and/or fire suppression water supply systems or storage containers that may be physically connected in any manner to an appliance capable of causing contamination of the potable water supply of the purveyor of record. Final approval of the system(s) under consideration will not be granted by this office until compliance with the requirements of the water purveyor of record are documented by that purveyor as having been met by the applicant(s). 2019 CFC Sec. 903.3.5 and Health and Safety Code 13114.7
85. ADDRESS IDENTIFICATION: (As noted on Sheet L0.0) New and existing buildings shall have approved address numbers, building numbers or approved building identification placed in a position that is plainly legible and visible from the street or road fronting the property. These numbers shall contrast with their background. Address numbers shall be Arabic numbers or alphabetical letters. Numbers shall be a minimum of 4 inches (101.6 mm) high with a minimum stroke width of 0.5 inch (12.7 mm). Where access is by means of a private road and the building cannot be viewed from the public way, a monument, pole or other sign or means shall be used to identify the structure. CFC Sec. 505.1.
86. CONSTRUCTION SITE FIRE SAFETY: (As noted on Sheet L0.0) All construction sites must comply with applicable provisions of the CFC Chapter 33 and our Standard Detail and Specification SI-7. Provide appropriate notations on subsequent plan submittals, as appropriate to the project. CFC Chp. 33.
87. EMERGENCY GATE/ACCESS GATE REQUIREMENTS: (As noted on Sheet C2.1 and L0.0) Gate installations shall conform with Fire Department Standard Details and Specification G-1 and, when open shall not obstruct any portion of the minimum required width for emergency access roadways or driveways. Locks, if provided, shall be fire department approved prior to installation. Gates across the emergency access roadways shall be equipped with an approved access devices. If the gates are operated electrically, an approved Knox key switch shall be installed; if they are operated manually, then an approved Knox padlock shall be

installed. Gates providing access from a road to a driveway or other roadway shall be at least 18 feet from the road being exited. [CFC Sec. 503.6 and 506] [LGTC Sec. 29.40.030]. A Knox Key Switch will be provided and installed as noted. Rev. 10/13/20 KB.

88. FIRE APPARATUS (ENGINE)ACCESS DRIVEWAY REQUIRED: (As noted on Sheet C2.1 and L0.0) Provide an access driveway with a paved all weather surface, a minimum unobstructed width of 12 feet, vertical clearance of 13 feet 6 inches, minimum circulating turning radius of 36 feet outside and 23 feet inside, and a maximum slope of 15%. Installations shall conform to Fire Department Standard Details and Specifications sheet D-1. Rev. 10/13/20 KB.
89. General: This review shall not be construed to be an approval of a violation of the provisions of the California Fire Code or of other laws or regulations of the jurisdiction. A permit presuming to give authority to violate or cancel the provisions of the fire code or other such laws or regulations shall not be valid. Any addition to or alteration of approved construction documents shall be approved in advance. [CFC, Ch.1, 105.3.6]

***This Page
Intentionally
Left Blank***