



TOWN OF LOS GATOS
COMMUNITY DEVELOPMENT DEPARTMENT
PLANNING DIVISION
(408) 354-6872 Fax (408) 354-7593

CIVIC CENTER
110 E. MAIN STREET
LOS GATOS, CA 95030

November 15, 2024

Vyankatesh and Rammy Muddada
15415 National Avenue
Los Gatos, CA 95032
Via Email

RE: 15411 National Avenue
Architecture and Site Application S-23-033

Requesting Approval to Construct a Single-Family Residence, and Site Improvements Requiring a Grading Permit on a Vacant Property Zoned R-1:8. APN 424-12-140. Categorically Exempt Pursuant to CEQA Guidelines Section 15303: New Construction.

PROPERTY OWNER: Vyankatesh and Rammy Muddada

APPLICANT: Jose Rama

At its meeting of November 13, 2024, the Town of Los Gatos Planning Commission approved the above referenced application with additional conditions:

- The tree species shall be mutually agreed upon by the neighbors that they are a minimum protective of privacy and non-allergenic to any of the neighbors.
- The applicant shall meet in good faith to relocate the offending windows such that they are the least offensive to the privacy interests of the neighbors.
- The privacy windows shall utilize obscured glass. Privacy film shall not be used.

The attached draft modified conditions of approval will not be final until the Planning Commission has approved the November 13, 2024, meeting minutes at their next meeting, confirming any additional or modified conditions of approval for the project in the underlined font. You will be notified in writing once the Planning Commission has approved the minutes.

PLEASE NOTE: Pursuant to Section 29.20.275 of the Town Code, this approval may be appealed to the Town Council within 10 days of the date the approval is granted. Therefore, this action for approval should not be considered final, and no permits by the Town will be issued until the appeal period has passed.

If you have any questions, you may contact me by email at ewalters@losgatosca.gov.

Sincerely,

Erin Walters
Associate Planner

Cc: Jose Rama, jer@jerdesigngroup.com

PLANNING COMMISSION – November 13, 2024
CONDITIONS OF APPROVAL

15411 National Avenue
Architecture and Site Application S-23-033

Requesting Approval for Construction of a Single-Family Residence and Site Improvements Requiring a Grading Permit on a Vacant Property Zoned R-1:8. APN 424-12-140. Categorically Exempt Pursuant to CEQA Guidelines Section 15303: New Construction.

Property Owner: Vyankatesh and Rammy Muddada.

Applicant: Jose Rama.

Project Planner: Erin Walters.

TO THE SATISFACTION OF THE COMMUNITY DEVELOPMENT DIRECTOR:

Planning Division

1. APPROVAL: This application shall be completed in accordance with all of the conditions of approval and in substantial compliance with the approved plans. Any changes or modifications to the approved plans and/or business operation shall be approved by the Community Development Director, DRC, or the Planning Commission depending on the scope of the changes.
2. EXPIRATION: The approval will expire two years from the approval date pursuant to Section 29.20.320 of the Town Code, unless the approval has been vested.
3. OUTDOOR LIGHTING: Exterior lighting shall be kept to a minimum, and shall be down directed fixtures that will not reflect or encroach onto adjacent properties. No flood lights shall be used unless it can be demonstrated that they are needed for safety or security.
4. TREE REMOVAL PERMIT: A Tree Removal Permit shall be obtained for any trees to be removed, prior to the issuance of a building or grading permit.
5. EXISTING TREES: All existing trees shown on the plan and trees required to remain or to be planted are specific subjects of approval of this plan, and must remain on the site.
6. ARBORIST REQUIREMENTS: The developer shall implement, at their cost, all recommendations identified in the Arborist's report for the project, on file in the Community Development Department. These recommendations must be incorporated in the building permit plans and completed prior to issuance of a building permit where applicable.
7. TREE FENCING: Protective tree fencing and other protection measures consistent with Section 29.10.1005 of the Town Code shall be placed at the drip line of existing trees prior to issuance of demolition and building permits and shall remain through all phases of construction. Include a tree protection plan with the construction plans.
8. TREE STAKING: All newly planted trees shall be double-staked using rubber tree ties.
9. FRONT YARD LANDSCAPE: Prior to issuance of a Certificate of Occupancy the front yard must be landscaped.
10. TREE SPECIES: The tree species shall be mutually agreed upon by the neighbors that they

- are a minimum protective of privacy and non-allergenic to any of the neighbors.
11. PRIVACY TREE PLANTING: Prior to obtaining a building final the property owner must plant five 24-gallon ~~Leyland Cypress~~ trees along the northern fence line. Privacy trees must be maintained by the property owner.
 12. WINDOW LOCATION – The applicant shall meet in good faith to relocate the offending windows such that they are the least offensive to the privacy interests of the neighbors.
 13. FROSTED/OBSCURE PRIVACY WINDOWS – The two second floor bedroom windows located on the northern elevation of the residence shall have frosted or obscure glass to provide privacy between properties.
 14. OBSCURE GLASS – The privacy windows shall utilize obscured glass. Privacy film shall not be used.
 15. WATER EFFICIENCY LANDSCAPE ORDINANCE: The final landscape plan shall meet the Town of Los Gatos Water Conservation Ordinance or the State Water Efficient Landscape Ordinance, whichever is more restrictive. A review fee based on the current fee schedule adopted by the Town Council is required when working landscape and irrigation plans are submitted for review.
 16. STORY POLES/PROJECT IDENTIFICATION SIGNAGE: Story poles and/or project identification signage on the project site shall be removed within 30 days of approval of the Architecture & Site application.
 17. TOWN INDEMNITY: Applicants are notified that Town Code Section 1.10.115 requires that any applicant who receives a permit or entitlement (“the Project”) from the Town shall defend (with counsel approved by Town), indemnify, and hold harmless the Town, its agents, officers, and employees from and against any claim, action, or proceeding (including without limitation any appeal or petition for review thereof) against the Town or its agents, officers or employees related to an approval of the Project, including without limitation any related application, permit, certification, condition, environmental determination, other approval, compliance or failure to comply with applicable laws and regulations, and/or processing methods (“Challenge”). Town may (but is not obligated to) defend such Challenge as Town, in its sole discretion, determines appropriate, all at applicant’s sole cost and expense.

Applicant shall bear any and all losses, damages, injuries, liabilities, costs and expenses (including, without limitation, staff time and in-house attorney’s fees on a fully-loaded basis, attorney’s fees for outside legal counsel, expert witness fees, court costs, and other litigation expenses) arising out of or related to any Challenge (“Costs”), whether incurred by Applicant, Town, or awarded to any third party, and shall pay to the Town upon demand any Costs incurred by the Town. No modification of the Project, any application, permit certification, condition, environmental determination, other approval, change in applicable laws and regulations, or change in such Challenge as Town, in its sole discretion, determines appropriate, all the applicant’s sole cost and expense. No modification of the Project, any application, permit certification, condition, environmental determination, other approval, change in applicable laws and regulations, or change in processing methods shall alter the applicant’s indemnity obligation.

18. COMPLIANCE MEMORANDUM: A memorandum shall be prepared and submitted with the

building plans detailing how the Conditions of Approval will be addressed.

Building Division

19. PERMITS REQUIRED: A Building Permit is required for the construction of the new single-family residence and attached garage. An additional Building Permit will be required for the PV System that is required by the California Energy Code.
20. APPLICABLE CODES: The current codes, as amended and adopted by the Town of Los Gatos as of January 1, 2023, are the 2022 California Building Standards Code, California Code of Regulations Title 24, Parts 1-12, including locally adopted Reach Codes.
21. CONDITIONS OF APPROVAL: The Conditions of Approval must be blue lined in full on the cover sheet of the construction plans. A Compliance Memorandum shall be prepared and submitted with the building permit application detailing how the Conditions of Approval will be addressed.
22. BUILDING & SUITE NUMBERS: Submit requests for new building addresses to the Building Division prior to submitting for the building permit application process.
23. SIZE OF PLANS: Minimum size 24" x 36", maximum size 30" x 42".
24. SOILS REPORT: A Soils Report, prepared to the satisfaction of the Building Official, containing foundation, and retaining wall design recommendations, shall be submitted with the Building Permit Application. This report shall be prepared by a licensed Civil Engineer specializing in soils mechanics.
25. SHORING: Shoring plans and calculations will be required for all excavations which exceed five (5) feet in depth, or which remove lateral support from any existing building, adjacent property, or the public right-of-way. Shoring plans and calculations shall be prepared by a California licensed engineer and shall conform to the Cal/OSHA regulations.
26. FOUNDATION INSPECTIONS: A pad certificate prepared by a licensed civil engineer or land surveyor shall be submitted to the project Building Inspector at foundation inspection. This certificate shall certify compliance with the recommendations as specified in the Soils Report, and that the building pad elevations and on-site retaining wall locations and elevations have been prepared according to the approved plans. Horizontal and vertical controls shall be set and certified by a licensed surveyor or registered Civil Engineer for the following items: Building pad elevation
 - a. Finish floor elevation
 - b. Foundation corner locations
 - c. Retaining wall(s) locations and elevations
27. TITLE 24 ENERGY COMPLIANCE: All required California Title 24 Energy Compliance Forms must be blue-lined (sticky-backed), i.e., directly printed, onto a plan sheet.
28. TOWN RESIDENTIAL ACCESSIBILITY STANDARDS: New residential units shall be designed with adaptability features for single-family residences per Town Resolution 1994-61:
 - a. Wood backing (2" x 8" minimum) shall be provided in all bathroom walls, at water closets, showers, and bathtubs, located 34 inches from the floor to the center of the backing, suitable for the installation of grab bars if needed in the future.
 - b. All passage doors shall be at least 32-inch-wide doors on the accessible floor level.

- c. The primary entrance door shall be a 36-inch-wide door including a 5'x 5' level landing, no more than 1 inch out of plane with the immediate interior floor level and with an 18-inch clearance at interior strike edge.
 - d. A door buzzer, bell or chime shall be hard wired at primary entrance.
29. BACKWATER VALVE: The scope of this project may require the installation of a sanitary sewer backwater valve per Town Ordinance 6.40.020. Please provide information on the plans if a backwater valve is required and the location of the installation. The Town of Los Gatos Ordinance and West Valley Sanitation District (WVSD) requires backwater valves on drainage piping serving fixtures that have flood level rims less than 12 inches above the elevation of the next upstream manhole.
30. HAZARDOUS FIRE ZONE: All projects in the Town of Los Gatos require Class A roof assemblies.
31. SPECIAL INSPECTIONS: When a special inspection is required by CBC Section 1704, the Architect or Engineer of Record shall prepare an inspection program that shall be submitted to the Building Official for approval prior to issuance of the Building Permit. The Town Special Inspection form must be completely filled-out and signed by all requested parties prior to permit issuance. Special Inspection forms are available online at www.losgatosca.gov/building.
32. BLUEPRINT FOR A CLEAN BAY SHEET: The Town standard Santa Clara Valley Nonpoint Source Pollution Control Program Sheet (page size same as submitted drawings) shall be part of the plan submittal as the second page. The specification sheet is available online at www.losgatosca.gov/building.
33. APPROVALS REQUIRED: The project requires the following departments and agencies approval before issuing a building permit:
- a. Community Development – Planning Division: (408) 354-6874
 - b. Engineering/Parks & Public Works Department: (408) 399-5771
 - c. Santa Clara County Fire Department: (408) 378-4010
 - d. West Valley Sanitation District: (408) 378-2407
 - e. Local School District: The Town will forward the paperwork to the appropriate school district(s) for processing. A copy of the paid receipt is required prior to permit issuance.

TO THE SATISFACTION OF THE DIRECTOR OF PARKS & PUBLIC WORKS:

Engineering Division

34. GENERAL: All public improvements shall be made according to the latest adopted Town Standard Plans, Standard Specifications and Engineering Design Standards. All work shall conform to the applicable Town ordinances. The adjacent public right-of-way shall be kept clear of all job-related mud, silt, concrete, dirt and other construction debris at the end of the day. Dirt and debris shall not be washed into storm drainage facilities. The storing of goods and materials on the sidewalk and/or the street will not be allowed unless an encroachment permit is issued by the Engineering Division of the Parks and Public Works Department. The Owner's representative in charge shall be at the job site during all working hours. Failure to maintain the public right-of-way according to this condition may result in

the issuance of correction notices, citations, or stop work orders and the Town performing the required maintenance at the Owner's expense.

35. PAYMENT OPTIONS:

- a. All payments regarding fees and deposits can be mailed to:

Town of Los Gatos PPW – Attn: Engineering Dept
41 Miles Avenue
Los Gatos, CA 95030

Or hand deliver/drop off payment in engineering lock box

Checks made out to **"Town of Los Gatos"** and should mention **address and application number** on memo/note line.

36. APPROVAL: This application shall be completed in accordance with all the conditions of approval listed below and in substantial compliance with the latest reviewed and approved development plans. Any changes or modifications to the approved plans or conditions of approvals shall be approved by the Town Engineer.
37. CONSTRUCTION PLAN REQUIREMENTS: Construction drawings shall comply with Section 1 (Construction Plan Requirements) of the Town's Engineering Design Standards, which are [available for download from the Town's website](#).
38. CHANGE OF OCCUPANCY: Prior to initial occupancy and any subsequent change in use or occupancy of any non-residential condominium space, the buyer or the new or existing occupant shall apply to the Community Development Department and obtain approval for use determination and building permit and obtain inspection approval for any necessary work to establish the use and/or occupancy consistent with that intended.
39. GENERAL LIABILITY INSURANCE: The property owner shall provide proof of insurance to the Town on a yearly basis. In addition to general coverage, the policy must cover all elements encroaching into the Town's right-of-way.
40. PUBLIC WORKS INSPECTIONS: The Owner, Applicant and/or Developer or their representative shall notify the Engineering Inspector at least twenty-four (24) hours before starting any work pertaining to on-site drainage facilities, grading or paving, and all work in the Town's right-of-way. Failure to do so will result in penalties and rejection of any work that occurred without inspection.
41. RESTORATION OF PUBLIC IMPROVEMENTS: The Owner, Applicant and/or Developer or their representative shall repair or replace all existing improvements not designated for removal that are damaged or removed because of the Owner, Applicant and/or Developer or their representative's operations. Improvements such as, but not limited to: curbs, gutters, sidewalks, driveways, signs, pavements, raised pavement markers, thermoplastic pavement markings, etc., shall be repaired and replaced to a condition equal to or better than the original condition. Any new concrete shall be free of stamps, logos, names, graffiti, etc. Any concrete identified that is displaying a stamp or equal shall be removed and replaced at the Contractor's sole expense and no additional compensation shall be allowed therefore. Existing improvement to be repaired or replaced shall be at the direction of the Engineering Construction Inspector and shall comply with all Title 24 Disabled Access

provisions. The restoration of all improvements identified by the Engineering Construction Inspector shall be completed before the issuance of a certificate of occupancy. The Owner, Applicant and/or Developer or their representative shall request a walk-through with the Engineering Construction Inspector before the start of construction to verify existing conditions.

42. PLAN CHECK FEES: Plan check fees associated with the Grading Permit shall be deposited with the Engineering Division of the Parks and Public Works Department prior to the commencement of plan check review.
43. SITE SUPERVISION: The General Contractor shall provide qualified supervision on the job site at all times during construction.
44. INSPECTION FEES: Inspection fees shall be deposited with the Town prior to the issuance of permits or recordation of maps.
45. DESIGN CHANGES: Any proposed changes to the approved plans shall be subject to the approval of the Town prior to the commencement of any and all altered work. The Owner's project engineer shall notify, in writing, the Town Engineer at least seventy-two (72) hours in advance of all the proposed changes. Any approved changes shall be incorporated into the final "as-built" plans.
46. PLANS AND STUDIES: All required plans and studies shall be prepared by a Registered Professional Engineer in the State of California and submitted to the Town Engineer for review and approval. Additionally, any post-project traffic or parking counts, or other studies imposed by the Planning Commission or Town Council shall be funded by the Owner, Applicant and/or Developer.
47. GRADING PERMIT DETERMINATION DURING CONSTRUCTION DRAWINGS: All grading work taking place with this application and related applications/projects within a two year time period are considered eligible for the grading permit process and will be counted toward the quantities used in determining grading permit requirements. In the event that, during the production of construction drawings and/or during construction of the plans approved with this application by the Town of Los Gatos, it is determined that a grading permit would be required as described in Chapter 12, Article II (Grading Permit) of the Town Code of the Town of Los Gatos, an Architecture and Site Application would need to be submitted by the Owner for review and approval by the Development Review Committee prior to applying for a grading permit.
48. GRADING: Any grading work, cut/fill, earthwork or combination thereof (completed or proposed on submitted plans) on the parcel over the upcoming two-year period are combined with regards to grading permit thresholds. This also applies to adjacent parcels with identical owners, applicants and or developers.
49. ILLEGAL GRADING: Per the Town's Comprehensive Fee Schedule, applications for work unlawfully completed shall be charged double the current fee. As a result, the required grading permit fees associated with an application for grading will be charged accordingly.
50. DUST CONTROL: Blowing dust shall be reduced by timing construction activities so that paving and building construction begin as soon as possible after completion of grading, and by landscaping disturbed soils as soon as possible. Further, water trucks shall be present and in use at the construction site. All portions of the site subject to blowing dust shall be watered as often as deemed necessary by the Town, or a minimum of three (3) times daily,

or apply (non-toxic) soil stabilizers on all unpaved access roads, parking areas, and staging areas at construction sites in order to insure proper control of blowing dust for the duration of the project. Watering on public streets shall not occur. Streets shall be cleaned by street sweepers or by hand as often as deemed necessary by the Town Engineer, or at least once a day. Watering associated with on-site construction activity shall take place between the hours of 8 a.m. and 5 p.m. and shall include at least one (1) late-afternoon watering to minimize the effects of blowing dust. All public streets soiled or littered due to this construction activity shall be cleaned and swept on a daily basis during the workweek to the satisfaction of the Town. Demolition or earthwork activities shall be halted when wind speeds (instantaneous gusts) exceed twenty (20) miles per hour (MPH). All trucks hauling soil, sand, or other loose debris shall be covered. For sites greater than four (4) acres in area:

- a. Enclose, cover, water twice daily or apply (non-toxic) soil binders to exposed stockpiles (dirt, sand, etc.).
 - b. Limit traffic speeds on unpaved roads to fifteen (15) miles per hour.
 - c. Install sandbags or other erosion control measures to prevent silt runoff to public roadways.
 - d. Replant vegetation in disturbed areas as quickly as possible.
 - e. Hydroseed or apply (non-toxic) soil stabilizers to inactive construction areas (previously graded areas inactive for ten days or more).
51. CONSTRUCTION ACTIVITIES: All construction shall conform to the latest requirements of the CASQA Stormwater Best Management Practices Handbooks for Construction Activities and New Development and Redevelopment, the Town's grading and erosion control ordinance, and other generally accepted engineering practices for erosion control as required by the Town Engineer when undertaking construction activities.
52. SILT AND MUD IN PUBLIC RIGHT-OF-WAY: It is the responsibility of Contractor and homeowner to make sure that all dirt tracked into the public right-of-way is cleaned up on a daily basis. Mud, silt, concrete and other construction debris SHALL NOT be washed into the Town's storm drains.
53. COVERED TRUCKS: All trucks transporting materials to and from the site shall be covered.
54. GOOD HOUSEKEEPING: Good housekeeping practices shall be observed at all times during the course of construction. All construction shall be diligently supervised by a person or persons authorized to do so at all times during working hours. The Owner's representative in charge shall be at the job site during all working hours. Failure to maintain the public right-of-way according to this condition may result in penalties and/or the Town performing the required maintenance at the Owner's expense
55. SITE DESIGN MEASURES: All projects shall incorporate at least one of the following measures:
- a. Protect sensitive areas and minimize changes to the natural topography.
 - b. Minimize impervious surface areas.
 - c. Direct roof downspouts to vegetated areas.
 - d. Use porous or pervious pavement surfaces on the driveway, at a minimum.
 - e. Use landscaping to treat stormwater.

56. CONSTRUCTION HOURS: All improvements and construction activities, including the delivery of construction materials, labors, heavy equipment, supplies, etc., shall be limited to the hours of 8:00 a.m. to 6:00 p.m., weekdays and 9:00 a.m. to 4:00 p.m. Saturdays. The Town may authorize, on a case-by-case basis, alternate construction hours. The Owner, Applicant and/or Developer shall provide written notice twenty-four (24) hours in advance of modified construction hours. Approval of this request is at discretion of the Town.
57. CONSTRUCTION NOISE: Between the hours of 8:00 a.m. to 6:00 p.m., weekdays and 9:00 a.m. to 4:00 p.m. Saturdays, construction, alteration or repair activities shall be allowed. No individual piece of equipment shall produce a noise level exceeding eighty-five (85) dBA at twenty-five (25) feet from the source. If the device is located within a structure on the property, the measurement shall be made at distances as close to twenty-five (25) feet from the device as possible. The noise level at any point outside of the property plane shall not exceed eighty-five (85) dBA.
58. DELAYED/DEFERRED REPORTS AND REVIEWS: TLGPPW strongly recommend that reports requiring a peer review be submitted and completed prior to committee approval/building permit stage. Note that these reviews may require a design change by the applicant and/or additional studies. Applicants who chose to defer assume risk that required changes may send project back to planning stage.
59. WATER METER: Water meters currently in public right-of-way shall be relocated within the property in question, within 30" of the property line / the public right-of-way line. The Owner, Applicant and/or Developer shall repair and replace to existing Town standards any portion of concrete flatwork within said right-of-way that is damaged during this activity prior to issuance of a certificate of occupancy.
60. SANITARY SEWER CLEANOUT: Sanitary sewer cleanouts currently in public right-of-way shall be relocated within the property in question, within one (1) foot of the property line per West Valley Sanitation District Standard Drawing 3, or at a location specified by the Town. The Owner, Applicant and/or Developer shall repair and replace to existing Town standards any portion of concrete flatwork within said right-of-way that is damaged during this activity prior to issuance of a certificate of occupancy.
61. PRECONSTRUCTION MEETING: Prior to issuance of any grading or building permits or the commencement of any site work, the general contractor shall:
 - a. Along with the Owner, Applicant and/or Developer, setup a pre-construction meeting with Eric Christianson, Senior Public Works Inspector echristianson@losgatosca.gov (408) 354-6824 to discuss the project conditions of approval, working hours, site maintenance and other construction matters;
 - b. Acknowledge in writing that they have read and understand the project conditions of approval and will make certain that all project sub-contractors have read and understand them as well prior to commencing any work, and that a copy of the project conditions of approval will be posted on-site at all times during construction.
62. CONSTRUCTION VEHICLE PARKING: Construction vehicle parking within the public right-of-way will only be allowed if it does not cause access or safety problems as determined by the Town.
63. FOR PLANTERS: The Owner, Applicant and/or Developer shall apply for an encroachment permit for the proposed planters within the public sidewalk and/or Town's right-of-

way. The Owner, Applicant and/or Developer shall work with Parks and Public Works Department staff to arrive at a mutually agreeable solution that addresses safety and aesthetic issues. If no solution is reached, the vegetative screening requirement shall be waived. A Private Improvements in the Public Right-of-Way (formerly Indemnity) Agreement will be required if planters are proposed to be located within the Town's right-of-way. A copy of the recorded agreement shall be submitted to the Engineering Division of the Parks and Public Works Department prior to the issuance of any grading or building permits.

64. PRIVATE IMPROVEMENTS IN THE PUBLIC RIGHT-OF-WAY (INDEMNITY AGREEMENT): The property owner shall enter into an agreement with the Town for all existing and proposed private improvements within the Town's right-of-way. The Owner shall be solely responsible for maintaining the improvements in a good and safe condition at all times and shall indemnify the Town of Los Gatos. The agreement must be completed and accepted by the Director of Parks and Public Works, and subsequently recorded by the Town Clerk at the Santa Clara County Office of the Clerk-Recorder, prior to the issuance of any grading or building permits.
65. STREET/SIDEWALK CLOSURE: Any proposed blockage or partial closure of the street and/or sidewalk requires an encroachment permit. Special provisions such as limitations on works hours, protective enclosures, or other means to facilitate public access in a safe manner may be required.
66. GRADING PERMIT: A grading permit is required for all site grading and drainage work except for exemptions listed in Section 12.20.015 of The Code of the Town of Los Gatos (Grading Ordinance). All grading work taking place with this application and related applications /projects within a two year time period are considered eligible for the grading permit process and will be counted toward the quantities used in determining grading permit requirements. After the preceding Architecture and Site Application has been approved by the respective deciding body and the appeal period has passed, the grading permit application with grading plans and associated required materials shall be submitted via email to the PPW engineer assigned to the A&S review. Plan check fees (determined after initial submittal) shall be sent to the Engineering Division of the Parks and Public Works Department located at 41 Miles Avenue. Unless specifically allowed by the Director of Parks and Public Works, the grading permit will be issued concurrently with the building permit. The grading permit is for work outside the building footprint(s). Prior to Engineering signing off and closing out on the issued grading permit, the Owner's soils engineer shall verify, with a stamped and signed letter, that the grading activities were completed per plans and per the requirements as noted in the soils report. A separate building permit, issued by the Building Department, located at 110 E. Main Street, is needed for grading within the building footprint.
67. SECURITY OF PERFORMANCE: Prior to approval of the grading permit, the applicant shall provide security for the performance of the work described and delineated on the approved grading plans, encroachment plans and or public improvement plans. The form of security shall be one (1) or a combination of the following to be determined by the Town Engineer and subject to the approval of the Town Attorney

- Bond or bonds issued by one (1) or more duly authorized corporate sureties on a form approved by the Town.
 - Deposit, with the Town, money, negotiable bonds of the kind approved for securing deposits of public monies, or other instrument of credit from one (1) or more financial institutions subject to regulation by the State or Federal Government wherein such financial institution pledges funds are on deposit and guaranteed for payment.
68. DRIVEWAY: The driveway conform to existing pavement on National Avenue shall be constructed in a manner such that the existing drainage patterns will not be obstructed. The Owner, Applicant and/or Developer shall install a Town standard residential driveway approach. The new driveway approach shall be constructed per Town Standard Plans and must be completed and accepted by the Town before a Certificate of Occupancy for any new building can be issued. New concrete shall be free of stamps, logos, names, graffiti, etc. Any concrete identified that is displaying a stamp or equal shall be removed and replaced at the Contractor's sole expense and no additional compensation shall be allowed therefore.
69. CONSTRUCTION EASEMENT: Prior to the issuance of a grading or building permit, it shall be the sole responsibility of the Owner, Applicant and/or Developer to obtain any and all proposed or required easements and/or permissions necessary to perform the grading herein proposed. Proof of agreement/approval is required prior to the issuance of any Permit.
70. DRAINAGE STUDY: Prior to the issuance of any grading or building permits, the following drainage studies shall be submitted to and approved by the Town Engineer: a drainage study of the project including diversions, off-site areas that drain onto and/or through the project, and justification of any diversions; a drainage study evidencing that the proposed drainage patterns will not overload the existing storm drain facilities; and detailed drainage studies indicating how the project grading, in conjunction with the drainage conveyance systems (including applicable swales, channels, street flows, catch basins, storm drains, and flood water retarding) will allow building pads to be safe from inundation from rainfall runoff which may be expected from all storms up to and including the theoretical 100-year flood.
71. TREE REMOVAL: Copies of all necessary tree removal permits shall be provided prior to the issuance of a building permit. An arborist report may be necessary. Please contact Tammy Robnett-Illges, Engineering Administrative Assistant trobnett-illges@losgatosca.gov (408) 399-5771 for more information.
72. DEDICATIONS: The following shall be dedicated by separate instrument. The dedications shall be recorded before any grading or building permits are issued:
- a. A 10-foot street right-of-way shall be dedicated in fee.
 - b. A 5-foot Public Service Easement.
73. DEMOLITION: Within 60-days of the Development Review Committee approval action being final (i.e. after the 10-day appeal period and no requested appeals being submitted to the Town), the Property Owner shall record a Deed Restriction on each of the number (#) parcels in question which prohibits the recording of a Certificate of Compliance until one of the two (2) prerequisite actions occurs prior to the proposed recordation: 1) removal of any structures which cross lot/property lines or 2) the Property Owner successfully

obtaining an Architecture & Site approval from the Town of Los Gatos for the demolition of the existing house and construction of a replacement house.

74. IMPROVEMENT AGREEMENT: The Owner, Applicant and/or Developer shall enter into an agreement to construct public improvements in accordance with Town Code Section 24.40.020. The Owner, Applicant and/or Developer shall supply suitable securities for all public improvements that are part of the development in a form acceptable to the Town in the amount of 100% performance and 100% labor and materials prior to the issuance of any encroachment, grading or building permit. The Owner, Applicant and/or Developer shall provide two (2) copies of documents verifying the cost of the public improvements to the satisfaction of the Engineering Division of the Parks and Public Works Department. An electronic copy (PDF) of the executed agreement shall be submitted to the Engineering Division of the Parks and Public Works Department prior to the issuance of any encroachment, grading or building permit.
75. JOINT TRENCH PLANS: Joint trench plans shall be reviewed and approved by the Town prior to recordation of a map. The joint trench plans shall include street and/or site lighting and associated photometrics. A letter shall be provided by PG&E stating that public street light billing will be by Rule LS2A, and that private lights shall be metered with billing to the homeowners' association. Pole numbers, assigned by PG&E, shall be clearly delineated on the plans.
76. PUBLIC IMPROVEMENTS: The following improvements shall be installed by the Owner and/or Applicant. Plans for those improvements shall be prepared by a California registered civil engineer, reviewed and approved by the Town, and guaranteed by contract, Faithful Performance Security and Labor & Materials Security before the issuance of any grading or building permits or the recordation of a map. The improvements must be completed and accepted by the Town before a Certificate of Occupancy for any new building can be issued.
 - a. National Avenue: New curb, gutter, sidewalk, streetlights, tie-in paving, signing, striping, utility pole relocation, as required.
 - b. National Ave: 2" overlay from the centerline to the edge of pavement, or alternative pavement restoration measure as approved by the Town Engineer.
77. CERTIFICATE OF OCCUPANCY: The Engineering Division of the Parks and Public Works Department will not sign off on a Temporary Certificate of Occupancy or a Final Certificate of Occupancy until all required improvements within the Town's right-of-way have been completed and approved by the Town.
78. FRONTAGE IMPROVEMENTS: The Owner and/or Applicant shall be required to improve the project's public frontage (right-of-way line to centerline and/or to limits per the direction of the Town Engineer) to current Town Standards. These improvements may include but not limited to curb, gutter, sidewalk, driveway approach(es), curb ramp(s), signs, pavement, raised pavement markers, thermoplastic pavement markings, storm drain facilities, traffic signal(s), street lighting (upgrade and/or repaint) etc. The improvements must be completed and accepted by the Town before a Certificate of Occupancy for any new building can be issued.
79. PARKING LOTS: Parking lots and other impervious areas shall be designed to drain stormwater runoff to vegetated drainage swales, filter strips, and/or other Low Impact Development (LID) treatment devices that can be integrated into required landscaping

areas and traffic islands prior to discharge into the storm drain system and/or public right-of-way. The amount of impervious area associated with parking lots shall be minimized by utilizing design features such as providing compact car spaces, reducing stall dimensions, incorporating efficient parking lanes, using permeable pavement where feasible, and adhering to the Town's [Parking Development Standards](#). The use of permeable paving for parking surfaces is encouraged to reduce runoff from the site. Such paving shall meet Santa Clara County Fire Department requirements and be structurally appropriate for the location.

80. UTILITIES: The Owner, Applicant and/or Developer shall install all new, relocated, or temporarily removed utility services, including telephone, electric power and all other communications lines underground, as required by Town Code Section 27.50.015(b). All new utility services shall be placed underground. Underground conduit shall be provided for cable television service. The Owner, Applicant and/or Developer is required to obtain approval of all proposed utility alignments from any and all utility service providers before a Certificate of Occupancy for any new building can be issued. The Town of Los Gatos does not approve or imply approval for final alignment or design of these facilities.
81. TRENCHING MORATORIUM: Trenching within a newly paved street will be allowed subject to the following requirements:
 - a. The Town standard "T" trench detail shall be used.
 - b. A Town-approved colored controlled density backfill shall be used.
 - c. All necessary utility trenches and related pavement cuts shall be consolidated to minimize the impacted area of the roadway.
 - d. The total asphalt thickness shall be a minimum of three (3) inches, meet Town standards, or shall match the existing thickness, whichever is greater. The final lift shall be 1.5-inches of one-half ($\frac{1}{2}$) inch medium asphalt. The initial lift(s) shall be of three-quarter ($\frac{3}{4}$) inch medium asphalt.
 - e. The Contractor shall schedule a pre-paving meeting with the Town Engineering Construction Inspector the day the paving is to take place.
 - f. A slurry seal topping may be required by the construction inspector depending their assessment of the quality of the trench paving. If required, the slurry seal shall extend the full width of the street and shall extend five (5) feet beyond the longitudinal limits of trenching. Slurry seal materials shall be approved by the Town Engineering Construction Inspector prior to placement. Black sand may be required in the slurry mix. All existing striping and pavement markings shall be replaced upon completion of slurry seal operations. All pavement restorations shall be completed and approved by the Inspector before occupancy.
82. VALLEY GUTTER REPAIR: The Owner/Applicant shall repair and replace to existing Town standards any valley gutter damaged now or during construction of this project. All new and existing adjacent infrastructure must meet Town standards. New valley gutter shall be constructed per Town Standard Details. New concrete shall be free of stamps, logos, names, graffiti, etc. Any concrete identified that is displaying a stamp or equal shall be removed and replaced at the Contractor's sole expense and no additional compensation shall be allowed therefore. The limits of valley gutter repair will be determined by the Engineering Construction Inspector during the construction phase of the project. The improvements

must be completed and accepted by the Town before a Certificate of Occupancy for any new building can be issued.

83. BICYCLE FACILITIES: Bicycle facilities including, but may not be limited to, bike lanes and bike boxes will be provided in all directions and approaches of improved streets and intersections as directed by Town Engineer.
84. TRAFFIC STUDY: Any development of land use that generates greater traffic impacts than those assumed in the traffic study report may require an updated traffic study in accordance with the Town's traffic impact policy. Applicant can receive proposals from vendors through the Town or submit studies from other consultants and pay for peer review. For more information please contact Mike Vroman, Senior Traffic Engineer MVroman@losgatosca.gov (408) 399-5777.
85. TRAFFIC IMPACT MITIGATION FEE: Prior to the issuance of any building or grading permits, the Owner shall pay the project's proportional share of transportation improvements needed to serve cumulative development within the Town of Los Gatos. The fee amount will be based upon the Town Council resolution in effect at the time the building permit is issued. The amount based on the current resolution is **\$10,457.76**.
86. HAULING OF SOIL: Hauling of soil on- or off-site shall not occur during the morning or evening peak periods (between 7:00 a.m. and 9:00 a.m. and between 4:00 p.m. and 6:00 p.m.), and at other times as specified by the Director of Parks and Public Works. Prior to the issuance of a grading or building permit, the Owner and/or Applicant or their representative shall work with the Town Building Department and Engineering Division Inspectors to devise a traffic control plan to ensure safe and efficient traffic flow under periods when soil is hauled on or off the project site. This may include, but is not limited to provisions for the Owner and/or Applicant to place construction notification signs noting the dates and time of construction and hauling activities, or providing additional traffic control. Coordination with other significant projects in the area may also be required. Cover all trucks hauling soil, sand and other loose debris.
87. CONSTRUCTION MANAGEMENT PLAN SHEET: Prior to the issuance of any grading or building permits, the Owner and/or Applicant's design consultant shall submit a construction management plan sheet (full-size) within the plan set that shall incorporate at a minimum the Earth Movement Plan, Traffic Control Plan, Project Schedule, site security fencing, employee parking, construction staging area, materials storage area(s), construction trailer(s), concrete washout(s) and proposed outhouse locations. Please refer to the Town's [Construction Management Plan Guidelines](#) document for additional information.
88. NPDES STORMWATER COMPLIANCE: In the event that, during the production of construction drawings for the plans approved with this application by the Town of Los Gatos, it is determined that the project will create and/or replace more than 2,500 square feet of impervious area, completion of the NPDES Stormwater Compliance Small Projects Worksheet and implementation of at least one of the six low impact development site design measures it specifies shall be completed and submitted to the Engineering Division before issuance of a grading/building permit.
89. EROSION CONTROL: Interim and final erosion control plans shall be prepared and submitted to the Engineering Division of the Parks and Public Works Department. A

maximum of two (2) weeks is allowed between clearing of an area and stabilizing/building on an area if grading is allowed during the rainy season. Interim erosion control measures, to be carried out during construction and before installation of the final landscaping, shall be included. Interim erosion control method shall include, but are not limited to: silt fences, fiber rolls (with locations and details), erosion control blankets, Town standard seeding specification, filter berms, check dams, retention basins, etc. Provide erosion control measures as needed to protect downstream water quality during winter months. The Town of Los Gatos Engineering Division of the Parks and Public Works Department and the Building Department will conduct periodic NPDES inspections of the site throughout the recognized storm season to verify compliance with the Construction General Permit and Stormwater ordinances and regulations.

90. AIR QUALITY: To limit the project's construction-related dust and criteria pollutant emissions, the following the Bay Area Air Quality Management District (BAAQMD)-recommended basic construction measures shall be included in the project's grading plan, building plans, and contract specifications:

- All exposed surfaces (e.g., parking areas, staging areas, soil piles, graded areas, and unpaved access roads) shall be watered two times per day, or otherwise kept dust-free.
- All haul trucks designated for removal of excavated soil and demolition debris from site shall be staged off-site until materials are ready for immediate loading and removal from site.
- All haul trucks transporting soil, sand, debris, or other loose material off-site shall be covered.
- As practicable, all haul trucks and other large construction equipment shall be staged in areas away from the adjacent residential homes.
- All visible mud or dirt track-out onto adjacent public roads shall be removed using wet power vacuum street sweepers at least once per day, or as deemed appropriate by Town Engineer. The use of dry power sweeping is prohibited. An on-site track-out control device is also recommended to minimize mud and dirt-track-out onto adjacent public roads.
- All vehicle speeds on unpaved surfaces shall be limited to fifteen (15) miles per hour.
- All driveways and sidewalks to be paved shall be completed as soon as possible. Building pads shall be laid as soon as possible after grading unless seeding or soil binders are used.
- Post a publicly visible sign with the telephone number and person to contact at the lead agency regarding dust complaints. This person shall respond and take corrective action within forty-eight (48) hours. The Air District's phone number shall also be visible to ensure compliance with applicable regulations. Please provide the BAAQMD's complaint number on the sign: 24-hour toll-free hotline at 1-800-334-ODOR (6367).
- All excavation, grading, and/or demolition activities shall be suspended when average wind speeds exceed twenty (20) miles per hour.
- Vegetative ground cover (e.g., fast-germinating native grass seed) shall be planted in disturbed areas as soon as possible and watered appropriately until vegetation is established.

91. **SITE DRAINAGE:** Rainwater leaders shall be discharged to splash blocks. No through curb drains will be allowed. On-site drainage systems for all projects shall include one of the alternatives included in section C.3.i of the Municipal Regional NPDES Permit. These include storm water reuse via cisterns or rain barrels, directing runoff from impervious surfaces to vegetated areas and use of permeable surfaces. If stormwater treatment facilities are to be used they shall be placed a minimum of ten (10) feet from the adjacent property line and/or right-of-way. Alternatively, the facility(ies) may be located with an offset between 5 and 10 feet from the adjacent property and/or right-of-way line(s) if the responsible engineer in charge provides a stamped and signed letter that addresses infiltration and states how facilities, improvements and infrastructure within the Town's right-of-way (driveway approach, curb and gutter, etc.) and/or the adjacent property will not be adversely affected. No improvements shall obstruct or divert runoff to the detriment of an adjacent, downstream or down slope property.

TO THE SATISFACTION OF THE SANTA CLARA COUNTY FIRE DEPARTMENT:

92. **GENERAL REVIEW:** Review of this Developmental proposal is limited to acceptability of site access, water supply and may include specific additional requirements as they pertain to fire department operations, and shall not be construed as a substitute for formal plan review to determine compliance with adopted model codes. Prior to performing any work, the applicant shall make application to, and receive from, the Building Department all applicable construction permits.
93. **FIRE SPRINKLERS REQUIRED:** (As Noted on Sheet CS) Approved automatic sprinkler systems in new and existing buildings and structures shall be provided in the locations described in this Section or in Sections 903.2.1 through 903.2.12 whichever is the more restrictive and Sections 903.2.14 through 903.2.21. For the purposes of this section, firewalls and fire barriers used to separate building areas shall be constructed in accordance with the California Building Code and shall be without openings or penetrations. 1. An automatic sprinkler system shall be provided throughout all new buildings and structures, other than Group R occupancies, except as follows: a. Buildings and structures not located in any Wildland-Urban Interface and not exceeding 1,200 square feet of fire area. b. Buildings and structures located in any Wildland-Urban Interface Fire Area and not exceeding 500 square feet of fire area. c. Group S-2 or U occupancies, including photovoltaic support structures, used exclusively for vehicle parking which meet all of the following: i. Noncombustible construction. ii. Maximum 5,000 square feet in building area. iii. Structure is open on not less than three (3) sides nor 75% of structure perimeter. iv. Minimum of 10 feet separation from existing buildings, or similar structures, unless area is separated by fire walls complying.
94. **WATER SUPPLY REQUIREMENTS:** Potable water supplies shall be protected from contamination caused by fire protection water supplies. It is the responsibility of the applicant and any contractors and subcontractors to contact the water purveyor supplying the site of such project, and to comply with the requirements of that purveyor. Such

requirements shall be incorporated into the design of any water-based fire protection systems, and/or fire suppression water supply systems or storage containers that may be physically connected in any manner to an appliance capable of causing contamination of the potable water supply of the purveyor of record. Final approval of the system(s) under consideration will not be granted by this office until compliance with the requirements of the water purveyor of record are documented by that purveyor as having been met by the applicant(s). 2019 CFC Sec. 903.3.5 and Health and Safety Code 13114.7.

95. ADDRESS IDENTIFICATION: New and existing buildings shall have approved address numbers, building numbers or approved building identification placed in a position that is plainly legible and visible from the street or road fronting the property. These numbers shall contrast with their background. Where required by the fire code official, address numbers shall be provided in additional approved locations to facilitate emergency response. Address numbers shall be Arabic numbers or alphabetical letters. Numbers shall be a minimum of 4 inches (101.6 mm) high with a minimum stroke width of 0.5 inch (12.7 mm). Where access is by means of a private road and the building cannot be viewed from the public way, a monument, pole or other sign or means shall be used to identify the structure. Address numbers shall be maintained. CFC Sec. 505.1.
96. CONSTRUCTION SITE FIRE SAFETY: All construction sites must comply with applicable provisions of the CFC Chapter 33 and our Standard Detail and Specification S1-7. Provide appropriate notations on subsequent plan submittals, as appropriate to the project. CFC Chp. 33.
97. FIRE APPARATUS (ENGINE)ACCESS DRIVEWAY REQUIRED: An access driveway shall be provided having an all-weather surface of either asphalt, concrete or other engineered surface capable of supporting 75,000 pounds and approved by a civil engineer. It shall have a minimum unobstructed width of 12 feet, vertical clearance of 13 feet 6 inches, minimum turning radius of 40 feet outside, and a maximum slope of 15%. Installations shall conform to Fire Department Standard Details and Specifications sheet D-1.
98. This review shall not be construed to be an approval of a violation of the provisions of the California Fire Code or of other laws or regulations of the jurisdiction. A permit presuming to give authority to violate or cancel the provisions of the fire code or other such laws or regulations shall not be valid. Any addition to or alteration of approved construction documents shall be approved in advance. [CFC, Ch.1, 105.3.6]

