PLANNING COMMISSION – *August 23, 2023* **CONDITIONS OF APPROVAL**

232 Danville Drive

Architecture and Site Application S-22-041

Requesting Approval for Demolition of an Existing Single-Family Residence and Construction of a New Single-Family Residence Requiring a Grading Permit on Property Zoned R-1:8. Located at 232 Danville Drive. APN 523-43-035. Categorically Exempt Pursuant to the California Environmental Quality Act, Section 15303: New Construction or Conversion of Small Structures.

PROPERTY OWNER: Cung Pham and Bien Vo. APPLICANT: D&Z Design Associates, Inc. PROJECT PLANNER: Savannah Van Akin.

TO THE SATISFACTION OF THE DIRECTOR OF COMMUNITY DEVELOPMENT:

Planning Division

- APPROVAL: This application shall be completed in accordance with all of the conditions of approval and in substantial compliance with the approved plans. Any changes or modifications to the approved plans and/or business operation shall be approved by the Community Development Director, DRC, or the Planning Commission depending on the scope of the changes.
- 2. EXPIRATION: The approval will expire two years from the approval date pursuant to Section 29.20.320 of the Town Code, unless the approval has been vested.
- 3. OUTDOOR LIGHTING: Exterior lighting shall be kept to a minimum, and shall be down directed fixtures that will not reflect or encroach onto adjacent properties. No flood lights shall be used unless it can be demonstrated that they are needed for safety or security.
- 4. TREE REMOVAL PERMIT: A Tree Removal Permit shall be obtained for any trees to be removed, prior to the issuance of a building or grading permit.
- 5. EXISTING TREES: All existing trees shown on the plan and trees required to remain or to be planted are specific subjects of approval of this plan, and must remain on the site.
- 6. ARBORIST REQUIREMENTS: The developer shall implement, at their cost, all recommendations identified in the Arborist's report for the project, on file in the Community Development Department. These recommendations must be incorporated in the building permit plans and completed prior to issuance of a building permit where applicable.
- 7. TREE FENCING: Protective tree fencing and other protection measures shall be placed at the drip line of existing trees prior to issuance of demolition and building permits and shall remain through all phases of construction. Include a tree protection plan with the construction plans.
- 8. TREE STAKING: All newly planted trees shall be double-staked using rubber tree ties.
- 9. FRONT YARD LANDSCAPE: Prior to issuance of a Certificate of Occupancy the front yard must be landscaped.

- 10. WATER EFFICIENCY LANDSCAPE ORDINANCE: The final landscape plan shall meet the Town of Los Gatos Water Conservation Ordinance or the State Water Efficient Landscape Ordinance, whichever is more restrictive. A review fee based on the current fee schedule adopted by the Town Council is required when working landscape and irrigation plans are submitted for review.
- 11. STORY POLES: The story poles on the project site shall be removed within 30 days of approval of the Architecture & Site application.
- 12. TOWN INDEMNITY: Applicants are notified that Town Code Section 1.10.115 requires that any applicant who receives a permit or entitlement ("the Project") from the Town shall defend (with counsel approved by Town), indemnify, and hold harmless the Town, its agents, officers, and employees from and against any claim, action, or proceeding (including without limitation any appeal or petition for review thereof) against the Town or its agents, officers or employees related to an approval of the Project, including without limitation any related application, permit, certification, condition, environmental determination, other approval, compliance or failure to comply with applicable laws and regulations, and/or processing methods ("Challenge"). Town may (but is not obligated to) defend such Challenge as Town, in its sole discretion, determines appropriate, all at applicant's sole cost and expense.

Applicant shall bear any and all losses, damages, injuries, liabilities, costs and expenses (including, without limitation, staff time and in-house attorney's fees on a fully-loaded basis, attorney's fees for outside legal counsel, expert witness fees, court costs, and other litigation expenses) arising out of or related to any Challenge ("Costs"), whether incurred by Applicant, Town, or awarded to any third party, and shall pay to the Town upon demand any Costs incurred by the Town. No modification of the Project, any application, permit certification, condition, environmental determination, other approval, change in applicable laws and regulations, or change in such Challenge as Town, in its sole discretion, determines appropriate, all the applicant's sole cost and expense. No modification of the Project, any application, permit certification, condition, environmental determination, other approval, change in applicable laws and regulations, or change in processing methods shall alter the applicant's indemnity obligation.

13. COMPLIANCE MEMORANDUM: A memorandum shall be prepared and submitted with the building plans detailing how the Conditions of Approval will be addressed.

Building Division

- 14. PERMITS REQUIRED: A Demolition Permit is required for the demolition of the existing commercial building. A separate Building Permit is required for the construction of the new commercial building and renovation of the remaining commercial building.
- 15. APPLICABLE CODES: The current codes, as amended and adopted by the Town of Los Gatos as of January 1, 2023, are the 2022 California Building Standards Code, California Code of Regulations Title 24, Parts 1-12, including locally adopted Energy Reach Codes.
- 16. CONDITIONS OF APPROVAL: The Conditions of Approval must be blue lined in full on the cover sheet of the construction plans. A Compliance Memorandum shall be prepared and submitted with the building permit application detailing how the Conditions of Approval will be addressed.

- 17. BUILDING & SUITE NUMBERS: Submit requests for new building addresses to the Building Division prior to submitting for the building permit application process.
- 18. SIZE OF PLANS: Minimum size 24" x 36", maximum size 30" x 42".
- 19. REQUIREMENTS FOR COMPLETE DEMOLITION OF STRUCTURE: Obtain a Building Department Demolition Application and a Bay Area Air Quality Management District Application from the Building Department Service Counter. Once the demolition form has been completed, all signatures obtained, and written verification from PG&E that all utilities have been disconnected, return the completed form to the Building Department Service Counter with the Air District's J# Certificate, PG&E verification, and three (3) sets of site plans showing all existing structures, existing utility service lines such as water, sewer, and PG&E. No demolition work shall be done without first obtaining a permit from the Town.
- 20. SOILS REPORT: A Soils Report, prepared to the satisfaction of the Building Official, containing foundation, and retaining wall design recommendations, shall be submitted with the Building Permit Application. This report shall be prepared by a licensed Civil Engineer specializing in soils mechanics.
- 21. SHORING: Shoring plans and calculations will be required for all excavations which exceed five (5) feet in depth, or which remove lateral support from any existing building, adjacent property, or the public right-of-way. Shoring plans and calculations shall be prepared by a California licensed engineer and shall confirm to the Cal/OSHA regulations.
- 22. FOUNDATION INSPECTIONS: A pad certificate prepared by a licensed civil engineer or land surveyor shall be submitted to the project Building Inspector at foundation inspection. This certificate shall certify compliance with the recommendations as specified in the Soils Report, and that the building pad elevations and on-site retaining wall locations and elevations have been prepared according to the approved plans. Horizontal and vertical controls shall be set and certified by a licensed surveyor or registered Civil Engineer for the following items:
 - a. Building pad elevation
 - b. Finish floor elevation
 - c. Foundation corner locations
 - d. Retaining wall(s) locations and elevations
- 23. TITLE 24 ENERGY COMPLIANCE: All required California Title 24 Energy Compliance Forms must be blue-lined (sticky-backed), i.e., directly printed, onto a plan sheet.
- 24. SITE ACCESSIBILITY: At least one accessible route within the boundary of the site shall be provided from public transportation stops, accessible parking and accessible passenger loading zones and public streets or sidewalks to the accessible building entrance that they serve. The accessible route shall, to the maximum extent feasible, coincide with the route for the general public. At least one accessible route shall connect all accessible buildings, facilities, elements, and spaces that are on the same site.
- 25. ACCESSIBLE PARKING: The parking lots where parking is provided for the public as clients, guests or employees, shall provide accessible parking. Accessible parking spaces serving a particular building shall be located on the shortest accessible route of travel from adjacent parking to an accessible entrance. In buildings with multiple accessible entrances with adjacent parking, accessible parking spaces shall be dispersed and located closest to the accessible entrances.
- 26. BACKWATER VALVE: The scope of this project may require the installation of a sanitary

- sewer backwater valve per Town Ordinance 6.50.025. Please provide information on the plans if a backwater valve is required and the location of the installation. The Town of Los Gatos Ordinance and West Valley Sanitation District (WVSD) requires backwater valves on drainage piping serving fixtures that have flood level rims less than 12 inches above the elevation of the next upstream manhole.
- 27. HAZARDOUS FIRE ZONE: All projects in the Town of Los Gatos require Class A roof assemblies.
- 28. SPECIAL INSPECTIONS: When a special inspection is required by CBC Section 1704, the Architect or Engineer of Record shall prepare an inspection program that shall be submitted to the Building Official for approval prior to issuance of the Building Permit. The Town Special Inspection form must be completely filled-out and signed by all requested parties prior to permit issuance. Special Inspection forms are available online at www.losgatosca.gov/building.
- 29. BLUEPRINT FOR A CLEAN BAY SHEET: The Town standard Santa Clara Valley Nonpoint Source Pollution Control Program Sheet (page size same as submitted drawings) shall be part of the plan submittal as the second page. The specification sheet is available online at www.losgatosca.gov/building.
- 30. APPROVALS REQUIRED: The project requires the following departments and agencies approval before issuing a building permit:

Community Development – Planning Division: (408) 354-6874 Engineering/Parks & Public Works Department: (408) 399-5771

Santa Clara County Fire Department: (408) 378-4010

West Valley Sanitation District: (408) 378-2407

Local School District: The Town will forward the paperwork to the appropriate school district(s) for processing. A copy of the paid receipt is required prior to permit issuance.

TO THE SATISFACTION OF THE DIRECTOR OF PARKS & PUBLIC WORKS:

Engineering Division

- 31. GENERAL: All public improvements shall be made according to the latest adopted Town Standard Plans, Standard Specifications and Engineering Design Standards. All work shall conform to the applicable Town ordinances. The adjacent public right-of-way shall be kept clear of all job-related mud, silt, concrete, dirt and other construction debris at the end of the day. Dirt and debris shall not be washed into storm drainage facilities. The storing of goods and materials on the sidewalk and/or the street will not be allowed unless an encroachment permit is issued by the Engineering Division of the Parks and Public Works Department. The Owner's representative in charge shall be at the job site during all working hours. Failure to maintain the public right-of-way according to this condition may result in the issuance of correction notices, citations, or stop work orders and the Town performing the required maintenance at the Owner's expense.
- 32. APPROVAL: This application shall be completed in accordance with all the conditions of approval listed below and in substantial compliance with the latest reviewed and approved development plans. Any changes or modifications to the approved plans or conditions of approvals shall be approved by the Town Engineer.

- 33. CONSTRUCTION PLAN REQUIREMENTS: Construction drawings shall comply with Section 1 (Construction Plan Requirements) of the Town's Engineering Design Standards, which are available for download from the Town's website.
- 34. PRIOR APPROVALS: All conditions per prior approvals shall be deemed in full force and affect for this approval.
- 35. ENCROACHMENT PERMIT: All work in the public right-of-way will require a Construction Encroachment Permit. All work over \$5,000 will require construction security. It is the responsibility of the Owner/Applicant/Developer to obtain any necessary encroachments permits from affected agencies and private parties, including but not limited to, Pacific Gas and Electric (PG&E), AT&T, Comcast, Santa Clara Valley Water District, California Department of Transportation (Caltrans). Copies of any approvals or permits must be submitted to the Town Engineering Division of the Parks and Public Works Department prior to releasing any permit.
- 36. PRIVATE IMPROVEMENTS IN THE PUBLIC RIGHT-OF-WAY (INDEMNITY AGREEMENT): The property owner shall enter into an agreement with the Town for all existing and proposed private improvements within the Town's right-of-way. The Owner shall be solely responsible for maintaining the improvements in a good and safe condition at all times and shall indemnify the Town of Los Gatos. The agreement must be completed and accepted by the Director of Parks and Public Works, and subsequently recorded by the Town Clerk at the Santa Clara County Office of the Clerk-Recorder, prior to the issuance of any grading or building permits. Please note that this process may take approximately six to eight (6-8) weeks.
- 37. GENERAL LIABILITY INSURANCE: The property owner shall provide proof of insurance to the Town on a yearly basis. In addition to general coverage, the policy must cover all elements encroaching into the Town's right-of-way.
- 38. PUBLIC WORKS INSPECTIONS: The Owner or their representative shall notify the Engineering Inspector at least twenty-four (24) hours before starting any work pertaining to on-site drainage facilities, grading or paving, and all work in the Town's right-of-way. Failure to do so will result in penalties and rejection of any work that occurred without inspection.
- 39. RESTORATION OF PUBLIC IMPROVEMENTS: The Owner and/or Developer or their representative shall repair or replace all existing improvements not designated for removal that are damaged or removed because of the Owner and/or Developer or their representative's operations. Improvements such as, but not limited to: curbs, gutters, sidewalks, driveways, signs, pavements, raised pavement markers, thermoplastic pavement markings, etc., shall be repaired and replaced to a condition equal to or better than the original condition. Any new concrete shall be free of stamps, logos, names, graffiti, etc. Any concrete identified that is displaying a stamp or equal shall be removed and replaced at the Contractor's sole expense and no additional compensation shall be allowed therefore. Existing improvement to be repaired or replaced shall be at the direction of the Engineering Construction Inspector and shall comply with all Title 24 Disabled Access provisions. The restoration of all improvements identified by the Engineering Construction Inspector shall be completed before the issuance of a certificate of occupancy. The Owner and/or Developer or their representative shall request a walk-through with the Engineering Construction Inspector before the start of construction to verify existing conditions.

- 40. SITE SUPERVISION: The General Contractor shall provide qualified supervision on the job site at all times during construction.
- 41. STREET/SIDEWALK CLOSURE: Any proposed blockage or partial closure of the street and/or sidewalk requires an encroachment permit. Special provisions such as limitations on works hours, protective enclosures, or other means to facilitate public access in a safe manner may be required.
- 42. PLAN CHECK FEES: Plan check fees associated with the Grading Permit shall be deposited with the Engineering Division of the Parks and Public Works Department prior to the commencement of plan check review.
- 43. INSPECTION FEES: Inspection fees shall be deposited with the Town prior to the issuance of any grading or building permits or recordation of the Parcel / Final Map.
- 44. PUBLIC WORKS INSPECTOR: The Owner shall fund a full time public works inspector, selected by the Town of Los Gatos, for the duration of the demolition and grading operations. The Owner will be charged on a time and materials basis. A deposit for the full amount, to be estimated by the Town based on the Contractor's approved schedule, shall be paid prior to issuance of the demolition permit.
- 45. DESIGN CHANGES: Any proposed changes to the approved plans shall be subject to the approval of the Town prior to the commencement of any and all altered work. The Owner's project engineer shall notify, in writing, the Town Engineer at least seventy-two (72) hours in advance of all the proposed changes. Any approved changes shall be incorporated into the final "as-built" plans.
- 46. PLANS AND STUDIES: All required plans and studies shall be prepared by a Registered Professional Engineer in the State of California and submitted to the Town Engineer for review and approval. Additionally, any post-project traffic or parking counts, or other studies imposed by the Planning Commission or Town Council shall be funded by the Owner.
- 47. GRADING PERMIT DETERMINATION DURING CONSTRUCTION DRAWINGS: In the event that, during the production of construction drawings and/or during construction of the plans approved with this application by the Town of Los Gatos, it is determined that a grading permit would be required as described in Chapter 12, Article II (Grading Permit) of the Town Code of the Town of Los Gatos, an Architecture and Site Application would need to be submitted by the Owner/Applicant/Developer for review and approval by the Development Review Committee prior to applying for a grading permit.
- 48. ILLEGAL GRADING: Per the Town's Comprehensive Fee Schedule, applications for work unlawfully completed shall be charged double the current fee. As a result, the required grading permit fees associated with an application for grading will be charged accordingly.
- 49. DRIVEWAY: The driveway conform to existing pavement on Alta Heights Ct. shall be constructed in a manner such that the existing drainage patterns will not be obstructed.
- 50. CONSTRUCTION EASEMENT: Prior to the issuance of a grading or building permit, it shall be the sole responsibility of the Owner to obtain any and all proposed or required easements and/or permissions necessary to perform the grading herein proposed. Proof of agreement/approval is required prior to the issuance of any Permit.
- 51. TREE REMOVAL: Copies of all necessary tree removal permits shall be provided prior to the issuance of a grading permit/building permit.

- 52. WEST VALLEY SANITATION DISTRICT: All sewer connection and treatment plant capacity fees shall be paid either immediately prior to the recordation of any subdivision or tract maps with respect to the subject property or properties or immediately prior to the issuance of a sewer connection permit, which ever event occurs first. Written confirmation of payment of these fees shall be provided prior to map recordation.
- 53. DEMOLITION: Within 60-days of the approval action being final (i.e. after the 10-day appeal period and no requested appeals being submitted to the Town), the Property Owner shall record a Deed Restriction on each of the parcels in question which prohibits the recording of a Certificate of Compliance until one of the two (2) prerequisite actions occurs prior to the proposed recordation: 1) removal of any structures which cross lot/property lines or 2) the Property Owner successfully obtaining an Architecture & Site approval from the Town of Los Gatos for the demolition of the existing house and construction of a replacement house.
- 54. DRIVEWAY APPROACH: The Owner and/or Developer shall install a Town standard residential driveway approach. The new driveway approach shall be constructed per Town Standard Plans and must be completed and accepted by the Town before a Certificate of Occupancy for any new building can be issued. New concrete shall be free of stamps, logos, names, graffiti, etc. Any concrete identified that is displaying a stamp or equal shall be removed and replaced at the Contractor's sole expense and no additional compensation shall be allowed therefore.
- 55. FENCING: Any fencing proposed within two hundred (200) feet of an intersection shall comply with Town Code Section §23.10.080.
- 56. SIGHT TRIANGLE AND TRAFFIC VIEW AREA: Any proposed improvements, including but not limiting to trees and hedges, will need to abide by Town Code Sections 23.10.080, 26.10.065, and 29.40.030.
- 57. FENCES: Fences between all adjacent parcels will need to be located on the property lines/boundary lines. Any existing fences that encroach into the neighbor's property will need to be removed and replaced to the correct location of the boundary lines before a Certificate of Occupancy for any new building can be issued. Waiver of this condition will require signed and notarized letters from all affected neighbors.
- 58. CONSTRUCTION VEHICLE PARKING: Construction vehicle parking within the public right-of-way will only be allowed if it does not cause access or safety problems as determined by the Town.
- 59. ADVANCE NOTIFICATION: Advance notification of all affected residents and emergency services shall be made regarding parking restriction, lane closure or road closure, with specification of dates and hours of operation.
- 60. HAULING OF SOIL: Hauling of soil on- or off-site shall not occur during the morning or evening peak periods (between 7:00 a.m. and 9:00 a.m. and between 4:00 p.m. and 6:00 p.m.), and at other times as specified by the Director of Parks and Public Works. Prior to the issuance of a grading or building permit, the Owner and/or Applicant or their representative shall work with the Town Building Department and Engineering Division Inspectors to devise a traffic control plan to ensure safe and efficient traffic flow under periods when soil is hauled on or off the project site. This may include, but is not limited to provisions for the Owner and/or Applicant to place construction notification signs noting the dates and time of construction and hauling activities, or providing additional traffic control. Coordination

- with other significant projects in the area may also be required. Cover all trucks hauling soil, sand and other loose debris.
- 61. CONSTRUCTION HOURS: All subdivision improvements and site improvements construction activities, including the delivery of construction materials, labors, heavy equipment, supplies, etc., shall be limited to the hours of 8:00 a.m. to 8:00 p.m., weekdays and 9:00 a.m. to 7:00 p.m. weekends and holidays. The Town may authorize, on a case-by-case basis, alternate construction hours. The Owner and/or Developer shall provide written notice twenty-four (24) hours in advance of modified construction hours. Approval of this request is at discretion of the Town.
- 62. CONSTRUCTION NOISE: Between the hours of 8:00 a.m. to 8:00 p.m., weekdays and 9:00 a.m. to 7:00 p.m. weekends and holidays, construction, alteration or repair activities shall be allowed. No individual piece of equipment shall produce a noise level exceeding eighty-five (85) dBA at twenty-five (25) feet from the source. If the device is located within a structure on the property, the measurement shall be made at distances as close to twenty-five (25) feet from the device as possible. The noise level at any point outside of the property plane shall not exceed eighty-five (85) dBA.
- 63. CONSTRUCTION MANAGEMENT PLAN SHEET: Prior to the issuance of any grading or building permits, the Owner and/or Applicant's design consultant shall submit a construction management plan sheet (full-size) within the plan set that shall incorporate at a minimum the Earth Movement Plan, Traffic Control Plan, Project Schedule, site security fencing, employee parking, construction staging area, materials storage area(s), construction trailer(s), concrete washout(s) and proposed outhouse locations. Please refer to the Town's Construction Management Plan Guidelines document for additional information.
- 64. BEST MANAGEMENT PRACTICES (BMPs): The Owner and/or Developer is responsible for ensuring that all contractors are aware of all storm water quality measures and that such measures are implemented. Best Management Practices (BMPs) shall be maintained and be placed for all areas that have been graded or disturbed and for all material, equipment and/or operations that need protection. Removal of BMPs (temporary removal during construction activities) shall be replaced at the end of each working day. Failure to comply with the construction BMP will result in the issuance of correction notices, citations, or stop work orders.
- 65. NPDES STORMWATER COMPLIANCE: In the event that, during the production of construction drawings for the plans approved with this application by the Town of Los Gatos, it is determined that the project will create and/or replace more than 2,500 square feet of impervious area, completion of the NPDES Stormwater Compliance Small Projects Worksheet and implementation of at least one of the six low impact development site design measures it specifies shall be completed and submitted to the Engineering Division before issuance of a grading/building permit.
- 66. SITE DESIGN MEASURES: All projects shall incorporate at least one of the following measures:
 - a. Protect sensitive areas and minimize changes to the natural topography.
 - b. Minimize impervious surface areas.
 - c. Direct roof downspouts to vegetated areas.
 - d. Use porous or pervious pavement surfaces on the driveway, at a minimum.

- e. Use landscaping to treat stormwater.
- 67. EROSION CONTROL: Interim and final erosion control plans shall be prepared and submitted to the Engineering Division of the Parks and Public Works Department. A maximum of two (2) weeks is allowed between clearing of an area and stabilizing/building on an area if grading is allowed during the rainy season. Interim erosion control measures, to be carried out during construction and before installation of the final landscaping, shall be included. Interim erosion control method shall include, but are not limited to: silt fences, fiber rolls (with locations and details), erosion control blankets, Town standard seeding specification, filter berms, check dams, retention basins, etc. Provide erosion control measures as needed to protect downstream water quality during winter months. The Town of Los Gatos Engineering Division of the Parks and Public Works Department and the Building Department will conduct periodic NPDES inspections of the site throughout the recognized storm season to verify compliance with the Construction General Permit and Stormwater ordinances and regulations.
- 68. DUST CONTROL: Blowing dust shall be reduced by timing construction activities so that paving and building construction begin as soon as possible after completion of grading, and by landscaping disturbed soils as soon as possible. Further, water trucks shall be present and in use at the construction site. All portions of the site subject to blowing dust shall be watered as often as deemed necessary by the Town, or a minimum of three (3) times daily, or apply (non-toxic) soil stabilizers on all unpaved access roads, parking areas, and staging areas at construction sites in order to insure proper control of blowing dust for the duration of the project. Watering on public streets shall not occur. Streets shall be cleaned by street sweepers or by hand as often as deemed necessary by the Town Engineer, or at least once a day. Watering associated with on-site construction activity shall take place between the hours of 8 a.m. and 5 p.m. and shall include at least one (1) late-afternoon watering to minimize the effects of blowing dust. All public streets soiled or littered due to this construction activity shall be cleaned and swept on a daily basis during the workweek to the satisfaction of the Town. Demolition or earthwork activities shall be halted when wind speeds (instantaneous gusts) exceed twenty (20) miles per hour (MPH). All trucks hauling soil, sand, or other loose debris shall be covered.
- 69. AIR QUALITY: To limit the project's construction-related dust and criteria pollutant emissions, the following the Bay Area Air Quality Management District (BAAQMD)-recommended basic construction measures shall be included in the project's grading plan, building plans, and contract specifications:
 - a. All exposed surfaces (e.g., parking areas, staging areas, soil piles, graded areas, and unpaved access roads) shall be watered two times per day, or otherwise kept dust-free
 - b. All haul trucks designated for removal of excavated soil and demolition debris from site shall be staged off-site until materials are ready for immediate loading and removal from site.
 - c. All haul trucks transporting soil, sand, debris, or other loose material off-site shall be covered.
 - d. As practicable, all haul trucks and other large construction equipment shall be staged in areas away from the adjacent residential homes.

- e. All visible mud or dirt track-out onto adjacent public roads shall be removed using wet power vacuum street sweepers at least once per day, or as deemed appropriate by Town Engineer. The use of dry power sweeping is prohibited. An on-site trackout control device is also recommended to minimize mud and dirt-track-out onto adjacent public roads.
- f. All vehicle speeds on unpaved surfaces shall be limited to fifteen (15) miles per hour.
- g. All driveways and sidewalks to be paved shall be completed as soon as possible. Building pads shall be laid as soon as possible after grading unless seeding or soil binders are used.
- h. Post a publicly visible sign with the telephone number and person to contact at the lead agency regarding dust complaints. This person shall respond and take corrective action within forty-eight (48) hours. The Air District's phone number shall also be visible to ensure compliance with applicable regulations. Please provide the BAAQMD's complaint number on the sign: 24-hour toll-free hotline at 1-800-334-ODOR (6367).
- i. All excavation, grading, and/or demolition activities shall be suspended when average wind speeds exceed twenty (20) miles per hour.
- Vegetative ground cover (e.g., fast-germinating native grass seed) shall be planted in disturbed areas as soon as possible and watered appropriately until vegetation is established.
- 70. DETAILING OF STORMWATER MANAGEMENT FACILITIES: Prior to the issuance of any grading or building permits, all pertinent details of any and all proposed stormwater management facilities, including, but not limited to, ditches, swales, pipes, bubble-ups, dry wells, outfalls, infiltration trenches, detention basins and energy dissipaters, shall be provided on submitted plans, reviewed by the Engineering Division of the Parks and Public Works Department, and approved for implementation.
- 71. CONSTRUCTION ACTIVITIES: All construction shall conform to the latest requirements of the CASQA Stormwater Best Management Practices Handbooks for Construction Activities and New Development and Redevelopment, the Town's grading and erosion control ordinance, and other generally accepted engineering practices for erosion control as required by the Town Engineer when undertaking construction activities.
- 72. SITE DRAINAGE: Rainwater leaders shall be discharged to splash blocks. No through curb drains will be allowed. Any storm drain inlets (public or private) directly connected to public storm system shall be stenciled/signed with appropriate "NO DUMPING Flows to Bay" NPDES required language. On-site drainage systems for all projects shall include one of the alternatives included in section C.3.i of the Municipal Regional NPDES Permit. These include storm water reuse via cisterns or rain barrels, directing runoff from impervious surfaces to vegetated areas and use of permeable surfaces. If stormwater treatment facilities are to be used they shall be placed a minimum of ten (10) feet from the adjacent property line and/or right-of-way. Alternatively, the facilities may be located with an offset between 5 and 10 feet from the adjacent property and/or right-of-way lines if the responsible engineer in charge provides a stamped and signed letter that addresses infiltration and states how facilities, improvements and infrastructure within the Town's right-of-way (driveway approach, curb and gutter, etc.) and/or the adjacent property will not be adversely affected.

- No improvements shall obstruct or divert runoff to the detriment of an adjacent, downstream or down slope property.
- 73. SILT AND MUD IN PUBLIC RIGHT-OF-WAY: It is the responsibility of Contractor and homeowner to make sure that all dirt tracked into the public right-of-way is cleaned up on a daily basis. Mud, silt, concrete and other construction debris SHALL NOT be washed into the Town's storm drains.
- 74. GOOD HOUSEKEEPING: Good housekeeping practices shall be observed at all times during the course of construction. All construction shall be diligently supervised by a person or persons authorized to do so at all times during working hours. The Owner's representative in charge shall be at the job site during all working hours. Failure to maintain the public right-of-way according to this condition may result in penalties and/or the Town performing the required maintenance at the Owner's expense.
- 75. NEIGHBORHOOD CONSTRUCTION COMMUNICATION PLAN: Immediately upon approval of an encroachment permit, the Owner and/or Developer shall initiate a weekly neighborhood email notification program to provide project status updates. The email notices shall also be posted on a bulletin board placed in a prominent location along the project perimeter.
- 76. PERMIT ISSUANCE: Permits for each phase shall be issued simultaneously.
- 77. COVERED TRUCKS: All trucks transporting materials to and from the site shall be covered.

TO THE SATISFACTION OF THE SANTA CLARA COUNTY FIRE DEPARTMENT:

- 78. GENERAL: Review of this Developmental proposal is limited to acceptability of site access, water supply and may include specific additional requirements as they pertain to fire department operations, and shall not be construed as a substitute for formal plan review to determine compliance with adopted model codes. Prior to performing any work, the applicant shall make application to, and receive from, the Building Department all applicable construction permits.
- 79. FIRE SPRINKLERS REQUIRED (As Noted on Sheet T1) An automatic residential fire sprinkler system shall be installed in one- and two-family dwellings as follows: 1) In all new one- and two-family dwellings and in existing one- and two-family dwellings when additions are made that increase the building area to more than 3,600 SF whether by increasing the area of the primary residence or by creation of an attached Accessory Dwelling Unit. 2) In all new basements and in existing basements that are expanded by more than 50%. 3) In all attached ADUs, additions or alterations to an existing one- and two-family dwelling that have an existing fire sprinkler system. Exceptions: 1) One or more additions made to a building after January 1, 2011 that does not total more than 1,000 square feet of building area and meets all access and water supply requirements of Chapter 5 and Appendix B and C of the 2019 California Fire Code. 2) Detached Accessory Dwelling Units, provided that all of the following are met: a) The unit meets the definition of an Accessory Dwelling Unit as defined in the Government Code Section 65852.2. b) The existing primary residence does not have automatic fire sprinklers. c) The detached ADU does not exceed 1,200 square feet in size. d) The unit is on the same lot as the primary residence. e) The unit meets all access and water supply requirements of Chapter 5 and Appendix B and C of the 2019 California Fire Code.

- 80. REQUIRED FIRE FLOW: (Letter received) The minimum require fireflow for this project is 875 Gallons Per Minute (GPM) at 20 psi residual pressure. This fireflow assumes installation of automatic fire sprinklers per CF [903.3.1.3].
- 81. WATER SUPPLY REQUIREMENTS: Potable water supplies shall be protected from contamination caused by fire protection water supplies. It is the responsibility of the applicant and any contractors and subcontractors to contact the water purveyor supplying the site of such project, and to comply with the requirements of that purveyor. Such requirements shall be incorporated into the design of any water-based fire protection systems, and/or fire suppression water supply systems or storage containers that may be physically connected in any manner to an appliance capable of causing contamination of the potable water supply of the purveyor of record. Final approval of the system(s) under consideration will not be granted by this office until compliance with the requirements of the water purveyor of record are documented by that purveyor as having been met by the applicant(s). 2019 CFC Sec. 903.3.5 and Health and Safety Code 13114.7.
- 82. ADDRESS IDENTIFICATION: New and existing buildings shall have approved address numbers, building numbers or approved building identification placed in a position that is plainly legible and visible from the street or road fronting the property. These numbers shall contrast with their background. Where required by the fire code official, address numbers shall be provided in additional approved locations to facilitate emergency response. Address numbers shall be Arabic numbers or alphabetical letters. Numbers shall be a minimum of 4 inches (101.6 mm) high with a minimum stroke width of 0.5 inch (12.7 mm). Where access is by means of a private road and the building cannot be viewed from the public way, a monument, pole or other sign or means shall be used to identify the structure. Address numbers shall be maintained. CFC Sec. 505.1.
- 83. CONSTRUCTION SITE FIRE SAFETY: All construction sites must comply with applicable provisions of the CFC Chapter 33 and our Standard Detail and Specification SI-7. Provide appropriate notations on subsequent plan submittals, as appropriate to the project. CFC Chp. 33.
- 84. GENERAL: This review shall not be construed to be an approval of a violation of the provisions of the California Fire Code or of other laws or regulations of the jurisdiction. A permit presuming to give authority to violate or cancel the provisions of the fire code or other such laws or regulations shall not be valid. Any addition to or alteration of approved construction documents shall be approved in advance. [CFC, Ch.1, 105.3.