16668 Shannon Road Los Gatos, CA.

MATERIAL BOARD



Main Building Color & Garage Doors: Swiss Coffee KM23
By: "Kelly Moore"



Accent Color: Winter Solstice KM5812 (All trims)
By: "Kelly Moore"



Suggested: Flat Tiles Roof by: Eagle Roofing 199 Charcoal range Golden eagle profiles

WINDOWS: BLACK ALUMINUM TILT & TURN

Tilt & Turn Windows

Highlights

A European classic, tilt & turn windows are inswing windows with a double function. With a turn of the handle they either tilt or swing in. The tilt function provides secure ventilation while maintaining beautiful views.

Overview

Zola's tilt & turn windows can be made to very large sizes, with the biggest reaching nearly five feet in width and eight feet in height. We use only the finest German multi-point hardware sets to ensure a smooth and effortless operation, security, and superb air sealing. Tilt & Turn windows can be made as single units, either left or right hand hung, or double french units.





70 a

ALUMINUM THERMO ALU90TM

Thermo Alu90 combines a Passive House level frame with the thin profile of aluminum for the modern high performance project. The frame is designed to support very large window sizes. Made in standard triple-pane, low-iron glass.

PERFORMANCE

Frame Depth = 90mm (3.54")

NFRC Values:

Fixed

U = 0.16 Btu/(h.ft2.F)

SHGC = up to 0.39

VT = 0.59

Condensation Resistance = 80

Operable

U = 0.18 Btu/(h.ft2.F)

SHGC = up to 0.34

VT = 0.5

Condensation Resistance = 78

CE Values:

Uf = 1.23 W/(m2K)

Ug = 0.53 W/(m2K)

Uw = 0.8 W/(m2K)

Psi = 0.050 W/mK

FINISH OPTIONS

Interior and Exterior: RAL powder coated, Tactile Series, and Anodized options.

CONFIGURATIONS AVAILABLE

Fixed

Tilt-turn, Tilt-only, Turn-only, Tilt-first Fixed/Operable combinations French window opening Lift-Slide Doors Entry Doors

HARDWARE

European multi-point locking system with upto eight locking points on windows and four points on entry doors. Visible hinges are standard but concealed hinges are available.



All performance data based on typical assemblies. Discuss specific performance values with a Zola Project Manager







CAT. #: LWM350-S7-GTL-



LWM350-S7-GTL EQUINOX

The LWM350 series of LED Wall Sconces is the latest addition to our growing line of innovative and exquisite wall mount luminaires. This series is available in four elegant shade designs and two progressive sizes. Its timeless design enhances architecture and garden elements such as pergolas or gazebos. Provide design continuity and use in conjunction with our LBD Bollard and LML Pendant Light series to create the perfect transition between landscape and architecture.

> Powered by **CREE**

> > 12 V


LEDS

See LWM250 for additional size and configuration options.


Features include:

- 20 Watts
- Cree XLAMP® Extreme High Power (XHP) LED
- 2700, 3000 or 4500K (CRI 80 typ.)
- Thermally Integrated® and Field Serviceable LED Module
- TRIAC Dimming to <10% typ.
- 12 VAC Electronic or Magnetic Source Compatible
- Solid Copper and Brass Construction






Standard Configuration



With optional MWM



With optional MJB

ORDERING GUIDE: LWM350-S7-GTL) L (LED) WM (WALL MOUNT) 350 (SERIES) S (SPHERICAL) 7 (INCHES) GTL (GLIMMER TOP W/ LOUVER)

☐ INDICATES REQUIRED FIELD [] INDICATES OPTIONAL FIFLD LED COLOR MOUNT

[27D] 2700K [30D] 3000K [45D] 4500K

[D] = Dimmable

[MJB] Micro Wall Mount w/ Micro J-Box Provides 3 ports for multi-conduit entries

[MWM] Micro Wall Mount

1/2 NPS CANOPIES:

[CP4] 4" Cover Plate*

[CP45] 4 1/2" Cover Plate * [MC45] 4 1/2" Mount Canopy*

[PC60] Power Canopy (Inc. 60W 120-12V trans.)*

[SMJB] 3 1/2" Surface Mount J-Box

*Brass Escutcheon is standard. Add "C" for Copper

FINISH

[NAT] Natural

[BLP] Bronze Living Patina

[BLP-XD] BLP Extra Dark

[NI] Nickel PVD*

*When NI is selected underside will match



