

PLANNING COMMISSION – February 28, 2024
CONDITIONS OF APPROVAL

15365 Santella Court
Architecture and Site Application S-24-002

Requesting Approval of a One-Year Time Extension to an Existing Architecture and Site Application (S-18-052) to Construct a New Single-Family Residence, Site Work Requiring a Grading Permit, and Removal of Large Protected Trees on a Vacant Property Zoned HR-2-1/2:PD. An Environmental Impact Report (EIR) was Prepared for the Planned Development and was Certified by the Town Council on December 19, 2005. No Further Environmental Analysis is Required for the Individual Lot Development. APN 527-09-036.

PROPERTY OWNER: Christian and Hellen Olgaard.

APPLICANT: Hari Sripadanna.

TO THE SATISFACTION OF THE DIRECTOR OF COMMUNITY DEVELOPMENT:

Planning Division

1. **APPROVAL:** This application shall be completed in accordance with all of the conditions of approval listed below and in substantial compliance with the plans approved and noted as received by the Town on February 28, 2026. Any changes or modifications to the approved plans shall be approved by the Community Development Director, the Development Review Committee, the Planning Commission, or Town Council, depending on the scope of the changes.
2. **EXPIRATION:** The approval will expire two years from the approval date pursuant to Section 29.20.320 of the Town Code, unless the approval has been vested.
3. **OUTDOOR LIGHTING:** Exterior lighting shall be kept to a minimum, and shall be down directed fixtures that will not reflect or encroach onto adjacent properties. No flood lights shall be used unless it can be demonstrated that they are needed for safety or security. The lighting plan shall be reviewed during building plan check.
4. **EXTERIOR COLOR:** The exterior colors of the house shall not exceed an average light reflectivity value of 30 and shall blend with the natural vegetation in conformance with the approved PD Ordinance 2237.
5. **LRV DEED RESTRICTION:** Prior to the issuance of a building permit, a deed restriction shall be recorded by the applicant with the Santa Clara County Recorder's Office that requires all exterior colors to be maintained in conformance with the approved PD Ordinance.
6. **GENERAL:** All existing trees shown on the plan and trees required to remain or to be planted are specific subjects of approval of this plan, and must remain on the site.
7. **MAINTENANCE AGREEMENT:** Following the issuance of a certificate of occupancy, the property owner shall execute a five-year maintenance agreement with the Town that the property owner agrees to protect and maintain the trees shown to remain on the

- approved plans, trees planted as part of the tree replacement requirements, and guarantees that said trees will always be in a healthy condition during the term of the maintenance agreement.
8. TREE DEED RESTRICTION: Prior to issuance of a building permit, a deed restriction shall be recorded by the applicant with the Santa Clara County Recorder's Office that identifies the on-site trees that were used to provide screening in the visibility analysis and requires their replacement if they die or are removed.
 9. TREE REMOVAL PERMIT: A Tree Removal Permit shall be obtained for any trees to be removed, prior to the issuance of a building or grading permit.
 10. ARBORIST REQUIREMENTS: The developer shall implement, at their cost, all recommendations made by Richard Gessner, identified in the Arborist report, dated as received November 29, 2018, the supplemental Arborist report, dated as received August 20, 2019, the addendum dated as received on November 27, 2023, and February 5, 2024, respectively, on file in the Community Development Department. A Compliance Memorandum shall be prepared by the applicant and submitted with the building permit application detailing how the recommendations have or will be addressed. These recommendations must be incorporated in the building permit plans, and completed prior to issuance of a building permit where applicable.
 11. TREE FENCING: Protective tree fencing shall be placed at the drip line of existing trees and shall remain through all phases of construction. Fencing shall be six-foot-high cyclone attached to two-inch diameter steel posts drive 18 inches into the ground and spaced no further than 10 feet apart. Include a tree protection fencing plan with the construction plans.
 12. REPLACEMENT TREES: New trees shall be planted to mitigate the loss of trees being removed. The number of trees and size of replacement trees shall be determined using the canopy replacement table in the Town Code. Town Code requires a minimum 24-inch box size replacement tree. New trees shall be double staked with rubber ties and shall be planted prior to final inspection and issuance of occupancy permits.
 13. LANDSCAPE PLAN: The final landscape plan shall comply with the Hillside Development Standards and Guidelines criteria for planting (ornamental planting shall be confined to areas within 30 feet of the house, inclusive of decks, patios and driveway).
 14. WATER EFFICIENCY LANDSCAPE ORDINANCE: The final landscape plan, including landscape and irrigation plans and calculations, shall meet the Town of Los Gatos Water Conservation Ordinance or the State Water Efficient Landscape Ordinance, whichever is more restrictive. The final landscape plan shall be reviewed by the Town's consultant prior to issuance of building permits. A review fee based on the current fee schedule adopted by the Town Council is required when working landscape and irrigation plans are submitted for review.
 15. PROPERTY FENCE: All new fencing shall comply with Town Code Section 29.40.0315 at building permit stage, unless an exception is granted by the Community Development Director.
 16. BMP IN-LIEU FEE: A Below Market Price (BMP) in-lieu fee (6% of the building valuation as determined by the Building Official) shall be paid by the developer prior to issuance of an occupancy permit for the new residence.
 17. FRONT YARD LANDSCAPE: Prior to issuance of a Certificate of Occupancy the front yard

- must be landscaped.
18. STORY POLES: The story poles on the project site shall be removed within 30 days of approval of the Architecture & Site application.
 19. NESTING BIRDS: To avoid impacts to nesting birds, the removal of trees and shrubs shall be minimized to the greatest extent feasible. Construction activities that include any tree removal, pruning, grading, grubbing, or demolition shall be conducted outside of the bird nesting season (January 15 through September 15) to the greatest extent feasible. If this type of construction starts, if work is scheduled to start or if work already occurring during the nesting season stops for at least two weeks and is scheduled to resume during the bird nesting season, then a qualified biologist shall conduct a pre-construction surveys for nesting birds to ensure that no nests would be disturbed during project construction. If project-related work is scheduled during the nesting season (February 15 to August 30 for small bird species such as passerines; January 15 to September 15 for owls; and February 15 to September 15 for other raptors), a qualified biologist shall conduct nesting bird surveys. Two surveys for active nests of such birds shall occur within 14 days prior to start of construction, with the second survey conducted with 48 hours prior to start of construction. Appropriate minimum survey radius surrounding each work area is typically 250 feet for passerines, 500 feet for smaller raptors, and 1,000 feet for larger raptors. Surveys shall be conducted at the appropriate times of day to observe nesting activities. If the qualified biologist documents active nests within the project site or in nearby surrounding areas, an appropriate buffer between each nest and active construction shall be established. The buffer shall be clearly marked and maintained until the young have fledged and are foraging independently. Prior to construction, the qualified biologist shall conduct baseline monitoring of each nest to characterize "normal" bird behavior and establish a buffer distance, which allows the birds to exhibit normal behavior. The qualified biologist shall monitor the nesting birds daily during construction activities and increase the buffer if birds show signs of unusual or distressed behavior (e.g. defensive flights and vocalizations, standing up from a brooding position, and/or flying away from the nest). If buffer establishment is not possible, the qualified biologist or construction foreman shall have the authority to cease all construction work in the area until the young have fledged and the nest is no longer active.
 20. SPECIAL-STATUS BATS: Approximately 14 days prior to tree removal or structure demolition activities, a qualified biologist shall conduct a habitat assessment for bats and potential roosting sites in trees to be removed, in trees within 50 feet of the development footprint, and within and surrounding any structures that may be disturbed by the project. These surveys will include a visual inspection of potential roosting features (bats need not be present) and a search for presence of guano within the project site, construction access routes, and 50 feet around these areas. Cavities, crevices, exfoliating bark, and bark fissures that could provide suitable potential nest or roost habitat for bats shall be surveyed. Assumptions can be made on what species is present due to observed visual characteristics along with habitat use, or the bats can be identified to the species level with the use of a bat echolocation detector such as an "Anabat" unit. Potential roosting features found during the survey shall be flagged or marked.

If no roosting sites or bats are found, a letter report confirming absence will be prepared and no further measures are required.

If bats or roosting sites are found, a letter report and supplemental documents will be prepared prior to grading permit issuance and the following monitoring, exclusion, and habitat replacement measures will be implemented:

- a. If bats are found roosting outside of the nursery season (May 1 through October 1), they will be evicted as described under (b) below. If bats are found roosting during the nursery season, they will be monitored to determine if the roost site is a maternal roost. This could occur by either visual inspection of the roost bat pups, if possible, or by monitoring the roost after the adults leave for the night to listen for bat pups. If the roost is determined to not be a maternal roost, then the bats will be evicted as described under (b) below. Because bat pups cannot leave the roost until they are mature enough, eviction of a maternal roost cannot occur during the nursery season. Therefore, if a maternal roost is present, a 50-foot buffer zone (or different size if determined in consultation with the CDFW) will be established around the roosting site within which no construction activities including tree removal or structure disturbance will occur until after the nursery season.
- b. If a non-breeding bat hibernaculum is found in a tree or snag scheduled for removal or on any structures scheduled to be disturbed by project activities, the individuals will be safely evicted, under the direction of a qualified bat biologist. If pre-construction surveys determine that there are bats present in any trees to be removed, exclusion structures (e.g. one-way doors or similar methods) shall be installed by a qualified biologist. The exclusion structures shall not be placed until the time of year in which young are able to fly, outside of the nursery season. Information on placement of exclusion structures shall be provided to the CDFW prior to construction.

If needed, other methods conducted under the direction of a qualified bat biologist could include: carefully opening the roosting area in a tree or snag by hand to expose the cavity and opening doors/windows on structures, or creating openings in walls to allow light into the structures. Removal of any trees or snags and disturbance of any structures will be conducted no earlier than the following day (i.e., at least one night will be provided between initial roost eviction disturbance and tree removal/structure disturbance). This action will allow bats to leave during dark hours, which increases their chance of finding new roosts with a minimum of potential predation.

21. **ARCHAEOLOGICAL RESOURCES AND HUMAN REMAINS:**

- a. In the event that archaeological traces are encountered, all construction within a 50-meter radius of the find will be halted, the Community Development Director will be notified, and an archaeologist will be retained to examine the find and make appropriate recommendations.
- b. If human remains are discovered, the Santa Clara County Coroner will be notified. The Coroner will determine whether or not the remains are Native American. If the

Coroner determines the remains are not subject to his authority, he will notify the Native American Heritage Commission, who shall attempt to identify descendants of the deceased Native Americans.

- c. If the Community Development Director finds that the archaeological find is not a significant resource, work will resume only after the submittal of a preliminary archaeological report and after provisions for reburial and ongoing monitoring are accepted. Provisions for identifying descendants of a deceased Native American and for reburial will follow the protocol set forth in CEQA Guidelines Section 15064.5(e). If the site is found to be a significant archaeological site, a mitigation program will be prepared and submitted to the Community Development Director for consideration and approval, in conformance with the protocol set forth in Public Resources Code Section 21083.2.
 - d. A final report shall be prepared when a find is determined to be a significant archaeological site, and/or when Native American remains are found on the site. The final report will include background information on the completed work, a description and list of identified resources, the disposition and curation of these resources, any testing, other recovered information, and conclusions.
22. DUSKY-FOOTED WOODRATS: This project will implement the following standard measures to minimize impacts on woodrats and active woodrat nests on the project site.
- PRECONSTRUCTION SURVEY. A qualified biologist will conduct a preconstruction survey for San Francisco dusky-footed woodrat nests within 30 days of the start of work activities. If active woodrat nests are determined to be present in, or within 10 feet of the impact areas, the conditions below (Avoidance and/or Nest Relocation) will be implemented, as appropriate. If no active woodrat nests are present on or within 10 feet of impact areas, no further conditions are warranted.
 - AVOIDANCE. Active woodrat nests that are detected within the work area will be avoided to the extent feasible. Ideally, a minimum 10-foot buffer will be maintained between project activities and woodrat nests to avoid disturbance. In some situations, a small buffer may be allowed if, in the opinion of a qualified biologist, nest relocation (below) would represent a greater disturbance to the woodrats than the adjacent work activities.
 - NEST RELOCATION. If avoidance of active woodrat nests within and immediately adjacent to (within 10 feet of) the work areas is not feasible, then nest materials will be relocated to suitable habitat as close to the project site as possible (ideally, within or immediately adjacent to the project site).

Relocation efforts will avoid the peak nesting season (February-July) to the maximum extent feasible. Prior to the start of construction activities, a qualified biologist will disturb the woodrat nest to the degree that all woodrats leave the nest and seek refuge outside of the construction area. Disturbance of the woodrat nest will be initiated no earlier than one hour before dusk to prevent the exposure of woodrats to diurnal predators. Subsequently, the biologist will dismantle and relocate the nest material by hand. During the deconstruction process, the biologist will attempt to assess if there are

juveniles in the nest. If immobile juveniles are observed, the deconstruction process will be discontinued until a time when the biologist believes the juveniles will be capable of independent survival (typically after 2 to 3 weeks). A no-disturbance buffer will be established around the nest until the juveniles are mobile. The nest may be dismantled once the biologist has determined that adverse impacts on the juveniles would not occur.

23. TOWN INDEMNITY: Applicants are notified that Town Code Section 1.10.115 requires that any applicant who receives a permit or entitlement ("the Project") from the Town shall defend (with counsel approved by Town), indemnify, and hold harmless the Town, its agents, officers, and employees from and against any claim, action, or proceeding (including without limitation any appeal or petition for review thereof) against the Town or its agents, officers or employees related to an approval of the Project, including without limitation any related application, permit, certification, condition, environmental determination, other approval, compliance or failure to comply with applicable laws and regulations, and/or processing methods ("Challenge"). Town may (but is not obligated to) defend such Challenge as Town, in its sole discretion, determines appropriate, all at applicant's sole cost and expense.

Applicant shall bear any and all losses, damages, injuries, liabilities, costs and expenses (including, without limitation, staff time and in-house attorney's fees on a fully-loaded basis, attorney's fees for outside legal counsel, expert witness fees, court costs, and other litigation expenses) arising out of or related to any Challenge ("Costs"), whether incurred by Applicant, Town, or awarded to any third party, and shall pay to the Town upon demand any Costs incurred by the Town. No modification of the Project, any application, permit certification, condition, environmental determination, other approval, change in applicable laws and regulations, or change in such Challenge as Town, in its sole discretion, determines appropriate, all the applicant's sole cost and expense. No modification of the Project, any application, permit certification, condition, environmental determination, other approval, change in applicable laws and regulations, or change in processing methods shall alter the applicant's indemnity obligation.

24. COMPLIANCE MEMORANDUM: A memorandum shall be prepared and submitted with the building plans detailing how the Conditions of Approval will be addressed.

Building Division

25. PERMITS REQUIRED: A Building Permit is required for the construction of the new single-family residence and attached garage. Additional Building Permits will be required for all detached structures such as swimming pools and retaining walls supporting a surcharge. A separate Building Permit will be required for the Photovoltaic System required by the California Energy Code.
26. APPLICABLE CODES: The current codes, as amended and adopted by the Town of Los Gatos as of January 1, 2023, are the 2022 California Building Standards Code, California Code of Regulations Title 24, Parts 1-12, including locally adopted Reach Codes.

27. **CONDITIONS OF APPROVAL:** The Conditions of Approval must be blue lined in full on the cover sheet of the construction plans. A Compliance Memorandum shall be prepared and submitted with the building permit application detailing how the Conditions of Approval will be addressed.
28. **BUILDING & SUITE NUMBERS:** Submit requests for new building addresses to the Building Division prior to submitting for the building permit application process.
29. **SIZE OF PLANS:** Minimum size 24" x 36", maximum size 30" x 42".
30. **SOILS REPORT:** A Soils Report, prepared to the satisfaction of the Building Official, containing foundation, and retaining wall design recommendations, shall be submitted with the Building Permit Application. This report shall be prepared by a licensed Civil Engineer specializing in soils mechanics.
31. **SHORING:** Shoring plans and calculations will be required for all excavations which exceed five (5) feet in depth, or which remove lateral support from any existing building, adjacent property, or the public right-of-way. Shoring plans and calculations shall be prepared by a California licensed engineer and shall confirm to the Cal/OSHA regulations.
32. **FOUNDATION INSPECTIONS:** A pad certificate prepared by a licensed civil engineer or land surveyor shall be submitted to the project Building Inspector at foundation inspection. This certificate shall certify compliance with the recommendations as specified in the Soils Report, and that the building pad elevations and on-site retaining wall locations and elevations have been prepared according to the approved plans. Horizontal and vertical controls shall be set and certified by a licensed surveyor or registered Civil Engineer for the following items:
 - a. Building pad elevation
 - b. Finish floor elevation
 - c. Foundation corner locations
 - d. Retaining wall(s) locations and elevations
33. **TITLE 24 ENERGY COMPLIANCE:** All required California Title 24 Energy Compliance Forms must be blue-lined (sticky-backed), i.e., directly printed, onto a plan sheet.
34. **TOWN RESIDENTIAL ACCESSIBILITY STANDARDS:** New residential units shall be designed with adaptability features for single-family residences per Town Resolution 1994-61:
 - a. Wood backing (2" x 8" minimum) shall be provided in all bathroom walls, at water closets, showers, and bathtubs, located 34 inches from the floor to the center of the backing, suitable for the installation of grab bars if needed in the future.
 - b. All passage doors shall be at least 32-inch-wide doors on the accessible floor level.
 - c. The primary entrance door shall be a 36-inch-wide door including a 5' x 5' level landing, no more than 1 inch out of plane with the immediate interior floor level and with an 18-inch clearance at interior strike edge.
 - d. A door buzzer, bell or chime shall be hard wired at primary entrance.
35. **BACKWATER VALVE:** The scope of this project may require the installation of a sanitary sewer backwater valve per Town Ordinance 6.40.020. Please provide information on the plans if a backwater valve is required and the location of the installation. The Town of Los Gatos Ordinance and West Valley Sanitation District (WVSD) requires backwater valves on drainage piping serving fixtures that have flood level rims less than 12 inches above the elevation of the next upstream manhole.

36. HAZARDOUS FIRE ZONE: All projects in the Town of Los Gatos require Class A roof assemblies.
37. WILDLAND-URBAN INTERFACE: This project is located in a Wildland-Urban Interface High Fire Area and must comply with Section R337 of the 2019 California Residential Code, Public Resources Code 4291 and California Government Code Section 51182.
38. PROVIDE DEFENSIBLE SPACE/FIRE BREAK LANDSCAPING PLAN: Prepared by a California licensed Landscape Architect in conformance with California Public Resources Code 4291 and California Government Code Section 51182.
39. PRIOR TO FINAL INSPECTION: Provide a letter from a California licensed Landscape Architect certifying the landscaping and vegetation clearance requirements have been completed per the California Public Resources Code 4291 and Government Code Section 51182.
40. SPECIAL INSPECTIONS: When a special inspection is required by CBC Section 1704, the Architect or Engineer of Record shall prepare an inspection program that shall be submitted to the Building Official for approval prior to issuance of the Building Permit. The Town Special Inspection form must be completely filled-out and signed by all requested parties prior to permit issuance. Special Inspection forms are available online at www.losgatosca.gov/building.
41. BLUEPRINT FOR A CLEAN BAY SHEET: The Town standard Santa Clara Valley Nonpoint Source Pollution Control Program Sheet (page size same as submitted drawings) shall be part of the plan submittal as the second page. The specification sheet is available online at www.losgatosca.gov/building.
42. APPROVALS REQUIRED: The project requires the following departments and agencies approval before issuing a building permit:
 - a. Community Development – Planning Division: (408) 354-6874
 - b. Engineering/Parks & Public Works Department: (408) 399-5771
 - c. Santa Clara County Fire Department: (408) 378-4010
 - d. West Valley Sanitation District: (408) 378-2407
 - e. Local School District: The Town will forward the paperwork to the appropriate school district(s) for processing. A copy of the paid receipt is required prior to permit issuance.

Engineering Division

43. GENERAL: All public improvements shall be made according to the latest adopted Town Standard Plans, Standard Specifications and Engineering Design Standards. All work shall conform to the applicable Town ordinances. The adjacent public right-of-way shall be kept clear of all job-related mud, silt, concrete, dirt and other construction debris at the end of the day. Dirt and debris shall not be washed into storm drainage facilities. The storing of goods and materials on the sidewalk and/or the street will not be allowed unless an encroachment permit is issued by the Engineering Division of the Parks and Public Works Department. The Owner and/or Applicant's representative in charge shall be at the job site during all working hours. Failure to maintain the public right-of-way according to this condition may result in the issuance of correction notices, citations, or stop work orders and the Town performing the required maintenance at the Owner and/or Applicant's expense.

44. APPROVAL: This application shall be completed in accordance with all the conditions of approval listed below and in substantial compliance with the latest reviewed and approved development plans. Any changes or modifications to the approved plans or conditions of approvals shall be approved by the Town Engineer.
45. PRIOR APPROVALS: All conditions per prior approvals (including Ordinance 2147, etc.) shall be deemed in full force and affect for this approval.
46. CHANGE OF OCCUPANCY: Prior to initial occupancy and any subsequent change in use or occupancy of any non-residential condominium space, the buyer or the new or existing occupant shall apply to the Community Development Department and obtain approval for use determination and building permit and obtain inspection approval for any necessary work to establish the use and/or occupancy consistent with that intended.
47. ENCROACHMENT PERMIT: All work in the public right-of-way will require a Construction Encroachment Permit. All work over \$5,000 will require construction security. It is the responsibility of the Owner/Applicant to obtain any necessary encroachment permits from affected agencies and private parties, including but not limited to, Pacific Gas and Electric (PG&E), AT&T, Comcast, Santa Clara Valley Water District, California Department of Transportation (Caltrans). Copies of any approvals or permits must be submitted to the Town Engineering Division of the Parks and Public Works Department prior to releasing any permit.
48. GENERAL LIABILITY INSURANCE: The property owner shall provide proof of insurance to the Town on a yearly basis. In addition to general coverage, the policy must cover all elements encroaching into the Town's right-of-way.
49. PUBLIC WORKS INSPECTIONS: The Owner and/or Applicant or their representative shall notify the Engineering Inspector at least twenty-four (24) hours before starting any work pertaining to on-site drainage facilities, grading or paving, and all work in the Town's right-of-way. Failure to do so will result in penalties and rejection of any work that occurred without inspection.
50. RESTORATION OF PUBLIC IMPROVEMENTS: The Owner and/or Applicant or their representative shall repair or replace all existing improvements not designated for removal that are damaged or removed because of the Owner and/or Applicant or their representative's operations. Improvements such as, but not limited to: curbs, gutters, sidewalks, driveways, signs, pavements, raised pavement markers, thermoplastic pavement markings, etc., shall be repaired and replaced to a condition equal to or better than the original condition. Any new concrete shall be free of stamps, logos, names, graffiti, etc. Any concrete identified that is displaying a stamp or equal shall be removed and replaced at the Contractor's sole expense and no additional compensation shall be allowed therefore. Existing improvement to be repaired or replaced shall be at the direction of the Engineering Construction Inspector and shall comply with all Title 24 Disabled Access provisions. The restoration of all improvements identified by the Engineering Construction Inspector shall be completed before the issuance of a certificate of occupancy. The Owner and/or Applicant or their representative shall request a walk-through with the Engineering Construction Inspector before the start of construction to verify existing conditions.

51. SITE SUPERVISION: The General Contractor shall provide qualified supervision on the job site at all times during construction.
52. STREET CLOSURE: Any proposed blockage or partial closure of the street requires an encroachment permit. Special provisions such as limitations on works hours, protective enclosures, or other means to facilitate public access in a safe manner may be required.
53. PLAN CHECK FEES: Plan check fees associated with the Grading Permit shall be deposited with the Engineering Division of the Parks and Public Works Department prior to the commencement of plan check review.
54. INSPECTION FEES: Inspection fees shall be deposited with the Town prior to the issuance of any grading or building permits.
55. DESIGN CHANGES: Any proposed changes to the approved plans shall be subject to the approval of the Town prior to the commencement of any and all altered work. The Owner and/or Applicant's project engineer shall notify, in writing, the Town Engineer at least seventy-two (72) hours in advance of all the proposed changes. Any approved changes shall be incorporated into the final "as-built" plans.
56. PLANS AND STUDIES: All required plans and studies shall be prepared by a Registered Professional Engineer in the State of California and submitted to the Town Engineer for review and approval. Additionally, any studies imposed by the Planning Commission or Town Council shall be funded by the Owner and/or Applicant.
57. GRADING PERMIT: A grading permit is required for all site grading and drainage work except for exemptions listed in Section 12.20.015 of The Code of the Town of Los Gatos (Grading Ordinance). After the preceding Architecture and Site Application has been approved by the respective deciding body, the grading permit application (with grading plans and associated required materials and plan check fees) shall be made to the Engineering Division of the Parks and Public Works Department located at 41 Miles Avenue. The grading plans shall include final grading, drainage, retaining wall location(s), driveway, utilities and interim erosion control. Grading plans shall list earthwork quantities and a table of existing and proposed impervious areas. Unless specifically allowed by the Director of Parks and Public Works, the grading permit will be issued concurrently with the building permit. The grading permit is for work outside the building footprint(s). Prior to Engineering signing off and closing out on the issued grading permit, the Owner/Applicant's soils engineer shall verify, with a stamped and signed letter, that the grading activities were completed per plans and per the requirements as noted in the soils report. A separate building permit, issued by the Building Department, located at 110 E. Main Street, is needed for grading within the building footprint.
58. GRADING ACTIVITY RESTRICTIONS: Upon receipt of a grading permit, any and all grading activities and operations shall not commence until after/occur during the rainy season, as defined by Town Code of the Town of Los Gatos, Sec. 12.10.020, (October 15-April 15), has ended.
59. COMPLIANCE WITH HILLSIDE DEVELOPMENT STANDARDS AND GUIDELINES: All grading activities and operations shall be in compliance with Section III of the Town's Hillside Development Standards and Guidelines. All development shall be in compliance with Section II of the Town's Hillside Development Standards and Guidelines.

60. DRIVEWAY: The driveway conform to existing pavement on Santella Court shall be constructed in a manner such that the existing drainage patterns will not be obstructed.
61. CONSTRUCTION EASEMENT: Prior to the issuance of a grading or building permit, it shall be the sole responsibility of the Owner and/or Applicant to obtain any and all proposed or required easements and/or permissions necessary to perform the grading herein proposed. Proof of agreement/approval is required prior to the issuance of any Permit.
62. DRAINAGE IMPROVEMENT: Prior to the issuance of any grading/improvement permits, whichever comes first, the Owner and/or Applicant shall:
 - a. Design provisions for surface drainage;
 - b. Design all necessary storm drain facilities extending to a satisfactory point of disposal for the proper control and disposal of storm runoff; and
 - c. Provide a recorded copy of any required easements to the Town.
63. TREE REMOVAL: Copies of all necessary tree removal permits shall be provided prior to the issuance of a grading permit/building permit.
64. SURVEYING CONTROLS: Horizontal and vertical controls shall be set and certified by a licensed surveyor or registered civil engineer qualified to practice land surveying, for the following items:
 - a. Retaining wall: top of wall elevations and locations.
 - b. Toe and top of cut and fill slopes.
65. PRECONSTRUCTION MEETING: Prior to issuance of any grading or building permits or the commencement of any site work, the general contractor shall:
 - a. Along with the Owner and/or Applicant, attend a pre-construction meeting with the Town Engineer to discuss the project conditions of approval, working hours, site maintenance and other construction matters;
 - b. Acknowledge in writing that they have read and understand the project conditions of approval and will make certain that all project sub-contractors have read and understand them as well prior to commencing any work, and that a copy of the project conditions of approval will be posted on-site at all times during construction.
66. RETAINING WALLS: A building permit, issued by the Building Department, located at 110 E. Main Street, may be required for site retaining walls. Walls are not reviewed or approved by the Engineering Division of Parks and Public Works during the grading permit plan review process.
67. SOILS REPORT: One copy of the soils and geologic report shall be submitted with the application. The soils report shall include specific criteria and standards governing site grading, drainage, pavement design, retaining wall design, and erosion control. The reports shall be signed and "wet stamped" by the engineer or geologist, in conformance with Section 6735 of the California Business and Professions Code.
68. GEOLOGY AND SOILS MITIGATION MEASURE: A geotechnical investigation shall be conducted for the project to determine the surface and sub-surface conditions at the site and to determine the potential for surface fault rupture on the site. The geotechnical study shall provide recommendations for site grading as well as the design of foundations, retaining walls, concrete slab-on-grade construction, excavation, drainage, on-site utility trenching and pavement sections. All recommendations of the investigation shall be incorporated into project plans.

69. **SOILS REVIEW:** Prior to Town approval of a development application, the Owner and/or Applicant's engineers shall prepare and submit a design-level geotechnical and geological investigation for review by the Town's consultant, with costs borne by the Owner and/or Applicant, and subsequent approval by the Town. The Owner and/or Applicant's soils engineer shall review the final grading and drainage plans to ensure that designs for foundations, retaining walls, site grading, and site drainage are in accordance with their recommendations and the peer review comments. Approval of the Owner and/or Applicant's soils engineer shall then be conveyed to the Town either by submitting a Plan Review Letter prior to issuance of grading or building permit(s).
70. **SOILS ENGINEER CONSTRUCTION OBSERVATION:** During construction, all excavations and grading shall be inspected by the Owner and/or Applicant's soils engineer prior to placement of concrete and/or backfill so they can verify that the actual conditions are as anticipated in the design-level geotechnical report and recommend appropriate changes in the recommendations contained in the report, if necessary. The results of the construction observation and testing shall be documented in an "as-built" letter/report prepared by the Owner and/or Applicant's soils engineer and submitted to the Town before a certificate of occupancy is granted.
71. **SOIL RECOMMENDATIONS:** The project shall incorporate the geotechnical/geological recommendations contained in the project's design-level geotechnical/geological investigation as prepared by the Owner and/or Applicant's engineer(s), and any subsequently required report or addendum. Subsequent reports or addendum are subject to peer review by the Town's consultant and costs shall be borne by the Owner and/or Applicant.
72. **DEDICATIONS:** The following shall be dedicated by separate instrument. The dedication shall be recorded before any grading or building permits are issued:
 - a. A Private Ingress Egress Easement (PIEE), twenty (20) feet in width, for the benefit of the neighboring Lot 8 to the west (15371 Santella Court; APN 527-09-035).
 - b. Storm drainage and sanitary sewer easements, as required.
73. **CERTIFICATE OF OCCUPANCY:** The Engineering Division of the Parks and Public Works Department will not sign off on a Temporary Certificate of Occupancy or a Final Certificate of Occupancy until all required improvements within the Town's right-of-way have been completed and approved by the Town.
74. **FRONTAGE IMPROVEMENTS:** The Owner and/or Applicant shall be required to improve the project's public frontage (right-of-way line to centerline and/or to limits per the direction of the Town Engineer) to current Town Standards. These improvements may include but not limited to curb, gutter, sidewalk, driveway approach(es), curb ramp(s), signs, pavement, raised pavement markers, thermoplastic pavement markings, storm drain facilities, traffic signal(s), street lighting (upgrade and/or repaint) etc. The improvements must be completed and accepted by the Town before a Certificate of Occupancy for any new building can be issued.
75. **UTILITIES:** The Owner and/or Applicant shall install all new, relocated, or temporarily removed utility services, including telephone, electric power and all other communications lines underground, as required by Town Code Section 27.50.015(b). All new utility services shall be placed underground. Underground conduit shall be provided for cable television service. The Owner and/or Applicant is required to obtain approval

of all proposed utility alignments from any and all utility service providers before a Certificate of Occupancy for any new building can be issued. The Town of Los Gatos does not approve or imply approval for final alignment or design of these facilities.

76. PRIVATE EASEMENTS: Agreements detailing rights, limitations and responsibilities of involved parties shall accompany any proposed private easement. Access driveway shall be within the recorded access easement. A new private access easement shall be recorded, and a copy of the recorded agreement shall be submitted to the Engineering Division of the Parks and Public Works Department, prior to issuance of a grading or building permit. A realigned access driveway shall be completed prior to the issuance of grading or building permit.
77. CURB AND GUTTER REPAIR: The Owner and/or Applicant shall repair and replace to existing Town standards any curb and gutter damaged now or during construction of this project. All new and existing adjacent infrastructure must meet Town standards. New curb and gutter shall be constructed per Town Standard Details. New concrete shall be free of stamps, logos, names, graffiti, etc. Any concrete identified that is displaying a stamp or equal shall be removed and replaced at the Contractor's sole expense and no additional compensation shall be allowed therefore. The limits of curb and gutter repair will be determined by the Engineering Construction Inspector during the construction phase of the project. The improvements must be completed and accepted by the Town before a Certificate of Occupancy for any new building can be issued.
78. DRIVEWAY APPROACH: The Owner and/or Applicant shall install one (1) Town standard residential driveway approach. The new driveway approach shall be constructed per Town Standard Plans and must be completed and accepted by the Town before a Certificate of Occupancy for any new building can be issued. New concrete shall be free of stamps, logos, names, graffiti, etc. Any concrete identified that is displaying a stamp or equal shall be removed and replaced at the Contractor's sole expense and no additional compensation shall be allowed therefore.
79. SIGHT TRIANGLE AND TRAFFIC VIEW AREA: Any proposed improvements, including but not limiting to trees and hedges, will need to abide by Town Code Sections 23.10.080, 26.10.065, and 29.40.030.
80. TRAFFIC IMPACT MITIGATION FEE: Prior to the issuance of any building or grading permits, the Owner/Applicant shall pay the project's proportional share of transportation improvements needed to serve cumulative development within the Town of Los Gatos. The fee amount will be based upon the Town Council resolution in effect at the time the building permit is issued. A fee of **\$46,585.71** shall be paid before issuance of any grading or building permit.
81. PRECONSTRUCTION PAVEMENT SURVEY: Prior to issuance of any grading or building permit, the Owner and/or Applicant shall complete a pavement condition survey documenting the extent of existing pavement defects using a smartphone video (in Landscape orientation only) or digital video camera. The survey shall extend through the Highlands of Los Gatos, from entry to the end of the Santella Court cul-de-sac. The results shall be documented in a report and submitted to the Town for review.
82. POSTCONSTRUCTION PAVEMENT SURVEY: The Owner and/or Applicant shall complete a pavement condition survey to determine whether road damage occurred as a result of project construction. Rehabilitation improvements required to restore the pavement to

- pre-construction condition and strength shall be determined using State of California procedures for deflection analysis. The results shall be documented in a report and submitted to the Town for review and approval before a Certificate of Occupancy for any new building can be issued. The Owner and/or Applicant shall be responsible for completing any required road repairs prior to release of the faithful performance bond.
83. CONSTRUCTION VEHICLE PARKING: Construction vehicle parking within the public right-of-way will only be allowed if it does not cause access or safety problems as determined by the Town.
 84. HAULING OF SOIL: Hauling of soil on- or off-site shall not occur during the morning or evening peak periods (between 7:00 a.m. and 9:00 a.m. and between 4:00 p.m. and 6:00 p.m.), and at other times as specified by the Director of Parks and Public Works. Prior to the issuance of a grading or building permit, the Owner and/or Applicant or their representative shall work with the Town Building Department and Engineering Division Inspectors to devise a traffic control plan to ensure safe and efficient traffic flow under periods when soil is hauled on or off the project site. This may include, but is not limited to provisions for the Owner and/or Applicant to place construction notification signs noting the dates and time of construction and hauling activities, or providing additional traffic control. Coordination with other significant projects in the area may also be required. Cover all trucks hauling soil, sand and other loose debris.
 85. CONSTRUCTION HOURS: All construction activities, including the delivery of construction materials, labors, heavy equipment, supplies, etc., shall be limited to the hours of 8:00 a.m. to 8:00 p.m., weekdays and 9:00 a.m. to 7:00 p.m. weekends and holidays. The Town may authorize, on a case-by-case basis, alternate construction hours. The Owner and/or Applicant shall provide written notice twenty-four (24) hours in advance of modified construction hours. Approval of this request is at discretion of the Town.
 86. CONSTRUCTION NOISE: Between the hours of 8:00 a.m. to 8:00 p.m., weekdays and 9:00 a.m. to 7:00 p.m. weekends and holidays, construction, alteration or repair activities shall be allowed. No individual piece of equipment shall produce a noise level exceeding eighty-five (85) dBA at twenty-five (25) feet from the source. If the device is located within a structure on the property, the measurement shall be made at distances as close to twenty-five (25) feet from the device as possible. The noise level at any point outside of the property plane shall not exceed eighty-five (85) dBA.
 87. CONSTRUCTION MANAGEMENT PLAN SHEET: Prior to the issuance of any grading or building permits, the Owner and/or Applicant's design consultant shall submit a construction management plan sheet (full-size) within the plan set that shall incorporate at a minimum the Earth Movement Plan, Project Schedule, employee parking, construction staging area, materials storage area(s), concrete washout(s) and proposed outhouse location(s). Please refer to the Town's [Construction Management Plan Guidelines](#) document for additional information.
 88. WVSD (West Valley Sanitation District): A Sanitary Sewer Clean-out is required for each property at the property line, within one (1) foot of the property line per West Valley Sanitation District Standard Drawing 3, or at a location specified by the Town.
 89. SANITARY SEWER BACKWATER VALVE: Drainage piping serving fixtures which have flood level rims less than twelve (12) inches (304.8 mm) above the elevation of the next upstream manhole and/or flushing inlet cover at the public or private sewer system

serving such drainage piping shall be protected from backflow of sewage by installing an approved type backwater valve. Fixtures above such elevation shall not discharge through the backwater valve, unless first approved by the Building Official. The Town shall not incur any liability or responsibility for damage resulting from a sewer overflow where the property owner or other person has failed to install a backwater valve as defined in the Uniform Plumbing Code adopted by the Town and maintain such device in a functional operation condition. Evidence of West Sanitation District's decision on whether a backwater device is needed shall be provided prior to the issuance of a building permit.

90. **BEST MANAGEMENT PRACTICES (BMPs):** The Owner and/or Applicant is responsible for ensuring that all contractors are aware of all storm water quality measures and that such measures are implemented. Best Management Practices (BMPs) shall be maintained and be placed for all areas that have been graded or disturbed and for all material, equipment and/or operations that need protection. Removal of BMPs (temporary removal during construction activities) shall be replaced at the end of each working day. Failure to comply with the construction BMP will result in the issuance of correction notices, citations, or stop work orders.
91. **STORMWATER DEVELOPMENT RUNOFF:** All new development and redevelopment projects are subject to the stormwater development runoff requirements. The Owner and/or Applicant or their design consultant shall submit a stormwater control plan and implement conditions of approval that reduce stormwater pollutant discharges through the construction, operation and maintenance of treatment measures and other appropriate source control and site design measures. Increases in runoff volume and flows shall be managed in accordance with the development runoff requirements.
92. **REGULATED PROJECT:** The project is classified as a Regulated Project per Provision C.3.b.ii. and is required to implement LID source control, site design, and stormwater treatment on-site in accordance with Provisions C.3.c. and C.3.d..
93. **SITE DESIGN MEASURES:** All projects shall incorporate at least one of the following measures:
 - a. Protect sensitive areas and minimize changes to the natural topography.
 - b. Minimize impervious surface areas.
 - c. Direct roof downspouts to vegetated areas.
 - d. Use porous or pervious pavement surfaces on the driveway, at a minimum.
 - e. Use landscaping to treat stormwater.
94. **GREEN ROOF:** A Green roof may be considered biotreatment systems that treat roof runoff only if they meet certain minimum specifications. The green roof system planting media shall be sufficiently deep to provide capacity within the pore space of the media for the required runoff volume specified by Provision C.3.d.i.(1), in addition to supporting the long-term health of the vegetation selected for the green roof, as specified by a landscape architect or other knowledgeable professional.
95. **UNLAWFUL DISCHARGES:** It is unlawful to discharge any wastewater, or cause hazardous domestic waste materials to be deposited in such a manner or location as to constitute a threatened discharge, into storm drains, gutters, creeks or the San Francisco Bay. Unlawful discharges to storm drains include, but are not limited to: discharges from

toilets, sinks, industrial processes, cooling systems, boilers, fabric cleaning, equipment cleaning or vehicle cleaning.

96. EROSION CONTROL: Interim and final erosion control plans shall be prepared and submitted to the Engineering Division of the Parks and Public Works Department. A maximum of two (2) weeks is allowed between clearing of an area and stabilizing/building on an area if grading is allowed during the rainy season. Interim erosion control measures, to be carried out during construction and before installation of the final landscaping, shall be included. Interim erosion control method shall include, but are not limited to: silt fences, fiber rolls (with locations and details), erosion control blankets, Town standard seeding specification, filter berms, check dams, retention basins, etc. Provide erosion control measures as needed to protect downstream water quality during winter months. The Town of Los Gatos Engineering Division of the Parks and Public Works Department and the Building Department will conduct periodic NPDES inspections of the site throughout the recognized storm season to verify compliance with the Construction General Permit and Stormwater ordinances and regulations.
97. DUST CONTROL: Blowing dust shall be reduced by timing construction activities so that paving and building construction begin as soon as possible after completion of grading, and by landscaping disturbed soils as soon as possible. Further, water trucks shall be present and in use at the construction site. All portions of the site subject to blowing dust shall be watered as often as deemed necessary by the Town, or a minimum of three (3) times daily, or apply (non-toxic) soil stabilizers on all unpaved access roads, parking areas, and staging areas at construction sites in order to insure proper control of blowing dust for the duration of the project. Watering on public streets shall not occur. Streets shall be cleaned by street sweepers or by hand as often as deemed necessary by the Town Engineer, or at least once a day. Watering associated with on-site construction activity shall take place between the hours of 8 a.m. and 5 p.m. and shall include at least one (1) late-afternoon watering to minimize the effects of blowing dust. All public streets soiled or littered due to this construction activity shall be cleaned and swept on a daily basis during the workweek to the satisfaction of the Town. Demolition or earthwork activities shall be halted when wind speeds (instantaneous gusts) exceed twenty (20) miles per hour (MPH). All trucks hauling soil, sand, or other loose debris shall be covered.
98. AIR QUALITY: To limit the project's construction-related dust and criteria pollutant emissions, the following the Bay Area Air Quality Management District (BAAQMD)-recommended basic construction measures shall be included in the project's grading plan, building plans, and contract specifications:
 - a. All exposed surfaces (e.g., parking areas, staging areas, soil piles, graded areas, and unpaved access roads) shall be watered two times per day, or otherwise kept dust-free.
 - b. All haul trucks designated for removal of excavated soil and demolition debris from site shall be staged off-site until materials are ready for immediate loading and removal from site.
 - c. All haul trucks transporting soil, sand, debris, or other loose material off-site shall be covered.
 - d. As practicable, all haul trucks and other large construction equipment shall be staged in areas away from the adjacent residential homes.

- e. All visible mud or dirt track-out onto adjacent public roads shall be removed using wet power vacuum street sweepers at least once per day, or as deemed appropriate by Town Engineer. The use of dry power sweeping is prohibited. An on-site track-out control device is also recommended to minimize mud and dirt-track-out onto adjacent public roads.
 - f. All vehicle speeds on unpaved surfaces shall be limited to fifteen (15) miles per hour.
 - g. All driveways and sidewalks to be paved shall be completed as soon as possible. Building pads shall be laid as soon as possible after grading unless seeding or soil binders are used.
 - h. Post a publicly visible sign with the telephone number and person to contact at the lead agency regarding dust complaints. This person shall respond and take corrective action within forty-eight (48) hours. The Air District's phone number shall also be visible to ensure compliance with applicable regulations.
 - i. All excavation, grading, and/or demolition activities shall be suspended when average wind speeds exceed twenty (20) miles per hour.
 - j. Vegetative ground cover (e.g., fast-germinating native grass seed) shall be planted in disturbed areas as soon as possible and watered appropriately until vegetation is established.
99. **DETAILING OF STORMWATER MANAGEMENT FACILITIES:** Prior to the issuance of any grading or building permits, all pertinent details of any and all proposed stormwater management facilities, including, but not limited to, ditches, swales, pipes, bubble-ups, dry wells, outfalls, infiltration trenches, detention basins and energy dissipaters, shall be provided on submitted plans, reviewed by the Engineering Division of the Parks and Public Works Department, and approved for implementation.
100. **CONSTRUCTION ACTIVITIES:** All construction shall conform to the latest requirements of the CASQA Stormwater Best Management Practices Handbooks for Construction Activities and New Development and Redevelopment, the Town's grading and erosion control ordinance, and other generally accepted engineering practices for erosion control as required by the Town Engineer when undertaking construction activities.
101. **WATER FEATURES:** New swimming pools, hot tubs or spas shall have a connection to the sanitary sewer system, subject to West Valley Sanitation District's authority and standards, to facilitate draining events. Discharges from these features shall be directed to the sanitary sewer and are not allowed into the storm drain system.
102. **SITE DRAINAGE:** Rainwater leaders shall be discharged to splash blocks. No through curb drains will be allowed. On-site drainage systems for all projects shall include one of the alternatives included in section C.3.i of the Municipal Regional NPDES Permit. These include storm water reuse via cisterns or rain barrels, directing runoff from impervious surfaces to vegetated areas and use of permeable surfaces. No improvements shall obstruct or divert runoff to the detriment of an adjacent, downstream or down slope property.
103. **STORM WATER MANAGEMENT PLAN:** A storm water management shall be included with the grading permit application for all Group 1 and Group 2 projects as defined in the amended provisions C.3 of the Municipal Regional Stormwater NPDES Permit, Order R2-2015-0049, NPDES Permit No. CAS612008. The plan shall delineate source control measures and BMPs together with the sizing calculations. The plan shall be certified by a

professional pre-qualified by the Town. In the event that the storm water measures proposed on the Planning approval differ significantly from those certified on the Building/Grading Permit, the Town may require a modification of the Planning approval prior to release of the Building Permit. The Owner and/or Applicant may elect to have the Planning submittal certified to avoid this possibility.

104. STORM WATER MANAGEMENT PLAN CERTIFICATION: Certification from the biotreatment soils provider is required and shall be given to Engineering Division Inspection staff a minimum of thirty (30) days prior to delivery of the material to the job site. Additionally deliver tags from the soil mix shall also be provided to Engineering Division Inspection staff. Sample Certification can be found here: http://www.scvurppp-w2k.com/nd_wp.shtml?zoom_highlight=BIOTREATMENT+SOIL.
105. SILT AND MUD IN PUBLIC RIGHT-OF-WAY: It is the responsibility of Contractor and homeowner to make sure that all dirt tracked into the public right-of-way is cleaned up on a daily basis. Mud, silt, concrete and other construction debris SHALL NOT be washed into the Town's storm drains.
106. GOOD HOUSEKEEPING: Good housekeeping practices shall be observed at all times during the course of construction. All construction shall be diligently supervised by a person or persons authorized to do so at all times during working hours. The Owner and/or Applicant's representative in charge shall be at the job site during all working hours. Failure to maintain the public right-of-way according to this condition may result in penalties and/or the Town performing the required maintenance at the Owner and/or Applicant's expense.
107. PERMIT ISSUANCE: Permits for each phase; reclamation, landscape, and grading, shall be issued simultaneously.
108. COVERED TRUCKS: All trucks transporting materials to and from the site shall be covered.

TO THE SATISFACTION OF THE SANTA CLARA COUNTY FIRE DEPARTMENT:

109. Review of this Developmental proposal is limited to acceptability of site access, water supply and may include specific additional requirements as they pertain to fire department operations, and shall not be construed as a substitute for formal plan review to determine compliance with adopted model codes. Prior to performing any work, the applicant shall make application to, and receive from, the Building Department all applicable construction permits.
110. NOTE: The subject property is located within the Very High Fire Hazard Severity Zone (VHFHSZ) of the Local Responsibility Area (LRA). Pursuant to California Public Resources Code (PRC) 4290, the California Board of Forestry and Fire Protection is required to "...adopt regulations implementing minimum fire safety standards related to defensible space" applicable to "the perimeters and access to all residential, commercial, and industrial building construction." In 2018, the Legislature passed and the Governor signed SB 901 (Dodd), which expanded the applicability of the regulations promulgated under PRC 4290 to land in the Local Responsibility Area (LRA) Very High Fire Hazard Severity Zone. All comments below that result from PRC 4290 are identified by **. Where a conflict exists between local & 4290 requirements, the more stringent

requirement shall apply. California Code of Regulations, Title 14, Division 1.5, Chapter 7, Subchapter

111. WIDTH: (As Noted on Sheet C9) (a) All roads shall be constructed to provide a minimum of two ten (10) foot traffic lanes, not including shoulder and striping. These traffic lanes shall provide for two-way traffic flow to support emergency vehicle and civilian egress, unless other standards are provided in this article or additional requirements are mandated by local jurisdictions or local subdivision requirements. Vertical clearances shall conform to the requirements in California Vehicle Code section 35250. (b) All one-way roads shall be constructed to provide a minimum of one twelve (12) foot traffic lane, not including shoulders. The local jurisdiction may approve one-way roads. (1) All one-way roads shall, at both ends, connect to a road with two traffic lanes providing for travel in different directions, and shall provide access to an area currently zoned for no more than ten (10) residential units. (2) In no case shall a one-way road exceed 2,640 feet in length. A turnout shall be placed and constructed at approximately the midpoint of each one-way road. (c) All driveways shall be constructed to provide a minimum of one (1) ten (10) foot traffic lane, fourteen (14) feet unobstructed horizontal clearance, and unobstructed vertical clearance of thirteen feet, six inches (13' 6"). California Code of Regulations, Title 14, Division 1.5, Chapter 7, Subchapter 2 Articles 1-5, § 1273.01.
112. ROAD SURFACES: (a) Roads shall be designed and maintained to support the imposed load of fire apparatus weighing at least 75,000 pounds and provide an aggregate base. (b) Driveways and road and driveway structures shall be designed and maintained to support at least 40,000 pounds. (c) Project proponent shall provide engineering specifications to support design, if requested by the local authority having jurisdiction. California Code of Regulations, Title 14, Division 1.5, Chapter 7, Subchapter 2, Articles 1-5, § 1273.02.
113. GRADES: (a) At no point shall the grade for all roads and driveways exceed 16 percent. (b) The grade may exceed 16%, not to exceed 20%, with approval from the local authority having jurisdiction and with mitigations to provide for same practical effect. California Code of Regulations, Title 14, Division 1.5, Chapter 7, Subchapter 2, Articles 1-5, § 1273.03.
114. RADIUS: (a) No road or road structure shall have a horizontal inside radius of curvature of less than fifty (50) feet. An additional surface width of four (4) feet shall be added to curves of 50-100 feet radius; two (2) feet to those from 100-200 feet. (b) The length of vertical curves in roadways, exclusive of gutters, ditches, and drainage structures designed to hold or divert water, shall be not less than one hundred (100) feet. California Code of Regulations, Title 14, Division 1.5, Chapter 7, Subchapter 2, Articles 1-5, § 1273.04.
115. TURNAROUND: (As Noted on Sheet C5) (a) Turnarounds are required on driveways and dead-end roads. (b) The minimum turning radius for a turnaround shall be forty (40) feet, not including parking, in accordance with the figures in 14 CCR §§ 1273.05(e) and 1273.05(f). If a hammerhead/T is used instead, the top of the "T" shall be a minimum of sixty (60) feet in length. (c) Driveways exceeding 150 feet in length, but less than 800 feet in length, shall provide a turnout near the midpoint of the driveway. Where the driveway exceeds 800 feet, turnouts shall be provided no more than 400 feet apart. (d) A turnaround shall be provided on driveways over 300 feet in length and shall be within

fifty (50) feet of the building. (e) Each dead-end road shall have a turnaround constructed at its terminus. Where parcels are zoned five (5) acres or larger, turnarounds shall be provided at a maximum of 1,320-foot intervals. (e) Figure A. Turnarounds on roads with two ten-foot traffic lanes. California Code of Regulations, Title 14, Division 1.5, Chapter 7, Subchapter 2, Articles 1-5, § 1273.05.

116. DEAD-END ROADS: (Request of Exception approval shown on sheet C9) (a) The maximum length of a dead-end road, including all dead-end roads accessed from that dead-end road, shall not exceed the following cumulative lengths, regardless of the number of parcels served: parcels zoned for less than one acre - 800 feet. Parcels zoned for 1 acre to 4.99 acres - 1,320 feet. Parcels zoned for 5 acres to 19.99 acres - 2,640 feet. Parcels zoned for 20 acres or larger - 5,280 feet. All lengths shall be measured from the edge of the road surface at the intersection that begins the road to the end of the road surface at its farthest point. Where a dead-end road crosses areas of differing zoned parcel sizes requiring different length limits, the shortest allowable length shall apply. (b) See 14 CCR § 1273.05 for dead-end road turnaround requirements. California Code of Regulations, Title 14, Division 1.5, Chapter 7, Subchapter 2, Articles 1-5, § 1273.08.
117. FIRE SPRINKLERS REQUIRED: (As Noted on Sheet A100) Approved automatic sprinkler systems in new and existing buildings and structures shall be provided in the locations described in this Section or in Sections 903.2.1 through 903.2.12 whichever is the more restrictive and Sections 903.2.14 through 903.2.21. For the purposes of this section, firewalls and fire barriers used to separate building areas shall be constructed in accordance with the California Building Code and shall be without openings or penetrations. 1. An automatic sprinkler system shall be provided throughout all new buildings and structures, other than Group R occupancies, except as follows: a. Buildings and structures not located in any Wildland-Urban Interface and not exceeding 1,200 square feet of fire area. b. Buildings and structures located in any Wildland-Urban Interface Fire Area and not exceeding 500 square feet of fire area. c. Group S-2 or U occupancies, including photovoltaic support structures, used exclusively for vehicle parking which meet all of the following: i. Noncombustible construction. ii. Maximum 5,000 square feet in building area. iii. Structure is open on not less than three (3) sides nor 75% of structure perimeter. iv. Minimum of 10 feet separation from existing buildings, or similar structures, unless area is separated by fire walls complying with California Building Code 706. d. Canopies, constructed in accordance with CBC 406.7.2, used exclusively for weather protection of vehicle fueling pads per CBC 406.7.1 and not exceeding 5,000 square feet of fire area. 2. An automatic sprinkler system shall be installed throughout all new buildings with a Group R fire area. Exception: Accessory Dwelling Unit, provided that all of the following are met: a. The unit meets the definition of an Accessory Dwelling Unit as defined in the Government Code Section 65852.2. b. The existing primary residence does not have automatic fire sprinklers. c. The accessory dwelling unit does not exceed 1,200 square feet in size. d. The unit is on the same lot as the primary residence. e. The unit meets all apparatus access and water supply requirements of Chapter 5 and Appendix B of the 2022 California Fire Code. 3. An approved automatic fire sprinkler system shall be installed in new manufactured homes (as defined in California Health and Safety Code Sections 18007 and 18009) and multifamily manufactured homes with two dwelling units (as defined in California

Health and Safety Code Section 18008.7) in accordance with Title 25 of the California Code of Regulations. 4. An automatic sprinkler system shall be installed throughout existing buildings with a Group R fire area when additions are made causing the fire area to exceed 3,600 square feet. Exception: Additions where all of the following are met: a. Building addition does not exceed 500 square feet. b. The resultant structure meets all water supply requirements of Chapter 5 and Appendix B of the 2022 California Fire Code. 5. An automatic sprinkler system shall be provided throughout existing Group A, B, E, F, L, M, S and U buildings and structures, when additions are made that increase the fire area to more than 3,600 square feet or that create conditions described in Sections 903.2.1 through 903.2.18. 6. Any change in the character of occupancy or in use of any building with a fire area equal to or greater than 3,600 square feet which, in the opinion of the fire code official or building official, would place the building into a more hazardous division of the same occupancy group or into a different group of occupancies and constitutes a greater degree of life safety 1 or increased fire risk 2, shall require the installation of an approved fire automatic fire sprinkler system.

118. FIRE DEPARTMENT (ENGINE) DRIVEWAY TURNAROUND REQUIRED: (As Noted on Sheet C5) Provide an approved fire department engine driveway turnaround with a minimum radius of 40 feet outside. Maximum grade in any direction shall be a maximum of 5%. Installations shall conform with Fire Department Standard Details and Specifications D-1. CFC Sec. 503.
119. FIRE APPARATUS (ENGINE) ACCESS DRIVEWAY REQUIRED: (Letter received) An access driveway shall be provided having an all-weather surface of either asphalt, concrete or other engineered surface capable of supporting 75,000 pounds and approved by a civil engineer. It shall have a minimum unobstructed width of 12 feet, vertical clearance of 13 feet 6 inches, minimum turning radius of 40 feet outside, and a maximum slope of 15%. Installations shall conform to Fire Department Standard Details and Specifications sheet D-1.
120. REQUIRED FIRE FLOW: (Letter received) The minimum required fireflow for this project is 1125 Gallons Per Minute (GPM) at 20 psi residual pressure. This fireflow assumes installation of automatic fire sprinklers per CFC [903.3.1.3]
121. ADDRESS IDENTIFICATION: New and existing buildings shall have approved address numbers, building numbers or approved building identification placed in a position that is plainly legible and visible from the street or road fronting the property. These numbers shall contrast with their background. Where required by the fire code official, address numbers shall be provided in additional approved locations to facilitate emergency response. Address numbers shall be Arabic numbers or alphabetical letters. Numbers shall be a minimum of 6 inches high with a minimum stroke width of 0.5 inch (12.7 mm). Where access is by means of a private road and the building cannot be viewed from the public way, a monument, pole or other sign or means shall be used to identify the structure. Address numbers shall be maintained. CFC Sec. 505.1.
122. WATER SUPPLY REQUIREMENTS: Potable water supplies shall be protected from contamination caused by fire protection water supplies. It is the responsibility of the applicant and any contractors and subcontractors to contact the water purveyor supplying the site of such project, and to comply with the requirements of that purveyor. Such requirements shall be incorporated into the design of any water-based

fire protection systems, and/or fire suppression water supply systems or storage containers that may be physically connected in any manner to an appliance capable of causing contamination of the potable water supply of the purveyor of record. Final approval of the system(s) under consideration will not be granted by this office until compliance with the requirements of the water purveyor of record are documented by that purveyor as having been met by the applicant(s). 2019 CFC Sec. 903.3.5 and Health and Safety Code 13114.7.

123. CONSTRUCTION SITE FIRE SAFETY: All construction sites must comply with applicable provisions of the CFC Chapter 33 and our Standard Detail and Specification S1-7. Provide appropriate notations on subsequent plan submittals, as appropriate to the project. CFC Chp. 33.
124. This review shall not be construed to be an approval of a violation of the provisions of the California Fire Code or of other laws or regulations of the jurisdiction. A permit presuming to give authority to violate or cancel the provisions of the fire code or other such laws or regulations shall not be valid. Any addition to or alteration of approved construction documents shall be approved in advance. [CFC, Ch.1, 105.3.6]