

Rural Vista Design Standards and Guidelines.

Vision

The foundation of beauty in Loxahatchee Groves is harmony with nature and the preservation of the native tree canopy. The following design standards are applicable to all non-residential and non-agricultural development. Development of commercial and civic uses on property is necessary for the sustainability of any community, but such development shall be well-planned and invoke thoughtful design concepts that will enhance and maintain the Town's rural nature. Development projects shall have a consistent architectural style and architectural treatment on buildings shall be consistent on all sides. Development shall take into consideration and attempt to preserve and maintain the existing viable tree canopy. Building design shall be residential in scale and reflect rural character. Pedestrian friendly enhancements such as walkways, trails, porches, benches, boardwalks, outdoor gathering areas shall be incorporated into development projects when possible. Equestrian amenities and trail connections shall be considered when a link to an existing or proposed equestrian trail is near the proposed development.

A. *Site Design.*

1. *Design Objective – Building Placement.* In the rural areas, buildings are generally required to locate in the interior of lots to provide adequate land for open space and tree retention around the perimeter property lines. When the land adjacent to exterior lot lines is kept free from development a variety of design objectives including: screening between incompatible land uses, pedestrian connections between developments, preservation of native vegetation, stormwater mitigation, and wildlife movement can be achieved.

a. *Standards.*

(1) Development projects shall incorporate the existing vegetation into their design. Screening is required adjacent to all exterior property lines, except for points of vehicular or pedestrian access, for new development. Trails, utilities, small accessory structures such as a gazebo or picnic table, and fencing that does not impede wildlife movement may be permitted within required screening areas when the integrity of the screening can be maintained. The following screening standards shall be required, adjacent to

the exterior of a development, for all new divisions of land, commercial, civic uses and utility buildings:

(a) Developments on five (5) acres or less – 35 feet.

(b) Developments on more than five (5) acres – 50 feet.

(2) In Developments that portion of a commercial or civic building that faces the street shall be located at least 25 feet from the screening. When outdoor gathering places are provided, the building is not required to be setback 25 feet from the screening as long as the building is located immediately adjacent to the outdoor gathering place.

b. *Guidelines.*

(1) Existing native vegetation shall be utilized for screening whenever possible. Supplemental landscaping may be necessary to provide an adequate screen. Drought tolerant vegetation is encouraged to avoid irrigation.

(2) Landscaped areas may be suitable for required screening when a site is devoid or deficient in the quality and quantity of screening that is necessary to meet the objectives of this design element.

B. *Building Design.*

1. *Design Objective – Architectural Character and details.* A rural or rustic design theme is required for new development and exterior remodels of all buildings in . This design can be achieved by introducing details such as knee bracing, wood siding, use of trim and siding, covered porches and window treatments. Designs styles reflecting rural character include Colonial, Victorian, Farmhouse, Rustic and Bungalow. (Examples of such designs are included in Exhibit A). Building styles and techniques that create structures with an industrial appearance shall be avoided.

a. *Standards.*

(1) Utilize wood, stone, brick, timber or other traditional building materials. Materials that mimic or simulate the appearance of these materials may be acceptable. Flat walls shall have a textured appearance or the appearance

of a pattern. Buildings shall not appear to be all brick or all rock. Incorporation of brick and rock as elements of the façade is acceptable.

(2) Window patterns shall be characterized by vertical proportions with horizontally oriented rectangular forms prohibited.

(3) The use of reflective or mirrored windows is prohibited.

(4) Tenant specific motifs shall be prohibited. As an alternative, signs may be used to identify a specific tenant.

(5) Standardized corporate or franchised style in the design of new buildings shall be prohibited.

(6) Accessory buildings and/or buildings in out parcels shall be designed of compatible building materials, roof forms, and color as primary structures within the development that conform to these design standards.

(7) Accessory structures and/or buildings in out parcels shall be designed to be architecturally comparable with the primary structure when the primary structure conforms to these design standards. Roof forms, building materials, and color shall be comparable to the primary structure.

(8) Box shaped exposed flat roofs, concrete, flat clay and barrel tile roofs are prohibited on all structures.

(9) Structures may have a hip, gambrel, or mansard roof. Dormers and cupolas are encouraged. Multiuser projects with multiple tenants may use breaks in the roof design to accentuate tenant separation. Roof proportion and pitch shall be relative to residential scale.

(10) All roof mounted equipment must be hidden from view. The roof must act as a parapet to screen mechanical equipment.

(11) Mansard roofs must be a minimum of 3 feet in height and a maximum of 8 feet in height. The pitch of a mansard roof may vary between 30 and 60 degrees.

(12) Multi-paned windows, or the appearance of multi-paned windows, such as one over one, two over two, or four over four patterns is encouraged.

(13) Trim shall be 4-6 inches at the corners of all windows and doors.

(14) The area of first story windows on street front elevations shall be at least twice the area of second story windows along the same side of the building.

2. *Design Objective – Building Mass.* The apparent scale of new commercial and civic developments shall be a human and residential scale.

a. *Standards.*

(1) The use of long blank walls is prohibited. The maximum allowable length of an uninterrupted building elevation is 25 feet. Visual interruptions to the planes of exterior walls shall be achieved through a combination of the following methods:

(a) Modulating building facades at depth of least 4 feet and a width of at least 8 feet.

(b) Prominent facades shall have no wall plane wider than 2.5 times the height of the wall plane.

(c) Provide a covered porch at the building entrances and sides. Porches are not required in the service areas of the building. Porches must have a depth of at least 8 feet and an area of at least 150 feet.

(2) Roof lines shall be interrupted every 50 feet with gable, hip, or dormer roof forms or a vertical shift of at least 5 feet.

(3) Walls of two story or more in height shall have breaks (i.e. canopy, molding, overhang, balcony, banding, or projections) approximately 10 feet above grade.

b. *Guidelines.*

(1) Avoid long, low wall planes

(2) Provide visual shifts in walls and roof surfaces.

3. *Design Objective – Non-vehicular pathways and pedestrian amenities.* Design buildings and developments that are intended for use by the general public with safe and attractive places for pedestrian, bicycle, and equestrian traffic including oriented features such as pedestrian walkways, trails and outdoor gathering places.

a. *Standards.*

(1) All development projects shall provide pathways or trails allowing safe passage. Development projects encompassing more than ten acres should include an outdoor gathering place such as a courtyard, plaza or covered area with seating.

(2) Outdoor gathering places shall be accessible to the pedestrian and equestrian.

(3) All development projects regardless of size shall provide pedestrian access internally and connectivity to adjacent development.

b. *Guidelines.*

(1) Provide shade either with trees or covering for outdoor gathering places.

(2) Mechanical and Waste Screening shall be employed to mask objectionable areas from public view. Concrete walls are prohibited as the primary screening mechanism unless the concrete wall is shielded by landscaping materials on at least three (3) sides.

C. *Color and Material Design.*

1. *Design Objective – Color.* Utilize natural colors that reflected in the approved color palette.

a. *Standards.*

(1) Facade colors shall not be used to identify specific tenants as typified by national corporate fast food restaurants and gasoline stations.

(2) Earth tone colors shall be used for masonry building materials.

(3) Typically, no more than three colors shall be used on one building, however, additional trim colors may be considered if they are a close shade of one of the other three colors.

b. *Guidelines.*

(1) The use of natural wood is encouraged over painting the wood or simulated wood material.

(2) Major architectural trim or details shall complement the main building's base color. Color is normally applied to major architectural trim and details such as window trim, corner siding trim, doors and door frames, knee bracing, and columns.

(3) Minor architectural details shall be highlighted with minor accent color that complements base and major trim color. Minor accent color is normally applied to window sash, doors, storefront frames and small architectural elements.

(4) Murals may be used on building facades and are encouraged to reflect the history or natural landscape of Loxahatchee Groves.

(5) Tinting may be used as an accessory element to a permitted window treatment.

(7) The base color of the main building or a complementary major accent color shall be used for metal roofs.

(8) The use of bold or primary colors for the main body of buildings shall be avoided.

2. *Design Objective – Exterior Building Materials.* Utilize natural materials such as stone, wood, heavy timbers, rough cut lumber or brick as exterior building materials.

a. *Standards.*

(1) Exterior Cladding shall be Stone, Wood textured concrete horizontal lap siding, Wood textured concrete simulated board and batten, Wood horizontal lap siding, Wood Board and Batten, Textured concrete block, brick or materials which simulate the appearance of those materials.

(2) Roof cladding shall be Raised seam metal, composite shake, Corrugated sheet metal, slate tile, or composition roofing shall be used for roof materials.

(3) Window and building trim shall be wood or have the appearance of wood.

(4) Posts or columns shall be wood, concrete with simulated wood texture, rock, stone, or made of materials that mimic or simulate the appearance of the natural materials. Decorative, ornate, or steel columns will have to be specifically approved and determined to be compatible with the overall architectural design and intent of these standards and guidelines.

(5) Porch railings should be wood or have the appearance of wood.

b. Guidelines.

(1) Encourage the use of native stone or brick as an accent.

(2) Building materials used for site features such as fences, and screen walls shall complement a primary on-site structure that conforms to these design standards.

(3) Utilize exterior building materials that simulate natural building materials.

D. Landscaping and Planting Design.

1. *Design Objective – Native Vegetation Screening and Perimeter Buffers.* The retention of native vegetation and significant trees is necessary to preserve and enhance the visual appearance of Loxahatchee Groves. Retaining native vegetation on a development site also supports various environmental systems and provides a better transition between permitted land uses. The retention or replanting of native vegetation is required for all projects. The following standards are intended to supplement the Tree Conservation and Landscape Standards in Chapter 87 .

a. Standards.

(1) Native vegetative screening shall be retained between rural development and roadway. The depth of screening buffers shall be

determined by evaluating the quality and quantity of natural vegetation that is available on the site together with intensity of the proposed use. In no case shall the screen buffer be less than 50 feet wide on projects encompassing more than 5 acres in size and 35 feet wide on projects on 5 acres or less . Supplemental plantings shall be provided when existing native plantings do not provide a complete visual screen.

(2) The native vegetation screening requirements in this Section must provide and maintain a dense screen. Where existing vegetation does not provide adequate screening, additional native plantings may be required. The vegetative screen may only be broken at points of vehicular or pedestrian access.

b. *Guidelines.*

- (1) Setback areas shall be retained in native vegetation where feasible and supplemented by planted native species where native vegetation is sparse or nonexistent.
- (2) Tree retention in clusters is a higher priority than tree retention in lineal strips.
- (3) Regimented parking lots with landscaping limited to a certain number of cars does not create a rural feeling or enhance the rural character of the project.
- (4) More innovative parking areas are needed to avoid the feeling of a sea of cars. Maintenance of existing native tree canopy and liberal use of shrubbery and parking screens, including consideration of parking in the rear rather than the front of the project is encouraged.

Definitions

1. Hip Roof- roof that slopes upward from all sides of a structure, having no vertical ends. The hip is the external angle at which adjacent sloping sides of a roof meet. The degree of such an angle is referred to as the hip bevel. The triangular sloping surface formed by hips that meet at a roof's ridge is called a hip end. A pyramidal hipped roof, also known as pavilion roof, is hipped equally at all

corners and the hips meet at a single peak, but the more common form of hip roof is above a rectangular structure, where a roof ridge meets two hips at either end.

2. Gable Roof - Gable, triangular section of wall at the end of a pitched roof, extending from the eaves to the peak.
3. Gambrel Roof - The gambrel roof is a type of gable roof with two slopes on each side, the upper being less steep than the lower. The mansard roof is a hipped gambrel roof, thus having two slopes on every side
4. Mansard Roof - type of roof having two slopes on every side, the lower slope being considerably steeper than the upper. In cross section the straight-sided mansard can appear like a gambrel roof, but it differs from the gambrel by displaying the same profile on all sides.
5. Outdoor Gathering Place – is any place designed for people to gather and meet, eat or recreate together.

6.

DRAFT