

MEDIUM AND HEAVY TRUCKS (25101600-21-STC)

Exhibit B.3 - Price Sheet - Dump Trucks

Commodity Code: 25101601 (DUMP TRUCKS)

Submitted By:		TAMPA TRUCK CENTER LLC					The Price Sheet is not complete unless used in conjunction with the detailed specifications and Exhibit A, Scope of Work.							
Group No./Name ¹	Base Vehicle Code ²	Base Vehicle Specification ³	GVWR (lbs.) ⁴	Payload Capacity (approx. lbs.) ⁵	Accepted Brands ⁶	Manufacturer/Brand ⁷	Representative Model ⁸	Representative Model Number ⁹	Base Vehicle Price (\$###,###.##) ¹⁰	OEM Options Discount (##%) ¹¹	Non-OEM Options Discount (##%) ¹²	Customer Pick-Up Discount (\$(#,###.##)) ¹⁴	Estimated Lead Time in Days (##) ¹⁵	
Group 3 - Dump Trucks	310	4 CU YD DUMP TRUCK, SINGLE AXLE, CLASS 7, 28,000 LBS. GVWR (4x2)	28,000	13,850	FORD F-SERIES, FREIGHTLINER M2, INTERNATIONAL MV/CV SERIES, OR APPROVED EQUIVALENT	FREIGHTLINER	M2	106	\$ 82,563.00	3%	0%	\$ (200.00)	120-180	
	320	5 CU YD DUMP TRUCK, SINGLE AXLE, CLASS 7, 33,000 LBS. GVWR (4x2)	33,000	18,200	FORD F-SERIES, FREIGHTLINER M2, INTERNATIONAL MV/CV SERIES, OR APPROVED EQUIVALENT	FREIGHTLINER	M2	106	\$ 86,998.00	3%	0%	\$ (200.00)	120-180	
	330	4 CU YD DUMP TRUCK, SINGLE AXLE, CREW CAB, CLASS 7, 28,000 LBS. GVWR (4x2)	28,000	12,950	FORD F-SERIES, FREIGHTLINER M2, INTERNATIONAL MV/CV SERIES, OR APPROVED EQUIVALENT	FREIGHTLINER	M2	106	\$ 89,240.00	3%	0%	\$ (200.00)	120-180	
	340	5 CU YD DUMP TRUCK, SINGLE AXLE, CREW CAB, CLASS 7, 33,000 LBS. GVWR (4x2)	33,000	17,350	FORD F-SERIES, FREIGHTLINER M2, INTERNATIONAL MV/CV SERIES, OR APPROVED EQUIVALENT	FREIGHTLINER	M2	106	\$ 93,974.00	3%	0%	\$ (200.00)	120-180	
	350	8 YARD DUMP TRUCK, 7.6L ENGINE, TANDEM AXLE, CLASS 8, 52,000 LBS. GVWR (6X4)	52,000	30,550	FREIGHTLINER M2/108/114/122, INTERNATIONAL LONESTAR/LT/RH SERIES, OR APPROVED EQUIVALENT	FREIGHTLINER	M2	106	\$ 98,268.00	3%	0%	\$ (200.00)	120-180	
	360	8 YARD DUMP TRUCK, 7.2L ENGINE, TANDEM AXLE, CLASS 8, 52,000 LBS. GVWR (6X4)	52,000	30,550	FREIGHTLINER M2/108/114/122, INTERNATIONAL LONESTAR/LT/RH SERIES, OR APPROVED EQUIVALENT	FREIGHTLINER	M2	106	\$ 96,249.00	3%	0%	\$ (200.00)	120-180	
	370	12 YARD DUMP TRUCK, 8.8L ENGINE, TANDEM AXLE, CLASS 8, 64,000 LBS. GVWR (6X4)	64,000	41,800	FREIGHTLINER M2/108/114/122, INTERNATIONAL LONESTAR/LT/RH SERIES, OR APPROVED EQUIVALENT	FREIGHTLINER	M2	106	\$ 106,887.00	3%	0%	\$ (200.00)	120-180	
	380	12 YARD DUMP TRUCK, 8.3L ENGINE, TANDEM AXLE, CLASS 8, 64,000 LBS. GVWR (6X4)	64,000	41,800	FREIGHTLINER M2/108/114/122, INTERNATIONAL LONESTAR/LT/RH SERIES, OR APPROVED EQUIVALENT	FREIGHTLINER	M2	106	\$ 106,330.00	3%	0%	\$ (200.00)	120-180	

MEDIUM AND HEAVY TRUCKS (25101600-21-STC)

Exhibit B.3 - Price Sheet - Dump Trucks

Commodity Code: 25101601 (DUMP TRUCKS) **Truck Body Specifications: 4 CUBIC YARD HEAVY-DUTY DUMP BODY**

Submitted By: TAMPA TRUCK CENTER LLC **The detailed specifications are not complete unless used in conjunction with the Price Sheet and Exhibit A, Scope of Work.**

Base Vehicle Code ²	Base Vehicle Specification ³	GVWR (lbs.) ⁴	Payload Capacity (approx. lbs.) ⁵	Accepted Brands ⁶	Intended Use
310	4 CU YD DUMP TRUCK, SINGLE AXLE, CLASS 7, 28,000 LBS. GVWR (4x2)	28,000	13,850	FORD F-SERIES, FREIGHTLINER M2, INTERNATIONAL MV/CV SERIES, OR APPROVED EQUIVALENT	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, TRASH, ETC. THIS VEHICLE IS RECOMMENDED TO TRANSPORT UP TO 3 INDIVIDUALS.

Manufacturer/Brand ⁷	Representative Model ⁸	Representative Model Number ⁹	Base Vehicle Price (\$###,###.##) ¹⁰	OEM Options Discount (##%) ¹¹	Non-OEM Options Discount (##%) ¹²	Customer Pick-Up Discount (\$#,###.##) ¹⁴	Estimated Lead Time in Days (###) ¹⁵
FREIGHTLINER	M2	106	\$ 82,563.00	3%	0%	\$ (200.00)	120-180

Specification Category ¹⁶	Section ¹⁷	Sub-section ¹⁸	Base Vehicle Specification Details ¹⁹	Representative Model Specification ²⁰	Options Specification Information ²¹						
					Option Availability ²²	Option Manufacturer ²³	Option Model Number ²⁴	Option CA Length ²⁵	Option Type ²⁶	Option MSRP ²⁷	Option Price ²⁸

ENGINE:	10	A.	Diesel engine, 5.9L, 210 Gross HP (per the latest issue of SAE J1349) and 520 lbs.-ft. Gross Torque, minimum.	Liters: 6.7 Gross HP: 220 Gross Torque: 520																
		B.	Emissions shall meet or exceed all applicable federal and State of Florida emissions and environmental laws, regulations, specifications, standards, and requirements in effect as of the date of manufacture.	Engine/Emissions Type: CUMMINS/SCR Urea Tank Size (in gallons), if required: 6																
		C.	Standard cooling system with antifreeze.																	
		D.	Dry type air cleaner with service (restriction) indicator.																	
		E.	Engine protection system, at a minimum, must be activated by low engine oil pressure, and high engine temperature. System shall, at a minimum, include a warning light(s) and derate (ramp down) feature that will reduce engine power and speed, or shut down the engine when any of these functions exceed normal limits.																	

ELECTRICAL SYSTEM:	12	A.	Minimum 100 amps 12 v. alternator.															
		B.	Batteries to have a minimum total of 1100 CCA @ 0 degrees F.															

TRANSMISSION:	20	A.	Automatic transmission, 5-speed minimum, with provisions for a PTO. Allison 2500RDS, or Approved Equivalent.															
		B.	Electronic PTO overspeed control. Chelsea, Muncie, or Approved Equivalent.	Manufacturer: MUNCIE Model Number: SPD-1000														

AXLES & SUSPENSION:	30	A.	Steel front axle and suspension, minimum 9,000 lbs. capacity.																	
		B.	Front shock absorbers.																	
		C.	Front wheel oil-lubricated bearings and seals.																	
		D.	Single speed rear axle and suspension, minimum 19,000 lbs. capacity. Rear axle ratio is to be a 5.57/5.71 for 2400 RPM engines, 5.57/5.71/5.86/5.88 for 2500 RPM engines, 6.14/6.43/6.50 for 2800 RPM engines, or the closest possible ratio available that will provide a top speed of approximately 65 MPH.	Rear Suspension Capacity (lbs.): 19000 Rear Axle Ratio: 6.14 Engine RPM: 2600 Top Speed (MPH): 67																
		E.	Front wheel hubs and rear axle shall be filled with synthetic lubricant.																	
		F.	Auxiliary rear leaf spring(s) or rubber helper.																	
		G.	"No-Spin" or driver control traction differential (DCDL) on rear axle.																	

PERFORMANCE ITEMS:	40	A.	Factory installed speedometer; odometer, ammeter or voltmeter, fuel gauge, engine oil pressure gauge, coolant temperature gauge, tachometer, air pressure gauge and dash mounted engine hour meter.															
		B.	Power steering.															

COMFORT ITEMS:	50	A.	Factory installed AM-FM stereo radio with 2 speakers and antenna.																
		B.	Air conditioner with integral heater and defroster.																
		C.	Arm rests both sides, if available; sun visors, both sides.																
		D.	Tinted glass all windows, including windshield.																

		A.	Air horn(s), mounted under the cab or hood, or behind the front bumper.															
		B.	Standard electric horn.															
		C.	Outside mirrors, left and right side. Mirrors to be 6 x 12 inches, minimum, with convex mirrors on both sides. Mirrors and brackets shall be of rust and corrosive resistance materials such as stainless steel, aluminum, coated metals or composite materials. Painted mirrors and brackets are not acceptable.															

Specification Category ¹⁶	Section ¹⁷	Sub-section ¹⁸	Base Vehicle Specification Details ¹⁹	Representative Model Specification ²⁰	Options Specification Information ²¹						
					Option Availability ²²	Option Manufacturer ²³	Option Model Number ²⁴	Option CA Length ²⁵	Option Type ²⁶	Option MSRP ²⁷	Option Price ²⁸
SAFETY ITEMS:	60	D.	Automatic-adjustable volume backup alarm. Must meet latest issue of SAE J994, Type B, 107dB (A). Factory or dealer installed.								
		E.	Rain Flaps: Splash and spray suppressant rain flaps, straight grass type, installed on heavy-duty hangers. Factory or dealer installed. NO VENDOR ADVERTISING OR IDENTIFICATION WILL BE PERMITTED ON RAIN FLAPS.								
		F.	All access steps shall be self-cleaning slip-resistant grating.								
		G.	Daytime running lights.								
BRAKES:	62	A.	ABS air brake system, minimum 13.2 cfm air compressor.								
		B.	Spring applied parking brake.								
		C.	Front and rear automatic slack adjusters.								
		D.	Front and rear dust shields.								
		E.	Outboard mounted brake drums, front and rear, if available. (NOTE: Allows brake repair without removing axle hubs.)								
		F.	Low air pressure warning indicator.								
		G.	Air dryer with heater. Bendix AD-9, AD-IP, AD-IS, Wabco System Saver 1200, or Approved Equivalent.	Air Dryer with Heater Type:	AD-9						
TIRES & WHEELS:	70	A.	6, 275/80R22.5G (14PR) or 295/75R22.5G (14PR) or larger, tubeless, low profile, radial tires with highway tread.								
		B.	All wheels to be 1-piece steel disc, 10-hole, I.S.O. hub pilot mount, 22.5 inch diameter.								
		C.	Front, inside rear and outside rear wheels to be fully interchangeable.								
CHASSIS, FRAME, CAB:	80	A.	Minimum 28,000 lbs. GVWR, factory certified.	GVWR (lbs.):	29000						
		B.	Minimum 859,000 in-lbs. RBM frame.	Frame RBM (lbs.):	1479600						
		C.	Cab-to-axle (CA) dimension as recommended by the body manufacturer. CA must provide a cab/body (CB) clearance of 3 to 5 inches.	Cab/Body (CB) Clearance:	75						
		D.	Factory installed fuel tank(s), minimum 70 U.S. gallons.	Fuel Tank(s) Capacity:	80						
		E.	Front tow hooks or tow pins.								
		F.	Standard front bumper.								
CAB EQUIPMENT:	82	A.	Conventional cab, with tilt-type hood and fender assembly.								
		B.	Full-width bench seat or individual driver seat with 2-man passenger seat.								
		C.	Grab handle(s) for cab entry, located at each entry door.								
		D.	Manufacturer's standard paint and colors.								
		E.	Rear cab window with fixed tinted glass.								
BODY:	84	A.	4 cu. yd. dump body, installed, with hoist and electric roll-up dump body tarp system, as per Specification: DUMP-4.	Body Manufacturer:	OX						
				Model Number:	MV8508						
				Hoist Manufacturer:	RUGBY						
Hoist Model Number:	5020										
Tarp Manufacturer:	MOUNTAIN										
Tarp Model Number:	10-16										
B.	Vehicle shall meet all requirements of Title 49, Code of Federal Regulations, and 393.86 rear end protection.										
C.	Body, hoist and electric roll-up dump body tarp system must be installed on the chassis and ready for use upon delivery.										
CONDITIONS:	90	A.	Respondent shall provide a manufacturer's print-out (Ford "DORA"/"Commercial Truck Tools", Freightliner "Spec Pro", International "Vehicle Specifications", Mack "Order/Customer/Vehicle Information", or Approved Equivalent) to verify the vehicle bid meets all the requirements of this specification. Also, any dealer installed aftermarket components, if specified, must be noted on the manufacturer's print-out.								
		B.	Welding shall not be permitted on the frame side rails, nor shall the frame rails be cut to lengthen or shorten the wheelbase. Wheelbase modifications are allowed only by sliding the suspension with the "AF" dimension affected accordingly (excess length behind the rear axle may be cut off as required). Any wheelbase modification shall result in a wheelbase and frame combination that is identical to one available from the manufacturer.								
		C.	Paint numbers are referenced only to identify colors.								

Specification Category ¹⁶	Section ¹⁷	Sub-section ¹⁸	Base Vehicle Specification Details ¹⁹	Representative Model Specification ²⁰	Options Specification Information ²¹								
					Option Availability ²²	Option Manufacturer ²³	Option Model Number ²⁴	Option CA Length ²⁵	Option Type ²⁶	Option MSRP ²⁷	Option Price ²⁸	Option Calculated Discount ²⁹	
OPTIONS:	20.01		Manual transmission, 6-speed minimum, with provisions for a PTO. Transmission must have a minimum low gear reduction of 9.01:1. Rear axle ratio shall be a 4.10/4.11 for 2400 RPM engines, 4.30/4.33 for 2500 RPM engines, 4.78/4.88 for 2800 RPM engines, or the closest possible ratio available that will provide a top speed of approximately 65 MPH. Transmission shall be filled with synthetic lubricant.	Rear Axle Ratio: 4.63	AC	FULLER	FS6406A		OEM		\$ (1,385.00)	Available (Credit)	
		Engine RPM: 2600											
		Top Speed (MPH): 67											
		30.01		Manufacturer's standard 4x4 drive system model in lieu of base equipment 4x2 model. Note: Provide only the difference in price between the 2-wheel drive model and the manufacturer's standard 4x4 model offered.		AC	MERITOR	400-103		OEM	\$ 31,606.00	\$ 30,657.00	3.00%
		50.01		Rain shields over door windows, both sides. Auto Ventshade Co., or Approved Equivalent. Factory or dealer installed.		AC				Non-OEM	\$ 200.00	\$ 200.00	0.00%
		60.01		Front clearance indicators. Factory or dealer installed. (Indicators shall be approximately 36 inches in length located on the left and right front corners of the vehicle.)		AC				Non-OEM	\$ 300.00	\$ 300.00	0.00%
		62.01		Automatic air brake drain system. ClearDrain System, or Approved Equivalent. Bid in lieu of the air dryers specified in Section 62. G. Unit must be installed by the vehicle manufacturer. Dealer installed units are not acceptable.		AC	CLEAR DRAIN	477-022		OEM	\$ 2,280.00	\$ 2,211.00	3.03%
		70.01		Tubeless radial tires with on/off highway tread for rear only. Bid 4, 11R22.5G (14PR) or larger tires for on/off highway use and 2, 11R22.5G (14PR) or larger tires for highway use. Rear tires to be Bridgestone M711, General D450, Goodyear G164 RTD, Michelin XDE, Hankook Z35A, Double Coin RR150, Continental HDL, or Approved Equivalent.	Front Tire Code: 093-1G4	AC				OEM	\$ 352.00	\$ 341.00	3.13%
			Rear Tire Code: 094-ODH										
		80.01		Pintle hook, installed. To be swivel type and must have a capacity of 49,000 lbs. gross trailer weight and 9800 lbs. vertical load, minimum. Hook shall be installed no more than 14 inches forward from the end of the body as measured from the center of the eye. Holland Model PH-760, Wallace Model B30, or Approved Equivalent.		AC	WALLACE	B30		Non-OEM	\$ 1,850.00	\$ 1,850.00	0.00%
		80.02		Air brake package for straight truck and trailer. Full trailer air brake controls with air lines, glad hands and wiring routed to the rear end of the frame.		AC		019-001		OEM	\$ 1,027.00	\$ 996.00	3.02%
		82.01		Special state color. DOT Yellow (DuPont Centari L9069A, Freightliner 3258, International 4421).		NC		980-4H9		OEM			Available (No Cost)
	82.02		2-tone colors. Manufacturer's standard 2-tone colors.		AC		065-902		OEM	\$ 1,426.00	\$ 1,383.00	3.02%	
	84.01		Vibrator installed on dump body. Phillips Temro, Inc., Model VIBRA 2000, or Approved Equivalent. To be installed on mounting base rather than dump body floor plate.		AC	PHILLIPS	VIBRA2000		Non-OEM	\$ 1,490.00	\$ 1,490.00	0.00%	

MEDIUM AND HEAVY TRUCKS (25101600-21-STC)															
Exhibit B.3 - Price Sheet - Dump Trucks															
Commodity Code: 25101601 (DUMP TRUCKS)						Truck Body Specifications: 5 CUBIC YARD HEAVY-DUTY DUMP BODY									
Submitted By:			TAMPA TRUCK CENTER LLC			The detailed specifications are not complete unless used in conjunction with the Price Sheet and Exhibit A, Scope of Work.									
Base Vehicle Code ²		Base Vehicle Specification ³				GVWR (lbs.) ⁴	Payload Capacity (approx. lbs.) ⁵	Accepted Brands ⁶			Intended Use				
320		5 CU YD DUMP TRUCK, SINGLE AXLE, CLASS 7, 33,000 LBS. GVWR (4x2)				33,000	18,200	FORD F-SERIES, FREIGHTLINER M2, INTERNATIONAL MV/CV SERIES, OR APPROVED EQUIVALENT			HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, TRASH, ETC. THIS VEHICLE IS RECOMMENDED TO TRANSPORT UP TO 3 INDIVIDUALS.				
Manufacturer/Brand ⁷		Representative Model ⁸		Representative Model Number ⁹	Base Vehicle Price (\$###,###.##) ¹⁰	OEM Options Discount (##%) ¹¹	Non-OEM Options Discount (##%) ¹²	Customer Pick-Up Discount (\$#,###.##) ¹⁴	Estimated Lead Time in Days (###) ¹⁵						
FREIGHTLINER		M2		106	\$ 86,998.00	3%	0%	\$ (200.00)	120-180						
Specification Category ¹⁶		Section ¹⁷	Sub-section ¹⁸	Base Vehicle Specification Details ¹⁹		Representative Model Specification ²⁰		Options Specification Information ²¹							
						Option Availability ²²	Option Manufacturer ²³	Option Model Number ²⁴	Option CA Length ²⁵	Option Type ²⁶	Option MSRP ²⁷	Option Price ²⁸	Option Calculated Discount ²⁹		
ENGINE:		10	A.	Diesel engine, 5.9L, 210 Gross HP (per the latest issue of SAE J1349) and 560 lbs.-ft. Gross Torque, minimum.		Liters:	6.7	Gross HP:	220	Gross Torque:	600				
			B.	Emissions shall meet or exceed all applicable federal and State of Florida emissions and environmental laws, regulations, specifications, standards, and requirements in effect as of the date of manufacture.		Engine/Emissions Type:	CUMMIN/SCR	Urea Tank Size (in gallons), if required:	6						
			C.	Standard cooling system with antifreeze.											
			D.	Dry type air cleaner with service (restriction) indicator.											
			E.	Engine protection system, at a minimum, must be activated by low engine oil pressure, and high engine temperature. System shall, at a minimum, include a warning light(s) and derate (ramp down) feature that will reduce engine power and speed, or shut down the engine when any of these functions exceed normal limits.											
ELECTRICAL SYSTEM:		12	A.	Minimum 100 amps 12 v. alternator.											
			B.	Batteries to have a minimum total of 1100 CCA @ 0 degrees F.											
TRANSMISSION:		20	A.	Automatic transmission, 6-speed minimum, (International may bid a 5-speed, if required for the engine bid) with provisions for a PTO. Allison 3500RDS, or Approved Equivalent.		Manufacturer:	MUNCIE	Model Number:	SPD-1000						
			B.	Electronic PTO overspeed control. Chelsea, Muncie, or Approved Equivalent.											
AXLES & SUSPENSION:		30	A.	Steel front axle and suspension, minimum 12,000 lbs. capacity.											
			B.	Front shock absorbers.											
			C.	Front wheel oil-lubricated bearings and seals.											
			D.	Single speed rear axle and suspension, minimum 21,000 lbs. capacity. Rear axle ratio is to be a 6.14/6.43/6.50 for 2400 RPM engines, 6.50/6.83/6.86 for 2500 RPM engines, 6.43/6.50 for a 2800 RPM engines, (International - 6.14/6.17 for a 2600 RPM engine), or the closest possible ratio available that will provide a top speed of approximately 65 MPH.		Rear Suspension Capacity (lbs.):	21000	Rear Axle Ratio:	6.83	Engine RPM:	2600	Top Speed (MPH):	68		
			E.	Front wheel hubs and rear axle shall be filled with synthetic lubricant.											
			F.	Auxiliary rear leaf spring(s) or rubber helper.											
			G.	"No-Spin" or driver control traction differential (DCDL) on rear axle.											
PERFORMANCE ITEMS:		40	A.	Factory installed speedometer, odometer, ammeter or voltmeter, fuel gauge, engine oil pressure gauge, coolant temperature gauge, tachometer, air pressure gauge and dash mounted engine hour meter.											
			B.	Power steering.											
COMFORT ITEMS:		50	A.	Factory installed AM-FM stereo radio with 2 speakers and antenna.											
			B.	Air conditioner with integral heater and defroster.											
			C.	Arm rests both sides, if available; sun visors, both sides.											
			D.	Tinted glass all windows, including windshield.											
			A.	Air horn(s), mounted under the cab or hood, or behind the front bumper.											
			B.	Standard electric horn.											
			C.	Outside mirrors, left and right side. Mirrors to be 6 x 12 inches, minimum, with convex mirrors on both sides. Mirrors and brackets shall be of rust and corrosive resistance materials such as stainless steel, aluminum, coated metals or composite materials. Painted mirrors and brackets are not acceptable.											

Specification Category ¹⁶	Section ¹⁷	Sub-section ¹⁸	Base Vehicle Specification Details ¹⁹	Representative Model Specification ²⁰	Options Specification Information ²¹						
					Option Availability ²²	Option Manufacturer ²³	Option Model Number ²⁴	Option CA Length ²⁵	Option Type ²⁶	Option MSRP ²⁷	Option Price ²⁸
SAFETY ITEMS:	60	D.	Automatic-adjustable volume backup alarm. Must meet latest issue of SAE J994, Type B, 107dB (A). Factory or dealer installed.								
		E.	Rain Flaps: Splash and spray suppressant rain flaps, straight grass type, installed on heavy-duty hangers. Factory or dealer installed.								
		F.	All access steps shall be self-cleaning slip-resistant grating.								
		G.	Daytime running lights.								
BRAKES:	62	A.	ABS air brake system, minimum 13.2 cfm air compressor.								
		B.	Spring applied parking brake.								
		C.	Front and rear automatic slack adjusters.								
		D.	Front and rear dust shields.								
		E.	Outboard mounted brake drums, front and rear, if available. (NOTE: Allows brake repair without removing axle hubs.)								
		F.	Low air pressure warning indicator.								
		G.	Air dryer with heater. Bendix AD-9, AD-IP, AD-IS, Wabco System Saver 1200, or Approved Equivalent.	Air Dryer with Heater Type:	AD-9						
TIRES & WHEELS:	70	A.	6, 275/80R22.5G (14PR) or 295/75R22.5G (14PR) or larger, tubeless, low profile, radial tires with highway tread.								
		B.	All wheels to be 1-piece steel disc, 10-hole, I.S.O. hub pilot mount, 22.5 inch diameter.								
		C.	Front, inside rear and outside rear wheels to be fully interchangeable.								
CHASSIS, FRAME, CAB:	80	A.	Minimum 33,000 lbs. GVWR, factory certified.	GVWR (lbs.):	33000						
		B.	Minimum 1,700,000 in-lbs. RBM frame.	Frame RBM (lbs.):	1808400						
		C.	Cab-to-axle (CA) dimension as recommended by the body manufacturer. CA must provide a cab/body (CB) clearance of 3 to 5 inches.	Cab/Body (CB) Clearance:	84						
		D.	Factory installed fuel tank(s), minimum 70 U.S. gallons.	Fuel Tank(s) Capacity:	80						
		E.	Front tow hooks or tow pins.								
		F.	Standard front bumper.								
CAB EQUIPMENT:	82	A.	Conventional cab, with tilt-type hood and fender assembly.								
		B.	Full-width bench seat or individual driver seat with 2-man passenger seat.								
		C.	Grab handle(s) for cab entry, located at each entry door.								
		D.	Manufacturer's standard paint and colors.								
		E.	Rear cab window with fixed tinted glass.								
BODY:	84	A.	5 cu. yd. dump body, installed, with hoist and electric roll-up dump body tarp system, as per Specification: DUMP-5.	Body Manufacturer:	OX						
				Model Number:	MV8510						
				Hoist Manufacturer:	RUGBY						
				Hoist Model Number:	5020						
				Tarp Manufacturer:	MOUNTAIN						
		Tarp Model Number:	10-16								
		B.	Vehicle shall meet all requirements of Title 49, Code of Federal Regulations, and 393.86 rear end protection.								
C.	Body, hoist and electric roll-up dump body tarp system must be installed on the chassis and ready for use upon delivery.										
CONDITIONS:	90	A.	Respondent shall provide a manufacturer's print-out (Ford "DORA"/"Commercial Truck Tools", Freightliner "Spec Pro", International "Vehicle Specifications", Mack "Order/Custom/Vehicle Information", or Approved Equivalent) to verify the vehicle bid meets all the requirements of this specification. Also, any dealer installed aftermarket components, if specified, must be noted on the manufacturer's print-out.								
		B.	Welding shall not be permitted on the frame side rails, nor shall the frame rails be cut to lengthen or shorten the wheelbase. Wheelbase modifications are allowed only by sliding the suspension with the "AF" dimension affected accordingly (excess length behind the rear axle may be cut off as required). Any wheelbase modification shall result in a wheelbase and frame combination that is identical to one available from the manufacturer.								
		C.	Paint numbers are referenced only to identify colors.								

Specification Category ¹⁶	Section ¹⁷	Sub-section ¹⁸	Base Vehicle Specification Details ¹⁹	Representative Model Specification ²⁰		Options Specification Information ²¹							
						Option Availability ²²	Option Manufacturer ²³	Option Model Number ²⁴	Option CA Length ²⁵	Option Type ²⁶	Option MSRP ²⁷	Option Price ²⁸	Option Calculated Discount ²⁹
OPTIONS:	20.01		Manual transmission, 6-speed minimum, with provisions for a PTO. Transmission must have a minimum low gear reduction of 9.01:1. Rear axle ratio shall be a 4.10/4.11 for 2400 RPM engines, 4.30/4.33 for 2500 RPM engines, 4.88/4.89 for 2800 RPM engines, or the closest possible ratio available that will provide a top speed of approximately 65 MPH. Transmission shall be filled with synthetic lubricant.	Rear Axle Ratio: 4.63	AC	FULLER	FS6406A		OEM		\$ (1,385.00)	Available (Credit)	
		Engine RPM: 2600											
		Top Speed (MPH): 66											
		30.01		Manufacturer's standard 4x4 drive system model in lieu of base equipment 4x2 model. Note: Provide only the difference in price between the 2-wheel drive model and the manufacturer's standard 4x4 model offered.		AC	MERITOR	400-103		OEM	\$ 31,606.00	\$ 30,657.00	3.00%
		50.01		Rain shields over door windows, both sides. Auto Ventshade Co., or Approved Equivalent. Factory or dealer installed.		AC				Non-OEM	\$ 200.00	\$ 200.00	0.00%
		60.01		Front clearance indicators. Factory or dealer installed. (Indicators shall be approximately 36 inches in length located on the left and right front corners of the vehicle.)		AC				Non-OEM	\$ 300.00	\$ 300.00	0.00%
		62.01		Automatic air brake drain system. ClearDrain System, or Approved Equivalent. Bid in lieu of the air dryers specified in Section 62. G. Unit must be installed by the vehicle manufacturer. Dealer installed units are not acceptable.		AC	CLEAR DRAIN	477-022		OEM	\$ 2,280.00	\$ 2,211.00	3.03%
		70.01		Tubeless radial tires with on/off highway tread for rear only. Bid 4, 11R22.5G (14PR) or larger tires for on/off highway use and 2, 11R22.5G (14PR) or larger tires for highway use. Rear tires to be Bridgestone M711, General D450, Goodyear G164 RTD, Michelin XDE, Hankook Z35A, Double Coin RR150, Continental HDL, or Approved Equivalent.	Front Tire Code: 093-930	AC				OEM	\$ 886.00	\$ 859.00	3.05%
			Rear Tire Code: 094-287										
		80.01		Pintle hook, installed. To be swivel type and must have a capacity of 49,000 lbs. gross trailer weight and 9800 lbs. vertical load, minimum. Hook shall be installed no more than 14 inches forward from the end of the body as measured from the center of the eye. Holland Model PH-760, Wallace Model B30, or Approved Equivalent.		AC	WALLACE	B30		Non-OEM	\$ 1,850.00	\$ 1,850.00	0.00%
		80.02		Air brake package for straight truck and trailer. Full trailer air brake controls with air lines, glad hands and wiring routed to the rear end of the frame.		AC		019-001		OEM	\$ 1,027.00	\$ 996.00	3.02%
		82.01		Special state color. DOT Yellow (DuPont Centari L9069A, Freightliner 3258, International 4421).		NC		980-4H9		OEM			Available (No Cost)
	82.02		2-tone colors. Manufacturer's standard 2-tone colors.		AC		065-902		OEM	\$ 1,426.00	\$ 1,383.00	3.02%	
	84.01		Vibrator installed on dump body. Phillips Temro, Inc., Model VIBRA 2000, or Approved Equivalent. To be installed on mounting base rather than dump body floor plate.		AC	PHILLIPS	VIBRA2000		Non-OEM	\$ 1,490.00	\$ 1,490.00	0.00%	

MEDIUM AND HEAVY TRUCKS (25101600-21-STC)

Exhibit B.3 - Price Sheet - Dump Trucks

Commodity Code: 25101601 (DUMP TRUCKS) **Truck Body Specifications: 4 CUBIC YARD HEAVY-DUTY DUMP BODY**

Submitted By: TAMPA TRUCK CENTER LLC **The detailed specifications are not complete unless used in conjunction with the Price Sheet and Exhibit A, Scope of Work.**

Base Vehicle Code ²	Base Vehicle Specification ³	GVWR (lbs.) ⁴	Payload Capacity (approx. lbs.) ⁵	Accepted Brands ⁶	Intended Use
330	4 CU YD DUMP TRUCK, SINGLE AXLE, CREW CAB, CLASS 7, 28,000 LBS. GVWR (4x2)	28,000	12,950	FORD F-SERIES, FREIGHTLINER M2, INTERNATIONAL MV/CV SERIES, OR APPROVED EQUIVALENT	HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, TRASH, ETC. THIS VEHICLE HAS 4 FULL SIZE DOORS AND IS RECOMMENDED TO TRANSPORT 4 TO 6 INDIVIDUALS.

Manufacturer/Brand ⁷	Representative Model ⁸	Representative Model Number ⁹	Base Vehicle Price (\$###,###.##) ¹⁰	OEM Options Discount (##%) ¹¹	Non-OEM Options Discount (##%) ¹²	Customer Pick-Up Discount (\$#.###.##) ¹⁴	Estimated Lead Time in Days (###) ¹⁵
FREIGHTLINER	M2	106	\$ 89,240.00	3%	0%	\$ (200.00)	120-180

Specification Category ¹⁶	Section ¹⁷	Sub-section ¹⁸	Base Vehicle Specification Details ¹⁹	Representative Model Specification ²⁰	Options Specification Information ²¹						
					Option Availability ²²	Option Manufacturer ²³	Option Model Number ²⁴	Option CA Length ²⁵	Option Type ²⁶	Option MSRP ²⁷	Option Price ²⁸

ENGINE:	10	A.	Diesel engine, 5.9L, 210 Gross HP (per the latest issue of SAE J1349) and 520 lbs.-ft. Gross Torque, minimum.	Liters: 6.7	Gross HP: 220	Gross Torque: 520
		B.	Emissions shall meet or exceed all applicable federal and State of Florida emissions and environmental laws, regulations, specifications, standards, and requirements in effect as of the date of manufacture.	Engine/Emissions Type: CUMMINS/SCR	Urea Tank Size (in gallons), if required: 6	
		C.	Standard cooling system with antifreeze.			
		D.	Dry type air cleaner with service (restriction) indicator.			
		E.	Engine protection system, at a minimum, must be activated by low engine oil pressure, and high engine temperature. System shall, at a minimum, include a warning light(s) and derate (ramp down) feature that will reduce engine power and speed, or shut down the engine when any of these functions exceed normal limits.			

ELECTRICAL SYSTEM:	12	A.	Minimum 100 amps 12 v. alternator.
		B.	Batteries to have a minimum total of 1100 CCA @ 0 degrees F.

TRANSMISSION:	20	A.	Automatic transmission, 5-speed minimum, with provisions for a PTO. Allison 2500RDS, or Approved Equivalent.
		B.	Electronic PTO overspeed control. Chelsea, Muncie, or Approved Equivalent. Manufacturer: MUNCIE Model Number: SPD-1000

AXLES & SUSPENSION:	30	A.	Steel front axle and suspension, minimum 9,000 lbs. capacity.				
		B.	Front shock absorbers.				
		C.	Front wheel oil-lubricated bearings and seals.				
		D.	Single speed rear axle and suspension, minimum 19,000 lbs. capacity. Rear axle ratio is to be a 5.57/5.71 for 2400 RPM engines, 5.57/5.71/5.86/5.88 for 2500 RPM engines, 6.14/6.43/6.50 for 2800 RPM engines, or the closest possible ratio available that will provide a top speed of approximately 65 MPH.	Rear Suspension Capacity (lbs.): 19000	Rear Axle Ratio: 6.14	Engine RPM: 2600	Top Speed (MPH): 67
		E.	Front wheel hubs and rear axle shall be filled with synthetic lubricant.				

PERFORMANCE ITEMS:	40	A.	Factory installed speedometer; odometer, ammeter or voltmeter, fuel gauge, engine oil pressure gauge, coolant temperature gauge, tachometer, air pressure gauge and dash mounted engine hour meter.
		B.	Power steering.

COMFORT ITEMS:	50	A.	Factory installed AM-FM stereo radio with 2 speakers and antenna.
		B.	Air conditioner with integral heater and defroster.
		C.	Arm rests both sides, if available; sun visors, both sides.
		D.	Tinted glass all windows, including windshield.

		A.	Air horn(s), mounted under the cab or hood, or behind the front bumper.
		B.	Standard electric horn.
		C.	Outside mirrors, left and right side. Mirrors to be 6 x 12 inches, minimum, with convex mirrors on both sides. Mirrors and brackets shall be of rust and corrosive resistance materials such as stainless steel, aluminum, coated metals or composite materials. Painted mirrors and brackets are not acceptable.

Specification Category ¹⁶	Section ¹⁷	Sub-section ¹⁸	Base Vehicle Specification Details ¹⁹	Representative Model Specification ²⁰	Options Specification Information ²¹						
					Option Availability ²²	Option Manufacturer ²³	Option Model Number ²⁴	Option CA Length ²⁵	Option Type ²⁶	Option MSRP ²⁷	Option Price ²⁸
SAFETY ITEMS:	60	D.	Automatic-adjustable volume backup alarm. Must meet latest issue of SAE J994, Type B, 107dB (A). Factory or dealer installed.								
		E.	Rain Flaps: Splash and spray suppressant rain flaps, straight grass type, installed on heavy-duty hangers. Factory or dealer installed.								
		F.	All access steps shall be self-cleaning slip-resistant grating.								
		G.	Daytime running lights.								
BRAKES:	62	A.	ABS air brake system, minimum 13.2 cfm air compressor.								
		B.	Spring applied parking brake.								
		C.	Front and rear automatic slack adjusters.								
		D.	Front and rear dust shields.								
		E.	Outboard mounted brake drums, front and rear, if available. (NOTE: Allows brake repair without removing axle hubs.)								
		F.	Low air pressure warning indicator.								
		G.	Air dryer with heater. Bendix AD-9, AD-IP, AD-IS, Wabco System Saver 1200, or Approved Equivalent.	Air Dryer with Heater Type:	AD-9						
TIRES & WHEELS:	70	A.	6, 275/80R22.5G (14PR) or 295/75R22.5G (14PR) or larger, tubeless, low profile, radial tires with highway tread.								
		B.	All wheels to be 1-piece steel disc, 10-hole, I.S.O. hub pilot mount, 22.5 inch diameter.								
		C.	Front, inside rear and outside rear wheels to be fully interchangeable.								
CHASSIS, FRAME, CAB:	80	A.	Minimum 28,000 lbs. GVWR, factory certified.	GVWR (lbs.):	29000						
		B.	Minimum 859,000 in-lbs. RBM frame.	Frame RBM (lbs.):	986400						
		C.	Cab-to-axle (CA) dimension as recommended by the body manufacturer. CA must provide a cab/body (CB) clearance of 3 to 5 inches.	Cab/Body (CB) Clearance:	75						
		D.	Factory installed fuel tank(s), minimum 70 U.S. gallons.	Fuel Tank(s) Capacity:	80						
		E.	Front tow hooks or tow pins.								
		F.	Standard front bumper.								
CAB EQUIPMENT:	82	A.	Crew cab, 146.0 inch BBC, minimum, 6 passenger, 4 door model with tilt-type hood and fender assembly.	BBC (Front bumper to back of cab) Dimension:	153.5						
		B.	Bench front seat and full width rear bench seat or individual driver seat with two-man passenger seat and full width rear bench seat. Front and rear seats must match in color. Seats must have the same type fabric and pattern, if available.								
		C.	Grab handle(s) for cab entry, located at each entry door.								
		D.	Manufacturer's standard paint and colors.								
BODY:	84	A.	4 cu. yd. dump body, installed, with hoist and electric roll-up dump body tarp system, as per Specification: DUMP-4.	Body Manufacturer:	OX						
				Model Number:	MV8509						
				Hoist Manufacturer:	RUGBY						
				Hoist Model Number:	5020						
				Tarp Manufacturer:	MOUNTAIN						
				Tarp Model Number:	10-16						
B.	Vehicle shall meet all requirements of Title 49, Code of Federal Regulations, and 393.86 rear end protection.										
C.	Body, hoist and electric roll-up dump body tarp system must be installed on the chassis and ready for use upon delivery.										
CONDITIONS:	90	A.	Respondent shall provide a manufacturer's print-out (Ford "DORA"/"Commercial Truck Tools", Freightliner "Spec Pro", International "Vehicle Specifications", Mack "Order/Custom/Vehicle Information", or Approved Equivalent) to verify the vehicle bid meets all the requirements of this specification. Also, any dealer installed aftermarket components, if specified, must be noted on the manufacturer's print-out.								
		B.	Welding shall not be permitted on the frame side rails, nor shall the frame rails be cut to lengthen or shorten the wheelbase. Wheelbase modifications are allowed only by sliding the suspension with the "AF" dimension affected accordingly (excess length behind the rear axle may be cut off as required). Any wheelbase modification shall result in a wheelbase and frame combination that is identical to one available from the manufacturer.								
		C.	Paint numbers are referenced only to identify colors.								

Specification Category ¹⁶	Section ¹⁷	Sub-section ¹⁸	Base Vehicle Specification Details ¹⁹	Representative Model Specification ²⁰	Options Specification Information ²¹								
					Option Availability ²²	Option Manufacturer ²³	Option Model Number ²⁴	Option CA Length ²⁵	Option Type ²⁶	Option MSRP ²⁷	Option Price ²⁸	Option Calculated Discount ²⁹	
OPTIONS:	20.01		Manual transmission, 6-speed minimum, with provisions for a PTO. Transmission must have a minimum low gear reduction of 9.01:1. Rear axle ratio shall be a 4.10/4.11 for 2400 RPM engines, 4.30/4.33 for 2500 RPM engines, 4.78/4.88 for 2800 RPM engines, or the closest possible ratio available that will provide a top speed of approximately 65 MPH. Transmission shall be filled with synthetic lubricant.	Rear Axle Ratio: 4.63	AC	FULLER	FS6406A		OEM		\$ (1,385.00)	Available (Credit)	
		Engine RPM: 2600											
		Top Speed (MPH): 67											
		30.01		Manufacturer's standard 4x4 drive system model in lieu of base equipment 4x2 model. Note: Provide only the difference in price between the 2-wheel drive model and the manufacturer's standard 4x4 model offered.		AC	MERITOR	400-103		OEM	\$ 31,606.00	\$ 30,657.00	3.00%
		50.01		Rain shields over door windows, both sides. Auto Ventshade Co., or Approved Equivalent. Factory or dealer installed.		AC				Non-OEM	\$ 200.00	\$ 200.00	0.00%
		60.01		Front clearance indicators. Factory or dealer installed. (Indicators shall be approximately 36 inches in length located on the left and right front corners of the vehicle.)		AC				Non-OEM	\$ 300.00	\$ 300.00	0.00%
		62.01		Automatic air brake drain system. ClearDrain System, or Approved Equivalent. Bid in lieu of the air dryers specified in Section 62. G. Unit must be installed by the vehicle manufacturer. Dealer installed units are not acceptable.		AC	CLEAR DRAIN	477-022		OEM	\$ 2,280.00	\$ 2,211.00	3.03%
		70.01		Tubeless radial tires with on/off highway tread for rear only. Bid 4, 11R22.5G (14PR) or larger tires for on/off highway use and 2, 11R22.5G (14PR) or larger tires for highway use. Rear tires to be Bridgestone M711, General D450, Goodyear G164 RTD, Michelin XDE, Hankook Z35A, Double Coin RR150, Continental HDL, or Approved Equivalent.	Front Tire Code: 093-1G4	AC				OEM	\$ 352.00	\$ 341.00	3.13%
			Rear Tire Code: 094-ODH										
		80.01		Pintle hook, installed. To be swivel type and must have a capacity of 49,000 lbs. gross trailer weight and 9800 lbs. vertical load, minimum. Hook shall be installed no more than 14 inches forward from the end of the body as measured from the center of the eye. Holland Model PH-760, Wallace Model B30, or Approved Equivalent.		AC	WALLACE	B30		Non-OEM	\$ 1,850.00	\$ 1,850.00	0.00%
		80.02		Air brake package for straight truck and trailer. Full trailer air brake controls with air lines, glad hands and wiring routed to the rear end of the frame.		AC		019-001		OEM	\$ 1,027.00	\$ 996.00	3.02%
		82.01		Special state color. DOT Yellow (DuPont Centari L9069A, Freightliner 3258, International 4421).		NC		980-4H9		OEM			Available (No Cost)
	82.02		2-tone colors. Manufacturer's standard 2-tone colors.		AC		065-902		OEM	\$ 1,426.00	\$ 1,383.00	3.02%	
	84.01		Vibrator installed on dump body. Phillips Temro, Inc., Model VIBRA 2000, or Approved Equivalent. To be installed on mounting base rather than dump body floor plate.		AC	PHILLIPS	VIBRA2000		Non-OEM	\$ 1,490.00	\$ 1,490.00	0.00%	

MEDIUM AND HEAVY TRUCKS (25101600-21-STC)															
Exhibit B.3 - Price Sheet - Dump Trucks															
Commodity Code: 25101601 (DUMP TRUCKS)						Truck Body Specifications: 5 CUBIC YARD HEAVY-DUTY DUMP BODY									
Submitted By:			TAMPA TRUCK CENTER LLC			The detailed specifications are not complete unless used in conjunction with the Price Sheet and Exhibit A, Scope of Work.									
Base Vehicle Code ²		Base Vehicle Specification ³				GVWR (lbs.) ⁴	Payload Capacity (approx. lbs.) ⁵	Accepted Brands ⁶			Intended Use				
340		5 CU YD DUMP TRUCK, SINGLE AXLE, CREW CAB, CLASS 7, 33,000 LBS. GVWR (4x2)				33,000	17,350	FORD F-SERIES, FREIGHTLINER M2, INTERNATIONAL MV/CV SERIES, OR APPROVED EQUIVALENT			HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, TRASH, ETC. THIS VEHICLE HAS 4 FULL SIZE DOORS AND IS RECOMMENDED TO TRANSPORT 4 TO 6 INDIVIDUALS.				
Manufacturer/Brand ⁷		Representative Model ⁸		Representative Model Number ⁹	Base Vehicle Price (\$###,###.##) ¹⁰	OEM Options Discount (##%) ¹¹	Non-OEM Options Discount (##%) ¹²	Customer Pick-Up Discount (\$#.###.##) ¹⁴	Estimated Lead Time in Days (###) ¹⁵						
FREIGHTLINER		M2		106	\$ 93,974.00	3%	0%	\$ (200.00)	120-180						
Specification Category ¹⁶		Section ¹⁷	Sub-section ¹⁸	Base Vehicle Specification Details ¹⁹		Representative Model Specification ²⁰		Options Specification Information ²¹							
						Option Availability ²²	Option Manufacturer ²³	Option Model Number ²⁴	Option CA Length ²⁵	Option Type ²⁶	Option MSRP ²⁷	Option Price ²⁸	Option Calculated Discount ²⁹		
ENGINE:		10	A.	Diesel engine, 5.9L, 210 Gross HP (per the latest issue of SAE J1349) and 560 lbs.-ft. Gross Torque, minimum.		Liters:	6.7	Gross HP:	220	Gross Torque:	600				
			B.	Emissions shall meet or exceed all applicable federal and State of Florida emissions and environmental laws, regulations, specifications, standards, and requirements in effect as of the date of manufacture.		Engine/Emissions Type:	CUMMINS/SCR	Urea Tank Size (in gallons), if required:	6						
			C.	Standard cooling system with antifreeze.											
			D.	Dry type air cleaner with service (restriction) indicator.											
			E.	Engine protection system, at a minimum, must be activated by low engine oil pressure, and high engine temperature. System shall, at a minimum, include a warning light(s) and derate (ramp down) feature that will reduce engine power and speed, or shut down the engine when any of these functions exceed normal limits.											
ELECTRICAL SYSTEM:		12	A.	Minimum 100 amps 12 v. alternator.											
			B.	Batteries to have a minimum total of 1100 CCA @ 0 degrees F.											
TRANSMISSION:		20	A.	Automatic transmission, 6-speed minimum, (International may bid a 5-speed, if required for the engine bid) with provisions for a PTO. Allison 3500RDS, or Approved Equivalent.		Manufacturer:	MUNCIE	Model Number:	SPD-1000						
			B.	Electronic PTO overspeed control. Chelsea, Muncie, or Approved Equivalent.											
AXLES & SUSPENSION:		30	A.	Steel front axle and suspension, minimum 12,000 lbs. capacity.											
			B.	Front shock absorbers.											
			C.	Front wheel oil-lubricated bearings and seals.											
			D.	Single speed rear axle and suspension, minimum 21,000 lbs. capacity. Rear axle ratio is to be a 6.14/6.43/6.50 for 2400 RPM engines, 6.50/6.83/6.86 for 2500 RPM engines, 6.43/6.50 for a 2800 RPM engines, (International - 6.14/6.17 for a 2600 RPM engine), or the closest possible ratio available that will provide a top speed of approximately 65 MPH.		Rear Suspension Capacity (lbs.):	21000	Rear Axle Ratio:	6.14	Engine RPM:	2600	Top Speed (MPH):	68		
			E.	Front wheel hubs and rear axle shall be filled with synthetic lubricant.											
			F.	Auxiliary rear leaf spring(s) or rubber helper.											
			G.	"No-Spin" or driver control traction differential (DCDL) on rear axle.											
PERFORMANCE ITEMS:		40	A.	Factory installed speedometer, odometer, ammeter or voltmeter, fuel gauge, engine oil pressure gauge, coolant temperature gauge, tachometer, air pressure gauge and dash mounted engine hour meter.											
			B.	Power steering.											
COMFORT ITEMS:		50	A.	Factory installed AM-FM stereo radio with 2 speakers and antenna.											
			B.	Air conditioner with integral heater and defroster.											
			C.	Arm rests both sides, if available; sun visors, both sides.											
			D.	Tinted glass all windows, including windshield.											
			A.	Air horn(s), mounted under the cab or hood, or behind the front bumper.											
			B.	Standard electric horn.											
			C.	Outside mirrors, left and right side. Mirrors to be 6 x 12 inches, minimum, with convex mirrors on both sides. Mirrors and brackets shall be of rust and corrosive resistance materials such as stainless steel, aluminum, coated metals or composite materials. Painted mirrors and brackets are not acceptable.											

Specification Category ¹⁶	Section ¹⁷	Sub-section ¹⁸	Base Vehicle Specification Details ¹⁹	Representative Model Specification ²⁰	Options Specification Information ²¹						
					Option Availability ²²	Option Manufacturer ²³	Option Model Number ²⁴	Option CA Length ²⁵	Option Type ²⁶	Option MSRP ²⁷	Option Price ²⁸
SAFETY ITEMS:	60	D.	Automatic-adjustable volume backup alarm. Must meet latest issue of SAE J994, Type B, 107dB (A). Factory or dealer installed.								
		E.	Rain Flaps: Splash and spray suppressant rain flaps, straight grass type, installed on heavy-duty hangers. Factory or dealer installed.								
		F.	All access steps shall be self-cleaning slip-resistant grating.								
		G.	Daytime running lights.								
BRAKES:	62	A.	ABS air brake system, minimum 13.2 cfm air compressor.								
		B.	Spring applied parking brake.								
		C.	Front and rear automatic slack adjusters.								
		D.	Front and rear dust shields.								
		E.	Outboard mounted brake drums, front and rear, if available. (NOTE: Allows brake repair without removing axle hubs.)								
		F.	Low air pressure warning indicator.								
		G.	Air dryer with heater. Bendix AD-9, AD-IP, AD-IS, Wabco System Saver 1200, or Approved Equivalent.	Air Dryer with Heater Type:	AD-9						
TIRES & WHEELS:	70	A.	6, 275/80R22.5G (14PR) or 295/75R22.5G (14PR) or larger, tubeless, low profile, radial tires with highway tread.								
		B.	All wheels to be 1-piece steel disc, 10-hole, I.S.O. hub pilot mount, 22.5 inch diameter.								
		C.	Front, inside rear and outside rear wheels to be fully interchangeable.								
CHASSIS, FRAME, CAB:	80	A.	Minimum 33,000 lbs. GVWR, factory certified.	GVWR (lbs.):	33000						
		B.	Minimum 1,700,000 in-lbs. RBM frame.	Frame RBM (lbs.):	1808400						
		C.	Cab-to-axle (CA) dimension as recommended by the body manufacturer. CA must provide a cab/body (CB) clearance of 3 to 5 inches.	Cab/Body (CB) Clearance:	84						
		D.	Factory installed fuel tank(s), minimum 70 U.S. gallons.	Fuel Tank(s) Capacity:	80						
		E.	Front tow hooks or tow pins.								
		F.	Standard front bumper.								
CAB EQUIPMENT:	82	A.	Crew cab, 146.0 inch BBC, minimum, 6 passenger, 4 door model with tilt-type hood and fender assembly.	BBC (Front bumper to back of cab) Dimension:	153.5						
		B.	Bench front seat and full width rear bench seat or individual driver seat with 2-man passenger seat and full width rear bench seat. Front and rear seats must match in color. Seats must have the same type fabric and pattern, if available.								
		C.	Grab handle(s) for cab entry, located at each entry door.								
		D.	Manufacturer's standard paint and colors.								
BODY:	84	A.	5 cu. yd. dump body, installed, with hoist and electric roll-up dump body tarp system, as per Specification: DUMP-5.	Body Manufacturer:	OX						
				Model Number:	MV8510						
				Hoist Manufacturer:	RUGBY						
				Hoist Model Number:	5020						
	Tarp Manufacturer:	MOUNTAIN									
	Tarp Model Number:	10-16									
B.	Vehicle shall meet all requirements of Title 49, Code of Federal Regulations, and 393.86 rear end protection.										
C.	Body, hoist and electric roll-up dump body tarp system must be installed on the chassis and ready for use upon delivery.										
CONDITIONS:	90	A.	Respondent shall provide a manufacturer's print-out (Ford "DORA"/"Commercial Truck Tools", Freightliner "Spec Pro", International "Vehicle Specifications", Mack "Order/Custom/Vehicle Information", or Approved Equivalent) to verify the vehicle bid meets all the requirements of this specification. Also, any dealer installed aftermarket components, if specified, must be noted on the manufacturer's print-out.								
		B.	Welding shall not be permitted on the frame side rails, nor shall the frame rails be cut to lengthen or shorten the wheelbase. Wheelbase modifications are allowed only by sliding the suspension with the "AF" dimension affected accordingly (excess length behind the rear axle may be cut off as required). Any wheelbase modification shall result in a wheelbase and frame combination that is identical to one available from the manufacturer.								
		C.	Paint numbers are referenced only to identify colors.								

Specification Category ¹⁶	Section ¹⁷	Sub-section ¹⁸	Base Vehicle Specification Details ¹⁹	Representative Model Specification ²⁰		Options Specification Information ²¹							
						Option Availability ²²	Option Manufacturer ²³	Option Model Number ²⁴	Option CA Length ²⁵	Option Type ²⁶	Option MSRP ²⁷	Option Price ²⁸	Option Calculated Discount ²⁹
OPTIONS:	20.01		Manual transmission, 6-speed minimum, with provisions for a PTO. Transmission must have a minimum low gear reduction of 9.01:1. Rear axle ratio shall be a 4.10/4.11 for 2400 RPM engines, 4.30/4.33 for 2500 RPM engines, 4.88/4.89 for 2800 RPM engines, or the closest possible ratio available that will provide a top speed of approximately 65 MPH. Transmission shall be filled with synthetic lubricant.	Rear Axle Ratio: 4.63	AC	FULLER	FS6406A		OEM		\$ (1,385.00)	Available (Credit)	
		Engine RPM: 2600											
		Top Speed (MPH): 66											
		30.01		Manufacturer's standard 4x4 drive system model in lieu of base equipment 4x2 model. Note: Provide only the difference in price between the 2-wheel drive model and the manufacturer's standard 4x4 model offered.		AC	MERITOR	400-103		OEM	\$ 31,606.00	\$ 30,657.00	3.00%
		50.01		Rain shields over door windows, both sides. Auto Ventshade Co., or Approved Equivalent. Factory or dealer installed.		AC				Non-OEM	\$ 200.00	\$ 200.00	0.00%
		60.01		Front clearance indicators. Factory or dealer installed. (Indicators shall be approximately 36 inches in length located on the left and right front corners of the vehicle.)		AC				Non-OEM	\$ 300.00	\$ 300.00	0.00%
		62.01		Automatic air brake drain system. ClearDrain System, or Approved Equivalent. Bid in lieu of the air dryers specified in Section 62. G. Unit must be installed by the vehicle manufacturer. Dealer installed units are not acceptable.		AC	CLEARDRAIN	477-022		OEM	\$ 2,280.00	\$ 2,211.00	3.03%
		70.01		Tubeless radial tires with on/off highway tread for rear only. Bid 4, 11R22.5G (14PR) or larger tires for on/off highway use and 2, 11R22.5G (14PR) or larger tires for highway use. Rear tires to be Bridgestone M711, General D450, Goodyear G164 RTD, Michelin XDE, Hankook Z35A, Double Coin RR150, Continental HDL, or Approved Equivalent.	Front Tire Code: 093-930	AC				OEM	\$ 886.00	\$ 859.00	3.05%
			Rear Tire Code: 094-287										
		80.01		Pintle hook, installed. To be swivel type and must have a capacity of 49,000 lbs. gross trailer weight and 9800 lbs. vertical load, minimum. Hook shall be installed no more than 14 inches forward from the end of the body as measured from the center of the eye. Holland Model PH-760, Wallace Model B30, or Approved Equivalent.		AC	WALLACE	B30		Non-OEM	\$ 1,850.00	\$ 1,850.00	0.00%
		80.02		Air brake package for straight truck and trailer. Full trailer air brake controls with air lines, glad hands and wiring routed to the rear end of the frame.		AC		019-001		OEM	\$ 1,027.00	\$ 996.00	3.02%
		82.01		Special state color. DOT Yellow (DuPont Centari L9069A, Freightliner 3258, International 4421).		NC		980-4H9		OEM			Available (No Cost)
	82.02		2-tone colors. Manufacturer's standard 2-tone colors.		AC		065-902		OEM	\$ 1,426.00	\$ 1,383.00	3.02%	
	84.01		Vibrator installed on dump body. Phillips Temro, Inc., Model VIBRA 2000, or Approved Equivalent. To be installed on mounting base rather than dump body floor plate.		AC	PHILLIPS	VIBRA2000		Non-OEM	\$ 1,490.00	\$ 1,490.00	0.00%	

MEDIUM AND HEAVY TRUCKS (25101600-21-STC)

Exhibit B.3 - Price Sheet - Dump Trucks

Commodity Code: 25101601 (DUMP TRUCKS) **Truck Body Specifications: 8 CUBIC YARD HEAVY-DUTY DUMP BODY**

Submitted By: TAMPA TRUCK CENTER LLC **The detailed specifications are not complete unless used in conjunction with the Price Sheet and Exhibit A, Scope of Work.**

Base Vehicle Code ²	Base Vehicle Specification ³	GVWR (lbs.) ⁴	Payload Capacity (approx. lbs.) ⁵	Accepted Brands ⁶				Intended Use
350	8 YARD DUMP TRUCK, 7.6L ENGINE, TANDEM AXLE, CLASS 8, 52,000 LBS. GVWR (6X4)	52,000	30,550	FREIGHTLINER M2/108/114/122, INTERNATIONAL LONESTAR/LT/RH SERIES, OR APPROVED EQUIVALENT				HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, ETC., AND TRANSPORTING UP TO 2 INDIVIDUALS.
Manufacturer/Brand ⁷	Representative Model ⁸	Representative Model Number ⁹	Base Vehicle Price (\$###,###.##) ¹⁰	OEM Options Discount (##%) ¹¹	Non-OEM Options Discount (##%) ¹²	Customer Pick-Up Discount (\$#,###.##) ¹⁴	Estimated Lead Time in Days (###) ¹⁵	
FREIGHTLINER	M2	106	\$ 98,268.00	3%	0%	\$ (200.00)	120-180	

Specification Category ¹⁶	Section ¹⁷	Sub-section ¹⁸	Base Vehicle Specification Details ¹⁹	Representative Model Specification ²⁰	Options Specification Information ²¹									
					Option Availability ²²	Option Manufacturer ²³	Option Model Number ²⁴	Option CA Length ²⁵	Option Type ²⁶	Option MSRP ²⁷	Option Price ²⁸	Option Calculated Discount ²⁹		
ENGINE:	10	A.	Diesel engine, wet sleeve, 7.6L, 260 Gross HP (per the latest issue of SAE J1349) and 800 lbs.-ft. Gross Torque, minimum.	Liters: 8.9 Gross HP: 260 Gross Torque: 860										
		B.	Emissions shall meet or exceed all applicable federal and State of Florida emissions and environmental laws, regulations, specifications, standards, and requirements in effect as of the date of manufacture.	Engine/Emissions Type: CUMMINS/SCR Urea Tank Size (in gallons), if required: 6										
		C.	Standard cooling system with antifreeze.											
		D.	Dry type air cleaner with service (restriction) indicator.											
		E.	Engine protection system, at a minimum, must be activated by low engine oil pressure, and high engine temperature. System shall, at a minimum, include a warning light(s) and derate (ramp down) feature that will reduce engine power and speed, or shut down the engine when any of these functions exceed normal limits.											
ELECTRICAL SYSTEM:	12	A.	Minimum 100 amps 12 v. alternator.											
		B.	Batteries to have a minimum total of 1100 CCA @ 0 degrees F.											
TRANSMISSION:	20	A.	Automatic transmission, 6-speed minimum, with provisions for a PTO. Allison 3500RDS, or Approved Equivalent.											
		B.	Electronic PTO overspeed control. Chelsea, Muncie, or Approved Equivalent.	Manufacturer: MUNCIE Model Number: SPD-1000										
AXLES & SUSPENSION:	30	A.	Steel front axle and suspension, minimum 12,000 lbs. capacity.											
		B.	Front shock absorbers.											
		C.	Front wheel oil-lubricated bearings and seals.											
		D.	Single speed tandem drive rear axle, minimum 40,000 lbs. capacity. Rear axle ratio is to be a 6.14/6.17 for 2200 RPM engines, 6.43/6.50 for 2400 RPM engines, or the closest possible ratio available that will provide a top speed of approximately 65 MPH. Minimum 40,000 lbs. rear suspension with minimum 52 inch steel walking beams. Hendrickson RT2-400/RT403, or Approved Equivalent.	Rear Suspension Type: RT403 Rear Suspension Capacity (lbs.): 40000 Rear Axle Ratio: 5.86 Engine RPM: 2600 Top Speed (MPH): 68										
		E.	Front wheel hubs and rear axle shall be filled with synthetic lubricant.											
		F.	"No-Spin" or driver control traction differential (DCDL) on the rearmost axle or both rear axles.											
PERFORMANCE ITEMS:	40	A.	Factory installed speedometer; odometer, ammeter or voltmeter, fuel gauge, engine oil pressure gauge, coolant temperature gauge, tachometer, air pressure gauge and dash mounted engine hour meter.											
		B.	Power steering.											
COMFORT ITEMS:	50	A.	Factory installed AM-FM stereo radio with 2 speakers and antenna.											
		B.	Air conditioner with integral heater and defroster.											
		C.	Arm rests both sides, if available; sun visors, both sides.											
		D.	Tinted glass all windows, including windshield.											
		A.	Air horn(s), mounted under the cab or hood, or behind the front bumper.											
		B.	Standard electric horn.											

Specification Category ¹⁶	Section ¹⁷	Sub-section ¹⁸	Base Vehicle Specification Details ¹⁹	Representative Model Specification ²⁰	Options Specification Information ²¹					
					Option Availability ²²	Option Manufacturer ²³	Option Model Number ²⁴	Option CA Length ²⁵	Option Type ²⁶	Option MSRP ²⁷
SAFETY ITEMS:	60	C.	Outside mirrors, left and right side. Mirrors to be 6 x 12 inches, minimum, with convex mirrors on both sides. Mirrors and brackets shall be of rust and corrosive resistance materials such as stainless steel, aluminum, coated metals or composite materials. Painted mirrors and brackets are not acceptable.							
		D.	Automatic-adjustable volume backup alarm. Must meet latest issue of SAE J994, Type B, 107dB (A). Factory or dealer installed.							
		E.	Rain Flaps: Splash and spray suppressant rain flaps, straight grass type, installed on heavy-duty hangers. Factory or dealer installed. NO VENDOR ADVERTISING OR IDENTIFICATION WILL BE PERMITTED ON RAIN FLAPS.							
		F.	All access steps shall be self-cleaning slip-resistant grating.							
		G.	Daytime running lights.							
BRAKES:	62	A.	ABS air brake system, minimum 13.2 cfm air compressor.							
		B.	Spring applied parking brake.							
		C.	Front and rear automatic slack adjusters.							
		D.	Front and rear dust shields.							
		E.	Outboard mounted brake drums, front and rear, if available. (NOTE: Allows brake repair without removing axle hubs.)							
		F.	Low air pressure warning indicator.							
		G.	Air dryer with heater. Bendix AD-9, AD-IP, AD-IS, Wabco System Saver 1200, or Approved Equivalent.	Air Dryer with Heater Type:	AD-9					
TIRES & WHEELS:	70	A.	10, 275/80R22.5G (14PR) or 295/75R22.5G (14PR) or larger, tubeless, low profile, radial tires with highway tread.							
		B.	All wheels to be 1-piece steel disc, 10-hole, I.S.O. hub pilot mount, 22.5 inch diameter.							
		C.	Front, inside rear and outside rear wheels to be fully interchangeable.							
CHASSIS, FRAME, CAB:	80	A.	Minimum 52,000 lbs. GVWR, factory certified.	GVWR (lbs.):	52000					
		B.	Minimum 2,400,000 in-lbs. RBM frame.	Frame RBM (lbs.):	2592000					
		C.	Cab-to-axle (CA) dimension as recommended by the body manufacturer. CA must provide a cab/body (CB) clearance of 3 to 5 inches.	Cab/Body (CB) Clearance:	97					
		D.	Factory installed fuel tank(s), minimum 100 U.S. gallons. State fuel tank(s) capacity.	Fuel Tank(s) Capacity:	100					
		E.	Front tow hooks or tow pins.							
CAB EQUIPMENT:	82	F.	Standard front bumper.							
		A.	Conventional cab, with tilt-type hood and fender assembly.							
		B.	High back air suspension driver seat with matching fixed base companion seat.							
		C.	Grab handle(s) for cab entry, located at each entry door.							
		D.	Manufacturer's standard paint and colors.							
BODY:	84	A.	8 cubic yard heavy-duty dump body, installed, with hoist and electric roll-up dump body tarp system, as per Specification: DUMP-8.	Body Manufacturer:	OX					
				Model Number:	MV8512					
				Hoist Manufacturer:	CRYSTEEL					
				Hoist Model Number:	63108					
				Tarp Manufacturer:	MOUNTAIN					
				Tarp Model Number:	10-16					
		B.	Vehicle shall meet all requirements of Title 49, Code of Federal Regulations, and 393.86 rear end protection.							
C.	Body, hoist and electric roll-up dump body tarp system must be installed on the chassis and ready for use upon delivery.									
CONDITIONS:	90	A.	Respondent shall provide a manufacturer's print-out (Ford "DORA"/"Commercial Truck Tools", Freightliner "Spec Pro", International "Vehicle Specifications", Mack "Order/Customer/Vehicle Information", or Approved Equivalent) to verify the vehicle bid meets all the requirements of this specification. Also, any dealer installed aftermarket components, if specified, must be noted on the manufacturer's print-out.							
		B.	Welding shall not be permitted on the frame side rails, nor shall the frame rails be cut to lengthen or shorten the wheelbase. Wheelbase modifications are allowed only by sliding the suspension with the "AF" dimension affected accordingly (excess length behind the rear axle may be cut off as required). Any wheelbase modification shall result in a wheelbase and frame combination that is identical to one available from the manufacturer.							
		C.	Paint numbers are referenced only to identify colors.							

Specification Category ¹⁶	Section ¹⁷	Sub-section ¹⁸	Base Vehicle Specification Details ¹⁹	Representative Model Specification ²⁰		Options Specification Information ²¹							
						Option Availability ²²	Option Manufacturer ²³	Option Model Number ²⁴	Option CA Length ²⁵	Option Type ²⁶	Option MSRP ²⁷	Option Price ²⁸	Option Calculated Discount ²⁹
OPTIONS:	20.01		Direct drive manual transmission, 10 forward speeds minimum, with provisions for a PTO. Transmission must have a minimum low gear reduction of 19.00:1. Rear axle ratio shall be a 3.90 for 2200 RPM engines, 4.11 for 2400 RPM engines, or the closest possible ratio available that will provide a top speed of approximately 65 MPH. Transmission shall be filled with synthetic lubricant. Minimum 14 inch diameter, 2-plate ceramic-faced clutch. NOTE: Include the credit for a manual transmission PTO as specified in the enclosed dump body specification.	Rear Axle Ratio: 4.63	AC	FULLER	RTO11908LL		OEM		\$ (1,287.00)	Available (Credit)	
		Engine RPM: 2200											
		Top Speed (MPH): 69											
		50.01		Rain shields over door windows, both sides. Auto Ventshade Co., or Approved Equivalent. Factory or dealer installed.		AC				Non-OEM	\$ 200.00	\$ 200.00	0.00%
		60.01		Front clearance indicators. Factory or dealer installed. (Indicators shall be approximately 36 inches in length located on the left and right front corners of the vehicle.)		AC				Non-OEM	\$ 300.00	\$ 300.00	0.00%
		62.01		Automatic air brake drain system. ClearDrain System, or Approved Equivalent. Bid in lieu of the air dryers specified in Section 62. G. Unit must be installed by the vehicle manufacturer. Dealer installed units are not acceptable.		AC	CLEARDRAIN	477-022		OEM	\$ 2,280.00	\$ 2,211.00	3.03%
		70.01		Tubeless radial tires with on/off highway tread for rear only. Bid 8, 11R22.5G (14PR) or larger tires for on/off highway use and 2, 11R22.5G (14PR) or larger tires for on highway use. Bid in lieu of base tires. Rear tires to be Bridgestone M711, General D450, Goodyear G164 RTD, Michelin XDE, Hankook Z35A, Double Coin RR150, Continental HDL, or Approved Equivalent.	Front Tire Code: 093-1P2	AC			OEM	\$ 422.00	\$ 409.00	3.08%	
			Rear Tire Code: 094-1MR										
		80.01		Pintle hook, installed. To be swivel type and must have a capacity of 49,000 lbs. gross trailer weight and 9800 lbs. vertical load, minimum. Hook shall be installed no more than 14 inches forward from the end of the body as measured from the center of the eye. Holland Model PH-760, Wallace Model B30, or Approved Equivalent.		AC	WALLACE	B30		Non-OEM	\$ 1,850.00	\$ 1,850.00	0.00%
		80.02		Air brake package for straight truck and trailer. Full trailer air brake controls with air lines, glad hands and wiring routed to the rear end of the frame.		AC		019-011		OEM	\$ 1,027.00	\$ 996.00	3.02%
		82.01		Special state color. DOT Yellow (DuPont Centari L9069A, Freightliner 3258, International 4421).		NC		980-4H9		OEM			Available (No Cost)
	82.02		2-tone colors. Manufacturer's standard 2-tone colors.		AC		065-902		OEM	\$ 1,426.00	\$ 1,383.00	3.02%	
	82.03		High back air suspension passenger seat. Bid in lieu of the matching fixed base passenger seat specified in Section 82.B.		AC		760-338		OEM	\$ 255.00	\$ 247.00	3.14%	
	84.01		Vibrator installed on dump body. Phillips Temro, Inc., Model VIBRA 3000, or Approved Equivalent. To be installed on mounting base rather than dump body floor plate.		AC	PHILLIPS	VIBRA2000		Non-OEM	\$ 1,490.00	\$ 1,490.00	0.00%	

MEDIUM AND HEAVY TRUCKS (25101600-21-STC)													
Exhibit B.3 - Price Sheet - Dump Trucks													
Commodity Code: 25101601 (DUMP TRUCKS)						Truck Body Specifications: 8 CUBIC YARD HEAVY-DUTY DUMP BODY							
Submitted By:			TAMPA TRUCK CENTER LLC			The detailed specifications are not complete unless used in conjunction with the Price Sheet and Exhibit A, Scope of Work.							
Base Vehicle Code ²		Base Vehicle Specification ³				GVWR (lbs.) ⁴	Payload Capacity (approx. lbs.) ⁵	Accepted Brands ⁶			Intended Use		
360		8 YARD DUMP TRUCK, 7.2L ENGINE, TANDEM AXLE, CLASS 8, 52,000 LBS. GVWR (6X4)				52,000	30,550	FREIGHTLINER M2/108/114/122, INTERNATIONAL LONESTAR/LT/RH SERIES, OR APPROVED EQUIVALENT			HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, ETC., AND TRANSPORTING UP TO 2 INDIVIDUALS.		
Manufacturer/Brand ⁷		Representative Model ⁸		Representative Model Number ⁹	Base Vehicle Price (\$###,###.##) ¹⁰	OEM Options Discount (##%) ¹¹	Non-OEM Options Discount (##%) ¹²	Customer Pick-Up Discount (\$#,###.##) ¹⁴	Estimated Lead Time in Days (###) ¹⁵				
FREIGHTLINER		M2		106	\$ 96,249.00	3%	0%	\$ (200.00)	120-180				
Specification Category ¹⁶		Section ¹⁷	Sub-section ¹⁸	Base Vehicle Specification Details ¹⁹		Representative Model Specification ²⁰		Options Specification Information ²¹					
						Option Availability ²²	Option Manufacturer ²³	Option Model Number ²⁴	Option CA Length ²⁵	Option Type ²⁶	Option MSRP ²⁷	Option Price ²⁸	Option Calculated Discount ²⁹
ENGINE:	10	A.	Diesel engine, 7.2L, 260 Gross HP (per the latest issue of SAE J1349) and 800 lbs.-ft. Gross Torque, minimum.		Liters:	8.9							
			Gross HP:	260									
			Gross Torque:	860									
		B.	Emissions shall meet or exceed all applicable federal and State of Florida emissions and environmental laws, regulations, specifications, standards, and requirements in effect as of the date of manufacture.		Engine/Emissions Type:	CUMMINS/SCR							
			Urea Tank Size (in gallons), if required:		6								
C.	Standard cooling system with antifreeze.												
D.	Dry type air cleaner with service (restriction) indicator.												
E.	Engine protection system, at a minimum, must be activated by low engine oil pressure, and high engine temperature. System shall, at a minimum, include a warning light(s) and derate (ramp down) feature that will reduce engine power and speed, or shut down the engine when any of these functions exceed normal limits.												
ELECTRICAL SYSTEM:	12	A.	Minimum 100 amps 12 v. alternator.										
		B.	Batteries to have a minimum total of 1100 CCA @ 0 degrees F.										
TRANSMISSION:	20	A.	Automatic transmission, 6-speed minimum, with provisions for a PTO. Allison 3500RDS, or Approved Equivalent.										
		B.	Electronic PTO overspeed control. Chelsea, Muncie, or Approved Equivalent.	Manufacturer:	MUNCIE	Model Number:	SPD-1000						
AXLES & SUSPENSION:	30	A.	Steel front axle and suspension, minimum 12,000 lbs. capacity.										
		B.	Front shock absorbers.										
		C.	Front wheel oil-lubricated bearings and seals.										
		D.	Single speed tandem drive rear axle, minimum 40,000 lbs. capacity. Rear axle ratio is to be a 6.14/6.17 for 2200 RPM engines, 6.43/6.50 for 2400, 6.83 for 2500 RPM engines, or the closest possible ratio available that will provide a top speed of approximately 65 MPH. Minimum 40,000 lbs. rear suspension with minimum 52 inch steel walking beams. Hendrickson RT2-400/RT403, or Approved Equivalent.		Rear Suspension Type:	RT403							
			Rear Suspension Capacity (lbs.):	40000									
			Rear Axle Ratio:	5.86									
Engine RPM:	2200												
E.	Front wheel hubs and rear axle shall be filled with synthetic lubricant.												
F.	"No-Spin" or driver control traction differential (DCDL) on the rearmost axle or both axles.												
PERFORMANCE ITEMS:	40	A.	Factory installed speedometer; odometer, ammeter or voltmeter, fuel gauge, engine oil pressure gauge, coolant temperature gauge, tachometer, air pressure gauge and dash mounted engine hour meter.										
		B.	Power steering.										
COMFORT ITEMS:	50	A.	Factory installed AM-FM stereo radio with 2 speakers and antenna.										
		B.	Air conditioner with integral heater and defroster.										
		C.	Arm rests both sides, if available; sun visors, both sides.										
		D.	Tinted glass all windows, including windshield.										
A.	Air horn(s), mounted under the cab or hood, or behind the front bumper.												
B.	Standard electric horn.												

Specification Category ¹⁶	Section ¹⁷	Sub-section ¹⁸	Base Vehicle Specification Details ¹⁹	Representative Model Specification ²⁰	Options Specification Information ²¹					
					Option Availability ²²	Option Manufacturer ²³	Option Model Number ²⁴	Option CA Length ²⁵	Option Type ²⁶	Option MSRP ²⁷
SAFETY ITEMS:	60	C.	Outside mirrors, left and right side. Mirrors to be 6 x 12 inches, minimum, with convex mirrors on both sides. Mirrors and brackets shall be of rust and corrosive resistance materials such as stainless steel, aluminum, coated metals or composite materials. Painted mirrors and brackets are not acceptable.							
		D.	Automatic-adjustable volume backup alarm. Must meet latest issue of SAE J994, Type B, 107dB (A). Factory or dealer installed.							
		E.	Rain Flaps: Splash and spray suppressant rain flaps, straight grass type, installed on heavy-duty hangers. Factory or dealer installed. NO VENDOR ADVERTISING OR IDENTIFICATION WILL BE PERMITTED ON RAIN FLAPS.							
		F.	All access steps shall be self-cleaning slip-resistant grating.							
		G.	Daytime running lights.							
		A.	ABS air brake system, minimum 13.2 cfm air compressor.							
		B.	Spring applied parking brake.							
BRAKES:	62	C.	Front and rear automatic slack adjusters.							
		D.	Front and rear dust shields.							
		E.	Outboard mounted brake drums, front and rear, if available. (NOTE: Allows brake repair without removing axle hubs.)							
		F.	Low air pressure warning indicator.							
		G.	Air dryer with heater. Bendix AD-9, AD-IP, AD-IS, Wabco System Saver 1200, or Approved Equivalent.	Air Dryer with Heater Type:	AD-9					
		A.	10, 275/80R22.5G (14PR) or 295/75R22.5G (14PR) or larger, tubeless, low profile, radial tires with highway tread.							
		B.	All wheels to be 1-piece steel disc, 10-hole, I.S.O. hub pilot mount, 22.5 inch diameter.							
TIRES & WHEELS:	70	C.	Front, inside rear and outside rear wheels to be fully interchangeable.							
		A.	Minimum 52,000 lbs. GVWR, factory certified.	GVWR (lbs.):	52000					
CHASSIS, FRAME, CAB:	80	B.	Minimum 2,400,000 in-lbs. RBM to rear end of frame, factory reinforced if necessary.	Frame RBM (lbs.):	2592000					
		C.	Cab-to-axle (CA) dimension as recommended by the body manufacturer. CA must provide a cab/body (CB) clearance of 3 to 5 inches.	Cab/Body (CB) Clearance:	97					
		D.	Factory installed fuel tank(s), minimum 100 U.S. gallons. State fuel tank(s) capacity.	Fuel Tank(s) Capacity:	100					
		E.	Front tow hooks or tow pins.							
		F.	Standard front bumper.							
CAB EQUIPMENT:	82	A.	Conventional cab, with tilt-type hood and fender assembly.							
		B.	High back air suspension driver seat with matching fixed base companion seat.							
		C.	Grab handle(s) for cab entry, located at each entry door.							
		D.	Manufacturer's standard paint and colors.							
		E.	Rear cab window with fixed tinted glass.							
BODY:	84	A.	8 cubic yard heavy-duty dump body, installed, with hoist and electric roll-up dump body tarp system, as per Specification: DUMP-8.	Body Manufacturer:	OX					
				Model Number:	MV8512					
				Hoist Manufacturer:	CRYSTEEL					
				Hoist Model Number:	63108					
				Tarp Manufacturer:	MOUNTAIN					
				Tarp Model Number:	10-16					
B.	Vehicle shall meet all requirements of Title 49, Code of Federal Regulations, and 393.86 rear end protection.									
C.	Body, hoist and electric roll-up dump body tarp system must be installed on the chassis and ready for use upon delivery.									
CONDITIONS:	90	A.	Respondent shall provide a manufacturer's print-out (Ford "DORA"/"Commercial Truck Tools", Freightliner "Spec Pro", International "Vehicle Specifications", Mack "Order/Custom/Information", or Approved Equivalent) to verify the vehicle bid meets all the requirements of this specification. Also, any dealer installed aftermarket components, if specified, must be noted on the manufacturer's print-out.							
		B.	Welding shall not be permitted on the frame side rails, nor shall the frame rails be cut to lengthen or shorten the wheelbase. Wheelbase modifications are allowed only by sliding the suspension with the "AF" dimension affected accordingly (excess length behind the rear axle may be cut off as required). Any wheelbase modification shall result in a wheelbase and frame combination that is identical to one available from the manufacturer.							
		C.	Paint numbers are referenced only to identify colors.							

Specification Category ¹⁶	Section ¹⁷	Sub-section ¹⁸	Base Vehicle Specification Details ¹⁹	Representative Model Specification ²⁰		Options Specification Information ²¹							
						Option Availability ²²	Option Manufacturer ²³	Option Model Number ²⁴	Option CA Length ²⁵	Option Type ²⁶	Option MSRP ²⁷	Option Price ²⁸	Option Calculated Discount ²⁹
OPTIONS:	20.01		Direct drive manual transmission, 10 forward speeds minimum, with provisions for a PTO. Transmission must have a minimum low gear reduction of 19.00:1. Rear axle ratio shall be a 3.90 for 2200 RPM engines, 4.11 for 2400 RPM engines, or the closest possible ratio available that will provide a top speed of approximately 65 MPH. Transmission shall be filled with synthetic lubricant. Minimum 14 inch diameter, 2-plate ceramic-faced clutch. NOTE: Include the credit for a manual transmission PTO as specified in the enclosed dump body specification.	Rear Axle Ratio: 4.63	AC	FULLER	RTO11908LL		OEM		\$ (1,287.00)	Available (Credit)	
		Engine RPM: 2200											
		Top Speed (MPH): 69											
		50.01		Rain shields over door windows, both sides. Auto Ventshade Co., or Approved Equivalent. Factory or dealer installed.		AC				Non-OEM	\$ 200.00	\$ 200.00	0.00%
		60.01		Front clearance indicators. Factory or dealer installed. (Indicators shall be approximately 36 inches in length located on the left and right front corners of the vehicle.)		AC				Non-OEM	\$ 300.00	\$ 300.00	0.00%
		62.01		Automatic air brake drain system. ClearDrain System, or Approved Equivalent. Bid in lieu of the air dryers specified in Section 62. G. Unit must be installed by the vehicle manufacturer. Dealer installed units are not acceptable.		AC	CLEARDRAIN	477-022		OEM	\$ 2,280.00	\$ 2,211.00	3.03%
		70.01		Tubeless radial tires with on/off highway tread for rear only. Bid 8, 11R22.5G (14PR) or larger tires for on/off highway use and 2, 11R22.5G (14PR) or larger tires for on highway use. Bid in lieu of base tires. Rear tires to be Bridgestone M711, General D450, Goodyear G164 RTD, Michelin XDE, Hankook Z35A, Double Coin RR150, Continental HDL, or Approved Equivalent.	Front Tire Code: 093-1P2	AC			OEM	\$ 422.00	\$ 409.00	3.08%	
			Rear Tire Code: 094-1MR										
		80.01		Pintle hook, installed. To be swivel type and must have a capacity of 49,000 lbs. gross trailer weight and 9800 lbs. vertical load, minimum. Hook shall be installed no more than 14 inches forward from the end of the body as measured from the center of the eye. Holland Model PH-760, Wallace Model B30, or Approved Equivalent.		AC	WALLACE	B30		Non-OEM	\$ 1,850.00	\$ 1,850.00	0.00%
		80.02		PURCHASER MUST SPECIFY BODY LENGTH AND TYPE (DUMP, STAKE, ETC.) IN ORDER FOR THE DEALER TO INSTALL THE PINTLE HOOK IN THE PROPER LOCATION		AC				OEM	\$ 1,027.00	\$ 996.00	3.02%
		82.01		Air brake package for straight truck and trailer. Full trailer air brake controls with air lines, glad hands and wiring routed to the rear end of the frame.		AC		019-001		OEM	\$ 1,027.00	\$ 996.00	3.02%
		82.02		Special state color. DOT Yellow (DuPont Centari L9069A, Freightliner 3258, International 4421).		NC		980-5H9		OEM			Available (No Cost)
	82.02		2-tone colors. Manufacturer's standard 2-tone colors.		AC		065-902		OEM	\$ 1,426.00	\$ 1,383.00	3.02%	
	82.03		High back air suspension passenger seat. Bid in lieu of the matching fixed base passenger seat specified in Section 82.B.		AC		760-338		OEM	\$ 255.00	\$ 247.00	3.14%	
	84.01		Vibrator installed on dump body. Phillips Temro, Inc., Model VIBRA 3000, or Approved Equivalent. To be installed on mounting base rather than dump body floor plate.		AC	PHILLIPS	VIBRA2000		Non-OEM	\$ 1,490.00	\$ 1,490.00	0.00%	

MEDIUM AND HEAVY TRUCKS (25101600-21-STC)

Exhibit B.3 - Price Sheet - Dump Trucks

Commodity Code: 25101601 (DUMP TRUCKS)

Truck Body Specifications: [12 CUBIC YARD HEAVY-DUTY DUMP BODY](#)

Submitted By:		TAMPA TRUCK CENTER LLC			The detailed specifications are not complete unless used in conjunction with the Price Sheet and Exhibit A, Scope of Work.									
Base Vehicle Code ²	Base Vehicle Specification ³			GVWR (lbs.) ⁴	Payload Capacity (approx. lbs.) ⁵	Accepted Brands ⁶			Intended Use					
370	12 YARD DUMP TRUCK, 8.8L ENGINE, TANDEM AXLE, CLASS 8, 64,000 LBS. GVWR (6X4)			64,000	41,800	FREIGHTLINER M2/108/114/122, INTERNATIONAL LONESTAR/LT/RH SERIES, OR APPROVED EQUIVALENT			HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, ETC., AND TRANSPORTING UP TO 2 INDIVIDUALS.					
Manufacturer/Brand ⁷	Representative Model ⁸		Representative Model Number ⁹	Base Vehicle Price (\$###,###.##) ¹⁰	OEM Options Discount (##%) ¹¹	Non-OEM Options Discount (##%) ¹²	Customer Pick-Up Discount (\$#,###.##) ¹⁴	Estimated Lead Time in Days (###) ¹⁵						
FREIGHTLINER	M2		106	\$ 106,887.00	3%	0%	\$ (200.00)	120-180						
Specification Category ¹⁶	Section ¹⁷	Sub-section ¹⁸	Base Vehicle Specification Details ¹⁹		Representative Model Specification ²⁰		Options Specification Information ²¹							
							Option Availability ²²	Option Manufacturer ²³	Option Model Number ²⁴	Option CA Length ²⁵	Option Type ²⁶	Option MSRP ²⁷	Option Price ²⁸	Option Calculated Discount ²⁹
ENGINE:	10	A.	Diesel engine, wet sleeve, 8.8L, 330 Gross HP (per the latest issue of SAE J1349) and 1100 lbs.-ft. Gross Torque, minimum.		Liters: 8.9	Gross HP: 360	Gross Torque: 1150							
		B.	Emissions shall meet or exceed all applicable federal and State of Florida emissions and environmental laws, regulations, specifications, standards, and requirements in effect as of the date of manufacture.		Engine/Emissions Type: CUMMINS/SCR	Urea Tank Size (in gallons), if required: 6								
		C.	Standard cooling system with antifreeze.											
		D.	Dry type air cleaner with service (restriction) indicator.											
		E.	Engine protection system, at a minimum, must be activated by low engine oil pressure, and high engine temperature. System shall, at a minimum, include a warning light(s) and derate (ramp down) feature that will reduce engine power and speed, or shut down the engine when any of these functions exceed normal limits.											
ELECTRICAL SYSTEM:	12	A.	Minimum 100 amps 12 v. alternator.											
		B.	Batteries to have a minimum total of 1100 CCA @ 0 degrees F.											
TRANSMISSION:	20	A.	Manual overdrive transmission, 10 forward speeds minimum, with provisions for a PTO. Transmission must have a minimum low gear reduction of 14.56:1.											
		B.	Electronic PTO overspeed control. Chelsea, Muncie, or Approved Equivalent.	Manufacturer: MUNCIE	Model Number: SPD-1000									
		C.	Transmission shall be filled with synthetic lubricant.											
		D.	Minimum 14 inch diameter 2-plate ceramic-faced clutch.											
AXLES & SUSPENSION:	30	A.	Steel front axle and suspension, minimum 18,000 lbs. capacity.											
		B.	Front shock absorbers.											
		C.	Front wheel oil-lubricated bearings and seals.											
		D.	Single speed tandem drive rear axle, minimum 46,000 lbs. capacity. Rear axle ratio is to be a 4.88/4.89, or the closest possible ratio available that will provide a top speed of approximately 65 MPH. Minimum 46,000 lbs. rear suspension with minimum 54 inch steel walking beams. Hendrickson RT2-460/RT463, Mack Camelback, or Approved Equivalent.	Rear Suspension Type: HAULMAAX	Rear Suspension Capacity (lbs.): 46000	Rear Axle Ratio: 4.89	Top Speed (MPH): 70							
		E.		Front wheel hubs and rear axle shall be filled with synthetic lubricant.										
		F.		"No-Spin" or driver control traction differential (DCDL) on the rearmost axle or both axles.										
G.	Factory installed speedometer; odometer, ammeter or voltmeter, fuel gauge, engine oil pressure gauge, coolant temperature gauge, tachometer, air pressure gauge and dash mounted engine hour meter.													
PERFORMANCE ITEMS:	40	A.	Power steering.											
		B.	Factory installed AM-FM stereo radio with 2 speakers and antenna.											
COMFORT ITEMS:	50	A.	Air conditioner with integral heater and defroster.											
		B.	Arm rests both sides, if available; sun visors, both sides.											
		C.	Tinted glass all windows, including windshield.											
		D.	Air horn(s), mounted under the cab or hood, or behind the front bumper.											
		A.	Standard electric horn.											

Specification Category ¹⁶	Section ¹⁷	Sub-section ¹⁸	Base Vehicle Specification Details ¹⁹	Representative Model Specification ²⁰	Options Specification Information ²¹						
					Option Availability ²²	Option Manufacturer ²³	Option Model Number ²⁴	Option CA Length ²⁵	Option Type ²⁶	Option MSRP ²⁷	Option Price ²⁸
SAFETY ITEMS:	60	C.	Outside mirrors, left and right side. Mirrors to be 6 x 12 inches, minimum, with convex mirrors on both sides. Mirrors and brackets shall be of rust and corrosive resistance materials such as stainless steel, aluminum, coated metals or composite materials. Painted mirrors and brackets are not acceptable.								
		D.	Automatic-adjustable volume backup alarm. Must meet latest issue of SAE J994, Type B, 107dB (A). Factory or dealer installed.								
		E.	Rain Flaps: Splash and spray suppressant rain flaps, straight grass type, installed on heavy-duty hangers. Factory or dealer installed. NO VENDOR ADVERTISING OR IDENTIFICATION WILL BE PERMITTED ON RAIN FLAPS.								
		F.	All access steps shall be self-cleaning slip-resistant grating.								
		G.	Daytime running lights.								
		A.	ABS air brake system, minimum 13.2 cfm air compressor.								
		B.	Spring applied parking brake.								
BRAKES:	62	C.	Front and rear automatic slack adjusters.								
		D.	Front and rear dust shields.								
		E.	Outboard mounted brake drums, front and rear, if available. (NOTE: Allows brake repair without removing axle hubs.)								
		F.	Low air pressure warning indicator.								
		G.	Air dryer with heater. Bendix AD-9, AD-IP, AD-IS, Wabco System Saver 1200, or Approved Equivalent.	Air Dryer with Heater Type:	AD-9						
		A.	Tubeless radial tires with highway tread. Bid 8, 11R22.5H (16 PR) or larger rear tires and 2, 385/65R22.5J (18PR) or larger front tires.								
		B.	All wheels to be 1-piece steel disc, 10-hole, I.S.O. hub pilot mount, 22.5 inch diameter.								
TIRES & WHEELS:	70	C.	Front, inside rear and outside rear wheels to be fully interchangeable.								
		A.	Minimum 64,000 lbs. GVWR, factory certified.	GVWR (lbs.):	64000						
		B.	Minimum 2,700,000 in-lbs. RBM to rear end of frame, factory reinforced if necessary.	Frame RBM (lbs.):	3217200						
CHASSIS, FRAME, CAB:	80	C.	Cab-to-axle (CA) dimension as recommended by the body manufacturer. CA must provide a cab/body (CB) clearance of 3 to 5 inches.	Cab/Body (CB) Clearance:	108						
		D.	Factory installed fuel tank(s), minimum 100 U.S. gallons. State fuel tank(s) capacity.	Fuel Tank(s) Capacity:	100						
		E.	Front tow hooks or tow pins.								
		F.	Standard front bumper.								
		A.	Conventional cab, with tilt-type hood and fender assembly.								
		B.	High back air suspension driver seat with matching fixed base companion seat.								
CAB EQUIPMENT:	82	C.	Grab handle(s) for cab entry, located at each entry door.								
		D.	Manufacturer's standard paint and colors.								
		E.	Rear cab window with fixed tinted glass.								
		A.	12 cubic yard heavy-duty dump body, installed, with hoist and electric roll-up dump body tarp system, as per Specification: DUMP-12 section.	Body Manufacturer:	OX						
				Model Number:	MV8514						
		Hoist Manufacturer:	CYRSTEEL								
		Hoist Model Number:	63108								
		Tarp Manufacturer:	MOUNTAIN								
		Tarp Model Number:	10-16								
BODY:	84	B.	Vehicle shall meet all requirements of Title 49, Code of Federal Regulations, and 393.86 rear end protection.								
		C.	Body, hoist and electric roll-up dump body tarp system must be installed on the chassis and ready for use upon delivery.								
		A.	Respondent shall provide a manufacturer's print-out (Ford "DORA"/"Commercial Truck Tools", Freightliner "Spec Pro", International "Vehicle Specifications", Mack "Order/Custom/Information", or Approved Equivalent) to verify the vehicle bid meets all the requirements of this specification. Also, any dealer installed aftermarket components, if specified, must be noted on the manufacturer's print-out.								
CONDITIONS:	90	B.	Welding shall not be permitted on the frame side rails, nor shall the frame rails be cut to lengthen or shorten the wheelbase. Wheelbase modifications are allowed only by sliding the suspension with the "AF" dimension affected accordingly (excess length behind the rear axle may be cut off as required). Any wheelbase modification shall result in a wheelbase and frame combination that is identical to one available from the manufacturer.								
		C.	Paint numbers are referenced only to identify colors.								
		50.01	Rain shields over door windows, both sides. Auto Ventshade Co., or Approved Equivalent. Factory or dealer installed.	AC				Non-OEM	\$ 200.00	\$ 200.00	0.00%
	60.01	Front clearance indicators. Factory or dealer installed. (Indicators shall be approximately 36 inches in length located on the left and right front corners of the vehicle.)	AC				Non-OEM	\$ 300.00	\$ 300.00	0.00%	

Specification Category ¹⁶	Section ¹⁷	Sub-section ¹⁸	Base Vehicle Specification Details ¹⁹	Representative Model Specification ²⁰	Options Specification Information ²¹											
					Option Availability ²²	Option Manufacturer ²³	Option Model Number ²⁴	Option CA Length ²⁵	Option Type ²⁶	Option MSRP ²⁷	Option Price ²⁸	Option Calculated Discount ²⁹				
OPTIONS:	62.01		Automatic air brake drain system. ClearDrain System, or Approved Equivalent. Bid in lieu of the air dryers specified in Section 62. G. Unit must be installed by the vehicle manufacturer. Dealer installed units are not acceptable.		AC	CLEAR DRAIN	477-022		OEM	\$ 2,280.00	\$ 2,211.00	3.03%				
	70.01		Tubeless radial tires with on/off highway tread for rear only. Bid 8, 11R22.5H (16PR) or larger tires for on/off highway use. Bid in lieu of base tires. Rear tires to be Bridgestone M711, General D450, Goodyear G164 RTD, Michelin XDE, Hankook Z35A, Double Coin RR150, Continental HDL, or Approved	<table border="1"> <tr> <td>Front Tire Code:</td> <td></td> </tr> <tr> <td>Rear Tire Code:</td> <td>094-1E5</td> </tr> </table>	Front Tire Code:		Rear Tire Code:	094-1E5	AC				OEM	\$ 181.00	\$ 175.00	3.31%
	Front Tire Code:															
	Rear Tire Code:	094-1E5														
	80.01		Pintle hook, installed. To be swivel type and must have a capacity of 49,000 lbs. gross trailer weight and 9800 lbs. vertical load, minimum. Hook shall be installed no more than 14 inches forward from the end of the body as measured from the center of the eye. Holland Model PH-760, Wallace Model B30, or Approved Equivalent. PURCHASER MUST SPECIFY BODY LENGTH AND TYPE (DUMP, STAKE, ETC.) IN ORDER FOR THE DEALER TO INSTALL THE PINTLE HOOK IN THE PROPER LOCATION		AC	WALLACE	B30		Non-OEM	\$ 1,850.00	\$ 1,850.00	0.00%				
	80.02		Air brake package for straight truck and trailer. Full trailer air brake controls with air lines, glad hands and wiring routed to the rear end of the frame.		AC		019-001		OEM	\$ 1,027.00	\$ 996.00	3.02%				
	82.01		Special state color. DOT Yellow (DuPont Centari L9069A, Freightliner 3258, International 4421).		NC		980-4H9		OEM			Available (No Cost)				
	82.02		2-tone colors. Manufacturer's standard 2-tone colors.		AC		065-902		OEM	\$ 1,426.00	\$ 1,383.00	3.02%				
	82.03		High back air suspension passenger seat. Bid in lieu of the matching fixed base passenger seat specified in Section 82.B.		AC		760-338		OEM	\$ 255.00	\$ 247.00	3.14%				
	84.01		Vibrator installed on dump body. Phillips Temro, Inc., Model VIBRA 3000, or Approved Equivalent. To be installed on mounting base rather than dump body floor plate.		AC	PHILLIPS	VIBRA2000		Non-OEM	\$ 1,490.00	\$ 1,490.00	0.00%				
84.02		Twin telescopic hoist for 12 cubic yard dump body. Galion UT66392, Heil Model HP2T52-72, Warren CFT-5397, or Approved Equivalent. Hoist is to be an N.T.E.A. Class 110, minimum. Bid in lieu of hoist specified in DUMP-12.		NA							Not Available					

MEDIUM AND HEAVY TRUCKS (25101600-21-STC)

Exhibit B.3 - Price Sheet - Dump Trucks

Commodity Code: 25101601 (DUMP TRUCKS)

Truck Body Specifications: [12 CUBIC YARD HEAVY-DUTY DUMP BODY](#)

Submitted By:		TAMPA TRUCK CENTER LLC			The detailed specifications are not complete unless used in conjunction with the Price Sheet and Exhibit A, Scope of Work.										
Base Vehicle Code ²	Base Vehicle Specification ³				GVWR (lbs.) ⁴	Payload Capacity (approx. lbs.) ⁵	Accepted Brands ⁶			Intended Use					
380	12 YARD DUMP TRUCK, 8.3L ENGINE, TANDEM AXLE, CLASS 8, 64,000 LBS. GVWR (6X4)				64,000	41,800	FREIGHTLINER M2/108/114/122, INTERNATIONAL LONESTAR/LT/RH SERIES, OR APPROVED EQUIVALENT			HAULING LOOSE MATERIALS SUCH AS DIRT, GRAVEL, ETC., AND TRANSPORTING UP TO 2 INDIVIDUALS.					
Manufacturer/Brand ⁷	Representative Model ⁸		Representative Model Number ⁹	Base Vehicle Price (\$###,###.##) ¹⁰	OEM Options Discount (##%) ¹¹	Non-OEM Options Discount (##%) ¹²	Customer Pick-Up Discount (\$#,###.##) ¹⁴	Estimated Lead Time in Days (###) ¹⁵							
FREIGHTLINER	M2		106	\$ 106,330.00	3%	0%	\$ (200.00)	120-180							
Specification Category ¹⁶	Section ¹⁷	Sub-section ¹⁸	Base Vehicle Specification Details ¹⁹		Representative Model Specification ²⁰		Options Specification Information ²¹								
							Option Availability ²²	Option Manufacturer ²³	Option Model Number ²⁴	Option CA Length ²⁵	Option Type ²⁶	Option MSRP ²⁷	Option Price ²⁸	Option Calculated Discount ²⁹	
ENGINE:	10	A.	Diesel engine, wet sleeve, 8.3L, 285 Gross HP (per the latest issue of SAE J1349) and 800 lbs.-ft. Gross Torque, minimum.		Liters: 8.9	Gross HP: 300	Gross Torque: 860								
		B.	Emissions shall meet or exceed all applicable federal and State of Florida emissions and environmental laws, regulations, specifications, standards, and requirements in effect as of the date of manufacture.		Engine/Emissions Type: CUMMINS/SCR	Urea Tank Size (in gallons), if required: 6									
		C.	Standard cooling system with antifreeze.												
		D.	Dry type air cleaner with service (restriction) indicator.												
		E.	Engine protection system, at a minimum, must be activated by low engine oil pressure, and high engine temperature. System shall, at a minimum, include a warning light(s) and derate (ramp down) feature that will reduce engine power and speed, or shut down the engine when any of these functions exceed normal limits.												
ELECTRICAL SYSTEM:	12	A.	Minimum 100 amps 12 v. alternator.												
		B.	Batteries to have a minimum total of 1100 CCA @ 0 degrees F.												
TRANSMISSION:	20	A.	Automatic transmission, 6-speed minimum, with provisions for a PTO. Allison 3500RDS, or Approved Equivalent.												
		B.	Electronic PTO overspeed control. Chelsea, Muncie, or Approved Equivalent.		Manufacturer: MUNCIE	Model Number: SPD-1000									
AXLES & SUSPENSION:	30	A.	Steel front axle and suspension, minimum 18,000 lbs. capacity.												
		B.	Front shock absorbers.												
		C.	Front wheel oil-lubricated bearings and seals.												
		D.	Single speed tandem drive rear axle, minimum 46,000 lbs. capacity. Rear axle ratio is to be a 6.14/6.17, or the closest possible ratio available that will provide a top speed of approximately 65 MPH. Minimum 46,000 lbs. rear suspension with minimum 54 inch steel walking beams. Hendrickson RT2-460/RT463, or Approved Equivalent.		Rear Suspension Type: HAULMAAX	Rear Suspension Capacity (lbs.): 46000	Rear Axle Ratio: 6.14	Top Speed (MPH): 67							
		E.	Front wheel hubs and rear axle shall be filled with synthetic lubricant.												
PERFORMANCE ITEMS:	40	A.	Factory installed speedometer; odometer, ammeter or voltmeter, fuel gauge, engine oil pressure gauge, coolant temperature gauge, tachometer, air pressure gauge and dash mounted engine hour meter.												
		B.	Power steering.												
COMFORT ITEMS:	50	A.	Factory installed AM-FM stereo radio with 2 speakers and antenna.												
		B.	Air conditioner with integral heater and defroster.												
		C.	Arm rests both sides, if available; sun visors, both sides.												
		D.	Tinted glass all windows, including windshield.												
		A.	Air horn(s), mounted under the cab or hood, or behind the front bumper.												
		B.	Standard electric horn.												
		C.	Outside mirrors, left and right side. Mirrors to be 6 x 12 inches, minimum, with convex mirrors on both sides. Mirrors and brackets shall be of rust and corrosive resistance materials such as stainless steel, aluminum, coated metals or composite materials. Painted mirrors and brackets are not acceptable.												

Specification Category ¹⁶	Section ¹⁷	Sub-section ¹⁸	Base Vehicle Specification Details ¹⁹	Representative Model Specification ²⁰	Options Specification Information ²¹									
					Option Availability ²²	Option Manufacturer ²³	Option Model Number ²⁴	Option CA Length ²⁵	Option Type ²⁶	Option MSRP ²⁷	Option Price ²⁸	Option Calculated Discount ²⁹		
SAFETY ITEMS:	60	D.	Automatic-adjustable volume backup alarm. Must meet latest issue of SAE J994, Type B, 107dB (A). Factory or dealer installed.											
		E.	Rain Flaps: Splash and spray suppressant rain flaps, straight grass type, installed on heavy-duty hangers. Factory or dealer installed.											
		F.	All access steps shall be self-cleaning slip-resistant grating.											
		G.	Daytime running lights.											
BRAKES:	62	A.	ABS air brake system, minimum 13.2 cfm air compressor.											
		B.	Spring applied parking brake.											
		C.	Front and rear automatic slack adjusters.											
		D.	Front and rear dust shields.											
		E.	Outboard mounted brake drums, front and rear, if available. (NOTE: Allows brake repair without removing axle hubs.)											
		F.	Low air pressure warning indicator.											
		G.	Air dryer with heater. Bendix AD-9, AD-IP, AD-IS, Wabco System Saver 1200, or Approved Equivalent.	Air Dryer with Heater Type:	AD-9									
TIRES & WHEELS:	70	A.	Tubeless radial tires with highway tread. Bid 8, 11R22.5H (16 PR) or larger rear tires and 2, 385/65R22.5J (18PR) or larger front tires.											
		B.	All wheels to be 1-piece steel disc, 10-hole, I.S.O. hub pilot mount, 22.5 inch diameter.											
		C.	Front, inside rear and outside rear wheels to be fully interchangeable.											
CHASSIS, FRAME, CAB:	80	A.	Minimum 64,000 lbs. GVWR, factory certified.	GVWR (lbs.):	64000									
		B.	Minimum 2,700,000 in-lbs. RBM to rear end of frame, factory reinforced if necessary.	Frame RBM (lbs.):	3217200									
		C.	Cab-to-axle (CA) dimension as recommended by the body manufacturer. CA must provide a cab/body (CB) clearance of 3 to 5 inches.	Cab/Body (CB) Clearance:	108									
		D.	Factory installed fuel tank(s), minimum 100 U.S. gallons. State fuel tank(s) capacity.	Fuel Tank(s) Capacity:	100									
		E.	Front tow hooks or tow pins.											
		F.	Standard front bumper.											
CAB EQUIPMENT:	82	A.	Conventional cab, with tilt-type hood and fender assembly.											
		B.	High back air suspension driver seat with matching fixed base companion seat.											
		C.	Grab handle(s) for cab entry, located at each entry door.											
		D.	Manufacturer's standard paint and colors.											
		E.	Rear cab window with fixed tinted glass.											
BODY:	84	A.	12 cubic yard heavy-duty dump body, installed, with hoist and electric roll-up dump body tarp system, as per Specification DUMP-12.	Body Manufacturer:	OX									
				Model Number:	MV8514									
				Hoist Manufacturer:	CRYSTEEL									
				Hoist Model Number:	63108									
Tarp Manufacturer:	MOUNTAIN													
Tarp Model Number:	10-16													
B.	Vehicle shall meet all requirements of Title 49, Code of Federal Regulations, and 393.86 rear end protection.													
C.	Body, hoist and electric roll-up dump body tarp system must be installed on the chassis and ready for use upon delivery.													
CONDITIONS:	90	A.	Respondent shall provide a manufacturer's print-out (Ford "DORA"/"Commercial Truck Tools", Freightliner "Spec Pro", International "Vehicle Specifications", Mack "Order/Customer/Vehicle Information", or Approved Equivalent) to verify the vehicle bid meets all the requirements of this specification. Also, any dealer installed aftermarket components, if specified, must be noted on the manufacturer's print-out.											
		B.	Welding shall not be permitted on the frame side rails, nor shall the frame rails be cut to lengthen or shorten the wheelbase. Wheelbase modifications are allowed only by sliding the suspension with the "AF" dimension affected accordingly (excess length behind the rear axle may be cut off as required). Any wheelbase modification shall result in a wheelbase and frame combination that is identical to one available from the manufacturer.											
		C.	Paint numbers are referenced only to identify colors.											
	50.01		Rain shields over door windows, both sides. Auto Ventshade Co., or Approved Equivalent. Factory or dealer installed.	AC					Non-OEM	\$ 200.00	\$ 200.00	0.00%		
	60.01		Front clearance indicators. Factory or dealer installed. (Indicators shall be approximately 36 inches in length located on the left and right front corners of the vehicle.)	AC					Non-OEM	\$ 300.00	\$ 300.00	0.00%		
	62.01		Automatic air brake drain system. ClearDrain System, or Approved Equivalent. Bid in lieu of the air dryers specified in Section 62. G. Unit must be installed by the vehicle manufacturer. Dealer installed units are not acceptable.	AC	CLEARRAIN	477-022			OEM	\$ 2,280.00	\$ 2,211.00	3.03%		

Specification Category ¹⁶	Section ¹⁷	Sub-section ¹⁸	Base Vehicle Specification Details ¹⁹	Representative Model Specification ²⁰	Options Specification Information ²¹											
					Option Availability ²²	Option Manufacturer ²³	Option Model Number ²⁴	Option CA Length ²⁵	Option Type ²⁶	Option MSRP ²⁷	Option Price ²⁸	Option Calculated Discount ²⁹				
OPTIONS:	70.01		Tubeless radial tires with on/off highway tread for rear only. Bid 8, 11R22.5H (16PR) or larger tires for on/off highway use. Bid in lieu of base tires. Rear tires to be Bridgestone M711, General D450, Goodyear G164 RTD, Michelin XDE, Hankook Z35A, Double Coin RR150, Continental HDL, or Approved	<table border="1"> <tr> <td>Front Tire Code:</td> <td></td> </tr> <tr> <td>Rear Tire Code:</td> <td>094-1E5</td> </tr> </table>	Front Tire Code:		Rear Tire Code:	094-1E5	AC				OEM	\$ 181.00	\$ 175.00	3.31%
	Front Tire Code:															
	Rear Tire Code:	094-1E5														
	80.01		Pintle hook, installed. To be swivel type and must have a capacity of 49,000 lbs. gross trailer weight and 9800 lbs. vertical load, minimum. Hook shall be installed no more than 14 inches forward from the end of the body as measured from the center of the eye. Holland Model PH-760, Wallace Model B30, or Approved Equivalent. PURCHASER MUST SPECIFY BODY LENGTH AND TYPE (DUMP, STAKE, ETC.) IN ORDER FOR THE DEALER TO INSTALL THE PINTLE HOOK IN THE PROPER LOCATION.		AC	WALLACE	B30		Non-OEM	\$ 1,850.00	\$ 1,850.00	0.00%				
	80.02		Air brake package for straight truck and trailer. Full trailer air brake controls with air lines, glad hands and wiring routed to the rear end of the frame.		AC		019-001		OEM	\$ 1,027.00	\$ 996.00	3.02%				
	82.01		Special state color. DOT Yellow (DuPont Centari L9069A, Freightliner 3258, International 4421).		NC		980-4H9		OEM			Available (No Cost)				
	82.02		2-tone colors. Manufacturer's standard 2-tone colors.		AC		065-902		OEM	\$ 1,426.00	\$ 1,383.00	3.02%				
	82.03		High back air suspension passenger seat. Bid in lieu of the matching fixed base passenger seat specified in Section 82.B.		AC		760-338		OEM	\$ 255.00	\$ 247.00	3.14%				
84.01		Vibrator installed on dump body. Phillips Temro, Inc., Model VIBRA 3000, or Approved Equivalent. To be installed on mounting base rather than dump body floor plate.		AC	PHILLIPS	VIBRA2000		Non-OEM	\$ 1,490.00	\$ 1,490.00	0.00%					
84.02		Twin telescopic hoist for 12 cubic yard dump body. Galion UT66392, HeilModel HP2T52-72, Warren CFT-5397, or Approved Equivalent. Hoist is to be an N.T.E.A. Class 110, minimum. Bid in lieu of hoist specified in DUMP-12.		NA							Not Available					