

to a grade parallel with the longitudinal street grade, and the ground elevation at the right-of-way line shall be not more than two (2) feet, nor less than three (3) inches above the elevation of the top of the adjacent curb. Landing walks of a width not less than eighteen (18) inches may be installed abutting the rear of the curb.

Sec. 6.5 LOTS: Standards that apply to residential lots follow.

6.501. Lot Size: All lots within subdivisions within the jurisdiction of this Ordinance, both inside and outside the City, shall meet the following conditions:

A. The depth of any lot shall not exceed three (3) times the average of the front lot and rear lot dimensions.

B. The minimum area of any lot shall be not less than seventy five hundred (7,500) square feet. For lots not to be served by sanitary sewer, where results of a percolation test prescribed by the Travis County Health Officer deems the minimum lot area insufficient, the City shall require additional area sufficient to accommodate the sanitary facilities deemed necessary by the Travis County Health Officer; provided that if the lot is within an area officially designated commercial by the City Council, then, such lot size shall be adequate to meet anticipated needs.

C. Corner lots shall have a minimum width of seventy-five (75) feet.

D. Minimum usable lot depths for lots backing on natural drainage easements shall be not less than one hundred (100) feet measured between front lot line and drainage easement.

6.502. Lot Facing:

A. Street Frontage: Each lot shall be provided with the minimum frontage on an existing or proposed public street required by the Zoning Ordinance.