



WHEN PROTECTION MEANS EVERYTHING.

HEIMAN FIRE EQUIPMENT THUNDERSTORM SLIDE IN UNIT

The
HEIMAN THUNDERSTORM SLIDE IN UNIT
is built for the rigors of the fire service with the
highest quality components to maximize the
integrity, durability, and life of the unit.



standard base price

\$12,695⁰⁰

shipping & delivery charge not included

pictured with additional
features and options



*pictured with some additional options and upgrades
*foam cell optional

STANDARD FEATURES

- 24 HP Honda engine
- Booster reel, 1" with manual rewind
- 100' 1" booster hose
- 3 piece Elkhart valves with NH thread and ball control handles
- Tank to pump line with valve
 - High Pressure: 2" valve
 - High Volume: 2.5" valve
- 3 gal fuel tank with G3 Fire copoly mounting bracket
- Push/Pull control rod for tank to pump
- Stainless steel manifold
- Expandable discharge manifold with garden hose discharge/drain
 - High pressure model: (1) 1.5" gate valve
 - High volume model: 2.5" x (2) 1.5" gated wye
- Liquid filled gauge on discharge manifold
- 2 1/2" inlet with cap
- 1" tank fill line
- Heavy duty Guzzler hand primer with metal top
- One year warranty on the unit


DIMENSIONS

94" L x 48" W

250 gallon: 52" H	400 gallon: 66" H
300 gallon: 56" H	500 gallon: 74" H



Completely enclosed control panel with on/off start, low pressure protection override, vernier throttle, choke, liquid filled gauge, low oil light, & light shield with LED light



"HOT SWAP"
Field replaceable pump end technology



Weather proof electrical box & high pressure flexline plumbing with stainless steel couplings



Elkhart valves with ball control handles on a painted stainless steel manifold



Powder-coated pump base



Push button electric rewind system



3 gal fuel tank with copoly mounting bracket



- Removable top with sleek stainless steel bolts
- Clearly labeled & color coded foam and water fill towers with strainer

Choice of **PUMPS**

STANDARD HIGH-PRESSURE PUMP

- 4-Stage Hotshot Pump Standard
- Honda engine
- Rotary & mechanical seals
- Centrifugal pump
- Sealed ball bearings
- Brass wear ring
- Stainless steel shaft
- Belt driven speed increaser for lower rpm's and higher pressure

HIGH VOLUME PUMP

- Aluminum alloy pump casing
- Bronze impeller
- Stainless steel shaft
- Mechanical shaft seal

REPLACE YOUR ENTIRE PUMP IN MINUTES!

The Thunderstorm Slide in Unit now comes plumbed ready for our exclusive "hot swap" quick change pump technology allowing users to quickly and easily field replace the Hot Shot 4 pump with minimal tools, because sometimes things happen. Purchase our optional pump end replacement kit and never be without a pump in the field.



Quick-release clamp & pump end

KIT INCLUDES

- Hot Shot 4 or Hellcat X2 pump end with quick-release clamp & 2 grooved bolt-on coupling clamps
- (1) 8" adjustable wrench
- (1) 7/16" wrench
- (1) 11/16" wrench

Release the clamp, use the wrenches to remove the bolt-on couplings, and then replace pump end with new one.

HIGH PRESSURE/MID RANGE "HOT SWAP" FIELD REPLACEABLE PUMPS

4-STAGE 4087-100032 MAX PRESSURE: 440 PSI MAX FLOW: 106 GPM	MID RANGE 4087-100067 MAX PRESSURE: 200 PSI MAX FLOW: 300 GPM
430 psi @ 10 gpm	290 gpm @ 10 psi
415 psi @ 20 gpm	275 gpm @ 50 psi
350 psi @ 65 gpm	215 gpm @ 100 psi
250 psi @ 94 gpm	112 gpm @ 150 psi
150 psi @ 105 gpm	50 gpm @ 175 psi

ADDITIONAL OPTIONAL PUMPS & PERFORMANCE

2-STAGE 3266-HHP24-H	HALE 3266-HAL30024H	DARLEY 3266-DAR24H
325 psi @ 35 gpm	380 gpm @ 25 psi	390 gpm @ 25 psi
295 psi @ 50 gpm	320 gpm @ 50 psi	300 gpm @ 70 psi
200 psi @ 90 gpm	240 gpm @ 75 psi	180 gpm @ 120 psi
150 psi @ 120 gpm	150 gpm @ 100 psi	95 gpm @ 150 psi

Standard **TANK** features

Engineered to withstand the rigors of the fire service, G3 Fire® MAGNITUDE copolymer polypropylene is UV stabilized with 10x the impact strength of standard polypropylene even through wide temperature ranges.

- 250 gallon, lightweight & corrosion resistant G3 Fire® MAGNITUDE copolymer polypropylene tank with limited lifetime warranty
- Full NFPA baffling
- Removable top for cleaning & service
- Built-in water sight gauge
- An internal sump designed for maximum water usage

ADDITIONAL INSTALLED OPTIONS & ACCESSORIES



Push button electric rewind system
+ \$585⁰⁰



Scotty foam system
+ \$1100⁰⁰



copolymer polypropylene hose tray
+ \$445⁰⁰



water level indicator
+ \$655⁰⁰



2.5" inlet w/cap and optional valve
+ \$525⁰⁰



Silvex Plus or Phos Chek foam
+ \$135⁰⁰/pail



Bubble Cup nozzle
1" 10/24 gpm
+ \$370⁰⁰



Tip 1.5" 20/60 gpm
+ \$99⁰⁰



LED work light
+ \$175⁰⁰

HIGH PRESSURE/MEDIUM VOLUME PUMP

- 4087-100108..... HONDA HIGH PRESSURE 4 STAGE..... [STANDARD] \$ STANDARD
- 3266-HHP24-H..... HONDA HIGH PRESSURE..... [ADD \$470] \$ _____

HIGH VOLUME/MEDIUM PRESSURE PUMP

- 4087-100122..... HONDA MID-RANGE 2-STAGE..... [NO CHARGE] \$ _____
- 3266-HAL30024H..... HONDA HIGH VOLUME (HALE)..... [ADD \$260] \$ _____
- 3266-DAR24H..... HONDA HIGH VOLUME (DARLEY)..... [ADD \$370] \$ _____
- OTHER: PLEASE SPECIFY _____ [ADD _____] \$ _____

- 4000-T-H200..... 200 GALLON COPOLY TANK _____ foam cell..... [DEDUCT \$100] \$ _____
- 4000-T-H250..... 250 GALLON COPOLY TANK _____ foam cell..... [STANDARD] \$ _____
- 4000-T-H300..... 300 GALLON COPOLY TANK _____ foam cell..... [ADD \$450] \$ _____
- 4000-T-H400..... 400 GALLON COPOLY TANK _____ foam cell..... [ADD \$1000] \$ _____
- 4000-T-H500..... 500 GALLON COPOLY TANK _____ foam cell..... [ADD \$1900] \$ _____
- 4000-CUSTOM TANK..... [ADD **\$885**] \$ **885**
- 4000-CUSTOM SKID..... [ADD \$ _____] \$ _____

- 2904-EF32-23-24..... In place of standard manual reel..... [ADD \$5 85] \$ **585**
- 2904-EF4038..... In place of standard manual reel..... [ADD \$ 275] \$ _____
- 2904-FH3..... ROLLER & SPOOL ASSEMBLY ON REEL: []top []bottom.. [ADD \$2 75 ea] \$ **550**
- 2930-575..... ADDITIONAL 50' OF 1" BOOSTER HOSE..... [ADD \$2 90] \$ _____
- SECOND REEL..... Electric Rewind, on top of tank, includes plumbing (add hose)..... [ADD \$1 700] \$ _____
- 1111-32..... NO HOSE REEL..... [DEDUCT \$390] \$ _____
- 1111-33..... NO STANDARD 100' BOOSTER HOSE..... [DEDUCT \$400] \$ _____
- 2118-BLCHY..... Lightweight, easy handling lead-in booster hose, 12.5'..... [ADD \$83] \$ _____

- 1242-S106-1600..... FOAM PRO SYSTEM, INSTALLED *with integrated 10 gal foam cell*..... [ADD \$6,700] \$ _____
- 3306-4072-H/cell..... SCOTTY FOAM SYSTEM, INSTALLED *with integrated 10 gal foam cell...* [ADD \$1,100] \$ _____
- 3306-4074-H/pickup..... SCOTTY FOAM SYSTEM, INSTALLED
with pick up tube and threaded cap for department supplied foam pails..... [ADD \$550] \$ _____

- 1430-08825001-FPMN ... GATED INLET, ELKHART..... [ADD \$525] \$ **525**
- 1430-08815101-MPMN .. Additional 1.5" DISCHARGE W/ VALVE..... [ADD \$395] \$ _____
- 4000-CPPHT..... COPOLY HOSE THROUGH for 1.5" hose [] PS [] DS..... [ADD \$445] \$ _____
- 2803-ITL-4L..... HALE/CLASS 1 WATER LEVEL LIGHT GAUGE..... [ADD \$655] \$ **665**
- 1111-INSTALL..... INSTALL MASTER SWITCH, UNIT, AND WIRE..... [ADD \$475] \$ _____
- 4109-H71030401..... LED WORK LIGHT..... [ADD \$175] \$ **175**
- 4087-250238..... 12 VOLT ELECTRIC PISTON PRIMER INSTALLED..... [ADD \$795] \$ _____
- 4087-600006..... PUMP END REPLACEMENT KIT (4-STAGE) HOT SHOT 4..... [ADD \$1925] \$ _____
- 4087-600007..... PUMP END REPLACEMENT KIT (MIDRANGE) HELLCAT X2..... [ADD \$1925] \$ _____
- UNDER SKID STORAGE COMPARTMENT W/DOOR..... [ADD \$1300] \$ _____
- CROSSLAY PLUMBED..... [ADD \$1200] \$ _____
- One (1) additional rewind button, poly bracket, wiring and installation** [ADD **\$345**] \$ **345**
- _____ [ADD \$ _____] \$ _____
- _____ [ADD \$ _____] \$ _____
- _____ [ADD \$ _____] \$ _____
- _____ [ADD \$ _____] \$ _____
- _____ [ADD \$ _____] \$ _____

FOB : Sioux Falls, SD **TOTAL \$ 16,425.00 each**

Remarks: Custom 300 gallon tank 40" Wide
Additional fill tower (opposite corner)
uni-strut added to top corner for fuel tank,
uni-strut each tank side for future mounting,
two reel rewind buttons, two on/off switches for
future use, and a guard over tank to pump linkage.
Actual tank size to be determined and approved.

Date: 04/20/2022 Salesperson: Chris Bornitz
 Fire Dept: Marshall Fire Department
 Contact: _____
 Phone #: _____
 Email: chrisbornitz@heimanfire.com

CUSTOMER REQUIRED TO HAVE FORKLIFT AVAILABLE FOR UNLOADING. *FOR UNITS OVER 7', EXTENDED FORKLIFT REQUIRED

Call your salesman for more options & pricing

WORK ORDER

Date 4-21-22

Invoice Order Quote Credit/Return Other



Heiman Fire Equipment | Federal ID # 42-0955663

2320 NW Blvd. Ashton, IA 51232
 Ph. 712.724.6212 | 1.800.831.8547
 Fax. 712.724.6474 | www.heimanfire.com

SALESMAN	
Name:	<u>CHRIS BORNITZ</u>
Ph. <u>605-530-8210</u>	E-mail: <u>chrisbornitz@heimanfire.com</u>

CUSTOMER	
Name	<u>marshall fire dept</u>
Address	_____
City	<u>marshall</u> State <u>mn</u> Zip _____
Ph.	_____ E-mail _____
Customer #	_____ PO# _____

SHIP TO		<input type="checkbox"/> same as CUSTOMER
Name	_____	
Address	_____	
City	_____ State _____ Zip _____	
Contact Name	_____ Contact Ph. _____	
<input type="checkbox"/> Commercial		<input type="checkbox"/> Residential

Qty Order	Qty Ship	Part Number	Description	Price	Total Amount
1			heiman fire thunderstorm skid	\$16425.00	\$16425
			unit to spec listed on spec sheet	\$	\$0
			free shipping,	\$	\$0
1			tft 1in ultimatic impulse nozel	\$1029.00	\$1029
			with treager an pistol grip	\$	\$0
				\$	\$0
				\$	\$0
				\$	\$0
				\$	\$0
				\$	\$0
				\$	\$0
				\$	\$0
				\$	\$0
				\$	\$0
				\$	\$0
				\$	\$0
				\$	\$0

Subtotal \$	17454
Shipping & handling	
Tax rate ___% Tax	
Credit	
TOTAL \$	

THIS IS NOT AN INVOICE. ALL INVOICES WILL BE SENT DIRECTLY FROM THE OFFICE.