

METROQUIP

VACTOR[®]

Subsidiary of Federal Signal Corporation

MERIDIAN

IDAHO

City of Meridian WWTP Vactor 2100i Recycler

2024 2100i PD, 18" Vacuum, Water Recycler, 12 Yrd Debris - See Specs	\$568,614.25
2025 Kenworth T880, 66,000 GVWR, X15 450V, Allison 4500 RDS - See Specs	\$155,665.00
Dealer Costs - Fuel, Pre-Delivery Inspection, Etc.	\$7,000.00
Total	\$731,279.25
Sourcewell Contract#101221-VTR Discount	-\$17,058.43
Grand Total	\$714,220.82

NOVEMBER 7, 2023 PRICING
VALID FOR 30 DAYS

List Summary

Order Qty	Part Number	Description	List Price
1	2112i-18	2100i PD, 18" Vacuum, 12 yrd Debris, Combo	\$309,766.00
1	2018i	Additional Water, 1500 Gal Total	\$5,120.00
1	5002iA	80 GPM/2500 PSI Jet Rodder pump	\$0.00
1	015iSTD	Customer Supplied Chassis Modification Charge	\$0.00
1	010iSTD	Operator Station Curbside Toolbox	\$0.00
1	011iSTD	Aluminum Fenders	\$0.00
1	012iSTD	Mud Flaps	\$0.00
1	014iSTD	Electric/Hydraulic Four Way Boom	\$0.00
1	016iSTD	Color Coded Sealed Electrical System	\$0.00
1	019iASTD	Intuitouch Electronic Package	\$0.00
1	020iSTD	Double Acting Hoist Cylinder	\$0.00
1	025iASTD	Handgun Assembly	\$0.00
1	026iSTD	Ex-Ten Steel Cylindrical Debris Tank	\$0.00
1	030iSTD	Flexible Hose Guide	\$0.00
1	032iSTD	(3) Nozzles with Carbide Inserts w/Rack	\$0.00
1	045iSTD	Suction Tube Storage	\$0.00
1	046iSTD	1" Nozzle Pipe	\$0.00
1	048iSTD	10' Leader Hose	\$0.00
1	1001iSTD	Flat Rear Door w/Hydraulic Locks	\$0.00
1	1005iSTD	Dual Stainless Steel Float Shut Off System	\$0.00
1	1009iSTD	Full Rear Door Swinging Screen	\$0.00
1	1016iSTD	Microstrainer Prior to Blower	\$0.00
1	1024iSTD	Debris Body Vacuum Relief System	\$0.00
1	1031iSTD	Debris Deflector Plate	\$0.00
1	1033iSTD	60" Dump Height	\$0.00
1	1041iSTD	Debris Body-Up Message and Alarm	\$0.00
1	1053iSTD	Stainless Steel Water Barrel for Jet Rodder Pump with Water Recycler	\$0.00
1	2001iSTD	Low Water Indicator On Screen w/Alarm and Water Pump Flow Indicator	\$0.00
1	2011iSTD	3" Y-Strainer at Passenger Side Fill with 25' Fill Hose	\$0.00
1	2022iSTD	Additional Water Tank Sight Gauge	\$0.00
1	2023iSTD	Liquid Float Level Indicator	\$0.00
1	3019iSTD	Digital Water Pressure Gauge	\$0.00
1	4000iSTD	180 deg. Non-Extending Boom	\$0.00
1	4006iSTD	Front Joystick Boom Control	\$0.00
1	4010iSTD	Boom Hose Storage	\$0.00
1	4017iSTD	Boom Out of Position Message and Alarm	\$0.00
1	5011iSTD	3" Y-Strainer @ Water Pump	\$0.00
1	5015iSTD	Midship Handgun Coupling	\$0.00
1	5022iSTD	Side Mounted Water Pump	\$0.00
1	6005iDSTD	Digital Hose Footage Counter	\$0.00
1	6007iSTD	Hose Reel Manual Hyd Extend/Retract	\$0.00
1	6009iSTD	Hose Reel Chain Cover	\$0.00
1	6020iBSTD	Hydraulic Extending 15", Rotating Hose Reel, 1" x 800' Capacity	\$0.00
1	6017iSTD	Hydraulic Tank Shutoff Valves	\$0.00
1	7001iSTD	Tachometer/Chassis Engine w/Hourmeter	\$0.00
1	7003iSTD	Water Pump Hour Meter	\$0.00
1	7004iSTD	PTO Hour Meter	\$0.00

1	7005iSTD	Hydraulic Oil Temp Alarm	\$0.00
1	7007iSTD	Tachometer & Hourmeter/Blower	\$0.00
1	8000iSTD	Circuit Breakers	\$0.00
1	8025iSTD	LED Lights, Clearance, Back-up, Stop, Tail & Turn	\$0.00
1	9002iSTD	Tow Hooks, Front	\$0.00
1	9002iSTD	Tow Hooks, Rear	\$0.00
1	9003iSTD	Electronic Back-Up Alarm	\$0.00
1	S390BSTD	7" Vacuum Pipe Package	\$0.00
1	S560STD	Emergency Flare Kit	\$0.00
1	S590STD	Fire Extinguisher 5 Lbs.	\$0.00
1	1003i	Debris Body Washout	\$1,926.00
1	1014i	Centrifugal Separators (Cyclones)	\$6,730.00
1	1015iAB	Folding Pipe Rack, Streetside, 7" Pipe	\$1,337.00
1	1015PBR	Rear Door Pipe Rack Removed	\$0.00
1	1016iASTD	Subframe Mounted, 2-Pipe Rack, 7"	\$0.00
1	1022i	Rear Door Splash Shield	\$1,961.00
1	1023i	Lube Manifold, with Lube Chart	\$2,912.00
1	1026i	Debris Body Vibrator, Electric	\$3,425.00
1	2006i	Air Purge	\$1,649.00
1	3015i	Front Blower Controls	\$1,862.00
1	3017i	Blower High Temp Safety Shutdown	\$664.00
1	3020i	Digital Water Level Indicator	\$858.00
1	3022i	Digital Grey Water Level Indicator	\$2,304.00
1	4018i	180 deg. 10' x 15' Rapid Deployment Boom - PROMO PRICING with Water Recycler Option	\$19,478.00
1	4011iB	Bellypack Wireless Controls with hose reel controls, 2-way communications, and LCD Display	\$3,965.00
1	4013i	Rotatable Boom Inlet Hose	\$723.00
1	4021iA	Vacuum Accumulator - Variable Speed	\$5,293.00
1	5008iB	Cold Weather Recirculator, PTO Driven, 25 GPM	\$2,188.00
1	5010iA	Rodder System Accumulator - Jack Hammer on/off Control at Hose Reel	\$998.00
1	5019i	Chassis Engine Cooling Package	\$4,467.00
1	5021iC	Hydro Excavation Kit - Includes Lances w/ Shield, Nozzles, Storage Tray, and Vacuum Tube	\$3,316.00
1	5029i	Cyclone Washout System	\$619.00
1	5029iA	RDB Washout Coupling	\$135.00
1	5030i	Water Recycler	\$130,364.00
1	6003iC	800' x 1" Piranha Sewer Hose 2500 PSI in lieu of STD	\$2,233.00
1	6004iB	Hose Wind Guide (Dual Roller), Auto, Indexing	\$4,786.00
1	6004iD	Rodder Hose Pinch Roller	\$1,773.00
1	6008i	Hose Reel Manual Rewind Tool	\$654.00
1	6014iA	2 High Pressure Hose Reels	\$3,581.00
1	6019i	Rodder Pump Drain Valves	\$624.00
1	6019iA	Final Filter and Silencer Ball Valve Drains	\$562.00
1	6031i	Front Hose Reel Tool Storage	\$375.00
1	8001iM	Rear Directional Control, LED Arrowstick	\$2,242.00
1	8001iN	Front Directional Control, LED Arrowstick	\$2,242.00

1	8020iL	14 Light Package, 14 Federal Signal Strobe Lights, LED	\$4,102.00
1	8027i	LED Mid-Ship Turn Signals	\$680.00
1	8028i	Worklights (2), LED, Boom	\$1,005.00
1	8029i	Worklights (2), LED, Rear Door	\$816.00
1	8029iA	Worklight, LED, Operators Station	\$748.00
1	8029iB	Worklight, LED, Hose Reel Manhole	\$748.00
1	8029iC	Worklight, LED, Curb Side	\$742.00
1	8029iD	Worklight, LED, Street Side	\$742.00
1	9021iB	Camera System, Front, Rear and Both Sides	\$1,898.00
1	9023iA	Safety Cone Storage Rack - Post Style	\$206.00
1	9023iB	Additional Safety Cone Storage Rack - Drop in Style	\$206.00
1	9070iB	Long Handle Tool Storage	\$439.00
1	i112STD	Module Paint, DuPont Imron Elite - Sanded Primer Base	\$0.00
1	i124STD	Vactor 2100i Body Decal, Standard	\$0.00
1	LOGO-LOOSE	Vactor/Guzzler Logos - Shipped Loose	\$0.00
1	500655B-30	Vactor Standard Manual and USB Version - 1 + Dealer	\$0.00
1	Chassis- Mod	Chassis Modifications Charges	\$350.00
1	CUSTOMER	2025 Kenworth T880, X15 450 HP, 4500 RDS, 66,000 GVWR	\$155,665.00
1	8030i	Hose Reel Wrapped for Delivery	\$0.00
1	R38723	Toolbox, Alum, 16W x 36H x 96D w/4 slide out trays (2 per side) w/lighting	\$6,240.00
1	R30989	LATERAL CLEANING KIT - MOUNT UNDER MID SHIP CONTROLS. ELECTRIC POWERED PAY-IN/PAY-OUT, 200' CAPACITY.	\$9,100.00
1	R33813	Debris body hydrant fill with air gap	\$2,269.00
1	R38782	Storage Basket Expanded Metal w/fold down door - Street side only mounted between the tandem and rear bumper.	\$1,395.00
1	R45684	ool Basket, Front bumper Mounted, Street side, only, 16 x 12 x 18 w/LED Side Marker; High pressure hose reel - Front bumper mounted (Curbside Bumper toolbox location)	\$1,496.00
1	VDS-153	Freight Charges	\$4,300.00

Chassis Source - Customer Supplied
Module Paint Match Cab - No
Module Paint Color - Blue
Module Paint Color Code - N4636H
Cab Color - Silver
Cab Color Code - C9339EB
Certified Unit Weights Required? - No

Chassis Note: None



CIT TRUCKS - PERU (C251)
 2650 MAY ROAD
 PERU, Illinois 61354

VACTOR MANUFACTURING
 1621 S ILLINOIS ST
 STREATOR, Illinois 61364
 United States of America

Grant Magerkurth
 Cell Phone:
 Office Phone: 815 224-4410
 Email: gmagerkurth@cittrucks.com

Jared Dippel

Vehicle Summary

	Unit		Chassis	
Model:	T880 Series Conventional	Fr Axle Load (lbs):		20000
Type:	FULL TRUCK	Rr Axle Load (lbs):		46000
Description 1:	POKT450A2023	G.C.W. (lbs):		66000
Description 2:	City of Meridian			
	Application	Road Conditions:		
Intended Serv.:	Construction: Vehicles used in the	Class A (Highway)		85
	cons			
Commodity:	Excavated earth	Class B (Hwy/Mtn)		10
		Class C (Off-Hwy)		5
		Class D (Off-Road)		0
	Body	Maximum Grade:		6
Type:	Vacuum tank	Wheelbase (in):		268
Length (ft):	23	Overhang (in):		88
Height (ft):	13.5	Fr Axle to BOC (in):		74
Max Laden Weight (lbs):	4000			
		Cab to Axle (in):		194
		Cab to EOF (in):		282
		Overall Comb. Length (in):		404.5
	Trailer			
No. of Trailer Axles:	0			
Type:				
Length (ft):	0			
Height (ft):	0			
Kingpin Inset (in):	0			
Corner Radius (in):	0			
	Restrictions			
Length (ft):	120			
Width (in):	102			
Height (ft):	13.5			

Special Req.
 U.S. Domestic registry, 50-state.

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.



Sales Code	Std/Opt	Description	\$ List	Weight
Model				
0000810	S	T880 Series Conventional	213,378	15,549
0070060	S	T880	0	0
0072001	O	Chassis operation will include stationary application used in lower 48 states [US only]. Stationary operation is defined as running the engine under load while stationary at a substantial fraction of engine gross horsepower (60% or greater) for an extended period of time (longer than 5 - 10 minutes).	0	0
0080055	O	CARB Idle Emissions Reduction - Cummins	106	0
0090000	S	Non-Sleeper w/rear axle capacity less than 59K.	0	0
0098412	O	State of Registry: Idaho	0	0
Engine & Equipment				
0130321	O	X15 450V 450@2000 1650@950 2021 with Intebrake, Productivity Series N09420 C333 0.....Reserve Speed Limit Offset (N09380 C334 0.....Maximum Cycle Distance (C334 N09360 C400 252...Reserve Speed Function Reset N09200 C399 120...Standard Maximum Speed Limit N09400 C401 10....Maximum Active Distance (C40 N09220 C402 0.....Expiration Distance (C402) N09540 C395 0.....Expiration Distance (C395) N09260 C121 64....Maximum Accelerator Pedal Ve N09440 C234 NO....Engine Protection Shutdown (N09460 C231 NO....Gear Down Protection (C231) N09580 C133 5.....Timer Setting (C133) N09680 C233 NO....Idle Shutdown Manual Overrul N09480 C132 1400..Max PTO Speed (C132) N09300 C128 64....Maximum Cruise Speed (C128) N09500 C239 NO....Cruise Control Auto Resume (N09520 C238 NO....Auto Engine Brake in Cruise N09240 C209 120...Hard Maximum Speed Limit (C2 N09780 C190 80....High Ambient Temperature Thr N09740 C188 40....Low Ambient Temperature Thre N09760 C189 60....Intermediate Ambient Tempera N09720 C382 YES...Enable Hot Ambient Automatic N09600 C396 YES...Enable Impending Shutdown Wa N09620 C397 60....Timer For Impending Shutdown N09640 C206 35....Engine Load Threshold (C206) N09560 C225 YES...Enable Idle Shutdown Park Br	5,245	465
1000046	O	EPA Emissions Warranty Engine	0	0
1000151	S	PremierSpec	0	0

Price Level: January 1, 2022

Deal: POKT450A2023

Printed On: 7/7/2023 10:56:48 AM

Date: July 07, 2023

Quote Number: QUO-965010-X4M6H8

Sales Code	Std/Opt	Description	\$ List	Weight
1000170	O	Enable engine regeneration in PTO mode Cummins	0	0
1000244	O	Gearing Analysis: Balance power/economy blend results.	0	0
1000256	O	Customer's Typical Operating Spd: 64 MPH	0	0
1000684	O	Effective VSL Setting NA	0	0
1000858	O	Engine Idle Shutdown Timer Disabled	0	0
1000859	O	Enable EIST Ambient Temp Override	0	0
1000891	O	Eff EIST NA Expiration Miles	0	0
1002080	O	Air compressor: Cummins 18.7 CFM, Naturally Aspirated for Cummins X15 engines	196	0
1051200	S	Air Cleaner: composite firewall mounted PACCAR or Cummins engines	0	0
1105220	O	Fan Hub: Horton 2-Speed for X15	5	0
1123555	S	Cooling module: 1330 square inches. Includes aluminum radiator core, aluminum charge air cooler, translucent surge tank and washer bottle, silicone hoses, and extended life coolant.	0	0
1247234	S	EXH: 2021 RH Under DPF/SCR with RH SOC Vertical tailpipe. Not 2.1m high roof sleepers	0	0
1290118	O	Tailpipe: 5 in. Single 18 in. 45 degree curved.	-95	0
1321109	O	Fuel Filter:PACCAR Standard Service Interval Fuel/Water Separator. 2017 and Later Emissions	73	0
1321205	S	Run Aid:Fuel Heat *For Fuel Filter	0	0
1321305	S	Start Aid:12V Heat *For Fuel Filter	0	0
1500029	O	Kenworth Fuel Cooler Required for Cummins engines with a single fuel tank. Required for PACCAR MX-13 engine with a single fuel tank and stationary use: High RPM, low vehicle speed, sustained for longer than 1 hour. Optional for all other applications.	217	6
1504005	O	Immersion block heater 120V 1500W w/plug under door on C500, T660, T800 & W900.	147	2
1509029	O	Shutoff valves for trailer heat with hoses routed at minimum 3 feet BOC/BOS. Installation includes shutoff valves on a loop of hose routed to 3' BOC/BOS. Trailer heat application not to exceed 12 kW (680 BTU/min) of heat draw from the engine. For applications requiring a significant amount of heat (6-12 kW, Ex: heating a tanker), the engine must be warmed up before opening shutoff valves allowing coolant to flow. A separate coolant heater is recommended for applications requiring more heat.	287	0
1816260	O	Alternator: PACCAR 160 amp, brush type	-53	0

Price Level: January 1, 2022

Deal: POKT450A2023

Printed On: 7/7/2023 10:56:48 AM

Date: July 07, 2023

Quote Number: QUO-965010-X4M6H8



Sales Code	Std/Opt	Description	\$ List	Weight
1821225	O	Batteries: 2 PACCAR GP31 threaded post (1000) 2000 CCA starting.	-240	-59
1836103	O	PACCAR Premium 12V Starter W/ Cummins X15 Engines PACCAR 12 volt electrical system. With centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system with circuit protection circuits number & color coded.	123	0
1840065	S	12V low voltage disconnect for starter battery protection.	0	0
1901017	S	Remote PTO/Throttle, 12-Pin, Engine Bay Remote Control Provision	0	0
1901078	O	J1939 Harness Extension Under Hood at Firewall Driver Side	134	0

Transmission & Clutch

2016627	O	Transmission: Allison 4500RDS 6-speed, With PTO drive gear. No Retarder. 6th Generation controls. For vocational applications. Includes shift control, transmission oil temperature gauge, oil level sensor & heat exchanger. Transynd transmission fluid is standard on all Allison 1000, 2000, 3000 & 4000 series transmissions.	25,321	478
2349099	U	ACTL S/C:2349006: JACKSHAFT INS <i>Narr ACTL S/C:2349006:JACKSHAFT INS</i>	3,263	0
2405899	U	ACTL S/C:2405815: 3 1810 W/1 CB	1,703	0
2410018	O	Torque converter included w/Allison Transmission.	0	0
2410151	O	Pushbutton control center console mounted. Class 8 with Allison Transmission.	0	0
2410204	O	Allison Fuel Sense: Delete	0	0
2410433	U	ALLISON GEN 5 RDS PACKAGE 172 <i>Narr ALLISON GEN 5 RDS PACKAGE 172 REQUIRED FOR BODY INSTALL</i>	0	0
2410999	U	ACTL S/C:2410072: NO AUTO NEUTL	0	0
2429378	O	Customer installed transmission PTO in the LH Mounted position (8 o'clock) for Allison 3000 & 4000 transmissions.	0	0
2460068	U	OPT LOC TRANS OIL COOLER FOR BODY <i>Narr OPT LOC TRANS OIL COOLER FOR BODY REQUIRED FOR BODY INSTALL</i>	608	0
2495023	O	Two steel centerbearing crossmembers installed with heavy-duty aluminum gussets replacing standard.	364	70

Front Axle & Equipment

2506181	O	Dana Spicer D2000 Front Axle rated 20K standard track.	371	-27
2621078	O	Front Brakes: 22K Bendix ES S-cam 16.5x6 in.	-494	-46
2690013	O	Front Brake Drum: 20,000 lbs. Meritor X30 light weight 16-1/2x6 in.	16	42

Price Level: January 1, 2022

Deal: POKT450A2023

Printed On: 7/7/2023 10:56:48 AM

Date: July 07, 2023

Quote Number: QUO-965010-X4M6H8

Sales Code	Std/Opt	Description	\$ List	Weight
2701319	S	Front Hubs Aluminum hub pilot 20,000 lbs. 16.5x6in. or 7in. or air disc brakes. 10 Bolt, 11-1/4 in. bolt circle.	0	0
2741970	S	ConMet PreSet Plus Hub package; front axle.	0	0
2750001	S	Hubcap: front vented.	0	0
2765001	O	Front Auto Slack Adjuster.	0	0
2866020	S	Front Springs: Taperleaf 20K w/ shock absorbers w/ maintenance-free elastomer spring pin bushings. Standard with rubber pins except for C500 which has threaded pins. Not available on W900L. W900B use 2866021.	0	0
2893642	O	Dual power steering gear: 16-22K TRW THP60 Not for use on T3.	60	54
2899336	S	Power Steering Cooler:Radiator Mounted Air-to-Oil	0	0
2900024	O	Front Frame Raised: 1 in.	48	0
Rear Axle & Equipment				
3144183	O	Dual Dana Spicer D46-172HP rear axle rated at 46K. w/ 16mm housing and 2.06in. shaft diameter. Includes pump. Tandem rear axles.	1,163	-156
3200430	O	Rear Axle Ratio - 4.30.	0	0
3334004	S	Dual Rear Brakes 16-1/2x7 in. to 46K; Bendix ES-extended service S-cam.	0	0
3392005	S	Dual Rear Brake Drums: cast. For use with 16.5X7" or 16.5X8.625" brake.	0	0
3407050	S	Dual Rear Hubs: Aluminum hub pilot 46K; 11.25" bolt circle. Requires "R" series outer ends.	0	0
3441972	S	ConMet PreSet Plus Hub package; dual rear axle.	0	0
3465002	S	Dual Rear axle automatic slack adjusters. For use with drum brakes.	0	0
3485207	S	Spring Brake: 3030 long stroke dual 30 square inches travel. Helps keep brakes in adjustment longer.	0	0
3495226	O	Bendix 4S/4M anti-lock brake system.	-3,677	0
3500037	O	Interaxle driveline:1 Dana 1710 Series Tandem Rear Axels Only.	-199	-12
3747460	O	Rear suspension: Tandem Hendrickson RT463 46K. 54 in. axle spacing. Steel beams & barpin bushing. 6 in. saddle height. Unladen Height: 11.1 in. Laden Height: 10 in.	-51	689
3830145	O	Delete standard heavy-duty air springs for rear suspension.	-37	-28
Tires & Wheels				
4038676	S	Front tires: Goodyear Armormax MSA 425/65R22.5	-9	-8

Sales Code	Std/ Opt	Description	\$ List	Weight
		20PR.44.4 in. diameter 20.6 in. SLR. all position. On/Off highway. Wide-base tire.		
4277487	O	Rear tires: Bridgestone M799 11R22.5 16PR. 42 in. diameter, drive. 19.5 in. SLR. Code is priced per pair of tires.	1,016	80
4900008	O	Rear Tire Quantity: 8	0	0
5045216	O	Front Wheel: Alcoa 82362 22.5x12.25 aluminum, with LM One [TM] finish High Polish, hub-pilot mount. 11400lb. maximum rating. Super single. Standard track axles may be over 102 in. w/425 tires. Air disc brake compatible.	-102	-10
5243550	O	Rear Wheel: Alcoa ULA18 22.5x8.25 MagnaForce aluminum alloy, hub-pilot mount. 7400lb maximum rating. Air Disc Brake compatible. High polish.	1,584	-316
5900008	O	Rear Wheel/Rim Quantity: 8	0	0
Frame & Equipment				
6054600	O	Frame Rails: 10-5/8 x 3-1/2 x 5/16 in. Steel to 337 in. to 416 in. Truck frame weight is 2.91 lb.-in. per pair of rails. Section modulus is 14.80, RBM is 1,776,000 in.-lbs per rail. Frame rail availability may be restricted based upon application, axle/suspension capacity, fifth wheel setting, or component/dimensional specifications. The results of the engineering review may result in a change to the requested frame rail. If a change is required Kenworth Application Engineering will advise the dealer of the appropriate material specification for a substitute rail.	466	393
6141600	O	Full Steel Insert: for 10-5/8 in. or 10-3/4 in. Steel 337 in. to 416 in. or 2nd insert for 11-5/8 in. steel frame. Adds 1,149,000 in.-lb to main rail RBM. Truck insert weight is 2.05 lb.-in. per pair of rails. Full frame insert length is equal to wheelbase plus rear frame cutoff plus dimension forward of front axle by model: T660, T680, T800, T880 = 21.26 in.; C500B = bumper setting minus 0.79 in.; W900B = 5.27 in., W900L = 1.50 in., W900S = 3.27 in.; T440/T470 50 in. bumper setting = 21.26 in., T470 73 in. bumper setting = 72.3 in.	2,681	773
6309910	U	Delete bumper: Requires a bumper setting code.	-408	0
6319485	S	48.5 in. Bumper setting. Requires a bumper code.	0	0
6391201	O	Custom Frame Layout: one chassis CFL A/D: SAME AS PREV 449043 CFL BBX: LOCATE AS CLOSE AS POSSIBLE TO DPF/SCR CFL A/T: 2 AIR TANKS UNDER BBOX SAME AS PREV 449043 CFL CM: SAME AS PREV 449043	1,380	0
6400636	O	Battery box cantilever aluminum BOC with fiberglass cover.	171	8
6409902	O	Battery box location: RH Side.	116	15
6451090	S	T470,C5, T6, T8 non-polished DPF/SCR or CNG cover diamond plate w/ step. For use w/ 2010 or later exhaust systems. For T8, use extended length non-polished battery box on opposite rail to match the length of under cab components. End plates will be painted standard black frame color.	0	0

Sales Code	Std/Opt	Description	\$ List	Weight
6679806	O	Do not drive: Bumper is deleted. Unit may be decked. Transporter review delivery options. Requires code 6309910 or 6309912.	0	0
6679911	O	Component Restriction: Do Not Drive- Unit may be decked.	0	0
6721102	S	Rear mudflap arms: Betts B-25 standard-duty, straight. Includes B1732 mounting brackets as standard.	0	0
6722000	S	Rear mudflap shields: White plastic antisail w/ Kenworth logo.	0	0
6742009	S	Square end-of-frame w/o crossmember; non-towing.	0	0
6790003	O	Special frame drill: dealer to provide drawing with dimensions and revision level. Acceptable hole diameters range from 10.2 mm to 40.4 mm. Preferred file format is .pdf. Not for use for rear suspension, fifth wheel or other published frame drilling code. Does not replace clear frame space requests or custom frame layout. <i>Narr 504400N REVC, SAME AS PREV 449043</i>	1,797	0
Fuel Tanks & Equip				
7210090	O	Fuel Tank: 90 US gallon 24.5in. aluminum under replace. Class 8 fuel tanks w/o locking caps include an anti-siphon device on the filler neck.	140	-4
7722153	S	Small round DEF tank, 14 gallons. The DEF tank will be located on the side you specified. If you have specific configuration or body builder concerns, please utilize the Custom Frame Layout option. Standard capacity is calculated by fuel capacity of the vehicle and will accommodate two diesel fill-ups for every DEF fill-up. For 1:1 DEF fuel fill ratio, add 7889204.	0	0
7831008	O	6 in. wide lower fuel tank step, for one 22 in. or 24.5 in. tank LH.	63	2
7840015	O	Polish only one aluminum tank.	477	0
7840038	O	Polished cover for 1 DEF tank any size.	352	3
7881300	O	Welded-in fitting w/ gasket & cover plate for mounting customer-installed fuel tank heater.	52	0
7881310	O	Plate and gasket moved to rear of under cab fuel tank. For customer installed fuel tank heaters only.	55	0
7889061	O	Polished stainless steel tank straps for 1 tank.	87	0
7889203	S	DEF to fuel fill ratio 2:1 or greater.	0	0
7889245	S	Anti-siphon device in fuel tank filler neck. For any number of fuel tanks.	0	0
7889604	S	DEF tank location is LH.	0	0
7920090	O	Location: 90 gal fuel tank LH under cab	0	0
Cab & Equipment				

Sales Code	Std/Opt	Description	\$ List	Weight
8025301	S	Cab: Stamped aluminum cab with panoramic curved glass windshield. Standard with stamped aluminum doors, heavy duty in-swinging hinges, and triple sealed doors. Manufactured using self-piercing rivets and structural adhesive. Includes LED exterior marker lights and turn signals.	0	0
8090604	O	Hood: T880 Standard Length With Mechanically Fastened Fenders. 122.6 inch BBC.	345	15
8098212	O	Bright Engine Air Intake Chrome Trimmed Engine Air Intake on Both Sides of Hood	105	0
8108011	S	Cab HVAC - Day Cab and 40in Sleeper System With Defrost, A/C, and 48,000 BTU/hr Heater. Includes automatic temperature control with one touch defrost operation and dash mounted cab temperature and solar intensity sensors. Pleated fresh air filter and cabin recirculation air filter standard. The Kenworth HVAC system is designed to provide optimal heating and cooling in all operating environments without need for additional insulation. Cab HVAC without sleeper heater AC is available with 40in sleeper.	0	0
8201047	S	Kenworth Smartwheel: 18 in. Non-Leather With Integrated Radio and Cruise Controls.	0	0
8201051	O	Column Mtd Retarder Control, RH Side Use with Manual & Allison Transmissions Only.	0	0
8201200	S	Adjustable telescoping tilt steering column.	0	0
8205202	U	PTO WIRING W/O DASH SW	30	0
8209999	O	Spare Power Wiring For Customer Installed Devices Behind Dash Cluster. Includes 2 batt, 2 ign, 1 acc, 1 LVD at 20A each.	93	2
8222404	S	Gauge: DD Virtual Gauge - Oil Temp Engine	0	0
8222413	S	Gauge: DD Virtual Gauge - Manifold Pressure Boost	0	0
8222414	S	Gauge: DD Virtual Gauge - Engine Percent Torque	0	0
8282027	S	Main Instrument Package: 15" Digital Display. Includes Speedometer, Tachometer, Primary Air Pressure, Secondary Air Pressure, Fuel Level #1, DEF Level, DPF Filter Status, Fuel Economy, Oil Pressure, Coolant Temp, OAT and Voltmeter, and Air Application.	0	0
8282107	O	Large flat panel on rider side dash for customer-installed controls. Reduces gauge count by 6.	45	0
8282120	O	USB Charging Port - Dash Panel *Requires 15" Digital Display 8282027/8282028	0	0
8300008	S	Interior color: Slate Gray	0	0
8330102	S	Interior package: Vantage daycab Includes durable headliner and vinyl sidewalls with geometric patterned trim and anodized aluminum accents throughout. Convenient overhead storage cubbies, full size glove box, two center console cupholders, and	0	0

Sales Code	Std/Opt	Description	\$ List	Weight
		large door pad map pocket. Standard LH/RH power windows, electric door locks, interior LED lighting, nighttime-friendly red ambient lighting for dash and footwell, and door mounted courtesy light. Includes two standard 12V power outlets. Driver sunvisor includes strap.		
8390634	S	Rubber floormat	0	0
8410278	O	Driver Seat: GT702 HB with DuraCloth w/ Vinyl material. The GT702 is standard with a single air bag, scissor linkage seat suspension that incorporates seat height memory, auto-leveling valves with exit air dump, and adjustable damper. It includes a dual chamber lumbar support, 10in Fore/Aft adjustment, 5in Up/Down adjustment with protection zones, 2.5in pan extension, 51 degree seat back recline, and 16 degree full seat tilt. Includes 3-point matching seat belts. DR seat standard w/ dual armrests.	291	10
8460278	O	Rider Seat: GT702 HB with DuraCloth w/ Vinyl material. The GT702 is standard with a single air bag, scissor linkage seat suspension that incorporates seat height memory, auto-leveling valves with exit air dump, and adjustable damper. It includes a dual chamber lumbar support, 10in Fore/Aft adjustment, 5in Up/Down adjustment with protection zones, 2.5in pan extension, 51 degree seat back recline, and 16 degree full seat tilt. Includes 3-point matching seat belts. RD seat standard w/ LH armrest.	567	44
8490181	S	Seat Color: Black	0	0
8601432	O	Kenworth Radio DEA710 AM/FM/WB/USB, Bluetooth	37	0
8698974	S	Base Level Audio System - Daycab:High Performance Door Speakers.	0	0
8700196	O	Turn Signal: Self-Cancelling	17	0
8700283	S	LH and RH Trip Ledge Rain Deflectors	0	0
8700406	O	Stainless steel permit panel on cab, driver side only	108	0
8700634	O	Provision For Ram Side Of Dash Allows To Maintain 12 Gauges	50	0
8700663	S	Kenworth TruckTech+ The Kenworth Remote Diagnostics system provides the Worlds Best reporting of engine and aftertreatment fault codes, as well as enhanced support for the truck owner through rapid communication of fault severity and recommended actions. This option is Standard on all Heavy Duty Kenworths with a PACCAR MX engine, Cummins X15 engine, PX engine or Natural Gas engine. Optional on Medium Duty Kenworths.	0	0
8800372	O	Grabhandle: LH, Exterior, Side of Cab - Ergonomic Grab Handle Mounted To The Left Hand Exterior Of The Cab For Entry and Exit.	148	3
8800402	S	Dual Cab Interior Grabhandles: A Pillar Mounted Dash Wrap and B Pillar Mounted Grabhandles	0	0
8832113	S	Kenworth Daylite Door with standard LH/RH	0	0

Sales Code	Std/Opt	Description	\$ List	Weight
		electric door locks and LH/RH electric window controls.		
8841411	S	Single air horn under cab.	0	0
8850139	S	Look-Down, Pass. Door, Black 11x6	0	0
8865003	O	Aero Mirror: Dual Kenworth Chrome Aero. Motorized Heated Mirrors, 7in X 13in With Chrome Mirror Shell and Black Mirror Arms. Also Includes LH/RH Heated 6in X 7in Convex Mirrors. Mirror Brackets Set For 8-1/2 ft Load Width. Mirror Controls Located On Driver Side Door Pad.	354	0
8871447	O	Rear cab stationary window with dark tint 19in x 36in.	45	0
8890101	S	One-piece bonded-in windshield with curved glass. Standard.	0	0
8890135	S	Exterior stainless steel sunvisor.	906	19
8890348	O	Wheelwell Fender Extension: 4.5 inches	19	1
8890876	S	Kenworth Cab/Sleeper Air Suspension.	0	0
Lights & Instruments				
9010553	S	Headlamps: SAE Dual Halogen Complex Reflector	0	0
9022137	S	Marker Lights: Five, rectangular, LED	0	0
9030016	S	Turn Signal Lights: Flush mounted LED. Mounted at top of fender wheel arc.	0	0
9030052	S	LED Stop, Turn, Tail: With Two LED Backup Lights and With An LED License Plate.	0	0
9090000	O	Daytime Running Lamps.	180	0
9090039	S	Marker Lights: Interrupter Switch. Included in Turn Signal For All Models Except T3. The T3 Switch Is In The Dash.	0	0
9090049	S	Omit Brake Light with Engine Brake. Can only be selected when chassis also has engine brake. Cannot be used with options to delete engine brake.	0	0
9090115	O	Reflectors: Two Midframe	23	0
9090126	O	Electric Backup Alarm: Meets SAE J994 & OSHA requirements.	167	4
9090302	O	Junction Box: Mounted Behind Cab or Sleeper Not Mounted at End of Frame.	157	1
9090849	O	Polyswitches replacing fuses. Switch will automatically reset after removal of excess load.	49	0
Air Equipment				
9101218	S	Air Dryer: Bendix AD-HF Puraguard Heated	0	0

Sales Code	Std/Opt	Description	\$ List	Weight
9108001	S	Moisture ejection valve w/ pull cable drain.	0	0
9140020	S	Nylon air tubing in frame & cab, excluding hoses subject to excessive heat or flexing.	0	0
9140248	O	Locate air dryer under LH rail BOC This code requires the use of a custom frame layout code.	0	0
Extended Warranty				
9200021	S	Base Warranty - Standard Service Heavy Duty 12 months / 100,000 miles / 160,000 km.	0	0
9212611	O	24 Month TruckTech+ Subscription for Cummins Engines	0	0
9220001	O	Base Warranty: Emissions 5YR/100K MI - EPA Engine	0	0
Miscellaneous				
9409852	O	GHG Secondary Manufacturer: Does Not Apply	0	0
9490003	O	Additional lead time required for off highway & /or specialty component truck.	0	0
9491659	S	VMUX Architecture	0	0
Promotions				
Paint				
9700000	O	Paint color number(s). N9702 A - C9339 BRT SILVER SPARKLE N9720 FRAME N0001 BLACK	0	0
9943004	O	Bumper Unpainted	0	0
9943052	O	Day Cab Pearl Metallic Paint	817	0
9944820	S	1 - Color Paint - Day Cab Color will be White if no other color is specified.	0	0
9965510	S	Base coat/clear coat. The Kenworth Color Selector contains additional instructions, as well as information on Kenworth paint guidelines and surface finish applications. Kenworth is standard with Dupont Imron Elite paint.	0	0

Order Comments



Total Weight

18,062

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information



Shipping Destinations

Intermediate Destination:

Final Destinations	Quantity
--------------------	----------