

**STORMWATER
CALCULATIONS FOR**

Project Mustang

**Joe Frank Porter Road
Mt. Pleasant, Maury County, TN
Gresham Smith Project #50114.00**

Tax Map 126, Parcel 041.01

August 28, 2025



Gresham Smith

**SUITE 1400
222 SECOND AVE. SOUTH NASHVILLE, TN
37201**

PHONE: 615-770-8100

CONTACT:

Valerie Rockhill

PHONE: 859-422-1963

EMAIL: Valerie.Rockhill@greshamsmith.com



Matthew McLaren

Digitally signed by Matthew McLaren
DN:
E=mat.mclaren@greshamsmith.com,
O=Gresham Smith, L=Nashville, S=Tennessee,
C=US
Date: 2025.08.28 15:05:54-0400

CONTENTS

PROJECT NARRATIVE	3
Project Description	
Soil Conditions	
Existing Stormwater Conditions	
Proposed Stormwater Conditions	
STORMWATER QUANTITY	4
Storm Sewer System	
Stormwater Detention	
STORMWATER QUALITY	5
POI AB	
POI C	
EROSION AND SEDIMENT CONTROL	6
Ditches A & B	
OFFSITE DRAINAGE	7

APPENDIX A: VICINITY MAP

APPENDIX B: DRAINAGE MAP EXHIBITS

APPENDIX C: STORM SEWERS

APPENDIX D: HYDROLOGIC CALCULATIONS

PROJECT NARRATIVE

Project Description

The 36.9 acre proposed site is located west of Joe Frank Porter Road, just north of State Route 43 Lawrenceburg Highway in northeast Mt. Pleasant, Tennessee.

Property improvements include parking, stormwater infrastructure, and one driveway connecting to the existing Joe Frank Porter Road cul-de-sac.

Soil Conditions

The USDA Web Soil Survey data for this property shows:

Map unit symbol	Map unit name	Rating	Acres in AOI	Percent of AOI
Ae	Armour silt loam, eroded gently sloping phase	B	0.3	0.7%
Bk	Braxton silty clay loam, eroded sloping phase	C	0.0	0.1%
Bm	Burgin silt loam, phosphatic phase (Eagleville)	D	1.8	5.0%
Df	Donerail silt loam, gently sloping phase	C	2.1	5.7%
Dg	Dunning silty clay loam, phosphatic phase	C/D	0.2	0.5%
Ga	Godwin silt loam	C/D	16.3	44.0%
Hr	Huntington silt loam, local alluvium phosphatic phase	B	0.1	0.2%
Mb	Maury silt loam, eroded gently sloping phase	A	16.2	43.8%
Totals for Area of Interest			36.9	100.0%

Refer to Appendix B for existing soils information

Existing Stormwater Conditions

The site is currently undeveloped and consists of open land used for agriculture. Runoff drains across the parcel from northeast to southwest, across the site into an unnamed tributary of Big Bigby Creek, TN06040003019, which is designated as impaired by nutrients. Two natural outfalls occur on the site and these will be analyzed in both the pre- and post- conditions.

Proposed Stormwater Conditions

All stormwater runoff will drain in a similar pattern as the existing site, from northeast to southwest. The two natural locations of stormwater discharge in the existing condition will be analyzed in the proposed condition. These discharge locations will be the Point of Interests (POI) AB and C.

POI AB:

On the developed portion of the site, POI AB, the stormwater will be collected via a combination of overland flow and underground pipe networks to either one of two riprap-lined ditches and/or a dry detention pond. A small portion of impervious area (0.74 acres) will directly flow into the detention pond without first entering a riprap-lined ditch. Stormwater that does not enter the storm network will bypass the detention pond and flow overland to the POI AB site outfall.

POI C:

For the undeveloped area at the south of the site, no changes will be made to the existing overland flow path to the POI C outfall. The area of drainage to this point of interest has been reduced from the pre- to the post- condition.

Refer to Appendix B for Existing and Proposed Hydrologic Plan Exhibits.

Stormwater Quantity

Storm Sewer System

The majority of all onsite water will be conveyed via a combination of surface runoff and the proposed storm network throughout the site. All disturbed areas of increased impervious runoff will be diverted to a dry detention pond before slow-release to the POI AB outfall.

The drainage area for each inlet and storm sewer calculations are provided in Appendix D.

Stormwater Detention

Stormwater detention for the proposed development has been provided through the use of the TR-55 method to meet the pre vs. post water quantity requirements, per the City of Mt. Pleasant. The calculations provided herein take into account all future parking and building expansion impervious areas shown on Site Plan. Stormwater over the disturbed portion of the site will be retained for a minimum of 24 hours in a dry detention basin before slow-releasing to the site outfall. The dry detention basin will also improve water quality by the provision for sediment and other pollutants to settle out over time, see Water Quality design.

The Detention Calculations are provided in Appendix D.

POI AB <i>Pre vs. Post Discharge Flow Rates (cfs)</i>						
	2-YR	5-YR	10-YR	25-YR	50-YR	100-YR
PRE	34.07	46.13	55.81	69.25	79.96	91.13
POST	18.76	22.60	25.47	29.36	32.38	35.46

POI C <i>Pre vs. Post Discharge Flow Rates (cfs)</i>						
	2-YR	5-YR	10-YR	25-YR	50-YR	100-YR
PRE	46.91	64.61	78.98	99.24	115.50	132.53
POST	16.89	22.34	26.67	32.63	37.37	42.29

Stormwater Quality

The City of Mt. Pleasant does not currently have water quality requirements for permitting but an effort was made to ensure that sediment transport to receiving waters would be minimal.

POI AB

The majority of surface drainage will be diverted through one of two riprap-lined ditches before being collected and detained in a dry detention basin. Stormwater routed through the pond will travel slowly over an elongated basin route before it discharges to POI AB. A trash rack will be located at the headwall of the basin outlet pipe to further deter negative impacts to receiving streams. There is a small area of impervious paving (0.74 acres) that will go directly to the dry detention basin without first entering a ditch.

POI C

The pre-construction drainage pattern for Watershed C (WS C) will continue undisturbed to POI C.

Erosion and Sediment Control

Ditches A & B:

Both ditches will be lined with Turf Reinforcement Mat (TRM) SC250 to diminish shear stress along the channel bottom and discourage sediment transport. The North American Green Erosion Control Materials Design Software (ECMDS) was used for the analysis of the channel lining and the Known Q was entered via watershed analysis using the Hydraflow Hydrograph Extension for Autodesk Civil 3D.

Ditch A

In order to analyze the channel lining for Ditch A, the Hydraflow Hydrograph Extension for Autodesk Civil 3D was utilized for Watershed 4 – POST WS A and the 10-year storm event. Ditch A conveys three (3) watersheds that enter at different points along the ditch, however, a conservative approach was taken to analyze the ditch as though all flows entered at the same point and were conveyed simultaneously. This ensures that Ditch A will not overflow and that flows entering the ditch will not produce any deleterious erosive effects along the length of the conveyance. The soil composition on site is primarily Silt Loam and Silty Clay Loam; for the analysis of the TRM lining, Silt Loam (SM), Loam (MH) and Clay Loam (CL) were all analyzed to ensure that the channel was stable.

Soils Report is provided in Appendix B. Channel Lining Analysis for Ditch A is provided in Appendix D.

Ditch B

In order to analyze the channel lining for Ditch B, the Hydraflow Hydrograph Extension for Autodesk Civil 3D was utilized for watershed 10 – POST WS B and the 10-year storm event. Ditch B conveys two (2) watersheds that enter at different points along the ditch, however, a conservative approach was taken to analyze the ditch as though all flows entered at the same point and were conveyed simultaneously. This ensures that Ditch B will not overflow and that flows entering the ditch will not produce any deleterious erosive effects along the length of the conveyance. The soil composition on site is primarily Silt Loam and Silty Clay Loam; for the analysis of the TRM lining, Silt Loam (SM), Loam (MH) and Clay Loam (CL) were all analyzed to ensure that the channel was stable.


Soils Report is provided in Appendix B. Channel Lining Analysis for Ditch B is provided in Appendix D.

For temporary and permanent construction measures, as well as sediment basin calculations, refer to the Stormwater Prevention Plan (SWPPP) for erosion control plan and details in Appendix D.

Offsite Drainage

The proposed site is downhill of agricultural land to the north that will contribute 12.21 acres of stormwater run-on. Due to the shape of the site, as well as the layout requirements of the building and vehicular circulation, it was difficult to bypass the entirety of the offsite drainage to the natural outfall of the site. Instead, approximately 12.05 acres of undeveloped offsite drainage will be accepted into the Stormwater Control Measures (SCMs) and treated within the detention pond before ultimately reaching the site outfall(s).

APPENDIX A: VICINITY MAP



VICINITY MAP
NOT TO SCALE



Mt. Pleasant, Tennessee

APPENDIX B: DRAINAGE MAP EXHIBITS


Soils Report

Existing Conditions Drainage Exhibit

Proposed Development Drainage Exhibit


NOAA Rainfall Data

Hydrologic Soil Group—Maury County, Tennessee
(BOUNDARY)



Soil Map may not be valid at this scale.

Map Scale: 1:4,390 if printed on A landscape (11" x 8.5") sheet.



Map projection: Web Mercator Corner coordinates: WGS84 Edge tics: UTM Zone 16N WGS84



Natural Resources
Conservation Service

Web Soil Survey
National Cooperative Soil Survey

6/10/2025
Page 1 of 4

Hydrologic Soil Group—Maury County, Tennessee (BOUNDARY)

MAP LEGEND

Area of Interest (AOI)

 Area of Interest (AOI)

Soils

Soil Rating Polygons

 A
 A/D
 B
 B/D
 C
 C/D
 D
 Not rated or not available

Soil Rating Lines

 A
 A/D
 B
 B/D
 C
 C/D
 D
 Not rated or not available

Soil Rating Points

 A
 A/D
 B
 B/D

 C
 C/D
 D
 Not rated or not available

Water Features

 Streams and Canals

Transportation

 Rails
 Interstate Highways
 US Routes
 Major Roads
 Local Roads

Background

 Aerial Photography

MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:20,000.

Warning: Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service
 Web Soil Survey URL:
 Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Maury County, Tennessee
 Survey Area Data: Version 19, Sep 12, 2024

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Mar 20, 2021—Jun 14, 2021

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.



Hydrologic Soil Group

Map unit symbol	Map unit name	Rating	Acres in AOI	Percent of AOI
Ae	Armour silt loam, eroded gently sloping phase	B	0.3	0.7%
Bk	Braxton silty clay loam, eroded sloping phase	C	0.0	0.1%
Bm	Burgin silt loam, phosphatic phase (Eagleville)	D	1.8	5.0%
Df	Donerail silt loam, gently sloping phase	C	2.1	5.7%
Dg	Dunning silty clay loam, phosphatic phase	C/D	0.2	0.5%
Ga	Godwin silt loam	C/D	16.3	44.0%
Hr	Huntington silt loam, local alluvium phosphatic phase	B	0.1	0.2%
Mb	Maury silt loam, eroded gently sloping phase	A	16.2	43.8%
Totals for Area of Interest			36.9	100.0%

Description

Hydrologic soil groups are based on estimates of runoff potential. Soils are assigned to one of four groups according to the rate of water infiltration when the soils are not protected by vegetation, are thoroughly wet, and receive precipitation from long-duration storms.

The soils in the United States are assigned to four groups (A, B, C, and D) and three dual classes (A/D, B/D, and C/D). The groups are defined as follows:

Group A. Soils having a high infiltration rate (low runoff potential) when thoroughly wet. These consist mainly of deep, well drained to excessively drained sands or gravelly sands. These soils have a high rate of water transmission.

Group B. Soils having a moderate infiltration rate when thoroughly wet. These consist chiefly of moderately deep or deep, moderately well drained or well drained soils that have moderately fine texture to moderately coarse texture. These soils have a moderate rate of water transmission.

Group C. Soils having a slow infiltration rate when thoroughly wet. These consist chiefly of soils having a layer that impedes the downward movement of water or soils of moderately fine texture or fine texture. These soils have a slow rate of water transmission.

Group D. Soils having a very slow infiltration rate (high runoff potential) when thoroughly wet. These consist chiefly of clays that have a high shrink-swell potential, soils that have a high water table, soils that have a claypan or clay layer at or near the surface, and soils that are shallow over nearly impervious material. These soils have a very slow rate of water transmission.

If a soil is assigned to a dual hydrologic group (A/D, B/D, or C/D), the first letter is for drained areas and the second is for undrained areas. Only the soils that in their natural condition are in group D are assigned to dual classes.

Rating Options

Aggregation Method: Dominant Condition

Component Percent Cutoff: None Specified

Tie-break Rule: Higher



POINT PRECIPITATION FREQUENCY ESTIMATES

G.M. Bonnin, D. Martin, B. Lin, T. Parzybok, M.Yekta, and D. Riley

NOAA, National Weather Service, Silver Spring, Maryland

[PF_tabular](#) | [PF_graphical](#) | [Maps & aerals](#)

PF tabular

PDS-based point precipitation frequency estimates with 90% confidence intervals (in inches) ¹										
Duration	Average recurrence interval (years)									
	1	2	5	10	25	50	100	200	500	1000
5-min	0.409 (0.377-0.448)	0.483 (0.445-0.528)	0.564 (0.519-0.618)	0.632 (0.580-0.690)	0.724 (0.659-0.790)	0.795 (0.719-0.866)	0.869 (0.781-0.948)	0.946 (0.843-1.03)	1.05 (0.923-1.15)	1.14 (0.986-1.24)
10-min	0.653 (0.602-0.715)	0.772 (0.711-0.845)	0.904 (0.831-0.990)	1.01 (0.927-1.10)	1.15 (1.05-1.26)	1.27 (1.15-1.38)	1.38 (1.24-1.51)	1.50 (1.34-1.64)	1.66 (1.46-1.82)	1.79 (1.55-1.96)
15-min	0.817 (0.752-0.894)	0.971 (0.894-1.06)	1.14 (1.05-1.25)	1.28 (1.17-1.40)	1.46 (1.33-1.60)	1.60 (1.45-1.75)	1.75 (1.57-1.90)	1.89 (1.68-2.06)	2.09 (1.84-2.29)	2.25 (1.95-2.46)
30-min	1.12 (1.03-1.22)	1.34 (1.24-1.47)	1.62 (1.49-1.78)	1.85 (1.70-2.02)	2.16 (1.97-2.36)	2.42 (2.18-2.63)	2.68 (2.40-2.92)	2.95 (2.62-3.21)	3.33 (2.92-3.64)	3.64 (3.16-3.98)
60-min	1.40 (1.29-1.53)	1.68 (1.55-1.84)	2.08 (1.92-2.28)	2.41 (2.21-2.64)	2.88 (2.62-3.15)	3.27 (2.96-3.56)	3.68 (3.31-4.02)	4.13 (3.68-4.50)	4.78 (4.19-5.22)	5.31 (4.61-5.81)
2-hr	1.61 (1.48-1.78)	1.94 (1.77-2.13)	2.40 (2.19-2.63)	2.78 (2.53-3.05)	3.33 (3.00-3.64)	3.79 (3.40-4.15)	4.28 (3.81-4.69)	4.82 (4.25-5.28)	5.60 (4.86-6.14)	6.25 (5.37-6.87)
3-hr	1.75 (1.61-1.92)	2.10 (1.93-2.31)	2.58 (2.37-2.83)	2.99 (2.73-3.28)	3.57 (3.24-3.91)	4.06 (3.66-4.45)	4.59 (4.10-5.02)	5.15 (4.56-5.64)	5.97 (5.22-6.54)	6.65 (5.74-7.29)
6-hr	2.18 (2.00-2.39)	2.59 (2.38-2.85)	3.16 (2.91-3.47)	3.65 (3.34-4.00)	4.34 (3.94-4.74)	4.92 (4.44-5.37)	5.53 (4.95-6.03)	6.19 (5.50-6.76)	7.14 (6.27-7.81)	7.92 (6.88-8.68)
12-hr	2.64 (2.43-2.90)	3.15 (2.90-3.46)	3.84 (3.53-4.21)	4.42 (4.04-4.83)	5.22 (4.75-5.71)	5.90 (5.34-6.44)	6.61 (5.93-7.21)	7.36 (6.57-8.05)	8.43 (7.44-9.23)	9.31 (8.13-10.2)
24-hr	3.26 (3.02-3.52)	3.89 (3.61-4.21)	4.74 (4.40-5.14)	5.41 (5.01-5.85)	6.33 (5.84-6.84)	7.06 (6.50-7.62)	7.82 (7.17-8.42)	8.58 (7.85-9.25)	9.63 (8.75-10.4)	10.5 (9.46-11.3)
2-day	3.85 (3.56-4.18)	4.61 (4.26-5.01)	5.62 (5.19-6.10)	6.42 (5.92-6.96)	7.50 (6.91-8.14)	8.37 (7.68-9.06)	9.26 (8.46-10.0)	10.2 (9.26-11.0)	11.4 (10.3-12.3)	12.4 (11.1-13.4)
3-day	4.12 (3.82-4.44)	4.92 (4.57-5.32)	5.98 (5.55-6.46)	6.80 (6.30-7.34)	7.90 (7.31-8.52)	8.77 (8.09-9.45)	9.64 (8.87-10.4)	10.5 (9.65-11.3)	11.7 (10.7-12.6)	12.6 (11.5-13.6)
4-day	4.38 (4.08-4.70)	5.23 (4.88-5.62)	6.34 (5.90-6.81)	7.18 (6.69-7.72)	8.30 (7.71-8.90)	9.17 (8.50-9.84)	10.0 (9.27-10.8)	10.9 (10.0-11.7)	12.0 (11.0-12.9)	12.9 (11.8-13.9)
7-day	5.16 (4.84-5.49)	6.15 (5.78-6.55)	7.38 (6.93-7.86)	8.32 (7.81-8.86)	9.56 (8.96-10.2)	10.5 (9.82-11.2)	11.4 (10.7-12.2)	12.3 (11.5-13.1)	13.5 (12.5-14.4)	14.4 (13.3-15.4)
10-day	5.87 (5.52-6.23)	6.97 (6.56-7.40)	8.30 (7.80-8.80)	9.32 (8.76-9.88)	10.6 (10.0-11.3)	11.7 (10.9-12.4)	12.7 (11.9-13.4)	13.7 (12.8-14.5)	15.0 (13.9-15.9)	16.0 (14.8-16.9)
20-day	8.06 (7.62-8.51)	9.51 (9.00-10.0)	11.1 (10.5-11.7)	12.2 (11.5-12.9)	13.6 (12.9-14.4)	14.7 (13.8-15.5)	15.7 (14.8-16.5)	16.6 (15.6-17.5)	17.7 (16.6-18.7)	18.5 (17.3-19.6)
30-day	9.92 (9.41-10.4)	11.7 (11.1-12.3)	13.4 (12.7-14.1)	14.6 (13.9-15.4)	16.2 (15.3-17.0)	17.3 (16.3-18.1)	18.3 (17.3-19.2)	19.2 (18.1-20.2)	20.3 (19.2-21.4)	21.1 (19.9-22.3)
45-day	12.5 (11.9-13.1)	14.6 (13.9-15.3)	16.6 (15.8-17.4)	18.0 (17.1-18.9)	19.8 (18.8-20.8)	21.1 (20.0-22.1)	22.2 (21.1-23.3)	23.3 (22.0-24.4)	24.5 (23.2-25.8)	25.4 (24.0-26.7)
60-day	14.9 (14.2-15.7)	17.5 (16.6-18.4)	19.8 (18.8-20.8)	21.4 (20.4-22.6)	23.4 (22.2-24.7)	24.8 (23.6-26.1)	26.1 (24.7-27.5)	27.3 (25.8-28.7)	28.6 (27.0-30.1)	29.5 (27.8-31.1)

¹ Precipitation frequency (PF) estimates in this table are based on frequency analysis of partial duration series (PDS).

Numbers in parenthesis are PF estimates at lower and upper bounds of the 90% confidence interval. The probability that precipitation frequency estimates (for a given duration and average recurrence interval) will be greater than the upper bound (or less than the lower bound) is 5%. Estimates at upper bounds are not checked against probable maximum precipitation (PMP) estimates and may be higher than currently valid PMP values.


Please refer to NOAA Atlas 14 document for more information.

[Back to Top](#)


PF graphical

PDS-based depth-duration-frequency (DDF) curves

Latitude: 35.5717°, Longitude: -87.1786°



Average recurrence interval (years)
1
2
5
10
25
50
100
200
500
1000




Duration	
5-min	2-day
10-min	3-day
15-min	4-day
30-min	7-day
60-min	10-day
2-hr	20-day
3-hr	30-day
6-hr	45-day
12-hr	60-day
24-hr	

[Back to Top](#)

Maps & aerials

Small scale terrain



Large scale terrain



Large scale map



Large scale aerial



[Back to Top](#)


[US Department of Commerce](#)
[National Oceanic and Atmospheric Administration](#)
[National Weather Service](#)
[National Water Center](#)
1325 East West Highway
Silver Spring, MD 20910
Questions?: HDSC.Questions@noaa.gov

[Disclaimer](#)

APPENDIX C: STORM SEWERS

STORM SEWER ANALYSIS REPORT – 10 YEAR

Hydraflow Storm Sewers Extension for Autodesk® Civil 3D® Plan



Project File: New.stm	Number of lines: 3	Date: 8/28/2025
-----------------------	--------------------	-----------------

Storm Sewer Inventory Report

Line No.	Alignment				Flow Data				Physical Data								Line ID
	Dnstr Line No.	Line Length (ft)	Defl angle (deg)	Junc Type	Known Q (cfs)	Drng Area (ac)	Runoff Coeff (C)	Inlet Time (min)	Invert El Dn (ft)	Line Slope (%)	Invert El Up (ft)	Line Size (in)	Line Shape	N Value (n)	J-Loss Coeff (K)	Inlet/ Rim El (ft)	
1	End	119.003	-32.267	DrGrt	0.00	0.36	0.65	0.0	611.00	5.85	617.96	15	Cir	0.012	0.50	625.00	ST-A2 - ST-A1
2	1	90.456	0.614	MH	0.00	0.18	0.95	5.0	618.03	1.67	619.54	12	Cir	0.012	0.15	626.76	ST-A3 - ST-A2
3	2	87.394	0.134	MH	0.00	0.18	0.95	5.0	619.54	2.36	621.60	12	Cir	0.012	1.00	629.34	ST-A4 - ST-A3
Project File: New.stm												Number of lines: 3				Date: 8/28/2025	

Storm Sewer Summary Report

Line No.	Line ID	Flow rate (cfs)	Line Size (in)	Line shape	Line length (ft)	Invert EL Dn (ft)	Invert EL Up (ft)	Line Slope (%)	HGL Down (ft)	HGL Up (ft)	Minor loss (ft)	HGL Junct (ft)	Dns Line No.	Junction Type
1	ST-A2 - ST-A1	4.11	15	Cir	119.003	611.00	617.96	5.849	611.82	618.78	0.18	618.78	End	DropGrate
2	ST-A3 - ST-A2	2.49	12	Cir	90.456	618.03	619.54	1.669	618.78	620.22	n/a	620.22 j	1	Manhole
3	ST-A4 - ST-A3	1.30	12	Cir	87.394	619.54	621.60	2.357	620.22	622.08	n/a	622.08 j	2	Manhole
Project File: New.stm									Number of lines: 3			Run Date: 8/28/2025		
NOTES: Return period = 10 Yrs. ; j - Line contains hyd. jump.														

Line No.	Area Dn (sqft)	Area Up (sqft)	Byp Ln No	Coeff C1 (C)	Coeff C2 (C)	Coeff C3 (C)	Capac Full (cfs)	Crit Depth (ft)	Cross SI, Sw (ft/ft)	Cross SI, Sx (ft/ft)	Curb Len (ft)	Defl Ang (Deg)	Depth Dn (ft)	Depth Up (ft)	DnStm Ln No	Drng Area (ac)	Easting X (ft)	EGL Dn (ft)	EGL Up (ft)	Energy Loss (ft)
1	0.85	0.85	Sag	0.35	0.50	0.95	16.92	0.82	0.020	0.020		-32.267	0.82	0.82**	Outfall	0.36	1616767.90	612.18	619.14	0.000
2	0.56	0.56	1	0.35	0.50	0.95	4.98	0.68				0.614	0.75	0.68**	1	0.18	1616844.90	619.08	620.52	0.000
3	0.37	0.37	2	0.35	0.50	0.95	5.92	0.48				0.134	0.68	0.48**	2	0.18	1616919.40	620.40	622.27	0.000

Project File: New.stm

Number of lines: 3

Date: 8/28/2025

NOTES: ** Critical depth


Flow Rate	Sf Ave	Sf Dn	Grate Area	Grate Len	Grate Width	Gnd/Rim El Dn	Gnd/Rim El Up	Gutter Depth	Gutter Slope	Gutter Spread	Gutter Width	HGL Dn	HGL Up	HGL Jnct	HGL Jmp Dn	HGL Jmp Up	Incr CxA	Incr Q	Inlet Depth	Inlet Eff
(cfs)	(ft/ft)	(ft/ft)	(sqft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft/ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)		(cfs)	(ft)	(%)
4.11	0.000	0.000	5.06	2.53	2.00	613.00	625.00	0.21	Sag	22.86	2.00	611.82	618.78	618.78			0.23	0.00	0.21	100
2.49	0.000	0.000				625.00	626.76					618.78	620.22 j	620.22	618.86	618.79	0.17	1.30		
1.30	0.000	0.000				626.76	629.34					620.22	622.08 j	622.08	620.23	620.15	0.17	1.30		
Project File: New.stm													Number of lines: 3			Date: 8/28/2025				
NOTES: ** Critical depth																				

Inlet ID	Inlet Loc		Inlet Time	i Sys	i Inlet	Invert Dn	Invert Up	Jump Loc	Jump Len	Vel Hd Jmp Dn	Vel Hd Jmp Up	J-Loss Coeff	Junct Type	Known Q	Cost RCP	Cost CMP	Cost PVC	
		(ft)	(min)	(in/hr)	(in/hr)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)			(cfs)				
ST-A2	Sag		0.0	7.13	0.00	611.00	617.96			0.00	0.00	0.50 z	Dp-Grate	0.00	4,185	3,767	3,557	
ST-A3	Sag		5.0	7.28	7.57	618.03	619.54	9.05	3.38	0.30	0.49	0.15 z	MH	0.00	3,280	2,952	2,788	
ST-A4	Sag		5.0	7.57	7.57	619.54	621.60	8.74	2.40	0.19	0.43	1.00 z	MH	0.00	3,175	2,858	2,699	
Project File: New.stm Number of lines: 3 Date: 8/28/2025																		
NOTES: Intensity = 73.40 / (Inlet time + 12.20) ^ 0.80 -- Return period = 10 Yrs. ; ** Critical depth																		

Line ID	Line Length	Line Size	Line Slope	Line Type	Local Depr	n-val Gutter	n-val Pipe	Minor Loss	Northing Y	Pipe Travel	Q Byp	Q Capt	Q Carry	Line Rise	Runoff Coeff	Line Span	Area A1	Area A2	Area A3
	(ft)	(in)	(%)		(in)			(ft)	(ft)	(min)	(cfs)	(cfs)	(cfs)	(in)	(C)	(in)	(ac)	(ac)	(ac)
ST-A2 - ST-A1	119.003	15	5.85	Cir			0.012	0.18	452173.60	0.58	0.00	2.59	2.59	15	0.65	15	0.18	0.00	0.18
ST-A3 - ST-A2	90.456	12	1.67	Cir			0.012	n/a	452221.07	0.47				12	0.95	12	0.00	0.00	0.18
ST-A4 - ST-A3	87.394	12	2.36	Cir			0.012	n/a	452266.76	0.88				12	0.95	12	0.00	0.00	0.18
Project File: New.stm										Number of lines: 3				Date: 8/28/2025					
NOTES: ** Critical depth																			

Tc	Throat Ht	Total Area	Total CxA	Total Runoff	Vel Ave	Vel Dn	Vel Hd Dn	Vel Hd Up	Vel Up	Cover Dn	Cover Up	Storage			
(min)	(in)	(ac)		(cfs)	(ft/s)	(ft/s)	(ft)	(ft)	(ft/s)	(ft)	(ft)	(cft)			
6.4		0.72	0.58	4.11	4.82	4.82	0.36	0.36	4.82	0.75	5.79	101.50			
5.9		0.36	0.34	2.49	4.18	3.94	0.30	0.30	4.41	5.97	6.22	54.12			
5.0		0.18	0.17	1.30	2.88	2.30	0.19	0.19	3.47	6.22	6.74	41.05			

Hydraflow Storm Sewers Extension for Autodesk® Civil 3D® Plan



Project File: New.stm	Number of lines: 2	Date: 8/7/2025
-----------------------	--------------------	----------------

Storm Sewer Inventory Report

Line No.	Alignment				Flow Data				Physical Data								Line ID
	Dnstr Line No.	Line Length (ft)	Defl angle (deg)	Junc Type	Known Q (cfs)	Drng Area (ac)	Runoff Coeff (C)	Inlet Time (min)	Invert El Dn (ft)	Line Slope (%)	Invert El Up (ft)	Line Size (in)	Line Shape	N Value (n)	J-Loss Coeff (K)	Inlet/ Rim El (ft)	
1	End	120.512	-31.955	DrGrt	0.00	0.45	0.55	5.0	611.00	8.30	621.00	15	Cir	0.012	0.50	627.00	ST-B2 - ST-B1
2	1	207.150	0.257	MH	0.00	0.63	0.95	5.0	621.00	1.93	625.00	12	Cir	0.012	1.00	628.83	ST-B3 - ST-B2
Project File: New.stm												Number of lines: 2				Date: 8/7/2025	

Storm Sewer Summary Report

Line No.	Line ID	Flow rate (cfs)	Line Size (in)	Line shape	Line length (ft)	Invert EL Dn (ft)	Invert EL Up (ft)	Line Slope (%)	HGL Down (ft)	HGL Up (ft)	Minor loss (ft)	HGL Junct (ft)	Dns Line No.	Junction Type
1	ST-B2 - ST-B1	6.24	15	Cir	120.512	611.00	621.00	8.298	612.01	622.01	n/a	622.01	End	DropGrate
2	ST-B3 - ST-B2	4.53	12	Cir	207.150	621.00	625.00	1.931	622.01	625.89	n/a	625.89 j	1	Manhole
Project File: New.stm									Number of lines: 2			Run Date: 8/7/2025		
NOTES: Return period = 10 Yrs. ; j - Line contains hyd. jump.														

Line No.	Area Dn (sqft)	Area Up (sqft)	Byp Ln No	Coeff C1 (C)	Coeff C2 (C)	Coeff C3 (C)	Capac Full (cfs)	Crit Depth (ft)	Cross SI, Sw (ft/ft)	Cross SI, Sx (ft/ft)	Curb Len (ft)	Defl Ang (Deg)	Depth Dn (ft)	Depth Up (ft)	DnStm Ln No	Drng Area (ac)	Easting X (ft)	EGL Dn (ft)	EGL Up (ft)	Energy Loss (ft)	
1	1.06	1.06	Sag	0.35	0.50	0.95	20.15	1.01	0.050	0.020		-31.955	1.01	1.01**	Outfall	0.45	1616916.40	612.55	622.55	0.000	
2	0.74	0.74	1	0.35	0.50	0.95	5.36	0.89				0.257	1.00	0.89**	1	0.63	1617092.65	622.53	626.48	2.705	


Flow Rate	Sf Ave	Sf Dn	Grate Area	Grate Len	Grate Width	Gnd/Rim El Dn	Gnd/Rim El Up	Gutter Depth	Gutter Slope	Gutter Spread	Gutter Width	HGL Dn	HGL Up	HGL Jnct	HGL Jmp Dn	HGL Jmp Up	Incr CxA	Incr Q	Inlet Depth	Inlet Eff	
(cfs)	(ft/ft)	(ft/ft)	(sqft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft/ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)		(cfs)	(ft)	(%)	
6.24	0.000	0.000	5.06	2.53	2.00	612.78	627.00	0.38	Sag	40.16	2.00	612.01	622.01	622.01			0.25	1.87	0.38	100	
4.53	1.306	1.381				627.00	628.83					622.01	625.89 j	625.89	622.29	622.22	0.60	4.53			
													Number of lines: 2			Date: 8/7/2025					
NOTES: ** Critical depth																					

Inlet ID	Inlet Loc		Inlet Time	i Sys	i Inlet	Invert Dn	Invert Up	Jump Loc	Jump Len	Vel Hd Jmp Dn	Vel Hd Jmp Up	J-Loss Coeff	Junct Type	Known Q	Cost RCP	Cost CMP	Cost PVC	Line ID
		(ft)	(min)	(in/hr)	(in/hr)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)			(cfs)				
ST-B2	Sag		5.0	7.37	7.57	611.00	621.00			0.00	0.00	0.50 z	Dp-Grate	0.00	4,023	3,620	3,419	ST-B2 - ST-B1
ST-B3	Sag		5.0	7.57	7.57	621.00	625.00	20.72	4.44	0.59	0.83	1.00 z	MH	0.00	6,277	5,649	5,335	ST-B3 - ST-B2
Project File: New.stm													Number of lines: 2			Date: 8/7/2025		
NOTES: Intensity = 73.40 / (Inlet time + 12.20) ^ 0.80 -- Return period = 10 Yrs. ; ** Critical depth																		

Line Length	Line Size	Line Slope	Line Type	Local Depr	n-val Gutter	n-val Pipe	Minor Loss	Northing Y	Pipe Travel	Q Byp	Q Capt	Q Carry	Line Rise	Runoff Coeff	Line Span	Area A1	Area A2	Area A3	Tc	Throat Ht	Total Area	Total CxA
(ft)	(in)	(%)		(in)			(ft)	(ft)	(min)	(cfs)	(cfs)	(cfs)	(in)	(C)	(in)	(ac)	(ac)	(ac)	(min)	(in)	(ac)	
120.512	15	8.30	Cir			0.012	n/a	451937.67	0.41	0.00	6.41	4.53	15	0.55	15	0.30	0.00	0.15	5.6		1.08	0.85
207.150	12	1.93	Cir			0.012	n/a	452046.51	0.60				12	0.95	12	0.00	0.00	0.63	5.0		0.63	0.60
Project File: New.stm													Number of lines: 2					Date: 8/7/2025				
NOTES: ** Critical depth																						

Storm Sewers

Hydraflow Storm Sewers Extension for Autodesk® Civil 3D® Plan



Storm Sewer Inventory Report

Line No.	Alignment				Flow Data				Physical Data								Line ID
	Dnstr Line No.	Line Length (ft)	Defl angle (deg)	Junc Type	Known Q (cfs)	Drng Area (ac)	Runoff Coeff (C)	Inlet Time (min)	Invert El Dn (ft)	Line Slope (%)	Invert El Up (ft)	Line Size (in)	Line Shape	N Value (n)	J-Loss Coeff (K)	Inlet/ Rim El (ft)	
1	End	87.053	-121.899	DrGrt	0.00	0.50	0.61	5.0	617.00	4.59	621.00	15	Cir	0.012	1.50	627.00	ST-C2 - ST-C1
2	1	249.817	90.069	MH	0.00	0.88	0.95	5.0	621.00	1.20	624.00	15	Cir	0.012	1.00	628.67	ST-C3 - ST-C2
Project File: New.stm												Number of lines: 2				Date: 8/7/2025	

Storm Sewer Summary Report

Line No.	Line ID	Flow rate (cfs)	Line Size (in)	Line shape	Line length (ft)	Invert EL Dn (ft)	Invert EL Up (ft)	Line Slope (%)	HGL Down (ft)	HGL Up (ft)	Minor loss (ft)	HGL Junct (ft)	Dns Line No.	Junction Type
1	ST-C2 - ST-C1	8.33	15	Cir	87.053	617.00	621.00	4.595	618.13	622.13	n/a	622.13	End	DropGrate
2	ST-C3 - ST-C2	6.33	15	Cir	249.817	621.00	624.00	1.201	622.13	625.01	n/a	625.01 j	1	Manhole
Project File: New.stm									Number of lines: 2			Run Date: 8/7/2025		
NOTES: Return period = 10 Yrs. ; j - Line contains hyd. jump.														

Line No.	Area Dn (sqft)	Area Up (sqft)	Byp Ln No	Coeff C1 (C)	Coeff C2 (C)	Coeff C3 (C)	Capac Full (cfs)	Crit Depth (ft)	Cross SI, Sw (ft/ft)	Cross SI, Sx (ft/ft)	Curb Len (ft)	Defl Ang (Deg)	Depth Dn (ft)	Depth Up (ft)	DnStm Ln No	Drng Area (ac)	Easting X (ft)	EGL Dn (ft)	EGL Up (ft)	Energy Loss (ft)
1	1.17	1.17	Sag	0.35	0.50	0.95	15.00	1.13	0.050	0.020		-121.899	1.13	1.13**	Outfall	0.50	1617138.53	618.92	622.92	0.000
2	1.07	1.07	1	0.35	0.50	0.95	7.67	1.01				90.069	1.13	1.01**	1	0.88	1617350.78	622.68	625.56	0.000

Project File: New.stm

Number of lines: 2

Date: 8/7/2025

NOTES: ** Critical depth

MyReport


Flow Rate	Sf Ave	Sf Dn	Grate Area	Grate Len	Grate Width	Gnd/Rim El Dn	Gnd/Rim El Up	Gutter Depth	Gutter Slope	Gutter Spread	Gutter Width	HGL Dn	HGL Up	HGL Jnct	HGL Jmp Dn	HGL Jmp Up	Incr CxA	Incr Q	Inlet Depth	Inlet Eff
(cfs)	(ft/ft)	(ft/ft)	(sqft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft/ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)		(cfs)	(ft)	(%)
8.33	0.000	0.000	5.06	2.53	2.00	619.78	627.00	0.47	Sag	48.58	2.00	618.13	622.13	622.13			0.31	2.31	0.47	100
6.33	0.000	0.000				627.00	628.67					622.13	625.01 j	625.01	622.31	622.24	0.84	6.33		
Project File: New.stm												Number of lines: 2				Date: 8/7/2025				
NOTES: ** Critical depth																				

Inlet ID	Inlet Loc		Inlet Time	i Sys	i Inlet	Invert Dn	Invert Up	Jump Loc	Jump Len	Vel Hd Jmp Dn	Vel Hd Jmp Up	J-Loss Coeff	Junct Type	Known Q	Cost RCP	Cost CMP	Cost PVC	Line ID
		(ft)	(min)	(in/hr)	(in/hr)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)			(cfs)				
ST-C2	Sag		5.0	7.30	7.57	617.00	621.00			0.00	0.00	1.50 z	Dp-Grate	0.00	3,003	2,702	2,552	ST-C2 - ST-C1
ST-C3	Sag		5.0	7.57	7.57	621.00	624.00	24.98	5.07	0.55	0.74	1.00 z	MH	0.00	8,853	7,967	7,525	ST-C3 - ST-C2
Project File: New.stm													Number of lines: 2			Date: 8/7/2025		
NOTES: Intensity = 73.40 / (Inlet time + 12.20) ^ 0.80 -- Return period = 10 Yrs. ; ** Critical depth																		

Line Length	Line Size	Line Slope	Line Type	Local Depr	n-val Gutter	n-val Pipe	Minor Loss	Northing Y	Pipe Travel	Q Byp	Q Capt	Q Carry	Line Rise	Runoff Coeff	Line Span	Area A1	Area A2	Area A3	Tc	Throat Ht	Total Area	Total CxA
(ft)	(in)	(%)		(in)			(ft)	(ft)	(min)	(cfs)	(cfs)	(cfs)	(in)	(C)	(in)	(ac)	(ac)	(ac)	(min)	(in)	(ac)	
87.053	15	4.59	Cir			0.012	n/a	452067.88	0.22	0.00	8.64	6.33	15	0.61	15	0.28	0.00	0.22	5.8		1.38	1.14
249.817	15	1.20	Cir			0.012	n/a	452199.64	0.81				15	0.95	15	0.00	0.00	0.88	5.0		0.88	0.84
Project File: New.stm														Number of lines: 2				Date: 8/7/2025				
NOTES: ** Critical depth																						

Storm Sewers

Hydraflow Storm Sewers Extension for Autodesk® Civil 3D® Plan



Storm Sewer Inventory Report

Line No.	Alignment				Flow Data				Physical Data								Line ID
	Dnstr Line No.	Line Length (ft)	Defl angle (deg)	Junc Type	Known Q (cfs)	Drng Area (ac)	Runoff Coeff (C)	Inlet Time (min)	Invert El Dn (ft)	Line Slope (%)	Invert El Up (ft)	Line Size (in)	Line Shape	N Value (n)	J-Loss Coeff (K)	Inlet/ Rim El (ft)	
1	End	81.446	-121.043	DrGrt	0.00	0.30	0.65	5.0	619.00	3.68	622.00	18	Cir	0.012	1.50	628.00	ST-D2 - ST-D1
2	1	137.097	91.907	MH	0.00	0.43	0.95	5.0	622.00	0.73	623.00	18	Cir	0.012	0.15	629.35	ST-D3 - ST-D2
3	2	148.658	-2.824	MH	0.00	0.62	0.95	5.0	623.00	0.67	624.00	15	Cir	0.012	1.00	629.15	ST-D4 - ST-D3
Project File: New.stm												Number of lines: 3				Date: 8/7/2025	

Storm Sewer Summary Report

Line No.	Line ID	Flow rate (cfs)	Line Size (in)	Line shape	Line length (ft)	Invert EL Dn (ft)	Invert EL Up (ft)	Line Slope (%)	HGL Down (ft)	HGL Up (ft)	Minor loss (ft)	HGL Junct (ft)	Dns Line No.	Junction Type
1	ST-D2 - ST-D1	8.55	18	Cir	81.446	619.00	622.00	3.683	620.13	623.13	n/a	623.13	End	DropGrate
2	ST-D3 - ST-D2	7.33	18	Cir	137.097	622.00	623.00	0.729	623.13	624.05	n/a	624.05 j	1	Manhole
3	ST-D4 - ST-D3	4.46	15	Cir	148.658	623.00	624.00	0.673	624.05	624.86	n/a	624.86 j	2	Manhole
Project File: New.stm									Number of lines: 3			Run Date: 8/7/2025		
NOTES: Return period = 10 Yrs. ; j - Line contains hyd. jump.														

Line No.	Area Dn (sqft)	Area Up (sqft)	Byp Ln No	Coeff C1 (C)	Coeff C2 (C)	Coeff C3 (C)	Capac Full (cfs)	Crit Depth (ft)	Cross SI, Sw (ft/ft)	Cross SI, Sx (ft/ft)	Curb Len (ft)	Defl Ang (Deg)	Depth Dn (ft)	Depth Up (ft)	DnStm Ln No	Drng Area (ac)	Easting X (ft)	EGL Dn (ft)	EGL Up (ft)	Energy Loss (ft)
1	1.43	1.43	Sag	0.35	0.50	0.95	21.83	1.13	0.050	0.020		-121.043	1.13	1.13**	Outfall	0.30	1617391.90	620.69	623.69	0.000
2	1.32	1.32	1	0.35	0.50	0.95	9.72	1.05				91.907	1.13	1.05**	1	0.43	1617511.65	623.61	624.53	0.000
3	0.89	0.89	2	0.35	0.50	0.95	5.74	0.86				-2.824	1.05	0.86**	2	0.62	1617637.78	624.43	625.24	0.000

Project File: New.stm

Number of lines: 3

Date: 8/7/2025

NOTES: ** Critical depth

Flow Rate	Sf Ave	Sf Dn	Grate Area	Grate Len	Grate Width	Gnd/Rim El Dn	Gnd/Rim El Up	Gutter Depth	Gutter Slope	Gutter Spread	Gutter Width	HGL Dn	HGL Up	HGL Jnct	HGL Jmp Dn	HGL Jmp Up	Incr CxA	Incr Q	Inlet Depth	Inlet Eff
(cfs)	(ft/ft)	(ft/ft)	(sqft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft/ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)		(cfs)	(ft)	(%)
8.55	0.000	0.000	5.06	2.53	2.00	621.03	628.00	0.48	Sag	49.98	2.00	620.13	623.13	623.13			0.20	1.48	0.48	100
7.33	0.000	0.000				628.00	629.35					623.13	624.05 j	624.05	623.15	623.12	0.41	3.09		
4.46	0.000	0.000				629.35	629.15					624.05	624.86 j	624.86	624.66	624.66	0.59	4.46		
Project File: New.stm													Number of lines: 3			Date: 8/7/2025				
NOTES: ** Critical depth																				

Inlet ID	Inlet Loc	(ft)	Inlet Time (min)	i Sys (in/hr)	i Inlet (in/hr)	Invert Dn (ft)	Invert Up (ft)	Jump Loc (ft)	Jump Len (ft)	Vel Hd Jmp Dn (ft)	Vel Hd Jmp Up (ft)	J-Loss Coeff	Junct Type	Known Q (cfs)	Cost RCP	Cost CMP	Cost PVC	Line ID
ST-D2	Sag		5.0	7.17	7.57	619.00	622.00			0.00	0.00	1.50 z	Dp-Grate	0.00	3,040	2,736	2,584	ST-D2 - ST-D1
ST-D3	Sag		5.0	7.34	7.57	622.00	623.00	13.71	5.25	0.48	0.56	0.15 z	MH	0.00	6,295	5,666	5,351	ST-D3 - ST-D2
ST-D4	Sag		5.0	7.57	7.57	623.00	624.00	118.93	4.29	0.38	0.41	1.00 z	MH	0.00	5,533	4,979	4,703	ST-D4 - ST-D3

Project File: New.stm

Number of lines: 3


Date: 8/7/2025

NOTES: Intensity = 73.40 / (Inlet time + 12.20) ^ 0.80 -- Return period = 10 Yrs. ; ** Critical depth

Line Length	Line Size	Line Slope	Line Type	Local Depr	n-val Gutter	n-val Pipe	Minor Loss	Northing Y	Pipe Travel	Q Byp	Q Capt	Q Carry	Line Rise	Runoff Coeff	Line Span	Area A1	Area A2	Area A3	Tc	Throat Ht	Total Area	Total CxA
(ft)	(in)	(%)		(in)			(ft)	(ft)	(min)	(cfs)	(cfs)	(cfs)	(in)	(C)	(in)	(ac)	(ac)	(ac)	(min)	(in)	(ac)	
81.446	18	3.68	Cir			0.012	n/a	452221.39	0.28	0.00	9.03	7.56	18	0.65	18	0.15	0.00	0.15	6.2		1.35	1.19
137.097	18	0.73	Cir			0.012	n/a	452288.14	0.55				18	0.95	18	0.00	0.00	0.43	5.7		1.05	1.00
148.658	15	0.67	Cir			0.012	n/a	452366.82	0.68				15	0.95	15	0.00	0.00	0.62	5.0		0.62	0.59
Project File: New.stm													Number of lines: 3					Date: 8/7/2025				
NOTES: ** Critical depth																						

Storm Sewers

Hydraflow Storm Sewers Extension for Autodesk® Civil 3D® Plan



Storm Sewer Inventory Report

Line No.	Alignment				Flow Data				Physical Data								Line ID
	Dnstr Line No.	Line Length (ft)	Defl angle (deg)	Junc Type	Known Q (cfs)	Drng Area (ac)	Runoff Coeff (C)	Inlet Time (min)	Invert El Dn (ft)	Line Slope (%)	Invert El Up (ft)	Line Size (in)	Line Shape	N Value (n)	J-Loss Coeff (K)	Inlet/ Rim El (ft)	
1	End	79.131	-121.631	DrGrt	0.00	0.30	0.53	5.0	621.00	1.26	622.00	18	Cir	0.012	1.50	628.00	ST-E2 - ST-E1
2	1	180.741	90.142	MH	0.00	0.58	0.95	5.0	622.00	1.11	624.00	15	Cir	0.012	0.15	628.97	ST-E3 - ST-E2
3	2	96.148	-0.130	MH	0.00	0.34	0.95	5.0	624.00	1.04	625.00	12	Cir	0.012	1.00	628.00	ST-E4 - ST-E3
Project File: New.stm												Number of lines: 3				Date: 8/7/2025	

Storm Sewer Summary Report

Line No.	Line ID	Flow rate (cfs)	Line Size (in)	Line shape	Line length (ft)	Invert EL Dn (ft)	Invert EL Up (ft)	Line Slope (%)	HGL Down (ft)	HGL Up (ft)	Minor loss (ft)	HGL Junct (ft)	Dns Line No.	Junction Type
1	ST-E2 - ST-E1	7.45	18	Cir	79.131	621.00	622.00	1.264	622.06	623.06	n/a	623.06	End	DropGrate
2	ST-E3 - ST-E2	6.47	15	Cir	180.741	622.00	624.00	1.107	623.06	625.02	n/a	625.02 j	1	Manhole
3	ST-E4 - ST-E3	2.45	12	Cir	96.148	624.00	625.00	1.040	625.02	625.67	n/a	625.67 j	2	Manhole
Project File: New.stm									Number of lines: 3			Run Date: 8/7/2025		
NOTES: Return period = 10 Yrs. ; j - Line contains hyd. jump.														

Line No.	Area Dn	Area Up	Byp Ln No	Coeff C1	Coeff C2	Coeff C3	Capac Full	Crit Depth	Cross SI, Sw	Cross SI, Sx	Curb Len	Defl Ang	Depth Dn	Depth Up	DnStm Ln No	Drng Area	Easting X	EGL Dn	EGL Up	Energy Loss
	(sqft)	(sqft)		(C)	(C)	(C)	(cfs)	(ft)	(ft/ft)	(ft/ft)	(ft)	(Deg)	(ft)	(ft)		(ac)	(ft)	(ft)	(ft)	(ft)
1	1.33	1.33	Sag	0.35	0.50	0.95	12.79	1.06	0.050	0.020		-121.631	1.06	1.06**	Outfall	0.30	1617646.53	622.54	623.54	0.000
2	1.08	1.08	1	0.35	0.50	0.95	7.36	1.02				90.142	1.06	1.02**	1	0.58	1617800.65	623.62	625.59	0.000
3	0.56	0.56	2	0.35	0.50	0.95	3.93	0.67				-0.130	1.00	0.67**	2	0.34	1617882.53	625.17	625.97	0.505

Flow Rate	Sf Ave	Sf Dn	Grate Area	Grate Len	Grate Width	Gnd/Rim El Dn	Gnd/Rim El Up	Gutter Depth	Gutter Slope	Gutter Spread	Gutter Width	HGL Dn	HGL Up	HGL Jnct	HGL Jmp Dn	HGL Jmp Up	Incr CxA	Incr Q	Inlet Depth	Inlet Eff				
(cfs)	(ft/ft)	(ft/ft)	(sqft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft/ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)		(cfs)	(ft)	(%)				
7.45	0.000	0.000	5.06	2.53	2.00	623.60	628.00	0.44	Sag	45.59	2.00	622.06	623.06	623.06			0.16	1.20	0.44	100				
6.47	0.000	0.000				628.00	628.97					623.06	625.02 j	625.02	623.23	623.18	0.55	4.17						
2.45	0.525	0.402				628.97	628.00					625.02	625.67 j	625.67	625.07	624.82	0.32	2.45						


MyReport

Inlet ID	Inlet Loc		Inlet Time	i Sys	i Inlet	Invert Dn	Invert Up	Jump Loc	Jump Len	Vel Hd Jmp Dn	Vel Hd Jmp Up	J-Loss Coeff	Junct Type	Known Q	Cost RCP	Cost CMP	Cost PVC	Line ID
		(ft)	(min)	(in/hr)	(in/hr)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)			(cfs)				
ST-E2	Sag		5.0	7.21	7.57	621.00	622.00			0.00	0.00	1.50 z	Dp-Grate	0.00	3,020	2,718	2,567	ST-E2 - ST-E1
ST-E3	Sag		5.0	7.40	7.57	622.00	624.00	18.07	5.13	0.56	0.69	0.15 z	MH	0.00	6,438	5,794	5,472	ST-E3 - ST-E2
ST-E4	Sag		5.0	7.57	7.57	624.00	625.00	19.23	4.34	0.18	0.43	1.00 z	MH	0.00	2,882	2,594	2,450	ST-E4 - ST-E3
</																		

Line Length	Line Size	Line Slope	Line Type	Local Depr	n-val Gutter	n-val Pipe	Minor Loss	Northing Y	Pipe Travel	Q Byp	Q Capt	Q Carry	Line Rise	Runoff Coeff	Line Span	Area A1	Area A2	Area A3	Tc	Throat Ht	Total Area	Total CxA
(ft)	(in)	(%)		(in)			(ft)	(ft)	(min)	(cfs)	(cfs)	(cfs)	(in)	(C)	(in)	(ac)	(ac)	(ac)	(min)	(in)	(ac)	
79.131	18	1.26	Cir			0.012	n/a	452383.95	0.32	0.00	7.82	6.62	18	0.53	18	0.21	0.00	0.09	6.1		1.22	1.03
180.741	15	1.11	Cir			0.012	n/a	452478.35	0.57				15	0.95	15	0.00	0.00	0.58	5.5		0.92	0.87
96.148	12	1.04	Cir			0.012	n/a	452528.76	0.51				12	0.95	12	0.00	0.00	0.34	5.0		0.34	0.32
Project File: New.stm													Number of lines: 3					Date: 8/7/2025				
NOTES: ** Critical depth																						

Storm Sewers

Hydraflow Storm Sewers Extension for Autodesk® Civil 3D® Plan



Project File: New.stm	Number of lines: 5	Date: 8/7/2025
-----------------------	--------------------	----------------

Storm Sewer Inventory Report

Line No.	Alignment				Flow Data				Physical Data								Line ID
	Dnstr Line No.	Line Length (ft)	Defl angle (deg)	Junc Type	Known Q (cfs)	Drng Area (ac)	Runoff Coeff (C)	Inlet Time (min)	Invert El Dn (ft)	Line Slope (%)	Invert El Up (ft)	Line Size (in)	Line Shape	N Value (n)	J-Loss Coeff (K)	Inlet/ Rim El (ft)	
1	End	59.180	-123.455	DrGrt	0.00	0.23	0.56	5.0	624.00	0.52	624.31	24	Cir	0.012	1.50	628.00	ST-F6 - ST-F4
2	1	57.777	31.719	DrGrt	0.00	0.63	0.70	5.0	624.31	0.50	624.60	21	Cir	0.012	0.84	628.20	ST-F5 - ST-F3
3	2	137.271	-30.514	DrGrt	0.00	0.61	0.74	5.0	624.60	0.51	625.30	18	Cir	0.012	1.23	628.50	ST-F3 - ST-F2
4	3	79.073	-51.647	DrGrt	0.00	0.60	0.49	5.0	625.30	0.51	625.70	15	Cir	0.012	1.00	628.00	ST-F2 - ST-F1
5	1	63.350	91.929	Curb	0.00	0.45	0.72	5.0	624.31	1.88	625.50	15	Cir	0.012	1.00	630.19	ST-F5 - ST-F4
Project File: New.stm												Number of lines: 5				Date: 8/7/2025	

Storm Sewer Summary Report

Line No.	Line ID	Flow rate (cfs)	Line Size (in)	Line shape	Line length (ft)	Invert EL Dn (ft)	Invert EL Up (ft)	Line Slope (%)	HGL Down (ft)	HGL Up (ft)	Minor loss (ft)	HGL Junct (ft)	Dns Line No.	Junction Type
1	ST-F6 - ST-F4	11.50	24	Cir	59.180	624.00	624.31	0.524	625.22	625.53	n/a	625.53	End	DropGrate
2	ST-F5 - ST-F3	8.42	21	Cir	57.777	624.31	624.60	0.502	625.53	625.68	n/a	625.68	1	DropGrate
3	ST-F3 - ST-F2	5.46	18	Cir	137.271	624.60	625.30	0.510	625.68	626.20	n/a	626.20 j	2	DropGrate
4	ST-F2 - ST-F1	2.23	15	Cir	79.073	625.30	625.70	0.506	626.20	626.30	n/a	626.30 j	3	DropGrate
5	ST-F5 - ST-F4	2.45	15	Cir	63.350	624.31	625.50	1.878	625.53	626.13	n/a	626.13 j	1	Curb-Horiz
Project File: New.stm									Number of lines: 5			Run Date: 8/7/2025		
NOTES: Return period = 10 Yrs. ; j - Line contains hyd. jump.														

Line No.	Area Dn (sqft)	Area Up (sqft)	Byp Ln No	Coeff C1 (C)	Coeff C2 (C)	Coeff C3 (C)	Capac Full (cfs)	Crit Depth (ft)	Cross SI, Sw (ft/ft)	Cross SI, Sx (ft/ft)	Curb Len (ft)	Defl Ang (Deg)	Depth Dn (ft)	Depth Up (ft)	DnStm Ln No	Drng Area (ac)	Easting X (ft)	EGL Dn (ft)	EGL Up (ft)	Energy Loss (ft)
1	2.00	2.00	Sag	0.35	0.50	0.95	17.73	1.22	0.050	0.020		-123.455	1.22	1.22**	Outfall	0.23	1617916.90	625.73	626.04	0.000
2	1.55	1.55	1	0.35	0.50	0.95	12.16	1.08	0.050	0.020		31.719	1.22	1.08**	1	0.63	1617915.15	625.98	626.13	0.000
3	1.11	1.11	2	0.35	0.50	0.95	8.12	0.90	0.050	0.020		-30.514	1.08	0.90**	2	0.61	1617841.90	625.93	626.58	0.562
4	0.58	0.58	3	0.35	0.50	0.95	4.98	0.60	0.020	0.020		-51.647	0.90	0.60**	3	0.60	1617763.28	626.43	626.53	0.000
5	0.62	0.62	1	0.35	0.50	0.95	9.59	0.63	0.050	0.020	4.25	91.929	1.22	0.63**	1	0.45	1617970.90	625.77	626.37	0.000

Project File: New.stm

Number of lines: 5

Date: 8/7/2025

NOTES: ** Critical depth

MyReport

Flow Rate	Sf Ave	Sf Dn	Grate Area	Grate Len	Grate Width	Gnd/Rim El Dn	Gnd/Rim El Up	Gutter Depth	Gutter Slope	Gutter Spread	Gutter Width	HGL Dn	HGL Up	HGL Jnct	HGL Jmp Dn	HGL Jmp Up	Incr CxA	Incr Q	Inlet Depth	Inlet Eff
(cfs)	(ft/ft)	(ft/ft)	(sqft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft/ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)		(cfs)	(ft)	(%)
11.50	0.000	0.000	5.06	2.53	2.00	626.81	628.00	0.11	Sag	12.87	2.00	625.22	625.53	625.53			0.13	0.98	0.11	100
8.42	0.000	0.000	5.06	2.53	2.00	628.00	628.20	0.25	Sag	26.71	2.00	625.53	625.68	625.68			0.44	3.34	0.25	100
5.46	0.409	0.308	5.06	2.53	2.00	628.20	628.50	0.25	Sag	27.10	2.00	625.68	626.20 j	626.20	625.71	625.66	0.45	3.42	0.25	100
2.23	0.000	0.000	5.06	2.53	2.00	628.50	628.00	0.19	Sag	20.85	2.00	626.20	626.30 j	626.30	626.22	626.18	0.29	2.23	0.19	100
2.45	0.000	0.000				628.00	630.19	0.32	Sag	13.21	2.00	625.53	626.13 j	626.13	625.51	625.07	0.32	2.45	0.32	100

Project File: New.stm

Number of lines: 5

Date: 8/7/2025

NOTES: ** Critical depth

Inlet ID	Inlet Loc		Inlet Time	i Sys	i Inlet	Invert Dn	Invert Up	Jump Loc	Jump Len	Vel Hd Jmp Dn	Vel Hd Jmp Up	J-Loss Coeff	Junct Type	Known Q	Cost RCP	Cost CMP	Cost PVC	Line ID
		(ft)	(min)	(in/hr)	(in/hr)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)			(cfs)				
ST-F4	Sag		5.0	7.02	7.57	624.00	624.31			0.00	0.00	1.50 z	Dp-Grate	0.00	2,224	2,002	1,890	ST-F6 - ST-F4
ST-F3	Sag		5.0	7.10	7.57	624.31	624.60			0.00	0.00	0.84 z	Dp-Grate	0.00	2,055	1,850	1,747	ST-F5 - ST-F3
ST-F2	Sag		5.0	7.33	7.57	624.60	625.30	27.45	4.83	0.32	0.38	1.23 z	Dp-Grate	0.00	4,484	4,036	3,811	ST-F3 - ST-F2
ST-F1	Sag		5.0	7.57	7.57	625.30	625.70	55.35	3.18	0.20	0.24	1.00 z	Dp-Grate	0.00	2,470	2,223	2,100	ST-F2 - ST-F1
ST-F5	Sag		5.0	7.57	7.57	624.31	625.50	12.67	4.83	0.09	0.65	1.00 z	Curb	0.00	2,228	2,005	1,893	ST-F5 - ST-F4

Project File: New.stm

Number of lines: 5


Date: 8/7/2025

NOTES: Intensity = 73.40 / (Inlet time + 12.20) ^ 0.80 -- Return period = 10 Yrs. ; ** Critical depth

Line Length	Line Size	Line Slope	Line Type	Local Depr	n-val Gutter	n-val Pipe	Minor Loss	Northing Y	Pipe Travel	Q Byp	Q Capt	Q Carry	Line Rise	Runoff Coeff	Line Span	Area A1	Area A2	Area A3	Tc	Throat Ht	Total Area	Total CxA
(ft)	(in)	(%)		(in)			(ft)	(ft)	(min)	(cfs)	(cfs)	(cfs)	(in)	(C)	(in)	(ac)	(ac)	(ac)	(min)	(in)	(ac)	
59.180	24	0.52	Cir			0.012	n/a	452534.07	0.27	0.00	0.98	0.00	24	0.56	24	0.15	0.00	0.08	6.7		2.52	1.64
57.777	21	0.50	Cir			0.012	n/a	452591.82	0.27	0.00	3.34	0.00	21	0.70	21	0.26	0.00	0.37	6.5		1.84	1.19
137.271	18	0.51	Cir			0.012	n/a	452707.92	0.73	0.00	3.42	0.00	18	0.74	18	0.21	0.00	0.40	5.7		1.21	0.75
79.073	15	0.51	Cir			0.012	n/a	452716.32	0.73	0.00	2.23	0.00	15	0.49	15	0.46	0.00	0.14	5.0		0.60	0.29
63.350	15	1.88	Cir	0.0		0.012	n/a	452567.20	0.53	0.00	2.45	0.00	15	0.72	15	0.17	0.00	0.28	5.0	4.0	0.45	0.32
Project File: New.stm														Number of lines: 5			Date: 8/7/2025					
NOTES: ** Critical depth																						

Storm Sewers

Hydraflow Storm Sewers Extension for Autodesk® Civil 3D® Plan



Project File: G-Double.stm	Number of lines: 1	Date: 8/11/2025
----------------------------	--------------------	-----------------

Storm Sewer Inventory Report

Line No.	Alignment				Flow Data				Physical Data								Line ID
	Dnstr Line No.	Line Length (ft)	Defl angle (deg)	Junc Type	Known Q (cfs)	Drng Area (ac)	Runoff Coeff (C)	Inlet Time (min)	Invert El Dn (ft)	Line Slope (%)	Invert El Up (ft)	Line Size (in)	Line Shape	N Value (n)	J-Loss Coeff (K)	Inlet/ Rim El (ft)	
1	End	22.456	147.792	Hdwl	0.00	0.27	0.86	5.0	626.50	1.78	626.90	8	Cir(2b)	0.012	1.00	628.09	ST-G2 - ST-G1 -Dou
Project File: G-Double.stm												Number of lines: 1			Date: 8/11/2025		

Storm Sewer Summary Report

Line No.	Line ID	Flow rate (cfs)	Line Size (in)	Line shape	Line length (ft)	Invert EL Dn (ft)	Invert EL Up (ft)	Line Slope (%)	HGL Down (ft)	HGL Up (ft)	Minor loss (ft)	HGL Junct (ft)	Dns Line No.	Junction Type
1	ST-G2 - ST-G1 -Double 8in Plpe	1.76	8	Cir(2b)	22.456	626.50	626.90	1.781	626.87	627.27	n/a	627.27	End	OpenHeadwall
Project File: G-Double.stm									Number of lines: 1			Run Date: 8/11/2025		
NOTES: Return period = 10 Yrs.														

Line No.	Area Dn (sqft)	Area Up (sqft)	Byp Ln No	Coeff C1 (C)	Coeff C2 (C)	Coeff C3 (C)	Capac Full (cfs)	Crit Depth (ft)	Cross SI, Sw (ft/ft)	Cross SI, Sx (ft/ft)	Curb Len (ft)	Defl Ang (Deg)	Depth Dn (ft)	Depth Up (ft)	DnStm Ln No	Drng Area (ac)	Easting X (ft)	EGL Dn (ft)	EGL Up (ft)	Energy Loss (ft)
1	0.40	0.40	n/a	0.35	0.50	0.95	3.49	0.37				147.792	0.37	0.37**	Outfall	0.27	1617019.78	627.17	627.57	0.000

Project File: G-Double.stm

Number of lines: 1

Date: 8/11/2025

NOTES: ** Critical depth


Flow Rate	Sf Ave	Sf Dn	Grate Area	Grate Len	Grate Width	Gnd/Rim El Dn	Gnd/Rim El Up	Gutter Depth	Gutter Slope	Gutter Spread	Gutter Width	HGL Dn	HGL Up	HGL Jnct	HGL Jmp Dn	HGL Jmp Up	Incr CxA	Incr Q	Inlet Depth	Inlet Eff
(cfs)	(ft/ft)	(ft/ft)	(sqft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft/ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)		(cfs)	(ft)	(%)
1.76	0.000	0.000				627.69	628.09					626.87	627.27	627.27			0.23	1.76		100
Project File: G-Double.stm												Number of lines: 1				Date: 8/11/2025				
NOTES: ** Critical depth																				

Inlet ID	Inlet Loc		Inlet Time	i Sys	i Inlet	Invert Dn	Invert Up	Jump Loc	Jump Len	Vel Hd Jmp Dn	Vel Hd Jmp Up	J-Loss Coeff	Junct Type	Known Q	Cost RCP	Cost CMP	Cost PVC	
		(ft)	(min)	(in/hr)	(in/hr)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)			(cfs)				
ST-G1	Sag		5.0	7.57	7.57	626.50	626.90			0.00	0.00	1.00 z	Hdwall	0.00	0	0	0	
Project File: G-Double.stm Number of lines: 1 Date: 8/11/2025 NOTES: Intensity = 73.40 / (Inlet time + 12.20) ^ 0.80 -- Return period = 10 Yrs. ; ** Critical depth																		

Line ID	Line Length (ft)	Line Size (in)	Line Slope (%)	Line Type	Local Depr (in)	n-val Gutter	n-val Pipe	Minor Loss (ft)	Northing Y (ft)	Pipe Travel (min)	Q Byp (cfs)	Q Capt (cfs)	Q Carry (cfs)	Line Rise (in)	Runoff Coeff (C)	Line Span (in)	Area A1 (ac)	Area A2 (ac)	Area A3 (ac)
ST-G2 - ST-G1 -Double 8in Pipe	22.456	8(2b)	1.78	Cir			0.012	n/a	452290.64	0.15	0.00	1.76	0.00	8	0.86	8	0.04	0.00	0.23
Project File: G-Double.stm										Number of lines: 1				Date: 8/11/2025					
NOTES: ** Critical depth																			

Tc	Throat Ht	Total Area	Total CxA	Total Runoff	Vel Ave	Vel Dn	Vel Hd Dn	Vel Hd Up	Vel Up	Cover Dn	Cover Up	Storage		
(min)	(in)	(ac)		(cfs)	(ft/s)	(ft/s)	(ft)	(ft)	(ft/s)	(ft)	(ft)	(cft)		
5.0		0.27	0.23	1.76	4.41	4.41	0.30	0.30	4.41	0.52	0.52	8.96		
Project File: G-Double.stm												Number of lines: 1		Date: 8/11/2025
NOTES: ** Critical depth														

Hydraflow Storm Sewers Extension for Autodesk® Civil 3D® Plan



Project File: H.stm	Number of lines: 1	Date: 8/11/2025
---------------------	--------------------	-----------------

Storm Sewer Inventory Report

Line No.	Alignment				Flow Data				Physical Data								Line ID
	Dnstr Line No.	Line Length (ft)	Defl angle (deg)	Junc Type	Known Q (cfs)	Drng Area (ac)	Runoff Coeff (C)	Inlet Time (min)	Invert El Dn (ft)	Line Slope (%)	Invert El Up (ft)	Line Size (in)	Line Shape	N Value (n)	J-Loss Coeff (K)	Inlet/ Rim El (ft)	
1	End	35.598	-31.430	Hdwl	1.89	0.66	0.78	5.0	623.97	0.55	624.17	18	Cir	0.012	1.00	626.73	ST-H1 - ST-H2
Project File: H.stm												Number of lines: 1				Date: 8/11/2025	

Storm Sewer Summary Report

Line No.	Line ID	Flow rate (cfs)	Line Size (in)	Line shape	Line length (ft)	Invert EL Dn (ft)	Invert EL Up (ft)	Line Slope (%)	HGL Down (ft)	HGL Up (ft)	Minor loss (ft)	HGL Junct (ft)	Dns Line No.	Junction Type
1	ST-H1 - ST-H2	5.79	18	Cir	35.598	623.97	624.17	0.553	625.77*	625.86*	0.17	626.03	End	OpenHeadwall
Project File: H.stm									Number of lines: 1			Run Date: 8/11/2025		
NOTES: Return period = 10 Yrs. ; *Surcharged (HGL above crown).														

Line No.	Area Dn (sqft)	Area Up (sqft)	Byp Ln No	Coeff C1 (C)	Coeff C2 (C)	Coeff C3 (C)	Capac Full (cfs)	Crit Depth (ft)	Cross SI, Sw (ft/ft)	Cross SI, Sx (ft/ft)	Curb Len (ft)	Defl Ang (Deg)	Depth Dn (ft)	Depth Up (ft)	DnStm Ln No	Drng Area (ac)	Easting X (ft)	EGL Dn (ft)	EGL Up (ft)	Energy Loss (ft)
1	1.77	1.77	n/a	0.35	0.50	0.95	8.46	0.93				-31.430	1.50	1.50	Outfall	0.66	1617373.40	625.94	626.03	0.092

Project File: H.stm

Number of lines: 1

Date: 8/11/2025

NOTES: ** Critical depth


Flow Rate	Sf Ave	Sf Dn	Grate Area	Grate Len	Grate Width	Gnd/Rim El Dn	Gnd/Rim El Up	Gutter Depth	Gutter Slope	Gutter Spread	Gutter Width	HGL Dn	HGL Up	HGL Jnct	HGL Jmp Dn	HGL Jmp Up	Incr CxA	Incr Q	Inlet Depth	Inlet Eff
(cfs)	(ft/ft)	(ft/ft)	(sqft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft/ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)		(cfs)	(ft)	(%)
5.79	0.259	0.259				626.53	626.73					625.77	625.86	626.03			0.51	5.79		100
Project File: H.stm													Number of lines: 1				Date: 8/11/2025			
NOTES: ** Critical depth																				

Inlet ID	Inlet Loc		Inlet Time	i Sys	i Inlet	Invert Dn	Invert Up	Jump Loc	Jump Len	Vel Hd Jmp Dn	Vel Hd Jmp Up	J-Loss Coeff	Junct Type	Known Q	Cost RCP	Cost CMP	Cost PVC	
		(ft)	(min)	(in/hr)	(in/hr)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)			(cfs)				
ST-H1	Sag		5.0	7.57	7.57	623.97	624.17			0.00	0.00	1.00	Hdwall	1.89	1,136	1,022	966	
Project File: H.stm Number of lines: 1 Date: 8/11/2025 NOTES: Intensity = 73.40 / (Inlet time + 12.20) ^ 0.80 -- Return period = 10 Yrs. ; ** Critical depth																		

Line ID	Line Length (ft)	Line Size (in)	Line Slope (%)	Line Type	Local Depr (in)	n-val Gutter	n-val Pipe	Minor Loss (ft)	Northing Y (ft)	Pipe Travel (min)	Q Byp (cfs)	Q Capt (cfs)	Q Carry (cfs)	Line Rise (in)	Runoff Coeff (C)	Line Span (in)	Area A1 (ac)	Area A2 (ac)	Area A3 (ac)
ST-H1 - ST-H2	35.598	18	0.55	Cir			0.012	0.17	452510.89	0.18	0.00	5.79	0.00	18	0.78	18	0.19	0.00	0.47
Project File: H.stm										Number of lines: 1					Date: 8/11/2025				
NOTES: ** Critical depth																			

Tc	Throat Ht	Total Area	Total CxA	Total Runoff	Vel Ave	Vel Dn	Vel Hd Dn	Vel Hd Up	Vel Up	Cover Dn	Cover Up	Storage			
(min)	(in)	(ac)		(cfs)	(ft/s)	(ft/s)	(ft)	(ft)	(ft/s)	(ft)	(ft)	(cft)			
5.0		0.66	0.51	3.90	3.28	3.28	0.17	0.17	3.28	1.06	1.06	62.89			
Project File: H.stm										Number of lines: 1			Date: 8/11/2025		
NOTES: ** Critical depth															

Hydraflow Storm Sewers Extension for Autodesk® Civil 3D® Plan



Project File: New.stm	Number of lines: 1	Date: 8/7/2025
-----------------------	--------------------	----------------

Storm Sewer Inventory Report

Line No.	Alignment				Flow Data				Physical Data								Line ID
	Dnstr Line No.	Line Length (ft)	Defl angle (deg)	Junc Type	Known Q (cfs)	Drng Area (ac)	Runoff Coeff (C)	Inlet Time (min)	Invert El Dn (ft)	Line Slope (%)	Invert El Up (ft)	Line Size (in)	Line Shape	N Value (n)	J-Loss Coeff (K)	Inlet/ Rim El (ft)	
1	End	24.314	-31.974	Hdwl	0.00	0.30	0.83	5.0	626.90	0.41	627.00	8	Cir(2b)	0.012	1.00	628.24	ST-I1 - ST-I2 (Dou
Project File: New.stm												Number of lines: 1				Date: 8/7/2025	

Storm Sewer Summary Report

Line No.	Line ID	Flow rate (cfs)	Line Size (in)	Line shape	Line length (ft)	Invert EL Dn (ft)	Invert EL Up (ft)	Line Slope (%)	HGL Down (ft)	HGL Up (ft)	Minor loss (ft)	HGL Junct (ft)	Dns Line No.	Junction Type
1	ST-I1 - ST-I2 (Double)	1.89	8	Cir(2b)	24.314	626.90	627.00	0.411	627.28	627.67	0.11	627.78	End	OpenHeadwall
Project File: New.stm									Number of lines: 1			Run Date: 8/7/2025		
NOTES: Return period = 10 Yrs.														

Line No.	Area Dn	Area Up	Byp Ln No	Coeff C1	Coeff C2	Coeff C3	Capac Full	Crit Depth	Cross Sl, Sw	Cross Sl, Sx	Curb Len	Defl Ang	Depth Dn	Depth Up	DnStm Ln No	Drng Area	Easting X	EGL Dn	EGL Up	Energy Loss
	(sqft)	(sqft)		(C)	(C)	(C)	(cfs)	(ft)	(ft/ft)	(ft/ft)	(ft)	(Deg)	(ft)	(ft)		(ac)	(ft)	(ft)	(ft)	(ft)
1	0.42	0.70	n/a	0.35	0.50	0.95	1.68	0.38				-31.974	0.38	0.67	Outfall	0.30	1617600.40	627.60	627.78	0.219
Project File: New.stm													Number of lines: 1				Date: 8/7/2025			
NOTES: ** Critical depth																				


Flow Rate	Sf Ave	Sf Dn	Grate Area	Grate Len	Grate Width	Gnd/Rim El Dn	Gnd/Rim El Up	Gutter Depth	Gutter Slope	Gutter Spread	Gutter Width	HGL Dn	HGL Up	HGL Jnct	HGL Jmp Dn	HGL Jmp Up	Incr CxA	Incr Q	Inlet Depth	Inlet Eff
(cfs)	(ft/ft)	(ft/ft)	(sqft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft/ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)		(cfs)	(ft)	(%)
1.89	0.902	1.301				628.09	628.24					627.28	627.67	627.78			0.25	1.89		100
Project File: New.stm													Number of lines: 1			Date: 8/7/2025				
NOTES: ** Critical depth																				

Inlet ID	Inlet Loc		Inlet Time	i Sys	i Inlet	Invert Dn	Invert Up	Jump Loc	Jump Len	Vel Hd Jmp Dn	Vel Hd Jmp Up	J-Loss Coeff	Junct Type	Known Q	Cost RCP	Cost CMP	Cost PVC	
		(ft)	(min)	(in/hr)	(in/hr)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)			(cfs)				
ST-I1 (Double)	Sag		5.0	7.57	7.57	626.90	627.00			0.00	0.00	1.00	Hdwall	0.00	0	0	0	
Project File: New.stm Number of lines: 1 Date: 8/7/2025 NOTES: Intensity = 73.40 / (Inlet time + 12.20) ^ 0.80 -- Return period = 10 Yrs. ; ** Critical depth																		

Line ID	Line Length	Line Size	Line Slope	Line Type	Local Depr	n-val Gutter	n-val Pipe	Minor Loss	Northing Y	Pipe Travel	Q Byp	Q Capt	Q Carry	Line Rise	Runoff Coeff	Line Span	Area A1	Area A2	Area A3	
	(ft)	(in)	(%)		(in)			(ft)	(ft)	(min)	(cfs)	(cfs)	(cfs)	(in)	(C)	(in)	(ac)	(ac)	(ac)	
ST-I1 - ST-I2 (Double)	24.314	8(2b)	0.41	Cir			0.012	0.11	452651.32	0.15	0.00	1.89	0.00	8	0.83	8	0.06	0.00	0.24	
Project File: New.stm											Number of lines: 1					Date: 8/7/2025				
NOTES: ** Critical depth																				

Tc	Throat Ht	Total Area	Total CxA	Total Runoff	Vel Ave	Vel Dn	Vel Hd Dn	Vel Hd Up	Vel Up	Cover Dn	Cover Up	Storage			
(min)	(in)	(ac)		(cfs)	(ft/s)	(ft/s)	(ft)	(ft)	(ft/s)	(ft)	(ft)	(cft)			
5.0		0.30	0.25	1.89	3.61	4.52	0.32	0.11	2.70	0.52	0.57	14.08			
Project File: New.stm										Number of lines: 1			Date: 8/7/2025		
NOTES: ** Critical depth															

Hydraflow Storm Sewers Extension for Autodesk® Civil 3D® Plan



Project File: J.stm	Number of lines: 2	Date: 8/11/2025
---------------------	--------------------	-----------------

Storm Sewer Inventory Report

Line No.	Alignment				Flow Data				Physical Data								Line ID
	Dnstr Line No.	Line Length (ft)	Defl angle (deg)	Junc Type	Known Q (cfs)	Drng Area (ac)	Runoff Coeff (C)	Inlet Time (min)	Invert El Dn (ft)	Line Slope (%)	Invert El Up (ft)	Line Size (in)	Line Shape	N Value (n)	J-Loss Coeff (K)	Inlet/ Rim El (ft)	
1	End	85.225	58.326	MH	0.00	0.00	0.00	0.0	621.00	1.08	621.92	24	Cir	0.012	0.15	626.30	ST-J3 - ST-J2
2	1	85.623	-0.033	Hdwl	7.55	0.94	0.78	5.0	621.92	1.00	622.78	24	Cir	0.012	1.00	626.31	ST-J2 - ST-J1
Project File: J.stm												Number of lines: 2				Date: 8/11/2025	

Storm Sewer Summary Report

Line No.	Line ID	Flow rate (cfs)	Line Size (in)	Line shape	Line length (ft)	Invert EL Dn (ft)	Invert EL Up (ft)	Line Slope (%)	HGL Down (ft)	HGL Up (ft)	Minor loss (ft)	HGL Junct (ft)	Dns Line No.	Junction Type
1	ST-J3 - ST-J2	13.02	24	Cir	85.225	621.00	621.92	1.079	622.30	623.22	0.08	623.22	End	Manhole
2	ST-J2 - ST-J1	13.10	24	Cir	85.623	621.92	622.78	1.004	623.22	624.08	n/a	624.08	1	OpenHeadwall
Project File: J.stm									Number of lines: 2			Run Date: 8/11/2025		
NOTES: Return period = 10 Yrs.														

Line No.	Area Dn (sqft)	Area Up (sqft)	Byp Ln No	Coeff C1 (C)	Coeff C2 (C)	Coeff C3 (C)	Capac Full (cfs)	Crit Depth (ft)	Cross SI, Sw (ft/ft)	Cross SI, Sx (ft/ft)	Curb Len (ft)	Defl Ang (Deg)	Depth Dn (ft)	Depth Up (ft)	DnStm Ln No	Drng Area (ac)	Easting X (ft)	EGL Dn (ft)	EGL Up (ft)	Energy Loss (ft)	
1	2.16	2.16	n/a	0.35	0.50	0.95	25.46	1.30				58.326	1.30	1.30**	Outfall	0.00	1617253.15	622.86	623.78	0.000	
2	2.16	2.16	1	0.35	0.50	0.95	24.56	1.30				-0.033	1.30	1.30**	1	0.94	1617298.15	623.79	624.65	0.000	

Project File: J.stm

Number of lines: 2

Date: 8/11/2025

NOTES: ** Critical depth


Flow Rate	Sf Ave	Sf Dn	Grate Area	Grate Len	Grate Width	Gnd/Rim El Dn	Gnd/Rim El Up	Gutter Depth	Gutter Slope	Gutter Spread	Gutter Width	HGL Dn	HGL Up	HGL Jnct	HGL Jmp Dn	HGL Jmp Up	Incr CxA	Incr Q	Inlet Depth	Inlet Eff		
(cfs)	(ft/ft)	(ft/ft)	(sqft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft/ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)		(cfs)	(ft)	(%)		
13.02	0.000	0.000				623.81	626.30					622.30	623.22	623.22			0.00	0.00				
13.10	0.000	0.000				626.30	626.31					623.22	624.08	624.08			0.73	13.10		100		
</																						

Inlet ID	Inlet Loc		Inlet Time	i Sys	i Inlet	Invert Dn	Invert Up	Jump Loc	Jump Len	Vel Hd Jmp Dn	Vel Hd Jmp Up	J-Loss Coeff	Junct Type	Known Q	Cost RCP	Cost CMP	Cost PVC	
		(ft)	(min)	(in/hr)	(in/hr)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)			(cfs)				
ST-J2	Sag		0.0	7.46	0.00	621.00	621.92			0.00	0.00	0.15 z	MH	0.00	3,344	3,010	2,842	
ST-J1	Sag		5.0	7.57	7.57	621.92	622.78			0.00	0.00	1.00 z	Hdwall	7.55	3,382	3,044	2,875	
Project File: J.stm Number of lines: 2 Date: 8/11/2025																		
NOTES: Intensity = 73.40 / (Inlet time + 12.20) ^ 0.80 -- Return period = 10 Yrs. ; ** Critical depth																		

Line ID	Line Length (ft)	Line Size (in)	Line Slope (%)	Line Type	Local Depr (in)	n-val Gutter	n-val Pipe	Minor Loss (ft)	Northing Y (ft)	Pipe Travel (min)	Q Byp (cfs)	Q Capt (cfs)	Q Carry (cfs)	Line Rise (in)	Runoff Coeff (C)	Line Span (in)	Area A1 (ac)	Area A2 (ac)	Area A3 (ac)
ST-J3 - ST-J2	85.225	24	1.08	Cir			0.012	0.08	452545.32	0.34				24	0.00	24	0.00	0.00	0.00
ST-J2 - ST-J1	85.623	24	1.00	Cir			0.012	n/a	452472.48	0.34	0.00	13.10	0.00	24	0.78	24	0.27	0.00	0.67
															</				

Tc	Throat Ht	Total Area	Total CxA	Total Runoff	Vel Ave	Vel Dn	Vel Hd Dn	Vel Hd Up	Vel Up	Cover Dn	Cover Up	Storage			
(min)	(in)	(ac)		(cfs)	(ft/s)	(ft/s)	(ft)	(ft)	(ft/s)	(ft)	(ft)	(cft)			
5.3		0.94	0.73	5.47	6.04	6.04	0.57	0.57	6.04	0.81	2.38	183.75			
5.0		0.94	0.73	5.55	6.07	6.08	0.57	0.57	6.05	2.38	1.53	184.97			
</															

Hydraflow Storm Sewers Extension for Autodesk® Civil 3D® Plan



Project File: New.stm	Number of lines: 1	Date: 8/28/2025
-----------------------	--------------------	-----------------

Storm Sewer Inventory Report

Line No.	Alignment				Flow Data				Physical Data								Line ID
	Dnstr Line No.	Line Length (ft)	Defl angle (deg)	Junc Type	Known Q (cfs)	Drng Area (ac)	Runoff Coeff (C)	Inlet Time (min)	Invert El Dn (ft)	Line Slope (%)	Invert El Up (ft)	Line Size (in)	Line Shape	N Value (n)	J-Loss Coeff (K)	Inlet/ Rim El (ft)	
1	End	68.953	-121.961	Hdwl	15.06	0.59	0.35	5.0	632.85	2.03	634.25	24	Cir	0.012	1.00	637.83	ST-K2 - ST-K1 (Pip
Project File: New.stm												Number of lines: 1				Date: 8/28/2025	

Storm Sewer Summary Report

Line No.	Line ID	Flow rate (cfs)	Line Size (in)	Line shape	Line length (ft)	Invert EL Dn (ft)	Invert EL Up (ft)	Line Slope (%)	HGL Down (ft)	HGL Up (ft)	Minor loss (ft)	HGL Junct (ft)	Dns Line No.	Junction Type
1	ST-K2 - ST-K1 (Pipe K)	16.62	24	Cir	68.953	632.85	634.25	2.030	634.32	635.72	0.70	635.72	End	OpenHeadwall
Project File: New.stm									Number of lines: 1			Run Date: 8/28/2025		
NOTES: Return period = 10 Yrs.														

Line No.	Area Dn (sqft)	Area Up (sqft)	Byp Ln No	Coeff C1 (C)	Coeff C2 (C)	Coeff C3 (C)	Capac Full (cfs)	Crit Depth (ft)	Cross SI, Sw (ft/ft)	Cross SI, Sx (ft/ft)	Curb Len (ft)	Defl Ang (Deg)	Depth Dn (ft)	Depth Up (ft)	DnStm Ln No	Drng Area (ac)	Easting X (ft)	EGL Dn (ft)	EGL Up (ft)	Energy Loss (ft)
1	2.47	2.47	n/a	0.35	0.50	0.95	34.91	1.47				-121.961	1.47	1.47**	Outfall	0.59	1618229.15	635.02	636.42	0.000

Project File: New.stm

Number of lines: 1

Date: 8/28/2025

NOTES: ** Critical depth

Flow Rate	Sf Ave	Sf Dn	Grate Area	Grate Len	Grate Width	Gnd/Rim El Dn	Gnd/Rim El Up	Gutter Depth	Gutter Slope	Gutter Spread	Gutter Width	HGL Dn	HGL Up	HGL Jnct	HGL Jmp Dn	HGL Jmp Up	Incr CxA	Incr Q	Inlet Depth	Inlet Eff
(cfs)	(ft/ft)	(ft/ft)	(sqft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft/ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)		(cfs)	(ft)	(%)
16.62	0.000	0.000				635.66	637.83					634.32	635.72	635.72			0.21	16.62		100
Project File: New.stm													Number of lines: 1			Date: 8/28/2025				
NOTES: ** Critical depth																				

Inlet ID	Inlet Loc		Inlet Time	i Sys	i Inlet	Invert Dn	Invert Up	Jump Loc	Jump Len	Vel Hd Jmp Dn	Vel Hd Jmp Up	J-Loss Coeff	Junct Type	Known Q	Cost RCP	Cost CMP	Cost PVC	
		(ft)	(min)	(in/hr)	(in/hr)	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)			(cfs)				
ST-K2	Sag		5.0	7.57	7.57	632.85	634.25			0.00	0.00	1.00 z	Hdwall	15.06	2,466	2,219	2,096	
Project File: New.stm Number of lines: 1 Date: 8/28/2025 NOTES: Intensity = 73.40 / (Inlet time + 12.20) ^ 0.80 -- Return period = 10 Yrs. ; ** Critical depth																		

Line ID	Line Length (ft)	Line Size (in)	Line Slope (%)	Line Type	Local Depr (in)	n-val Gutter	n-val Pipe	Minor Loss (ft)	Northing Y (ft)	Pipe Travel (min)	Q Byp (cfs)	Q Capt (cfs)	Q Carry (cfs)	Line Rise (in)	Runoff Coeff (C)	Line Span (in)	Area A1 (ac)	Area A2 (ac)	Area A3 (ac)
ST-K2 - ST-K1 (Pipe K)	68.953	24	2.03	Cir			0.012	0.70	452736.10	0.22	0.00	16.62	0.00	24	0.35	24	0.59	0.00	0.00
Project File: New.stm										Number of lines: 1					Date: 8/28/2025				
NOTES: ** Critical depth																			

Tc	Throat Ht	Total Area	Total CxA	Total Runoff	Vel Ave	Vel Dn	Vel Hd Dn	Vel Hd Up	Vel Up	Cover Dn	Cover Up	Storage			
(min)	(in)	(ac)		(cfs)	(ft/s)	(ft/s)	(ft)	(ft)	(ft/s)	(ft)	(ft)	(cft)			
5.0		0.59	0.21	1.56	6.72	6.72	0.70	0.70	6.72	0.81	1.58	170.47			
Project File: New.stm										Number of lines: 1			Date: 8/28/2025		
NOTES: ** Critical depth															

APPENDIX D: HYDROLOGIC CALCULATIONS


Hydraflow Watershed Analysis Report
Channel and Channel Lining Reports – 10 Year
Sediment Basin Calculations

Watershed Model Schematic.....	1
Hydrograph Return Period Recap.....	2
2 - Year	
Summary Report.....	3
Hydrograph Reports.....	4
Hydrograph No. 1, SCS Runoff, WS A.....	4
TR-55 Tc Worksheet.....	5
Hydrograph No. 2, SCS Runoff, OFFSITE A.....	6
TR-55 Tc Worksheet.....	7
Hydrograph No. 3, Combine, POST WS A.....	8
Hydrograph No. 4, Reach, DITCH A.....	9
Hydrograph No. 5, SCS Runoff, WS A3.....	10
TR-55 Tc Worksheet.....	11
Hydrograph No. 6, SCS Runoff, Undisturbed - WS A.....	12
TR-55 Tc Worksheet.....	13
Hydrograph No. 7, SCS Runoff, WS B.....	14
TR-55 Tc Worksheet.....	15
Hydrograph No. 8, SCS Runoff, OFFSITE B.....	16
TR-55 Tc Worksheet.....	17
Hydrograph No. 9, Combine, POST WS B.....	18
Hydrograph No. 10, Reach, DITCH B.....	19
Hydrograph No. 11, Combine, WS AB.....	20
Hydrograph No. 12, SCS Runoff, PRE POI AB.....	21
TR-55 Tc Worksheet.....	22
Hydrograph No. 13, SCS Runoff, PRE WS C.....	23
TR-55 Tc Worksheet.....	24
Hydrograph No. 14, SCS Runoff, OFFSITE C.....	25
TR-55 Tc Worksheet.....	26
Hydrograph No. 15, Combine, PRE POI C.....	27
Hydrograph No. 16, Reservoir, DRY POND.....	28
Pond Report - DRY POND.....	29
Hydrograph No. 17, SCS Runoff, POST WS C.....	30
TR-55 Tc Worksheet.....	31
Hydrograph No. 18, SCS Runoff, OFFSITE C.....	32
Hydrograph No. 19, Combine, POST POI C.....	33
Hydrograph No. 20, Combine, POST POI AB.....	34
100 - Year	
Summary Report.....	35
Hydrograph Reports.....	36
Hydrograph No. 1, SCS Runoff, WS A.....	36
Hydrograph No. 2, SCS Runoff, OFFSITE A.....	37
Hydrograph No. 3, Combine, POST WS A.....	38
Hydrograph No. 4, Reach, DITCH A.....	39
Hydrograph No. 5, SCS Runoff, WS A3.....	40
Hydrograph No. 6, SCS Runoff, Undisturbed - WS A.....	41

Hydrograph No. 7, SCS Runoff, WS B.....	42
Hydrograph No. 8, SCS Runoff, OFFSITE B.....	43
Hydrograph No. 9, Combine, POST WS B.....	44
Hydrograph No. 10, Reach, DITCH B.....	45
Hydrograph No. 11, Combine, WS AB.....	46
Hydrograph No. 12, SCS Runoff, PRE POI AB.....	47
Hydrograph No. 13, SCS Runoff, PRE WS C.....	48
Hydrograph No. 14, SCS Runoff, OFFSITE C.....	49
Hydrograph No. 15, Combine, PRE POI C.....	50
Hydrograph No. 16, Reservoir, DRY POND.....	51
Hydrograph No. 17, SCS Runoff, POST WS C.....	52
Hydrograph No. 18, SCS Runoff, OFFSITE C.....	53
Hydrograph No. 19, Combine, POST POI C.....	54
Hydrograph No. 20, Combine, POST POI AB.....	55
 IDF Report.....	 56

Watershed Model Schematic

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025



Hydrograph Summary Report

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025

Hyd. No.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description
1	SCS Runoff	35.20	2	718	83,178	-----	-----	-----	WS A
2	SCS Runoff	9.833	2	734	44,645	-----	-----	-----	OFFSITE A
3	Combine	39.71	2	720	127,823	1, 2	-----	-----	POST WS A
4	Reach	31.81	2	724	127,819	3	-----	-----	DITCH A
5	SCS Runoff	22.25	2	720	60,085	-----	-----	-----	WS A3
6	SCS Runoff	9.222	2	726	32,159	-----	-----	-----	Undisturbed - WS A
7	SCS Runoff	51.56	2	718	128,574	-----	-----	-----	WS B
8	SCS Runoff	7.418	2	722	20,892	-----	-----	-----	OFFSITE B
9	Combine	57.76	2	718	149,466	7, 8	-----	-----	POST WS B
10	Reach	49.21	2	724	149,463	9	-----	-----	DITCH B
11	Combine	101.11	2	722	337,368	4, 5, 10	-----	-----	WS AB
12	SCS Runoff	34.07	2	732	147,606	-----	-----	-----	PRE POI AB
13	SCS Runoff	31.02	2	734	140,667	-----	-----	-----	PRE WS C
14	SCS Runoff	16.28	2	732	67,195	-----	-----	-----	OFFSITE C
15	Combine	46.91	2	734	207,862	13, 14	-----	-----	PRE POI C
16	Reservoir	11.28	2	772	337,366	11	611.32	153,693	DRY POND
17	SCS Runoff	16.79	2	734	76,047	-----	-----	-----	POST WS C
18	SCS Runoff	0.862	2	716	1,922	-----	-----	-----	OFFSITE C
19	Combine	16.89	2	734	77,970	17, 18	-----	-----	POST POI C
20	Combine	18.76	2	728	369,525	6, 16,	-----	-----	POST POI AB
Mustang.gpw					Return Period: 2 Year			Wednesday, 08 / 6 / 2025	


Hydrograph Report

Hyd. No. 1

WS A

Hydrograph type	=	SCS Runoff	Peak discharge	=	35.20 cfs
Storm frequency	=	2 yrs	Time to peak	=	718 min
Time interval	=	2 min	Hyd. volume	=	83,178 cuft
Drainage area	=	8.140 ac	Curve number	=	90*
Basin Slope	=	0.0 %	Hydraulic length	=	0 ft
Tc method	=	TR55	Time of conc. (Tc)	=	8.30 min
Total precip.	=	3.89 in	Distribution	=	Type II
Storm duration	=	24 hrs	Shape factor	=	484

* Composite (Area/CN) = [(1.740 x 72) + (2.310 x 91) + (4.090 x 98)] / 8.140



TR55 Tc Worksheet

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025

Hyd. No. 1

WS A

<u>Description</u>	<u>A</u>	<u>B</u>	<u>C</u>	<u>Totals</u>			
Sheet Flow							
Manning's n-value	= 0.035	0.011	0.011				
Flow length (ft)	= 71.0	0.0	0.0				
Two-year 24-hr precip. (in)	= 3.89	0.00	0.00				
Land slope (%)	= 0.50	0.00	0.00				
Travel Time (min)	= 3.67	+	0.00	+	0.00	=	3.67
Shallow Concentrated Flow							
Flow length (ft)	= 88.00	235.00	46.00				
Watercourse slope (%)	= 2.27	0.85	0.50				
Surface description	= Unpaved	Unpaved	Unpaved				
Average velocity (ft/s)	=2.43	1.49	1.14				
Travel Time (min)	= 0.60	+	2.63	+	0.67	=	3.91
Channel Flow							
X sectional flow area (sqft)	= 0.79	3.14	21.97				
Wetted perimeter (ft)	= 3.14	6.28	1.50				
Channel slope (%)	= 1.32	2.25	1.35				
Manning's n-value	= 0.011	0.011	0.035				
Velocity (ft/s)	=6.17	12.77	29.88				
Flow length (ft)	{0}65.0	178.0	629.0				
Travel Time (min)	= 0.18	+	0.23	+	0.35	=	0.76
Total Travel Time, Tc				8.30 min			


Hydrograph Report

Hyd. No. 2

OFFSITE A

Hydrograph type	=	SCS Runoff	Peak discharge	=	9.833 cfs
Storm frequency	=	2 yrs	Time to peak	=	734 min
Time interval	=	2 min	Hyd. volume	=	44,645 cuft
Drainage area	=	8.780 ac	Curve number	=	72*
Basin Slope	=	0.0 %	Hydraulic length	=	0 ft
Tc method	=	TR55	Time of conc. (Tc)	=	32.40 min
Total precip.	=	3.89 in	Distribution	=	Type II
Storm duration	=	24 hrs	Shape factor	=	484

* Composite (Area/CN) = [(8.780 x 72)] / 8.780



TR55 Tc Worksheet

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025

Hyd. No. 2

OFFSITE A


<u>Description</u>	<u>A</u>	<u>B</u>	<u>C</u>	<u>Totals</u>
Sheet Flow				
Manning's n-value	= 0.170	0.011	0.011	
Flow length (ft)	= 100.0	0.0	0.0	
Two-year 24-hr precip. (in)	= 3.89	0.00	0.00	
Land slope (%)	= 0.49	0.00	0.00	
Travel Time (min)	= 17.24	+ 0.00	+ 0.00	= 17.24
Shallow Concentrated Flow				
Flow length (ft)	= 1027.00	0.00	0.00	
Watercourse slope (%)	= 0.49	0.00	0.00	
Surface description	= Unpaved	Paved	Paved	
Average velocity (ft/s)	=1.13	0.00	0.00	
Travel Time (min)	= 15.16	+ 0.00	+ 0.00	= 15.16
Channel Flow				
X sectional flow area (sqft)	= 0.00	0.00	0.00	
Wetted perimeter (ft)	= 0.00	0.00	0.00	
Channel slope (%)	= 0.00	0.00	0.00	
Manning's n-value	= 0.015	0.015	0.015	
Velocity (ft/s)	=0.00	0.00	0.00	
Flow length (ft)	(0)0.0	0.0	0.0	
Travel Time (min)	= 0.00	+ 0.00	+ 0.00	= 0.00
Total Travel Time, Tc				32.40 min

Hydrograph Report

Hyd. No. 3

POST WS A

Hydrograph type	= Combine	Peak discharge	= 39.71 cfs
Storm frequency	= 2 yrs	Time to peak	= 720 min
Time interval	= 2 min	Hyd. volume	= 127,823 cuft
Inflow hyds.	= 1, 2	Contrib. drain. area	= 16.920 ac




Hydrograph Report

Hyd. No. 4

DITCH A

Hydrograph type	= Reach	Peak discharge	= 31.81 cfs
Storm frequency	= 2 yrs	Time to peak	= 724 min
Time interval	= 2 min	Hyd. volume	= 127,819 cuft
Inflow hyd. No.	= 3 - POST WS A	Section type	= Trapezoidal
Reach length	= 2104.0 ft	Channel slope	= 1.3 %
Manning's n	= 0.035	Bottom width	= 3.0 ft
Side slope	= 3.0:1	Max. depth	= 3.0 ft
Rating curve x	= 2.306	Rating curve m	= 1.248
Ave. velocity	= 4.06 ft/s	Routing coeff.	= 0.2526

Modified Att-Kin routing method used.




Hydrograph Report

Hyd. No. 5

WS A3

Hydrograph type	=	SCS Runoff	Peak discharge	=	22.25 cfs
Storm frequency	=	2 yrs	Time to peak	=	720 min
Time interval	=	2 min	Hyd. volume	=	60,085 cuft
Drainage area	=	5.330 ac	Curve number	=	92*
Basin Slope	=	0.0 %	Hydraulic length	=	0 ft
Tc method	=	TR55	Time of conc. (Tc)	=	11.30 min
Total precip.	=	3.89 in	Distribution	=	Type II
Storm duration	=	24 hrs	Shape factor	=	484

* Composite (Area/CN) = [(4.590 x 91) + (0.740 x 98)] / 5.330



TR55 Tc Worksheet

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025

Hyd. No. 5

WS A3

<u>Description</u>	<u>A</u>	<u>B</u>	<u>C</u>	<u>Totals</u>			
Sheet Flow							
Manning's n-value	= 0.035	0.011	0.011				
Flow length (ft)	= 100.0	0.0	0.0				
Two-year 24-hr precip. (in)	= 3.89	0.00	0.00				
Land slope (%)	= 0.50	0.00	0.00				
Travel Time (min)	= 4.83	+	0.00	+	0.00	=	4.83
Shallow Concentrated Flow							
Flow length (ft)	= 437.00	0.00	0.00				
Watercourse slope (%)	= 0.50	0.00	0.00				
Surface description	= Unpaved	Paved	Unpaved				
Average velocity (ft/s)	=1.14	0.00	0.00				
Travel Time (min)	= 6.38	+	0.00	+	0.00	=	6.38
Channel Flow							
X sectional flow area (sqft)	= 21.97	0.00	0.00				
Wetted perimeter (ft)	= 1.50	0.00	0.00				
Channel slope (%)	= 1.35	0.00	0.00				
Manning's n-value	= 0.035	0.013	0.015				
Velocity (ft/s)	=29.88	0.00	0.00				
Flow length (ft)	(0)143.0	0.0	0.0				
Travel Time (min)	= 0.08	+	0.00	+	0.00	=	0.08
Total Travel Time, Tc				11.30 min			

Hydrograph Report

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025


Wednesday, 08 / 6 / 2025

Hyd. No. 6

Undisturbed - WS A

Hydrograph type	=	SCS Runoff	Peak discharge	=	9.222 cfs
Storm frequency	=	2 yrs	Time to peak	=	726 min
Time interval	=	2 min	Hyd. volume	=	32,159 cuft
Drainage area	=	3.200 ac	Curve number	=	89*
Basin Slope	=	0.0 %	Hydraulic length	=	0 ft
Tc method	=	TR55	Time of conc. (Tc)	=	23.39 min
Total precip.	=	3.89 in	Distribution	=	Type II
Storm duration	=	24 hrs	Shape factor	=	484

* Composite (Area/CN) = [(0.180 x 72) + (0.750 x 88) + (2.120 x 91)] / 3.200



TR55 Tc Worksheet

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025

Hyd. No. 6

Undisturbed - WS A

<u>Description</u>	<u>A</u>	<u>B</u>	<u>C</u>	<u>Totals</u>
Sheet Flow				
Manning's n-value	= 0.170	0.011	0.011	
Flow length (ft)	= 100.0	0.0	0.0	
Two-year 24-hr precip. (in)	= 3.89	0.00	0.00	
Land slope (%)	= 1.72	0.00	0.00	
Travel Time (min)	= 10.43	+	0.00	+
			0.00	= 10.43
Shallow Concentrated Flow				
Flow length (ft)	= 1645.00	0.00	0.00	
Watercourse slope (%)	= 1.72	0.00	0.00	
Surface description	= Unpaved	Paved	Paved	
Average velocity (ft/s)	=2.12	0.00	0.00	
Travel Time (min)	= 12.96	+	0.00	+
			0.00	= 12.96
Channel Flow				
X sectional flow area (sqft)	= 0.00	0.00	0.00	
Wetted perimeter (ft)	= 0.00	0.00	0.00	
Channel slope (%)	= 0.00	0.00	0.00	
Manning's n-value	= 0.015	0.015	0.015	
Velocity (ft/s)	=0.00	0.00	0.00	
Flow length (ft)	(0)0.0	0.0	0.0	
Travel Time (min)	= 0.00	+	0.00	+
			0.00	= 0.00
Total Travel Time, Tc				23.39 min


Hydrograph Report

Hyd. No. 7

WS B

Hydrograph type	=	SCS Runoff	Peak discharge	=	51.56 cfs
Storm frequency	=	2 yrs	Time to peak	=	718 min
Time interval	=	2 min	Hyd. volume	=	128,574 cuft
Drainage area	=	10.660 ac	Curve number	=	95*
Basin Slope	=	0.0 %	Hydraulic length	=	0 ft
Tc method	=	TR55	Time of conc. (Tc)	=	7.20 min
Total precip.	=	3.89 in	Distribution	=	Type II
Storm duration	=	24 hrs	Shape factor	=	484

* Composite (Area/CN) = [(5.190 x 91) + (5.470 x 98)] / 10.660



TR55 Tc Worksheet

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025

Hyd. No. 7

WS B

<u>Description</u>	<u>A</u>	<u>B</u>	<u>C</u>	<u>Totals</u>			
Sheet Flow							
Manning's n-value	= 0.035	0.011	0.011				
Flow length (ft)	= 100.0	0.0	0.0				
Two-year 24-hr precip. (in)	= 3.89	0.00	0.00				
Land slope (%)	= 0.50	0.00	0.00				
Travel Time (min)	= 4.83	+	0.00	+	0.00	=	4.83
Shallow Concentrated Flow							
Flow length (ft)	= 99.00	0.00	0.00				
Watercourse slope (%)	= 0.50	0.00	0.00				
Surface description	= Unpaved	Unpaved	Paved				
Average velocity (ft/s)	=1.14	0.00	0.00				
Travel Time (min)	= 1.45	+	0.00	+	0.00	=	1.45
Channel Flow							
X sectional flow area (sqft)	= 3.14	21.97	0.00				
Wetted perimeter (ft)	= 6.28	1.50	0.00				
Channel slope (%)	= 2.10	1.40	0.00				
Manning's n-value	= 0.013	0.035	0.015				
Velocity (ft/s)	=10.44	30.42	0.00				
Flow length (ft)	(0)67.0	1577.0	0.0				
Travel Time (min)	= 0.11	+	0.86	+	0.00	=	0.97
Total Travel Time, Tc					7.20 min		


Hydrograph Report

Hyd. No. 8

OFFSITE B

Hydrograph type	=	SCS Runoff	Peak discharge	=	7.418 cfs
Storm frequency	=	2 yrs	Time to peak	=	722 min
Time interval	=	2 min	Hyd. volume	=	20,892 cuft
Drainage area	=	3.280 ac	Curve number	=	78*
Basin Slope	=	0.0 %	Hydraulic length	=	0 ft
Tc method	=	TR55	Time of conc. (Tc)	=	14.40 min
Total precip.	=	3.89 in	Distribution	=	Type II
Storm duration	=	24 hrs	Shape factor	=	484

* Composite (Area/CN) = [(1.940 x 72) + (0.580 x 81) + (0.690 x 91) + (0.070 x 98)] / 3.280



TR55 Tc Worksheet

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025

Hyd. No. 8

OFFSITE B


<u>Description</u>	<u>A</u>	<u>B</u>	<u>C</u>	<u>Totals</u>
Sheet Flow				
Manning's n-value	= 0.170	0.011	0.011	
Flow length (ft)	= 100.0	0.0	0.0	
Two-year 24-hr precip. (in)	= 3.89	0.00	0.00	
Land slope (%)	= 1.65	0.00	0.00	
Travel Time (min)	= 10.61	+	0.00	+
			0.00	= 10.61
Shallow Concentrated Flow				
Flow length (ft)	= 476.00	0.00	0.00	
Watercourse slope (%)	= 1.65	0.00	0.00	
Surface description	= Unpaved	Paved	Paved	
Average velocity (ft/s)	=2.07	0.00	0.00	
Travel Time (min)	= 3.83	+	0.00	+
			0.00	= 3.83
Channel Flow				
X sectional flow area (sqft)	= 0.00	0.00	0.00	
Wetted perimeter (ft)	= 0.00	0.00	0.00	
Channel slope (%)	= 0.00	0.00	0.00	
Manning's n-value	= 0.015	0.015	0.015	
Velocity (ft/s)	=0.00	0.00	0.00	
Flow length (ft)	(0)0.0	0.0	0.0	
Travel Time (min)	= 0.00	+	0.00	+
			0.00	= 0.00
Total Travel Time, Tc				14.40 min

Hydrograph Report

Hyd. No. 9

POST WS B

Hydrograph type	= Combine	Peak discharge	= 57.76 cfs
Storm frequency	= 2 yrs	Time to peak	= 718 min
Time interval	= 2 min	Hyd. volume	= 149,466 cuft
Inflow hyds.	= 7, 8	Contrib. drain. area	= 13.940 ac



Hydrograph Report

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025

Wednesday, 08 / 6 / 2025


Hyd. No. 10

DITCH B

Hydrograph type = Reach
 Storm frequency = 2 yrs
 Time interval = 2 min
 Inflow hyd. No. = 9 - POST WS B
 Reach length = 1752.0 ft
 Manning's n = 0.035
 Side slope = 3.0:1
 Rating curve x = 2.421
 Ave. velocity = 4.55 ft/s

Peak discharge = 49.21 cfs
 Time to peak = 724 min
 Hyd. volume = 149,463 cuft
 Section type = Trapezoidal
 Channel slope = 1.4 %
 Bottom width = 3.0 ft
 Max. depth = 3.0 ft
 Rating curve m = 1.248
 Routing coeff. = 0.3256

Modified Att-Kin routing method used.




Hydrograph Report

Hyd. No. 11

WS AB

Hydrograph type	= Combine	Peak discharge	= 101.11 cfs
Storm frequency	= 2 yrs	Time to peak	= 722 min
Time interval	= 2 min	Hyd. volume	= 337,368 cuft
Inflow hyds.	= 4, 5, 10	Contrib. drain. area	= 5.330 ac



Hydrograph Report

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025

Wednesday, 08 / 6 / 2025

Hyd. No. 12

PRE POI AB


Hydrograph type = SCS Runoff
 Storm frequency = 2 yrs
 Time interval = 2 min
 Drainage area = 19.040 ac
 Basin Slope = 0.0 %
 Tc method = TR55
 Total precip. = 3.89 in
 Storm duration = 24 hrs

Peak discharge = 34.07 cfs
 Time to peak = 732 min
 Hyd. volume = 147,606 cuft
 Curve number = 82*
 Hydraulic length = 0 ft
 Time of conc. (Tc) = 32.80 min
 Distribution = Type II
 Shape factor = 484

* Composite (Area/CN) = $[(8.630 \times 72) + (1.450 \times 88) + (7.160 \times 91) + (1.800 \times 91)] / 19.040$

PRE POI AB

Hyd. No. 12 -- 2 Year



TR55 Tc Worksheet

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025

Hyd. No. 12

PRE POI AB

<u>Description</u>	<u>A</u>	<u>B</u>	<u>C</u>	<u>Totals</u>
Sheet Flow				
Manning's n-value	= 0.170	0.011	0.011	
Flow length (ft)	= 100.0	0.0	0.0	
Two-year 24-hr precip. (in)	= 3.89	0.00	0.00	
Land slope (%)	= 0.50	0.00	0.00	
Travel Time (min)	= 17.10	+	0.00	+
			0.00	= 17.10
Shallow Concentrated Flow				
Flow length (ft)	= 1872.00	0.00	0.00	
Watercourse slope (%)	= 1.52	0.00	0.00	
Surface description	= Unpaved	Paved	Paved	
Average velocity (ft/s)	=1.99	0.00	0.00	
Travel Time (min)	= 15.68	+	0.00	+
			0.00	= 15.68
Channel Flow				
X sectional flow area (sqft)	= 0.00	0.00	0.00	
Wetted perimeter (ft)	= 0.00	0.00	0.00	
Channel slope (%)	= 0.00	0.00	0.00	
Manning's n-value	= 0.015	0.015	0.015	
Velocity (ft/s)	=0.00	0.00	0.00	
Flow length (ft)	(0)0.0	0.0	0.0	
Travel Time (min)	= 0.00	+	0.00	+
			0.00	= 0.00
Total Travel Time, Tc				32.80 min

Hydrograph Report

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025


Wednesday, 08 / 6 / 2025

Hyd. No. 13

PRE WS C

Hydrograph type	= SCS Runoff	Peak discharge	= 31.02 cfs
Storm frequency	= 2 yrs	Time to peak	= 734 min
Time interval	= 2 min	Hyd. volume	= 140,667 cuft
Drainage area	= 17.890 ac	Curve number	= 83*
Basin Slope	= 0.0 %	Hydraulic length	= 0 ft
Tc method	= TR55	Time of conc. (Tc)	= 34.60 min
Total precip.	= 3.89 in	Distribution	= Type II
Storm duration	= 24 hrs	Shape factor	= 484

* Composite (Area/CN) = [(7.590 x 72) + (0.390 x 81) + (0.830 x 88) + (9.080 x 91)] / 17.890



TR55 Tc Worksheet

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025

Hyd. No. 13

PRE WS C

<u>Description</u>	<u>A</u>	<u>B</u>	<u>C</u>	<u>Totals</u>
Sheet Flow				
Manning's n-value	= 0.170	0.011	0.011	
Flow length (ft)	= 100.0	0.0	0.0	
Two-year 24-hr precip. (in)	= 3.89	0.00	0.00	
Land slope (%)	= 1.34	0.00	0.00	
Travel Time (min)	= 11.53	+	0.00	+
			0.00	= 11.53
Shallow Concentrated Flow				
Flow length (ft)	= 2584.00	0.00	0.00	
Watercourse slope (%)	= 1.34	0.00	0.00	
Surface description	= Unpaved	Paved	Paved	
Average velocity (ft/s)	=1.87	0.00	0.00	
Travel Time (min)	= 23.06	+	0.00	+
			0.00	= 23.06
Channel Flow				
X sectional flow area (sqft)	= 0.00	0.00	0.00	
Wetted perimeter (ft)	= 0.00	0.00	0.00	
Channel slope (%)	= 0.00	0.00	0.00	
Manning's n-value	= 0.015	0.015	0.015	
Velocity (ft/s)	=0.00	0.00	0.00	
Flow length (ft)	(0)0.0	0.0	0.0	
Travel Time (min)	= 0.00	+	0.00	+
			0.00	= 0.00
Total Travel Time, Tc				34.60 min


Hydrograph Report

Hyd. No. 14

OFFSITE C

Hydrograph type	=	SCS Runoff	Peak discharge	=	16.28 cfs
Storm frequency	=	2 yrs	Time to peak	=	732 min
Time interval	=	2 min	Hyd. volume	=	67,195 cuft
Drainage area	=	12.210 ac	Curve number	=	74*
Basin Slope	=	0.0 %	Hydraulic length	=	0 ft
Tc method	=	TR55	Time of conc. (Tc)	=	27.00 min
Total precip.	=	3.89 in	Distribution	=	Type II
Storm duration	=	24 hrs	Shape factor	=	484

* Composite (Area/CN) = [(10.710 x 72) + (0.620 x 81) + (0.710 x 91) + (0.170 x 98)] / 12.210



TR55 Tc Worksheet

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025

Hyd. No. 14

OFFSITE C

<u>Description</u>	<u>A</u>	<u>B</u>	<u>C</u>	<u>Totals</u>
Sheet Flow				
Manning's n-value	= 0.170	0.011	0.011	
Flow length (ft)	= 100.0	0.0	0.0	
Two-year 24-hr precip. (in)	= 3.89	0.00	0.00	
Land slope (%)	= 0.62	0.00	0.00	
Travel Time (min)	= 15.69	+ 0.00	+ 0.00	= 15.69
Shallow Concentrated Flow				
Flow length (ft)	= 864.00	0.00	0.00	
Watercourse slope (%)	= 0.62	0.00	0.00	
Surface description	= Unpaved	Paved	Paved	
Average velocity (ft/s)	=1.27	0.00	0.00	
Travel Time (min)	= 11.33	+ 0.00	+ 0.00	= 11.33
Channel Flow				
X sectional flow area (sqft)	= 0.00	0.00	0.00	
Wetted perimeter (ft)	= 0.00	0.00	0.00	
Channel slope (%)	= 0.00	0.00	0.00	
Manning's n-value	= 0.015	0.015	0.015	
Velocity (ft/s)	=0.00	0.00	0.00	
Flow length (ft)	(0)0.0	0.0	0.0	
Travel Time (min)	= 0.00	+ 0.00	+ 0.00	= 0.00
Total Travel Time, Tc				27.00 min

Hydrograph Report


Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025

Wednesday, 08 / 6 / 2025

Hyd. No. 15

PRE POI C

Hydrograph type	= Combine	Peak discharge	= 46.91 cfs
Storm frequency	= 2 yrs	Time to peak	= 734 min
Time interval	= 2 min	Hyd. volume	= 207,862 cuft
Inflow hyds.	= 13, 14	Contrib. drain. area	= 30.100 ac



Hydrograph Report

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025


Wednesday, 08 / 6 / 2025

Hyd. No. 16

DRY POND

Hydrograph type	= Reservoir	Peak discharge	= 11.28 cfs
Storm frequency	= 2 yrs	Time to peak	= 772 min
Time interval	= 2 min	Hyd. volume	= 337,366 cuft
Inflow hyd. No.	= 11 - WS AB	Max. Elevation	= 611.32 ft
Reservoir name	= DRY POND	Max. Storage	= 153,693 cuft

Storage Indication method used.



Pond No. 1 - DRY POND

Pond Data

Contours -User-defined contour areas. Average end area method used for volume calculation. Beginning Elevation = 609.00 ft

Stage / Storage Table

Stage (ft)	Elevation (ft)	Contour area (sqft)	Incr. Storage (cuft)	Total storage (cuft)
0.00	609.00	13,063	0	0
1.00	610.00	50,447	31,755	31,755
2.00	611.00	117,425	83,936	115,691
3.00	612.00	121,802	119,614	235,305
4.00	613.00	127,271	124,537	359,841
5.00	614.00	133,397	130,334	490,175
6.00	615.00	140,392	136,895	627,070
7.00	616.00	148,314	144,353	771,423


Culvert / Orifice Structures

	[A]	[B]	[C]	[PrfRsr]
Rise (in)	= 18.00	0.00	0.00	0.00
Span (in)	= 18.00	0.00	0.00	0.00
No. Barrels	= 1	0	0	0
Invert El. (ft)	= 608.50	0.00	0.00	0.00
Length (ft)	= 58.00	0.00	0.00	0.00
Slope (%)	= 0.51	0.00	0.00	n/a
N-Value	= .013	.013	.013	n/a
Orifice Coeff.	= 0.60	0.60	0.60	0.60
Multi-Stage	= n/a	No	No	No

Weir Structures

	[A]	[B]	[C]	[D]
Crest Len (ft)	= 38.00	0.00	0.00	0.00
Crest El. (ft)	= 613.29	0.00	0.00	0.00
Weir Coeff.	= 2.63	3.33	3.33	3.33
Weir Type	= Ciphti	---	---	---
Multi-Stage	= No	No	No	Yes
Exfil.(in/hr)	= 0.000 (by Wet area)			
TW Elev. (ft)	= 0.00			

Note: Culvert/Orifice outflows are analyzed under inlet (ic) and outlet (oc) control. Weir risers checked for orifice conditions (ic) and submergence (s).




Hydrograph Report

Hyd. No. 17

POST WS C

Hydrograph type	=	SCS Runoff	Peak discharge	=	16.79 cfs
Storm frequency	=	2 yrs	Time to peak	=	734 min
Time interval	=	2 min	Hyd. volume	=	76,047 cuft
Drainage area	=	8.980 ac	Curve number	=	85*
Basin Slope	=	0.0 %	Hydraulic length	=	0 ft
Tc method	=	TR55	Time of conc. (Tc)	=	34.10 min
Total precip.	=	3.89 in	Distribution	=	Type II
Storm duration	=	24 hrs	Shape factor	=	484

* Composite (Area/CN) = [(2.480 x 72) + (0.260 x 81) + (0.830 x 88) + (5.410 x 91)] / 8.980



TR55 Tc Worksheet

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025

Hyd. No. 17

POST WS C

<u>Description</u>	<u>A</u>	<u>B</u>	<u>C</u>	<u>Totals</u>
Sheet Flow				
Manning's n-value	= 0.170	0.011	0.011	
Flow length (ft)	= 100.0	0.0	0.0	
Two-year 24-hr precip. (in)	= 3.89	0.00	0.00	
Land slope (%)	= 1.50	0.00	0.00	
Travel Time (min)	= 11.02	+ 0.00	+ 0.00	= 11.02
Shallow Concentrated Flow				
Flow length (ft)	= 2584.00	0.00	0.00	
Watercourse slope (%)	= 1.34	0.00	0.00	
Surface description	= Unpaved	Paved	Paved	
Average velocity (ft/s)	=1.87	0.00	0.00	
Travel Time (min)	= 23.06	+ 0.00	+ 0.00	= 23.06
Channel Flow				
X sectional flow area (sqft)	= 0.00	0.00	0.00	
Wetted perimeter (ft)	= 0.00	0.00	0.00	
Channel slope (%)	= 0.00	0.00	0.00	
Manning's n-value	= 0.015	0.015	0.015	
Velocity (ft/s)	=0.00	0.00	0.00	
Flow length (ft)	(0)0.0	0.0	0.0	
Travel Time (min)	= 0.00	+ 0.00	+ 0.00	= 0.00
Total Travel Time, Tc				34.10 min

Hydrograph Report

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025


Wednesday, 08 / 6 / 2025

Hyd. No. 18

OFFSITE C

Hydrograph type	=	SCS Runoff	Peak discharge	=	0.862 cfs
Storm frequency	=	2 yrs	Time to peak	=	716 min
Time interval	=	2 min	Hyd. volume	=	1,922 cuft
Drainage area	=	0.170 ac	Curve number	=	95*
Basin Slope	=	0.0 %	Hydraulic length	=	0 ft
Tc method	=	User	Time of conc. (Tc)	=	5.00 min
Total precip.	=	3.89 in	Distribution	=	Type II
Storm duration	=	24 hrs	Shape factor	=	484

* Composite (Area/CN) = [(0.020 x 81) + (0.030 x 91) + (0.120 x 98)] / 0.170




Hydrograph Report

Hyd. No. 19

POST POI C

Hydrograph type	= Combine	Peak discharge	= 16.89 cfs
Storm frequency	= 2 yrs	Time to peak	= 734 min
Time interval	= 2 min	Hyd. volume	= 77,970 cuft
Inflow hyds.	= 17, 18	Contrib. drain. area	= 9.150 ac




Hydrograph Report

Hyd. No. 20

POST POI AB

Hydrograph type	= Combine	Peak discharge	= 18.76 cfs
Storm frequency	= 2 yrs	Time to peak	= 728 min
Time interval	= 2 min	Hyd. volume	= 369,525 cuft
Inflow hyds.	= 6, 16	Contrib. drain. area	= 3.200 ac



Hydrograph Summary Report

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025

Hyd. No.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description
1	SCS Runoff	78.82	2	718	195,858	-----	-----	-----	WS A
2	SCS Runoff	33.88	2	732	146,403	-----	-----	-----	OFFSITE A
3	Combine	97.64	2	720	342,261	1, 2	-----	-----	POST WS A
4	Reach	82.89	2	724	342,258	3	-----	-----	DITCH A
5	SCS Runoff	48.37	2	720	136,980	-----	-----	-----	WS A3
6	SCS Runoff	21.25	2	726	76,974	-----	-----	-----	Undisturbed - WS A
7	SCS Runoff	107.31	2	718	279,462	-----	-----	-----	WS B
8	SCS Runoff	21.39	2	722	60,654	-----	-----	-----	OFFSITE B
9	Combine	126.00	2	718	340,117	7, 8	-----	-----	POST WS B
10	Reach	111.16	2	722	340,113	9	-----	-----	DITCH B
11	Combine	238.22	2	722	819,353	4, 5, 10	-----	-----	WS AB
12	SCS Runoff	91.13	2	732	398,114	-----	-----	-----	PRE POI AB
13	SCS Runoff	81.17	2	734	372,741	-----	-----	-----	PRE WS C
14	SCS Runoff	52.85	2	730	211,196	-----	-----	-----	OFFSITE C
15	Combine	132.53	2	732	583,938	13, 14	-----	-----	PRE POI C
16	Reservoir	24.13	2	774	819,350	11	613.45	419,139	DRY POND
17	SCS Runoff	42.09	2	734	194,641	-----	-----	-----	POST WS C
18	SCS Runoff	1.792	2	716	4,178	-----	-----	-----	OFFSITE C
19	Combine	42.29	2	734	198,819	17, 18	-----	-----	POST POI C
20	Combine	35.46	2	728	896,324	6, 16,	-----	-----	POST POI AB
Mustang.gpw					Return Period: 100 Year			Wednesday, 08 / 6 / 2025	


Hydrograph Report

Hyd. No. 1

WS A

Hydrograph type	=	SCS Runoff	Peak discharge	=	78.82 cfs
Storm frequency	=	100 yrs	Time to peak	=	718 min
Time interval	=	2 min	Hyd. volume	=	195,858 cuft
Drainage area	=	8.140 ac	Curve number	=	90*
Basin Slope	=	0.0 %	Hydraulic length	=	0 ft
Tc method	=	TR55	Time of conc. (Tc)	=	8.30 min
Total precip.	=	7.82 in	Distribution	=	Type II
Storm duration	=	24 hrs	Shape factor	=	484

* Composite (Area/CN) = [(1.740 x 72) + (2.310 x 91) + (4.090 x 98)] / 8.140



Hydrograph Report

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025


Wednesday, 08 / 6 / 2025

Hyd. No. 2

OFFSITE A

Hydrograph type	= SCS Runoff	Peak discharge	= 33.88 cfs
Storm frequency	= 100 yrs	Time to peak	= 732 min
Time interval	= 2 min	Hyd. volume	= 146,403 cuft
Drainage area	= 8.780 ac	Curve number	= 72*
Basin Slope	= 0.0 %	Hydraulic length	= 0 ft
Tc method	= TR55	Time of conc. (Tc)	= 32.40 min
Total precip.	= 7.82 in	Distribution	= Type II
Storm duration	= 24 hrs	Shape factor	= 484

* Composite (Area/CN) = [(8.780 x 72)] / 8.780




Hydrograph Report

Hyd. No. 3

POST WS A

Hydrograph type	= Combine	Peak discharge	= 97.64 cfs
Storm frequency	= 100 yrs	Time to peak	= 720 min
Time interval	= 2 min	Hyd. volume	= 342,261 cuft
Inflow hyds.	= 1, 2	Contrib. drain. area	= 16.920 ac



Hydrograph Report

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025


Wednesday, 08 / 6 / 2025

Hyd. No. 4

DITCH A

Hydrograph type	= Reach	Peak discharge	= 82.89 cfs
Storm frequency	= 100 yrs	Time to peak	= 724 min
Time interval	= 2 min	Hyd. volume	= 342,258 cuft
Inflow hyd. No.	= 3 - POST WS A	Section type	= Trapezoidal
Reach length	= 2104.0 ft	Channel slope	= 1.3 %
Manning's n	= 0.035	Bottom width	= 3.0 ft
Side slope	= 3.0:1	Max. depth	= 3.0 ft
Rating curve x	= 2.306	Rating curve m	= 1.248
Ave. velocity	= 4.86 ft/s	Routing coeff.	= 0.2948

Modified Att-Kin routing method used.



Hydrograph Report

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025


Wednesday, 08 / 6 / 2025

Hyd. No. 5

WS A3

Hydrograph type	= SCS Runoff	Peak discharge	= 48.37 cfs
Storm frequency	= 100 yrs	Time to peak	= 720 min
Time interval	= 2 min	Hyd. volume	= 136,980 cuft
Drainage area	= 5.330 ac	Curve number	= 92*
Basin Slope	= 0.0 %	Hydraulic length	= 0 ft
Tc method	= TR55	Time of conc. (Tc)	= 11.30 min
Total precip.	= 7.82 in	Distribution	= Type II
Storm duration	= 24 hrs	Shape factor	= 484

* Composite (Area/CN) = [(4.590 x 91) + (0.740 x 98)] / 5.330



Hydrograph Report

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025


Wednesday, 08 / 6 / 2025

Hyd. No. 6

Undisturbed - WS A

Hydrograph type	= SCS Runoff	Peak discharge	= 21.25 cfs
Storm frequency	= 100 yrs	Time to peak	= 726 min
Time interval	= 2 min	Hyd. volume	= 76,974 cuft
Drainage area	= 3.200 ac	Curve number	= 89*
Basin Slope	= 0.0 %	Hydraulic length	= 0 ft
Tc method	= TR55	Time of conc. (Tc)	= 23.39 min
Total precip.	= 7.82 in	Distribution	= Type II
Storm duration	= 24 hrs	Shape factor	= 484

* Composite (Area/CN) = $[(0.180 \times 72) + (0.750 \times 88) + (2.120 \times 91)] / 3.200$




Hydrograph Report

Hyd. No. 7

WS B

Hydrograph type	=	SCS Runoff	Peak discharge	=	107.31 cfs
Storm frequency	=	100 yrs	Time to peak	=	718 min
Time interval	=	2 min	Hyd. volume	=	279,462 cuft
Drainage area	=	10.660 ac	Curve number	=	95*
Basin Slope	=	0.0 %	Hydraulic length	=	0 ft
Tc method	=	TR55	Time of conc. (Tc)	=	7.20 min
Total precip.	=	7.82 in	Distribution	=	Type II
Storm duration	=	24 hrs	Shape factor	=	484

* Composite (Area/CN) = [(5.190 x 91) + (5.470 x 98)] / 10.660




Hydrograph Report

Hyd. No. 8

OFFSITE B

Hydrograph type	=	SCS Runoff	Peak discharge	=	21.39 cfs
Storm frequency	=	100 yrs	Time to peak	=	722 min
Time interval	=	2 min	Hyd. volume	=	60,654 cuft
Drainage area	=	3.280 ac	Curve number	=	78*
Basin Slope	=	0.0 %	Hydraulic length	=	0 ft
Tc method	=	TR55	Time of conc. (Tc)	=	14.40 min
Total precip.	=	7.82 in	Distribution	=	Type II
Storm duration	=	24 hrs	Shape factor	=	484

* Composite (Area/CN) = [(1.940 x 72) + (0.580 x 81) + (0.690 x 91) + (0.070 x 98)] / 3.280




Hydrograph Report

Hyd. No. 9

POST WS B

Hydrograph type	= Combine	Peak discharge	= 126.00 cfs
Storm frequency	= 100 yrs	Time to peak	= 718 min
Time interval	= 2 min	Hyd. volume	= 340,117 cuft
Inflow hyds.	= 7, 8	Contrib. drain. area	= 13.940 ac



Hydrograph Report

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025

Wednesday, 08 / 6 / 2025


Hyd. No. 10

DITCH B

Hydrograph type = Reach
 Storm frequency = 100 yrs
 Time interval = 2 min
 Inflow hyd. No. = 9 - POST WS B
 Reach length = 1752.0 ft
 Manning's n = 0.035
 Side slope = 3.0:1
 Rating curve x = 2.421
 Ave. velocity = 5.31 ft/s

Peak discharge = 111.16 cfs
 Time to peak = 722 min
 Hyd. volume = 340,113 cuft
 Section type = Trapezoidal
 Channel slope = 1.4 %
 Bottom width = 3.0 ft
 Max. depth = 3.0 ft
 Rating curve m = 1.248
 Routing coeff. = 0.3701

Modified Att-Kin routing method used.




Hydrograph Report

Hyd. No. 11

WS AB

Hydrograph type	= Combine	Peak discharge	= 238.22 cfs
Storm frequency	= 100 yrs	Time to peak	= 722 min
Time interval	= 2 min	Hyd. volume	= 819,353 cuft
Inflow hyds.	= 4, 5, 10	Contrib. drain. area	= 5.330 ac



Hydrograph Report

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025


Wednesday, 08 / 6 / 2025

Hyd. No. 12

PRE POI AB

Hydrograph type	= SCS Runoff	Peak discharge	= 91.13 cfs
Storm frequency	= 100 yrs	Time to peak	= 732 min
Time interval	= 2 min	Hyd. volume	= 398,114 cuft
Drainage area	= 19.040 ac	Curve number	= 82*
Basin Slope	= 0.0 %	Hydraulic length	= 0 ft
Tc method	= TR55	Time of conc. (Tc)	= 32.80 min
Total precip.	= 7.82 in	Distribution	= Type II
Storm duration	= 24 hrs	Shape factor	= 484

* Composite (Area/CN) = [(8.630 x 72) + (1.450 x 88) + (7.160 x 91) + (1.800 x 91)] / 19.040



Hydrograph Report

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025


Wednesday, 08 / 6 / 2025

Hyd. No. 13

PRE WS C

Hydrograph type	= SCS Runoff	Peak discharge	= 81.17 cfs
Storm frequency	= 100 yrs	Time to peak	= 734 min
Time interval	= 2 min	Hyd. volume	= 372,741 cuft
Drainage area	= 17.890 ac	Curve number	= 83*
Basin Slope	= 0.0 %	Hydraulic length	= 0 ft
Tc method	= TR55	Time of conc. (Tc)	= 34.60 min
Total precip.	= 7.82 in	Distribution	= Type II
Storm duration	= 24 hrs	Shape factor	= 484

* Composite (Area/CN) = [(7.590 x 72) + (0.390 x 81) + (0.830 x 88) + (9.080 x 91)] / 17.890



Hydrograph Report

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025


Wednesday, 08 / 6 / 2025

Hyd. No. 14

OFFSITE C

Hydrograph type	=	SCS Runoff	Peak discharge	=	52.85 cfs
Storm frequency	=	100 yrs	Time to peak	=	730 min
Time interval	=	2 min	Hyd. volume	=	211,196 cuft
Drainage area	=	12.210 ac	Curve number	=	74*
Basin Slope	=	0.0 %	Hydraulic length	=	0 ft
Tc method	=	TR55	Time of conc. (Tc)	=	27.00 min
Total precip.	=	7.82 in	Distribution	=	Type II
Storm duration	=	24 hrs	Shape factor	=	484

* Composite (Area/CN) = [(10.710 x 72) + (0.620 x 81) + (0.710 x 91) + (0.170 x 98)] / 12.210




Hydrograph Report

Hyd. No. 15

PRE POI C

Hydrograph type	= Combine	Peak discharge	= 132.53 cfs
Storm frequency	= 100 yrs	Time to peak	= 732 min
Time interval	= 2 min	Hyd. volume	= 583,938 cuft
Inflow hyds.	= 13, 14	Contrib. drain. area	= 30.100 ac



Hydrograph Report

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025


Wednesday, 08 / 6 / 2025

Hyd. No. 16

DRY POND

Hydrograph type	= Reservoir	Peak discharge	= 24.13 cfs
Storm frequency	= 100 yrs	Time to peak	= 774 min
Time interval	= 2 min	Hyd. volume	= 819,350 cuft
Inflow hyd. No.	= 11 - WS AB	Max. Elevation	= 613.45 ft
Reservoir name	= DRY POND	Max. Storage	= 419,139 cuft

Storage Indication method used.




Hydrograph Report

Hyd. No. 17

POST WS C

Hydrograph type	= SCS Runoff	Peak discharge	= 42.09 cfs
Storm frequency	= 100 yrs	Time to peak	= 734 min
Time interval	= 2 min	Hyd. volume	= 194,641 cuft
Drainage area	= 8.980 ac	Curve number	= 85*
Basin Slope	= 0.0 %	Hydraulic length	= 0 ft
Tc method	= TR55	Time of conc. (Tc)	= 34.10 min
Total precip.	= 7.82 in	Distribution	= Type II
Storm duration	= 24 hrs	Shape factor	= 484

* Composite (Area/CN) = [(2.480 x 72) + (0.260 x 81) + (0.830 x 88) + (5.410 x 91)] / 8.980




Hydrograph Report

Hyd. No. 18

OFFSITE C

Hydrograph type	=	SCS Runoff	Peak discharge	=	1.792 cfs
Storm frequency	=	100 yrs	Time to peak	=	716 min
Time interval	=	2 min	Hyd. volume	=	4,178 cuft
Drainage area	=	0.170 ac	Curve number	=	95*
Basin Slope	=	0.0 %	Hydraulic length	=	0 ft
Tc method	=	User	Time of conc. (Tc)	=	5.00 min
Total precip.	=	7.82 in	Distribution	=	Type II
Storm duration	=	24 hrs	Shape factor	=	484

* Composite (Area/CN) = [(0.020 x 81) + (0.030 x 91) + (0.120 x 98)] / 0.170




Hydrograph Report

Hyd. No. 19

POST POI C

Hydrograph type	= Combine	Peak discharge	= 42.29 cfs
Storm frequency	= 100 yrs	Time to peak	= 734 min
Time interval	= 2 min	Hyd. volume	= 198,819 cuft
Inflow hyds.	= 17, 18	Contrib. drain. area	= 9.150 ac




Hydrograph Report

Hyd. No. 20

POST POI AB

Hydrograph type	= Combine	Peak discharge	= 35.46 cfs
Storm frequency	= 100 yrs	Time to peak	= 728 min
Time interval	= 2 min	Hyd. volume	= 896,324 cuft
Inflow hyds.	= 6, 16	Contrib. drain. area	= 3.200 ac



Channel Report

DITCH A

Trapezoidal


Bottom Width (ft) = 3.00
Side Slopes (z:1) = 3.00, 3.00
Total Depth (ft) = 3.00
Invert Elev (ft) = 630.00
Slope (%) = 1.15
N-Value = 0.035

Calculations

Compute by: Known Q
Known Q (cfs) = 61.75

Highlighted

Depth (ft) = 1.69
Q (cfs) = 61.75
Area (sqft) = 13.64
Velocity (ft/s) = 4.53
Wetted Perim (ft) = 13.69
Crit Depth, Yc (ft) = 1.50
Top Width (ft) = 13.14
EGL (ft) = 2.01




Hydrograph Report

Hyd. No. 3

POST WS A

Hydrograph type	= Combine	Peak discharge	= 61.75 cfs
Storm frequency	= 10 yrs	Time to peak	= 12.00 hrs
Time interval	= 2 min	Hyd. volume	= 207,510 cuft
Inflow hyds.	= 1, 2	Contrib. drain. area	= 16.920 ac





North American Green
 5401 St. Wendel-Cynthiana Rd.
 Poseyville, Indiana 47633
 Tel. 800.772.2040
 >Fax 812.867.0247
 www.nagreen.com
 ECMDS v7.0

CHANNEL ANALYSIS

> > > A

Name A
 Discharge 61.75
 Channel Slope 0.0115
 Channel Bottom Width 3
 Left Side Slope 3
 Right Side Slope 3
 Existing Bend Radius 25
 Low Flow Liner
 Retardence Class C 6-12 in
 Vegetation Type Bunch Type
 Vegetation Density Good 65-79%
 Soil Type Clay Loam (CL)

SC250

Phase	Reach	Discharge	Velocity	Normal Depth	Mannings N	Permissible Shear Stress	Calculated Shear Stress	Safety Factor	Remarks	Staple Pattern
SC250 Unvegetated	Straight	61.75 cfs	4.29 ft/s	1.75 ft	0.038	3 lbs/ft2	1.25 lbs/ft2	2.39	STABLE	E
Underlying Substrate	Straight	61.75 cfs	4.29 ft/s	1.75 ft	0.038	3.27 lbs/ft2	0.74 lbs/ft2	4.45	STABLE	E
SC250 Reinforced Vegetation	Straight	61.75 cfs	3.45 ft/s	1.99 ft	0.051	10 lbs/ft2	1.43 lbs/ft2	6.99	STABLE	E
Underlying Substrate	Straight	61.75 cfs	3.45 ft/s	1.99 ft	0.051	3.61 lbs/ft2	0.82 lbs/ft2	4.38	STABLE	E
SC250 Unvegetated	Bend	61.75 cfs	4.29 ft/s	1.75 ft	0.038	3 lbs/ft2	2.51 lbs/ft2	1.2	STABLE	E
Underlying Substrate	Bend	61.75 cfs	4.29 ft/s	1.75 ft	0.038	3.27 lbs/ft2	1.47 lbs/ft2	2.22	STABLE	E
SC250 Reinforced Vegetation	Bend	61.75 cfs	3.45 ft/s	1.99 ft	0.051	10 lbs/ft2	2.86 lbs/ft2	3.5	STABLE	E
Underlying Substrate	Bend	61.75 cfs	3.45 ft/s	1.99 ft	0.051	3.61 lbs/ft2	1.65 lbs/ft2	2.19	STABLE	E



North American Green
 5401 St. Wendel-Cynthiana Rd.
 Poseyville, Indiana 47633
 Tel. 800.772.2040
 >Fax 812.867.0247
 www.nagreen.com
 ECMDS v7.0

ANALYSIS COMPUTATIONS

> > > [View Computation](#)

Inputs	
Channel Discharge (Q):	61.75 cfs
Peak Flow Period (H):	hours
Channel Slope (S0):	0.0115 ft/ft
Bottom Width (B):	3 ft
Left Side Slope (ZL):	3 (H : V)
Right Side Slope (ZR):	3 (H : V)
Existing Channel Bend:	Yes
Bend Coefficient (Kb):	
Channel Bend Radius:	25 ft
Retardance Class of Vegetation:	C 6-12 in
Vegetation Type:	Bunch Type
Vegetation Density:	Good 65-79%
Soil Type:	Clay Loam (CL)
Channel Lining Options	
SC250 Protection Type	Permanent

Basic Relationships
$A = \text{Cross sectional area, ft}^2 \text{ (m}^2\text{)} = (B * D) + (Z_L / 2 * D^2) + (Z_R / 2 * D^2)$
Where:
B = Base width of channel, ft (m)
D = Flow depth, ft (m)
Z _L = Left side bank slope (H : 1 V)
Z _R = Right side bank slope (H : 1 V)
$P = \text{Wetted perimeter, ft (m)} = B + Z_L * D + Z_R * D$
$R = \text{Hydraulic radius, ft (m)} = A / P$
$V = \text{Flow velocity, ft/s (m/s)} = Q / A$
Where:
Q = Channel discharge, cfs (cms)
$\text{Tau}_a = \text{Average bed shear stress, psf (Pa)} = 62.4 * R * S_0$
Where:
S ₀ = Gradient of channel, ft/ft (m/m)
$\text{Tau}_0 = \text{Maximum bed shear stress, psf (Pa)} = 62.4 * D * S_0$

Unvegetated Conditions Computations:
$n = \text{Manning's } n = a * \text{Tau}_a^b$
and (iteratively solved),
$n = 1.486 / Q * A * R^{2/3} S_0^{0.5}$
Where:
n = Manning's n
a = Product specific coefficient from performance testing
b = Product specific coefficient from performance testing

$SF_P = \text{Product factor of safety} = \tau_{TV} / \tau_{a0}$
Where:
$\tau_{TV} = \text{Permissible shear stress from testing, psf (Pa)}$
$\tau_{a0} = \text{In place permissible shear, psf (Pa)} = \tau_{TV} / \alpha * (\tau_{a5} + \alpha / 4.3)$
Where:
$\alpha = \text{unit conversion constant, 0.14 English, 6.5 Metric}$
$\tau_{a5} = \text{Permissible shear stress of soil}$
$SFL = \text{Factor of safety of installed liner} = \tau_{a0} / \tau_{a5}$

Vegetated Computations:
$n = \text{Manning's } n = \alpha * C_n * \tau_{a0}^{-0.4}$
<u>and (iteratively solved).</u>
$n = 1.486 / Q * A * R(2/3) S_0^{0.5}$
Where:
$\alpha = \text{Unit conversion constant, 0.213 English, 1.0 Metric}$
$C_n = \text{Vegetation retardance coefficient}$
$SF_P = \text{Product factor of safety} = \tau_{TV} / \tau_{a0}$
Where:
$\tau_{TV} = \text{Permissible shear stress from testing, psf (Pa)}$
$\tau_{a0} = \text{In place permissible shear, psf (Pa)} = \tau_{a5} / (1 - C_{FTRM}) * (n / n_s)^2$
Where:
$C_{FTRM} = \text{Coefficient of TRM performance derived from testing}$
$\tau_{a5} = \text{Permissible shear stress of soil}$
$n_s = \text{Manning's of soil bed if left unprotected}$
$SFL = \text{Factor of safety of installed liner} = \tau_{a0} / \tau_{a5}$

SC250

Phase	Mannings N	Predicted flow depth (D)	Cross sectional area (A)	Wetted perimeter (P)	Hydraulic radius (R)	Flow velocity (V)	Froude number (FR)	Calculated Shear Stress	SFP/SFL
SC250 Unvegetated	0.038	1.75 ft	14.38 ft ²	14.04 ft	1.02 ft	4.29 ft/s	0.75	1.25 lbs/ft ²	2.39 (SFP)
Underlying Substrate	0.038	1.75 ft	14.38 ft ²	14.04 ft	1.02 ft	4.29 ft/s	0.75	0.74 lbs/ft ²	4.45 (SFL)
SC250 Reinforced Vegetation	0.051	1.99 ft	17.9 ft ²	15.61 ft	1.15 ft	3.45 ft/s	0.57	1.43 lbs/ft ²	6.99 (SFP)
Underlying Substrate	0.051	1.99 ft	17.9 ft ²	15.61 ft	1.15 ft	3.45 ft/s	0.57	0.82 lbs/ft ²	4.38 (SFL)
SC250 Unvegetated	0.038	1.75 ft	14.38 ft ²	14.04 ft	1.02 ft	4.29 ft/s	0.75	2.51 lbs/ft ²	1.2 (SFP)
Underlying Substrate	0.038	1.75 ft	14.38 ft ²	14.04 ft	1.02 ft	4.29 ft/s	0.75	1.47 lbs/ft ²	2.22 (SFL)
SC250 Reinforced Vegetation	0.051	1.99 ft	17.9 ft ²	15.61 ft	1.15 ft	3.45 ft/s	0.57	2.86 lbs/ft ²	3.5 (SFP)
Underlying Substrate	0.051	1.99 ft	17.9 ft ²	15.61 ft	1.15 ft	3.45 ft/s	0.57	1.65 lbs/ft ²	2.19 (SFL)



North American Green
 5401 St. Wendel-Cynthiana Rd.
 Poseyville, Indiana 47633
 Tel. 800.772.2040
 >Fax 812.867.0247
 www.nagreen.com
 ECMDS v7.0

CHANNEL ANALYSIS

> > > A

Name A
 Discharge 61.75
 Channel Slope 0.0115
 Channel Bottom Width 3
 Left Side Slope 3
 Right Side Slope 3
 Existing Bend Radius 25
 Low Flow Liner
 Retardence Class C 6-12 in
 Vegetation Type Bunch Type
 Vegetation Density Good 65-79%
 Soil Type Loam (MH)

SC250

Phase	Reach	Discharge	Velocity	Normal Depth	Mannings N	Permissible Shear Stress	Calculated Shear Stress	Safety Factor	Remarks	Staple Pattern
SC250 Unvegetated	Straight	61.75 cfs	4.29 ft/s	1.75 ft	0.038	3 lbs/ft ²	1.25 lbs/ft ²	2.39	STABLE	E
Underlying Substrate	Straight	61.75 cfs	4.29 ft/s	1.75 ft	0.038	2.41 lbs/ft ²	0.74 lbs/ft ²	3.28	STABLE	E
SC250 Reinforced Vegetation	Straight	61.75 cfs	3.45 ft/s	1.99 ft	0.051	10 lbs/ft ²	1.43 lbs/ft ²	6.99	STABLE	E
Underlying Substrate	Straight	61.75 cfs	3.45 ft/s	1.99 ft	0.051	3 lbs/ft ²	0.82 lbs/ft ²	3.64	STABLE	E
SC250 Unvegetated	Bend	61.75 cfs	4.29 ft/s	1.75 ft	0.038	3 lbs/ft ²	2.51 lbs/ft ²	1.2	STABLE	E
Underlying Substrate	Bend	61.75 cfs	4.29 ft/s	1.75 ft	0.038	2.41 lbs/ft ²	1.47 lbs/ft ²	1.64	STABLE	E
SC250 Reinforced Vegetation	Bend	61.75 cfs	3.45 ft/s	1.99 ft	0.051	10 lbs/ft ²	2.86 lbs/ft ²	3.5	STABLE	E
Underlying Substrate	Bend	61.75 cfs	3.45 ft/s	1.99 ft	0.051	3 lbs/ft ²	1.65 lbs/ft ²	1.82	STABLE	E



North American Green
 5401 St. Wendel-Cynthiana Rd.
 Poseyville, Indiana 47633
 Tel. 800.772.2040
 >Fax 812.867.0247
 www.nagreen.com
 ECMDS v7.0

ANALYSIS COMPUTATIONS

> > > [View Computation](#)

Inputs	
Channel Discharge (Q):	61.75 cfs
Peak Flow Period (H):	hours
Channel Slope (S0):	0.0115 ft/ft
Bottom Width (B):	3 ft
Left Side Slope (ZL):	3 (H : V)
Right Side Slope (ZR):	3 (H : V)
Existing Channel Bend:	Yes
Bend Coefficient (Kb):	
Channel Bend Radius:	25 ft
Retardance Class of Vegetation:	C 6-12 in
Vegetation Type:	Bunch Type
Vegetation Density:	Good 65-79%
Soil Type:	Loam (MH)
Channel Lining Options	
SC250 Protection Type	Permanent

Basic Relationships
$A = \text{Cross sectional area, ft}^2 \text{ (m}^2\text{)} = (B * D) + (Z_L / 2 * D^2) + (Z_R / 2 * D^2)$
Where:
B = Base width of channel, ft (m)
D = Flow depth, ft (m)
Z _L = Left side bank slope (H : 1 V)
Z _R = Right side bank slope (H : 1 V)
$P = \text{Wetted perimeter, ft (m)} = B + Z_L * D + Z_R * D$
$R = \text{Hydraulic radius, ft (m)} = A / P$
$V = \text{Flow velocity, ft/s (m/s)} = Q / A$
Where:
Q = Channel discharge, cfs (cms)
$\text{Tau}_a \text{ Average bed shear stress, psf (Pa)} = 62.4 * R * S_0$
Where:
S ₀ = Gradient of channel, ft/ft (m/m)
$\text{Tau}_0 = \text{Maximum bed shear stress, psf (Pa)} = 62.4 * D * S_0$

Unvegetated Conditions Computations:
$n = \text{Manning's } n = a * \text{Tau}_a^b$
and (iteratively solved),
$n = 1.486 / Q * A * R^{2/3} S_0^{0.5}$
Where:
n = Manning's n
a = Product specific coefficient from performance testing
b = Product specific coefficient from performance testing

$SF_P = \text{Product factor of safety} = \tau_{TV} / \tau_{a0}$
Where:
$\tau_{TV} = \text{Permissible shear stress from testing, psf (Pa)}$
$\tau_{a0} = \text{In place permissible shear, psf (Pa)} = \tau_{TV} / \alpha * (\tau_{a5} + \alpha / 4.3)$
Where:
$\alpha = \text{unit conversion constant, 0.14 English, 6.5 Metric}$
$\tau_{a5} = \text{Permissible shear stress of soil}$
$SFL = \text{Factor of safety of installed liner} = \tau_{a0} / \tau_{a5}$

Vegetated Computations:
$n = \text{Manning's } n = \alpha * C_n * \tau_{a0}^{-0.4}$
<u>and (iteratively solved).</u>
$n = 1.486 / Q * A * R(2/3) S_0^{0.5}$
Where:
$\alpha = \text{Unit conversion constant, 0.213 English, 1.0 Metric}$
$C_n = \text{Vegetation retardance coefficient}$
$SF_P = \text{Product factor of safety} = \tau_{TV} / \tau_{a0}$
Where:
$\tau_{TV} = \text{Permissible shear stress from testing, psf (Pa)}$
$\tau_{a0} = \text{In place permissible shear, psf (Pa)} = \tau_{a5} / (1 - C_{FTRM}) * (n / n_s)^2$
Where:
$C_{FTRM} = \text{Coefficient of TRM performance derived from testing}$
$\tau_{a5} = \text{Permissible shear stress of soil}$
$n_s = \text{Manning's of soil bed if left unprotected}$
$SFL = \text{Factor of safety of installed liner} = \tau_{a0} / \tau_{a5}$

SC250

Phase	Mannings N	Predicted flow depth (D)	Cross sectional area (A)	Wetted perimeter (P)	Hydraulic radius (R)	Flow velocity (V)	Froude number (FR)	Calculated Shear Stress	SFP/SFL
SC250 Unvegetated	0.038	1.75 ft	14.38 ft ²	14.04 ft	1.02 ft	4.29 ft/s	0.75	1.25 lbs/ft ²	2.39 (SFP)
Underlying Substrate	0.038	1.75 ft	14.38 ft ²	14.04 ft	1.02 ft	4.29 ft/s	0.75	0.74 lbs/ft ²	3.28 (SFL)
SC250 Reinforced Vegetation	0.051	1.99 ft	17.9 ft ²	15.61 ft	1.15 ft	3.45 ft/s	0.57	1.43 lbs/ft ²	6.99 (SFP)
Underlying Substrate	0.051	1.99 ft	17.9 ft ²	15.61 ft	1.15 ft	3.45 ft/s	0.57	0.82 lbs/ft ²	3.64 (SFL)
SC250 Unvegetated	0.038	1.75 ft	14.38 ft ²	14.04 ft	1.02 ft	4.29 ft/s	0.75	2.51 lbs/ft ²	1.2 (SFP)
Underlying Substrate	0.038	1.75 ft	14.38 ft ²	14.04 ft	1.02 ft	4.29 ft/s	0.75	1.47 lbs/ft ²	1.64 (SFL)
SC250 Reinforced Vegetation	0.051	1.99 ft	17.9 ft ²	15.61 ft	1.15 ft	3.45 ft/s	0.57	2.86 lbs/ft ²	3.5 (SFP)
Underlying Substrate	0.051	1.99 ft	17.9 ft ²	15.61 ft	1.15 ft	3.45 ft/s	0.57	1.65 lbs/ft ²	1.82 (SFL)



North American Green
 5401 St. Wendel-Cynthiana Rd.
 Poseyville, Indiana 47633
 Tel. 800.772.2040
 >Fax 812.867.0247
 www.nagreen.com
 ECMDS v7.0

CHANNEL ANALYSIS

> > > A

Name A
 Discharge 61.75
 Channel Slope 0.0115
 Channel Bottom Width 3
 Left Side Slope 3
 Right Side Slope 3
 Existing Bend Radius 25
 Low Flow Liner
 Retardence Class C 6-12 in
 Vegetation Type Bunch Type
 Vegetation Density Good 65-79%
 Soil Type Silt Loam (SM)

SC250

Phase	Reach	Discharge	Velocity	Normal Depth	Mannings N	Permissible Shear Stress	Calculated Shear Stress	Safety Factor	Remarks	Staple Pattern
SC250 Unvegetated	Straight	61.75 cfs	4.29 ft/s	1.75 ft	0.038	3 lbs/ft ²	1.25 lbs/ft ²	2.39	STABLE	E
Underlying Substrate	Straight	61.75 cfs	4.29 ft/s	1.75 ft	0.038	2.2 lbs/ft ²	0.74 lbs/ft ²	2.99	STABLE	E
SC250 Reinforced Vegetation	Straight	61.75 cfs	3.45 ft/s	1.99 ft	0.051	10 lbs/ft ²	1.43 lbs/ft ²	6.99	STABLE	E
Underlying Substrate	Straight	61.75 cfs	3.45 ft/s	1.99 ft	0.051	3 lbs/ft ²	0.82 lbs/ft ²	3.64	STABLE	E
SC250 Unvegetated	Bend	61.75 cfs	4.29 ft/s	1.75 ft	0.038	3 lbs/ft ²	2.51 lbs/ft ²	1.2	STABLE	E
Underlying Substrate	Bend	61.75 cfs	4.29 ft/s	1.75 ft	0.038	2.2 lbs/ft ²	1.47 lbs/ft ²	1.49	STABLE	E
SC250 Reinforced Vegetation	Bend	61.75 cfs	3.45 ft/s	1.99 ft	0.051	10 lbs/ft ²	2.86 lbs/ft ²	3.5	STABLE	E
Underlying Substrate	Bend	61.75 cfs	3.45 ft/s	1.99 ft	0.051	3 lbs/ft ²	1.65 lbs/ft ²	1.82	STABLE	E



North American Green
 5401 St. Wendel-Cynthiana Rd.
 Poseyville, Indiana 47633
 Tel. 800.772.2040
 >Fax 812.867.0247
 www.nagreen.com
 ECMDS v7.0

ANALYSIS COMPUTATIONS

> > > [View Computation](#)

Inputs	
Channel Discharge (Q):	61.75 cfs
Peak Flow Period (H):	hours
Channel Slope (S0):	0.0115 ft/ft
Bottom Width (B):	3 ft
Left Side Slope (ZL):	3 (H : V)
Right Side Slope (ZR):	3 (H : V)
Existing Channel Bend:	Yes
Bend Coefficient (Kb):	
Channel Bend Radius:	25 ft
Retardance Class of Vegetation:	C 6-12 in
Vegetation Type:	Bunch Type
Vegetation Density:	Good 65-79%
Soil Type:	Silt Loam (SM)
Channel Lining Options	
SC250 Protection Type	Permanent

Basic Relationships
$A = \text{Cross sectional area, ft}^2 \text{ (m}^2\text{)} = (B * D) + (Z_L / 2 * D^2) + (Z_R / 2 * D^2)$
Where:
B = Base width of channel, ft (m)
D = Flow depth, ft (m)
Z _L = Left side bank slope (H : 1 V)
Z _R = Right side bank slope (H : 1 V)
$P = \text{Wetted perimeter, ft (m)} = B + Z_L * D + Z_R * D$
$R = \text{Hydraulic radius, ft (m)} = A / P$
$V = \text{Flow velocity, ft/s (m/s)} = Q / A$
Where:
Q = Channel discharge, cfs (cms)
$\text{Tau}_a = \text{Average bed shear stress, psf (Pa)} = 62.4 * R * S_0$
Where:
S ₀ = Gradient of channel, ft/ft (m/m)
$\text{Tau}_0 = \text{Maximum bed shear stress, psf (Pa)} = 62.4 * D * S_0$

Unvegetated Conditions Computations:
$n = \text{Manning's } n = a * \text{Tau}_a^b$
and (iteratively solved),
$n = 1.486 / Q * A * R^{(2/3)} S_0^{0.5}$
Where:
n = Manning's n
a = Product specific coefficient from performance testing
b = Product specific coefficient from performance testing

SF _P = Product factor of safety = Tau _T / Tau ₀
Where:
Tau _T = Permissible shear stress from testing, psf (Pa)
Tau _p = In place permissible shear, psf (Pa) = Tau _T / alpha * (Tau _s + alpha / 4.3)
Where:
alpha = unit conversion constant, 0.14 English, 6.5 Metric
Tau _s = Permissible shear stress of soil
SFL = Factor of safety of installed liner = Tau _p / Tau _a

Vegetated Computations:
n = Manning's n = alpha * Cn* Tau _a -0.4
<u>and (iteratively solved).</u>
n = 1.486 / Q * A * R(2/3)S ₀ ^{0.5}
Where:
alpha = Unit conversion constant, 0.213 English, 1.0 Metric
Cn = Vegetation retardance coefficient
SF _P = Product factor of safety = Tau _{TV} / Tau ₀
Where:
Tau _{TV} = Permissible shear stress from testing, psf (Pa)
Tau _p = In place permissible shear, psf (Pa) = Tau _s / (1 - C _{FRM}) * (n / n _s) ²
Where:
C _{FRM} = Coefficient of TRM performance derived from testing Tau _s = Permissible shear stress of soil
n _s = Manning's of soil bed if left unprotected
SFL = Factor of safety of installed liner = Tau _p / Tau _a

SC250

Phase	Mannings N	Predicted flow depth (D)	Cross sectional area (A)	Wetted perimeter (P)	Hydraulic radius (R)	Flow velocity (V)	Froude number (FR)	Calculated Shear Stress	SFP/SFL
SC250 Unvegetated	0.038	1.75 ft	14.38 ft2	14.04 ft	1.02 ft	4.29 ft/s	0.75	1.25 lbs/ft2	2.39 (SFP)
Underlying Substrate	0.038	1.75 ft	14.38 ft2	14.04 ft	1.02 ft	4.29 ft/s	0.75	0.74 lbs/ft2	2.99 (SFL)
SC250 Reinforced Vegetation	0.051	1.99 ft	17.9 ft2	15.61 ft	1.15 ft	3.45 ft/s	0.57	1.43 lbs/ft2	6.99 (SFP)
Underlying Substrate	0.051	1.99 ft	17.9 ft2	15.61 ft	1.15 ft	3.45 ft/s	0.57	0.82 lbs/ft2	3.64 (SFL)
SC250 Unvegetated	0.038	1.75 ft	14.38 ft2	14.04 ft	1.02 ft	4.29 ft/s	0.75	2.51 lbs/ft2	1.2 (SFP)
Underlying Substrate	0.038	1.75 ft	14.38 ft2	14.04 ft	1.02 ft	4.29 ft/s	0.75	1.47 lbs/ft2	1.49 (SFL)
SC250 Reinforced Vegetation	0.051	1.99 ft	17.9 ft2	15.61 ft	1.15 ft	3.45 ft/s	0.57	2.86 lbs/ft2	3.5 (SFP)
Underlying Substrate	0.051	1.99 ft	17.9 ft2	15.61 ft	1.15 ft	3.45 ft/s	0.57	1.65 lbs/ft2	1.82 (SFL)

Channel Report

DITCH B

Trapezoidal


Bottom Width (ft)	= 3.00
Side Slopes (z:1)	= 3.00, 3.00
Total Depth (ft)	= 3.00
Invert Elev (ft)	= 636.50
Slope (%)	= 1.38
N-Value	= 0.035

Calculations

Compute by:	Known Q
Known Q (cfs)	= 84.12

Highlighted

Depth (ft)	= 1.87
Q (cfs)	= 84.12
Area (sqft)	= 16.10
Velocity (ft/s)	= 5.22
Wetted Perim (ft)	= 14.83
Crit Depth, Yc (ft)	= 1.75
Top Width (ft)	= 14.22
EGL (ft)	= 2.29




Hydrograph Report

Hyd. No. 9

POST WS B

Hydrograph type	= Combine	Peak discharge	= 84.12 cfs
Storm frequency	= 10 yrs	Time to peak	= 11.97 hrs
Time interval	= 2 min	Hyd. volume	= 222,302 cuft
Inflow hyds.	= 7, 8	Contrib. drain. area	= 13.940 ac





North American Green
 5401 St. Wendel-Cynthiana Rd.
 Poseyville, Indiana 47633
 Tel. 800.772.2040
 >Fax 812.867.0247
 www.nagreen.com
 ECMDS v7.0

CHANNEL ANALYSIS

> > > B

Name B
 Discharge 84.12
 Channel Slope 0.0138
 Channel Bottom Width 3
 Left Side Slope 3
 Right Side Slope 3
 Low Flow Liner
 Retardence Class C 6-12 in
 Vegetation Type Bunch Type
 Vegetation Density Good 65-79%
 Soil Type Clay Loam (CL)

SC250

Phase	Reach	Discharge	Velocity	Normal Depth	Mannings N	Permissible Shear Stress	Calculated Shear Stress	Safety Factor	Remarks	Staple Pattern
SC250 Unvegetated	Straight	84.12 cfs	5.19 ft/s	1.88 ft	0.036	3 lbs/ft ²	1.61 lbs/ft ²	1.86	STABLE	E
Underlying Substrate	Straight	84.12 cfs	5.19 ft/s	1.88 ft	0.036	3.27 lbs/ft ²	0.94 lbs/ft ²	3.49	STABLE	E
SC250 Reinforced Vegetation	Straight	84.12 cfs	4.28 ft/s	2.11 ft	0.046	10 lbs/ft ²	1.82 lbs/ft ²	5.51	STABLE	E
Underlying Substrate	Straight	84.12 cfs	4.28 ft/s	2.11 ft	0.046	3 lbs/ft ²	1.04 lbs/ft ²	2.89	STABLE	E



North American Green
 5401 St. Wendel-Cynthiana Rd.
 Poseyville, Indiana 47633
 Tel. 800.772.2040
 >Fax 812.867.0247
 www.nagreen.com
 ECMDS v7.0

ANALYSIS COMPUTATIONS

> > > [View Computation](#)

Inputs	
Channel Discharge (Q):	84.12 cfs
Peak Flow Period (H):	hours
Channel Slope (S0):	0.0138 ft/ft
Bottom Width (B):	3 ft
Left Side Slope (ZL):	3 (H : V)
Right Side Slope (ZR):	3 (H : V)
Existing Channel Bend:	No
Bend Coefficient (Kb):	1
Channel Bend Radius:	
Retardance Class of Vegetation:	C 6-12 in
Vegetation Type:	Bunch Type
Vegetation Density:	Good 65-79%
Soil Type:	Clay Loam (CL)
Channel Lining Options	
SC250 Protection Type	Permanent

Basic Relationships
$A = \text{Cross sectional area, ft}^2 \text{ (m}^2\text{)} = (B * D) + (Z_L / 2 * D^2) + (Z_R / 2 * D^2)$
Where:
B = Base width of channel, ft (m)
D = Flow depth, ft (m)
Z _L = Left side bank slope (H : 1 V)
Z _R = Right side bank slope (H : 1 V)
$P = \text{Wetted perimeter, ft (m)} = B + Z_L * D + Z_R * D$
$R = \text{Hydraulic radius, ft (m)} = A / P$
$V = \text{Flow velocity, ft/s (m/s)} = Q / A$
Where:
Q = Channel discharge, cfs (cms)
$\tau_{avg} = \text{Average bed shear stress, psf (Pa)} = 62.4 * R * S_0$
Where:
S ₀ = Gradient of channel, ft/ft (m/m)
$\tau_{max} = \text{Maximum bed shear stress, psf (Pa)} = 62.4 * D * S_0$

Unvegetated Conditions Computations:
$n = \text{Manning's } n = a * \tau_{avg}$
<u>and (iteratively solved),</u>
$n = 1.486 / Q * A * R^{(2/3)} S_0^{0.5}$
Where:
n = Manning's n
a = Product specific coefficient from performance testing
b = Product specific coefficient from performance testing

SF _P = Product factor of safety = Tau _T / Tau ₀
Where:
Tau _T = Permissible shear stress from testing, psf (Pa)
Tau _p = In place permissible shear, psf (Pa) = Tau _T / alpha * (Tau _s + alpha / 4.3)
Where:
alpha = unit conversion constant, 0.14 English, 6.5 Metric
Tau _s = Permissible shear stress of soil
SFL = Factor of safety of installed liner = Tau _p / Tau _a

Vegetated Computations:
n = Manning's n = alpha * Cn* Tau _a -0.4
<u>and (iteratively solved).</u>
n = 1.486 / Q * A * R(2/3)S ₀ ^{0.5}
Where:
alpha = Unit conversion constant, 0.213 English, 1.0 Metric
Cn = Vegetation retardance coefficient
SF _P = Product factor of safety = Tau _{TV} / Tau ₀
Where:
Tau _{TV} = Permissible shear stress from testing, psf (Pa)
Tau _p = In place permissible shear, psf (Pa) = Tau _s / (1 - C _{FRM}) * (n / n _s) ²
Where:
C _{FRM} = Coefficient of TRM performance derived from testing Tau _s = Permissible shear stress of soil
n _s = Manning's of soil bed if left unprotected
SFL = Factor of safety of installed liner = Tau _p / Tau _a

SC250

Phase	Mannings N	Predicted flow depth (D)	Cross sectional area (A)	Wetted perimeter (P)	Hydraulic radius (R)	Flow velocity (V)	Froude number (FR)	Calculated Shear Stress	SFP/SFL
SC250 Unvegetated	0.036	1.88 ft	16.18 ft2	14.86 ft	1.09 ft	5.19 ft/s	0.88	1.61 lbs/ft2	1.86 (SFP)
Underlying Substrate	0.036	1.88 ft	16.18 ft2	14.86 ft	1.09 ft	5.19 ft/s	0.88	0.94 lbs/ft2	3.49 (SFL)
SC250 Reinforced Vegetation	0.046	2.11 ft	19.67 ft2	16.34 ft	1.2 ft	4.28 ft/s	0.69	1.82 lbs/ft2	5.51 (SFP)
Underlying Substrate	0.046	2.11 ft	19.67 ft2	16.34 ft	1.2 ft	4.28 ft/s	0.69	1.04 lbs/ft2	2.89 (SFL)



North American Green
 5401 St. Wendel-Cynthiana Rd.
 Poseyville, Indiana 47633
 Tel. 800.772.2040
 >Fax 812.867.0247
 www.nagreen.com
 ECMDS v7.0

CHANNEL ANALYSIS

> > > B

Name B
 Discharge 84.12
 Channel Slope 0.0138
 Channel Bottom Width 3
 Left Side Slope 3
 Right Side Slope 3
 Low Flow Liner
 Retardence Class C 6-12 in
 Vegetation Type Bunch Type
 Vegetation Density Good 65-79%
 Soil Type Loam (MH)

SC250

Phase	Reach	Discharge	Velocity	Normal Depth	Mannings N	Permissible Shear Stress	Calculated Shear Stress	Safety Factor	Remarks	Staple Pattern
SC250 Unvegetated	Straight	84.12 cfs	5.19 ft/s	1.88 ft	0.036	3 lbs/ft ²	1.61 lbs/ft ²	1.86	STABLE	E
Underlying Substrate	Straight	84.12 cfs	5.19 ft/s	1.88 ft	0.036	2.41 lbs/ft ²	0.94 lbs/ft ²	2.57	STABLE	E
SC250 Reinforced Vegetation	Straight	84.12 cfs	4.28 ft/s	2.11 ft	0.046	10 lbs/ft ²	1.82 lbs/ft ²	5.51	STABLE	E
Underlying Substrate	Straight	84.12 cfs	4.28 ft/s	2.11 ft	0.046	3 lbs/ft ²	1.04 lbs/ft ²	2.89	STABLE	E



North American Green
 5401 St. Wendel-Cynthiana Rd.
 Poseyville, Indiana 47633
 Tel. 800.772.2040
 >Fax 812.867.0247
 www.nagreen.com
 ECMDS v7.0

ANALYSIS COMPUTATIONS

> > > [View Computation](#)

Inputs	
Channel Discharge (Q):	84.12 cfs
Peak Flow Period (H):	hours
Channel Slope (S0):	0.0138 ft/ft
Bottom Width (B):	3 ft
Left Side Slope (ZL):	3 (H : V)
Right Side Slope (ZR):	3 (H : V)
Existing Channel Bend:	No
Bend Coefficient (Kb):	1
Channel Bend Radius:	
Retardance Class of Vegetation:	C 6-12 in
Vegetation Type:	Bunch Type
Vegetation Density:	Good 65-79%
Soil Type:	Loam (MH)
Channel Lining Options	
SC250 Protection Type	Permanent

Basic Relationships
$A = \text{Cross sectional area, ft}^2 \text{ (m}^2\text{)} = (B * D) + (Z_L / 2 * D^2) + (Z_R / 2 * D^2)$
Where:
B = Base width of channel, ft (m)
D = Flow depth, ft (m)
Z _L = Left side bank slope (H : 1 V)
Z _R = Right side bank slope (H : 1 V)
$P = \text{Wetted perimeter, ft (m)} = B + Z_L * D + Z_R * D$
$R = \text{Hydraulic radius, ft (m)} = A / P$
$V = \text{Flow velocity, ft/s (m/s)} = Q / A$
Where:
Q = Channel discharge, cfs (cms)
$\text{Tau}_a \text{ Average bed shear stress, psf (Pa)} = 62.4 * R * S_0$
Where:
S ₀ = Gradient of channel, ft/ft (m/m)
$\text{Tau}_0 = \text{Maximum bed shear stress, psf (Pa)} = 62.4 * D * S_0$

Unvegetated Conditions Computations:
$n = \text{Manning's } n = a * \text{Tau}_a^b$
and (iteratively solved),
$n = 1.486 / Q * A * R^{(2/3)} S_0^{0.5}$
Where:
n = Manning's n
a = Product specific coefficient from performance testing
b = Product specific coefficient from performance testing

$SF_P = \text{Product factor of safety} = \tau_{TV} / \tau_{a0}$
Where:
$\tau_{TV} = \text{Permissible shear stress from testing, psf (Pa)}$
$\tau_{a0} = \text{In place permissible shear, psf (Pa)} = \tau_{TV} / \alpha * (\tau_{a5} + \alpha / 4.3)$
Where:
$\alpha = \text{unit conversion constant, 0.14 English, 6.5 Metric}$
$\tau_{a5} = \text{Permissible shear stress of soil}$
$SFL = \text{Factor of safety of installed liner} = \tau_{a0} / \tau_{a5}$

Vegetated Computations:
$n = \text{Manning's } n = \alpha * C_n * \tau_{a0}^{-0.4}$
<u>and (iteratively solved).</u>
$n = 1.486 / Q * A * R(2/3) S_0^{0.5}$
Where:
$\alpha = \text{Unit conversion constant, 0.213 English, 1.0 Metric}$
$C_n = \text{Vegetation retardance coefficient}$
$SF_P = \text{Product factor of safety} = \tau_{TV} / \tau_{a0}$
Where:
$\tau_{TV} = \text{Permissible shear stress from testing, psf (Pa)}$
$\tau_{a0} = \text{In place permissible shear, psf (Pa)} = \tau_{a5} / (1 - C_{FTRM}) * (n / n_s)^2$
Where:
$C_{FTRM} = \text{Coefficient of TRM performance derived from testing}$
$\tau_{a5} = \text{Permissible shear stress of soil}$
$n_s = \text{Manning's of soil bed if left unprotected}$
$SFL = \text{Factor of safety of installed liner} = \tau_{a0} / \tau_{a5}$

SC250

Phase	Mannings N	Predicted flow depth (D)	Cross sectional area (A)	Wetted perimeter (P)	Hydraulic radius (R)	Flow velocity (V)	Froude number (FR)	Calculated Shear Stress	SFP/SFL
SC250 Unvegetated	0.036	1.88 ft	16.18 ft ²	14.86 ft	1.09 ft	5.19 ft/s	0.88	1.61 lbs/ft ²	1.86 (SFP)
Underlying Substrate	0.036	1.88 ft	16.18 ft ²	14.86 ft	1.09 ft	5.19 ft/s	0.88	0.94 lbs/ft ²	2.57 (SFL)
SC250 Reinforced Vegetation	0.046	2.11 ft	19.67 ft ²	16.34 ft	1.2 ft	4.28 ft/s	0.69	1.82 lbs/ft ²	5.51 (SFP)
Underlying Substrate	0.046	2.11 ft	19.67 ft ²	16.34 ft	1.2 ft	4.28 ft/s	0.69	1.04 lbs/ft ²	2.89 (SFL)



North American Green
 5401 St. Wendel-Cynthiana Rd.
 Poseyville, Indiana 47633
 Tel. 800.772.2040
 >Fax 812.867.0247
 www.nagreen.com
 ECMDS v7.0

CHANNEL ANALYSIS

> > > B

Name B
 Discharge 84.12
 Channel Slope 0.0138
 Channel Bottom Width 3
 Left Side Slope 3
 Right Side Slope 3
 Low Flow Liner
 Retardence Class C 6-12 in
 Vegetation Type Bunch Type
 Vegetation Density Good 65-79%
 Soil Type Silt Loam (SM)

SC250

Phase	Reach	Discharge	Velocity	Normal Depth	Mannings N	Permissible Shear Stress	Calculated Shear Stress	Safety Factor	Remarks	Staple Pattern
SC250 Unvegetated	Straight	84.12 cfs	5.19 ft/s	1.88 ft	0.036	3 lbs/ft ²	1.61 lbs/ft ²	1.86	STABLE	E
Underlying Substrate	Straight	84.12 cfs	5.19 ft/s	1.88 ft	0.036	2.2 lbs/ft ²	0.94 lbs/ft ²	2.34	STABLE	E
SC250 Reinforced Vegetation	Straight	84.12 cfs	4.28 ft/s	2.11 ft	0.046	10 lbs/ft ²	1.82 lbs/ft ²	5.51	STABLE	E
Underlying Substrate	Straight	84.12 cfs	4.28 ft/s	2.11 ft	0.046	3 lbs/ft ²	1.04 lbs/ft ²	2.89	STABLE	E



North American Green
 5401 St. Wendel-Cynthiana Rd.
 Poseyville, Indiana 47633
 Tel. 800.772.2040
 >Fax 812.867.0247
 www.nagreen.com
 ECMDS v7.0

ANALYSIS COMPUTATIONS

> > > [View Computation](#)

Inputs	
Channel Discharge (Q):	84.12 cfs
Peak Flow Period (H):	hours
Channel Slope (S0):	0.0138 ft/ft
Bottom Width (B):	3 ft
Left Side Slope (ZL):	3 (H : V)
Right Side Slope (ZR):	3 (H : V)
Existing Channel Bend:	No
Bend Coefficient (Kb):	1
Channel Bend Radius:	
Retardance Class of Vegetation:	C 6-12 in
Vegetation Type:	Bunch Type
Vegetation Density:	Good 65-79%
Soil Type:	Silt Loam (SM)
Channel Lining Options	
SC250 Protection Type	Permanent

Basic Relationships
$A = \text{Cross sectional area, ft}^2 \text{ (m}^2\text{)} = (B * D) + (Z_L / 2 * D^2) + (Z_R / 2 * D^2)$
Where:
B = Base width of channel, ft (m)
D = Flow depth, ft (m)
Z _L = Left side bank slope (H : 1 V)
Z _R = Right side bank slope (H : 1 V)
$P = \text{Wetted perimeter, ft (m)} = B + Z_L * D + Z_R * D$
$R = \text{Hydraulic radius, ft (m)} = A / P$
$V = \text{Flow velocity, ft/s (m/s)} = Q / A$
Where:
Q = Channel discharge, cfs (cms)
$\tau_{avg} = \text{Average bed shear stress, psf (Pa)} = 62.4 * R * S_0$
Where:
S ₀ = Gradient of channel, ft/ft (m/m)
$\tau_{max} = \text{Maximum bed shear stress, psf (Pa)} = 62.4 * D * S_0$

Unvegetated Conditions Computations:
$n = \text{Manning's } n = a * \tau_{avg}$
and (iteratively solved),
$n = 1.486 / Q * A * R^{2/3} S_0^{0.5}$
Where:
n = Manning's n
a = Product specific coefficient from performance testing
b = Product specific coefficient from performance testing

$SF_P = \text{Product factor of safety} = \tau_{TV} / \tau_{a0}$
Where:
$\tau_{TV} = \text{Permissible shear stress from testing, psf (Pa)}$
$\tau_{a0} = \text{In place permissible shear, psf (Pa)} = \tau_{TV} / \alpha * (\tau_{a5} + \alpha / 4.3)$
Where:
$\alpha = \text{unit conversion constant, 0.14 English, 6.5 Metric}$
$\tau_{a5} = \text{Permissible shear stress of soil}$
$SFL = \text{Factor of safety of installed liner} = \tau_{a0} / \tau_{a5}$

Vegetated Computations:
$n = \text{Manning's } n = \alpha * C_n * \tau_{a0}^{-0.4}$
<u>and (iteratively solved)</u>
$n = 1.486 / Q * A * R(2/3) S_0^{0.5}$
Where:
$\alpha = \text{Unit conversion constant, 0.213 English, 1.0 Metric}$
$C_n = \text{Vegetation retardance coefficient}$
$SF_P = \text{Product factor of safety} = \tau_{TV} / \tau_{a0}$
Where:
$\tau_{TV} = \text{Permissible shear stress from testing, psf (Pa)}$
$\tau_{a0} = \text{In place permissible shear, psf (Pa)} = \tau_{a5} / (1 - C_{FTRM}) * (n / n_s)^2$
Where:
$C_{FTRM} = \text{Coefficient of TRM performance derived from testing}$
$\tau_{a5} = \text{Permissible shear stress of soil}$
$n_s = \text{Manning's of soil bed if left unprotected}$
$SFL = \text{Factor of safety of installed liner} = \tau_{a0} / \tau_{a5}$

SC250

Phase	Mannings N	Predicted flow depth (D)	Cross sectional area (A)	Wetted perimeter (P)	Hydraulic radius (R)	Flow velocity (V)	Froude number (FR)	Calculated Shear Stress	SFP/SFL
SC250 Unvegetated	0.036	1.88 ft	16.18 ft ²	14.86 ft	1.09 ft	5.19 ft/s	0.88	1.61 lbs/ft ²	1.86 (SFP)
Underlying Substrate	0.036	1.88 ft	16.18 ft ²	14.86 ft	1.09 ft	5.19 ft/s	0.88	0.94 lbs/ft ²	2.34 (SFL)
SC250 Reinforced Vegetation	0.046	2.11 ft	19.67 ft ²	16.34 ft	1.2 ft	4.28 ft/s	0.69	1.82 lbs/ft ²	5.51 (SFP)
Underlying Substrate	0.046	2.11 ft	19.67 ft ²	16.34 ft	1.2 ft	4.28 ft/s	0.69	1.04 lbs/ft ²	2.89 (SFL)

Sediment Basin Calculations:

Total Drainage Area: 36.62 acres

Required Storage:

Total Storage Volume: 3618 cf/ac * 36.62 ac = 132,491.16 cf

Wet Storage: 1809 cf/ac * 36.62 ac = 66,245.58 cf

Dry Storage: 1809 cf/ac * 36.62 ac = 66,245.58 cf

- Forebay: 453.6 cf/ac * 36.62 = 16,610.83 cf
- Main Basin: 66,245.58 cf – 16,610.83 cf = 49,634.75 cf

Provided Storage:

Wet Storage:

- Bottom Dimensions (609.00 ft): 13,063.44 sf
- Permanent Pool Dimensions (611.00 ft): 89,656.47 sf

$$V = \frac{(13,063.44 + 89,656.47) * 2}{2} = 102,719.91 \text{ cf}$$

Total Wet Storage (Bottom of Pond to Permanent Pool): 102,719.91 cf > 66,245.58 cf

Dry Storage:

Forebay A:

- Bottom of Forebay A Dimensions (611.00 ft): 13,854.73 sf
- Top of Forebay A Dimensions (613.00 ft): 16,704.68 sf

$$V = \frac{(13,854.73 + 16,704.68) * 2}{2} = 30,559.41 \text{ cf}$$

Forebay B:

- Bottom of Forebay B Dimensions (611.00 ft): 12,378.46 sf
- Top of Forebay B Dimensions (613.00 ft): 15,570.87 sf

$$V = \frac{(12,378.46 + 15,570.87) * 2}{2} = 27,949.33 \text{ cf}$$

Total Forebay Storage: 58,508.74 cf > 16,610.83 cf

Main Basin:

- Dimensions at Permanent Pool (611.00 ft): 89,656.47 sf
- Dimensions at Top (613.00 ft): 95,017.49 sf

$$V = \frac{(89,656.47 + 95,017.49) * 2}{2} = 184,673.96 \text{ cf}$$

Main Basin Storage: 184,673.96 > 49,634.75 cf

Total Dry Storage, including Forebay:

58,508.74 cf + 184,673.96 = 243,182.70 cf > 66,245.58 cf

Total Provided Storage:

102,720 cf + 243,183 cf = 345,903 cf > 132,491 cf

Principal Spillway:

Elevation: 612.00 ft

$Q_{p_{5yr,24hr}} = 193.48 \text{ cfs}$

Emergency Spillway:

Elevation: 613.29 ft

$Q_{p_{25yr,24hr}} = 277.51 \text{ cfs}^*$

*TR-55 generated via Hydraflow Hydrographs Extension for Autodesk Civil 3D

Weir Length = 38 ft

Design Flow:

277.51 cfs – 31.37 cfs* = 246.14 cfs

*Interpolated flow credited to 3 ft diameter principal spillway at 1 ft head over crest given by Hydraflow Express Extension for Autodesk Civil 3D

Top of Berm: 616.00 ft

613.29 ft (E-spillway Elev) + 1.71 ft* (depth of 25 yr storm) + 1 ft (min. freeboard) = 616.01 ft

*Flow control depth given by Hydraflow Express Extension for Autodesk Civil 3D at the design flow Q


Skimmer:

Required Basin volume in cubic feet 243183 The required basin volume is the actual volume you intend to drain, not the provided or total volume which is often larger. If a pool of water is to be maintained between storms, do not include that volume.	Days to Drain 3 Number of Days to drain is usually determined by local or state regulations. Where there is no requirement 3 days is recommended. Keep in mind the quicker the basin is to drain the larger the skimmer required. In NC, assume 3 days to drain.
Skimmer Size 8 inches	Orifice Percentage 85%

Using the Simple Faircloth Skimmer Sizing Calculator at <https://fairclothskimmer.com/sediment-skimmer-calculator/>

Watershed Model Schematic

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025



Legend

<u>Hyd.</u>	<u>Origin</u>	<u>Description</u>
1	SCS Runoff	SEDIMENT BASIN
2	Reservoir	RESERVOIR

Hydrograph Summary Report

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025


Hyd. No.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description
1	SCS Runoff	193.48	2	716	401,919	-----	-----	-----	SEDIMENT BASIN
2	Reservoir	11.97	2	760	401,853	1	611.79	209,849	RESERVOIR
SedimentBasinMustang.gpw					Return Period: 5 Year			Tuesday, 08 / 5 / 2025	

Hydrograph Report

Hyd. No. 1

SEDIMENT BASIN

Hydrograph type	= SCS Runoff	Peak discharge	= 193.48 cfs
Storm frequency	= 5 yrs	Time to peak	= 716 min
Time interval	= 2 min	Hyd. volume	= 401,919 cuft
Drainage area	= 36.620 ac	Curve number	= 86
Basin Slope	= 0.0 %	Hydraulic length	= 0 ft
Tc method	= User	Time of conc. (Tc)	= 5.00 min
Total precip.	= 4.74 in	Distribution	= Type II
Storm duration	= 24 hrs	Shape factor	= 484



Hydrograph Report

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025


Tuesday, 08 / 5 / 2025

Hyd. No. 2

RESERVOIR

Hydrograph type	= Reservoir	Peak discharge	= 11.97 cfs
Storm frequency	= 5 yrs	Time to peak	= 760 min
Time interval	= 2 min	Hyd. volume	= 401,853 cuft
Inflow hyd. No.	= 1 - SEDIMENT BASIN	Max. Elevation	= 611.79 ft
Reservoir name	= SEDIMENT BASIN	Max. Storage	= 209,849 cuft

Storage Indication method used.



Pond No. 1 - SEDIMENT BASIN

Pond Data

Contours -User-defined contour areas. Average end area method used for volume calculation. Beginning Elevation = 609.00 ft

Stage / Storage Table

Stage (ft)	Elevation (ft)	Contour area (sqft)	Incr. Storage (cuft)	Total storage (cuft)
0.00	609.00	13,063	0	0
1.00	610.00	50,447	31,755	31,755
2.00	611.00	117,425	83,936	115,691
3.00	612.00	121,802	119,614	235,305
4.00	613.00	127,271	124,537	359,841
5.00	614.00	133,397	130,334	490,175
6.00	615.00	140,392	136,895	627,070
7.00	616.00	148,314	144,353	771,423


Culvert / Orifice Structures

	[A]	[B]	[C]	[PrfRsr]
Rise (in)	= 18.00	Inactive	0.00	0.00
Span (in)	= 18.00	0.00	0.00	0.00
No. Barrels	= 1	1	0	0
Invert El. (ft)	= 609.00	0.00	0.00	0.00
Length (ft)	= 76.00	0.00	0.00	0.00
Slope (%)	= 1.00	0.00	0.00	n/a
N-Value	= .013	.013	.013	n/a
Orifice Coeff.	= 0.60	0.60	0.60	0.60
Multi-Stage	= n/a	No	No	No

Weir Structures

	[A]	[B]	[C]	[D]
Crest Len (ft)	= 9.42	38.00	0.00	0.00
Crest El. (ft)	= 612.00	613.29	0.00	0.00
Weir Coeff.	= 3.33	2.63	3.33	3.33
Weir Type	= 1	Ciplti	---	---
Multi-Stage	= Yes	No	No	Yes
Exfil.(in/hr)	= 0.000 (by Wet area)			
TW Elev. (ft)	= 0.00			

Note: Culvert/Orifice outflows are analyzed under inlet (ic) and outlet (oc) control. Weir risers checked for orifice conditions (ic) and submergence (s).



Hydrograph Summary Report

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025

Hyd. No.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description
1	SCS Runoff	277.51	2	716	588,683	-----	-----	-----	SEDIMENT BASIN
2	Reservoir	14.30	2	774	588,606	1	612.66	317,854	RESERVOIR
SedimentBasinMustang.gpw					Return Period: 25 Year			Tuesday, 08 / 5 / 2025	

Hydrograph Report


Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2025

Tuesday, 08 / 5 / 2025

Hyd. No. 1

SEDIMENT BASIN

Hydrograph type	= SCS Runoff	Peak discharge	= 277.51 cfs
Storm frequency	= 25 yrs	Time to peak	= 716 min
Time interval	= 2 min	Hyd. volume	= 588,683 cuft
Drainage area	= 36.620 ac	Curve number	= 86
Basin Slope	= 0.0 %	Hydraulic length	= 0 ft
Tc method	= User	Time of conc. (Tc)	= 5.00 min
Total precip.	= 6.33 in	Distribution	= Type II
Storm duration	= 24 hrs	Shape factor	= 484




Hydrograph Report

Hyd. No. 2

RESERVOIR

Hydrograph type	= Reservoir	Peak discharge	= 14.30 cfs
Storm frequency	= 25 yrs	Time to peak	= 774 min
Time interval	= 2 min	Hyd. volume	= 588,606 cuft
Inflow hyd. No.	= 1 - SEDIMENT BASIN	Max. Elevation	= 612.66 ft
Reservoir name	= SEDIMENT BASIN	Max. Storage	= 317,854 cuft

Storage Indication method used.



Weir Report

Principal Spillway-Known Q

Rectangular Weir


Crest = Sharp
Bottom Length (ft) = 9.42
Total Depth (ft) = 4.00

Calculations

Weir Coeff. Cw = 3.33
Compute by: Q vs Depth
No. Increments = 40

Highlighted

Depth (ft) = 1.00
Q (cfs) = 31.37
Area (sqft) = 9.42
Velocity (ft/s) = 3.33
Top Width (ft) = 9.42



Weir Report

Espillway-Design Q

Trapezoidal Weir

Crest	= Sharp
Bottom Length (ft)	= 38.00
Total Depth (ft)	= 2.71
Side Slope (z:1)	= 3.00

Highlighted

Depth (ft)	= 1.71
Q (cfs)	= 246.14
Area (sqft)	= 73.75
Velocity (ft/s)	= 3.34
Top Width (ft)	= 48.26

Calculations

Weir Coeff. Cw	= 2.63
Compute by:	Known Q
Known Q (cfs)	= 246.14

