



Heiman Fire Equipment Inc.

2320 N. W. Blvd.
 Ashton, Iowa 51232-7096
 (712) 724-6212 Fax (712) 724-6474

QUOTE

Customer

Name	Moberly Fire Dept.		
Address	310 N. Clark St.		
City	Moberly	State	MO ZIP 65270
Phone	Don Ryan 660-269-8705	ryand@moberlyfd.com	

Date	7/22/2025
Customer #	5007
Rep	Les Hinnen
PO #	

Qty	Description	Unit Price	TOTAL
1	Coltri air compressor system per attached specification	\$57,514.00	\$57,514.00
Shipping estimated at \$3,800.00			

Payment Details	
<input type="radio"/>	ORDER
<input type="radio"/>	INVOICE
<input checked="" type="radio"/>	QUOTE
Les Hinnen	
660-973-1189	
Chillicothe, MO 64601	

SubTotal	\$57,514.00
Shipping & Handling	
Taxes	
TOTAL	\$57,514.00

Office Use Only

DESCRIPTION

SILENT HD 450 ET – 4 STAGE / 10HP / 15.9 CFM / 450 L/PM / 6000 PSI / THREE PHASE / 230 V / 60 HZ / UL 508A CONTROL PANEL / OIL PUMP / EXTRA INTERCOOLERS / AUTO-STOP / AUTO-CONDENSATE / DUAL SEPARATORS / DUAL FILTRATION / SOUNDPROOF CABINET 68 DB.

DUAL FILTRATION

The filtration cleans 106,000 cu ft for producing Grade E air:

- **FILTER ONE MOLECULAR SIEVE**
The molecular sieve, through porous micro granules, is used to absorb moisture.
- **FILTER TWO MOLECULAR SIEVE, ACTIVATED CARBON AND CO-CATALYST**
The CO-catalyst, in addition to the molecular sieve and the activated carbon, will allow it to absorb any sign of Carbon Monoxide.

CONTROL PANEL / ELECTRICAL SWITCHBOARD

The cabinet is equipped with a high-pressure connection, a complete control panel, and an electrical switchboard – interstage pressure gauges, phase controller, cabin temperature, hour meter, emergency stop and digital pressure switch.

SAFEGUARD

SAFEGUARD is a fully digital instrument with a visible and audible alarm if carbon monoxide is present over the preset limits. It is based on a state-of-the art carbon monoxide electrochemical sensor with long term stability and virtually calibration-free. The instrument is able to read 5 ppm (parts per million), in compliance with the NFPA standards.

CABINET

The cabinet is powder-coated to resist humidity and rust.

ELECTRONICS

All electronics are **UL 508A compliant**.

ARMOUR FILL ENCLOSURE – SSX2 (SSCFS2-4HP)

Explosion Proof fill enclosure.

- 2 SCBA Cylinder Positions
- Dual Wall Construction
- Isolated Valves (fill one bottle at a time or 2 simultaneously)
- Fill Regulator
- Powder-coated and Hammered Steel
- NFPA 1901 Certification
- 4 ISO 6000 PSI CASCADE BOTTLES
-