

Customer Proposal Letter

CITY OF NORMAN
PO BOX 370
NORMAN, OK 73070

Thank you for trusting us with your business. Please review the proposal below, and if you approve, sign and return to us at your convenience. We look forward to working with you and will continue to do our best to earn your trust now and in the future.

VEHICLE INFORMATION

Year 2024 Make Peterbilt Model 520 Stock # TBD Serial # TBD

Additional Vehicle Details: (3) 2024 Peterbilt 520 ASL Chassis, Oklahoma State Contract SW0035T, Cummins L9N, Allison 4500 RDS Transmission, Cummins 5 year/150,000 miles warranty

	3	Total
Quantity		
Truck Price per Unit	\$ 201,225.00	\$ 603,675.00
F.E.T. (Factory & Dealer Paid)	\$ 0.00	
Net Sales Price	\$ 201,225.00	\$ 603,675.00
Optional Extended Warranty(ies)	\$ 3,235.00	\$ 9,705.00
State Sales Tax		
Documentary Fee	\$ 250.00	\$ 750.00
Total Sales Price	\$ 204,710.00	\$ 614,130.00
Trade Allowance (see DISCLAIMER Below)		
Deposit / Down Payment		
Unpaid Balance Due on Delivery	\$ 204,710.00	\$ 614,130.00

Sales Representative

William Duncan

Printed Name

Date _____

Purchaser

Signature

Printed Name / Title

Date _____

Accepted by Sales Manager
or General Manager

Signature

Printed Name

Date _____

Quote good until 3/5/2023

Note: The above Customer Proposal is a quotation only. Sale terms subject to approval of Sales Manager of Dealer.

DISCLAIMER: Any order based on this Proposal is subject to Customer executing Dealer's standard form Retail Sales Order and other required documents incorporating the above terms. Any documentary fees, FET, state tax, title, registration and license fees subject to adjustment and change. This Proposal is based upon Dealer's current and expected inventory, which is subject to change. Dealer is not obligated to retain any specific vehicles in stock, nor maintain specific inventory levels. Dealer shall not be obligated to fulfill Proposal in event quoted vehicle(s) is not in stock or available within requested delivery schedule. Manufacturer has reserved the right to change the price to Dealer of any vehicle not currently in Dealer's stock, without notice to Dealer and Dealer reserves the right to change Quotation Total to reflect any price increases from Manufacturer. Dealer shall not be liable for any delay in providing or inability to provide Quoted Vehicle(s). Above listed Trade Value based upon current appraisal of Trade Vehicle(s). Dealer may adjust Trade Value of Trade Vehicle(s) to reflect changes in condition and/or mileage of Trade Vehicle(s) between date of current appraisal and acceptance of the Trade Vehicle by Customer.

⁽¹⁾ Includes subscription period for # of specified months. ⁽²⁾ Customer's use of RushCare Service is governed by the RushCare User Agreement located at <https://www.rushtruckcenters.com/rushcare-user-agreement>. ⁽³⁾ Customer's use of Telematics Services is governed by separate 3rd party license terms and Rush is not liable for the Telematics Service. ⁽⁴⁾ Gap Coverage is provided and administered by an independent 3rd party provider under a separate contract directly between Customer and the 3rd party provider.

~~\$201,475~~



Rush Pblt Truck Centers (O500)
8700 West I-40
Oklahoma City, Oklahoma 73128

+ 3235 warranty
~~\$204,710~~

City Of Norman
Po Box 370
Norman, Oklahoma 73070
United States of America

William Duncan
Cell Phone: 405-922-4093
Office Phone: 405-782-3508
Email: duncanw@rushenterprises.com

Mike White

Vehicle Summary

Unit		Chassis	
Model:	Model 520	Fr Axle Load (lbs):	20000
Type:	Full Truck	Rr Axle Load (lbs):	46000
Description 1:	520 ASL CNG	G.C.W. (lbs):	66000
Description 2:	Clone of Chassis 111520 Model 520		
Application		Road Conditions:	
Intended Serv.:	Refuse/On-Highway	Class A (Highway)	100
Commodity:	Refuse, Scrap, Recycling	Class B (Hwy/Mtn)	0
		Class C (Off-Hwy)	0
		Class D (Off-Road)	0
Body		Maximum Grade:	6
Type:	Automated Side Loader	Wheelbase (in):	216
Length (ft):	24	Overhang (in):	60
Height (ft):	13.5	Fr Axle to BOC (in):	0.1
Max Laden Weight (lbs):	10000		
Trailer		Cab to Axle (in):	215.9
No. of Trailer Axles:	0	Cab to EOF (in):	275.9
Type:		Overall Comb. Length (in):	333.6
Length (ft):	0		
Height (ft):	0	Special Req.	
Kingpin Inset (in):	0		
Corner Radius (in):	0		
Restrictions			
Length (ft):	40		
Width (in):	102		
Height (ft):	13.5		

~~\$201,475~~

5 YEAR / 150,000 \$3235 warranty

Approved by: _____

Date: _____

~~TOTAL \$204,710~~

Note: All sales are F.O.B. designated plant of manufacture.



Sales Code	Std/ Opt	Description	\$ List	Weight
Base Model				
0005201	S	Model 520 Peterbilt's Model 520 is built to withstand the harsh demands of the refuse industry. The rugged, aluminum cab delivers best-in-class durability for increased uptime and lap seam construction on a zinc-coated steel sub-frame for corrosion resistance. Bulkhead-style doors provide years of watertight performance. This low-cab forward vehicle adds a new dimension of productivity and versatility. An industry-leading, 65-degree cab tilt enhances maintenance and serviceability. Body installation is cost effective and efficient and the center console provides convenient access to body control integration points.	220,522	16,475
0091180	S	Refuse, Scrap, Recycling	0	0
0093035	S	Refuse/On-Highway Truck or tractor which hauls refuse, recycled material, etc. Includes roll-on/roll-off container movement, as well as hauling refuse from transfer stations to, but not into, landfills.	0	0
0095120	O	Automated Side Loader A lift-equipped truck used to pick up wheeled waste containers to load waste materials into the truck body. Requires a single operator. The load is removed by a tilt of the truck body.	0	0
0098170	S	United States Registry Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0	0
Configuration				
0200672	O	Labrie Natural Gas Fuel System Assembler	0	0
Frame & Equipment				
0514160	O	10-3/4" Steel Rails 306-342" 10.75x3.5x.375 Dimension, 2,136,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair	441	182
0601500	O	Full Steel Inner Liner	963	672
0620110	O	FEPTO Provision 9in Bumper Extension Includes 1350 Series Front Drive PTO Attachment Provision, Radiator with PTO Cut-Out in Grille, Radiator Protection Sleeve, and Bumper Extension	1,693	42
0620500	O	Frame Components Bolted IPO Huck Fastened	91	0
0644020	O	EOF Square with Steel Crossmember	236	64
0651090	S	Omit Rear Mudflaps and Hangers	0	0
0713130	O	(2) Solid Mount Cable Hooks	0	40
Front Axle & Equipment				

Price Level: January 1, 2023

100% Complete

Date: February 01, 2023

Deal: 520 ASL CNG

Quote Number: QUO-1026837-T5Z7C8

Printed On: 2/1/2023 7:30:27 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
1011890	S	PACCAR FX-20 Steer Axle 20,000 lbs. 4" Drop Axle is designed for applications with a gross axle weight rating (GAWR) of 20,000 pounds. Front axle is designed for demanding applications such as construction, heavy haul, refuse, and other vocational uses. Robust forged steel beam construction for long-lasting performance. It utilizes innovative tapered kingpin roller bearings for more efficient operation and improved steering efficiency.	0	0
		The PACCAR Steer Axle comes standard with the PACCAR warranty of 5 years, 750,000 miles.		
1114030	S	Taper Leaf Springs, Shocks 20,000 lb Standard with Heavy Resistance Shocks.	0	0
1243010	S	Power Steering Sheppard M100 Dual Gear For use with 16,000 to 20,000 lb. axle ratings. Glidekote splines on steering shaft extend service life of components.	0	0
1354840	O	PHP10 Iron PreSet PLUS Hubs PHP10 iron PreSet PLUS hubs have a fully integrated spindle nut design, an optimized wheel spacer, magnetic fill plug on drive and trailer hubs for inspection of metal particles in lubricant, with a long life oil seal and bearings are pre-adjusted. Use with Front Axle.	-580	84
1380280	O	Bendix Air Cam Front Drum Brakes 16.5x7 For use with 16,000 lbs to 23,000 lbs steer axles or front drive axles. Includes automatic slack adjusters & outboard mounted brake drums.	682	0
1380490	O	PACCAR FX Wide Track IPO Standard 71in KPI IPO 69in front axle for improved turning radius.	0	0
1391410	O	Gusseted Cam Brackets, Steer Axle	28	0
1392970	O	Heavy Duty Cam Bushings, Steer Axle	31	0
Rear Axle & Equipment				
1523440	S	Dana Spicer D46-172 46,000 LBS Dana Spicer D46-172 46,000 lbs tandem drive axles offer efficiency improvement, axle weight reduction and reduced lube quantity.	0	0
1616300	O	PHP10 Iron PreSet PLUS Hubs	-670	0
1680280	O	Bendix Smart ATC Traction Control	266	2
1680440	O	Refuse Service Brakes, Steer And Drive Axles Designed for heavy-duty applications for refuse industry, providing long brake life, safety and performance.	0	0
1680450	O	Rear Brake Camshaft Reinforcement Rear brake camshaft reinforcement helps guard against wear and corrosion.	65	9
1680490	O	Gusseted Cam Brackets, Drive Axle(s)	72	2
1680500	S	SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve	0	0

Price Level: January 1, 2023

100% Complete

Date: February 01, 2023

Deal: 520 ASL CNG

Quote Number: QUO-1026837-T5Z7C8

Printed On: 2/1/2023 7:30:27 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
		allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.		
1680910	O	Heavy Duty Brake Drums, Drive Axle(s) Use with 16.5x7 Brakes	283	21
1682430	S	Anti-Lock Braking System (ABS) 4S4M ABS-6. Includes air braking system.	0	0
1684200	S	Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0	0
1687010	O	Bendix Air Cam Rear Drum Brakes 16.5x7 Bendix Air Cam Rear Drum Brakes to fit all heavy haul, construction, refuse and highway truck and tractor applications. Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums.	-406	0
1705570	O	Ratio 5.57 Rear Axle	0	0
1824440	O	Hendrickson HMX EX 460 46,000 LBS., 52" Haulmax, 70K Creep Rating. Includes Traax Rod as standard, option 1920905 is not needed or available. Progressive load spring system easily adjusts to the load for an enhanced combination of empty-ride quality and loaded stability.	1,968	-88
1921375	O	16.5" Saddle Height HMX EX 400/460 IPO Std 18.5"	428	0

Engine & Equipment

2056317	O	L9N 320@2000 GOV@2200 1000@1300 (2018 Emissions) Magnetic engine oil drain plug captures and holds any metal fragments in engine oil to extend service life. N21430 N201 0.....Reserve Speed Limit Offset (N21410 N202 0.....Maximum Cycle Distance (N202 N21400 N203 252...Reserve Speed Function Reset N21320 N205 120...Standard Maximum Speed Limit N21420 N206 0.....Maximum Active Distance (N20 N21470 P062 NO....Cruise Control Auto Resume (N21480 P068 NO....Auto Engine Brake in Cruise N21450 P026 NO....Gear Down Protection (P026) N21440 P015 NO....Engine Protection Shutdown (N21340 P112 93....Hard Maximum Speed Limit (P1 N21350 P001 65....Maximum Accelerator Pedal Ve N21370 P059 65....Maximum Cruise Speed (P059) N21590 P230 YES...Enable Hot Ambient Automatic N21530 P233 YES...Enable Impending Shutdown Wa N21540 P234 60....Timer For Impending Shutdown N21460 P046 1400..Max PTO Speed (P046) N21520 P030 5.....Timer Setting (P030) N21570 P031 NO....Idle Shutdown Manual Overrul	21,607	0
---------	---	---	--------	---

Price Level: January 1, 2023

100% Complete

Date: February 01, 2023

Deal: 520 ASL CNG

Quote Number: QUO-1026837-T5Z7C8

Printed On: 2/1/2023 7:30:27 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
		N21610 P172 40....Low Ambient Temperature Thre		
		N21630 P171 80....High Ambient Temperature Thr		
		N21550 P516 100...Engine Load Threshold (P516)		
		N21510 P520 YES...Enable Idle Shutdown Park Br		
		N21620 P173 60....Intermediate Ambient Tempera		
		N21330 N207 0.....Expiration Distance (N207)		
		N21500 N209 0.....Expiration Distance (N209)		
2091130	S	VMUX Electronics Architecture	0	0
2091305	O	Engine Idle Shutdown Timer Enabled	0	0
2091315	O	Enable EIST Ambient Temp Overrule	0	0
2091372		Eff EIST NA Expiration Miles	0	0
2091640		Effective VSL Setting NA	0	0
2092013	O	Typical Operating Speed 60 MPH	0	0
2092033	O	Powertrain Optimized for Balance Best analysis for vehicles where service includes frequent start and stop cycles.	0	0
2140220	S	CARB Engine Idling Compliance DECLINED By Dealer/Customer	0	0
2140450	O	Remote PTO/Throttle, 12-Pin Eng Bay Remote Control Provision	103	0
2140670	O	EPA Emission Warranty	0	0
2147460	S	Bed Plate for PX-9, L9N Engines Designed to increase engine longevity by incorporating a stiffener bracket on the bottom side of the engine, inside the oil pan, for additional reinforcement. Required for all PX-9/L9N refuse applications and recommended for other high load 9-liter applications.	0	0
2513060	S	PACCAR 160 Amp Alternator, Brushed PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0	0
2521090	O	Immersion Type Block Heater 110-120V Standard location for 2.1M and 1.9M models is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	86	2
2522110	O	PACCAR 12V Starter, N/A PACCAR MX Engines PACCAR 12-volt electrical system. With centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	0	0
2538040	S	3 PACCAR Premium 12V Dual Purpose Batt 2190 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0	0

Price Level: January 1, 2023

100% Complete

Date: February 01, 2023

Deal: 520 ASL CNG

Quote Number: QUO-1026837-T5Z7C8

Printed On: 2/1/2023 7:30:27 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
2539220	O	Battery Jumper Terminals Mtd In Front Of Battery Box	198	4
2539740	O	Kissling Battery Disconnect Switch 300AMP Dual Tab Mounted on Battery Box	160	3
2621000	S	2-Speed Fan Clutch For Frequent Start/Stops A 2-speed fan clutch is ideal for vocational applications where the fan clutch engagement time exceeds 10% of the engine run time. When the fan clutch is disengaged, the fan still rotates at 15-25% of the engine RPM. This fan rotation provides crucial airflow to the engine and draws virtually no horsepower.	0	0
2723210	S	18.7 CFM Air Compressor N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	0	0
2921170	O	Spin-On Fuel/Water Separator for Natural Gas Engines	0	0
2921210	S	No Fluid Heat Option for Fuel Filter	0	0
2921310	S	No Electric Heat Option for Fuel Filter	0	0
3010400	O	Engine Protection Shutdown w/ Label Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature.	10	0
3114270	S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 367 1325 sq in, 367 HH Fepto 1325 sq in, 365 Fepto 1183 sq in, 365 Full Frame Extension 1000 sq in, 520 1202 sq in, 579 1456.9 sq in, 535/536/537/548 949.3 sq in, 537/548 VOC 1000.3 sq in, 389/367 HH 1604 sq in, 365/567 1379 sq in.	0	0
3120320	O	Bugscreen	140	0
3120450	S	Stainless Steel Grille	0	0
3261980	S	Heavy Duty Air Cleaner Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.	0	0
3281750	O	Pre-Cleaner ECG	142	13
3365450	O	Exhaust Single LH Vertical Natural Gas Engines Only	8,885	-486
3381770	O	Curved Tip Standpipe(s)	43	1
3387650	O	36" Single Standpipe L9N Engine Only	0	0

Price Level: January 1, 2023

100% Complete

Date: February 01, 2023

Deal: 520 ASL CNG

Quote Number: QUO-1026837-T5Z7C8

Printed On: 2/1/2023 7:30:27 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
------------	----------	-------------	---------	--------

Transmission & Equipment

4052970	O	Allison 4500 RDS-P Transmission, Gen 6 Rugged Duty Series	18,543	390
4210190	O	1810 HD Driveline, 1 Midship Bearing 4.5in x .180 wall tubing	-389	15
4216590	O	1710 Driveline Interaxle For tandem rear axles	-101	-5
4252890	O	Allison FuelSense 2.0 Not Desired	-106	0
4252950	O	Omit Allison Neutral At Stop	0	0
4256020	S	Console Mounted Push Button Shifter	0	0
4256740	O	Allison 6-Speed Configuration, Wide Ratio Gears Allison 4500 transmission only	0	0
4256870	O	Allison Output Function S Neutral Indicator Allison output function S Neutral Indicator for PTO. Required on Refuse Packer Applications. With this configuration NEUTRAL only, PTO engagement is permitted only when the transmission is in Neutral. Once the transmission is in Neutral, the PTO is automatically engaged and fast idle is initiated when the PTO switch is on. In addition with this configuration Pack-on-the-fly, the PTO is automatically engaged and fast idle is initiated when the PTO switch is On concurrently with shifting of the transmission to Neutral.	0	0

Air & Trailer Equipment

4510210	S	Bendix AD-HF EP Air Dryer, Heater Coalescing filter, extended purge. Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technology in the the air dryer cartridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant.	0	0
4520180	O	Air Tank Valve Guards	23	0
4520420	O	Pull Cords All Air Tanks	3	1
4540420	S	Nylon Chassis Hose	0	0
4543320	S	Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0	0

Tires & Wheels

Price Level: January 1, 2023

100% Complete

Date: February 01, 2023

Deal: 520 ASL CNG

Quote Number: QUO-1026837-T5Z7C8

Printed On: 2/1/2023 7:30:27 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
5032320	O	FF: GY 20ply 315/80R22.5 G289 WHA Diameter = 43.1 inches; SLR = 20.0 inches. Compares to Michelin XZUS 2 and Bridgestone M860 tread.	332	-20
5130630	O	RR: GY 16ply 11R22.5 Endurance LHD Efficiency Rating: Poor Diameter= 42.4 inches; SLR= 19.9 inches	1,436	100
5190008	S	Code-rear Tire Qty 08	0	0
5210550	S	FF: Accur Std Armor 29039PK 22.5X9.00 PHP10-5 Hand Holes	0	0
5310600	S	RR: Accur Std Armor 50291PK 22.5X8.25 Heavy Duty, Two Hand Holes	0	0
5390008	S	Code-rear Rim Qty 08	0	0
Fuel Tanks				
5532010	O	No Fuel Tank/Fuel System Provided, CNG Only	-424	0
5604000	O	Location LH BOC 000 Gal	0	0
5653070	O	CNG / LNG Frame Rail Mounted Tank Only	0	0
5653180	O	CNG Fuel System Compressed Natural Gas Fuel System.	0	0
Battery Box & Bumper				
6010460	O	Aluminum Space Saver Battery Box LH Back Of Cab	145	-11
6030360	O	Mount Space Saver Battery Box Top Of Box 8" Below top of frame	722	0
6122810	O	Steel Bumper Swept Back Painted Requires bumper extension, includes two front tow eyes with pins	-20	2
6132400	O	Notched Top Flange Of Bumper Does not include fepto provisions	50	0
Cab & Equipment				
6501090	O	53" LCF ProBilt Cab RH Drive Use with auto-trans. Includes steel frames with aluminum and fiberglass panels, all aluminum doors, dual door stops, door locks, tinted safety glass thru-out, cab and door mounted entry grab handles, 65 degree hydraulic tilt, stainless steel grille, dual rear cab fenders, service module BOC (cab tilt pump, oil fill and dipstick, coolant fill and check, fluid fill and dipstick for auto trans), door mounted armrests, power windows, doghouse full insulation, rubber floor mats, ergonomic center control console, removable instrument panel, Driver Information Display, LED backlit gauges, adjustable side flip-down interior sunvisor, 16" steering wheel with integrated horn button, tilt/telescopic adjustable column, over-door storage, driver and passenger side cup holders, USB charging port and 12VDC charging outlet, header includes HVAC	1,361	0

Price Level: January 1, 2023

100% Complete

Date: February 01, 2023

Deal: 520 ASL CNG

Quote Number: QUO-1026837-T5Z7C8

Printed On: 2/1/2023 7:30:27 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
		controls, rear cab corner windows, 18" bolt-on step on each side, self-canceling turn signals and Front Directional and Side Mounted Turn Signals.		
6540160	S	Thermal Insulation Package in Cab The thermal insulation package is designed to make the cab thermally efficient in extreme temperatures. The model 520 adds insulation surrounding the doghouse to reduce engine heat transmitted to the cab.	0	0
6800500	S	4.5" Rubber Flares On Cab And wheel well fenders	0	0
6911720	S	Peterbilt Driver Seat	0	0
6921720	S	Peterbilt Passenger Seat	0	0
6931120	O	Seat Belt Color Orange IPO Standard Black	10	0
6939400	O	Air Ride Driver	389	43
6939420	O	High Back Driver	33	0
6939470	S	Vinyl Driver	0	0
6939510	S	Non-Air Ride Passenger	0	0
6939540	S	Low Back Passenger	0	0
6939570	S	Vinyl Passenger	0	0
7000000	S	Gray Interior Color Includes ABS gray headliner & rear cab panel, gray vinyl engine tunnel cover. For LH, RH, and dual steer dual seated power windows are standard on both doors. For dual steer RH stand-up the LH window is power and the RH window is a manual sliding window.	0	0
7001520	S	Adjustable Steering Column - Tilt/Telescope	0	0
7001620	S	Steering Wheel With Peterbilt Logo Steering Wheel with embossed Peterbilt logo over horn button.	0	0
7040020	O	Diamond Plate Floor Covering on Driver side floor in place of Rubber Mat. In Dual Steer application RH Diamond Plate covering is standard. Single drive applications the Diamond Plate is optional.	46	6
7110680	S	Exterior Cab Entry Grabhandle Textured; NFPA compliant. Available on Day Cab specifications only.	0	0
7220150	O	Rear Window Back of Cab Dark Tint 18.5in X 54in	24	0
7230350	S	2-Piece Flat Windshield	0	0
7322010	S	Combo Fresh Air Heater/Air Conditioner	0	0

Price Level: January 1, 2023

100% Complete

Date: February 01, 2023

Deal: 520 ASL CNG

Quote Number: QUO-1026837-T5Z7C8

Printed On: 2/1/2023 7:30:27 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
		With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.		
7330920	O	(2) Defroster Fan On Rear Header	237	60
7410040	O	Outside Sunvisor - Stainless Steel Not available with 2.1M high roof sleeper.	366	4
7560100	O	Mirrors SSTL Each Side Heated and Motorized with Switch on Door.	-30	-7
7610020	S	(1) Air Horn 15" Painted Mounted under cab.	0	0
7722120	O	ConcertClass, AM/FM, Weatherband, 3.5 Aux	467	10
7725740	O	Midlevel Speaker Package For Cab (4) Speakers	135	6
7728020	O	Bluetooth Located On Driver Side	0	0
7728030	O	Radio Mute When In Reverse For automatic or automated transmission	0	0
7728040	O	Bluetooth Phone and Audio Requires USB Port	62	0
7728050	O	USB Port	62	0
7788055	S	SmartLINQ Remote Diagnostics SmartLINQ is Peterbilts proprietary remote diagnostics service which monitors the engine and aftertreatment for diagnostic codes providing real-time code analysis maximizing vehicle uptime and strengthening the fleets partnership with their dealer. SmartLINQ provides fault coverage for over 800 codes, a customizable email notification for 116 codes plus a web portal to manage your entire fleet included at no additional charge. SmartLINQ is compatible with any telematics system and doesnt require a specific fleet management system. For those whose customers utilize PeopleNet, the pre-wire with remote diagnostics will provide a more integrated solution utilizing the existing SmartLINQ modem. For those whose customers utilize other fleet services products, the existing pre-wire option for the other fleet service devices will continue to be available. Standard on Class 8 engines and available on Models 348, 337, 330 and 325 with a PX-9, PX-7 or Cummins Westport natural gas engine.	0	0
7788058	O	24 Months SmartLINQ Subscription Cummins Engines.	0	0
7851330	O	Cab Tilt Pump Air Assist	512	0
7851870	O	Rain Gutters Over Driver and Passenger Doors	76	8
7852150	S	Peterbilt Pantograph Windshield Wipers With intermittent feature.	0	0
7900090	O	Triangle Reflector Kit, Ship Loose	30	13

Price Level: January 1, 2023

100% Complete

Date: February 01, 2023

Deal: 520 ASL CNG

Quote Number: QUO-1026837-T5Z7C8

Printed On: 2/1/2023 7:30:27 AM



Sales Code	Std/Opt	Description	\$ List	Weight
		Florescent triangle emergency road flares are designed to meet and exceed all DOT standards.		
7901140	O	Backup Alarm (87-112 DB) Variable adjusting	129	6
8011800	O	Drive Axle #1 Front Oil Temperature Gauge Located in Digital Cluster Display.	36	0
8011810	O	Drive Axle #2 Rear Oil Temperature Gauge Located in Digital Cluster Display.	36	0
8011850	S	Transmission Oil Temperature (Main) Located in Digital Cluster Display.	0	0
8021315	S	Air Restriction Indicator Mounted on exhaust stanchion	0	0
8031120	O	Warning Light Battery Disconnect, Switch Engaged Marker light external mounted	14	0
8070260	O	Switch To Deactivate ATC Traction Control Bendix ATC is required on the specification. Switch is to temporarily disable the Traction Control in extreme conditions such as snow, ice or mud. The ATC warning light will display in a constant state.	0	0
8070880	O	Main Instrumentation Panel (Gas Engine) Digital Cluster 7" Display includes: Physical (Analog) - Speedometer, Tachometer, Oil Pressure, Coolant Temp and Display Gauges - Fuel Level, Volts Telltale, OAT and Primary Air Pressure, Secondary Air Pressure for air brake trucks.	0	0
8110090	S	Headlights Single Rectangular Halogen	0	0
8120570	S	(5) LED Clearance With (2) LED Marker Lights Includes (5) lights mounted on roof of cab and (1) cab side marker light mounted in front of each cab door	0	0
8133900	S	None Furnished Stop/Tail/Backup Lights Available with full truck only, not available with tractor	0	0
8134160	O	Self-Canceling Turn Signal	0	0

Paint

8530770	O	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - L0895EY GREEN N85700 BUMPER L0001EA BLACK N85500 CAB ROOF L0895EY GREEN N85200 FRAME L0001EA BLACK	0	0
---------	---	--	---	---

Shipping Destination

Options Not Subject To Discount

9400090	S	Peterbilt Class 8 Standard Coverage 1 year/100,000 Miles (160,000 km)	0	0
9407147	O	Fuel Price Index Factor \$438 NET	438	0

Miscellaneous

Price Level: January 1, 2023

100% Complete

Date: February 01, 2023

Deal: 520 ASL CNG

Quote Number: QUO-1026837-T5Z7C8

Printed On: 2/1/2023 7:30:27 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
9409086	O	State Registry: Oklahoma	0	0

Promotions

Order Comments

Total List Price (W/O Freight & Warranty & Surcharges)	\$281,696
Marketing and Service Support Fee	\$1,095
Prepaid Freight	\$4,300
Total Surcharge/Options Not Subject To Discount	\$438
Total Weight	17,664

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information