

Road Closure - 2025 Moovin thru the Midway 5k



Sources: Esri, Airbus DS, USGS, NGA, NASA, CGIAR, N Robinson, NCEAS, NLS, OS, NMA, Geodaten, Rijkswaterstaat, GSA, Geoland, FEMA, Intermap and the GIS user community

MAP INTERPRETATION NOTICE

Map information depicted is not intended to replace or substitute for any official or primary source. This map was intended to meet National Map Accuracy Standards and use the most recent, accurate sources available to the people of the City of Novi. Boundary measurements and area calculations are approximate and should not be construed as survey measurements performed by a licensed Michigan Surveyor as defined in Michigan Public Act 132 of 1970 as amended. Please contact the City GIS Manager to confirm source and accuracy information related to this map.

0 0.075 0.15 0.3 0.45

1 inch = 752 feet



Map Print Date:
6/20/2024



City of Novi

45175 Ten Mile Rd
Novi, MI 48375
cityofnovi.org

PARKING



2024 5K Map



46850 Grand River Ave

This floorplan has been designed to be used exclusively by Art Craft Display, Inc and their clients. S.Karakula (8-15-23)

★ 20amp

◆ clowns

sardo

Taft Rd



ROAD CLOSURE PERMIT FOR BLOCK PARTIES AND PARADES

Permit No.: **PRCL25-015**

Issue Date:

Upon the request of **Michigan State Fair, LLC**, in accordance with the provisions of the Code of Ordinances of the City of Novi, Michigan Section 33-52, Parades and Processions in the Uniform Traffic Code, and Section 31-9, Road Closures, a permit to temporarily close **West bound lanes of Grand River Ave from Taft Rd to 46850 Grand River Ave** for the purpose of a **Moovin' thru the Midway 5k - 2025 michigan state fair** is granted as follows:

Applicant: The Michigan State Fair, LLC

Street Address: The right West bound lane of Grand River Ave at Taft Rd to 46850 Grand River Ave.

Name of street(s) requested for closure: West bound lanes of Grand River Ave at Taft Rd to 46850 Grand River Ave.

Date of Closure: Saturday, August 30th, 2025, From: 7:30am To: 9:30am

Notes/Special Requests: Would like to close one west-bound lane of Grand River Ave for our "Moovin' thru the Midway 5K race".

If the applicant needs barricades, barrels, or cones for the event, the applicant **MUST** contact DPW Field Operations at 248-735-5640 at least 7 business days prior to the event to make the request and coordinate locations.

Approved by:

Ben Croy, City Engineer

cc: Erick Zinser, Director of Public Safety/Chief of Police
John Martin, Fire Chief
Scott Beatens, Assistant Police Chief
Todd Seog, Assistant Fire Chief
Kristie Gruenwald, Police Commander
Jason Meier, Police Commander
Matt Wiktorowski, Field Operations Senior Manager
Aaron Staup, Construction Engineer

AS A CONDITION OF THE APPROVAL OF THIS APPLICATION, THE APPLICANT AGREES TO THE FOLLOWING CONDITIONS:

1. The application agrees to secure, or cause to be secured, a permit from the Board prior to the commencement of construction or maintenance operations. If a contractor is to perform the construction or maintenance entailed in this application, the contractor shall secure the permit from the Board prior to the commencement of construction or maintenance operations and thereby assumes responsibility, along with the applicant, for any provisions of this application which apply to them.
2. Any and all construction proposed under this application will meet all requirements of the Board, together with the Supplemental Specifications as set forth below.
3. The applicant agrees to save harmless, indemnify, defend, and represent the Board and its employees against any and all claims for bodily injury or property damage, or any other claim arising out of or related to the creation, operation, use, or continuing existence of the structure or facility covered by the permit or for any other work done within county road right-of-way whether or not specifically authorized or in conformance with the description of activities for which the permit was issued. Applicant agrees and understands that the obligations set forth herein are binding upon their successors, transferors, assigns, sureties, and guarantors. The Applicant shall maintain insurance of a type and in an amount in conformance with the Board's established requirements and provide certificates of insurance in a type and amount which shall assure conformance with the Board's established requirements is currently in force for any and all facilities installed in the Board's right of way.
4. The applicant agrees to surrender the permit herein applied for; surrender all rights hereunder; cease operations; and remove, alter, relocate at applicant's own expense, the facilities for which this permit is granted whenever ordered to do so by the Board because of the need for the area covered by this permit for public uses or because of a default in the conditions of the permit. Upon failure to remove, alter, relocate or surrender the facilities pursuant to the order of the Board, the applicant agrees to reimburse the Board for its cost in doing same.
5. Nothing in this application shall be construed to grant any rights whatsoever to any public utilities whatsoever except as to the consent herein specifically given, nor to otherwise impair any existing rights granted in accordance with the constitution or laws of this State.
6. The obligation to construct, operate, use and/or maintain the facility to the satisfaction of the Board remains in force as long as the facility exists and is within the right-of-way under the jurisdiction of the Board. The applicant is obliged to repair any damage to the road and right of way which is a result of the facility and which occurs or appears after the permit licensee is released.
7. The necessary construction zone signing for the protection of traffic shall be in accordance with the most current edition of the Michigan Manual of Uniform Traffic Control Devices, Part 6. All such devices shall be furnished, installed and maintained by the Permit Holder. All construction signage shall have black lettering on a reflective fluorescent orange background, unless otherwise specified. The Permit Holder shall provide any additional signs, barricades and/or lights, at the Permit Holder's expense, required to protect the general motoring public and the work zone when requested by the Road Commission.
8. **ADDITIONAL CONDITIONS:** As will be identified in approved permit description.

SUPPLEMENTAL SPECIFICATIONS

1. **EXCAVATION AND DISPOSAL OF EXCAVATED MATERIAL:** The contractor and/or the utility company shall provide and place the necessary sheeting, shoring and bracing required to prevent caving, loss or settlement of foundation material supporting the pavement, or any other highway installation such as sewers, culverts, etc. The contractor and/or utility company shall assume the full responsibility for this protection. Excavated material shall be stocked in such locations that it does not obstruct vision on the traveled portion of the highway and in such a manner that it will not interfere with the flow of traffic. Sod and topsoil shall be stocked separately from other excavated material. The applicant shall dispose of all surplus and unsuitable material outside of the limits of the right-of-way unless the permit provides for, and with approval of abutting property owners, disposal at approved locations with the right-of-way. In the latter case, the material shall be leveled and trimmed in a manner approved by the Road Commission for Oakland County.
2. **BACKFILLING AND COMPACTING BACKFILL:** All trenches, holes, pits, and other excavations shall be filled with approved excavated earth or with MDOT Class II granular material if so provided, placed in successive layers not more than 9 inches in depth, loose measure, and each layer shall be thoroughly compacted by tamping and all backfill compaction will be subject to check by the Controlled Density Method (minimum 95%). Restoration shall be such that it will provide a condition equal to or better than the original condition and in accordance with current Road Commission for Oakland County standards. Any excavation within the right of way outside traveled portion of road must be maintained until all settlement has occurred and must be restored and seeded or sodded as directed. The permit will not be released until the Road Commission is satisfied that no further settlement will occur.
3. **CROSSING ROADBED BY TUNNELING, DIRECTIONAL BORE, JACK CASING AND BORE:** When the pipe is installed by tunneling without cutting the existing pavement, the tunnel shall be adequately sheeted or shored to prevent the sides and top from collapsing or the pavement from settling or cracking. Directional bore shall be at least 4 diameters under the pavement or 48 inches, whichever is greater. When the pipe is installed by boring and jacking, the leading edge of the pipe must always precede the auger. The tunnel backfill shall be made by tamping a dry mix of lean concrete into place so as to completely fill any voids remaining around the installation. The concrete shall be composed of one part of Portland cement and 10 parts of sand-gravel by volume. Tunnel and boring pits shall be at least 10 feet from the edge of the pavement unless otherwise approved.
4. **CROSSING BY CUTTING GRAVEL ROADS:** All trenches are to be backfilled with approved material to within 12 inches of surface within the limits of the roadbed. Backfill methods will be as described in paragraph 2 above. All surplus excavated material will be disposed of as described in paragraph 1. The top 12 inches within the roadbed will be backfilled with processed road gravel (MDOT 22A or 23A). Trenches outside of the roadbed will be backfilled in accordance with paragraph 2 above.
5. **CROSSING BY CUTTING PAVEMENT AND TRENCHING:** When this method is approved by the Road Commission, the pavement shall be cut so that the opening is a minimum of 5 feet wide and at least 1 foot wider on each side than the trench. In no case shall an open cut result in a remaining slab width of less than 5 feet from patch to an existing joint. The cut shall be made by sawing to a full pavement depth. Cuts in concrete residential and commercial drives shall be as above except that the patch width shall be a minimum of 3 feet and the remaining slab from patch to existing joint a minimum of 3 feet. Backfill shall be made with MDOT Class II granular material. After the backfill has been placed by control density method and thoroughly compacted, the pavement shall be replaced with a temporary surface of approved hot-mixed bituminous material and later replaced with new pavement of the original type and quality by the Permit Licensee unless other provisions are included in the permit.
6. **DEPTH OF COVER MATERIAL:** Pipes shall be placed to a depth that will provide not less than 4 feet of cover between the top of roadway surface and top of the pipe.
7. **TREE TRIMMING OR REMOVAL:** All trees that may be affected by the proposed construction shall be shown on the plans. The plan must clearly indicate which trees are proposed to be removed, trimmed and/or tunneled. This work, if approved, must be done in accordance with current Board standards, including advance notification of abutting property owners. Wood Disposal License Agreement(s) will be required for any tree work.
8. **DISPOSAL OF GROUND WATER:** Roadside drainage systems – open ditches, storm sewers, etc. – shall not be used for the disposal of water pumped from below the surface of the ground unless specifically allowed by the Road Commission. Details such as volume and frequency of discharge, erosion control, duration of use, NPDES permit and other pertinent information as may be required must be submitted with the application for such permission.
9. Any proposed operation in the right of way not covered by the above specifications, submitted with this application, shall be done in accordance with any additional specifications deemed necessary by the Board or as outlined in the Permit Rules, Specifications and Guidelines.